2020-01-28: Our resources

# ds-incubator eBook: bit.ly/2dii-ds-incubator

ds-incubator on rstudio.cloud: bit.ly/rs-cloud-ds-incubator

coding

Miscellaneous resources

📓 **2DegreesInvesting** / **resources**

👁 Unwatch ▾ 3   ⭐ Star 3   🍴 Fork 1

| ‹› Code | ⊙ Issues 82 | ⑂ Pull requests 0 | ▶ Actions | ⊞ Projects 0 | 📖 Wiki | 🛡 Security | 📊 Insights | ⚙ Settings |

Filters ▾   🔍 is:issue is:open   🏷 Labels 65   🚩 Milestones 0   **New issue**

☐ ⊙ **82 Open** ✓ **1 Closed**　　Author ▾   Label ▾   Projects ▾   Milestones ▾   Assignee ▾   Sort ▾

☐ ⊙ **Code smells and feels (Jenny Bryan)** `refactoring` `style`
#84 opened 18 minutes ago by maurolepore

☐ ⊙ **The Shapes of Code** `best-practice` `refactoring` `style`
#83 opened 21 minutes ago by maurolepore

☐ ⊙ **The ds-incubator website / eBook** `ds-incubator`
#82 opened 5 days ago by maurolepore

☐ ⊙ **2dii accounts** `accounts` `rstudio`　　💬 1
#81 opened 6 days ago by maurolepore

☐ ⊙ **Free resources to learn R** `learn`　　💬 3
#80 opened 6 days ago by maurolepore

☐ ⊙ **ds-incubator playlist** `best-practice` `ds-incubator` `video`
#79 opened 7 days ago by maurolepore

☐ ⊙ **Debugging in RStudio** `bug` `rstudio` `troubleshoot` `workflow`　　💬 2
#78 opened 19 days ago by jdhoffa

Poroposed topics for meetups (#11)

Gotchas

14.12 Style

14.12.1 Limit your code to 80 characters per line

For reference, in RStudio you can set a margin column at 80 characters (*Tools > Global Options > Code > Show margin > Margin column*).

> Strive to limit your code to 80 characters per line. This fits comfortably on a printed page with a reasonably sized font. If you find yourself running out of room, this is a good indication that you should encapsulate some of the work in a separate function.

– https://style.tidyverse.org/syntax.html#long-lines

> If a function definition runs over multiple lines, indent the second line to where the definition starts.

– https://style.tidyverse.org/functions.html#long-lines-1

r2dii

Paths pointing to 2dii's dropbox-folder

MASTER.DATA.PATH() FIN.DATA.PATH() CBMARKET.DATA.PATH() DATA.STORE.PATH() ANALYSIS.INPUTS.PATH()	Create paths to specific 2dii directories, depending on a configuration file
USER.NAME() DROPBOX.PATH() GIT.PATH() WEBTOOL.PATH() COMPANY.PATH() dbox_port_00() SCENARIO.DATA.PATH() dbox_port2_10proj() EQMARKET.DATA.PATH() MARKET.DATA.PATH() INDEX.DATA.PATH() INDEX.RESULTS.DATA.PATH() FUND.DATA.PATH()	Create paths to specific 2dii directories
find_dropbox_2dii() path_dropbox_2dii()	Easily access directories in your local copy of 2dii's Dropbox folder

Contents

Handle the configuration file

Paths pointing to 2dii's dropbox-folder

Access configuration parameters

Handle unclean names

Miscellaneous