

Reproducible examples

The replex package

reprex

- [reprex usage](#)
- [Reprex do's and don'ts](#)
- [This seems like a lot of work!](#)
- [Using datapasta with reprex](#)

Creating data

Creating data from an R object

```
# Biochemical Oxygen Demand
```

```
datasets::BOD
```

```
#> Time demand
```

```
#> 1      1      8.3
```

```
#> 2      2     10.3
```

```
#> 3      3     19.0
```

```
#> 4      4     16.0
```

```
#> 5      5     15.6
```

```
#> 6      7     19.8
```

dput()

```
dput(BOD)
```

```
#> structure(list(Time = c(1, 2, 3, 4, 5, 7), demand = c(8.3, 10.3,  
#> 19, 16, 15.6, 19.8)), class = "data.frame", row.names = c(NA,  
#> -6L), reference = "A1.4, p. 270")
```

```
bod <- structure(list(Time = c(1, 2, 3, 4, 5, 7), demand = c(8.3, 10.3,  
19, 16, 15.6, 19.8)), class = "data.frame", row.names = c(NA,  
-6L), reference = "A1.4, p. 270")
```

```
bod
```

```
#>   Time demand  
#> 1     1    8.3  
#> 2     2   10.3  
#> 3     3   19.0  
#> 4     4   16.0  
#> 5     5   15.6  
#> 6     7   19.8
```

datapasta::dpasta()

```
BOD %>%
```

```
  datapasta::dpasta()
```

```
#> data.frame(
```

```
#>   Time = c(1, 2, 3, 4, 5, 7),
```

```
#>   demand = c(8.3, 10.3, 19, 16, 15.6, 19.8)
```

```
#> )
```

datapasta::tribble_paste()

```
BOD %>%
```

```
  datapasta::tribble_paste()
```

```
#> tribble::tribble(  
#>   ~Time, ~demand,  
#>     1,    8.3,  
#>     2,   10.3,  
#>     3,    19,  
#>     4,    16,  
#>     5,   15.6,  
#>     7,   19.8  
#> )
```


Beyond repress

Why .Rmd?

- reprex can't read data from your system


```
reprex::reprex(  
  readr::read_csv(here::here("your-file.csv"))  
)  
#> Error: 'your-file.csv' does not exist in current working directory  
( 'C:/Users/Mauro/AppData/Local/Temp/RtmpCqzepI/reprex4e7022114c1f' ).
```

- reprex can.

```
data <- readr::read_csv(here::here("your-file.csv"))  
head(data, 2)  
#> # A tibble: 2 x 2  
#>   Time demand  
#>   <dbl>   <dbl>  
#> 1     1     8.3  
#> 2     2    10.3
```


Create a GitHub document

_File > New File > R Markdown...



Why here::here?

.Rmd files have a weird notion of working directory



`here::here()` is what you normally expect.

```
here::here()
```

```
#> [1] "C:/Users/Mauro/git/ds-incubator"
```

Workflow

- Write your-file.Rmd, e.g.:

```
library(here)
```

```
data <- read.csv(here::here("your-file.csv"), stringsAsFactors = FALSE)
```

```
head(data, 2)
```

```
#>   Time demand
```

```
#> 1      1      8.3
```

```
#> 2      2     10.3
```

```
# More code ...
```

- Knit your-file.Rmd (press the *Knit* button).
- Commit and push; GitHub will render your-file.md beautifully.
- Share your-file.csv and the [link to your-file.md](#).