

2E0LXY

LoRa APRS iGate and Digipeater

Installation, configuration and operation manual

Heltec WiFi LoRa 32 V3.2/V4 and LilyGO LoRa32 V2.1

Regional profiles and safe first-run setup - Firmware v1.3.0 - July 2026

2E0LXY

ESP32 Heltec LoRa APRS iGate

Online

Configuration

Packets

RF Map

Diagnostics

Update

Backup

Reboot

Save changes

Station

Add your Ham callsign and SSID.

You can leave a comment describing your station.

In the bottom there is a field for personal note that can only be seen in WEB GUI.

Callsign - SSID

2E0LXY-9

Your licensed amateur-radio callsign and SSID, used to identify this station on RF and APRS-IS.

Beacon Comment

UK LoRa APRS iGate + WIDE1 Digi

Short station description appended to position beacons.

Beacon Path

WIDE1-1

RF digipeater path used by this station's own LoRa APRS beacons.

Symbol

Green Star with L - Digipeater

The APRS map symbol that represents this iGate or digipeater.

Latitude

0

Fallback latitude used only when live GPS positioning is disabled.

Longitude

0

Fallback longitude used only when live GPS positioning is disabled.

Personal Note

Describe here your Station

Send Status at each Boot

Status

Custom Status

Tactical Callsign

Optional short on-air identity; leave blank to use the main callsign everywhere.



Copyright © 2026 2E0LXY for original modifications. 2E0LXY LoRa APRS iGate. GNU GPLv3 - supplied without warranty.

1. Purpose

This firmware turns a Heltec WiFi LoRa 32 V3.2, Heltec WiFi LoRa 32 V4 or LilyGO TTGO LoRa32 V2.1 into a region-configurable LoRa APRS receive iGate, APRS-IS connected station and configurable WIDE1/WIDE2 digipeater.

It includes a modern browser interface, RF packet map, diagnostics, Wi-Fi scanning and board-safe GitHub OTA updates. The Heltec build also supports external GPS.

2. Safety and licence

- An amateur-radio licence and valid callsign are required for RF transmission.
- Check the current national band plan and local coordination before transmitting.
- Use the minimum RF power that provides reliable local coverage.
- Back up configuration before updating firmware.
- Keep USB power connected throughout installation.
- The firmware is GPLv3 software supplied without warranty.

3. Hardware

Supported release target

Board	Processor	LoRa radio	Flash
Heltec WiFi LoRa 32 V3.2	ESP32-S3	SX1262	8 MB
LilyGO TTGO LoRa32 V2.1	ESP32	SX1278	4 MB
Heltec WiFi LoRa 32 V4	ESP32-S3	SX1262 + external RF front end	16 MB

Each board generation has a separate OTA and full-flash image. Never cross-flash the images.

GPS wiring

GPS module	Heltec V3.2
TX	GPIO 47 (ESP32 RX)
RX	GPIO 48 (ESP32 TX)
GND	GND
Power	Use the voltage required by the GPS module

The firmware starts at 9600 baud and automatically checks 38400, 115200 and 4800 baud until it receives a checksum-valid NMEA sentence. Confirm the module voltage before applying power.

The Heltec V4 GPS connector uses GPIO38 to receive GPS TX and GPIO39 to transmit to GPS RX. The firmware drives the revision-specific control lines needed by both the V4.2 GC1109 and V4.3 KCT8103L RF front ends. GPIO34 enables the GNSS power rail and GPIO40 releases the receiver from standby when live GPS is enabled.

4. Installation

Browser installer

1. Open the 2E0LXY GitHub Pages installer in desktop Chrome or Edge.
2. Connect one supported board directly by USB.
3. Select the exact board installer. V3.2 and V4 cannot be distinguished by chip family because both use ESP32-S3.

4. Choose its serial device.
5. Confirm installation and wait for verification and reboot.

The full installer can erase stored settings. Existing stations should download a configuration backup first.

Manual USB flash

Download the matching full-flash image from GitHub Releases and write it to address 0x0:

- 2E0LXY-Heltec-V3.2-full-flash.bin for Heltec ESP32-S3.
- 2E0LXY-LilyGO-LoRa32-V2.1-full-flash.bin for LilyGO ESP32.
- 2E0LXY-Heltec-V4-full-flash.bin for Heltec V4 only.

OTA update

Open **Update** in the device interface. The page compares the installed version with the latest 2E0LXY GitHub release. The compiled board identity selects the exact V3.2, V4 or LilyGO OTA filename. Installation is enabled only when that compatible asset is attached.

5. First connection

After boot, the iGate tries each saved Wi-Fi network. If none connects, its recovery access point becomes available. Connect to it and open <http://192.168.4.1/>. Change all default and recovery passwords before placing the device in service.

6. Regional LoRa APRS profiles

Profile	RX frequency	TX frequency	APRS-IS
United Kingdom	439.9125 MHz	439.9125 MHz	www.aprsnet.uk
IARU Region 1 common	433.775 MHz	433.775 MHz	rotate.aprs2.net
Custom / locally coordinated	Operator supplied	Operator supplied	Operator supplied

Presets use SF12, 125 kHz and CR 4/5. A 433.900 MHz Region 1 TX split is available by editing the TX field but is never enabled automatically. There is no universal North American or worldwide channel: use the applicable national band plan and local coordinator. Both ends of an RF link must use matching modulation parameters.

Select the physical radio hardware band first. The firmware rejects frequencies outside that band and rejects unsupported LoRa power, bandwidth and coding-rate values. A new installation starts with LoRa TX and digipeating disabled. Existing UK configurations retain their operational settings during migration.

The Region section also controls miles/kilometres, metres/feet, mph/km/h and °C/°F. Named timezones automatically apply daylight-saving changes.

7. Station configuration

- **Callsign - SSID:** licensed callsign and station SSID.
- **Tactical callsign:** optional short identity.
- **Beacon comment:** concise public station description.
- **Beacon path:** path for this station's own RF beacon.
- **Symbol:** map symbol for an iGate or digipeater.
- **Latitude/longitude:** safe fallback while GPS is disabled, unavailable

or waiting for a valid fix.

- **GPS beacon:** automatically replaces the fallback with live coordinates

after a valid fix.

- **Position ambiguity:** reduces public coordinate precision.

The live **GPS Receiver** panel separately reports hardware/UART detection and position-fix validity. It shows satellites, HDOP, coordinates, altitude, speed, course, GPS UTC time, NMEA checksum totals and data age. Saving the GPS enable switch restarts the iGate so the UART can be changed safely.

For this third iGate, 2E0LXY-9 is used. Avoid SSID -10 where it is already assigned to another station.

8. Wi-Fi

Select **Scan nearby Wi-Fi**, choose a network, enter its passphrase and save. Multiple networks may be stored. The startup delay allows a router or mobile hotspot time to become available after a power failure.

Never publish a configuration backup: it contains network and management credentials.

9. APRS-IS

The regional preset supplies starting settings:

Setting	Value
Server	UK: <code>www.aprsnet.uk</code> ; other regions: <code>rotate.aprs2.net</code> or a regional server
Port	14580
Filter	m/100
Passcode	Callsign-specific APRS-IS passcode

APRS Net UK provides a live APRS map, LoRa views, messaging, weather, watchlists, alerts and utilities. A free member account adds persistent watchlists, synced alerts and offline message storage.

Messages or objects should be gated from APRS-IS to RF only when useful locally and permitted by the routing safeguards.

10. Digipeater

- **Off:** no RF packet repeating.
- **WIDE1 fill-in:** local fill-in operation.
- **WIDE2 + WIDE1:** wider digipeater behaviour.
- **Backup digipeater:** falls back to local repeating if Wi-Fi or

APRS-IS is unavailable.

- **Eco mode:** reduces power consumption but can disable parts of the display, networking or web interface.

Use a conservative beacon interval and path. Excessive repeating creates collisions and reduces channel capacity.

11. RF packets and map

The **Packets** page lists recently received RF packets with local NTP time, RSSI and SNR. The map's **Show** selector provides **RF only**, **APRS-IS** and **All** views. RF history remains separate so a busy internet feed cannot displace packets actually heard or transmitted by the radio. Only packets containing a supported APRS position are mapped.

12. Diagnostics

The diagnostics page reports:

- Valid RF packets.
- Duplicates suppressed.
- CRC failures and other radio errors.
- Successful transmissions and TX errors.
- Free heap and Wi-Fi RSSI.
- Heard stations with packet count, RSSI, SNR and frequency error.

CRC-failed frames are counted but never repaired, gated or repeated.

13. Time

The NTP section displays the actual device time, synchronization state, server and named timezone. Named zones automatically follow their configured daylight-saving rule. A fixed UTC offset remains available for locations that do not use a listed zone. Confirm the displayed time after changing it.

14. Backup, restore and security

- Download a configuration backup before major changes.
- Store backups privately because they contain passwords.
- Enable web authentication and use a unique password.
- Protect OTA credentials.
- Limit remote management to trusted callsigns and RF-only operation

where appropriate.

- Do not expose the HTTP interface directly to the public internet.

15. Firmware updates

The GitHub updater performs these checks:

1. Read the latest release from the standalone 2E0LXY repository.
2. Confirm that the matching Heltec or LilyGO OTA image is attached.
3. Compare semantic versions.
4. Require operator confirmation.
5. Download and write the firmware.
6. Verify the write and reboot.

Manual ElegantOTA upload remains available as a recovery route.

16. Tracker interoperability

The receiver is intended for standard LoRa APRS frames and Base91 APRS positions using matching radio settings. Battery telemetry, GPS positions and normal APRS paths are processed by the existing APRS packet pipeline.

Tracker SmartBeaconing, motion turn detection, tracker push-buttons and GPS power toggling are transmitter functions and do not belong in a fixed iGate. Experimental APRS434 18-byte address-compressed frames are not claimed as compatible until decoding and gating are validated with captured test vectors.

17. Troubleshooting

Web page is unavailable

Confirm the displayed IP address, Wi-Fi connection and eco mode. Ping the device, reconnect by USB and inspect serial output at 115200 baud.

APRS-IS will not connect

Check DNS, server, port, passcode and filter. Confirm the callsign is valid and the device has internet access.

No RF packets

Check antenna connection, RX enabled state, frequency and LoRa parameters. Compare diagnostics counters and verify that another station uses the same profile.

GPS does not fix

Confirm TX-to-RX crossover, GPIO 47/48, automatic baud scanning, antenna view of the sky and adequate module power. A cold start may take several minutes.

OTA fails

Keep power connected, verify internet access and retry manual firmware upload. Do not upload the full-flash image through the OTA form.

18. Project links

- Source: <https://github.com/2E0LXY/2E0LXY-LoRa-APRS-iGate>
- Releases: <https://github.com/2E0LXY/2E0LXY-LoRa-APRS-iGate/releases>
- Installer: <https://2e0lxy.github.io/2E0LXY-LoRa-APRS-iGate/>
- APRS Net UK: <https://www.aprsnet.uk/>

19. Acknowledgement

Copyright © 2026 2E0LXY for original modifications and additions.

Thank you to CA2RXU for creating the original LoRa APRS iGate project. Original contributor notices remain in the source where required.