# Admin

- Assign 2 issues posted, open for fix and resubmit
- printf perseverance and pride!!

Today: Thanks for the memory!

Linker memory map, address space layout

Loading, how an executable file becomes a running program

Heap allocation, malloc and free

Memory Map

32-bit address space

512 MB of physical RAM

0xffffffff

GPU

CPU

Peripheral Registers   0x20000000

You are here!

Ref: BCM2835-ARM-Peripherals.pdf

```
SECTIONS
{
    .text 0x8000 : { *(.text.start)
                      *(.text*)}

    .rodata :      { *(.rodata*) }
    .data :        { *(.data*) }


    __bss_start__ = .;
    .bss :         { *(.bss*)
                      *(COMMON) }
    __bss_end__ = ALIGN(8);
}
```

Use this memory for heap☞

(zeroed data) **.bss**

(initialized data) **.data**

(read-only data) **.rodata**

.text

0x8000000

```
_cstart
main
```

```
_start:
    mov sp, #0x8000000
    mov fp, #0
    bl _cstart


void _cstart(void) {
    char *bss = &__bss_start__;
    while (bss < &__bss_end__)
        *bss++ = 0;
    }
    main();
}
```

__bss_end__

```
00000000
00000000
```
__bss_start__

```
20200008
63733130
```

```
00002017
00000365
```

```
e3a0b000
e3a0d302
```
0x8000

blink.bin

Global allocation

+ **Convenient**
    Fixed location, shared across entire program

+ **Fairly efficient, plentiful**
    No explicit allocation/deallocation
    Heavy cost to send over serial line to bootloader

+ **Reasonable type safety**

- **Size fixed at declaration, no option to resize**

+/- **Scope and lifetime is global**
    No encapsulation, hard to track use/dependencies
    One shared namespace, have to manually manage conflicts
    Frowned upon stylistically

Stack allocation

+ **Convenient**

    Automatic alloc/dealloc on function entry/exit

+ **Efficient, fairly plentiful**

    Fast to allocate/deallocate, low consequence if large size

+ **Reasonable type safety**

- **Size fixed at declaration, no option to resize**

+/- **Scope/lifetime dictated by control flow**

    Private to stack frame

    Does not persist after function exits

Heap allocation

+ **Moderately efficient**
  Have to search for available space, update record-keeping
+ **Very plentiful**
  Heap enlarges on demand to limits of address space
+ **Versatile, under programmer control**
  Can precisely determine scope, lifetime
  Can be resized

- **Low type safety**
  Interface is raw void *, number of bytes
- **Much opportunity for error**
    (allocate wrong size, use after free, double free)
- **Leaks** (less critical, but annoying nonetheless)

Heap interface

```
void *malloc (size_t nbytes);
void  free (void *ptr);
```

void* pointer

"Generic" pointer, a memory address

Type of pointee is not specified, could be any data

What you can do with a void*

Pass to/from function, pointer assignment

What you cannot do with a void*

Cannot dereference (must cast first)

Cannot do pointer arithmetic (cast to char * to manually control scaling)

Cannot use array indexing (size of pointee not known!)

Why do we need a heap?

Let's see an example!

code/heap/names.c

How to implement a heap

```c
void *sbrk(int nbytes)
{
    static void *heap_end = &__bss_end__;

    void *prev_end = heap_end;
    heap_end = (char *)heap_end + nbytes;
    return prev_end;
}
```

Stack

0x800000

heap_end

__bss_end__

.bss
```
00000000
00000000
```
__bss_start__

.data
```
20200008
63733130
```

.rodata
```
00002017
00000365
```

.text
```
e3a0b000
e3a0d302
```
0x8000

Tracing the bump allocator

Each square represents 8 bytes of space

p1 = malloc(32)

p2 = malloc(40)

p3 = malloc(48)

free(p2)

p4 = malloc(16)

Bump Memory Allocator

code/heap/malloc.c

Evaluate bump allocator

+ Operations super-fast

+ Very simple code, easy to verify, test, debug

- No recycling/re-use

    (in what situations will this be problematic?)

- Sad consequences when sbrk() advances into stack

    (what can we do about that?)

Pre-block header, implicit list

*Each square represents 8 bytes, header records size of payload in bytes*

p1 = malloc(32)

| 32 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

p2 = malloc(40)

| 32 | | | | | 40 | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

p3 = malloc(48)

| 32 | | | | | 40 | | | | | 48 | | | | | | | | | | | | | | | | | | | | | | | |

free(p2)

| 32 | | | | | 40 | | | | | 48 | | | | | | | | | | | | | | | | | | | | | | | |

p4 = malloc(16)

| 32 | | | | | 16 | | | 16 | | | 48 | | | | | | | | | | | | | | | | | | | | | | |

Header struct

```
struct header {
    unsigned int size;
    unsigned int status;
};                                   // sizeof(struct header) = 8 bytes

enum { IN_USE = 0, FREE = 1};


void *malloc(size_t nbytes)
{
    nbytes = roundup(nbytes, 8);
    size_t total_bytes = nbytes + sizeof(struct header);

    struct header *hdr = sbrk(total_bytes); // extend end of heap
    hdr->size = nbytes;
    hdr->status = IN_USE;
    return hdr + 1;       // return address at start of payload
}
```

Challenges for malloc client

- **Correct allocation (size in bytes)**

- **Correct access to block (within bounds, not freed)**

- **Correct free (once and only once, at correct time)**

What happens if you…

— forget to free a block after you are done using it?
— access a memory block after you freed it?
— free a block twice?
— free a pointer you didn't malloc?
— access outside the bounds of a heap-allocated block?

Challenges for malloc implementor

just `malloc` is easy 😎
`malloc` with `free` is hard 🤔
Efficient `malloc` with `free` ….Yikes! 🥵

Complex code (pointer math, typecasts)
Thorough testing is challenge (more so than usual)
Critical system component
    correctness is non-negotiable, ideally fast and compact

Survival strategies:
    draw pictures
    printf (you've earned it!!)
    early tests use examples small enough to trace by hand if need be
    build up to bigger, more complex tests