

OPEN-SOURCE EBOOK

++101 LINUX COMMANDS

BOBBY ILIEV

Table of Contents

101 Linux commands Open-source eBook	15
Hacktoberfest	16
About me	17
Ebook PDF Generation Tool	19
Book Cover	20
License	21
The ls command	22
The cd command	25
The cat command	28
The tac command	31
The head command	33
The tail command	35
The pwd command	38
The touch Command	40
The cal Command	43

The bc command	46
The df command	50
The help command	54
Syntax	55
Options	56
Example	57
The factor command	58
Syntax	59
Options	60
Examples	61
The uname command	62
Syntax:	63
Examples	64
Options	65
The mkdir command	66
Syntax	67
Examples	68
Options	69
The gzip command	70
Usage	71
Compress a file	72
Decompress a file	73

The **who** command

The **who** command lets you print out a list of logged-in users, the current run level of the system and the time of last system boot.

Examples

1. Print out all details of currently logged-in users

```
who -a
```

2. Print out the list of all dead processes

```
who -d -H
```

Syntax:

```
who [options] [filename]
```

Additional Flags and their Functionalities

Short Flag	Description
-r	prints all the current runlevel
-d	print all the dead processes
-q	print all the login names and total number of logged on users
-h	print the heading of the columns displayed

Short Flag	Description
-b	print the time of last system boot

018-the-free-command.md

The **free** command

The **free** command in Linux/Unix is used to show memory (RAM/SWAP) information.

Usage

Show memory usage

Action: --- Output the memory usage - available and used, as well as swap

Details: --- Outputted values are not human-readable (are in bytes)

Command:

```
free
```


Show memory usage in human-readable form

Action: --- Output the memory usage - available and used, as well as swap

Details: --- Outputted values ARE human-readable (are in GB / MB)

Command:

```
free -h
```

The **groups** command

In Linux, there can be multiple users (those who use/operate the system), and groups (a collection of users). Groups make it easy to manage users with the same security and access privileges. A user can be part of different groups.

Important Points:

The **groups** command prints the names of the primary and any supplementary groups for each given username, or the current process if no names are given. If more than one name is given, the name of each user is printed before the list of that user's groups and the username is separated from the group list by a colon.

Syntax:

```
groups [username]
```

Example 1

Provided with a username

```
groups demon
```

In this example, username demon is passed with groups command and the output shows the groups in which the user demon is present,

separated by a colon.

Example 2

When no username is passed then this will display the group membership for the current user:

```
groups
```

Here the current user is demon . So when we run the **groups** command without arguments we get the groups in which demon is a user.

Example 3

Passing root with groups command:

```
$demon# groups
```

Note: Primary and supplementary groups for a process are normally inherited from its parent and are usually unchanged since login. This means that if you change the group database after logging in, groups will not reflect your changes within your existing login session. The only options are -help and -version.

The `man` command

The `man` command is used to display the manual of any command that we can run on the terminal. It provides information like: DESCRIPTION, OPTIONS, AUTHORS and more.

Examples:

1. Man page for `printf`:

```
man printf
```

2. Man page section 2 for `intro`:

```
man 2 intro
```

Syntax:

```
man [SECTION-NUM] [COMMAND NAME]
```

Additional Flags and their Functionalities:

Short Flag	Long Flag	Description
<code>-f</code>	-	Return the sections of an command
<code>-a</code>	-	Display all the manual pages of an command

Short Flag	Long Flag	Description
-k	-	Searches the given command with RegEx in all man pages
-w	-	Returns the location of a given command man page
-I	-	Searches the command manual case sensitive

This is a sample from "101 Linux Commands eBook" by Bobby Iliev the Hacktoberfest
community.

For more information, [Click here](#).