SES/RAS 598: Space Robotics and Al

Lecture 1: Course Introduction & State Estimation Overview

Dr. Jnaneshwar Das

Arizona State University School of Earth and Space Exploration

Spring 2025



Lecture Outline

- Course Overview
- State Estimation Fundamentals
- 3 Linear Dynamical Systems
- 4 Next Steps

• Meeting Times: Tu/Th 10:30-11:45am

• **Meeting Times:** Tu/Th 10:30-11:45am

• Location: PSF 647

- Meeting Times: Tu/Th 10:30-11:45am
- Location: PSF 647
- Course Components:
 - Assignments (20%)
 - Midterm Project (20%)
 - Final Project (50%)
 - Class Participation (10%)

- Meeting Times: Tu/Th 10:30-11:45am
- Location: PSF 647
- Course Components:
 - Assignments (20%)
 - Midterm Project (20%)
 - Final Project (50%)
 - Class Participation (10%)
- Prerequisites:
 - Linear algebra, calculus, probability theory
 - Python programming with NumPy, SciPy
 - Basic computer vision concepts
 - Linux/Unix systems experience

Course Resources

Recommended Books:

- Probabilistic Robotics (Thrun, Burgard, Fox)
- Optimal State Estimation (Simon)
- Pattern Recognition and Machine Learning (Bishop)

Course Resources

Recommended Books:

- Probabilistic Robotics (Thrun, Burgard, Fox)
- Optimal State Estimation (Simon)
- Pattern Recognition and Machine Learning (Bishop)

• Interactive Tutorials:

- Sensor Fusion
- Parameter Estimation
- Gaussian Processes

Course Resources

Recommended Books:

- Probabilistic Robotics (Thrun, Burgard, Fox)
- Optimal State Estimation (Simon)
- Pattern Recognition and Machine Learning (Bishop)

• Interactive Tutorials:

- Sensor Fusion
- Parameter Estimation
- Gaussian Processes

Required Software:

- Linux OS
- ROS2
- Python with scientific computing libraries

Why State Estimation?

Real-World Applications:

- Mars rover navigation
- Drone flight control
- Satellite attitude determination

Why State Estimation?

• Real-World Applications:

- Mars rover navigation
- Drone flight control
- Satellite attitude determination

• Key Challenges:

- Sensor noise and uncertainty
- Environmental dynamics
- Resource constraints

Why State Estimation?

Real-World Applications:

- Mars rover navigation
- Drone flight control
- Satellite attitude determination

• Key Challenges:

- Sensor noise and uncertainty
- Environmental dynamics
- Resource constraints

• Impact on Space Exploration:

- Autonomous navigation
- Precision landing
- Sample collection

Least Squares Estimation

• Mathematical Foundation:

$$\hat{\theta} = \underset{\theta}{\operatorname{arg\,min}} \sum_{i=1}^{n} (y_i - h(\theta))^2$$

Least Squares Estimation

• Mathematical Foundation:

$$\hat{\theta} = \underset{\theta}{\operatorname{arg\,min}} \sum_{i=1}^{n} (y_i - h(\theta))^2$$

• Key Properties:

- Minimizes squared error
- Optimal for Gaussian noise
- Computationally efficient

Least Squares Estimation

• Mathematical Foundation:

$$\hat{\theta} = \underset{\theta}{\operatorname{arg\,min}} \sum_{i=1}^{n} (y_i - h(\theta))^2$$

• Key Properties:

- Minimizes squared error
- Optimal for Gaussian noise
- Computationally efficient

• Applications:

- Sensor calibration
- Trajectory estimation
- Parameter identification

Implementation Example: Least Squares Estimation

```
1 import numpy as np
2 from scipy.optimize import minimize
  class LeastSquaresEstimator:
5
      def __init__(self, measurements, measurement_model):
6
          self.v = measurements
                                       # Measurement vector
          self.h = measurement model
                                       # Measurement model function
8
      def cost_function(self, theta):
          """Compute sum of squared errors."""
          residuals = self.v - self.h(theta)
          return np.sum(residuals**2)
      def estimate(self. theta init):
          """Find parameters that minimize squared error."""
          result = minimize(self.cost_function, theta_init,
                          method='Nelder-Mead')
          return result.x # Return optimal parameters
```

Maximum Likelihood Estimation

• Principle:

$$\hat{\theta}_{\mathsf{MLE}} = \underset{\theta}{\mathsf{arg}} \max_{i=1}^{n} p(y_i|\theta)$$

Maximum Likelihood Estimation

• Principle:

$$\hat{ heta}_{\mathsf{MLE}} = rg\max_{ heta} \prod_{i=1}^n p(y_i| heta)$$

- Connection to Least Squares:
 - Equivalent under Gaussian assumptions
 - More general framework
 - Handles different noise models

Maximum Likelihood Estimation

• Principle:

$$\hat{ heta}_{\mathsf{MLE}} = rg \max_{ heta} \prod_{i=1}^n p(y_i| heta)$$

- Connection to Least Squares:
 - Equivalent under Gaussian assumptions
 - More general framework
 - Handles different noise models
- Space Applications:
 - Orbit determination
 - Attitude estimation
 - Sensor fusion



Implementation Example: Maximum Likelihood Estimation

```
1 import numpy as np
2 from scipy.stats import norm
3 from scipy.optimize import minimize
4
  class MLEstimator:
6
      def init (self. measurements. measurement model):
          self.v = measurements
                                  # Measurement vector
8
          self.h = measurement model
                                       # Measurement model function
      def neg log likelihood(self, theta):
          """Compute negative log-likelihood."""
          residuals = self.y - self.h(theta) # Assuming Gaussian noise model
          return -np.sum(norm.logpdf(residuals))
      def estimate(self, theta init):
          """Find parameters that maximize likelihood."""
          result = minimize(self.neg log likelihood, theta init.
                          method='Nelder-Mead')
          return result.x # Return optimal parameters
```

State-Space Models

System Dynamics:

$$x_{k+1} = Ax_k + Bu_k + w_k$$
$$y_k = Cx_k + v_k$$

State-Space Models

System Dynamics:

$$x_{k+1} = Ax_k + Bu_k + w_k$$
$$y_k = Cx_k + v_k$$

Components:

- State vector x_k
- Input vector u_k
- Measurement vector y_k
- Process noise w_k
- Measurement noise v_k

Case Study: Mars Rover Navigation

State Variables:

- Position (x, y, z)
- Orientation (roll, pitch, yaw)
- Velocities

Case Study: Mars Rover Navigation

State Variables:

- Position (x, y, z)
- Orientation (roll, pitch, yaw)
- Velocities

Sensors:

- Visual odometry
- Inertial measurement unit (IMU)
- Sun sensors

Case Study: Mars Rover Navigation

State Variables:

- Position (x, y, z)
- Orientation (roll, pitch, yaw)
- Velocities

Sensors:

- Visual odometry
- Inertial measurement unit (IMU)
- Sun sensors

Challenges:

- Wheel slippage
- Varying terrain
- Limited computational resources

Implementation Example: State-Space Model

```
1 import numpy as np
 from scipy.stats import multivariate_normal
 class LinearStateSpaceModel:
5
      def init (self. A. B. C. Q. R):
          self.A = A # State transition matrix
6
          self.B = B # Input matrix
          self.C = C # Measurement matrix
9
          self.Q = Q # Process noise covariance
          self R = R # Measurement noise covariance
      def propagate_state(self, x, u=None):
          """Propagate state forward one step."""
          w = multivariate_normal.rvs(mean=np.zeros(x.shape), cov=self.Q)
          if u is not None:
              return self.A @ x + self.B @ n + w
          return self.A @ x + w
      def get_measurement(self, x):
          """Get noisy measurement of current state."""
          v = multivariate_normal.rvs(mean=np.zeros(self.C.shape[0]), cov=self.R)
          return self.C @ x + v
```

Preparation for Next Lecture

• Review:

- Matrix operations
- Probability concepts
- Basic Python programming

Preparation for Next Lecture

• Review:

- Matrix operations
- Probability concepts
- Basic Python programming

Setup:

- Install Linux if needed
- Configure ROS2 environment
- Test Python scientific libraries

Preparation for Next Lecture

• Review:

- Matrix operations
- Probability concepts
- Basic Python programming

Setup:

- Install Linux if needed
- Configure ROS2 environment
- Test Python scientific libraries

• Reading:

- Skim Kalman filter basics
- Review assigned papers
- Explore interactive tutorials

Questions?

Thank you!

Contact: jdas5@asu.edu