

FIT2095 e-Business software technologies - S2 2021

[Dashboard](#) / [My units](#) / [FIT2095_S2_2021](#) / [Assessments](#) / [Week 4 Pre-Reading Quiz](#)**Started on** Saturday, 14 August 2021, 11:42 AM**State** Finished**Completed on** Saturday, 14 August 2021, 11:50 AM**Time taken** 8 mins 4 secs**Grade** 10.00 out of 10.00 (100%)[Print friendly format](#)

Question 1

Correct

Mark 1.00 out of 1.00

To have a templates application-wide variable in Express.js, I have to:

Select one:

- ☐ a. declare the variable in a package and expose it using module.exports
- ☐ b. declare the variable using **let**
- ☐ c. declare the variable using **var**
- ☒ d. app.set() and provide a pair of key and value



Your answer is correct.

The correct answer is: app.set() and provide a pair of key and value

Question 2

Correct

Mark 1.00 out of 1.00

Which option is false for the following code?

```
app.get('/',function(rqe, res){
  res.sendFile(__dirname + '/index.html');
});
```

Select one:

- ☐ a. The express statement is capable to receive POST request data in req.body property
- ☐ b. the callback will be invoked when the pathname = "/"
- ☐ c. By using __dirname, the path of "index.html" is relative to the project's folder
- ☐ d. No error will be thrown if we remove __dirname

☒ e. Select this option if you believe more than one option is false



Your answer is correct.

The correct answer is: Select this option if you believe more than one option is false

Question 3

Correct

Mark 1.00 out of 1.00

Assume you have this fragment of code:

```
app.post('/data', function (req, res) {  
  console.log(req.body.username);  
  console.log(req.body.userage);  
  res.send('Thank You')  
})
```

Which option is True?

Select one:

- ☒ a. The properties of req.body object are generated using body-parser middleware
- ☐ b. The properties of req.body object are generated using morgan middleware
- ☐ c. The properties of req.body object are automatically generated by Express (No need to install middleware)
- ☐ d. The properties of req.body object are automatically generated by Node.js (No need to install middleware)



Your answer is correct.

The correct answer is: The properties of req.body object are generated using body-parser middleware

Question 4

Correct

Mark 1.00 out of 1.00

```
const morgan = require('morgan');
```

morgan is?

Select one:

- ☐ a. a package for parsing incoming HTTP requests
- ☒ b. HTTP request logger middleware
- ☐ c. HTTP logger middleware for GET requests only
- ☐ d. a Node.js package for managing static assets
- ☐ e. None of the above



Your answer is correct.

The correct answer is: HTTP request logger middleware

Question 5

Correct

Mark 1.00 out of 1.00

```
app.get('/', function (req, res) {  
  let randomId = Math.round(Math.random() * 100);  
  res.render('index.html', { username: "admin", id: randomId });  
});
```

When does the callback function execute?

Select one:

- ☐ a. when the user sends a POST request
- ☒ b. when the user navigates to `http://localhost:8080`
- ☐ c. when the server invokes `app.get()` method
- ☐ d. when the user navigates to `http://localhost:8080/function`
- ☐ e. if the pathname has '/' character after a none empty pathname



Your answer is correct.

The correct answer is: when the user navigates to `http://localhost:8080`

Question 6

Correct

Mark 1.00 out of 1.00

Which of the following is true for the following code?

```
res.render('index.html', { username: "admin", id: randomId });
```

Select one:

- ☐ a. `res.render` sends the object `{ username: "admin", id: randomId }` to the client
- ☐ b. `res.render` generates a new local HTML file using the object `{ username: "admin", id: randomId }`
- ☐ c. `res.render` method sends the static content of `index.html` to the client
- ☒ d. `res.render` sends to the client the rendered HTML of `index.html` after applying the object `{ username: "admin", id: randomId }` to it



Your answer is correct.

The correct answer is: `res.render` sends to the client the rendered HTML of `index.html` after applying the object `{ username: "admin", id: randomId }` to it

Question 7

Correct

Mark 1.00 out of 1.00

The following statement has a syntax error:

The following statement has a syntax error.

```
<h1> Welcome <% username%> </h1>
```

Which option is correct?

Select one:

- ☒ a. `<h1> Welcome <%= username%> </h1>` ✓
- ☐ b. `<h1> Welcome <= username %> </h1>`
- ☐ c. `<h1> Welcome <%= username=%> </h1>`
- ☐ d. `<h1> Welcome <%= username/> </h1>`

Your answer is correct.

The correct answer is:

```
<h1> Welcome <%= username%> </h1>
```

Question 8

Correct

Mark 1.00 out of 1.00

The default location of the HTML files for EJS view engine is:

NOTE: [root] is the root directory of the project

Select one:

- ☐ a. [root]
- ☐ b. [root]/html/views
- ☒ c. [root]/views ✓
- ☐ d. [root]/ejs

Your answer is correct.

The correct answer is: [root]/views

Question 9

Correct

Mark 1.00 out of 1.00

For express to publicly serve static images files in a directory named 'images', I have to use:

Select one:

- ☐ a. `app.use('images')`
- ☒ b. `app.use(express.static('images'))` ✓
- ☐ c. `app.use(app.static('public'))`
- ☐ d. `app.use(express.static('public'))`
- ☐ e. `express.static('images')`

Your answer is correct.

The correct answer is: `app.use(express.static('images'))`

Question **10**

Correct

Mark 1.00 out of 1.00

The following fragment of code has a syntax error:

```
<h3>list of items:
  <ul>
    <% for ( var i =0; i< ar.length;i++){ %>
      <li>
        <%= ar[i].item%>
      </li>
    </ul>
    <% }%>
</h3>
```

The correct option is:

Select one:

☐ a.

```
<h3>list of items:
  <ul>
    <%= for ( var i =0; i< ar.length;i++){ %>
      <li>
        <%= ar[i].item%>
      </li>
    <% }%>
  </ul>
</h3>
```

☐ b.

```
<h3>list of items:
  <ul>
    <% for ( var i =0; i< ar.length;i++){ %>
      <li>
        <% ar[i].item%>
      </li>
    <% =}%>
  </ul>
</h3>
```

☒ c.

```
<h3>list of items:
  <ul>
    <% for ( var i =0; i< ar.length;i++){ %>
      <li>
        <%= ar[i].item%>
      </li>
    <% }%>
  </ul>
</h3>
```

 ✓

☐ d.

```
<h3>list of items:
  <ul>
    <% for ( var i =0; i< ar.length;i++){
      <li>
        <%= ar[i].item%>
      </li>
    <% }%>
  </ul>
</h3>
```

Your answer is correct.

The correct answer is:

```
<h3>list of items:
  <ul>
    <% for ( var i =0; i< ar.length;i++){ %>
      <li>
        <%= ar[i].item%>
      </li>
    <% }%>
  </ul>
</h3>
```

[◀ Week 3 Pre-Reading Quiz](#)

Jump to...

[Week 5 Pre-Reading Quiz ▶](#)