

# FIT3152 Data analytics. Tutorial 11:

## Text analytics

---

Contents:

- Text analytics, text processing and clustering in R
1. Work through the examples in the lecture slides.
  2. Text pre-processing

Create a Term-Document Matrix of the following data following the process outlined in the lecture notes: (Tokenise, Convert case, Filtering – including removing stop words, Stemming)

ID	Document
Doc1	Jazz music has a swing rhythm
Doc2	Swing is hard to explain
Doc3	Swing rhythm is a natural rhythm

3. Create 3 text documents following the example in the lecture notes and create a Term-Document matrix using R.

```
# set working directory to desktop
setwd("~/Desktop")
# clean up the environment before starting
rm(list = ls())
library(slam)
library(tm)
library(SnowballC)

#Get file path to folder "test" where the documents are located
cname = file.path(".", "Tute_Q3")
cname
print(dir(cname))
docs = Corpus(DirSource((cname)))
print(summary(docs))

#Tokenisation
docs <- tm_map(docs, removeNumbers)
docs <- tm_map(docs, removePunctuation)
docs <- tm_map(docs, content_transformer(tolower))

#Filter words
# Remove stop words and white space
docs <- tm_map(docs, removeWords, stopwords("english"))
docs <- tm_map(docs, stripWhitespace)

# Stem
docs <- tm_map(docs, stemDocument, language = "english")

#Create document term matrix
dtm <- DocumentTermMatrix(docs)
dtm = as.data.frame(as.matrix(dtm))
write.csv(dtm, "dtm.csv")
```

	explain	hard	jazz	music	natur	rhythm	swing
Doc1.txt	0	0	1	1	0	1	1
Doc2.txt	1	1	0	0	0	0	1
Doc3.txt	0	0	0	0	1	2	1

Calculate the Cosine Distance between each pair of documents using TDFM.

	explain	had	jazz	music	natur	rhythm	swing						Cosine Distance
Doc1	0	0	1	1	0	1	1						
Doc2	1	1	0	0	0	0	1						
Doc3	0	0	0	0	1	2	1						
Doc1	0	0	1	1	0	1	1		num	1.00	=		0.29
Doc2	1	1	0	0	0	0	1		den	3.46			
Doc2	1	1	0	0	0	0	1		num	1.00	=		0.24
Doc3	0	0	0	0	1	2	1		den	4.24			
Doc1	0	0	1	1	0	1	1		num	3.00	=		0.61
Doc3	0	0	0	0	1	2	1		den	4.90			

4. A number of reports relating to UFO sightings have been stored in the file (UFOsample.csv). Read the data into R, process and cluster the text. Adapt the following code fragment below to read each row of a csv file as a separate document into a corpus:

```

UFO = read.csv("UFOsample.csv", header = FALSE)
UFO = data.frame(doc_id = row.names(UFO), text =UFO[1])
colnames(UFO) = c('doc_id', 'text')
docs = Corpus(DataframeSource(UFO))


# set working directory to desktop
setwd("~/Desktop")
# clean up the environment before starting
rm(list = ls())
library(slam)
library(tm)
library(SnowballC)

#Build corpus from the text data file
UFO <- read.csv("UFOsample.csv", header = FALSE)
docs = Corpus(DataframeSource(UFO))
print(summary(docs))

#Tokenise
# Hyphen to space, ref Williams
toSpace <- content_transformer(function(x, pattern) gsub(pattern, " ", x))
docs <- tm_map(docs, toSpace, "--")
docs <- tm_map(docs, removeNumbers)
docs <- tm_map(docs, removePunctuation)
docs <- tm_map(docs, content_transformer(tolower))
#Filter Words
# Remove stop words and white space
docs <- tm_map(docs, removeWords, stopwords("english"))
docs <- tm_map(docs, stripWhitespace)
# Stem
docs <- tm_map(docs, stemDocument, language = "english")
#Create document term matrix
dtm <- DocumentTermMatrix(docs)
#Remove sparse terms
dim(dtm)
dtms <- removeSparseTerms(dtm, 0.2)

```

```
dtms = as.matrix(dtms)
write.csv(dtms, "dtms_UFO.csv")
#cluster
distmatrix = dist(scale(dtms))
fit = hclust(distmatrix, method = "ward.D")
plot(fit)
plot(fit, hang = -1)
```



Note very small dtm for these data - gives a better clustering

	abduct	figur	light	like	look	see	time
1	1	2	0	2	0	1	0
2	1	5	2	0	1	2	1
3	1	1	5	0	3	4	2
4	2	1	2	3	5	1	0
5	1	2	28	14	35	15	25
6	1	1	0	2	0	3	4
7	1	1	0	5	5	0	1
8	1	1	0	2	1	0	6
9	1	1	34	7	8	11	8
10	2	0	5	3	4	0	1
11	...	...	...	...	...	...	...

5. A selection of Usenet articles taken from 20 newsgroups are in the zipped folder (mini\_newsgroups\_mixedup.zip). These documents were obtained from the UCI KDD Archive of data sources for machine learning. Ref: <http://kdd.ics.uci.edu/databases/20newsgroups/20newsgroups.data.html>. The topics are: alt.atheism; comp.graphics, comp.os.ms-windows.misc, comp.sys.ibm.pc.hardware, comp.sys.mac.hardware, comp.windows.x, misc.forsale, rec.autos, rec.motorcycles, rec.sport.baseball, rec.sport.hockey, sci.crypt, sci.electronics, sci.med, sci.space, soc.religion.christian, talk.politics.guns, talk.politics.mideast, talk.politics.misc, talk.religion.misc.

Note: these articles have been vetted for expletives but some may contain offensive content. Therefore you are not encouraged to read these in detail. (Newsgroup topic appears in header)

- (a) Process and cluster the data. Inspect the Term-Document Matrix or word frequency counts. This should identify words that appear commonly in each article, regardless of topic.

```
#Build corpus on usenet data
cname = file.path(".", "mini_newsgroups_mixedup")
docs = Corpus(DirSource((cname)))
print(summary(docs))

# Specific transformations
# Hyphen to space, ref Williams
toSpace <- content_transformer(function(x, pattern) gsub(pattern, " ", x))
docs <- tm_map(docs, toSpace, "-")
# cantaloupe to space, ref Williams
toSpace <- content_transformer(function(x, pattern) gsub(pattern, " ", x))
docs <- tm_map(docs, toSpace, "cantaloupe")
# newsgroup to space, ref Williams
toSpace <- content_transformer(function(x, pattern) gsub(pattern, " ", x))
docs <- tm_map(docs, toSpace, "newsgroup")

# Tokenise
#inspect(docs[1])
docs <- tm_map(docs, removeNumbers)
docs <- tm_map(docs, removePunctuation)
docs <- tm_map(docs, content_transformer(tolower))
# Remove stop words and white space
docs <- tm_map(docs, removeWords, stopwords("english"))
docs <- tm_map(docs, stripWhitespace)
# Stem
docs <- tm_map(docs, stemDocument, language = "english")

#Create document term matrix
dtm <- DocumentTermMatrix(docs)


# Check Word frequencies, ref Williams
freq <- colSums(as.matrix(dtm))
length(freq)
ord = order(freq)
freq[head(ord)]
freq[tail(ord)]

# Frequency of frequencies, ref Williams
head(table(freq), 10)
tail(table(freq), 10)
dim(dtm)
dtms <- removeSparseTerms(dtm, 0.9)
dim(dtms)

# inspect(dtms)
findFreqTerms(dtm, lowfreq = 10)
dtms = as.matrix(dtms)
write.csv(dtms, "dtms.csv")


#cluster
distmatrix = dist(scale(dtms))
fit = hclust(distmatrix, method = "ward.D")
cutfit = cutree(fit, k = 20)
plot(fit)
plot(fit, hang = -1)
```

```
cutfit
sort(cutfit)
```




- (b) Using the information gained in Part (a) re-process the articles to eliminate these specific words or phrases and then re-cluster the data. If you are using hierarchical clustering, partition the data into 20 clusters.

```
# after checking TDM a few more stems to remove
toSpace <- content_transformer(function(x, pattern) gsub(pattern, " ", x))
docs <- tm_map(docs, toSpace, "newsgroup")
docs <- tm_map(docs, toSpace, "subject")
docs <- tm_map(docs, toSpace, "message")
docs <- tm_map(docs, toSpace, "date")
docs <- tm_map(docs, toSpace, "line")
docs <- tm_map(docs, toSpace, "organ")
docs <- tm_map(docs, toSpace, "gmt")
docs <- tm_map(docs, toSpace, "path")
docs <- tm_map(docs, toSpace, "univers")
docs <- tm_map(docs, toSpace, "refer")
docs <- tm_map(docs, toSpace, "srcvscmuedu")
docs <- tm_map(docs, toSpace,
"srcvscmuedumagnesiumclubcccmuedunewsseicmueducisohio")
docs <- tm_map(docs, toSpace, "sender")
docs <- tm_map(docs, toSpace, "usenet")
docs <- tm_map(docs, toSpace, "magnesiumclubcccmuedunewsseicmueducisohio")
docs <- tm_map(docs, toSpace, "apr")
docs <- tm_map(docs, toSpace, "write")
docs <- tm_map(docs, stripWhitespace)
```




```
dtms <- removeSparseTerms(dtm, 0.9)
```



- (c) Inspect the clusters obtained in Part (b), do the clusters contain articles on the same or similar topics? Hint: look at the document IDs. Newsgroup topics are coded (approximately) by topic as TTTxxx where TTT is the topic code.

```
# I tried this, not that successful...
cutfit = as.data.frame(as.table(cutfit))
boxplot(as.numeric(as.character(Var1)) ~ Freq, data = cutfit)
```



6. The text for the novel *David Copperfield*, by Charles Dickens was obtained from Project Gutenberg, ref: <https://www.gutenberg.org>. An edited version of this text – with material not in the original book removed is in text file (David Copperfield PG Edit.txt).
- (a) Process the data for text analysis and create a data frame of the top 100 or 200 most frequently appearing words. Plot a column graph of these word frequencies. What do you observe?

```
#Get corpus
cname = file.path(".", "David_Copperfield")
print(dir(cname))
docs = Corpus(DirSource((cname)))

# Tokenise
#writeLines(as.character(docs[[1]]))
docs <- tm_map(docs, removeNumbers)
docs <- tm_map(docs, removePunctuation)
```

```
docs <- tm_map(docs, content_transformer(tolower))
# Remove stop words and white space
docs <- tm_map(docs, removeWords, stopwords("english"))
docs <- tm_map(docs, stripWhitespace)
# Stem
docs <- tm_map(docs, stemDocument, language = "english")


# Create document term matrix
dtm <- DocumentTermMatrix(docs)

# Check word frequencies, ref Williams
freq <- colSums(as.matrix(dtm))
length(freq)
ord = order(freq)
freq[head(ord)]
freq[tail(ord)]

# Frequency of frequencies, ref Williams
head(table(freq), 10)
tail(table(freq), 10)
dim(dtm)

freq = as.data.frame(as.table(freq))
nfreq <- freq[order(-freq$Freq),]
nfreq = nfreq[1:100,]

#plot column graph of frequent words
nfreq$Var1 <- factor(nfreq$Var1, levels = nfreq$Var1[order(-nfreq$Freq)])
ggplot(data=nfreq, aes(x=Var1, y=log10(Freq))) + geom_bar(stat="identity")
+ theme_minimal()
```



```
print(nfreq$Var1)
```

[1] said	look	littl	know	one
[6] micawb	aunt	upon	say	time
[11] peggotti	come	like	miss	now
[16] hand	think	mrs	never	much
[21] old	see	made	dear	good
[26] thought	well	went	will	copperfield
[31] dora	dont	head	traddl	day
[36] make	take	face	ever	came
[41] return	eye	agn	away	mother
[46] sir	way	might	great	love
[51] quit	even	saw	put	hous
[56] back	steerforth	man	long	first
[61] night	can	may	always	must

[66]	mind	took	ask	noth	turn
[71]	anoth	home	seem	room	murdston
[76]	doctor	without	two	friend	life
[81]	got	thing	walk	cri	word
[86]	young	call	still	last	place
[91]	believ	door	found	hope	repli
[96]	better	sat	though	done	heart

- (b) Using the data in Part (a) inspect the data frame and using Wikipedia or any other source identify the main characters listed. Reprocess your data to selectively remove these characters and re-plot the word frequencies.

I'll leave this to you!