

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

October 7, 2019

Table of Contents

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

1 Introduction

2 Background

3 Apparatus

4 Method

5 Results

6 Conclusions

7 Future Work

8 References

Introduction

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

- Wheel ‘truing’ is the process of adjusting spoke tension to minimize lateral, radial, and tension variations
- Commercial robotic bicycle wheel truing machines employ an open loop algorithm that operates iteratively
- This method may not achieve wheel specifications requiring human intervention

The work that follows demonstrates an optimal approach to wheel truing using system identification techniques and feedback control to achieve wheel alignment.

The Bicycle Wheel

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

- The bicycle wheel is a structure consisting of a rim, a hub, and spokes connecting the hub to the rim
- The spokes are under tension to provide the stiffness to wheel structure
- The rim is under compression
- The wheel can be considered a system of springs in parallel and series combinations
- Spoke tension must be high enough to support the load (bicycle and rider) but not so high that the rim warps laterally
- Spokes patterns vary from radial to nearly tangential

Bicycle Wheel Geometry

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References




Image credit: Ford, Matthew, *Reinventing the Wheel: Stress Analysis, Stability, and Optimization of the Bicycle Wheel*, PhD. Dissertation Northwestern University, December 2018.

Wheel Truing

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

- Spoke tension is adjusted by tightening or loosening the spoke via a threaded nipple seated in the rim
- Spoke tension consists of lateral, radial, and tangential components at the rim
- Spoke tension is adjusted such that rim is ‘true’ in both lateral and radial dimensions, and desired mean tension is achieved
- Conventional truing algorithm:
 - 1 Adjust mean tension
 - 2 Minimize lateral variations
 - 3 Minimize radial variations
 - 4 Repeat until all desired specifications are met

Apparatus

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

- Centrimaster Comfort Wheel Truing Stand
- WheelFanatyk Digital Tension Gauge
- Canon EOS M, prime 22mm lens
- Wheel: Stans ZTR Alpha Rim, DT Swiss Competition spokes, White Industries MI5 hub



System Identification Methodology

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method


Results

Conclusions

Future Work

References

Identify the lateral, radial and tension changes ('gain curves') induced by a unit spoke adjustment for each spoke



Theoretical gain curves derived for a generic wheel using <https://github.com/dashdotrobot/bike-wheel-calc>

Measurements Using Computer Vision

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References




(a)



(b)



(c)



(d)

Algorithm to interpret gauge displacements:

- ① Reference image (a)
- ② Measurement (or zero value) image (b)
- ③ Subtract measurement from reference (c)
- ④ Binary threshold and mask (d)
- ⑤ Calculate angle of centroid from gauge center
- ⑥ Calculate displacement measurement from angle

Spoke Tension Measurements



WheelFanatyk spoke tension meter. Image credit: <https://www.wheelfanatyk.com>

- Digital spoke tension measurements
- Data collected through USB to PC
- Meter collects displacement of spoke by calibrated spring
- Reference measurement accounts for variation of spoke thickness
- Tension values interpolated from calibration table

Measurement Data Vector

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

Measurement data collected for a wheel under test:

$$\mathbf{U} = \begin{bmatrix} u(\theta = 1\frac{2\pi}{2n_s}) \\ u(\theta = 2\frac{2\pi}{2n_s}) \\ \vdots \\ u(\theta = 2n_s\frac{2\pi}{2n_s}) \end{bmatrix}, \quad \mathbf{V} = \begin{bmatrix} v(\theta = 1\frac{2\pi}{2n_s}) \\ v(\theta = 2\frac{2\pi}{2n_s}) \\ \vdots \\ v(\theta = 2n_s\frac{2\pi}{2n_s}) \end{bmatrix}, \quad \mathbf{T} = \begin{bmatrix} t(\theta = 1\frac{2\pi}{n_s}) \\ t(\theta = 2\frac{2\pi}{n_s}) \\ \vdots \\ t(\theta = n_s\frac{2\pi}{n_s}) \end{bmatrix}$$
$$\mathbf{Y} = \begin{bmatrix} \mathbf{U} \\ \mathbf{V} \\ \mathbf{T} - \bar{\mathbf{T}} \end{bmatrix}$$

- n_s = number of spokes
- θ = rim angle measurement location where $\theta = 0$ is taken to be the valve hole
- $u(\theta), v(\theta), t(\theta)$ = lateral, radial, and tension measurements taken at rim angle θ
- \bar{T} = mean spoke tension

Gain Matrices

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

Let $\mathbf{u}_s = u_s(\theta)$ be the lateral displacement vector (gain curve) for every discrete θ around the rim induced by turning spoke s by one rotation. The matrix of all \mathbf{u}_s gain curves is defined to be the lateral 'gain' matrix Φ_u . The radial and tension gain matrices are similarly defined.

$$\Phi_u = [\mathbf{u}_1 \quad \mathbf{u}_2 \quad \dots \quad \mathbf{u}_{n_s}]$$

$$\Phi_v = [\mathbf{v}_1 \quad \mathbf{v}_2 \quad \dots \quad \mathbf{v}_{n_s}]$$

$$\Phi_t = [\mathbf{t}_1 \quad \mathbf{t}_2 \quad \dots \quad \mathbf{t}_{n_s}]$$

Measurement Prediction

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

Let \mathbf{d} be a vector of spoke rotations. Let \mathbf{Y}_b be the baseline wheel measurements, that is, the state of the wheel prior to the application of \mathbf{d} . The predicted lateral, radial, and tension measurements, $\hat{\mathbf{Y}}$, after applying \mathbf{d} to the spokes is given by:

$$\Phi = \begin{bmatrix} \Phi_u \\ \Phi_v \\ \Phi_t \end{bmatrix}$$

$$\hat{\mathbf{Y}} = \mathbf{Y}_b + \Phi\mathbf{d}$$

Multi-objective Least Squares

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction
Background
Apparatus
Method
Results
Conclusions
Future Work
References

Compute the optimal vector of spoke rotations, \mathbf{d}_{ls} , from the set of measurements, $\{\mathbf{u}, \mathbf{v}, \mathbf{T}\}$ given the weighting factors μ_v and μ_t :

$$\tilde{\Phi} = \begin{bmatrix} \Phi_u \\ \Phi_v\sqrt{\mu_v} \\ \Phi_t\sqrt{\mu_t} \end{bmatrix} \quad \tilde{\mathbf{Y}} = \begin{bmatrix} \mathbf{u} \\ \mathbf{v}\sqrt{\mu_v} \\ (\mathbf{T} - \bar{\mathbf{T}})\sqrt{\mu_t} \end{bmatrix}$$
$$\mathbf{d}_{ls} = \tilde{\Phi}^\dagger \tilde{\mathbf{Y}}$$

Where $\tilde{\Phi}^\dagger$ is the pseudo-inverse of $\tilde{\Phi}$. The weighting factors represent the tradeoff between the lateral, radial, and tension variables and are found through evaluation of the wheel specification, as well as the noise and accuracy of the measurements.

Tension Targeting

- Targeting a different tension, T_d , can be accomplished by substituting T_d for \bar{T} into \mathbf{Y}
- However:
 - T_d is weighted when calculating \mathbf{d} —not desirable
 - Non-ideality in tension gain curves is amplified when T_d is significantly different than \bar{T}
- Note: *ensemble average tension changes do not affect lateral and radial displacements.*
- Equivalently, a constant added to \mathbf{d} does not effect lateral and radial displacements
- Therefore average tension changes ($T_d - \bar{T}$) are separable from total tension changes ($\Phi_t \mathbf{d}$) and predicted with higher confidence

Tension Targeting

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

A better approach is to subtract the mean adjustment value from \mathbf{d}_{ls} and to calculate a constant factor, d_{cm} that induces the desired change in mean tension:

$$\begin{aligned}\mathbf{d} &= -(\mathbf{d}_{ls} - \bar{d}_{ls}) \\ d_{cm} &= (T_d - \bar{T})/c\end{aligned}$$

where c is the proportionality constant between mean tension and mean adjustment. The predicted tension vector, $\hat{\mathbf{T}}$, becomes:

$$\begin{aligned}\hat{\mathbf{T}} &= \bar{T} + \Phi_t \mathbf{d} + d_{cm} c \\ &= T_d + \Phi_t \mathbf{d}\end{aligned}$$

Truing Algorithm

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method

Results

Conclusions

Future Work

References

- \mathbf{d} is vector of nipple rotations that take the wheel from current to desired state
- Spoke nipple turns are difficult to apply accurately. Instead predict the state of the system after each adjustment (entry in \mathbf{d})
- Adjust the spoke until the lateral displacement at the spoke location matches the prediction
- After all spokes adjusted, measure state of the system
- Demonstrated graphically in the next slides...

Truing Algorithm

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Thick curve is predicted profile, diamond is lateral target

Truing Algorithm

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Thick curve is predicted profile, diamond is lateral target

Truing Algorithm

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Thick curve is predicted profile, diamond is lateral target

Truing Algorithm

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Thick curve is predicted profile, diamond is lateral target

Truing Algorithm

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Thick curve is predicted profile, diamond is lateral target

Truing Algorithm

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



- Predicted lateral profiles *after* each spoke adjustment
- Diamonds represent lateral targets
- Green represents final (trued) profile

Computer Vision Validation

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus



Method

Results

Conclusions

Future Work

References



- Four dual gauge readings were recorded
- Gauges were set to 1mm, 0.5mm, 0.1mm, and 0mm
- Visual analysis and CV algorithm results compared
- Visual analysis resolution is 0.0135mm
- Results agree to $\pm 0.007\text{mm}$

Tension Gain Curves

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method


Results

Conclusions

Future Work

References

- 32 tension curves were collected
- Four distinct patterns identified:
 - Non-drive side leading
 - Drive side leading
 - Non-drive side trailing
 - Drive side trailing



Lateral and Radial Gain Curves

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results


Conclusions

Future Work

References



(a)



(b)

- 32 lateral and radial curves measured (a)
- Mean gain curves used for model (b)
- Curves normalized to same rim angle and side for clarity

Truing Algorithm Simulation

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus



Method

Results

Conclusions

Future Work

References



- Random spoke displacement vector, \mathbf{d} , generated
- Noise added to simulated profile
- Spoke displacement vector, $\hat{\mathbf{d}}$, predicted
- Weighting factors adjusted for performance

Simulation Error

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus

Method


Results

Conclusions

Future Work

References

- Lateral displacement is more sensitive than radial with same spec
- Units comparison of tension to lateral
 $\implies \mu_t < \frac{0.6}{300}$
- Weighting factors yielding satisfactory performance:
 - $\mu_v = 0.5$
 - $\mu_t = 1.0e - 5$



Experiment 1: De-true Test Wheel

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus



Method

Results

Conclusions

Future Work

References



- Simulation spoke vector \mathbf{d} applied to manually-trued test wheel
- Spokes adjusted using lateral feedback
- The model predicts the experimental results well

Experiment 2: True Test Wheel to 1000N

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Parameter	Initial ($\mu \pm \sigma$)	Final ($\mu \pm \sigma$)
Lateral [mm]	0.160 ± 0.736	-0.037 ± 0.107
Radial [mm]	0.050 ± 0.158	-0.046 ± 0.047
Tension [N]	556 ± 211	1009 ± 45

Single iteration effectively trues a wheel

Experiment 3: Iterate Truing Algorithm

Bicycle Wheel System Identification and Optimal Truing Algorithm

Aaron Hunter

Introduction

Background

Apparatus


Method

Results

Conclusions

Future Work

References



Wheel measurements ($\mu \pm \sigma$):

Parameter	Initial	Final
Lateral [mm]	-0.037 ± 0.107	0.028 ± 0.073
Radial [mm]	-0.046 ± 0.047	-0.031 ± 0.034
Tension [N]	1009 ± 45	989 ± 39

Small but significant improvement after second iteration

Conclusions

- System identification techniques used to develop linear model of a wheel subject to spoke tension inputs
- Computer vision techniques provide finer resolution from analog gauges than visual estimations
- Computer vision vastly reduces time for data collection
- The model can be used to predict:
 - Lateral displacement
 - Radial displacement
 - Tension changes
- Multi-objective least squares approximations of these parameters used to find optimal spoke displacements for wheel truing
- Wheel truing algorithm minimizes errors in tension adjustment using lateral feedback

Conclusions

- Truing performance limited by spoke tension adjustment resolution:
 - Spoke twist during adjustment
 - Friction at nipple/spoke thread interface
- Truing performance also limited by tension measurement accuracy and resolution
 - Small effects due to spoke patterns not captured by model

Future Work

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction
Background
Apparatus

Method

Results

Conclusions

Future Work

- Comparison with theoretical models
- Extension of model to include tension offset (side to side)
- Improved resolution/accuracy tensiometer
- Mechatronic implementation

References

Bicycle Wheel
System
Identification
and Optimal
Truing
Algorithm

Aaron Hunter

Introduction
Background
Apparatus
Method
Results
Conclusions
Future Work
References

- Ford, Matthew, *Reinventing the Wheel: Stress Analysis, Stability, and Optimization of the Bicycle Wheel*, PhD. Dissertation Northwestern University, December 2018
- Brandt, Jobst, *The Bicycle Wheel*, Avocet, 1993