1 Concourse CheatSheet

Tools

Updated: September 13, 2018

 \bullet PDF Link: cheatsheet-concourse-A4.pdf

• Blog URL: https://cheatsheet.dennyzhang.com/cheatsheet-concourse-A4

• Category: tools

File me Issues or star this repo

See more CheatSheets from Denny: #denny-cheatsheets

1.1 Concepts

Name Summary
Targets alias of endpoint urls
Behavior

Links:

https://concourse-ci.org/concepts.html

1.2 Concourse fly

Name	Summary
fly login	fly -t <target> login -c \$concourse_url -t <team></team></target>
Update pipeline	setpipeline.sh <pipeline_name></pipeline_name>
Login to container	fly -t <target> hijack -u <job_url></job_url></target>
Get pipeline definition	fly -t \$target get-pipeline -p \$job-name > job.yaml link: fly-getpipeline
List all authenticated end points	fly targets link: fly targets

1.3 Modules

Name	Summary
Git repo	git-resource example: example-git.yml
Google Bucket	gcs-resource
Docker image	docker-image-resource

Links:

https://concoursetutorial.com/

https://github.com/concourse/docker-image-resource

https://github.com/frodenas/gcs-resource https://github.com/concourse/git-resource

1.4 fly Online Usage

bash-3.2\$ fly --help
error: Usage:

fly [OPTIONS] <command>

Application Options:

-t, --target= Concourse target name

-v, --version Print the version of Fly and exit
--verbose Print API requests and responses

--print-table-headers Print table headers even for redirected output

Help Options:

-h, --help Show this help message

Available commands:

abort-build Abort a build (aliases: ab)
builds List builds data (aliases: bs)
check-resource Check a resource (aliases: cr)

checklist Print a Checkfile of the given pipeline (aliases: cl) Print the active containers (aliases: cs) containers destroy-pipeline Destroy a pipeline (aliases: dp) Destroy a team and delete all of its data (aliases: dt) destroy-team Execute a one-off build using local bits (aliases: e) execute Make a pipeline publicly viewable (aliases: ep) expose-pipeline Format a pipeline config (aliases: fp) format-pipeline get-pipeline Get a pipeline's current configuration (aliases: gp) Print this help message help hide-pipeline Hide a pipeline from the public (aliases: hp) Execute a command in a container (aliases: intercept, i) hijack List the jobs in the pipelines (aliases: js) jobs Authenticate with the target (aliases: 1) login logout Release authentication with the target (aliases: o) Orders pipelines (aliases: op) order-pipelines Pause a job (aliases: pj) pause-job Pause a pipeline (aliases: pp) pause-pipeline Pause a resource (aliases: pr) pause-resource pipelines List the configured pipelines (aliases: ps) Prune a stalled, landing, landed, or retiring worker (aliases: pw) prune-worker Rename a pipeline (aliases: rp) rename-pipeline rename-team Rename a team (aliases: rt) Create or update a pipeline's configuration (aliases: sp) set-pipeline Create or modify a team to have the given credentials (aliases: st) set-team status Login status Download and replace the current fly from the target (aliases: s) sync List saved targets (aliases: ts) targets List the configured teams (aliases: t) teams Start a job in a pipeline (aliases: tj) trigger-job unpause-job Unpause a job (aliases: uj) unpause-pipeline Un-pause a pipeline (aliases: up) Unpause a resource (aliases: ur) unpause-resource validate-pipeline Validate a pipeline config (aliases: vp) List the active volumes (aliases: vs) volumes watch Stream a build's output (aliases: w) List the registered workers (aliases: ws) workers

1.5 More Resources

http://www.mikeball.info/blog/concourse-git-resource/ License: Code is licensed under MIT License.