

CheatSheet: Concourse

VMWARE

- PDF Link: [cheatsheet-concourse-A4.pdf](#), Category: vmware
- Blog URL: <https://cheatsheet.dennyzhang.com/cheatsheet-concourse-A4>
- Related posts: Bosh CheatSheet, PKS CheatSheet, #denny-cheatsheets

File me Issues or star this repo

1.1 Concourse Advanced

Name	Summary
github-release resource cannot find old tag	<code>fly -t \$target cr -r \$pipeline-name/\$resource-name -f tag:\$tag</code>
fly set-pipeline run into "error: forbidden"	Need to logout from both fly client (<code>fly logout --all</code>) and Concourse GUI
List team details for all targets	<code>fly -t \$target teams -d, ~/.flyrc</code>
Hijack to containers with a successful run	You can't. By design when task has passed, the container will be deleted
Split one pipeline yaml into small reusable pieces	Not supported. Link: GitHub. For now, we need to workaround it.
Reference	concourse-tutorial, concourse-pipeline-samples

1.2 Concourse Resources & Examples

Name	Summary
Hello world pipeline	example: helloworld.yml
Pass output to input across different tasks	example: tasks-output-input.yml
Trigger pipeline test every 5 minutes	example: run-test-regularly.yml
git-resource	example: example-git.yml
concourse-curl-resource: http download link	example: url-download.yml
github-release	
docker-image-resource: docker image	
gcs-resource: google bucket	
file-downloader-resource	enable downloading pivotal product files and stemcells
PCF pipelines examples	GitHub: pcf-pipelines

<https://raw.githubusercontent.com/dennyzhang/cheatsheet.dennyzhang.com/master/cheatsheet-concourse-A4/concourse-sample.png>

1.3 Concourse Containers

Name	Summary
Login to container	<code>fly -t \$target hijack -u \$job_url</code>
Run command without sudden exit	<code>nohup SOMECOMMAND & tail -f nohup.out</code>

1.4 Concourse Concepts

Name	Summary
Links	Link: Concourse Concepts, Link: concoursetutorial.com
Pipelines	
Jobs	
Tasks	
fly	Pipelines are configured entirely via the fly. There is no GUI. Link: fly
Behaviors	
Step: tags	Use tag to match workers
Resource	Allow you to define inputs and outputs to jobs in a pipeline
Targets	Alias of Concourse endpoints
Teams	
bbl (bosh-bootloader)	GitHub: bosh-bootloader

1.5 Concourse Authentication & Authorization

Name	Summary
Fly login to the default main team	<code>fly -t \$target login -n main -c \$concourse_url</code>
Fly login to a different team	<code>fly -t \$target login -n \$team_name -c \$concourse_url</code>
List all teams	<code>fly -t \$target teams, fly -t \$target teams -d</code>
Fly logout all targets	<code>fly logout --all</code>
Create a team	<code>fly -t \$target set-team -n \$team_name --allow-all-users</code>
Destroy a team	<code>fly -t \$target destroy-team --team-name \$team_name</code>
Grant Github team access	<code>fly -t \$target set-team -n \$team_name --github-org \$my_org</code>
Login to a team	<code>fly -t \$target set-team -n \$team_name</code>
Fly conf file	<code>~/.flyrc</code>
Reference	After login to the main team, you can update other teams. Link: Concourse Team

1.6 Concourse Pipeline

Name	Summary
List all authenticated end points	<code>fly targets</code> Link: fly targets
fly login	<code>fly -t \$target login -c \$concourse_url -n \$team_name</code>
Get pipeline definition	<code>fly -t \$target get-pipeline -p \$job-name > job.yaml</code> Link: fly-getpipeline
Update pipeline	<code>fly -t \$target set-pipeline -p \$pipeline_name -c pipeline.yml -l credentials.y</code>
Update pipeline	<code>fly -t \$target set-pipeline -p \$pipeline_name -c pipeline.yml -v env1=var1</code>
Destroy pipeline	<code>fly -t \$target destroy-pipeline -p \$pipeline_name</code>
Format pipeline	<code>fly format-pipeline -c pipeline.yml</code>
Validate pipeline	<code>fly validate-pipeline -c pipeline.yml</code>

1.7 Concourse GUI/UI

Name	Summary
URL for pipelines for a given team	Search by team, then generate a url
Get fly version	<code>fly --version</code>

1.8 fly Online Usage

```
bash-3.2$ fly --help
error: Usage:
  fly [OPTIONS] <command>
```

Application Options:

<code>-t, --target=</code>	Concourse target name
<code>-v, --version</code>	Print the version of Fly and exit
<code>--verbose</code>	Print API requests and responses
<code>--print-table-headers</code>	Print table headers even for redirected output

Help Options:

<code>-h, --help</code>	Show this help message
-------------------------	------------------------

Available commands:

<code>abort-build</code>	Abort a build (aliases: ab)
<code>builds</code>	List builds data (aliases: bs)
<code>check-resource</code>	Check a resource (aliases: cr)
<code>checklist</code>	Print a Checkfile of the given pipeline (aliases: cl)
<code>containers</code>	Print the active containers (aliases: cs)
<code>destroy-pipeline</code>	Destroy a pipeline (aliases: dp)
<code>destroy-team</code>	Destroy a team and delete all of its data (aliases: dt)
<code>execute</code>	Execute a one-off build using local bits (aliases: e)
<code>expose-pipeline</code>	Make a pipeline publicly viewable (aliases: ep)
<code>format-pipeline</code>	Format a pipeline config (aliases: fp)

get-pipeline	Get a pipeline's current configuration (aliases: gp)
help	Print this help message
hide-pipeline	Hide a pipeline from the public (aliases: hp)
hijack	Execute a command in a container (aliases: intercept, i)
jobs	List the jobs in the pipelines (aliases: js)
login	Authenticate with the target (aliases: l)
logout	Release authentication with the target (aliases: o)
order-pipelines	Orders pipelines (aliases: op)
pause-job	Pause a job (aliases: pj)
pause-pipeline	Pause a pipeline (aliases: pp)
pause-resource	Pause a resource (aliases: pr)
pipelines	List the configured pipelines (aliases: ps)
prune-worker	Prune a stalled, landing, landed, or retiring worker (aliases: pw)
rename-pipeline	Rename a pipeline (aliases: rp)
rename-team	Rename a team (aliases: rt)
set-pipeline	Create or update a pipeline's configuration (aliases: sp)
set-team	Create or modify a team to have the given credentials (aliases: st)
status	Login status
sync	Download and replace the current fly from the target (aliases: s)
targets	List saved targets (aliases: ts)
teams	List the configured teams (aliases: t)
trigger-job	Start a job in a pipeline (aliases: tj)
unpause-job	Unpause a job (aliases: uj)
unpause-pipeline	Un-pause a pipeline (aliases: up)
unpause-resource	Unpause a resource (aliases: ur)
validate-pipeline	Validate a pipeline config (aliases: vp)
volumes	List the active volumes (aliases: vs)
watch	Stream a build's output (aliases: w)
workers	List the registered workers (aliases: ws)

1.9 fly set-pipeline Online Usage

```
> fly set-pipeline --help
error: Usage:
  fly [OPTIONS] set-pipeline [set-pipeline-OPTIONS]
```

Application Options:

-t, --target=	Concourse target name
-v, --version	Print the version of Fly and exit
--verbose	Print API requests and responses
--print-table-headers	Print table headers even for redirected output

Help Options:

-h, --help	Show this help message
------------	------------------------

[set-pipeline command options]

-n, --non-interactive	Skips interactions, uses default values
--no-color	Disable color output
--check-creds	Validate credential variables against credential manager
-p, --pipeline=	Pipeline to configure
-c, --config=	Pipeline configuration file
-v, --var=[NAME=STRING]	Specify a string value to set for a variable in the pipeline
-y, --yaml-var=[NAME=YAML]	Specify a YAML value to set for a variable in the pipeline
-l, --load-vars-from=	Variable flag that can be used for filling in template values in configuration

1.10 More Resources

<http://www.mikeball.info/blog/concourse-git-resource/>
<https://concoursetutorial.com/>

License: Code is licensed under MIT License.