# 1 CheatSheet: Mongodb

Tools

Updated: January 12, 2019

- PDF Link: cheatsheet-mongodb-A4.pdf, Category: Tools
- ullet Blog URL: https://cheatsheet.dennyzhang.com/cheatsheet-mongodb-A4
- Related posts: Prometheus CheatSheet, Nagios CheatSheet, #denny-cheatsheets

File me Issues or star this repo.

### 1.1 Mongodb Operation

Name	Summary
Connect to mongodb	mongo 192.168.75.108:12345/d_2003 -u u_2003 -p XXXX
Start mongo	<pre>mongodconfig /etc/mongod.conf</pre>
Stop mongo	kill -15 <pid>; mongoeval "db.getSiblingDB('admin').shutdownServer()"</pid>
Mongo script get parameters	mongo –eval "var day='2013-07-26'" localhost:27017/shopex mongojs/update-index.js
Mongo data folder	/var/lib/mongodb/journal
Export to json file	mongoexportdb shopexcollection orderout collection.json
Import json file	mongoimportupsertdb shopexcollection orderfile collection.json

### 1.2 Mongodb Basic

Name	Summary
Remove table	db.kvstore.remove()
define stored procedure	<pre>db.system.js.save({_id:"addNumbers", value:function(x, y){ return x + y; }})</pre>
view stored procedure	db.system.js.find()
call stored procedure	db.eval('addNumbers(3, 4.2)')
Create record	db.users.insert({"name":{"first":"refactor","last":"refactor2"},"age":24})
Update record	db.users.update({"age":30}, {\$set:{"age":31}});
Delete by filtering	db.users.remove({"age":30})
Loop cusror	<pre>while(s.hasNext()) printjson(s.next());</pre>
Loop array	$i=0;  ext{ while} (i <  ext{s.length})  ext{ printjson} ( ext{s}[i++]);$

## 1.3 Mongodb Query

Name	Summary
Basic query	db.users.find({"name":{"first":"refactor","last":"refactor2"}})
Basic query	$db.users.find({"name.first":"refactor"})$
great than / or equal	$db.users.find({"age":{"\$gte":20}})$
not equal	$db.users.find({"age":{"$ne":31}})$
exists	db.users.find({"age":{"\$exists":true}})
in	db.users.find( $\{\text{"age":}\{\text{"$in":}[21,24]\}\}$ )
not in	db.users.find( $\{\text{"age":}\{\text{"$nin":}[21,23]\}\}$ )
or	db.users.find({"\$or":[{"name.last":"another"}, {"age":31}]})
Count matched records	$\label{localization} $\operatorname{db.order.find}(\{\text{"created":}\{\text{"$regex":"2013-07-12.*"}\}\}).count()$$
	$db.users.find({"age":{"$nin":[21,23]}}).count()$
query by offset	$db.users.find({"age":{"$nin":[21,23]}}).skip(1).limit(2)$
sort	$db.users.find().sort({"age":24});$
reverse order	$db.users.find().sort({"name.last": -1})$
	db.users.find().forEach( function(u) { printjson(u); } );
$\mod 20$	db.users.find( $\{\text{"age":}\{\text{"$mod":}[20,4]\}\}$ )
Parse string to float	parseFloat(v.availableConfirmFee, 10);
filter by "like"	$db.taobao.find(\{"created":/2013-07-12.*/\})$
	$db.order.find(\{"created":/2013-07-14.*/, "num": \{"\$exists": false\}\}).forEach(\ function(u)\ \{\ printjson(u.ternation(u), u.ternation(u), u.t$
	db.order.find({"created":{"\$regex":day}}).count();
	db.order.distinct("buyerNick", {"created":{"\$regex":day}}).length

## 1.4 More Resources

License: Code is licensed under MIT License.

Updated: January 12, 2019