

CheatSheet: Linux Disk

LINUX

- PDF Link: [cheatsheet-disk-A4.pdf](#), Category: linux
- Blog URL: <https://cheatsheet.dennyzhang.com/cheatsheet-disk-A4>
- Related posts: CheatSheet: Linux Process, CheatSheet: Linux Networking, #denny-cheatsheets

File me Issues or star this repo.

1.1 Summary

Name	Comment
df	Show information about the file system.
du	Summarize disk usage of each FILE, recursively for directories.
dd	Copy a file, converting and formatting according to the operands.
mount	Mount file systems.
lsblk	List information about all available or the specified block devices.
Reference	CheatSheet: Linux Process, CheatSheet: Linux Networking, CheatSheet: Linux Disk

1.2 du

Name	Comment
Show the disk usage of current folder	<code>du -sh</code>
Show disk usage for a given folder	<code>du -h -d 2 /data/elasticsearch/</code>
Sort directories/files by size	GitHub: sort-disk-size.sh

1.3 df

Name	Comment
List all disks with humanreadable format	<code>df -h</code>

1.4 dd

Name	Comment
Create a file with fixed size and random context	<code>dd if=/dev/urandom of=/tmp/random.txt count=3 bs=256</code>
Create a file with fixed size and empty context	<code>dd if=/dev/zero of=/tmp/random.txt count=3 bs=256</code>

1.5 mount

Name	Comment
Mount an ISO to a folder	<code>mount -o loop my-disk.iso /mnt/disk</code>
Mount NFS	<code>mount -t nfs 192.168.1.1:/usr/share /mnt/share</code>
Remount rootfs as read-write in repair mode	<code>mount -o remount,rw /</code>

1.6 lsblk

Name	Comment
List all available block devices	<code>lsblk</code>
List all scsi devices	<code>lsblk --scsi</code>
Show a specific device	<code>lsblk /dev/sda</code>
List block devices with filesystem info	<code>lsblk --fs</code>

1.7 Online Help Usage

```
> du --help
```

```
Usage: du [OPTION]... [FILE]...
```

```
or: du [OPTION]... --files0-from=F
```

```
Summarize disk usage of each FILE, recursively for directories.
```

Mandatory arguments to long options are mandatory for short options too.

```
-0, --null          end each output line with 0 byte rather than newline
```

```

-a, --all                write counts for all files, not just directories
--apparent-size          print apparent sizes, rather than disk usage; although
                        the apparent size is usually smaller, it may be
                        larger due to holes in ('sparse') files, internal
                        fragmentation, indirect blocks, and the like
-B, --block-size=SIZE    scale sizes by SIZE before printing them; e.g.,
                        '-BM' prints sizes in units of 1,048,576 bytes;
                        see SIZE format below
-b, --bytes              equivalent to '--apparent-size --block-size=1'
-c, --total              produce a grand total
-D, --dereference-args   dereference only symlinks that are listed on the
                        command line
-d, --max-depth=N        print the total for a directory (or file, with --all)
                        only if it is N or fewer levels below the command
                        line argument; --max-depth=0 is the same as
                        --summarize
--files0-from=F          summarize disk usage of the
                        NUL-terminated file names specified in file F;
                        if F is -, then read names from standard input
-H                      equivalent to --dereference-args (-D)
-h, --human-readable     print sizes in human readable format (e.g., 1K 234M 2G)
--inodes                list inode usage information instead of block usage
-k                      like --block-size=1K
-L, --dereference        dereference all symbolic links
-l, --count-links        count sizes many times if hard linked
-m                      like --block-size=1M
-P, --no-dereference     don't follow any symbolic links (this is the default)
-S, --separate-dirs      for directories do not include size of subdirectories
--si                    like -h, but use powers of 1000 not 1024
-s, --summarize          display only a total for each argument
-t, --threshold=SIZE    exclude entries smaller than SIZE if positive,
                        or entries greater than SIZE if negative
--time                  show time of the last modification of any file in the
                        directory, or any of its subdirectories
--time=WORD             show time as WORD instead of modification time:
                        atime, access, use, ctime or status
--time-style=STYLE      show times using STYLE, which can be:
                        full-iso, long-iso, iso, or +FORMAT;
                        FORMAT is interpreted like in 'date'
-X, --exclude-from=FILE  exclude files that match any pattern in FILE
--exclude=PATTERN        exclude files that match PATTERN
-x, --one-file-system    skip directories on different file systems
--help                  display this help and exit
--version                output version information and exit

```

Display values are in units of the first available SIZE from --block-size, and the DU_BLOCK_SIZE, BLOCK_SIZE and BLOCKSIZE environment variables. Otherwise, units default to 1024 bytes (or 512 if POSIXLY_CORRECT is set).

SIZE is an integer and optional unit (example: 10M is 10*1024*1024). Units are K, M, G, T, P, E, Z, Y (powers of 1024) or KB, MB, ... (powers of 1000).

GNU coreutils online help: <http://www.gnu.org/software/coreutils/>
 For complete documentation, run: `info coreutils 'du invocation'`

1.8 More Resources

License: Code is licendiff under MIT License.