

CheatSheet: vagrant

CLOUD

```
#+BEGINEXPORT HTML <a href="https://github.com/dennyzhang/cheatsheet.dennyzhang.com/tree/master/cheatsheet-vagrant-A4"></a> <div id="the whole thing" style="overflow: hidden;"> <div style="float: left; padding: 5px"> <a href="https://www.linkedin.com/in/dennyzhang001"></a></div> <div style="float: left; padding: 5px"><a href="https://github.com/dennyzhang"></a></div> <div style="float: left; padding: 5px"><a href="https://www.dennyzhang.com/slack" target="_blank" rel="nofollow"></a></div> </div>
<br/><br/> <a href="http://makeapullrequest.com" target="_blank" rel="nofollow"></a> #+ENDHTML
```

- PDF Link: [cheatsheet-vagrant-A4.pdf](#), Category: Cloud
- Blog URL: <https://cheatsheet.dennyzhang.com/cheatsheet-vagrant-A4>
- Related posts: [Docker CheatSheet](#), [Kubectl CheatSheet](#), [#denny-cheatsheets](#)

File me Issues or star this repo.

1.1 vagrant Basic

Name	Command
Vagrant supported providers	VirtualBox, VMware, Docker, Hyper-V
Check version	<code>vagrant version</code>
Start vm from vagrantfile	<code>vagrant up</code> . Sample vagrantfile
Start vm with customization	<code>vagrant up --debug</code> , <code>vagrant up --provider virtualbox</code>
Destroy vagrant vm	<code>vagrant destroy</code>
SSH to vagrant vm	<code>vagrant ssh</code>
lists all boxes installed into Vagrant	<code>vagrant box list</code>
Vagrant data folder	<code>~/ .vagrant.d</code>
Reference	Link: vagrant cli , Link: Discover Vagrant Boxes

1.2 vagrant start vms

Name	Command
ubuntu 14.04 64bits	<code>vagrant init ubuntu/trusty64</code>
ubuntu 12.04 32bits	<code>vagrant init hashicorp/precise32</code>
ubuntu 12.04 64bits	<code>vagrant init hashicorp/precise64</code>
ubuntu 16.04 64bits	<code>vagrant init hashicorp-vagrant/ubuntu-16.04</code>
CentOS 6.5	<code>vagrant init chef/centos-6.5</code>
Start vm from image	<code>vagrant init precise64 http://files.vagrantup.com/precise64.box</code>

1.3 vagrant advanced

Name	Command
Show Vagrant environments	<code>vagrant global-status</code>
stops the vagrant machine	<code>vagrant halt</code>
package virtualbox vm to boxfile	<code>vagrant package --base my-virtual-machine</code>
Get detail ssh configuration	<code>vagrant ssh-config</code>
Start vm with	<code>vagrant up --debug</code>
Copy local files to vagrant vm	<code>copy-to-vagrant.sh</code>
Update vagrant boxes	<code>vagrant box update</code> , <code>vagrant box update --box \$box_name</code>
Destroy all old boxes	<code>vagrant box destroy</code>
Vagrant add a secondary drive	
Vagrant resize disk	

1.4 Online Help Usage

```
> vagrant --help
```

WARNING: This command has been deprecated in favor of ‘vagrant cloud auth login’

Usage: vagrant [options] <command> [<args>]

```
-v, --version      Print the version and exit.
-h, --help         Print this help.
```

Common commands:

box	manages boxes: installation, removal, etc.
cloud	manages everything related to Vagrant Cloud
destroy	stops and deletes all traces of the vagrant machine
global-status	outputs status Vagrant environments for this user
halt	stops the vagrant machine
help	shows the help for a subcommand
init	initializes a new Vagrant environment by creating a Vagrantfile
login	
package	packages a running vagrant environment into a box
plugin	manages plugins: install, uninstall, update, etc.
port	displays information about guest port mappings
powershell	connects to machine via powershell remoting
provision	provisions the vagrant machine
push	deploys code in this environment to a configured destination
rdp	connects to machine via RDP
reload	restarts vagrant machine, loads new Vagrantfile configuration
resume	resume a suspended vagrant machine
snapshot	manages snapshots: saving, restoring, etc.
ssh	connects to machine via SSH
ssh-config	outputs OpenSSH valid configuration to connect to the machine
status	outputs status of the vagrant machine
suspend	suspends the machine
up	starts and provisions the vagrant environment
upload	upload to machine via communicator
validate	validates the Vagrantfile
version	prints current and latest Vagrant version
winrm	executes commands on a machine via WinRM
winrm-config	outputs WinRM configuration to connect to the machine

For help on any individual command run ‘vagrant COMMAND -h’

Additional subcommands are available, but are either more advanced or not commonly used. To see all subcommands, run the command ‘vagrant list-commands’.

1.5 More Resources

<https://www.vagrantup.com/docs/cli/>

<https://github.com/vagrant/vagrant>

<https://www.vagrantup.com/docs/provisioning/shell.html> License: Code is licensed under MIT License.

```
#+BEGIN_EXPORT HTML <a href="https://cheatsheet.dennyzhang.com"></a>
<a href="https://cheatsheet.dennyzhang.com"></a> #+END_HTML
```