## 1 Kubernetes kind CheatSheet

CLOUD

Updated: July 12, 2019

- PDF Link: cheatsheet-kind-A4.pdf, Category: Cloud
- Blog URL: https://cheatsheet.dennyzhang.com/cheatsheet-kind-A4
- Related posts: Minikube CheatSheet, Kubernetes Yaml, #denny-cheatsheets

File me Issues or star this repo.

See more CheatSheets from Denny: #denny-cheatsheets

• Check kubernetes cheatsheet: https://cheatsheet.dennyzhang.com/cheatsheet-kubernetes-A4

## 1.1 kind basic

| Name                | Command  |  |
|---------------------|--|--|
| Kind                | Kubernetes IN Docker - local clusters for testing Kubernetes |  |
| Install kind        | Install go and docker, then go get -u sigs.k8s.io/kind       |  |
| Check kind cli      | which kind, kind version                                     |  |
| Create kind clusrer | kind create clustername clusterapi                           |  |
| Reference           | Minikube CheatSheet, Kubernetes kind CheatSheet              |  |
| Reference           | Kubectl CheatSheet, Kubernetes Yaml                          |  |

## 1.2 kind Command

| Name                            | Command                            |
|---------------------------------|------------------------------------|
| List all kind clusters          | kind get clusters                  |
| List all nodes per cluster name | kind get nodesname \$cluster_name  |
| Create kind clusrer             | kind create clustername clusterapi |
| Delete kind cluster             | kind delete clustername clusterapi |

# 1.3 kind CLI Online Help

```
> kind version
0.3.0-alpha
```

> kind --help

kind creates and manages local Kubernetes clusters using Docker container 'nodes'

#### Usage:

kind [command]

### Available Commands:

| build      | Build one of [base-image, node-image]                              |
|------------|--|
| completion | Output shell completion code for the specified shell (bash or zsh) |
| create     | Creates one of [cluster]   |
| delete     | Deletes one of [cluster]   |
| export     | exports one of [logs]  |
| get        | Gets one of [clusters, nodes, kubeconfig-path]                     |
| help       | Help about any command   |
| load       | Loads images into nodes  |
| version    | prints the kind CLI version  |
|            |  |

### Flags:

```
-h, --help help for kind
--loglevel string logrus log level [panic, fatal, error, warning, info, debug] (default "warning")
--version version for kind
```

Use "kind [command] --help" for more information about a command.

# 1.4 More Resources

License: Code is licensed under MIT License.

https://github.com/kubernetes/minikube/tree/master/docs

Updated: July 12, 2019