

Competitive Programming and Contests

Rossano Venturini
rossano.venturini@unipi.it

Competitive Programming and Contests

- Teacher: [Rossano Venturini](#)
- Teaching assistant: [Giulio Ermanno Pibiri](#)
- CFU: 6
- Period: First semester
- Language: English
- Lectures schedule: Wednesday 14-16 (Lab I) and Friday 11-13 (C1).
- Question time: After lectures or by appointment
- [Google group](#) to discuss solutions

<https://github.com/rossanoventurini/CompetitiveProgramming>

Google™



twitter



LinkedIn

facebook®

ebay®

You Tube

amazon.com®

flickr™

Bloomberg

Microsoft®

How we hire

We're looking for our next Noogler - someone who's good for the role, good for Google and good at lots of things.

Things move quickly around here. At Internet speed. That means we have to be nimble, both in how we work and how we hire. We look for people who are great at lots of things, love big challenges and welcome big changes. We can't have too many specialists in just one particular area. We're looking for people who are good for Google—and not just for right now, but for the long term.

This is the core of how we hire. Our process is pretty basic; the path to getting hired usually involves a first conversation with a recruiter, a phone interview and an onsite interview at one of our offices. But there are a few things we've baked in along the way that make getting hired at Google a little different.

How we interview

We're looking for smart, team-oriented people who can get things done. When you interview at Google, you'll likely interview with four or five Googlers. They're looking for four things:

Leadership

We'll want to know how you've flexed different muscles in different situations in order to mobilize a team. This might be by asserting a leadership role at work or with an organization, or by helping a team succeed when you weren't officially appointed as the leader.

Role-Related Knowledge

We're looking for people who have a variety of strengths and passions, not just isolated skill sets. We also want to make sure that you have the experience and the background that will set you up for success in your role. For engineering candidates in particular, we'll be looking to check out your coding skills and technical areas of expertise.

How You Think

We're less concerned about grades and transcripts and more interested in how you think. We're likely to ask you some role-related questions that provide insight into how you solve problems. Show us how you would tackle the problem presented—don't get hung up on nailing the “right” answer.

Googleyness

We want to get a feel for what makes you, well, you. We also want to make sure this is a place you'll thrive, so we'll be looking for signs around your comfort with ambiguity, your bias to action and your collaborative nature.

How we decide

There are also a few other things we do to make sure we're always hiring the right candidate for the right role and for Google.

How we hire

We're looking for our next Noogler - someone who's good for the role, good for Google and good at lots of things.

Things move quickly around here. At Internet speed. That means we have to be nimble, both in how we work and how we hire. We look for people who are great at lots of things, love big challenges and welcome big changes. We can't have too many specialists in just one particular area. We're looking for people who are good for Google—and not just for right now, but for the long term.

This is the core of how we hire. Our process is pretty basic; the path to getting hired usually involves a first conversation with a recruiter, a phone interview and an onsite interview at one of our offices. But there are a few things we've baked in along the way that make getting hired at Google a little different.

How we interview

We're looking for smart, team-oriented people who can get things done. When you interview at Google, you'll likely interview with four or five Googlers. They're looking for four things:

Leadership

We'll want to know how you've flexed different muscles in different situations in order to mobilize a team. This might be by asserting a leadership role at work or with an organization, or by helping a team succeed when you weren't officially appointed as the leader.

Role-Related Knowledge

We're looking for people who have a variety of strengths and passions, not just isolated skill sets. We also want to make sure that you have the experience and the background that will set you up for success in your role. For engineering candidates in particular, we'll be looking to check out your coding skills and technical areas of expertise.

How You Think

We're less concerned about grades and transcripts and more interested in how you think. We're likely to ask you some role-related questions that provide insight into how you solve problems. Show us how you would tackle the problem presented—don't get hung up on nailing the “right” answer.

Googleyness

We want to get a feel for what makes you, well, you. We also want to make sure this is a place you'll thrive, so we'll be looking for signs around your comfort with ambiguity, your bias to action and your collaborative nature.

How we decide

There are also a few other things we do to make sure we're always hiring the right candidate for the right role and for Google.

How we hire

We're looking for our next Noogler - someone who's good for the role, good for Google and good at lots of things.

Things move quickly around here. At Internet speed. That means we have to be nimble, both in how we work and how we hire. We look for people who are great at lots of things, love big challenges and welcome big changes. We can't have too many specialists in just one particular area. We're looking for people who are good for Google—and not just for right now, but for the long term.

This is the core of how we hire. Our process is pretty basic; the path to getting hired usually involves a first conversation with a recruiter, a phone interview and an onsite interview at one of our offices. But there are a few things we've baked in along the way that make getting hired at Google a little different.

How we interview

We're looking for smart, team-oriented people who can get things done. When you interview at Google, you'll likely interview with four or five Googlers. They're looking for four things:

Leadership

We'll want to know how you've flexed different muscles in different situations in order to mobilize a team. This might be by asserting a leadership role at work or with an organization, or by helping a team succeed when you weren't officially appointed as the leader.

Role-Related Knowledge

We're looking for people who have a variety of strengths and passions, not just isolated skill sets. We also want to make sure that you have the experience and the background that will set you up for success in your role. For engineering candidates in particular, we'll be looking to check out your coding skills and technical areas of expertise.

How You Think

We're less concerned about grades and transcripts and more interested in how you think. We're likely to ask you some role-related questions that provide insight into how you solve problems. Show us how you would tackle the problem presented—don't get hung up on nailing the "right" answer.

Googleyness

We want to get a feel for what makes you, well, you. We also want to make sure this is a place you'll thrive, so we'll be looking for signs around your comfort with ambiguity, your bias to action and your collaborative nature.

How we decide

There are also a few other things we do to make sure we're always hiring the right candidate for the right role and for Google.



Content
Tools
Help
Wikipedia

Wikipedia
Community portal
Recent changes
Wikipedia

Where
Changes

Pages
Help link
Page
Page

t

Article

[Talk](#)

Read

[Edit](#)[View history](#)

Participate in the world's largest photo competition and help improve Wikipedia!



Microsoft interview

From Wikipedia, the free encyclopedia

The **Microsoft interview** is a [job interview](#) technique used by [Microsoft](#) to assess possible future Microsoft employees. It is significant because Microsoft's model was pioneering, and later picked up and developed by other companies including [Amazon](#), [Facebook](#), and [Google](#)^[*citation needed*]^[1]

Contents [\[hide\]](#)

- 1 Innovation
- 2 Further information
 - 2.1 Interview questions previously used by Microsoft
 - 2.2 Interview resources
- 3 References
- 4 External links

Innovation

[\[edit\]](#)

The Microsoft Interview was a pioneer in that it was about technical knowledge, problem solving and creativity as opposed to the [goal and weaknesses interviews](#) most companies used at the time. Initially based on Bill Gates' obsession with puzzles, many of the puzzles presented during interviews started off being [Fermi problems](#), or sometimes logic problems, and have eventually transitioned over the years into questions relevant to programming^[2]: *[P]uzzles test competitive edge as well as intelligence. Like business or football, a logic puzzle divides the world into winners and losers. You either get the answer, or you don't... Winning has to matter.*^[3] [Joel Spolsky](#) phrased the problem as identifying people who are *smart and get things done* while separating them from *people who are smart but don't get things done* and *people who get things done but are not smart*^[4]^[5]

This model is now used widely in the IT Industry, though it has been found that relationships that start under intense circumstances never last.



Content
Tools
Help
Wikipedia

Wikipedia
Community portal
Recent changes
Wikipedia

Where
Changes

Pages
Link
Page
Page

t

Article [Talk](#)

[Read](#) [Edit](#) [View history](#)



Participate in the world's largest photo competition and help improve Wikipedia!



Microsoft interview

From Wikipedia, the free encyclopedia

The **Microsoft interview** is a [job interview](#) technique used by [Microsoft](#) to assess possible future Microsoft employees. It is significant because Microsoft's model was pioneering, and later picked up and developed by other companies including [Amazon](#), [Facebook](#), and [Google](#)^[*citation needed*]^[1]

Contents [\[hide\]](#)

- 1 Innovation
- 2 Further information
 - 2.1 Interview questions previously used by Microsoft
 - 2.2 Interview resources
- 3 References
- 4 External links

Innovation

[\[edit\]](#)

The Microsoft Interview was a pioneer in that it was about technical knowledge, problem solving and creativity as opposed to the [goal and weaknesses interviews](#) most companies used at the time. Initially based on Bill Gates' obsession with puzzles, many of the puzzles presented during interviews started off being [Fermi problems](#), or sometimes logic problems, and have eventually transitioned over the years into questions relevant to programming^[2]: *[P]uzzles test competitive edge as well as intelligence. Like business or football, a logic puzzle divides the world into winners and losers. You either get the answer, or you don't... Winning has to matter.*^[3] [Joel Spolsky](#) phrased the problem as identifying people who are *smart and get things done* while separating them from *people who are smart but don't get things done* and *people who get things done but are not smart*^[4]^[5]

This model is now used widely in the IT Industry, though it has been found that relationships that start under intense circumstances never last.

Google™



Please review the following topics:

Big-O notations also known as "the run time characteristic of an algorithm". You may want to refresh hash tables, heaps, binary trees, linked lists, depth-first search, recursion. For more information on Algorithms you can visit:

http://www.topcoder.com/tc?module=Static&d1=tutorials&d2=alg_index

Coding: You should know at least one programming language really well, and it should preferably be C++ or Java. C# is OK too, since it's pretty similar to Java. You will be expected to write some code in at least some of your interviews. You will be expected to know a fair amount of detail about your favorite programming language.

Sorting: Know how to sort. Don't do bubble-sort. You should know the details of at least one $n \cdot \log(n)$ sorting algorithm, preferably two (say, quick sort and merge sort). Merge sort can be highly useful in situations where quick sort is impractical, so take a look at it.



Hashtables: Arguably the single most important data structure known to mankind. You absolutely should know how they work. Be able to implement one using only arrays in your favorite language, in about the space of one interview.

Trees: Know about trees; basic tree construction, traversal and manipulation algorithms. Familiarize yourself with binary trees, n-ary trees, and trie-trees. Be familiar with at least one type of balanced binary tree, whether it's a red/black tree, a splay tree or an AVL tree, and know how it's implemented. Understand tree traversal

Algorithms: BFS and DFS, and know the difference between inorder, postorder and preorder.

Graphs: Graphs are really important at Google. There are 3 basic ways to represent a graph in memory (objects and pointers, matrix, and adjacency list); familiarize yourself with each representation and its pros & cons. You should know the basic graph traversal algorithms: breadth-first search and depth-first search. Know their computational complexity, their tradeoffs, and how to implement them in real code. If you get a chance, try to study up on fancier algorithms, such as Dijkstra and A*.



Other Data Structures: You should study up on as many other data structures and algorithms as possible. You should especially know about the most famous classes of NP-complete problems, such as traveling salesman and the knapsack problem, and be able to recognize them when an interviewer asks you them in disguise. Find out what NP-complete means.

Mathematics: Some interviewers ask basic discrete math questions. This is more prevalent at Google than at other companies because counting problems, probability problems, and other Discrete Math 101 situations surrounds us. Spend some time before the interview refreshing your memory on (or teaching yourself) the essentials of combinatorics and probability. You should be familiar with n-choose-k problems and their ilk – the more the better.

Operating Systems: Know about processes, threads and concurrency issues. Know about locks and mutexes and semaphores and monitors and how they work. Know about deadlock and livelock and how to avoid them. Know what resources a processes needs, and a thread needs, and how context switching works, and how it's initiated by the operating system and underlying hardware. Know a little about scheduling. The world is rapidly moving towards multi-core, so know the fundamentals of "modern" concurrency constructs. For information on System

Leaders in an array

Show Topic Tags

Payu

Write a program to print all the LEADERS in the array. An element is leader if it is greater than all the elements to its right side. The rightmost element is always a leader.

Input:

The first line of input contains an integer T denoting the number of test cases. The description of T test cases follows.

The first line of each test case contains a single integer N denoting the size of array. The second line contains N space-separated integers A1, A2, ..., AN denoting the elements of the array.

Output:

Print all the leaders.

Kadane's Algorithm

Show Topic Tags

Hike Flipkart FactSet D-E-Shaw Amazon Accolite
Morgan-Stanley Microsoft MetLife Housing.com
Snapdeal Samsung Payu Oracle Ola-Cabs
[24]7 Innovation Lab Zoho Walmart Visa Teradata

Given an array containing both negative and positive integers. Find the contiguous sub-array with maximum sum.

Input:

The first line of input contains an integer T denoting the number of test cases. The description of T test cases follows. The first line of each test case contains a single integer N denoting the size of array. The second line contains N space-separated integers A_1, A_2, \dots, A_N denoting the elements of the array.

Output:

Print the maximum sum of the contiguous sub-array in a separate line for each test case.

Kadane's Algorithm

Show Topic Tags

Hike Flipkart FactSet D-E-Shaw Amazon Accolite
Morgan-Stanley Microsoft MetLife Housing.com
Snapdeal Samsung Payu Oracle Ola-Cabs
[24]7 Innovation Lab Zoho Walmart Visa Teradata

Given an array containing both negative and positive integers. Find the contiguous sub-array with maximum sum.

Input:

The first line of input contains an integer T denoting the number of test cases. The description of T test cases follows. The first line of each test case contains a single integer N denoting the size of array. The second line contains N space-separated integers A_1, A_2, \dots, A_N denoting the elements of the array.

Output:

Print the maximum sum of the contiguous sub-array in a separate line for each test case.

a

-1	5	8	-9	4	1
----	---	---	----	---	---

Kadane's Algorithm

Show Topic Tags

Hike Flipkart FactSet D-E-Shaw Amazon Accolite
Morgan-Stanley Microsoft MetLife Housing.com
Snapdeal Samsung Payu Oracle Ola-Cabs
[24]7 Innovation Lab Zoho Walmart Visa Teradata

Given an array containing both negative and positive integers. Find the contiguous sub-array with maximum sum.

Input:

The first line of input contains an integer T denoting the number of test cases. The description of T test cases follows. The first line of each test case contains a single integer N denoting the size of array. The second line contains N space-separated integers A_1, A_2, \dots, A_N denoting the elements of the array.

Output:

Print the maximum sum of the contiguous sub-array in a separate line for each test case.

a

-1	5	8	-9	4	1
----	---	---	----	---	---

Kadane's Algorithm

Show Topic Tags

Hike Flipkart FactSet D-E-Shaw Amazon Accolite
Morgan-Stanley Microsoft MetLife Housing.com
Snapdeal Samsung Payu Oracle Ola-Cabs
[24]7 Innovation Lab Zoho Walmart Visa Teradata

Given an array containing both negative and positive integers. Find the contiguous sub-array with maximum sum.

Input:

The first line of input contains an integer T denoting the number of test cases. The description of T test cases follows. The first line of each test case contains a single integer N denoting the size of array. The second line contains N space-separated integers A_1, A_2, \dots, A_N denoting the elements of the array.

Output:

Print the maximum sum of the contiguous sub-array in a separate line for each test case.

a

-1	5	8	-9	4	1
----	---	---	----	---	---

output: 13

Solution 1


```
max = 0;

for(i=0; i<n; i++)
{
    for(j=i; j<n; j++)
    {
        sum=0;
        for(k=i; k<=j; k++)
        {
            sum+=a[k];
        }
        if(sum > max) max=sum;
    }
}
```

Solution 1

```
max = 0;


for(i=0; i<n; i++)
{
    for(j=i; j<n; j++)
    {
        sum=0;
        for(k=i; k<=j; k++)
        {
            sum+=a[k];
        }
        if(sum > max) max=sum;
    }
}
```



Solution 1

```
max = 0;

for(i=0; i<n; i++)
{
    for(j=i; j<n; j++)
    {
        sum=0;
        for(k=i; k<=j; k++)
        {
            sum+=a[k];
        }
        if(sum > max) max=sum;
    }
}
```




Solution 1

```
max = 0;

for(i=0; i<n; i++)
{
    for(j=i; j<n; j++)
    {
        sum=0;
        for(k=i; k<=j; k++)
        {
            sum+=a[k];
        }
        if(sum > max) max=sum;
    }
}
```

$O(1)$ $O(n)$




Solution 1

```
max = 0;

for(i=0; i<n; i++)
{
    for(j=i; j<n; j++)
    {
        sum=0;
        for(k=i; k<=j; k++)
        {
            sum+=a[k];
        }
        if(sum > max) max=sum;
    }
}
```

$O(1)$ $O(n)$ $O(n^2)$



Solution 1

```
max = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
  for(j=i; j<n; j++)
```

```
  {
```

```
    sum=0;
```

```
    for(k=i; k<=j; k++)
```

```
    {
```


```
      sum+=a[k];
```

```
    }
```


```
    if(sum > max) max=sum;
```

```
  }
```

```
}
```



a



Solution 1

```
max = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
  for(j=i; j<n; j++)
```

```
  {
```

```
    sum=0;
```

```
    for(k=i; k<=j; k++)
```

```
    {
```

```
      sum+=a[k];
```

```
    }
```

```
    if(sum > max) max=sum;
```

```
  }
```

```
}
```



$O(1)$



$O(n)$



$O(n^2)$



$O(n^3)$

a

-1	5	8	-9	4	1
----	---	---	----	---	---

i


j

Complexity: $O(n^3)$:- (

Solution 2

```
max = 0;


for(i=0; i<n; i++)
{
    sum=0;
    for(j=i; j<n; j++)
    {
        sum+=a[j];
        if(sum > max)
            max=sum;
    }
}
```




Solution 2

```
max = 0;

for(i=0; i<n; i++)
{
    sum=0;
    for(j=i; j<n; j++)
    {
        sum+=a[j];
        if(sum > max)
            max=sum;
    }
}
```

 $O(1)$




Solution 2

```
max = 0;

for(i=0; i<n; i++)
{
    sum=0;
    for(j=i; j<n; j++)
    {
        sum+=a[j];
        if(sum > max)
            max=sum;
    }
}
```

$O(1)$ $O(n)$



Solution 2

```
max = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    sum=0;
```

```
    for(j=i; j<n; j++)
```

```
    {
```

```
        sum+=a[j];
```

```
        if(sum > max)
```

```
            max=sum;
```

```
    }
```

```
}
```

$O(1)$

$O(n)$

$O(n^2)$

a

-1	5	8	-9	4	1
----	---	---	----	---	---

i

j

Solution 2


```
max = 0;

for(i=0; i<n; i++)
{
    sum=0;
    for(j=i; j<n; j++)
    {
        sum+=a[j];
        if(sum > max)
            max=sum;
    }
}
```

$O(1)$

$O(n)$

$O(n^2)$



Complexity: $O(n^2)$:-|

Any better solution?

We can exploit two properties of the subarray with maximum sum

Any better solution?

We can exploit two properties of the subarray with maximum sum

- 1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.

Any better solution?

We can exploit two properties of the subarray with maximum sum

- 1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.

a

-1	5	8	-9	4	1
----	---	---	----	---	---

Any better solution?

We can exploit two properties of the subarray with maximum sum

- 1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.

a

-1	5	8	-9	4	1
----	---	---	----	---	---

Any better solution?

We can exploit two properties of the subarray with maximum sum

- 1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.

a

-1	5	8	-9	4	1
----	---	---	----	---	---

Any better solution?

We can exploit two properties of the subarray with maximum sum

- 1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.
- 2) The value that precede the first value of the **optimal sub-array** is negative. By contradiction, include this positive value to get sub-array with a larger sum.

a

-1	5	8	-9	4	1
----	---	---	----	---	---


Any better solution?

We can exploit two properties of the subarray with maximum sum

1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.



2) The value that precede the first value of the **optimal sub-array** is negative. By contradiction, include this positive value to get sub-array with a larger sum.




Any better solution?

We can exploit two properties of the subarray with maximum sum

1) Sum of values in any prefix of the **optimal sub-array** is positive. By contradiction, remove a negative prefix to get sub-array with a larger sum.



2) The value that precede the first value of the **optimal sub-array** is negative. By contradiction, include this positive value to get sub-array with a larger sum.



Solution 3

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```

Solution 3

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```


```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```



$O(1)$

Solution 3

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```



$O(1)$



$O(n)$

Solution 3

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```



$O(1)$



$O(n)$

Complexity: $O(n)$:-)

Solution 3

Sum

-1

-1	5	8	-9	4	1
----	---	---	----	---	---

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```

O(1)

O(n)

Complexity: O(n) :-)

Solution 3

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```

$O(1)$

$O(n)$

Sum

-1

-1	5	8	-9	4	1
----	---	---	----	---	---

5

-1	5	8	-9	4	1
----	---	---	----	---	---

Complexity: $O(n)$:-)

Solution 3

```
max = 0; sum = 0;

for(i=0; i<n; i++)
{
    if(sum > 0) sum+=a[i];
    else sum=a[i];

    if(sum > max) max=sum;
}
```

$O(1)$ $O(n)$

Sum

-1	-1	5	8	-9	4	1
5	-1	5	8	-9	4	1
13	-1	5	8	-9	4	1

Complexity: $O(n)$:-)

Solution 3

```
max = 0; sum = 0;

for(i=0; i<n; i++)
{
    if(sum > 0) sum+=a[i];
    else sum=a[i];

    if(sum > max) max=sum;
}
```

$O(1)$

$O(n)$

Sum

-1	-1	5	8	-9	4	1
5	-1	5	8	-9	4	1
13	-1	5	8	-9	4	1
4	-1	5	8	-9	4	1

Complexity: $O(n)$:-)

Solution 3

```
max = 0; sum = 0;

for(i=0; i<n; i++)
{
    if(sum > 0) sum+=a[i];
    else sum=a[i];

    if(sum > max) max=sum;
}
```

$O(1)$

$O(n)$

Sum

-1	-1	5	8	-9	4	1
5	-1	5	8	-9	4	1
13	-1	5	8	-9	4	1
4	-1	5	8	-9	4	1
8	-1	5	8	-9	4	1

Complexity: $O(n)$:-)

Solution 3

```
max = 0; sum = 0;
```

```
for(i=0; i<n; i++)
```

```
{
```

```
    if(sum > 0) sum+=a[i];
```

```
    else sum=a[i];
```

```
    if(sum > max) max=sum;
```

```
}
```

$O(1)$

$O(n)$

Sum

-1

-1	5	8	-9	4	1
----	---	---	----	---	---

5

-1	5	8	-9	4	1
----	---	---	----	---	---

13

-1	5	8	-9	4	1
----	---	---	----	---	---

4

-1	5	8	-9	4	1
----	---	---	----	---	---

8

-1	5	8	-9	4	1
----	---	---	----	---	---

9

-1	5	8	-9	4	1
----	---	---	----	---	---

Complexity: $O(n)$:-)

Missing number in array

Show Topic Tags

Payu

Ola-Cabs

Microsoft

Intuit

Cisco

Amazon

Given an array of size $n-1$ and given that there are numbers from 1 to n with one missing, the missing number is to be found.

Input:

The first line of input contains an integer T denoting the number of test cases.

The first line of each test case is N , size of array.

The second line of each test case contains $N-1$ input $C[i]$, numbers in array.

Output:

Print the missing number in array.

Goals and opportunities

The goal of the course is to improve programming and problem solving skills of the students by facing them with difficult problems and by presenting the techniques that help their reasoning in the implementation of correct and efficient solutions. The importance of these skills has been recognized by the most important software companies worldwide, which evaluate candidates in their job interviews mostly by the ability in addressing such difficult problems (e.g., see [here](#)).

A natural goal is to involve the students in the intellectual pleasure of programming and problem solving, also preparing them for the most important international online contests, such as [Topcoder](#), [Codeforces](#), [HackerRank](#), [CodeChef](#), [Facebook Hacker Cup](#), [Google Code Jam](#) and so on, for internships in most important companies and their interviews. A desirable side-effect of the course could be to organize and prepare teams of students for online contests.

The course will provide the opportunity of

- facing with challenging algorithmic problems;
- improving problem solving and programming skills;
- getting in touch with some big companies for internships, scholarships, or thesis proposals.

References

- Introduction to Algorithms, 3rd Edition, Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, Clifford Stein, The MIT Press, 2009 ([Amazon](#)) [CCLR]
- Algorithms, 4th Edition, Robert Sedgewick, Kevin Wayne, Addison-Wesley Professional, 2011 ([Amazon](#)) [RS]
- Algorithms, Sanjoy Dasgupta, Christos Papadimitriou, Umesh Vazirani, McGraw-Hill, 2006. ([Amazon](#)) [DPZ]
- Programming Challenges: The Programming Contest Training Manual, Steven S. Skiena, Miguel A. Revilla, Springer, 2003 ([Amazon](#)) [SR]
- Competitive Programming 3: The New Lower Bound of Programming Contests, Steven Halim, Felix Halim, ([here](#)) [HH]
- Competitive Programmer's Handbook, Antti Laaksonen ([here](#)) [L]
- The C++ Programming Language, 4th Edition, Bjarne Stroustrup, Addison-Wesley Professional, 2013 ([Amazon](#))
- The C++ Standard Library: A Tutorial and Reference (2nd Edition), Nicolai M. Josuttis, Addison-Wesley Professional, 2012 ([Amazon](#))

Useful links

- Erik D Demaine, Srinivas Devadas, Nancy Ann Lynch, "[MIT Design and Analysis of Algorithms](#)", MIT Algorithm course which includes video lectures
- Tim Roughgarden, "[Algorithm specialization](#)", Coursera
- [Visualgo](#): visualising data structures and algorithms through animation
- Geeks for Geeks: [Company interviews preparation](#)
- [Interviews common coding questions](#)
- How to: Work at Google — Example Coding/Engineering Interview [Video](#)
- [Google's Code Jam](#)
- [Topcoder](#)
- [Codeforces](#)
- [Geeks for Geeks](#)
- [CodeChef - Data Structures and Algorithms links](#)
- Geeks for Geeks: [Top 10 Algorithms and Data Structures for Competitive Programming](#)
- [List](#) of resources for competitive programming

Tentative Schedule

	Lecture	References	Problems
	Standard Template Library (STL)	Tutorial and STL algorithms	
	Searching and Sorting: Binary Search, QuickSort, and MergeSort	[CCLR] Chapters 2.3 and 7	Towers (solution) , Finding Team Member (solution) , and Megacity (solution)
	Coding: Searching and Sorting in C++ and Inversion count		Interesting drinks , Inversion Count (solution) , Find Pair (solution) , and Two Heaps (solution)
	Trees	[CCLR] Chapters 10.4 and 12. Tree traversal	Firing Employees , Check for BST , Preorder Traversal and BST , and Maximum path sum
	Prefix sum: Binary Indexed Tree (aka BIT or Fenwick tree)	Fenwick tree: description , tutorial , video , visualgo , and code . Range updates on Fenwick tree (Optional).	Ilya and Queries (solution) , Alice, Bob and Chocolate (solution) , Number of Ways (solution) , Little Girl and Maximum Sum (solution) , and Update the array (solution)
	Coding: applications of Fenwick tree		Pashmak and Parmida's problem (solution) and Nested Segments (solution)

Exam

Exam

- **Homeworks (0 — 15 points)**
 - You are expected to solve all the problems in the Web page
 - A solution consists in a description (in English) and tested implementation
 - For each solution you should provide **your own** description and implementation. You must be able to describe all its details.
 - **Note:** all the presented solutions (description + code) **MUST** specify inspiring references (if any)
 - Use a github repository (public or private) to collect your solutions
 - **Remember:** we are here to learn and improve our skills. Just a motivation for not cheating.

Exam

- **Homeworks (0 — 15 points)**

- You are expected to solve all the problems in the Web page
- A solution consists in a description (in English) and tested implementation
- For each solution you should provide **your own** description and implementation. You must be able to describe all its details.
- **Note:** all the presented solutions (description + code) **MUST** specify inspiring references (if any)
- Use a github repository (public or private) to collect your solutions
- **Remember:** we are here to learn and improve our skills. Just a motivation for not cheating.

- **Written/oral exam (0 — 15 points)**

- Well, you know, the professor asks, the student tries to answer...
 - Questions about the material of the course (easy part)
 - Solve some **new** problems. Impossible to do if you cheated on the homeworks. Just a more convincing motivation for not cheating :-).

Exam

- **Homeworks (0 — 15 points)**
 - You are expected to solve all the problems in the Web page
 - A solution consists in a description (in English) and tested implementation
 - For each solution you should provide **your own** description and implementation. You must be able to describe all its details.
 - **Note:** all the presented solutions (description + code) **MUST** specify inspiring references (if any)
 - Use a github repository (public or private) to collect your solutions
 - **Remember:** we are here to learn and improve our skills. Just a motivation for not cheating.
- **Written/oral exam (0 — 15 points)**
 - Well, you know, the professor asks, the student tries to answer...
 - Questions about the material of the course (easy part)
 - Solve some **new** problems. Impossible to do if you cheated on the homeworks. Just a more convincing motivation for not cheating :-).
- **Bonus points (0 — $+\infty$ points)**
 - Active participation to our Google group: 1 – 5 points for outstanding contributors
 - Well-prepared attempt to participate to online contests: +1 point for each high level contest
 - Successful interview with a big company: +3 points

Active participation!

- We have a Google group to discuss problems
 - Please, use your real name!
- Actively participate by
 - Presenting solutions to unsolved problems
 - Presenting alternative solutions to solved ones
 - Proposing new interesting problems
 - Presenting algorithmic techniques and data structures
 - Answering other students questions
 - Discussing online contests
 - **Note:** a proposed solution (description + code) MUST specify inspiring references (including other students), if any.
- Feel free to discuss any topic related to the content of the course

Trapping Rain Water

Show Topic Tags

Payu


Microsoft

D-E-Shaw

Amazon

Accolite

Given n non-negative integers in array representing an elevation map where the width of each bar is 1, compute how much water it is able to trap after raining.



Bars for input {3, 0, 0, 2, 0, 4}

Total trapped water = $3 + 3 + 1 + 3 = 10$