

Thinking and Designing Architecture



- » Skan.ai - chief Architect
- » Ai.robotics - chief Architect
- » Genpact - solution Architect
- » Welldoc - chief Architect
- » Microsoft
- » Mercedes
- » Siemens
- » Honeywell



Mubarak



- Arch Requirements (QAW)
  - Context, key fun, quality, constraints, assumption
- Arch Decisions
  - Logical, Deployment, Security, ...
- Arch Eval (ATAM, ARID, SAAM)
  - Justification

# Part I

## **Architecture nut and bolts**

What is a Architecture Blue print?

How is Architecture different from design ?

What is difference between Application Architecture and Enterprise Architecture ?


What is Role of a Application Architect ?

Application Architect vs Solution Architect

Application Architect vs Vertical Architect

# Architecture vs Design


Quality	Measure	Approach
• Performance (Resource)	• tps	
• Maintainability	• Response time	• Versioning
• Reliability (Trust)	• Latency	• Modularity
• Robustness (Rugud)	• % uptime	• Concurrency
• Scalability (volume)	• % downtime	• Caching
• Availability	• No of clicks	• Lazy loading
• Security (Trust)	• Probability	• ACID
• Usability	•	•




# Engineering vs Tuning



Attribute	Measure	Approach
• Performance <—		• Caching
• Maintainability <—	• Response time	• Parallel
• Security (Trust) <—	• Memory	• Pooling
• Scalability (Volume - I/O, CPU, Memory) <—	• CPU	• Lazy Loading
• Usability x	• I/O	• Compression
• Availability <—	• Latency	• Chunking
• Reliability (Trust) <—	• TPS	• Reusability/ Extensible
• Robustness (Rugud)	• ...	• Modular /Component
•		• Low Coupling
		• EDA
		• ACID - transaction
		• Input Validation






**Pre**

# **Engineering vs Tuning**

**Post**



**Architecture Design**

**UI Design**

**Test Design**

**Module Design**

**Class Design**

**Code Design**

# **Architecture vs Design**

**System quality**

**Code Maintainability**

**Detail Design**

**Module Design**

**Class Design**


**Low Level Design**

**Code design**


**Implementation Design**


# Types of Architect

## Architect Roles










	Business	Enterprise	Solution	Application
<b>Soft Skills</b>				
Communicates well with key stakeholders (C-level officers)	#	*	#	#
Communicates well with stakeholders (Director / Manager level)	*	*	*	#
Public Speaking	~	*	~	#
Writing Skills	*	*	~	#
<b>Hard Skills</b>				
Business Process Engineering	*	*	~	#
Programming	#	#	*	*
Requirements Analysis	*	~	~	#
Software Design	#	~	*	*
Scope	Process	Organization	Single Solution	Single Project

# Solution Architect



# Part II

## **Collect Architectural Requirements**

Understanding Quality of Service -

What is Quality Model

Quality Attribute scenarios

Quality Attribute Workshop (QAW)

Identification of architectural drivers

Implicit and explicit characteristics


Gathering Performance scenarios


Gathering Maintainability scenarios

Lab : Architecture driven requirements engineering using QAW

**Arch Req**

# 1. Context view







Business customer











## 2. Functional view







Admin



Auditor




**Start Audit**



**View Audit**

# 3. Quality View



# Usability  
# Portability  
# Interoperability

# Quality Model

- IEEE
- ISO
- MacCal
- Bohem
- ..

As a user I want to **add a todo** In the app

As a user I want to **add a todo** In the app . The todo is added In **< 3 secs**

**SEI - Software Engineering Institute**



## Quality Attribute Scenarios

Quality	Source (who)	Stimulus (action)	Artifact (which)	Environment (context)	Response (output)	Measure (scale)
Performance	As a user	I want to add a todo	In the portal	During peak load.	The todo is added	In < 3 secs
Reliability	As a user	I want to add a todo	From the portal	Duplicate request	Duplicate entry is detected	In 100% of cases
Maintainability	Developer	Change the Configuration engine	In the Frame work	During maintenance	The configuration mechanism is replaced	In < 1 week
Security	unknown identity	requests to add a new todo	In the portal	During Normal load.	block access to the data and record the access attempts	100% probability of detecting the attack, 100% probability of denying access
Availability	The processor	Failed	In the db server	During Operational Hours	Secondary is made Primary	In < 5 minutes

**BA, product owners, ...**  
**Dev, QA, Ops**

**Seed scenarios**  
**List of scenarios (Today | growth | exploratory)**

Source: Processor

Stimulus: Stop working during Peak Hours

Artifact: in the central system

environment: during Peak Hours (8 am - 12 pm)

Response : Notification to operator, system Administrator

....

Measure: not more than 5 minutes to get a new processor running

A processor stops working during Peak Hours in the central system

during Peak Hours, Notification to operator, system Administrator

..... Should ... not more than 5 minutes to get a new processor running

# Performance

Scenario Portion	Possible Values
Source	Internal to the system, External to the system
Stimulus	Periodic events, sporadic events, Bursty events, stochastic events
Artifact	System, component
Environment	Normal mode; overload mode, Reduced capacity mode, Emergency mode, Peak mode
Response	Process stimuli; change level of service
RespMeasure	Latency, deadline, throughput, jitter, miss rate, data loss

1. What is the expected response time for each use case?
2. What is the average/max/min expected response time?
3. What resources are being used (CPU, LAN, etc.)?
4. What is the resource consumption?
5. What is the resource arbitration policy?
6. What is the expected number of concurrent sessions?
7. Are there any particularly long computations that occur when a certain state is true?
8. Are server processes single or multithreaded?
9. Is there sufficient network bandwidth to all nodes on the network?
10. Are there multiple threads or processes accessing a shared resource? How is access managed?
11. Will bad performance dramatically affect usability?
12. Is the response time synchronous or asynchronous?
13. What is the expected batch cycle time?
14. How much can performance vary based on the time of day, week, month, or system load?
15. What is the expected growth of system load?
16. Increased network bandwidth consumption?
17. Increased database server processing, resulting in reduced throughput.
18. Increased memory consumption, excessive cache misses
19. Increased client response time, reduced throughput, and server resource over utilization.

# Modifiability

Portion of Scenario	Possible Values
Source	End user, developer, system administrator
Stimulus	Wishes to add/delete/modify/vary functionality, quality attribute, capacity or technology
Artifact	Code, Data, Components, Configurations, Interfaces, Resources
Environment	At runtime, compile time, build time, design time
Response	Locates places in architecture to be modified; makes modification without affecting other functionality; tests modification; deploys modification
Response Measure	Cost in effort, Cost in money, Cost in time, Cost in number, size, complexity of affected artifacts, Extent affects other system functions or qualities, New defects introduce

1. Is this system the start of a new product line?
2. Will other systems be built that more or less match the characteristics of the system under construction? If so, what components will be reused in those systems?
3. What Changes could impact components, services, features, and interfaces when adding or changing the functionality, fixing errors, and meeting new business requirements ?
4. Does business rule values change frequently ?
5. Does Business process change frequently ?
6. What existing components are available for reuse?
7. Are there existing frameworks or other code assets that can be reused?
8. Will other applications reuse the technical infrastructure that is created for this application?
9. What are the associated costs, risks, and benefits of building reusable components?
- 10.Excessive dependencies between components and layers
- 11.The use of direct communication prevents changes to the physical deployment of components and layers.
- 12.Reliance on custom implementations of features such as authentication and authorization prevents reuse.
- 13.The logic code of components and segments is not cohesive.
- 14.The code base is large, unmanageable, fragile, or over complex.
- 15.The existing code does not have an automated regression test suite.
- 16.Lack of documentation may hinder usage, management, and future upgrades.

# Testability

Scenario Portion	Possible Values
Source	Unit tester, Integration tester, System tester, Acceptance tester, End user, Automated testing tools
Stimulus	Analysis, architecture, design, class, subsystem integration, system delivered
Artifact	Portion of the system being tested( Piece of design, piece of code, complete system)
Environment	Design time, Development time, Compile time, Integration time, Deployment time, Run time
Response	Execute test suite & capture results, Capture cause of fault, Control & monitor state of the system
RespMeasure	Effort to find fault, Effort to achieve coverage %,Probability of fault being revealed by next test, Time to perform tests, Effort to detect faults, Length of longest dependency chain, Time to prepare test environment, Reduction in risk exposure



1. Are there tools, processes, and techniques in place to test language classes, components, and services?
2. Are there hooks in the frameworks to perform unit tests?
3. Can automated testing tools be used to test the system?
4. Can the system run in a debugger?
5. Complex applications with many processing permutations are not tested consistently, perhaps because automated or granular testing cannot be performed if the application has a monolithic design.
6. Lack of test planning.
7. Poor test coverage, for both manual and automated tests.
8. Input and output inconsistencies; for the same input, the output is not the same and the output does not fully cover the output domain even when all known variations of input are provided.

# 4. Constraints view

It should work on IE 11, Chrome and Firefox

---

Should work on windows, unix, Mac platforms

---

Should deploy on Azure Cloud

---

---

# 5. Assumptions View

1	Will use open source Technologies only
2	
3	

# Part III

Building Architecture

Understanding Types of Applications

- # Client, Native, Web, background

- # Server, API, Backend

- # Brokered

Decomposing system into Applications

- # layered, Hexagonal

- # pipes and filters

- # Micro kernel

- # Component based

- # Micro service


- # Event driven Architecture

- # MVC, MVP, MVVM


# Arch Design

**Decisions**

# Logical View



# Step 1. Decompose the system into Applications/Tiers




ToDo Portal  
(Single Page Application)

ToDo API Service  
(Api Application)




ToDo Job Service  
(Background Application)








# Choose System Decomposition Patterns




Actor \*








**Layered Architecture**



**Pipes and Filters**



# Microkernel Architecture



Core

Layer

Layer

Filter

Filter


Filter

Layer


Plugins

Plugins


Plugins








**MVC**



**MVP**




**MVVM**

1

Ship one binary

Application  
Exe




**Compile time  
monolithic**

2

Ship one binary

Application  
Exe




**Link time  
monolithic**

3

Ship multiple binary

Process




**Runtime  
monolithic**

In process  
comp

Ship multiple binary & host in multiple process


4

Process



Distributed  
comp

Process




Distributed  
comp

**Distributed Application**


5

Process



Application1


Process




Application2

**Micro Application**

# Service Oriented Architecture






Eclipse IDE. Downloading the basic Eclipse product provides you little more than a fancy editor. However, once you start adding plug-ins, it becomes a highly customizable and useful product.

An application is required to perform a variety of tasks of varying complexity on the information that it processes. The processing tasks performed by each module, or the deployment requirements for each task, could change as business requirements are updated. Also, additional processing might be required in the future, or the order in which the tasks performed by the processing could change. A solution is required that addresses these issues, and increases the possibilities for code reuse.

A workflow implementation. The implementation of a workflow contains concepts like the order of the different steps, evaluating the results of steps, deciding what the next step is, etc.



A task scheduler. A scheduler contains all the logic for scheduling and triggering tasks



Internet browsers plug-ins add additional capabilities that are not otherwise found in the basic browser

Networking engineering is a complicated task, which involves software, firmware, chip level engineering, hardware, and electric pulses. To ease network engineering, the whole networking concept is decomposed into more manageable parts.

# Break an app into smaller manageable piece

	2 Modules	2 Applications	W	Score
Share Database / Storage	Yes	No	2	
Share Infra (Hosting)	Yes	No	3	
Share Sorce Control	Yes	No	2	
Share CI/CD (Build Server)	Yes or No	No	3	
Share functional logic (same feature)		No		
Fun Requirements	Shared	Its own	1	
SCRUM Team / Sprint	Shared	Its own	1	
Test Cases	Shared	Its own	1	
Architecture	Shared	Its own	1	
Technology Stack / Fwks	Shared	Its own	1	

```
graph TD; Application[Application] --- Modules1[Modules]; Application --- Modules2[Modules]; Application --- Modules3[Modules];
```


Application

Modules

Modules

Modules

**3 or 4**



**App**

Inventory code

**Binary**

Accounting Code

**Binary**

**App**





Inventory code

**Binary**


**App**

Accounting Code


**Binary**



# Inventory Application







VM



Inventory App

Accounting App

```
graph TD; A[APP] --- B[APP]; A --- C[APP]; A --- D[APP]; A --- E[APP];
```

APP

APP


APP

APP

APP


# Types of Microservice

1  
Web Server




Angular (SPA)

2  
Web Server





JSP, Servlet, JSF (Server pages)


3  
Desktop



Swing, Android, iOS (Native)






	Pros/ Cons	Solution
Development time		
Micro-service practices Learning Curve		
Resource Performance (CPU, Memory, I/O)		
Db Transaction Management		
Views / Report / Dash board/ join		
Infra Cost		
First time Deployment effort		
Debugging, Error Handling (End to End)		
Integration Test		
Log Mgmt (debug/ error )		
Config Mgmt		
Authentication (who)		
Authorization (what can they do)		
Audit Log mgmt (who accessed what)		
Monitoring / Alerting		
Data Security and Privacy (transit, storage)		
Build Pipeline (CI)		
Agile Architecture (Agility to change)		
Feature Shipping (Agility to ship)/ CD		
Scalability (volume - request, data,		
Availability		
Ability to do Polygot		




# Inventory Application



Decentralize Domain  
Centralize Tech


# Pyramid test




# Unit Test

- Documentation for Code
- Design Code
- Regression
- Find Bugs

Its working don't touch it






Manual Test - 2%


UI Automation Test - 3 %

API Test - 10%

Integration Test - 15 %


Unit Test - 70%





**Runtime  
monolithic**

In process  
comp




**Micro Application**

# 1. Performance

Operation	Cpu Cycles
• 10 + 12	3
• Calling a in-memory Method	10
• Create Thread	2,00,000
• Destroy Thread	1,00,000
• Database Call	40,00,000
• Distributed Fun Call	20,00,000
Write to disk	10,00,000




Process




10 cpu cycles

Process




10,00,000 cpu cycles


Process













## 2. Db transaction




## 2. Db transaction








## 2. Db transaction




## 2. Db transaction

2 phase commit  
JTX , MSDTC, ...




### 3. Db query






# 3. Query




## 4. Development time




# 5. Learning Curve



## 6. Infra Cost



# 7. Debugging



Dev & Ops Teams



Log Data

Web Logs  
App Logs  
Database Logs  
Container Logs

Metrics Data


Container Metrics  
Host Metrics  
Database Metics  
Network Metrics  
Storage Metrics

APM Data

Real User Monitoring  
Txn Perf Monitoring  
Distributed Tracing

Uptime Data

Uptime  
Response Time



# Part IV

Addressing Performance Scenarios

- # Performance Engineering

- # CPU Performance patterns

- # I/O Performance patterns

- # Memory performance patterns

- # Performance anti patterns

Lab : Building Architecture for a Desktop Application



# Performance View

# Engineering for Performance

## Performance Objectives

(Response Time, Throughput, Resource Utilization, Workload)

## Performance Modeling

(Scenarios, Objectives, Workloads, Requirements, Budgets, Metrics)

## Architecture and Design Guidelines

(Principles, Practices and Patterns)

## Performance and Scalability Frame

Coupling and Cohesion  
Communication  
Concurrency

Resource Management  
Caching, State Management  
Data Structures / Algorithms

## Measuring, Testing, Tuning

### Measuring

Response Time  
Throughput  
Resource Utilization  
Workload

### Testing

Load Testing  
Stress Testing  
Capacity Testing

### Tuning

Network  
System  
Platform  
Application


## Roles

(Architects, Developers, Testers, Administrators)

## Life Cycle






(Requirements, Design, Develop, Test, Deploy, Maintain)

# Performance Modeling



# Allocate Budget


Know the cost of your materials.





For the ones that look risky, conduct some experiments (prototypes)

if you do not know how much time to assign, simply divide the total time equally between the steps.


Spread your budget across your processing steps








# Synchronization







# Part V

Addressing Cross cutting concerns -

- # logging

- # exception handling

Addressing Operational concerns -


- # Health monitoring Patterns

- # Alerts

# 3. Cross cutting concerns



The **crosscutting concern** is a concern which is needed in almost every module of an application.



## **Evaluate Architecture**

Architecture Trade of Analysis Method (ATAM)

Scenario generation using Utility Tree

Mapping Quality attributes with Architectural Decisions

Documenting Risks, Non Risks and sensitivity points

Lab : Evaluate Architecture using ATAM

# **Part 3**

# **Arch Risks**

	Risk	I	L	R	C	Notes
1	Performance of the View Todo is significantly impacted by large data volumes.	8	4	32	High	Testing to be undertaken to gauge impact.
2	Limitations of JPA API result in complex workarounds in repository implementation or workarounds in other architectural layers.	6	4	24	Medium	Can fall back to Hibernate which provides richer ORM functionality.
3	The Open Source tools and components selected lack the capabilities of equivalent commercial products limiting the features that can be implemented (e.g. GIS components).	6	3	18	High	Investigate alternative products.

- Risk - The description of the architectural risk.
- Impact to Project - The impact the risk will have on the project
  - (1 = Minor impact, 10 = Showstopper)
- Likelihood - The likelihood of the risk eventuating (1 = Low, 953 = Highly likely)
- Rating - The overall rating for the risk based on Impact \* Likelihood (1 = Minor, 90 = Critical)
- Confidence - The confidence in resolving the issue should it eventuate (Low, Medium, High)

- ATAM
- ARID
- SAAM
-



# Evaluate Architecture (ATAM)

**# identify all Architectural approaches  
(design)**

**# A1 (CQRS)**

**# A2(Cube)**

**# A3 (Caching)**

**...**

**# identify all quality requirements  
(requirements)**

**# s1 (< 5 sec)**

**# s2 (99.99%)**

**# s3 (...)**

**# ...**

**# analyse Scenario -> Approach**

**S1 -> A1, A2**

**S2 -> A6,A8, A9**

**S3-> ?**

**S4 -> A6, ?**

**=> Risk & trade off's**

**# brainstorm for scenarios**

**# s8**

**# s9**

**# s10**

**# ...**

**# analyse Scenario -> Approach**

**S8 -> A1, A2**

**S9 -> A6,A8, A9**

**S10-> ?**

**=> Risk & trade off's**

