PYRO-SAFE® Flammotect - single layer

Fire resistance max. El 90 acc. EN 13501-2

Mixed penetration sealing system made of mineral-fibre board (1 x 60 mm) and ablative coating



System Data

Certificate of usability		ETA-14/0418	
Thickness structural element	Wall	≥ 100 ≥ 125	
	Floor		
Sealing thickness	Wall	≥ 60	
	Floor	≥ 60	
Maxiumum Sealing size	Wall	1175 x 1200	
	Floor	1200 x 2400 oder 800 x ∞	

Dimensions in mm



General Information

Field of application

· Plasterboard wall, solid wall, floor

Allowed services

Services			Maximum diameter
	Cables		≤ 80
	Cable bundles		≤ 100 / ≤ 21
E E E E MAN	Cable trays		without restrictions
	EIC	single	≤ 32 / ≤ 21
	EIC	bundled	≤ 100 / ≤ 32 / ≤ 21
Time to the second	PE-lines "speed pipes"		$24x \le 7.0$ $7x \le 10.0$ $5x \le 12.0$
	Combustible pipes		≤ 110
	Multilay	erpipes	≤ 63
		nbustible pipes with on made of mineral fibre	≤ 219,1 (steel) ≤ 88,9 (copper)
		nbustible pipes with on made of FEF	≤ 170 (steel) ≤ 108 (copper)
le l	HVAC s	plit-line-combinations	Dimensions in mn

Dimensions in mm

PYRO-SAFE® Flammotect - single layer

Fire resistance max. El 90 acc. EN 13501-2

Products

PYRO-SAFE® FLAMMOTECT-A

Fire protection coating

Coating

12,5 kg pail – Item No. 01155101 15 kg pail – Item No. 01155105

Solid emulsion

12,5 kg pail – Item No. 01155106

15 kg pail – Item No. 01155107

Filler

12,5 kg pail – Item No. 01155104

15 kg pail - Item No. 01155109

Mineral fibre board - both sides pre-coated with PYRO-SAFE® FLAMMOTECT-A

1000 x 600 x 60 mm - Item No. 011812160

PYRO-SAFE® DG-CR 1.5

Fire protection wrap

Roll: length 10 m / width 125 mm - Item No. 01261125

PYRO-SAFE® DG-CR BS

Fire protection wrap

Roll: length 10 m / width 100 mm – Item No. 01264100

Lamella mat "Klimarock"

3,05 m² per roll – Item No. 01187100

Loose mineral wool

10 kg bag – Item No. 01183000

Label
1 piece – Item No. 01229000

