DECLARATION OF PERFORMANCE NO. 15122015 VARIANT N-B



Product FLAMRO Variant N-B

1. Unique identification code of the product-type RA-15-0677

2. Intended use Pipe sealing

3. Manufacturer FLAMRO Brandschutz-Systeme GmbH

56291 Leiningen

Germany

4. Authorised representative **not relevant**

5. System(s) of AVCP System 1

6a) Harmonised standard **not relevant**

6b) European Assessment Document ETAG Nº 026 Part 2, August 2011

European Technical Assessment ETA-15/0677

Technical Assessment Body ETA-Danmark A/S, DK-2150 Nordhavn

Notified body/ ies Materialprüfanstalt für das Bauwesen Braunschweig,

Nº 0761

7. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Fire resistance as a pipe sealing for combustible pipes on flexible and rigid walls (thickness ≥ 100 mm) or rigid floors (thickness ≥ 150 mm) constructions by means of the fire protection collar type FLAMRO Variant N-B with a max. dimension of 160 mm. *)	Max. El 240 - U/C	ETA-15/0677
Durability and serviceability	use category type Y ₁	
Air permeability	NPD	
Water permeability	NPD	

DECLARATION OF PERFORMANCE NO. 15122015 VARIANT N-B



Release of dangerous substances	none	
Mechanical resistance and stability	NPD	
Resistance to impact/ movement	NPD	
Adhesion	NPD	
Airborne sound insulation	NPD	
Thermal properties	NPD	
Water vapour permeability	NPD	
Components – reaction to fire: Variant N-B (steel housing) ROKU®Strip EM	Class acc. to EN 13501-1 A1 E	

^{*)} according to ETA-15/0677

 Appropriate Technical Documentation / Specific Technical Documentation:

not relevant

Online-copy of Declaration of Performance

www.flamro.de

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Hemp, Head of R & D / Authorised officer

FLAMRO Brandschutz-Systeme GmbH

Olin r. Well