PYRO-SAFE® ES

Fire resistance max. EI 90 acc. EN 13501-2

Easy-to-build penetration sealing system made of mineral wool and ablative filler

General Information

Field of application

- Plasterboard wall, solid wall, floor

Allowed services

Services		Maximum diameter
Cables		≤ 21
Cable bundles		≤ 100 / ≤ 21
EIC	single	≤ 32 / ≤ 21
EIC	bundled	≤ 100 / ≤ 32 / ≤ 21
Combustible pipes		≤ 32
HVAC split-line-combinations		✓

Dimensions in mm

System Data

Certificate of usability		ETA-14/0418
Thickness structural element	Wall	≥ 100
	Floor	≥ 125
Sealing thickness	Wall	≥ 100
	Floor	≥ 125
Maxiumum Sealing size	Wall	350 x 150 (square) or Ø 150 (round)
	Floor	350 x 150 (square) or Ø 160 (round)

Dimensions in mm

Products

PYRO-SAFE® FLAMMOTECT-A
Fire protection coating
Coating
12,5 kg pail – Item No. 01155101
15 kg pail – Item No. 01155105
Solid emulsion
12,5 kg pail – Item No. 01155106
15 kg pail – Item No. 01155107
Filler
12,5 kg pail – Item No. 01155104
15 kg pail – Item No. 01155109

Loose mineral wool
10 kg bag – Item No. 01183000

PYRO-SAFE® DG-CR 1.5
Fire protection wrap
Roll: length 10 m / width 125 mm – Item No. 01261125

Label
1 piece – Item No. 01229000