PYRO-SAFE® Flammotect - double layer

Fire resistance max. El 120 acc. EN 13501-2

Mixed penetration sealing system made of mineral-fibre boards (2 x 60 mm) and ablative coating



System Data

Certificate of usability		ETA-14/0418
Thickness structural element	Wall	≥ 100 ≥ 150
	Floor	
Sealing thickness	Wall	≥ 120
	Floor	≥ 150
Maxiumum Sealing size	Wall	1400 x 2000
	Floor	1400 x 2000

Dimensions in mm



General Information

Field of application

· Plasterboard wall, solid wall, floor

Allowed services

Services			Maximum diameter
· ·	Cables		≤ 80
	Cable bundles		≤ 100 / ≤ 21
= = = A40	Cable trays		without restrictions
	EIC	single	≤ 32 / ≤ 21
	EIC	bundled	≤ 100 / ≤ 32 / ≤ 21
	PE-lines "speed pipes"		$24x \le 7.0$ $7x \le 10.0$ $5x \le 12.0$
	Combu	stible pipes	≤ 160
	Multilay	erpipes	≤ 63
		nbustible pipes with on made of mineral fibre	≤ 323,9 (steel) ≤ 108 (copper)
		nbustible pipes with on made of FEF	≤ 170 (steel) ≤ 108 (copper)
5	HVAC s	plit-line-combinations	√

Dimensions in mm

PYRO-SAFE® Flammotect - double layer

Fire resistance max. El 120 acc. EN 13501-2

Products

PYRO-SAFE® FLAMMOTECT-A

Fire protection coating

Coating

12,5 kg pail – Item No. 01155101 15 kg pail – Item No. 01155105

Solid emulsion

12,5 kg pail – Item No. 01155106 15 kg pail – Item No. 01155107

Filler

12,5 kg pail – Item No. 01155104 15 kg pail – Item No. 01155109

Mineral fibre board - one side pre-coated with PYRO-SAFE® FLAMMOTECT-A

1000 x 600 x 60 mm - Item No. 01181160

PYRO-SAFE® DG-CR 1.5

Fire protection wrap

Roll: length 10 m / width 125 mm – Item No. 01261125

PYRO-SAFE® DG-CR BS

Fire protection wrap

Roll: length 10 m / width 100 mm – Item No. 01264100

Lamella mat "Klimarock"
3,05 m² per roll – Item No. 01187100

Loose mineral wool 10 kg bag – Item No. 01183000

Label 1 piece – Item No. 01229000

