



## Table of Contents

- Practical: The Community Analysis Pipeline (CAP)
  - Begin by Activating CAP
    - [(Return to Top)](#return-to-toptable-of-contents)
  - 1. Retrieving Data
    - 1.1 Download MGCM Output with MarsPull.py
      - Skip this if you have done it already!
      - If you have any **fort.11** files **other than the ones listed above** in **either** directory, **delete** them.
      - [(Return to Top)](#return-to-toptable-of-contents)
  - 2. File Manipulations
    - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.1 Convert the **fort.11** files into **netCDF** files
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.2 Interpolate **atmos\_average** to standard pressure coordinates
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.3 Add mass stream function (**msf**) to the pressure-interpolated file
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.4 Add density (**rho**) and mid-point altitude (**zfull**) to **atmos\_average**
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.5 Interpolate **atmos\_average** to standard altitude
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.6 Time-shift and pressure-interpolate the **diurn** file
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.7 Apply a low-pass filter (**-lpf**) to the surface pressure (**ps**) and temperature (**ts**) in the **daily** file
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.8 Estimate the magnitude of the wind shear using CAP
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.9 Calculate the column-integrated dust, water ice, and water vapor mixing ratios in the **daily** file
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.10 Display the values of **pfull**, then display the minimum, mean, and maximum near-surface temperatures **temp** over the globe
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 2.1b (for /ACTIVECLDS) Convert **fort.11** files into **netCDF** files
    - 2.2b (for /ACTIVECLDS) Interpolate **atmos\_average** to standard pressure
    - 2.5b (for /ACTIVECLDS) Interpolate **atmos\_average** to standard altitude
      - [(Return to Top)](#return-to-toptable-of-contents)
- Optional: Download the Answer Key for Step 2 \* [(Return to Top)](#return-to-toptable-of-contents)

- Break! \* [(Return to Top)](#return-to-toptable-of-contents)
  - 3. Plotting Routines
    - [(Return to Top)](#return-to-toptable-of-contents)
    - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.1 Create a global map of surface albedo (alb) with topography (zsurf) contoured on top
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.2 Plot the zonal mean zonal wind cross-section at Ls=270° using altitude as the vertical coordinate
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.3 Add the same plot for the RAC case to the same page
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.4 Overplot temperature in solid contours
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.5 Plot the surface CO2 ice content in g/m2 and compute and plot surface wind speed from the U and V winds
    - 3.6 Make the following changes to the plots you created in 3.5
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.7 Create the following zonal mean time X lat plots on a new page
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.8 Plot the following two cross-sections (lat X lev) on the same page
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.9 Plot zonal mean temperature from the RIC and RAC cases
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.10 Generate two 1D temperature profiles (temp) from the RIC case
      - **NOTE:** You do not use HOLD ON and HOLD OFF to overplot 1D plots. HOLD is always for drawing separate plots on the same page
      - [(Return to Top)](#return-to-toptable-of-contents)
    - 3.11 Plot the 1D filtered and unfiltered surface pressure over a 20-sol period
      - [(Return to Top)](#return-to-toptable-of-contents)
  - That's a Wrap!
    - [(Return to Top)](#return-to-toptable-of-contents)

---

## Practical: The Community Analysis Pipeline (CAP)

---

**Recap:** CAP is a Python toolkit designed to simplify post-processing and plotting MGCM output. CAP consists of five Python executables:

1. MarsPull.py for accessing MGCM output
2. MarsFiles.py for reducing the files
3. MarsVars.py for performing variable operations
4. MarsInterp.py for interpolating the vertical grid
5. MarsPlot.py for visualizing the MGCM output

It is useful to divide these functions into three categories and explore them in order:

1. [Retrieving Data](#) -> [MarsPull.py](#)
2. [File Manipulations](#) -> [MarsFiles.py](#), [MarsVars.py](#), & [MarsInterp.py](#)
3. [Plotting Routines](#) -> [MarsPlot.py](#)

You already have experience using [MarsPull.py](#) for retrieving data, which was covered at the end of [CAP\\_Install.md](#). We will build on that knowledge in this tutorial. You may revisit the installation instructions at any time during the tutorial.

## Begin by Activating CAP

As always with CAP, you must activate the [amesCAP](#) virtual environment to access the Python executables:

```
(local)>$ source ~/amesCAP/bin/activate      # bash
(local)>$ source ~/amesCAP/bin/activate.csh   # csh/tcsh
# ..... OR .....
(local)>$ source ~/amesCAP/Scripts/activate  # Windows
```

Your prompt should change to confirm you're in the virtual environment. Before continuing, make sure you're using the most up-to-date version of CAP by running:

```
(AmesCAP)>$ pip install git+https://github.com/NASA-Planetary-Science/AmesCAP.git --upgrade
```

Then, confirm that CAP's executables are accessible by typing:

```
(AmesCAP)>$ MarsPull.py -h
```

This is the `--help` argument, which shows the documentation for any of the [Mars\\*.py](#) executables.

Let's begin with a review of the data retrieval process you performed when installing CAP ([CAP\\_Install.md](#)).

[\(Return to Top\)](#)

---

## 1. Retrieving Data

### 1.1 Download MGCM Output with [MarsPull.py](#)

**Skip this if you have done it already**

[MarsPull](#) is used to access and download MGCM output files from the [MCMC Data portal](#). During the installation, you were asked to:

1. Create a directory called `/CAP_tutorial`
2. Create two subdirectories: `/INERTCLDS` and `/ACTIVECLDS`

3. Use **MarsPull** to download several **fort.11** files into each.

In each subdirectory, **MarsPull** was used to retrieve files from the corresponding simulation on the data portal:

```
(AmesCAP)>$ MarsPull.py -id INERTCLDS -ls 255 285    # in the /INERTCLDS
directory
# and
(AmesCAP)>$ MarsPull.py -id ACTIVECLDS -ls 255 285  # in the /ACTIVECLDS
directory
```

You should have the following 5 **fort.11** files in each directory:

```
(AmesCAP)>$ ls CAP_tutorial/INERTCLDS
> fort.11_0719 fort.11_0720 fort.11_0721 fort.11_0722 fort.11_0723
(AmesCAP)>$ ls CAP_tutorial/ACTIVECLDS
> fort.11_0719 fort.11_0720 fort.11_0721 fort.11_0722 fort.11_0723
```

If you have any **fort.11** files other than the ones listed above in either directory, delete them

[\(Return to Top\)](#)

---

## 2. File Manipulations

We've retrieved the **fort.11** files from the data portal and we can now begin processing the data.

CAP's post-processing capabilities include interpolating and regridding data to different vertical coordinate systems, adding derived variables to the files, and converting between filetypes, just to name a few examples.

The following exercises are designed to demonstrate how CAP can be used for post-processing MGCM output. Please follow along with the demonstration. **We will use the files created here to make plots with **MarsPlot** later, so do not delete anything!**

Begin in the **/INERTCLDS** directory and complete exercises 2.1-2.10:

```
(AmesCAP)>$ cd ~/CAP_tutorial/INERTCLDS
```

[\(Return to Top\)](#)

---

### 2.1 Convert the **fort.11** files into **netCDF** files

In the **/INERTCLDS** directory, type:

```
(AmesCAP)>$ MarsFiles.py fort.11_* -fv3 fixed average daily diurn
```

Several **netCDF** files were created from the **fort.11** files:

```
(AmesCAP)>$ ls
> 07180.atmos_average.nc 07190.atmos_average.nc 07200.atmos_average.nc
07210.atmos_average.nc 07220.atmos_average.nc
> 07180.atmos_daily.nc 07190.atmos_daily.nc 07200.atmos_daily.nc
07210.atmos_daily.nc 07220.atmos_daily.nc
> 07180.atmos_diurn.nc 07190.atmos_diurn.nc 07200.atmos_diurn.nc
07210.atmos_diurn.nc 07220.atmos_diurn.nc
> 07180.fixed.nc 07190.fixed.nc 07200.fixed.nc
07210.fixed.nc 07220.fixed.nc
```

Remember, the **netCDF** filetypes are:

Type	Description
*atmos_fixed.nc	static variables that <b>do not change over time</b>
*atmos_average.nc	<b>5-day averages</b> of MGCM output
*atmos_diurn.nc	files contain <b>hourly</b> MGCM output averaged over 5 days
*atmos_daily.nc	<b>continuous time series</b> of the MGCM output

**NOTE:** the 5-digit sol number at the beginning of each **netCDF** file indicates when the file's records begin. These files are pulled from a simulation that was warm-started from a 10 year run. **10 years x ~668 sols/year = 6680 sols**. The earliest date on these files is 07180 (the middle of the year).

For easier post-processing and plotting, concatenate like-filetypes along the **time** axis:

```
(AmesCAP)>$ MarsFiles.py *fixed.nc -c
(AmesCAP)>$ MarsFiles.py *average.nc -c
(AmesCAP)>$ MarsFiles.py *diurn.nc -c
(AmesCAP)>$ MarsFiles.py *daily.nc -c
```

Our directory now contains **four** **netCDF** files in addition to the **fort.11** files:

```
(AmesCAP)>$ ls
> 07180.atmos_fixed.nc fort.11_0719 fort.11_0723
> 07180.atmos_average.nc fort.11_0720
> 07180.atmos_diurn.nc fort.11_0721
> 07180.atmos_daily.nc fort.11_0722
```

[\(Return to Top\)](#)

---

## 2.2 Interpolate `atmos_average` to standard pressure coordinates

This step uses `MarsInterp`, and the documentation can be viewed using the `--help` argument:

```
(AmesCAP)>$ MarsInterp.py -h
```

Use the `--type (-t)` argument to interpolate the file to standard pressure coordinates (`pstd`):

```
(AmesCAP)>$ MarsInterp.py 07180.atmos_average.nc -t pstd
```

A new pressure-interpolated file called `07180.atmos_average_pstd.nc` was created and the original file was preserved.

[\(Return to Top\)](#)

---

## 2.3 Add mass stream function (`msf`) to the pressure-interpolated file

This step uses `MarsVars`, and the documentation can be viewed using the `--help` argument:

```
(AmesCAP)>$ MarsVars.py -h
```

Adding or removing variables from files is done using the `-add` and `-rem` arguments in the call to `MarsVars`. `msf` is a variable derived from the meridional wind (`vcomp`), so we must first confirm that `vcomp` is indeed a variable in `07180.atmos_average_pstd.nc` by using the `MarsPlot.py --inspect (-i)` command to list the variables in the file:

```
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average_pstd.nc

> =====DIMENSIONS=====
> ['lat', 'lon', 'phalf', 'time', 'pstd']
> .. (etc) ..
> =====CONTENT=====
> .. (etc) ..
> vcomp          : ('time', 'pstd', 'lat', 'lon')= (10, 36, 36, 60),
meridional wind  [m/s]
> .. (etc) ..
> Ls ranging from 255.42 to 284.19: 45.00 days
>                (MY 01)   (MY 01)
> =====
```

We can see that `vcomp` is a variable in the file and therefore `msf` can be derived and added:

```
(AmesCAP)>$ MarsVars.py 07180.atmos_average_pstd.nc -add msf
```

**Note:** `msf` should not be added before pressure-interpolating the file because it is derived on pressure coordinates.

**MarsPlot.py -i works on any netCDF file, not just the ones created with CAP!**

[\(Return to Top\)](#)

## 2.4 Add density (`rho`) and mid-point altitude (`zfull`) to `atmos_average`

This step also uses the `-add` function from `MarsVars`:

```
(AmesCAP)>$ MarsVars.py 07180.atmos_average.nc -add rho zfull
```

Density (`rho`) is derived from pressure (`pfull`) and temperature (`temp`), and mid-point altitude (`zfull`) is obtained via hydrostatic integration.

**Note:** `rho` and `zfull` must be added to a file before interpolating to another vertical coordinate. Unlike `msf`, these variables are computed on the native model grid and will not be properly calculated on any other vertical grid.

[\(Return to Top\)](#)

## 2.5 Interpolate `atmos_average` to standard altitude

Now that `rho` and `zfull` have been added to `07180.atmos_average.nc`, interpolating the file to standard altitude will include those variables in the new file (`07180.atmos_average_zstd.nc`):

```
(AmesCAP)>$ MarsInterp.py 07180.atmos_average.nc -t zstd
```

Your `/INERTCLDS` directory should now contain the fort.11 files and six `netCDF` files:

```
> 07180.atmos_fixed.nc      07180.atmos_average_pstd.nc      fort.11_0721
> 07180.atmos_average.nc   07180.atmos_average_zstd.nc      fort.11_0722
> 07180.atmos_diurn.nc     fort.11_0719                      fort.11_0723
> 07180.atmos_daily.nc     fort.11_0720
```

Use the inspect (`MarsPlot.py -i`) function to confirm that:

- The original file (`07180.atmos_average.nc`) contains `rho` and `zfull` but not `msf`.
- The altitude-interpolated file (`07180.atmos_average_zstd.nc`) contains `rho` and `zfull` but not `msf`.
- The pressure-interpolated file (`07180.atmos_average_pstd.nc`) contains `msf` but not `rho` or `zfull`.

```
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average.nc          # contains rho,
zfull, not msf
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average_zstd.nc     # contains rho,
zfull, not msf
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average_pstd.nc     # contains msf
```

[\(Return to Top\)](#)

## 2.6 Time-shift and pressure-interpolate the `diurn` file

The time-shift function is part of `MarsFiles` and pressure-interpolating is, as we know, part of `MarsInterp`. We'll start by pressure-interpolating the file, **but note that these functions can be used in either order**.

The `diurn` file is organized by time-of-day assuming **universal time** beginning at the Martian prime meridian. Time-shifting the file converts the file to **uniform local time**, which is useful for comparing MGCM output to observations from satellites in fixed local time orbit, for example. Time-shifting can only be done on the `diurn` files because these contain a local time dimension (`ltst`).

For this exercise, include only the surface pressure (`ps`), surface temperature (`ts`), and atmospheric temperature (`temp`) variables. This will minimize file size and processing time.

Time-shift `ps`, `ts`, and `temp` using `MarsFiles`:

```
(AmesCAP)>$ MarsFiles.py 07180.atmos_diurn.nc -t --include ts ps temp
```

This created a new file ending in `_T.nc` and containing only `ts`, `ps`, `temp`, and their relevant dimensions. Now, pressure-interpolate the file using `MarsInterp`:

```
(AmesCAP)>$ MarsInterp.py 07180.atmos_diurn_T.nc -t pstd
```

This should take just over a minute.

**Note:** Interpolating large files (such as `daily` or `diurn` files) with CAP can take a long time because the code is written in Python. That's why we are only including three variables (`ps`, `ts`, and `temp`) in this particular demonstration.

After time-shifting and pressure-interpolating, `/INERTCLDS` should contain three `diurn` files:



```
> 07180.atmos_diurn.nc 07180.atmos_diurn_T.nc
07180.atmos_diurn_T_pstd.nc
```

**Note:** We will *not* do this here, but you can create custom vertical grids that you want CAP to interpolate to. See the documentation for [MarsInterp](#) for more information.

[\(Return to Top\)](#)

## 2.7 Apply a low-pass filter (`-lpf`) to the surface pressure (`ps`) and temperature (`ts`) in the `daily` file

Temporal filtering and tidal analyses are functions of [MarsFiles](#). The low-pass filter argument requires a cutoff frequency, `sol_max`. Here, we use a 2-sol cut-off frequency to isolate synoptic-scale features. Include only `ps` and `ts` in the new file:

```
(AmesCAP)>$ MarsFiles.py 07180.atmos_daily.nc -lpf 2 -include ps ts
```

This created `07180.atmos_daily_lpf.nc` containing only `ps`, `ts`, and their relevant dimensions.

[\(Return to Top\)](#)

## 2.8 Estimate the magnitude of the wind shear using CAP

This can be done by vertically-differentiating the zonal (U) and meridional (V) winds, i.e. computing  $dU/dz$  and  $dV/dz$ . The U and V winds are output by the model as `ucomp` and `vcomp`, respectively.

You already know that [MarsVars](#) is used for adding variables, however, the `-add` argument will not work here. Instead, there is a call specifically for vertical differentiation called `-zdiff`.

Compute and add  $dU/dz$  and  $dV/dz$  to `07180.atmos_average_zstd.nc` using `-zdiff`:

```
(AmesCAP)>$ MarsVars.py 07180.atmos_average_zstd.nc -zdiff ucomp vcomp
```

Using the inspect ([MarsPlot.py -i](#)) function, we can see the new variables in the file:

```
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average_zstd.nc
> =====DIMENSIONS=====
> ['lat', 'lon', 'phalf', 'time', 'zstd']
> .. (etc) ..
> =====CONTENT=====
> .. (etc) ..
> d_dz_ucomp      : ('time', 'zstd', 'lat', 'lon')= (10, 45, 36, 60),
```

```

vertical gradient of zonal wind  [m/s/m]
> d_dz_vcomp      : ('time', 'zstd', 'lat', 'lon')= (10, 45, 36, 60),
vertical gradient of meridional wind  [m/m]
> .. (etc) ..
>
> Ls ranging from 255.42 to 284.19: 45.00 days
>                (MY 01)   (MY 01)
> =====

```

[\(Return to Top\)](#)

## 2.9 Calculate the column-integrated dust, water ice, and water vapor mixing ratios in the **daily** file

Similar to the **-zdiff** function, **MarsVars** has a **-col** function that performs a column integration on specified variables.

Column-integrate the dust, water ice, and water vapor mixing ratios like so:

```

(AmesCAP)>$ MarsVars.py 07180.atmos_daily.nc -col dst_mass ice_mass
vap_mass

```

Using the inspect (**MarsPlot.py -i**) function, we can see the new variables in the file:

```

(AmesCAP)>$ MarsPlot.py -i 07180.atmos_daily.nc
> =====DIMENSIONS=====
> ['lat', 'lon', 'pfull', 'phalf', 'zgrid', 'scalar_axis', 'time']
> .. (etc) ..
> =====CONTENT=====
> .. (etc) ..
> dst_mass_col    : ('time', 'lat', 'lon')= (800, 36, 60), column
integration of dust aerosol mass mixing ratio  [kg/m2]
> ice_mass_col    : ('time', 'lat', 'lon')= (800, 36, 60), column
integration of water ice aerosol mass mixing ratio  [kg/m2]
> vap_mass_col    : ('time', 'lat', 'lon')= (800, 36, 60), column
integration of water vapor mass mixing ratio  [kg/m2]
> dst_mass        : ('time', 'pfull', 'lat', 'lon')= (800, 24, 36, 60),
dust aerosol mass mixing ratio  [kg/kg]
> ice_mass        : ('time', 'pfull', 'lat', 'lon')= (800, 24, 36, 60),
water ice aerosol mass mixing ratio  [kg/kg]
> vap_mass        : ('time', 'pfull', 'lat', 'lon')= (800, 24, 36, 60),
water vapor mass mixing ratio  [kg/kg]
>
> Ls ranging from 254.12 to 286.06: 49.94 days
>                (MY 01)   (MY 01)
> =====

```

2.10 Display the values of `pfull`, then display the minimum, mean, and maximum near-surface temperatures `temp` over the globe

Here, we build on our knowledge of the inspect (`MarsPlot.py -i`) function. We already know that `MarsPlot.py -i` displays the variables in a file and information about the file, but `--inspect` can be combined with `--dump` and `--stat` to show more information about specific variables.

```
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average.nc -dump pfull
> pfull=
> [8.7662227e-02 2.5499690e-01 5.4266089e-01 1.0518962e+00 1.9545468e+00
> 3.5580616e+00 6.2466631e+00 1.0509957e+01 1.7400265e+01 2.8756382e+01
> 4.7480076e+01 7.8348366e+01 1.2924281e+02 2.0770235e+02 3.0938846e+02
> 4.1609518e+02 5.1308148e+02 5.9254102e+02 6.4705731e+02 6.7754218e+02
> 6.9152936e+02 6.9731799e+02 6.9994830e+02 7.0082477e+02]
>
```

Indexing specific values of `pfull` is done using quotes and square brackets:

```
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average.nc -dump 'pfull[-1]'
> pfull[-1]=
> 700.8247680664062
>
```

**Note:** quotes ' ' are necessary when browsing dimensions.

The minimum, mean, and maximum values of a variable are computed and displayed in the terminal with the `-stat` argument. `-stat` is better suited for visualizing statistics over large arrays like the four-dimensional temperature variable (`temp`). Given the dimensions of the `temp` variable, `[time, pfull, lat, lon]`, use `-stat` to display the minimum, mean, and maximum **near-surface air temperature (over all timesteps and all locations)**:

```
(AmesCAP)>$ MarsPlot.py -i 07180.atmos_average.nc -stat 'temp[:, -1, :, :]'
>

```

	VAR	MIN	MEAN	MAX
>				
>				

```

|_____|_____|_____|_____|
|
>          temp[:, -1, :, :] |          149.016 |          202.508 |
251.05 |
>
|_____|_____|_____|_____|
|

```

[\(Return to Top\)](#)

and... that's it for post-processing the data in the RIC simulation!

Before moving on to plotting, we need to repeat some of these steps for the RAC simulation. Feel free to repeat all of Steps 2.1-2.10 for the RAC case if you like, but **you are only required to repeat Steps 2.1, 2.2, and 2.5** for this tutorial. For simplicity, we've summarized these steps here:

### 2.1b (for /ACTIVECLDS) Convert **fort.11** files into **netCDF** files

In the /ACTIVECLDS directory, use **MarsFiles** to convert from **fort.11** to **netCDF**, and then concatenate the files along their **time** axes:

```

(AmesCAP)>$ MarsFiles.py fort.11_* -fv3 fixed average daily diurn
(AmesCAP)>$ MarsFiles.py *fixed.nc -c
(AmesCAP)>$ MarsFiles.py *average.nc -c
(AmesCAP)>$ MarsFiles.py *diurn.nc -c
(AmesCAP)>$ MarsFiles.py *daily.nc -c

```

/ACTIVECLDS should now contain the original **fort.11** files and just **four netCDF** files:

```

> 07180.atmos_fixed.nc      fort.11_0719      fort.11_0723
> 07180.atmos_average.nc   fort.11_0720
> 07180.atmos_diurn.nc     fort.11_0721
> 07180.atmos_daily.nc     fort.11_0722

```

### 2.2b (for /ACTIVECLDS) Interpolate **atmos\_average** to standard pressure

Use **MarsInterp**'s **--type (-t)** command to create **07180.atmos\_average\_pstd.nc**:

```

(AmesCAP)>$ MarsInterp.py 07180.atmos_average.nc -t pstd

```

### 2.5b (for /ACTIVECLDS) Interpolate **atmos\_average** to standard altitude

Again, use **MarsInterp**'s **--type (-t)** command to create **07180.atmos\_average\_zstd.nc**:

```
(AmesCAP)>$ MarsInterp.py 07180.atmos_average.nc -t zstd
```

Your **/ACTIVECLDS** directory should now contain the fort.11 files and six **netCDF** files:

```
> 07180.atmos_fixed.nc      07180.atmos_average_pstd.nc      fort.11_0721
> 07180.atmos_average.nc    07180.atmos_average_zstd.nc      fort.11_0722
> 07180.atmos_diurn.nc      fort.11_0719                        fort.11_0723
> 07180.atmos_daily.nc      fort.11_0720
```

[\(Return to Top\)](#)

---

## Optional: Download the Answer Key for Step 2

---

1. Download **KEY.zip** from the CAP tutorial GitHub page [here](#).
2. **Double-click KEY.zip** to unzip the file (do not do this from the command line) -> this should create a **KEY/** directory
3. Open a terminal and run the command:

```
(AmesCAP)>$ path/to/KEY/Step2_Check.sh
```

**Note:** any permission errors can be fixed by running:

```
(AmesCAP)>$ chmod 766 path/to/KEY/Step2_Check.sh
```

**Step2\_Check.sh** will prompt you for the path to your **/CAP\_tutorial** directory:

```
(AmesCAP)>$ path/to/KEY/Step2_Check.sh
> Please type the path to the directory containing CAP_tutorial, i.e.
/Users/username:
>
/Users/username/path/to/directory
>
> Looking in /Users/username/path/to/directory for CAP_tutorial
```

When the script is done checking your answers, it will notify you which (if any) files or variables are missing from Step 2. Go back to the Step listed and redo them!

If you are really stuck, you can run this shell script that will do all of Step 2 for you. This ensures you can follow along with the plotting routines in Step 3.

To run the answer key, type in your terminal:

```
(AmesCAP)>$ path/to/KEY/KEY.sh
```

This will again ask for the path to `/CAP_tutorial`:

```
(AmesCAP)>$ path/to/KEY/KEY.sh
> Please type the path to the directory containing CAP_tutorial, i.e.
/Users/username:
>
/Users/username/path/to/directory
>
> Looking in /Users/username/path/to/directory for CAP_tutorial
```

**Note:** Optionally, you can move `KEY.in` to your `/CAP_tutorial/INERTCLDS` directory and `KEY.sh` will do all of Step 2 **AND Step 3** for you.

[\(Return to Top\)](#)

---

# Break

---

Once you've completed Step 2, you are welcome to take a 15 minute break from the tutorial.

You can use this time to catch up if you haven't completed Steps 1 and/or 2 already, but we highly encourage you to step away from your machine for these 15 minutes.

[\(Return to Top\)](#)

---

## 3. Plotting Routines

Time to practice plotting MGCM output with CAP!

CAP's plotting routine is `MarsPlot`, which can create several plot types:

Type of plot	MarsPlot Designation
Longitude v Latitude	Plot 2D lon x lat
Longitude v Time	Plot 2D lon x time
Longitude v Level	Plot 2D lon x lev

Type of plot	MarsPlot Designation
Latitude v Level	Plot 2D lat x lev
Time v Latitude	Plot 2D time x lat
Time v level	Plot 2D time x lev
Any 1-D line plot	Plot 1D

**MarsPlot** is customizable. Options include:

- PDF or image format
- Landscape or portrait mode
- 1+ plots per page
- Overplotting is supported
- Adjustable axes dimensions, colormaps, map projections, contour levels, etc.

**Plotting with CAP requires passing a template to **MarsPlot**.**

Create the default template by typing:

```
(AmesCAP)>$ MarsPlot.py -template
```

The template is called **Custom.in**. We will edit **Custom.in** to create various plots. **We highly recommend using a text editor that opens **Custom.in** in its own window.** Some options include: gvim, sublime text, atom, and pyzo.

If you use vim, you just have to be familiar with copying and pasting in the terminal. You will also benefit from opening another terminal from which to run command-line calls.

Open **Custom.in** in your preferred text editor, for example:

```
(AmesCAP)>$ gvim Custom.in
```

Scroll down until you see the first two templates shown in the image below:

```
~/CAP_Tutorial/INERTCLDS — vim Custom.in — 115x33
```

```
Custom.in  
<<<<<<<<<<<<<<< Simulations >>>>>>>>>>>>>>>>>>  
ref> None  
2>  
3>  
=====
```

```
START
```

```
HOLD ON  
<<<<<<<<<<<<| Plot 2D lon X lat = True |>>>>>>>>>>>>>>>>>>  
Title           = None  
Main Variable   = fixed.zsurf  
Cmin, Cmax      = None  
Ls 0-360       = None  
Level [Pa/m]    = None  
2nd Variable    = None  
Contours Var 2  = None  
Axis Options : lon = [None,None] | lat = [None,None] | cmap = jet | scale = lin | proj = cart
```

```
<<<<<<<<<<<<| Plot 2D lat X lev = True |>>>>>>>>>>>>>>>>>>  
Title           = None  
Main Variable   = atmos_average.ucomp  
Cmin, Cmax      = None  
Ls 0-360       = None  
Lon +/-180     = None  
2nd Variable    = None  
Contours Var 2  = None  
Axis Options : Lat = [None,None] | level[Pa/m] = [None,None] | cmap = jet |scale = lin
```

```
HOLD OFF  
#=====
```

```
~/CAP_Tutorial/INERTCLDS/Custom.in  CWD: /Users/cbatters/CAP_Tutorial/INERTCLDS  Line: 73  Column: 1
```

By default, `Custom.in` is set to create the two plots shown above: a global topographical map and a zonal mean wind cross-section. The plot type is indicated at the top of each template:

[illegible]

When set to `True` (as it is here), `MarsPlot` will draw that plot. If `False`, `MarsPlot` will skip that plot.

The variable to be plotted is **Main Variable**, which requires the variable name and the file containing it as input:

```
Main Variable = fixed.zsurf # file.variable
```

**Without making any changes to `Custom.in`**, close the file and pass it back to **MarsPlot**:

```
(AmesCAP)>$ MarsPlot.py Custom.in
```

This creates `Diagnostics.pdf`, a single-page PDF displaying the two plots we just discussed: global topography and zonal mean wind. Open the PDF to see the plots.

You can rename `Custom.in` and still pass it to `MarsPlot` successfully. If the template is named anything other than `Custom.in`, `MarsPlot` will produce a PDF named after the template, i.e. `myplots.in` creates `myplots.pdf`. For example:



***(Return to Top)***

***(Return to Top)***

17 / 24

18 / 24

```
> Main Variable = atmos_average_zstd@2.ump
```

Save `Custom.in` and pass it to `MarsPlot`. View `Diagnostics.pdf` to see the results.

### 3.4 Overplot temperature in solid contours

[illegible]

***(Return to Top)***

- Convert kg/m<sup>2</sup> -> g/m<sup>2</sup>
- Set the plot area to between 50 °N and 90 °N.

```
Main Variable = [atmos daily.snow]*1000
```

19 / 24

- Call both `ucomp` and `vcomp` under **Main Variable**

Using square brackets, **Main Variable** is set (and computed) like:

```
Main Variable = sqrt([atmos_daily.ucomp]**2+[atmos_daily.vcomp]**2)
```

Use **HOLD ON** and **HOLD OFF** again. You can use this syntax multiple times in the same template.

The general format will be:

```
> HOLD ON
>
> <<<<<<| Plot 2D lon X lat = True |>>>>>>
> Title      = Surface CO2 Ice (g/m2)
> .. (etc) ..
>
> <<<<<<| Plot 2D lon X lat = True |>>>>>>
> Title      = Surface Wind Speed (m/s)
> .. (etc) ..
>
> HOLD OFF
```

Name the plots accordingly. Save **Custom.in** and pass it to **MarsPlot**. You should see two plots on one page in **Diagnostics.pdf**

### 3.6 Make the following changes to the plots you created in 3.5

For the **surface CO2 ice** plot:

- Set the projection type to **Npole**
- Change the Y axis limits to 60-90 N

For the **surface wind speed** plot:

- Draw contours at 1, 10, and 20, m/s (*add a second variable!*)
- Constrain the Y axis limits to the northern hemisphere
- Constrain the X axis limits to the western hemisphere

**Hint:** we set the latitude range in the previous plot by editing `lat` in **Axis Options**:

```
Axis Options : lon = [None, None] | lat = [50, 90] | cmap = jet | scale =
lin | proj = cart
```

but this only works for cylindrical projections (cartesian **cart**, Robinson **robin**, Mollweide **moll**).

When you choose an azimuthal projection (North polar **Npole**, South polar **Spole**, orthographic **ortho**), you set the **bounding latitude** by adding an argument *after* specifying the projection:

```
Axis Options : lon = [None, None] | lat = [None, None] | cmap = jet | scale
              = lin | proj = Npole 60
```

For each azimuthal projection, acceptable arguments are: `proj = Npole lat_max`, `proj = Spole lat_min`, and `proj = ortho lon_center lat_center`.

[\(Return to Top\)](#)

### 3.7 Create the following zonal mean `time X lat` plots on a new page

Source all of the variables from the `atmos_daily` file in `/INERTCLDS`:

- Surface Temperature (`ts`). Set the colormap to `nipy_spectral`.
- Column dust mass (`dst_mass_col`). Set the colormap to `Spectral_r`.
- Column water ice mass (`ice_mass_col`). Set the colormap to `Spectral_r`.
- Column water vapor mass (`vap_mass_col`). Set the colormap to `Spectral_r`.

**NOTE:** set the colormap (`cmap`) in `Axis Options`:

```
Axis Options : sols = [None, None] | lat = [None, None] | cmap =
              nipy_spectral | scale = lin
```

The general format will look like:

```
> HOLD ON
>
> <<<<<<| Plot 2D time X lat = True |>>>>>>
> Title    = Zonal Mean Surface Temperature (K)
> .. (etc) ..
>
> <<<<<<| Plot 2D time X lat = True |>>>>>>
> Title    = Zonal Mean Column Integrated Dust Mass (kg/m2)
> .. (etc) ..
>
> <<<<<<| Plot 2D time X lat = True |>>>>>>
> Title    = Zonal Mean Column Integrated Water Ice Mass (kg/m2)
> .. (etc) ..
>
> <<<<<<| Plot 2D time X lat = True |>>>>>>
> Title    = 1Zonal Mean Column Integrated Water Vapor Mass (kg/m2)
> .. (etc) ..
>
> HOLD OFF
```

Name the plots accordingly. Save `Custom.in` and pass it to `MarsPlot`.

[\(Return to Top\)](#)

---

### 3.8 Plot the following two cross-sections (**lat** X **lev**) on the same page

#### Zonal mean mass streamfunction (**msf**) at Ls=270°

- Force symmetrical contouring by setting the colorbar's minimum and maximum values to -150 and 150
- Overplot solid contours at **-100,-50,-10,-5,5,10,50,100** (Hint: set both **Main Variable** and **2nd Variable** to **msf**)
- Adjust the Y axis limits to 1,000-1 Pa
- Change the colormap from **jet** to **RdBu\_r**

#### Zonal mean temperature (**temp**) at Ls=270°

- Source **temp** from the same pressure-interpolated file you sourced **msf** from
- Overplot (**2nd Variable**) the zonal mean zonal wind (**ucomp**)
- Adjust the Y axis limits to 1,000-1 Pa
- Set the colormap to **jet**

Don't forget to use **HOLD ON** and **HOLD OFF** and to name your plots accordingly. Save **Custom.in** and pass it to **MarsPlot**.

[\(Return to Top\)](#)

---

### 3.9 Plot zonal mean temperature from the RIC and RAC cases

Create the plots at Ls=270° from the **atmos\_average\_pstd** file, then create a difference plot.

Make use of **HOLD ON** and **HOLD OFF** again here. Copy and paste a **lat x lev** template, edit the first plot, then copy and paste that two more times. For the difference plot, you'll need subtract the two **temp** variables from one another, so make use of **@N** to point to the **/ACTIVECLDS** directory and square brackets **[]** to subtract one variable from the other:

```
> Main Variable = [atmos_average_pstd.temp]-[atmos_average_pstd@2.temp]
```

- On the RIC & RAC plots: set the minimum and maximum contour-fill interval (**Cmin,Cmax**) to 130 and 250 (K)
- On the difference plot: set the colormap to **RdBu**
- On the difference plot: set the minimum and maximum contour-fill interval (**Cmin,Cmax**) -15 and 15 (K)
- On all three plots: set the vertical range to 1,000 - 1 Pa
- On all three plots: set proper titles

Save **Custom.in** and pass it to **MarsPlot**.

[\(Return to Top\)](#)

---

### 3.10 Generate two 1D temperature profiles (**temp**) from the RIC case

Draw the 3 AM and 3 PM thermal profiles at **50°N**, **150°E** at  $L_s=270^\circ$ . Call **temp** from the **atmos\_diurn\_T\_pstd** file, which is the time-shifted and pressure-interpolated version of the diurn file. 3 AM is index=**3**, 3 PM is index=**15**, so **Main Variable** will be set as:

```
> Main Variable      = atmos_diurn_T_pstd.temp{ tod=3 }
#                    filename.var{ tod=X }
```

for the 3 AM line, and

```
> Main Variable      = atmos_diurn_T_pstd.temp{tod=15}
```

for the 3 PM line. You will have to specify **Level [Pa/m]** as the other axis:

```
> Level [Pa/m]      = AXIS
```

Note that when you specify level as the AXIS, MarsPlot automatically reverses the axes to draw a vertical profile of the requested variable.

Finally, change the Y axis limits from **None** to **1000,1** Pa:

```
> lat,lon+/-180,[Pa/m],sols = [1000,1]
```

As a reminder, to draw two lines on one axes, use **ADD LINE**:

```
> <<<<<<| Plot 1D = True |>>>>>>
> Main Variable      = var1
> .. (etc) ..
>
> ADD LINE
>
> <<<<<<| Plot 1D = True |>>>>>>
> Main Variable      = var2
> .. (etc) ..
```

**NOTE:** You do not use **HOLD ON** and **HOLD OFF** to overplot 1D plots. **HOLD** is always for drawing separate plots on the same page

Save `Custom.in` and pass it to `MarsPlot`. View `Diagnostics.pdf`.

[\(Return to Top\)](#)

---

### 3.11 Plot the 1D filtered and unfiltered surface pressure over a 20-sol period

Compare the unfiltered surface pressure `ps`, which is the original variable in the original daily file (`atmos_daily`), to the filtered surface pressure, which is the time-filtered variable created when we applied a low-pass filter to the daily file (`atmos_daily_lpf`) in exercise 2.6, at 50°N and 150°E.

- Both are 1D plots. Use `ADD LINE` to plot on the same axes
- Use `ps` from `atmos_daily` and `atmos_daily_lpf`
- Set `Latitude = 50` and `Lon +/-180 = 150`
- To show a 20-sol period: under `Axis Options`, set the X axis range to (`Ls = [260, 280]`)
- Narrow the Y axis range: under `Axis Options`, set the Y axis range to (`var = [860,980]` Pa)

Save `Custom.in` and pass it to `MarsPlot`. View `Diagnostics.pdf`.

[\(Return to Top\)](#)

---

## That's a Wrap

This concludes the practical exercise portion of the CAP tutorial. Please keep these exercises as a reference for the future!

*This document was completed in October 2021. Written by Alex Kling, Courtney Batterson, and Victoria Hartwick*

Please submit feedback to Alex Kling: alexandre.m.kling@nasa.gov

[\(Return to Top\)](#)

---