

Gnowee

Generated by Doxygen 1.8.6

Wed May 10 2017 11:51:16

Contents

1	Main Page	1
2	Module Index	3
2.1	Modules	3
3	Namespace Index	5
3.1	Packages	5
4	Hierarchical Index	7
4.1	Class Hierarchy	7
5	Class Index	9
5.1	Class List	9
6	File Index	11
6.1	File List	11
7	Module Documentation	13
7.1	Constraints	13
7.1.1	Detailed Description	13
7.2	Gnowee	14
7.2.1	Detailed Description	14
7.2.2	Function Documentation	14
7.2.2.1	main	14
7.3	GnoweeHeuristics	16
7.3.1	Detailed Description	16
7.3.2	Function Documentation	16
7.3.2.1	rejection_bounds	16
7.3.2.2	simple_bounds	17
7.4	GnoweeUtilities	18
7.4.1	Detailed Description	18
7.5	ObjectiveFunction	19
7.5.1	Detailed Description	19
7.5.2	Function Documentation	19

7.5.2.1	prod	19
7.6	Sampling	20
7.6.1	Detailed Description	20
7.6.2	Function Documentation	20
7.6.2.1	get_cdr_permutations	20
7.6.2.2	initial_samples	21
7.6.2.3	levy	21
7.6.2.4	NOLH	22
7.6.2.5	params	22
7.6.2.6	plot_samples	22
7.6.2.7	tlf	22
8	Namespace Documentation	25
8.1	Gnowee Namespace Reference	25
8.1.1	Detailed Description	25
9	Class Documentation	27
9.1	Constraints.Constraint Class Reference	27
9.1.1	Detailed Description	28
9.1.2	Constructor & Destructor Documentation	28
9.1.2.1	__init__	28
9.1.3	Member Function Documentation	28
9.1.3.1	__repr__	28
9.1.3.2	__str__	28
9.1.3.3	get_penalty	28
9.1.3.4	greater_than	29
9.1.3.5	less_or_equal	29
9.1.3.6	less_than	29
9.1.3.7	set_constraint_func	30
9.1.4	Member Data Documentation	30
9.1.4.1	constraint	30
9.1.4.2	func	30
9.2	GnoweeUtilities.Event Class Reference	30
9.2.1	Detailed Description	31
9.2.2	Constructor & Destructor Documentation	31
9.2.2.1	__init__	31
9.2.3	Member Function Documentation	31
9.2.3.1	__repr__	31
9.2.3.2	__str__	32
9.2.4	Member Data Documentation	32
9.2.4.1	design	32

9.2.4.2	evaluations	32
9.2.4.3	fitness	32
9.2.4.4	generation	32
9.3	GnoweeHeuristics.GnoweeHeuristics Class Reference	32
9.3.1	Detailed Description	34
9.3.2	Constructor & Destructor Documentation	34
9.3.2.1	__init__	34
9.3.3	Member Function Documentation	35
9.3.3.1	__repr__	35
9.3.3.2	__str__	35
9.3.3.3	cont_levy_flight	36
9.3.3.4	crossover	36
9.3.3.5	disc_levy_flight	37
9.3.3.6	elite_crossover	37
9.3.3.7	initialize	38
9.3.3.8	mutate	38
9.3.3.9	scatter_search	39
9.3.4	Member Data Documentation	40
9.3.4.1	alpha	40
9.3.4.2	convTol	40
9.3.4.3	fracDiscovered	40
9.3.4.4	fracElite	40
9.3.4.5	fracLevy	40
9.3.4.6	gamma	40
9.3.4.7	initSampling	40
9.3.4.8	maxFevals	41
9.3.4.9	maxGens	41
9.3.4.10	n	41
9.3.4.11	optConvTol	41
9.3.4.12	optimalFitness	41
9.3.4.13	penalty	41
9.3.4.14	population	41
9.3.4.15	scalingFactor	41
9.3.4.16	stallLimit	41
9.4	ObjectiveFunction.ObjectiveFunction Class Reference	41
9.4.1	Detailed Description	43
9.4.2	Constructor & Destructor Documentation	43
9.4.2.1	__init__	43
9.4.3	Member Function Documentation	43
9.4.3.1	__repr__	43

9.4.3.2	__str__	44
9.4.3.3	ackley	45
9.4.3.4	dejong	45
9.4.3.5	easom	46
9.4.3.6	griewank	46
9.4.3.7	mi_chemical_process	47
9.4.3.8	mi_pressure_vessel	47
9.4.3.9	mi_spring	48
9.4.3.10	pressure_vessel	48
9.4.3.11	rastrigin	49
9.4.3.12	rosenbrock	49
9.4.3.13	set_obj_func	50
9.4.3.14	shifted_ackley	50
9.4.3.15	shifted_dejong	51
9.4.3.16	shifted_easom	51
9.4.3.17	shifted_griewank	52
9.4.3.18	shifted_rastrigin	52
9.4.3.19	shifted_rosenbrock	53
9.4.3.20	speed_reducer	53
9.4.3.21	spring	54
9.4.3.22	tsp	54
9.4.3.23	welded_beam	55
9.4.4	Member Data Documentation	55
9.4.4.1	func	55
9.4.4.2	objective	55
9.5	GnoweeUtilities.Parent Class Reference	56
9.5.1	Detailed Description	56
9.5.2	Constructor & Destructor Documentation	56
9.5.2.1	__init__	56
9.5.3	Member Function Documentation	57
9.5.3.1	__repr__	57
9.5.3.2	__str__	57
9.5.4	Member Data Documentation	57
9.5.4.1	changeCount	57
9.5.4.2	fitness	57
9.5.4.3	stallCount	57
9.5.4.4	variables	57
9.6	GnoweeUtilities.ProblemParameters Class Reference	58
9.6.1	Detailed Description	58
9.6.2	Constructor & Destructor Documentation	59

9.6.2.1	<code>__init__</code>	59
9.6.3	Member Function Documentation	60
9.6.3.1	<code>__repr__</code>	60
9.6.3.2	<code>__str__</code>	61
9.6.3.3	<code>get_preset_params</code>	61
9.6.4	Member Data Documentation	61
9.6.4.1	<code>discreteVals</code>	61
9.6.4.2	<code>histTitle</code>	61
9.6.4.3	<code>lb</code>	61
9.6.4.4	<code>optimum</code>	61
9.6.4.5	<code>pltTitle</code>	62
9.6.4.6	<code>ub</code>	62
9.6.4.7	<code>varNames</code>	62
9.6.4.8	<code>varType</code>	62
9.7	GnoweeUtilities.Switch Class Reference	62
9.7.1	Detailed Description	62
9.7.2	Constructor & Destructor Documentation	63
9.7.2.1	<code>__init__</code>	63
9.7.3	Member Function Documentation	63
9.7.3.1	<code>__iter__</code>	63
9.7.3.2	<code>match</code>	63
9.7.4	Member Data Documentation	63
9.7.4.1	<code>fall</code>	63
9.7.4.2	<code>value</code>	63
9.8	GnoweeUtilities.WeightedRandomGenerator Class Reference	64
9.8.1	Detailed Description	64
10	File Documentation	65
10.1	<code>/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Constraints.py</code> File Reference	65
10.2	<code>/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Gnowee.py</code> File Reference	65
10.3	<code>/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeHeuristics.py</code> File Reference	65
10.4	<code>/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeUtilities.py</code> File Reference	66
10.5	<code>/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ObjectiveFunction.py</code> File Reference	66
10.6	<code>/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Sampling.py</code> File Reference	67
Index		68

Chapter 1

Main Page

Gnowee

Version

1.0

[Gnowee](#) is a general nearly-global metaheuristic optimization algorithm. It uses a blend of common heuristics to solve difficult gradient free constrained MINLP problems with mixed variables. It is capable of solving simpler problems, but may not be the algorithm of choice.

Running [Gnowee](#)

For examples on how to run [Gnowee](#), please refer to the runGnowee notebook included in the src directory.

Licensing Information

Contact information

Bugs and suggestions for improvement can be submitted via the GitHub page: <https://github.com/-SlaybaughLab/Gnowee>

Alternatively, questions or comments on [Gnowee](#) can be directed to:

James Bevins

james.e.bevins@gmail.com

Citation Information

To cite [Gnowee](#), use the following reference:

Chapter 2

Module Index

2.1 Modules

Here is a list of all modules:

Constraints	13
Gnowee	14
GnoweeHeuristics	16
GnoweeUtilities	18
ObjectiveFunction	19
Sampling	20

Chapter 3

Namespace Index

3.1 Packages

Here are the packages with brief descriptions (if available):

Gnowee	Contains the Gnowee optimization program and associated utilities	25
------------------------	---	--------------------

Chapter 4

Hierarchical Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

object	
Constraints.Constraint	27
GnoweeHeuristics.GnoweeHeuristics	32
GnoweeUtilities.Event	30
GnoweeUtilities.Parent	56
GnoweeUtilities.ProblemParameters	58
GnoweeUtilities.Switch	62
GnoweeUtilities.WeightedRandomGenerator	64
ObjectiveFunction.ObjectiveFunction	41

Chapter 5

Class Index

5.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

Constraints.Constraint	
The class creates a Constraints object that can be used in optimization algorithms	27
GnoweeUtilities.Event	
Represents a snapshot in the optimization process to be used for debugging, benchmarking, and user feedback	30
GnoweeHeuristics.GnoweeHeuristics	
The class is the foundation of the Gnowee optimization algorithm	32
ObjectiveFunction.ObjectiveFunction	
The class creates a ObjectiveFunction object that can be used in optimization algorithms . . .	41
GnoweeUtilities.Parent	
The class contains all of the parameters pertinent to a member of the population	56
GnoweeUtilities.ProblemParameters	
Creates an object containing key features of the chosen optimization problem	58
GnoweeUtilities.Switch	
Creates a switch class object to switch between cases	62
GnoweeUtilities.WeightedRandomGenerator	
.	64

Chapter 6

File Index

6.1 File List

Here is a list of all documented files with brief descriptions:

/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ Constraints.py	65
/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ Gnowee.py	65
/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ GnoweeHeuristics.py	65
/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ GnoweeUtilities.py	66
/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ ObjectiveFunction.py	66
/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ Sampling.py	67

Chapter 7

Module Documentation

7.1 Constraints

Defines a class to perform constraint calculations.

Classes

- class [Constraints.Constraint](#)

The class creates a Constraints object that can be used in optimization algorithms.

7.1.1 Detailed Description

Defines a class to perform constraint calculations.

Author

James Bevins,

Date

9May17

7.2 Gnowee

Main program for the [Gnowee](#) metaheuristic algorithm.

Functions

- `def Gnowee.main`

Main controller program for the [Gnowee](#) optimization.

7.2.1 Detailed Description

Main program for the [Gnowee](#) metaheuristic algorithm. General nearly-global metaheuristic optimization algorithm. Uses a blend of common heuristics to solve difficult gradient free constrained MINLP problems with categorical variables. It is capable of solving simpler problems, but may not be the algorithm of choice.

For examples on how to run [Gnowee](#), please refer to the `runGnowee` notebook included in the `src` directory.

Author

James Bevins

Date

9May17

7.2.2 Function Documentation

7.2.2.1 `def Gnowee.main (func, lb, ub, varType, gh, discreteVals = [])`

Main controller program for the [Gnowee](#) optimization.

Parameters

<i>func</i>	<i>function</i> The objective function to be minimized.
<i>lb</i>	<i>list or array</i> The lower bounds of the design variable(s). Only enter the bounds for continuous and integer/binary variables. The order must match the order specified in <i>varType</i> and <i>ub</i> .
<i>ub</i>	<i>list or array</i> The upper bounds of the design variable(s). Only enter the bounds for continuous and integer/binary variables. The order must match the order specified in <i>varType</i> and <i>lb</i> .
<i>varType</i>	<i>list or array</i> The type of variable for each position in the upper and lower bounds array. Discrete variables are to be included last as they are specified separately from the <i>lb/ub</i> through the <i>discreteVals</i> optional input. A variable can have two types (for example, 'dx' could denote a layer that can take multiple materials and be placed at multiple design locations) Allowed values: 'c' = continuous over a given range (range specified in <i>lb</i> & <i>ub</i>). 'i' = integer/binary (difference denoted by <i>ub/lb</i>). 'd' = discrete where the allowed values are given by the option <i>discreteVals</i> <i>nxm</i> array with <i>n</i> =# of discrete variables and <i>m</i> =# of values that can be taken for each variable. 'x' = combinatorial. All of the variables denoted by <i>x</i> are assumed to be "swappable" in combinatorial permutations. There must be at least two variables denoted as combinatorial. 'f' = fixed design variable. Will not be considered of any permutation.
	<i>gh: GnoweeHeuristic object</i> An object containing the settings and methods required for the Gnowee optimization algorithm.
<i>discreteVals</i>	<i>list of list(s)</i> <i>nxm</i> with <i>n</i> =# of discrete variables and <i>m</i> =# of values that can be taken for each variable. For example, if you had two variables representing the tickness and diameter of a cylinder that take standard values, the <i>discreteVals</i> could be specified as: <i>discreteVals</i> = [[0.125, 0.25, 0.375], [0.25, 0.5, 0.75]] Gnowee will then map the optimization results to these allowed values.

Returns

list: List for design event objects for the current top solution vs generation. Only stores the information when new optimal designs are found.

7.3 GnoweeHeuristics

Heuristics and settings supporting the [Gnowee](#) metaheuristic optimization algorithm.

Classes

- class [GnoweeHeuristics.GnoweeHeuristics](#)
The class is the foundation of the [Gnowee](#) optimization algorithm.

Functions

- def [GnoweeHeuristics.simple_bounds](#)
Application of problem boundaries to generated solutions.
- def [GnoweeHeuristics.rejection_bounds](#)
Application of problem boundaries to generated solutions.

7.3.1 Detailed Description

Heuristics and settings supporting the [Gnowee](#) metaheuristic optimization algorithm. This instantiates the class and methods necessary to perform an optimization using the [Gnowee](#) algorithm. Each of the heuristics can also be used independently of the [Gnowee](#) algorithm by instantiating this class and choosing the desired heuristic.

The default settings are those found to be best for a suite of benchmark problems but one may find alternative settings are useful for the problem of interest based on the fitness landscape and type of variables.

Author

James Bevins

Date

8May17

7.3.2 Function Documentation

7.3.2.1 def GnoweeHeuristics.rejection_bounds (parent, child, stepSize, lb, ub)

Application of problem boundaries to generated solutions.

Adjusts step size for all rejected solutions until within the boundaries.

Parameters

<i>parent</i>	<i>array</i> The current system designs.
<i>child</i>	<i>array</i> The proposed new system designs.
<i>stepSize</i>	<i>float</i> The stepsize for the permutation.

<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).

Returns

array: The new system design that is within problem boundaries.

7.3.2.2 `def GnoweeHeuristics.simple_bounds (child, lb, ub)`

Application of problem boundaries to generated solutions.

If outside of the boundaries, the variable defaults to the boundary.

Parameters

<i>child</i>	<i>array</i> The proposed new system designs.
<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).

Returns

array: The new system design that is within problem boundaries.

7.4 GnoweeUtilities

Classes and methods to support the [Gnowee](#) optimization algorithm.

Classes

- class [GnoweeUtilities.Parent](#)
The class contains all of the parameters pertinent to a member of the population.
- class [GnoweeUtilities.Event](#)
Represents a snapshot in the optimization process to be used for debugging, benchmarking, and user feedback.
- class [GnoweeUtilities.ProblemParameters](#)
Creates an object containing key features of the chosen optimization problem.
- class [GnoweeUtilities.Switch](#)
Creates a switch class object to switch between cases.

7.4.1 Detailed Description

Classes and methods to support the [Gnowee](#) optimization algorithm.

Author

James Bevins

Date

9May17

7.5 ObjectiveFunction

Defines a class to perform objective function calculations.

Classes

- class [ObjectiveFunction.ObjectiveFunction](#)

The class creates a [ObjectiveFunction](#) object that can be used in optimization algorithms.

Functions

- def [ObjectiveFunction.prod](#)

Computes the product of a set of numbers (ie big PI, multiplicative equivalent to sum).

7.5.1 Detailed Description

Defines a class to perform objective function calculations. This class contains the necessary functions and methods to create objective functions and initialize the necessary parameters. The class is pre-stocked with common benchmark functions for easy fishing.

Users can modify the this class to add additional functions following the format of the functions currently in the class.

Author

James Bevins

Date

10May17

7.5.2 Function Documentation

7.5.2.1 def ObjectiveFunction.prod (*iterable*)

Computes the product of a set of numbers (ie big PI, multiplicative equivalent to sum).

Parameters

<i>iterable</i>	<i>list or array or generator</i>	Iterable set to multiply.
-----------------	-----------------------------------	---------------------------

Returns

float: The product of all of the items in iterable

7.6 Sampling

Different methods to perform phase space sampling and random walks.

Functions

- def [Sampling.initial_samples](#)
Generate a set of samples in a given phase space.
- def [Sampling.plot_samples](#)
Plot the first 2 and 3 dimensions on the sample distribution.
- def [Sampling.levy](#)
Sample the Levy distribution given by.
- def [Sampling.tlf](#)
Samples from a truncated Levy flight distribution (TLF) according to Manegna, "Stochastic Process with Ultraslow Convergence to a Gaussian: The Truncated Levy Flight" to map a levy distribution onto the interval [0,1].
- def [Sampling.NOLH](#)
This library allows to generate Nearly Orthogonal Latin Hypercubes (NOLH) according to Cioppa (2007) and De Rainville et al.
- def [Sampling.params](#)
Returns the NOLH order \$m\$, the required configuration length \$q\$ and the number of columns to remove to obtain the desired dimensionality.
- def [Sampling.get_cdr_permutations](#)
Generate a set of CDR permutations for NOLH.

7.6.1 Detailed Description

Different methods to perform phase space sampling and random walks. Design of experiment and phase space sampling methods. Includes some vizualization tools.

Dependencies on pyDOE.

Author

James Bevins

Date

8May17

7.6.2 Function Documentation

7.6.2.1 def Sampling.get_cdr_permutations (dim)

Generate a set of CDR permutations for NOLH.

Parameters

<i>dim</i>	<i>integer</i> The dimension of the space.
------------	---

Returns

array: A configuration vector.

array: Array containing the indexes of the colummns to be removed from conf vector.

7.6.2.2 def Sampling.initial_samples (lb, ub, method, numSamp)

Generate a set of samples in a given phase space.

The current methods available are 'random', 'nolh', 'nolh-rp', 'nolh-cdr', or 'lhc'.

Parameters

<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>method</i>	<i>string</i> String representing the chosen sampling method. Valid options are: 'random', 'nolh', 'nolh-rp', 'nolh-cdr', or 'lhc'.
<i>numSamp</i>	<i>integer</i> The number of samples to be generated. Ignored for nolh algorithms.

Returns

array: The list of coordinates for the sampled phase space.

7.6.2.3 def Sampling.levy (nc, nr = 0, alpha = 1.5, gam = 1, n = 1)

Sample the Levy distribution given by.

$$L_{\alpha,\gamma}(z) = \frac{1}{\pi} \int_0^{+\infty} e^{-\gamma q^\alpha} \cos(qz) dq$$

using the Mantegna algorithm outlined in "Fast, Accurate Algorithm for Numerical Simulation of Levy Stable Stochastic Processes."

Parameters

<i>nc</i>	<i>integer</i> The number of columns of Levy values for the return array.
<i>nr</i>	<i>integer</i> The number of rows of Levy values for the return array.
<i>alpha</i>	<i>float</i> Levy exponent - defines the index of the distribution and controls scale properties of the stochastic process.
<i>gam</i>	<i>float</i> Gamma - Scale unit of process for Levy flights.
<i>n</i>	<i>integer</i> Number of independent variables - can be used to reduce Levy flight sampling variance.

Returns

array: Array representing the levy flights for each nest.

7.6.2.4 `def Sampling.NOLH (conf, remove = None)`

This library allows to generate Nearly Orthogonal Latin Hypercubes (NOLH) according to Cioppa (2007) and De Rainville et al.

(2012) and reference therein.

<https://pypi.python.org/pypi/pynolh>

Constructs a Nearly Orthogonal Latin Hypercube (NOLH) of order m from a configuration vector $conf$. The configuration vector may contain either the numbers in $[0, q-1]$ or $[1, q]$ where $q = 2^{m-1}$. The columns to be removed are also in $[0, d-1]$ or $[1, d]$ where $d = m + \frac{m-1}{2}$ is the NOLH dimensionality.

The whole library is incorporated here with minimal modification for commonality and consolidation of methods.

Parameters

<i>conf</i>	<i>array</i> Configuration vector.
<i>remove</i>	<i>array</i> Array containing the indexes of the columns to be removed from conf vector.

Returns

array: Array containing nearly orthogonal latin hypercube sampling.

7.6.2.5 `def Sampling.params (dim)`

Returns the NOLH order m , the required configuration length q and the number of columns to remove to obtain the desired dimensionality.

Parameters

<i>dim</i>	<i>integer</i> The dimension of the space.
------------	---

7.6.2.6 `def Sampling.plot_samples (s)`

Plot the first 2 and 3 dimensions on the sample distribution.

Can't plot the full hyperspace yet. Produces a very simple plot for visualizing the difference in the sampling methods.

Parameters

<i>s</i>	<i>array</i> The list of coordinates for the sampled phase space.
----------	--

7.6.2.7 `def Sampling.tlf (numRows = 1, numCol = 1, alpha = 1.5, gam = 1., cutPoint = 10.)`

Samples from a truncated Levy flight distribution (TLF) according to Manegna, "Stochastic Process with Ultraslow Convergence to a Gaussian: The Truncated Levy Flight" to map a levy distribution onto the interval $[0,1]$.

Parameters

<i>numRow</i>	<i>integer</i> Number of rows of Levy flights to sample.
<i>numCol</i>	<i>integer</i> Number of columns of Levy flights to sample.
<i>alpha</i>	<i>float</i> Levy exponent - defines the index of the distribution and controls scale properties of the stochastic process.
<i>gam</i>	<i>float</i> Gamma - Scale unit of process for Levy flights.
<i>cutPoint</i>	<i>float</i> Point at which to cut sampled Levy values and resample.

Returns

array: Array representing the levy flights on the interval (0,1).

Chapter 8

Namespace Documentation

8.1 Gnowee Namespace Reference

Contains the [Gnowee](#) optimization program and associated utilities.

Functions

- `def main`
Main controller program for the [Gnowee](#) optimization.

8.1.1 Detailed Description

Contains the [Gnowee](#) optimization program and associated utilities.

Version

1.0

General nearly-global metaheuristic optimization algorithm. Uses a blend of common heuristics to solve difficult gradient free constrained MINLP problems with categorical variables. It is capable of solving simpler problems, but may not be the algorithm of choice.

For examples on how to run [Gnowee](#), please refer to the runGnowee notebook included in the src directory.

Author

James Bevins

Date

9May17

See Also

[Gnowee](#)
[GnoweeHeuristics](#)
[GnoweeUtilities](#)
[ObjectiveFunction](#)
[Constraints](#)
[OptiPlot](#)
[Sampling](#)


Chapter 9

Class Documentation

9.1 Constraints.Constraint Class Reference

The class creates a Constraints object that can be used in optimization algorithms.

Inheritance diagram for Constraints.Constraint:



Public Member Functions

- `def __init__`
Constructor to build the ObjectiveFunction class.
- `def __repr__`
Constraint class param print function.
- `def __str__`
Human readable Constraint print function.
- `def set_constraint_func`
Converts an input string name for a function to a function handle.
- `def get_penalty`
Calculate the constraint violation penalty, if any.
- `def less_or_equal`
Compares a previously calculated value to a user specified maximum including that maximum.
- `def less_than`
Compares a previously calculated value to a user specified maximum excluding that maximum.
- `def greater_than`
Compares the calculated value to the minimum specified by the user.

Public Attributes

- `func`
function handle: The function handle for the constraint function to be used for the optimization.
- `constraint`
float: The constraint to be enforced.

- [penalty](#)

float: The penalty to be applied if the constraint is violated

9.1.1 Detailed Description

The class creates a Constraints object that can be used in optimization algorithms.

9.1.2 Constructor & Destructor Documentation

9.1.2.1 `def Constraints.Constraint.__init__(self, method=None, constraint=None, penalty=1E15)`

Constructor to build the ObjectiveFunction class.

Parameters

<i>self</i>	<i>object pointer</i> The object pointer.
<i>method</i>	<i>string</i> The name of the constraint function to evaluate.
<i>constraint</i>	<i>float</i> The constraint to be compared against.
<i>penalty</i>	<i>float</i> The penalty to be applied if a constraint is violated. 1E15 is recommended.

9.1.3 Member Function Documentation

9.1.3.1 `def Constraints.Constraint.__repr__(self)`

[Constraint](#) class param print function.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
-------------	---

9.1.3.2 `def Constraints.Constraint.__str__(self)`

Human readable [Constraint](#) print function.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
-------------	---

9.1.3.3 `def Constraints.Constraint.get_penalty(self, violation)`

Calculate the constraint violation penalty, if any.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
<i>violation</i>	<i>float</i> The magnitude of the constraint violation used for scaling the penalty.

Returns

float: The scaled penalty.

9.1.3.4 def Constraints.Constraint.greater_than (*self*, *candidate*)

Compares the calculated value to the minimum specified by the user.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
<i>candidate</i>	<i>float</i> The calculated value corresponding to a candidate design.

Returns

float: The penalty associated with the candidate design.

9.1.3.5 def Constraints.Constraint.less_or_equal (*self*, *candidate*)

Compares a previously calculated value to a user specified maximum including that maximum.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
<i>candidate</i>	<i>float</i> The calculated value corresponding to a candidate design.

Returns

float: The penalty associated with the candidate design.

9.1.3.6 def Constraints.Constraint.less_than (*self*, *candidate*)

Compares a previously calculated value to a user specified maximum excluding that maximum.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
<i>candidate</i>	<i>float</i> The calculated value corresponding to a candidate design.

Returns

float: The penalty associated with the candidate design.

9.1.3.7 def Constraints.Constraint.set_constraint_func (self, funcName)

Converts an input string name for a function to a function handle.

Parameters

<i>self</i>	<i>pointer</i> The Constraint pointer.
<i>funcName</i>	<i>string</i> A string identifying the constraint function to be used.

9.1.4 Member Data Documentation**9.1.4.1 Constraints.Constraint.constraint**

float: The constraint to be enforced.

9.1.4.2 Constraints.Constraint.func

function handle: The function handle for the constraint function to be used for the optimization.

The function must be specified as a method of the class.


The documentation for this class was generated from the following file:

- /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/[Constraints.py](#)

9.2 GnoweeUtilities.Event Class Reference

Represents a snapshot in the optimization process to be used for debugging, benchmarking, and user feedback.

Inheritance diagram for GnoweeUtilities.Event:



Public Member Functions

- `def __init__`
Constructor to build the [Event](#) class.
- `def __repr__`
[Event](#) print function.
- `def __str__`
Human readable [Event](#) print function.

Public Attributes

- [generation](#)
integer: The generation the design was arrived at.
- [evaluations](#)
integer: The number of fitness evaluations done to obtain this design.
- [fitness](#)
float: The assessed fitness for the current set of variables.
- [design](#)
array: The set of variables representing a design solution.

9.2.1 Detailed Description

Represents a snapshot in the optimization process to be used for debugging, benchmarking, and user feedback.

9.2.2 Constructor & Destructor Documentation

9.2.2.1 `def GnoweeUtilities.Event.__init__(self, generation, evaluations, fitness, design)`

Constructor to build the [Event](#) class.

Parameters

<i>self</i>	Event pointer The Event pointer.
<i>generation</i>	<i>integer</i> The generation the design was arrived at.
<i>evaluations</i>	<i>integer</i> The number of fitness evaluations done to obtain this design.
<i>fitness</i>	<i>float</i> The assessed fitness for the current set of variables.
<i>design</i>	<i>array</i> The set of variables representing a design solution.

9.2.3 Member Function Documentation

9.2.3.1 `def GnoweeUtilities.Event.__repr__(self)`

[Event](#) print function.

Parameters

<i>self</i>	<i>Event pointer</i> The <i>Event</i> pointer.
-------------	---

9.2.3.2 `def GnoweeUtilities.Event.__str__(self)`

Human readable *Event* print function.

Parameters

<i>self</i>	<i>Event pointer</i> The <i>Event</i> pointer.
-------------	---

9.2.4 Member Data Documentation

9.2.4.1 `GnoweeUtilities.Event.design`

array: The set of variables representing a design solution.

9.2.4.2 `GnoweeUtilities.Event.evaluations`

integer: The number of fitness evaluations done to obtain this design.

9.2.4.3 `GnoweeUtilities.Event.fitness`

float: The assessed fitness for the current set of variables.

9.2.4.4 `GnoweeUtilities.Event.generation`

integer: The generation the design was arrived at.


The documentation for this class was generated from the following file:

- `/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeUtilities.py`

9.3 GnoweeHeuristics.GnoweeHeuristics Class Reference

The class is the foundation of the *Gnowee* optimization algorithm.

Inheritance diagram for `GnoweeHeuristics.GnoweeHeuristics`:



Public Member Functions

- def `__init__`
Constructor to build the [GnoweeHeuristics](#) class.
- def `__repr__`
[GnoweeHeuristics](#) print function.
- def `__str__`
Human readable [GnoweeHeuristics](#) print function.
- def `initialize`
Initialize the population according to the sampling method chosen.
- def `disc_levy_flight`
Generate new children using truncated Levy flights permutation of current generation design parameters according to:
- def `cont_levy_flight`
Generate new children using Levy flights permutation of current generation design parameters according to:
- def `scatter_search`
Generate new designs using the scatter search heuristic according to:
- def `elite_crossover`
Generate new designs by using inver-over on combinatorial variables.
- def `crossover`
Generate new children using distance based crossover strategies on the top parent.
- def `mutate`
Generate new children by adding a weighted difference between two population vectors to a third vector.

Public Attributes

- `population`
integer The number of members in each generation.
- `initSampling`
string The method used to sample the phase space and create the initial population.
- `fracDiscovered`
float Discovery probability used for the [mutate\(\)](#) heuristic.
- `fracElite`
float Elite fraction probability used for the [scatter_search\(\)](#), [crossover\(\)](#), and [cont_crossover\(\)](#) heuristics.
- `fracLevy`
float Levy flight probability used for the [disc_levy_flight\(\)](#) and [cont_levy_flight\(\)](#) heuristics.
- `alpha`
float Levy exponent - defines the index of the distribution and controls scale properties of the stochastic process.
- `gamma`
float Gamma - scale unit of process for Levy flights.
- `n`
integer Number of independent variables - can be used to reduce Levy flight sampling variance.
- `scalingFactor`
float Step size scaling factor used to adjust Levy flights to length scale of system.
- `penalty`
float Individual constraint violation penalty to add to objective function.
- `maxGens`
integer The maximum number of generations to search.
- `maxFevals`
integer The maximum number of objective function evaluations.
- `convTol`

- float* The minimum change of the best objective value before the search terminates.
- [stallLimit](#)
integer The maximum number of generations to search without a decrease exceeding `convTol`.
- [optimalFitness](#)
float The best known fitness value for the problem considered used to test for convergence.
- [optConvTol](#)
float The maximum deviation from the best known fitness value before the search terminates.

9.3.1 Detailed Description

The class is the foundation of the [Gnowee](#) optimization algorithm.

It sets the settings required for the algorithm and defines the heuristics.

9.3.2 Constructor & Destructor Documentation

9.3.2.1 `def GnoweeHeuristics.GnoweeHeuristics.__init__(self, population = 25, initSampling = 'lhc', fracDiscovered = 0.2, fracElite = 0.2, fracLevy = 0.2, alpha = 1.5, gamma = 1, n = 1, scalingFactor = 10.0, penalty = 0.0, maxGens = 20000, maxFevals = 200000, convTol = 1e-6, stallLimit = 225, optimalFitness = 0, optConvTol = 1e-2)`

Constructor to build the [GnoweeHeuristics](#) class.

The default settings are found to be optimized for a wide range of problems, but can be changed to optimize performance for a particular problem type or class. For more details, refer to the benchmark code in the development branch of the repo or [<insert link="" to="" paper="">](#).

If the optimal fitness is unknown, as it often is, this can be left as zero or some reasonable guess based on the understanding of the problem. If the optimal fitness is set below what is actually obtainable, the only impact is the removal of this convergence criteria, and the program will still run.

Parameters

<i>self</i>	<i>GnoweeHeuristic pointer</i> The GnoweeHeuristics pointer.
<i>population</i>	<i>integer</i> The number of members in each generation.
<i>initSampling</i>	<i>string</i> The method used to sample the phase space and create the initial population. Valid options are 'random', 'nolh', 'nolh-rp', 'nolh-cdr', and 'lhc' as specified in <code>init_samples()</code> .
<i>fracDiscovered</i>	<i>: float</i> Discovery probability used for the mutate() heuristic.
<i>fracElite</i>	<i>float</i> Elite fraction probability used for the scatter_search() , crossover() , and <code>cont_crossover()</code> heuristics.

<i>fracLevy</i>	<i>float</i> Levy flight probability used for the disc_levy_flight() and cont_levy_flight() heuristics.
<i>alpha</i>	<i>float</i> Levy exponent - defines the index of the distribution and controls scale properties of the stochastic process.
<i>gamma</i>	<i>float</i> Gamma - scale unit of process for Levy flights.
<i>n</i>	<i>integer</i> Number of independent variables - can be used to reduce Levy flight sampling variance.
<i>penalty</i>	<i>float</i> Individual constraint violation penalty to add to objective function.
<i>scalingFactor</i>	<i>float</i> Step size scaling factor used to adjust Levy flights to length scale of system. The implementation of the Levy flight sampling makes this largely arbitrary.
<i>maxGens</i>	<i>integer</i> The maximum number of generations to search.
<i>maxFevals</i>	<i>integer</i> The maximum number of objective function evaluations.
<i>convTol</i>	<i>float</i> The minimum change of the best objective value before the search terminates.
<i>stallLimit</i>	<i>integer</i> The maximum number of generations to search without a decrease exceeding convTol.
<i>optimalFitness</i>	<i>float</i> The best know fitness value for the problem considered used to test for convergence.
<i>optConvTol</i>	<i>float</i> The maximum deviation from the best know fitness value before the search terminates.

9.3.3 Member Function Documentation

9.3.3.1 `def GnoweeHeuristics.GnoweeHeuristics.__repr__(self)`

[GnoweeHeuristics](#) print function.

Parameters

<i>self</i>	<i>GnoweeHeuristics pointer</i> The GnoweeHeuristics pointer.
-------------	--

9.3.3.2 `def GnoweeHeuristics.GnoweeHeuristics.__str__(self)`

Human readable [GnoweeHeuristics](#) print function.

Parameters

<i>self</i>	<i>GnoweeHeuristics</i> pointer The GnoweeHeuristics pointer.
-------------	--

9.3.3.3 `def GnoweeHeuristics.GnoweeHeuristics.cont_levy_flight (self, pop, lb, ub, varID)`

Generate new children using Levy flights permutation of current generation design parameters according to:

$$x_r^{g+1} = x_r^g + \frac{1}{\beta} L_{\alpha,\gamma},$$

where $L_{\alpha,\gamma}$ is calculated in [levy\(\)](#) according to the Mantegna algorithm. Applies [rejection_bounds\(\)](#) to ensure all solutions lie within the design space by adapting the step size to the size of the design space.

Parameters

<i>self</i>	<i>GnoweeHeuristic</i> pointer The GnoweeHeuristics pointer.
<i>pop</i>	<i>list of arrays</i> The current parent sets of design variables representing system designs for the population.
<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>varID</i>	<i>array</i> A truth array indicating the location of the variables to be permuted. If the variable is to be permuted, a 1 is inserted at the variable location; otherwise a 0.

Returns

list of arrays: The proposed children sets of design variables representing the updated design parameters.
list: A list of the identities of the chosen index for each child.

9.3.3.4 `def GnoweeHeuristics.GnoweeHeuristics.crossover (self, pop, lb, ub, varID, intDiscID=None)`

Generate new children using distance based crossover strategies on the top parent.

Ideas adapted from Walton "Modified Cuckoo Search: A New Gradient Free Optimisation Algorithm" and Storn "Differential Evolution - A Simple and Efficient Heuristic for Global Optimization over Continuous Spaces"

Parameters

<i>self</i>	<i>GnoweeHeuristic</i> pointer The GnoweeHeuristics pointer.
<i>pop</i>	<i>list of arrays</i> The current parent sets of design variables representing system designs for the population.

<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>varID</i>	<i>array</i> A truth array indicating the location of the variables to be permuted. If the variable is to be permuted, a 1 is inserted at the variable location; otherwise a 0.
<i>intDiscID</i>	<i>array</i> A truth array indicating the location of the discrete variable. A 1 is inserted at the discrete variable location; otherwise a 0. If no discrete variables, the array will be set to 0 automatically.

Returns

list of arrays: The proposed children sets of design variables representing the updated design parameters.
list: A list of the identities of the chosen index for each child.

9.3.3.5 def GnoweeHeuristics.GnoweeHeuristics.disc_levy_flight (self, pop, lb, ub, varID)

Generate new children using truncated Levy flights permutation of current generation design parameters according to:

$$L_{\alpha,\gamma} = \text{FLOOR}(TLF_{\alpha,\gamma} * D(x)),$$

where $TLF_{\alpha,\gamma}$ is calculated in [tlf\(\)](#). Applies [rejection_bounds\(\)](#) to ensure all solutions lie within the design space by adapting the step size to the size of the design space.

Parameters

<i>self</i>	<i>GnoweeHeuristic pointer</i> The GnoweeHeuristics pointer.
<i>pop</i>	<i>list of arrays</i> The current parent sets of design variables representing system designs for the population.
<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>varID</i>	<i>array</i> A truth array indicating the location of the variables to be permuted. If the variable is to be permuted, a 1 is inserted at the variable location; otherwise a 0.

Returns

list of arrays: The proposed children sets of design variables representing the updated design parameters.
list: A list of the identities of the chosen index for each child.

9.3.3.6 def GnoweeHeuristics.GnoweeHeuristics.elite_crossover (self, pop)

Generate new designs by using inver-over on combinatorial variables.

Adapted from ideas in Tao, "Iver-over Operator for the TSP."

Parameters

<i>self</i>	<i>GnoweeHeuristic pointer</i> The GnoweeHeuristics pointer.
<i>pop</i>	<i>list of arrays</i> The current parent sets of design variables representing system designs for the population.

Returns

list of arrays: The proposed children sets of design variables representing the updated design parameters.

9.3.3.7 def GnoweeHeuristics.GnoweeHeuristics.initialize (self, numSamples, sampleMethod, lb, ub, varType)

Initialize the population according to the sampling method chosen.

Parameters

<i>self</i>	<i>GnoweeHeuristic pointer</i> The GnoweeHeuristics pointer.
<i>numSamples</i>	<i>integer</i> The number of samples to be generated.
<i>sampleMethod</i>	<i>string</i> The method used to sample the phase space and create the initial population. Valid options are 'random', 'nolh', 'nolh-rp', 'nolh-cdr', and 'lhc' as specified in <code>init_samples()</code> .
<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>varType</i>	<i>array</i> The type of variable for each design parameter. Allowed values: 'c' = continuous 'i' = integer/binary (difference denoted by ub/lb) 'd' = discrete where the allowed values are given by the option <code>discreteVals</code> nxm array with n=# of discrete variables and m=# of values that can be taken for each variable 'x' = combinatorial. All of the variables denoted by x are assumed to be "swappable" in combinatorial permutations. There must be at least two variables denoted as combinatorial. 'f' = fixed design variable

Returns

list of arrays: The initialized set of samples.

9.3.3.8 def GnoweeHeuristics.GnoweeHeuristics.mutate (self, pop, lb, ub, varID, intDiscID = None)

Generate new children by adding a weighted difference between two population vectors to a third vector.

Ideas adapted from Storn, "Differential Evolution - A Simple and Efficient Heuristic for Global Optimization over Continuous Spaces" and Yang, "Nature Inspired Optimmmization Algorithms"

Parameters

<i>self</i>	<i>GnoweeHeuristic pointer</i> The GnoweeHeuristics pointer.
<i>pop</i>	<i>list of arrays</i> The current parent sets of design variables representing system designs for the population.
<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>varID</i>	<i>array</i> A truth array indicating the location of the variables to be permuted. If the variable is to be permuted, a 1 is inserted at the variable location; otherwise a 0.
<i>intDiscID</i>	<i>array</i> A truth array indicating the location of the discrete variable. A 1 is inserted at the discrete variable location; otherwise a 0. If no discrete variables, the array will be set to 0 automatically.

Returns

list of arrays: The proposed children sets of design variables representing the updated design parameters.

9.3.3.9 `def GnoweeHeuristics.GnoweeHeuristics.scatter_search (self, pop, lb, ub, varID, intDiscID=None)`

Generate new designs using the scatter search heuristic according to:

$$x^{g+1} = c_1 + (c_2 - c_1)r$$

where

$$c_1 = x^e - d(1 + \alpha\beta)$$

$$c_2 = x^e - d(1 - \alpha\beta)$$

$$d = \frac{x^r - x^e}{2}$$

and

$$\alpha = 1 \text{ if } i < j \text{ \& -1 if } i > j$$

$$\beta = \frac{|j-i|-1}{b-2}$$

where b is the size of the population.

Adapted from ideas in Egea, "An evolutionary method for complex- process optimization."

Applies [simple_bounds\(\)](#) to ensure all solutions lie within the design space by adapting the step size to the size of the design space.

Parameters

<i>self</i>	<i>GnoweeHeuristic pointer</i> The GnoweeHeuristics pointer.
-------------	---

<i>pop</i>	<i>list of arrays</i> The current parent sets of design variables representing system designs for the population.
<i>lb</i>	<i>array</i> The lower bounds of the design variable(s).
<i>ub</i>	<i>array</i> The upper bounds of the design variable(s).
<i>varID</i>	<i>array</i> A truth array indicating the location of the variables to be permuted. If the variable is to be permuted, a 1 is inserted at the variable location; otherwise a 0.
<i>intDiscID</i>	<i>array</i> A truth array indicating the location of the discrete variable. A 1 is inserted at the discrete variable location; otherwise a 0. If no discrete variables, the array will be set to 0 automatically.

Returns

list of arrays: The proposed children sets of design variables representing the updated design parameters.

list: A list of the identities of the chosen index for each child.

9.3.4 Member Data Documentation

9.3.4.1 GnoweeHeuristics.GnoweeHeuristics.alpha

float Levy exponent - defines the index of the distribution and controls scale properties of the stochastic process.

9.3.4.2 GnoweeHeuristics.GnoweeHeuristics.convTol

float The minimum change of the best objective value before the search terminates.

9.3.4.3 GnoweeHeuristics.GnoweeHeuristics.fracDiscovered

float Discovery probability used for the [mutate\(\)](#) heuristic.

9.3.4.4 GnoweeHeuristics.GnoweeHeuristics.fracElite

float Elite fraction probability used for the [scatter_search\(\)](#), [crossover\(\)](#), and [cont_crossover\(\)](#) heuristics.

9.3.4.5 GnoweeHeuristics.GnoweeHeuristics.fracLevy

float Levy flight probability used for the [disc_levy_flight\(\)](#) and [cont_levy_flight\(\)](#) heuristics.

9.3.4.6 GnoweeHeuristics.GnoweeHeuristics.gamma

float Gamma - scale unit of process for Levy flights.

9.3.4.7 GnoweeHeuristics.GnoweeHeuristics.initSampling

string The method used to sample the phase space and create the initial population.

Valid options are 'random', 'nolh', 'nolh-rp', 'nolh-cdr', and 'lhc' as specified in `init_samples()`.

9.3.4.8 GnoweeHeuristics.GnoweeHeuristics.maxFevals

integer The maximum number of objective function evaluations.

9.3.4.9 GnoweeHeuristics.GnoweeHeuristics.maxGens

integer The maximum number of generations to search.

9.3.4.10 GnoweeHeuristics.GnoweeHeuristics.n

integer Number of independent variables - can be used to reduce Levy flight sampling variance.

9.3.4.11 GnoweeHeuristics.GnoweeHeuristics.optConvTol

float The maximum deviation from the best know fitness value before the search terminates.

9.3.4.12 GnoweeHeuristics.GnoweeHeuristics.optimalFitness

float The best know fitness value for the problem considered used to test for convergence.

9.3.4.13 GnoweeHeuristics.GnoweeHeuristics.penalty

float Individual constraint violation penalty to add to objective function.

9.3.4.14 GnoweeHeuristics.GnoweeHeuristics.population

integer The number of members in each generation.

9.3.4.15 GnoweeHeuristics.GnoweeHeuristics.scalingFactor

float Step size scaling factor used to adjust Levy flights to length scale of system.

The implementation of the Levy flight sampling makes this largely arbitrary.

9.3.4.16 GnoweeHeuristics.GnoweeHeuristics.stallLimit

integer The maximum number of generations to search without a decrease exceeding `convTol`.


The documentation for this class was generated from the following file:

- `/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeHeuristics.py`

9.4 ObjectiveFunction.ObjectiveFunction Class Reference

The class creates a [ObjectiveFunction](#) object that can be used in optimization algorithms.

Inheritance diagram for `ObjectiveFunction.ObjectiveFunction`:



Public Member Functions

- def [__init__](#)
Constructor to build the [ObjectiveFunction](#) class.
- def [__repr__](#)
[ObjectiveFunction](#) class param print function.
- def [__str__](#)
Human readable [ObjectiveFunction](#) print function.
- def [set_obj_func](#)
Converts an input string name for a function to a function handle.
- def [spring](#)
Spring objective function with penalty method of constraint enforcement.
- def [mi_spring](#)
Spring objective function with penalty method of constraint enforcement.
- def [welded_beam](#)
Welded Beam objective function with penalty method of constraint enforcement.
- def [pressure_vessel](#)
Pressure vessel objective function with penalty method of constraint enforcement.
- def [mi_pressure_vessel](#)
Mixed Integer Pressure vessel objective function with penalty method of constraint enforcement.
- def [speed_reducer](#)
Speed reducer objective function with penalty method of constraint enforcement.
- def [mi_chemical_process](#)
Chemical process design mixed integer problem.
- def [ackley](#)
Ackley Function: Multimodal, n dimensional.
- def [shifted_ackley](#)
Ackley Function: Multimodal, n dimensional Ackley Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.
- def [dejong](#)
De Jong Function: Unimodal, n -dimensional.
- def [shifted_dejong](#)
De Jong Function: Unimodal, n -dimensional De Jong Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.
- def [easom](#)
Easom Function: Multimodal, n -dimensional.
- def [shifted_easom](#)
Easom Function: Multimodal, n -dimensional Easom Function that is shifted from the symmetric π , π optimum.
- def [griewank](#)
Griewank Function: Multimodal, n -dimensional.
- def [shifted_griewank](#)
Griewank Function: Multimodal, n -dimensional Griewank Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.
- def [rastrigin](#)
Rastrigin Function: Multimodal, n -dimensional.

- def [shifted_rastrigin](#)
Rastrigin Function: Multimodal, n-dimensional Rastrigin Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.
- def [rosenbrock](#)
Rosenbrock Function: uni-modal, n-dimensional.
- def [shifted_rosenbrock](#)
Rosenbrock Function: uni-modal, n-dimensional Rosenbrock Function that is shifted from the symmetric 0,0,0...0 optimum.
- def [tsp](#)
Generic objective funtion to evaluate the TSP optimization by calculating total distance traveled.

Public Attributes

- [func](#)
function handle The function handle for the objective function to be used for the optimization.
- [objective](#)
integer, float, or numpy array The desired outcome of the optimization.

9.4.1 Detailed Description

The class creates a [ObjectiveFunction](#) object that can be used in optimization algorithms.

9.4.2 Constructor & Destructor Documentation

9.4.2.1 `def ObjectiveFunction.ObjectiveFunction.__init__(self, method = None, objective = None)`

Constructor to build the [ObjectiveFunction](#) class.

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>method</i>	<i>string</i> The name of the objective function to evaluate.
<i>objective</i>	<i>integer, float, or numpy array</i> The desired objective associated with the optimization. The chosen value and type must be compatible with the optiization function chosen.

9.4.3 Member Function Documentation

9.4.3.1 `def ObjectiveFunction.ObjectiveFunction.__repr__(self)`

[ObjectiveFunction](#) class param print function.

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
-------------	--

9.4.3.2 `def ObjectiveFunction.ObjectiveFunction.__str__(self)`

Human readable [ObjectiveFunction](#) print function.

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
-------------	--

9.4.3.3 `def ObjectiveFunction.ObjectiveFunction.ackley (self, u, penalty = 0.0)`

Ackley Function: Multimodal, n dimensional.

Optimal example:

$u = [0, 0, 0, 0, \dots, n-1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.4 `def ObjectiveFunction.ObjectiveFunction.dejong (self, u, penalty = 0.0)`

De Jong Function: Unimodal, n-dimensional.

Optimal example:

$u = [0, 0, 0, 0, \dots, n-1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.

<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.
----------------	--

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.5 `def ObjectiveFunction.ObjectiveFunction.easom (self, u, penalty = 0.0)`

Easom Function: Multimodal, n-dimensional.

Optimal example:

`u = [pi, pi]`

`fitness = 1.0`

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.6 `def ObjectiveFunction.ObjectiveFunction.griewank (self, u, penalty = 0.0)`

Griewank Function: Multimodal, n-dimensional.

Optimal example:

`u = [0, 0, 0, ..., 0]`

`fitness = 0.0`

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
-------------	--

<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.7 `def ObjectiveFunction.ObjectiveFunction.mi_chemical_process (self, u, penalty=1E15)`

Chemical process design mixed integer problem.

Optimal example:

`u = [(0.2, 0.8, 1.907878, 1, 1, 0, 1]`

`fitness = 4.579582`

Taken from: "An Improved PSO Algorithm for Solving Non-convex NLP/MINLP Problems with Equality Constraints"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated. [x1, x2, x3, y1, y2, y3, y4]
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.8 `def ObjectiveFunction.ObjectiveFunction.mi_pressure_vessel (self, u, penalty=1E15)`

Mixed Integer Pressure vessel objective function with penalty method of constraint enforcement.

Near optimal example:

`u = [58.2298, 44.0291, 17, 9]`

`fitness = 7203.24`

Optimal example obtained with [Gnowee](#):

`u = [38.819876, 221.985576, 0.750000, 0.375000]`

`fitness = 5855.893191`

Taken from: "Nonlinear Integer and Discrete Programming in Mechanical Design Optimization"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.9 `def ObjectiveFunction.ObjectiveFunction.mi_spring (self, u, penalty = 1E15)`

Spring objective function with penalty method of constraint enforcement.

Optimal Example:

`u = [1.22304104, 9, 36] = [1.22304104, 9, 0.307]`

`fitness = 2.65856`

Taken from Lampinen, "Mixed Integer-Discrete-Continuous Optimization by Differential Evolution"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.10 `def ObjectiveFunction.ObjectiveFunction.pressure_vessel (self, u, penalty = 1E15)`

Pressure vessel objective function with penalty method of constraint enforcement.

Near Optimal Example:

`u = [0.81250000001, 0.4375, 42.098445595854923, 176.6365958424394]`

`fitness = 6059.714335`

Optimal obtained using [Gnowee](#):

`u = [0.7781686880924992, 0.3846491857203429, 40.319621144688995, 199.99996630362293]`

`fitness = 5885.33285347`

Taken from: "Solving Engineering Optimization Problems with the Simple Constrained Particle Swarm Optimizer"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.
array: The assessed value for each constraint for the specified input.

9.4.3.11 `def ObjectiveFunction.ObjectiveFunction.rastrigin (self, u, penalty = 0.0)`

Rastrigin Function: Multimodal, n-dimensional.

Optimal example:

$u = [0, 0, 0, \dots, 0]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.
array: The assessed value for each constraint for the specified input.

9.4.3.12 `def ObjectiveFunction.ObjectiveFunction.rosenbrock (self, u, penalty = 0.0)`

Rosenbrock Function: uni-modal, n-dimensional.

Optimal example:

$u = [1, 1, 1, \dots, 1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.13 `def ObjectiveFunction.ObjectiveFunction.set_obj_func (self, funcName)`

Converts an input string name for a function to a function handle.

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>funcName</i>	<i>string</i> A string identifying the objective function to be used.

9.4.3.14 `def ObjectiveFunction.ObjectiveFunction.shifted_ackley (self, u, penalty = 0.0)`

Ackley Function: Multimodal, n dimensional Ackley Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.

Optimal example:

$u = [0, 1, 2, 3, \dots, n-1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.
array: The assessed value for each constraint for the specified input.

9.4.3.15 `def ObjectiveFunction.ObjectiveFunction.shifted_dejong (self, u, penalty = 0.0)`

De Jong Function: Unimodal, n-dimensional De Jong Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.

Optimal example:

$u = [0, 1, 2, 3, \dots, n-1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Taken from: "Solving Engineering Optimization Problems with the Simple Constrained Particle Swarm Optimizer"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.
array: The assessed value for each constraint for the specified input.

9.4.3.16 `def ObjectiveFunction.ObjectiveFunction.shifted_easom (self, u, penalty = 0.0)`

Easom Function: Multimodal, n-dimensional Easom Function that is shifted from the symmetric π , π optimum.

Optimal example:

$u = [\pi, \pi+1]$

fitness = 1.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.

<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.
----------------	--

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.17 `def ObjectiveFunction.ObjectiveFunction.shifted_griewank (self, u, penalty = 0.0)`

Griewank Function: Multimodal, n-dimensional Griewank Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.

Optimal example:

$u = [0, 1, 2, \dots, n-1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.18 `def ObjectiveFunction.ObjectiveFunction.shifted_rastrigin (self, u, penalty = 0.0)`

Rastrigin Function: Multimodal, n-dimensional Rastrigin Function that is shifted from the symmetric 0, 0, 0, ..., 0 optimum.

Optimal example:

$u = [0, 1, 2, \dots, n-1]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.19 def ObjectiveFunction.ObjectiveFunction.shifted_rosenbrock (self, u, penalty = 0.0)

Rosenbrock Function: uni-modal, n-dimensional Rosenbrock Function that is shifted from the symmetric 0,0,0...0 optimum.

Optimal example:

$u = [1, 2, 3, \dots, n]$

fitness = 0.0

Taken from: "Nature-Inspired Optimization Algorithms"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.20 def ObjectiveFunction.ObjectiveFunction.speed_reducer (self, u, penalty = 1E15)

Speed reducer objective function with penalty method of constraint enforcement.

Optimal example:

$u = [58.2298, 44.0291, 17, 9]$

fitness = 2996.34784914

Optimal example obtained with [Gnowee](#):

$u = [3.500000, 0.7, 17, 7.300000, 7.800000, 3.350214, 5.286683]$

fitness = 5855.893191

Taken from: "Solving Engineering Optimization Problems with the Simple Constrained Particle Swarm Optimizer"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.21 `def ObjectiveFunction.ObjectiveFunction.spring (self, u, penalty = 1E15)`

Spring objective function with penalty method of constraint enforcement.

Optimal Example:

`u = [0.05169046, 0.356750, 11.287126]`

fitness = 0.0126653101469

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.22 `def ObjectiveFunction.ObjectiveFunction.tsp (self, u, penalty = 0.0)`

Generic objective function to evaluate the TSP optimization by calculating total distance traveled.

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
-------------	--

<i>u</i>	<i>array</i> The city pairs to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty. Not used for this function; included for method input consistency.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.3.23 `def ObjectiveFunction.ObjectiveFunction.welded_beam (self, u, penalty = 1E15)`

Welded Beam objective function with penalty method of constraint enforcement.

Optimal Example:

`u = [0.20572965, 3.47048857, 9.0366249, 0.20572965]`

`fitness = 1.7248525603892848`

Taken from: "Solving Engineering Optimization Problems with the Simple Constrained Particle Swarm Optimizer"

Parameters

<i>self</i>	<i>pointer</i> The ObjectiveFunction pointer.
<i>u</i>	<i>array</i> The design parameters to be evaluated.
<i>penalty</i>	<i>float</i> Per constraint violation penalty.

Returns

array: The fitness associated with the specified input.

array: The assessed value for each constraint for the specified input.

9.4.4 Member Data Documentation**9.4.4.1 ObjectiveFunction.ObjectiveFunction.func**

function handle The function handle for the objective function to be used for the optimization.

The function must be specified as a method of the class.

9.4.4.2 ObjectiveFunction.ObjectiveFunction.objective

integer, float, or numpy array The desired outcome of the optimization.


The documentation for this class was generated from the following file:

- `/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/ObjectiveFunction.py`

9.5 GnoweeUtilities.Parent Class Reference

The class contains all of the parameters pertinent to a member of the population.

Inheritance diagram for GnoweeUtilities.Parent:



Public Member Functions

- `def __init__`
Constructor to build the [Parent](#) class.
- `def __repr__`
[Parent](#) print function.
- `def __str__`
Human readable [Parent](#) print function.

Public Attributes

- [variables](#)
array: The set of variables representing a design solution.
- [fitness](#)
float: The assessed fitness for the current set of variables.
- [changeCount](#)
integer: The number of improvements to the current population member.
- [stallCount](#)
integer: he number of evaluations since the last improvement.

9.5.1 Detailed Description

The class contains all of the parameters pertinent to a member of the population.

9.5.2 Constructor & Destructor Documentation

9.5.2.1 `def GnoweeUtilities.Parent.__init__(self, variables=None, fitness=1E15, changeCount=0, stallCount=0)`

Constructor to build the [Parent](#) class.

Parameters

<i>self</i>	Parent pointer The Parent pointer.
-------------	---

<i>variables</i>	<i>array</i> The set of variables representing a design solution.
<i>fitness</i>	<i>float</i> The assessed fitness for the current set of variables.
<i>changeCount</i>	<i>integer</i> The number of improvements to the current population member.
<i>stallCount</i>	<i>integer</i> The number of evaluations since the last improvement.

9.5.3 Member Function Documentation

9.5.3.1 def GnoweeUtilities.Parent.__repr__(self)

[Parent](#) print function.

Parameters

<i>self</i>	<i>Parent pointer</i> The Parent pointer.
-------------	--

9.5.3.2 def GnoweeUtilities.Parent.__str__(self)

Human readable [Parent](#) print function.

Parameters

<i>self</i>	<i>Parent pointer</i> The Parent pointer.
-------------	--

9.5.4 Member Data Documentation

9.5.4.1 GnoweeUtilities.Parent.changeCount

integer: The number of improvements to the current population member.

9.5.4.2 GnoweeUtilities.Parent.fitness

float: The assessed fitness for the current set of variables.

9.5.4.3 GnoweeUtilities.Parent.stallCount

integer: he number of evaluations since the last improvement.

9.5.4.4 GnoweeUtilities.Parent.variables

array: The set of variables representing a design solution.


The documentation for this class was generated from the following file:

- [/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeUtilities.py](#)

9.6 GnoweeUtilities.ProblemParameters Class Reference

Creates an object containing key features of the chosen optimization problem.

Inheritance diagram for GnoweeUtilities.ProblemParameters:



Public Member Functions

- `def __init__`
- `def __repr__`
ProblemParameters class attribute print function.
- `def __str__`
Human readable ProblemParameters print function.
- `def get_preset_params`
Instantiates a ProblemParameters object and populations member variables from a set of predefined problem types.

Public Attributes

- `lb`
array: The lower bounds of the design variable(s).
- `ub`
array: The upper bounds of the design variable(s).
- `varType`
array: The type of variable for each position in the upper and lower bounds array.
- `discreteVals`
array: nxm with n=# of discrete variables and m=# of values that can be taken for each variable.
- `optimum`
float: The global optimal solution.
- `pltTitle`
string: The title used for plotting the results of the optimization.
- `histTitle`
string: The plot title for the histogram of the optimization results.
- `varNames`
list of strings: The names of the variables for the optimization problem.

9.6.1 Detailed Description

Creates an object containing key features of the chosen optimization problem.

The methods provide a way of predefining problems for repeated use.

9.6.2 Constructor & Destructor Documentation

9.6.2.1 `def GnoweeUtilities.ProblemParameters.__init__(self, lowerBounds = [], upperBounds = [], varType = [], discreteVals = [], optimum = 0.0, pltTitle = "", histTitle = "", varNames = "")`

Parameters

<i>self</i>	<i>pointer</i> The ProblemParameters pointer.
<i>lowerBounds</i>	<i>array</i> The lower bounds of the design variable(s). Only enter the bounds for continuous and integer/binary variables. The order must match the order specified in varType and ub.
<i>upperbounds</i>	<i>array</i> The upper bounds of the design variable(s). Only enter the bounds for continuous and integer/binary variables. The order must match the order specified in varType and lb.
<i>varType</i>	<i>list or array</i> The type of variable for each position in the upper and lower bounds array. Discrete variables are to be included last as they are specified separately from the lb/ub through the discreteVals optional input. A variable can have two types (for example, 'dx' could denote a layer that can take multiple materials and be placed at multiple design locations) Allowed values: 'c' = continuous over a given range (range specified in lb & ub). 'i' = integer/binary (difference denoted by ub/lb). 'd' = discrete where the allowed values are given by the option discreteVals nxm array with n=# of discrete variables and m=# of values that can be taken for each variable. 'x' = combinatorial. All of the variables denoted by x are assumed to be "swappable" in combinatorial permutations. There must be at least two variables denoted as combinatorial. 'f' = fixed design variable. Will not be considered of any permutation.
<i>discreteVals</i>	<i>list of list(s)</i> nxm with n=# of discrete variables and m=# of values that can be taken for each variable. For example, if you had two variables representing the tickness and diameter of a cylinder that take standard values, the discreteVals could be specified as: discreteVals = [[0.125, 0.25, 0.375], [0.25, 0.5, 0.75]] Gnowee will then map the optimization results to these allowed values.
<i>optimum</i>	<i>float</i> The global optimal solution.
<i>pltTitle</i>	<i>string</i> The title used for plotting the results of the optimization.
<i>histTitle</i>	<i>string</i> The plot title for the histogram of the optimization results.
<i>varNames</i>	<i>list of strings</i> The names of the variables for the optimization problem.

9.6.3 Member Function Documentation

9.6.3.1 `def GnoweeUtilities.ProblemParameters.__repr__(self)`

[ProblemParameters](#) class attribute print function.

Parameters

<i>self</i>	<i>pointer</i> The ProblemParameters pointer.
-------------	--

9.6.3.2 def GnoweeUtilities.ProblemParameters.__str__(self)

Human readable [ProblemParameters](#) print function.

Parameters

<i>self</i>	<i>pointer</i> The ProblemParameters pointer.
-------------	--

9.6.3.3 def GnoweeUtilities.ProblemParameters.get_preset_params(self, funct, algorithm = "", dimension = 2)

Instantiates a [ProblemParameters](#) object and populations member variables from a set of predefined problem types.

Parameters

<i>self</i>	<i>pointer</i> The ProblemParameters pointer.
<i>funct</i>	<i>string</i> Name of function being optimized.
<i>algorithm</i>	<i>string</i> Name of optimization program used.
<i>dimension</i>	<i>integer</i> Used to set the dimension for scalable problems.

Returns

[ProblemParameters](#) object: A [ProblemParameters](#) object with populated member variables.

9.6.4 Member Data Documentation

9.6.4.1 GnoweeUtilities.ProblemParameters.discreteVals

array: nxm with n=# of discrete variables and m=# of values that can be taken for each variable.

9.6.4.2 GnoweeUtilities.ProblemParameters.histTitle

string: The plot title for the histogram of the optimization results.

9.6.4.3 GnoweeUtilities.ProblemParameters.lb

array: The lower bounds of the design variable(s).

9.6.4.4 GnoweeUtilities.ProblemParameters.optimum

float: The global optimal solution.

9.6.4.5 GnoweeUtilities.ProblemParameters.pltTitle

string: The title used for plotting the results of the optimization.

9.6.4.6 def GnoweeUtilities.ProblemParameters.ub

array: The upper bounds of the design variable(s).

9.6.4.7 GnoweeUtilities.ProblemParameters.varNames

list of strings: The names of the variables for the optimization problem.

9.6.4.8 GnoweeUtilities.ProblemParameters.varType

array: The type of variable for each position in the upper and lower bounds array.


The documentation for this class was generated from the following file:

- /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/[GnoweeUtilities.py](#)

9.7 GnoweeUtilities.Switch Class Reference

Creates a switch class object to switch between cases.

Inheritance diagram for GnoweeUtilities.Switch:



Public Member Functions

- def [__init__](#)
Case constructor.
- def [__iter__](#)
Return the match method once, then stop.
- def [match](#)
Indicate whether or not to enter a case suite.

Public Attributes

- [value](#)
string: Case selector value.
- [fall](#)
boolean: Match indicator.

9.7.1 Detailed Description

Creates a switch class object to switch between cases.

9.7.2 Constructor & Destructor Documentation

9.7.2.1 def GnoweeUtilities.Switch.__init__(self, value)

Case constructor.

Parameters

<i>self</i>	<i>pointer</i> The Switch pointer.
<i>value</i>	<i>string</i> Case selector value.

9.7.3 Member Function Documentation

9.7.3.1 def GnoweeUtilities.Switch.__iter__(self)

Return the match method once, then stop.

Parameters

<i>self</i>	<i>pointer</i> The Switch pointer.
-------------	---

9.7.3.2 def GnoweeUtilities.Switch.match(self, args)

Indicate whether or not to enter a case suite.

Parameters

<i>self</i>	<i>pointer</i> The Switch pointer.
<i>*args</i>	<i>list</i> List of comparisons.

Returns

boolean: Outcome of comparison match

9.7.4 Member Data Documentation

9.7.4.1 GnoweeUtilities.Switch.fall

boolean: Match indicator.

9.7.4.2 GnoweeUtilities.Switch.value


string: Case selector value.

The documentation for this class was generated from the following file:

- /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/[GnoweeUtilities.py](#)

9.8 GnoweeUtilities.WeightedRandomGenerator Class Reference

Inheritance diagram for GnoweeUtilities.WeightedRandomGenerator:



Public Member Functions

- `def __init__`
- `def next`
- `def __call__`

Public Attributes

- `totals`

9.8.1 Detailed Description

Defines a class of weights to be used to select number of instances in array randomly with linear weighting.

```
Parameters
=====
self : object
    Current instance of the class
weights : array
    The array of weights (Higher = more likely to be selected)

Returns
=====
bisect.bisect_right(self.totals, rnd) : integer
    The randomly selected index of the weights array
```

The documentation for this class was generated from the following file:

- `/home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeUtilities.py`

Chapter 10

File Documentation

10.1 /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Constraints.py File Reference

Classes

- class [Constraints.Constraint](#)

The class creates a Constraints object that can be used in optimization algorithms.

10.2 /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Gnowee.py File Reference

Namespaces

- [Gnowee](#)

Contains the [Gnowee](#) optimization program and associated utilities.

Functions

- def [Gnowee.main](#)

Main controller program for the [Gnowee](#) optimization.

10.3 /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeHeuristics.py File Reference

Classes

- class [GnoweeHeuristics.GnoweeHeuristics](#)

The class is the foundation of the [Gnowee](#) optimization algorithm.

Namespaces

- [Gnowee](#)

Contains the [Gnowee](#) optimization program and associated utilities.

Functions

- def [GnoweeHeuristics.simple_bounds](#)
Application of problem boundaries to generated solutions.
- def [GnoweeHeuristics.rejection_bounds](#)
Application of problem boundaries to generated solutions.

10.4 /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/GnoweeUtilities.py File Reference

Classes

- class [GnoweeUtilities.Parent](#)
The class contains all of the parameters pertinent to a member of the population.
- class [GnoweeUtilities.Event](#)
Represents a snapshot in the optimization process to be used for debugging, benchmarking, and user feedback.
- class [GnoweeUtilities.ProblemParameters](#)
Creates an object containing key features of the chosen optimization problem.
- class [GnoweeUtilities.Switch](#)
Creates a switch class object to switch between cases.
- class [GnoweeUtilities.WeightedRandomGenerator](#)

Namespaces

- [Gnowee](#)
Contains the [Gnowee](#) optimization program and associated utilities.

Functions

- def **GnoweeUtilities.Get_Best**

10.5 /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Objective-Function.py File Reference

Classes

- class [ObjectiveFunction.ObjectiveFunction](#)
The class creates a [ObjectiveFunction](#) object that can be used in optimization algorithms.

Namespaces

- [Gnowee](#)
Contains the [Gnowee](#) optimization program and associated utilities.

Functions

- def [ObjectiveFunction.prod](#)
Computes the product of a set of numbers (ie big PI, multiplicative equivalent to sum).

10.6 /home/pyne-user/Dropbox/UCB/Research/ETAs/Design/Gnowee/src/Sampling.py File Reference

Namespaces

- [Gnowee](#)
Contains the [Gnowee](#) optimization program and associated utilities.

Functions

- def [Sampling.initial_samples](#)
Generate a set of samples in a given phase space.
- def [Sampling.plot_samples](#)
Plot the first 2 and 3 dimensions on the sample distribution.
- def [Sampling.levy](#)
Sample the Levy distribution given by.
- def [Sampling.tlf](#)
Samples from a truncated Levy flight distribution (TLF) according to Manegna, "Stochastic Process with Ultraslow Convergence to a Gaussian: The Truncated Levy Flight" to map a levy distribution onto the interval [0,1].
- def [Sampling.NOLH](#)
This library allows to generate Nearly Orthogonal Latin Hypercubes (NOLH) according to Cioppa (2007) and De Rainville et al.
- def [Sampling.params](#)
Returns the NOLH order \$m\$, the required configuration length \$q\$ and the number of columns to remove to obtain the desired dimensionality.
- def [Sampling.get_cdr_permutations](#)
Generate a set of CDR permutations for NOLH.

Variables

- tuple **`Sampling.parser`**
- string **`Sampling.help`** = "The configuration vector given as a list N1 N2 ... Nm"
- tuple **`Sampling.args`** = `parser.parse_args()`

Index

/home/pyne-user/Dropbox/UCB/Research/ETAs/-
Design/Gnowee/src/Constraints.py, 65
/home/pyne-user/Dropbox/UCB/Research/ETAs/-
Design/Gnowee/src/Gnowee.py, 65
/home/pyne-user/Dropbox/UCB/Research/ETAs/-
Design/Gnowee/src/GnoweeHeuristics.py, 65
/home/pyne-user/Dropbox/UCB/Research/ETAs/-
Design/Gnowee/src/GnoweeUtilities.py, 66
/home/pyne-user/Dropbox/UCB/Research/ETAs/-
Design/Gnowee/src/ObjectiveFunction.py, 66
/home/pyne-user/Dropbox/UCB/Research/ETAs/-
Design/Gnowee/src/Sampling.py, 67
__init__
 Constraints::Constraint, 28
 GnoweeHeuristics::GnoweeHeuristics, 34
 GnoweeUtilities::Event, 31
 GnoweeUtilities::Parent, 56
 GnoweeUtilities::ProblemParameters, 59
 GnoweeUtilities::Switch, 63
 ObjectiveFunction::ObjectiveFunction, 43
__iter__
 GnoweeUtilities::Switch, 63
__repr__
 Constraints::Constraint, 28
 GnoweeHeuristics::GnoweeHeuristics, 35
 GnoweeUtilities::Event, 31
 GnoweeUtilities::Parent, 57
 GnoweeUtilities::ProblemParameters, 60
 ObjectiveFunction::ObjectiveFunction, 43
__str__
 Constraints::Constraint, 28
 GnoweeHeuristics::GnoweeHeuristics, 35
 GnoweeUtilities::Event, 32
 GnoweeUtilities::Parent, 57
 GnoweeUtilities::ProblemParameters, 61
 ObjectiveFunction::ObjectiveFunction, 43
ackley
 ObjectiveFunction::ObjectiveFunction, 45
alpha
 GnoweeHeuristics::GnoweeHeuristics, 40
changeCount
 GnoweeUtilities::Parent, 57
constraint
 Constraints::Constraint, 30
Constraints, 13
Constraints.Constraint, 27
Constraints::Constraint
 __init__, 28
 __repr__, 28
 __str__, 28
 constraint, 30
 func, 30
 get_penalty, 28
 greater_than, 29
 less_or_equal, 29
 less_than, 29
 set_constraint_func, 30
cont_levy_flight
 GnoweeHeuristics::GnoweeHeuristics, 36
convTol
 GnoweeHeuristics::GnoweeHeuristics, 40
crossover
 GnoweeHeuristics::GnoweeHeuristics, 36
dejong
 ObjectiveFunction::ObjectiveFunction, 45
design
 GnoweeUtilities::Event, 32
disc_levy_flight
 GnoweeHeuristics::GnoweeHeuristics, 37
discreteVals
 GnoweeUtilities::ProblemParameters, 61
easom
 ObjectiveFunction::ObjectiveFunction, 46
elite_crossover
 GnoweeHeuristics::GnoweeHeuristics, 37
evaluations
 GnoweeUtilities::Event, 32
fall
 GnoweeUtilities::Switch, 63
fitness
 GnoweeUtilities::Event, 32
 GnoweeUtilities::Parent, 57
fracDiscovered
 GnoweeHeuristics::GnoweeHeuristics, 40
fracElite
 GnoweeHeuristics::GnoweeHeuristics, 40
fracLevy
 GnoweeHeuristics::GnoweeHeuristics, 40
func
 Constraints::Constraint, 30
 ObjectiveFunction::ObjectiveFunction, 55
gamma
 GnoweeHeuristics::GnoweeHeuristics, 40

- generation
 - GnoweeUtilities::Event, 32
- get_cdr_permutations
 - Sampling, 20
- get_penalty
 - Constraints::Constraint, 28
- get_preset_params
 - GnoweeUtilities::ProblemParameters, 61
- Gnowee, 14, 25
 - main, 14
- GnoweeHeuristics, 16
 - rejection_bounds, 16
 - simple_bounds, 17
- GnoweeHeuristics.GnoweeHeuristics, 32
- GnoweeHeuristics::GnoweeHeuristics
 - __init__, 34
 - __repr__, 35
 - __str__, 35
 - alpha, 40
 - cont_levy_flight, 36
 - convTol, 40
 - crossover, 36
 - disc_levy_flight, 37
 - elite_crossover, 37
 - fracDiscovered, 40
 - fracElite, 40
 - fracLevy, 40
 - gamma, 40
 - initSampling, 40
 - initialize, 38
 - maxFevals, 41
 - maxGens, 41
 - mutate, 38
 - n, 41
 - optConvTol, 41
 - optimalFitness, 41
 - penalty, 41
 - population, 41
 - scalingFactor, 41
 - scatter_search, 39
 - stallLimit, 41
- GnoweeUtilities, 18
- GnoweeUtilities.Event, 30
- GnoweeUtilities.Parent, 56
- GnoweeUtilities.ProblemParameters, 58
- GnoweeUtilities.Switch, 62
- GnoweeUtilities.WeightedRandomGenerator, 64
- GnoweeUtilities::Event
 - __init__, 31
 - __repr__, 31
 - __str__, 32
 - design, 32
 - evaluations, 32
 - fitness, 32
 - generation, 32
- GnoweeUtilities::Parent
 - __init__, 56
 - __repr__, 57
 - __str__, 57
 - changeCount, 57
 - fitness, 57
 - stallCount, 57
 - variables, 57
- GnoweeUtilities::ProblemParameters
 - __init__, 59
 - __repr__, 60
 - __str__, 61
 - discreteVals, 61
 - get_preset_params, 61
 - histTitle, 61
 - lb, 61
 - optimum, 61
 - pltTitle, 61
 - ub, 62
 - varNames, 62
 - varType, 62
- GnoweeUtilities::Switch
 - __init__, 63
 - __iter__, 63
 - fall, 63
 - match, 63
 - value, 63
- greater_than
 - Constraints::Constraint, 29
- griewank
 - ObjectiveFunction::ObjectiveFunction, 46
- histTitle
 - GnoweeUtilities::ProblemParameters, 61
- initSampling
 - GnoweeHeuristics::GnoweeHeuristics, 40
- initial_samples
 - Sampling, 20
- initialize
 - GnoweeHeuristics::GnoweeHeuristics, 38
- lb
 - GnoweeUtilities::ProblemParameters, 61
- less_or_equal
 - Constraints::Constraint, 29
- less_than
 - Constraints::Constraint, 29
- levy
 - Sampling, 21
- main
 - Gnowee, 14
- match
 - GnoweeUtilities::Switch, 63
- maxFevals
 - GnoweeHeuristics::GnoweeHeuristics, 41
- maxGens
 - GnoweeHeuristics::GnoweeHeuristics, 41
- mi_chemical_process
 - ObjectiveFunction::ObjectiveFunction, 47
- mi_pressure_vessel

- ObjectiveFunction::ObjectiveFunction, 47
- mi_spring
 - ObjectiveFunction::ObjectiveFunction, 48
- mutate
 - GnoweeHeuristics::GnoweeHeuristics, 38
- n
 - GnoweeHeuristics::GnoweeHeuristics, 41
- NOLH
 - Sampling, 21
- objective
 - ObjectiveFunction::ObjectiveFunction, 55
- ObjectiveFunction, 19
 - prod, 19
- ObjectiveFunction.ObjectiveFunction, 41
- ObjectiveFunction::ObjectiveFunction
 - __init__, 43
 - __repr__, 43
 - __str__, 43
 - ackley, 45
 - dejong, 45
 - easom, 46
 - func, 55
 - griewank, 46
 - mi_chemical_process, 47
 - mi_pressure_vessel, 47
 - mi_spring, 48
 - objective, 55
 - pressure_vessel, 48
 - rastrigin, 49
 - rosenbrock, 49
 - set_obj_func, 50
 - shifted_ackley, 50
 - shifted_dejong, 51
 - shifted_easom, 51
 - shifted_griewank, 52
 - shifted_rastrigin, 52
 - shifted_rosenbrock, 53
 - speed_reducer, 53
 - spring, 54
 - tsp, 54
 - welded_beam, 55
- optConvTol
 - GnoweeHeuristics::GnoweeHeuristics, 41
- optimalFitness
 - GnoweeHeuristics::GnoweeHeuristics, 41
- optimum
 - GnoweeUtilities::ProblemParameters, 61
- params
 - Sampling, 22
- penalty
 - GnoweeHeuristics::GnoweeHeuristics, 41
- plot_samples
 - Sampling, 22
- pltTitle
 - GnoweeUtilities::ProblemParameters, 61
- population
 - GnoweeHeuristics::GnoweeHeuristics, 41
- pressure_vessel
 - ObjectiveFunction::ObjectiveFunction, 48
- prod
 - ObjectiveFunction, 19
- rastrigin
 - ObjectiveFunction::ObjectiveFunction, 49
- rejection_bounds
 - GnoweeHeuristics, 16
- rosenbrock
 - ObjectiveFunction::ObjectiveFunction, 49
- Sampling, 20
 - get_cdr_permutations, 20
 - initial_samples, 20
 - levy, 21
 - NOLH, 21
 - params, 22
 - plot_samples, 22
 - tlf, 22
- scalingFactor
 - GnoweeHeuristics::GnoweeHeuristics, 41
- scatter_search
 - GnoweeHeuristics::GnoweeHeuristics, 39
- set_constraint_func
 - Constraints::Constraint, 30
- set_obj_func
 - ObjectiveFunction::ObjectiveFunction, 50
- shifted_ackley
 - ObjectiveFunction::ObjectiveFunction, 50
- shifted_dejong
 - ObjectiveFunction::ObjectiveFunction, 51
- shifted_easom
 - ObjectiveFunction::ObjectiveFunction, 51
- shifted_griewank
 - ObjectiveFunction::ObjectiveFunction, 52
- shifted_rastrigin
 - ObjectiveFunction::ObjectiveFunction, 52
- shifted_rosenbrock
 - ObjectiveFunction::ObjectiveFunction, 53
- simple_bounds
 - GnoweeHeuristics, 17
- speed_reducer
 - ObjectiveFunction::ObjectiveFunction, 53
- spring
 - ObjectiveFunction::ObjectiveFunction, 54
- stallCount
 - GnoweeUtilities::Parent, 57
- stallLimit
 - GnoweeHeuristics::GnoweeHeuristics, 41
- tlf
 - Sampling, 22
- tsp
 - ObjectiveFunction::ObjectiveFunction, 54
- ub
 - GnoweeUtilities::ProblemParameters, 62

value
 GnoweeUtilities::Switch, [63](#)
varNames
 GnoweeUtilities::ProblemParameters, [62](#)
varType
 GnoweeUtilities::ProblemParameters, [62](#)
variables
 GnoweeUtilities::Parent, [57](#)

welded_beam
 ObjectiveFunction::ObjectiveFunction, [55](#)