

Package ‘iMKT’

December 29, 2017

Title McDonald and Kreitman Test and its extensions calculation

Version 0.1.1

Date 2017-12-01

Description McDonald and Kreitman Test and its extensions.

Author Sergi Hervas <sergi.hervas@uab.cat>
Marta Coronado <marta.coronado@uab.cat>
Jesús Murga <jesus.murga@uab.cat>

Maintainer Jesús Murga <jesus.murga@uab.cat>

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

Depends R (>= 3.3), ggplot2,

Imports knitr, utils, stats, cowplot, reshape2, nls2, MASS, ggthemes

VignetteBuilder knitr

NeedsCompilation no

R topics documented:

asymptoticMK	2
checkInput	3
completeMKT	3
DGRP	4
FWW	5
iMK	6
loadPopFly	7
loadPopHuman	8
mydafdata	8
mydivergencedata	9
PopFlyAnalysis	9
PopHumanAnalysis	10
standard	11
themePublication	12

Index**13**

asymptoticMK

*asymptoticMK***Description**

asymptoticMK developed in "Haller BC, Messer PW. asymptoticMK: A Web-Based Tool for the Asymptotic McDonald-Kreitman Test. G3 (Bethesda). 2017 May 5;7(5):1569-1575". Adapted from: <http://github.com/MesserLab/asymptoticMK>

Usage

```
asymptoticMK(daf, divergence, xlow, xhigh, seed)
```

Arguments

daf	data frame containing DAF, Pi and P0 values
divergence	data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes
xlow	lower limit for asymptotic alpha fit
xhigh	higher limit for asymptotic alpha fit
seed	seed value (optional). No seed by default

Details

The standard McDonald and Kreitman test (MKT) is used to detect the signature of selection at the molecular level. The MKT compares the amount of variation within a species (polymorphism, P) to the divergence (D) between species at two types of sites, one of which is putatively neutral and used as the reference to detect selection at the other type of site. In the standard MKT, these sites are synonymous (putatively neutral, 0) and non-synonymous sites (selected sites, i) in a coding region. Under strict neutrality, the ratio of the number of selected and neutral polymorphic sites (P_i/P_0) is equal to the ratio of the number of selected and neutral divergence sites (D_i/D_0).

Value

Estimation of alpha asymptotic value and details of the model fit

Examples

```
asymptoticMK(mydafdata, mydivergencedata, 0, 0.9)
```

checkInput	<i>checkInput</i>
------------	-------------------

Description

Check input data and return detailed errors when it is malformed.

Usage

checkInput(daf, divergence, xlow, xhigh)

Arguments

daf	data frame containing DAF, Pi and P0 values
divergence	data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes
xlow	lower limit for asymptotic alpha fit
xhigh	higher limit for asymptotic alpha fit

Details

This function checks input data used in most package’s functions (arguments daf, divergence, xlow and xhigh) and returns a brief description of the error(s) found. If data does not pass check_input() the requested analysis is not performed.

Value

None

completeMKT	<i>completeMKT</i>
-------------	--------------------

Description

completeMKT() put details here

Usage

completeMKT(daf, divergence, xlow, xhigh, seed)

Arguments

daf	data frame containing DAF, Pi and P0 values
divergence	data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes
xlow	lower limit for asymptotic alpha fit
xhigh	higher limit for asymptotic alpha fit
seed	seed value (optional). No seed by default

Details

put description here

Value

Execute all the MKT extensions

Examples

completeMKT(mydafdata, mydivergencedata, 0, 0.9)

DGRP	<i>DGRP</i>
------	-------------

Description

DGRP() Perform MKT corrected with DGRP method

Usage

DGRP(daf, divergence, list_cutoffs = c(0, 0.05, 0.1), plot = FALSE)

Arguments

daf	data frame containing DAF, Pi and P0 values
divergence	data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes
list_cutoffs	list of cutoffs to use (optional). Default cutoffs are: 0, 0.05, 0.1
plot	report plot (optional). Default is FALSE

Details

The standard McDonald and Kreitman test (MKT) is used to detect the signature of selection at the molecular level. The MKT compares the amount of variation within a species (polymorphism, P) to the divergence (D) between species at two types of sites, one of which is putatively neutral and used as the reference to detect selection at the other type of site. In the standard MKT, these sites are synonymous (putatively neutral, 0) and non-synonymous sites (selected sites, i) in a coding region. Under strict neutrality, the ratio of the number of selected and neutral polymorphic sites (P_i/P_0) is equal to the ratio of the number of selected and neutral divergence sites (D_i/D_0). The null hypothesis of neutrality is rejected in a MKT when $D_i/D_0 > P_i/P_0$. The excess of divergence relative to polymorphism for class i , is interpreted as adaptive selection for a subset of sites i . The fraction of adaptive fixations, α , is estimated from $1 - (P_i/P_0)(D_0/D_i)$. The significance of the test can be assessed with a Fisher exact test. The estimate of α can be easily biased by the segregation of slightly deleterious non-synonymous substitutions. Specifically, slightly deleterious mutations tend to contribute more to polymorphism than to divergence, and thus, lead to an underestimation of α . Because adaptive mutations and weakly deleterious selection act in opposite directions on the MKT, α and the fraction of substitutions that are slightly deleterious, b , will be both underestimated when the two selection regimes occur. To take adaptive and slightly deleterious mutations mutually into account, P_i , the count of segregating sites in class i , should be separated into the number of neutral variants and the number of weakly deleterious variants, $P_i = P_{i\text{neutral}} + P_{i\text{weak del}}$. α is then estimated as $1 - (P_{i\text{neutral}}/P_0)(D_0/D_i)$.

Value

MKT corrected by the DGRP method. List with α results, graph, divergence metrics, MKT tables and negative selection fractions

Examples

```
## Using default cutoffs
DGRP(mydafdata, mydivergencedata)
## Using custom cutoffs
DGRP(mydafdata, mydivergencedata, c(0.05, 0.1, 0.15))
```

FWW

FWW

Description

FWW() Perform MKT corrected with FWW method

Usage

```
FWW(daf, divergence, list_cutoffs = c(0, 0.05, 0.1), plot = FALSE)
```

Arguments

daf	data frame containing DAF, Pi and P0 values
divergence	data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes
list_cutoffs	list of cutoffs to use (optional). Default cutoffs are: 0, 0.05, 0.1
plot	report plot (optional). Default is FALSE

Details

The standard McDonald and Kreitman test (MKT) is used to detect the signature of selection at the molecular level. The MKT compares the amount of variation within a species (polymorphism, P) to the divergence (D) between species at two types of sites, one of which is putatively netral and used as the reference to detect selection at the other type of site. In the standard MKT, these sites are synonymous (putatively neutral, 0) and non-synonymous sites (selected sites, i) in a coding region. Under strict neutrality, the ratio of the number of selected and neutral polymorphic sites (P_i/P_0) is equal to the ratio of the number of selected and neutral divergence sites (D_i/D_0). The null hypothesis of neutrality is rejected in a MKT when $D_i/D_0 > P_i/P_0$. The excess of divergence relative to polymorphism for class i, is interpreted as adaptive selection for a subset of sites i. The fraction of adaptive fixations, `alpha.symbol`, is estimated from $1-(P_i/P_0)(D_s/D_n)$. The significance of the test can be assesed with a Fisher exact test.The estimate of `alpha.symbol` can be easily biased by the segregation of slightly deleterious non-synonymous substitutions. Specifically, slightly deleterious mutations tend to contribute more to polymorphism than to divergence, and thus, lead to an under-estimation of alpha. Bevause they tend to segregate at lower frequencies than do neutral mutations, they can be apartially controled for by removing low frequency polymorphisms from the analysis (Fay et al. 2001). This is known as the FWW method.

Value

MKT corrected by the FWW method

Examples

```
## Using default cutoffs
FWW(mydafdata, mydivergencedata)
## Using custom cutoffs and rendering plot
FWW(mydafdata, mydivergencedata, c(0.05, 0.1, 0.15), plot=TRUE)
```

iMK	<i>iMK</i>
-----	------------

Description

iMK: alpha asymptotic + negative selection (d,b,f)
#details details here

Usage

```
iMK(daf, divergence, xlow, xhigh, seed, plot = FALSE)
```

Arguments

daf	data frame containing DAF, Pi and P0 values
divergence	data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes
xlow	lower limit for asymptotic alpha fit
xhigh	higher limit for asymptotic alpha fit
seed	seed value (optional). No seed by default
plot	report plots of daf, alpha and negative selection fractions (optional). Default is FALSE

Value

iMK

Examples

```
## Without plot
iMK(mydafdata, mydivergencedata, 0, 0.9)
## With plot
iMK(mydafdata, mydivergencedata, 0, 0.9, plot=TRUE)
```

loadPopFly

loadPopFly

Description

Load PopFly dataset

Usage

```
loadPopFly()
```

Details

This function loads PopFly data (<http://popfly.uab.cat/>) into the current workspace. Data is stored in a dataframe named PopFlyData.

Value

None

Examples

```
# loadPopFly()
```

loadPopHuman	<i>loadPopHuman</i>
--------------	---------------------

Description

Load PopHuman dataset

Usage

```
loadPopHuman()
```

Details

This function loads PopHuman data (<http://pophuman.uab.cat/>) into the current workspace. Data is stored in a dataframe named PopFlyData.

Value

None

Examples

```
# loadPopHuman()
```

mydafdata	<i>Example data frames</i>
-----------	----------------------------

Description

Data frame containing divergence sample data to execute the functions

- daf. derived allele frequency (DAF) categories
- Pi. number of selected polymorphic sites for each daf category
- P0. number of neutral polymorphic sites for each daf category

Usage

```
mydafdata
```

Format

A data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes

mydivergencedata	<i>Example data frames</i>
------------------	----------------------------

Description

Data frame containing divergence sample data to execute the functions

- mi. number of selected analyzed sites
- Di. number of selected divergent sites (fixed differences)
- m0. number of neutral analyzed sites
- D0. number of neutral divergent sites (fixed differences)

Usage

```
mydivergencedata
```

Format

A data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes

PopFlyAnalysis	<i>PopFlyAnalysis</i>
----------------	-----------------------

Description

Perform any MK test using a subset of PopFly data defined by custom genes and populations lists

Usage

```
PopFlyAnalysis(genes = c("gene1", "gene2", "..."), pops = c("pop1", "pop2",
  "..."), recomb = TRUE/FALSE, bins = 0, test = c("standard", "DGRP",
  "FWW", "asymptotic", "iMK"), xlow = 0, xhigh = 1)
```

Arguments

genes	list of genes
pops	list of populations
recomb	group genes according to recombination values (must specify number of bins). TRUE/FALSE. Recomb values (cM/Mb) from Comeron et al. 2012.
bins	number of recombination bins to compute (mandatory if recomb = TRUE)
test	which test to perform. Options include: standard (default), DGRP, FWW, asymptotic, iMK
xlow	lower limit for asymptotic alpha fit (default=0)
xhigh	higher limit for asymptotic alpha fit (default=1)

Details

Recombination values (recomb=T) from Comeron et al. 2012 (reference!)

Value

None

Examples

```
## List of genes
# mygenes <- c("FBgn0053196", "FBgn0086906", "FBgn0261836", "FBgn0031617",
#             "FBgn0260965", "FBgn0028899", "FBgn0052580", "FBgn0036181",
#             "FBgn0263077", "FBgn0013733", "FBgn0031857", "FBgn0037836")
## Perform analyses
# PopFlyAnalysis(genes=mygenes , pops=c("RAL","ZI"), recomb=F, test="iMK", xlow=0, xhigh=0.9)
# PopFlyAnalysis(genes=mygenes , pops=c("RAL","ZI"), recomb=T, bins=3, test="DGRP")
```

PopHumanAnalysis

PopHumanAnalysis

Description

Perform any MK test using a subset of PopHuman data defined by custom genes and populations lists

Usage

```
PopHumanAnalysis(genes = c("gene1", "gene2", "..."), pops = c("pop1",
  "pop2", "..."), recomb = TRUE/FALSE, bins = 0, test = c("standard",
  "DGRP", "FWW", "asymptotic", "iMK"), xlow = 0, xhigh = 1)
```

Arguments

genes	list of genes
pops	list of populations
recomb	group genes according to recombination values (must specify number of bins). TRUE/FALSE. Recomb values (cM/Mb) from Bheller et al.
bins	number of recombination bins to compute (mandatory if recomb = TRUE)
test	which test to perform. Options include: standard (default), DGRP, FWW, asymptotic, iMK
xlow	lower limit for asymptotic alpha fit (default=0)
xhigh	higher limit for asymptotic alpha fit (default=1)

Details

Recombination values (recomb=T) from Bheller et al. (reference!)

Value

None

Examples

```
## List of genes
# mygenes <- c("AHNAK2", "MUC5B", "MUC4", "TTN", "MUC16", "PLIN4",
#             "OBSCN", "PLEC", "MUC12", "PKD1", "LAMA5", "HELZ2")
## Perform analyses
# PopHumanAnalysis(genes=mygenes , pops=c("CEU", "YRI"), recomb=F, test="standard")
# PopHumanAnalysis(genes=mygenes , pops=c("CEU"), recomb=T, bins=3, test="DGRP")
```

standard	<i>mkt_standard</i>
----------	---------------------

Description

mkt_standard() MKT standard formula

Usage

```
standard(daf, divergence)
```

Arguments

- daf data frame containing DAF, Pi and P0 values
- divergence data frame containing divergent and analyzed sites for selected (i) and neutral (0) classes

Details

The standard McDonald and Kreitman test (MKT) is used to detect the signature of selection at the molecular level. The MKT compares the amount of variation within a species (polymorphism, P) to the divergence (D) between species at two types of sites, one of which is putatively netral and used as the reference to detect selection at the other type of site. In the standard MKT, these sites are synonymous (putatively neutral, 0) and non-synonymous sites (selected sites, i) in a coding region. Under strict neutrality, the ratio of the number of selected and neutral polymorphic sites (Pi/P0) is equal to the ratio of the number of selected and neutral divergence sites (Di/D0).

Value

Standard McDonald and Kreitman Test

Examples

```
standard(mydafdata, mydivergencedata)
```

themePublication	<i>ggplot theme for publication ready Plots</i>
------------------	---

Description

Date = 04/07/2015 Author = Koundinya Desiraju

Usage

```
themePublication(base_size = 14, base_family = "sans")
```

Arguments

base_size	base size required from themePublication
base_family	font to load in themePublication

Details

Default theme used for plot images. From <http://rpubs.com/Koundy/71792>

Value

plot theme

Examples

```
# themePublication(14, "sans")
```

Index

*Topic **datasets**

mydafdata, [8](#)

mydivergencedata, [9](#)

asymptoticMK, [2](#)

checkInput, [3](#)

completeMKT, [3](#)

DGRP, [4](#)

FWW, [5](#)

iMK, [6](#)

loadPopFly, [7](#)

loadPopHuman, [8](#)

mydafdata, [8](#)

mydivergencedata, [9](#)

PopFlyAnalysis, [9](#)

PopHumanAnalysis, [10](#)

standard, [11](#)

themePublication, [12](#)