


An - Yang Speckle Filter



The screenshot shows the 'Speckle Filter' window with the following settings:

- Input Directory:** D:/My_Data_Directory
- Output Directory:** D:/My_Data_Directory_PRE / T3
- Init Row:** 1, **End Row:** 900, **Init Col:** 1, **End Col:** 1024
- Filter Name:** W. AN and J. YANG - Non Local Pretest Filter
- Output Format:** [S2] >> [T3] (selected)
- Number of Looks:** 1, **K Coefficient:** 20
- Patch Window Size Row:** 3, **Searching Window Size Row:** 15
- Patch Window Size Col:** 3, **Searching Window Size Col:** 15
- System Noise Filtering (HV / VH):** unchecked
- Buttons:** Run, Help (question mark), Exit

Description:

This function is used to apply a Polarimetric Speckle filtering on polarimetric raw binary data.

The proposed polarimetric Speckle Filter is :

- W. AN & J. YANG - Non Local Pretest Filter.

According to the input data format, indicated in the widget, different compatible output data formats are proposed according the following table:

Input Data Format	Output Data Format
(2x2) Sinclair matrix [S2]	[T3], [T4], [C3], [C4]
(3x3) Coherency matrix [T3]	[T3]
(4x4) Coherency matrix [T4]	[T4]
(2x2) Covariance matrix [C2]	[C2]
(3x3) Covariance matrix [C3]	[C3]
(4x4) Covariance matrix [C4]	[C4]
Dual Polarimetric Elements (Sxx, Sxy)	[C2]

Comments:

Parameters written in Red can be modified directly by the user from the keyboard.

Input/Output Arguments:

Input Directory	Indicates the location of the considered Main Directory (MD) containing the polarimetric data sets to be filtered.
Output Directory	Indicates the location of the filtered data output directory. The default value is set automatically to : Main Directory_PRE / YY , where YY is associated with the Output Data Format (C2 , C3 , C4 , T3 or T4).

Output Image Number of Rows/Columns:

The output image numbers of rows and columns are initialised to the input data set dimensions.

Users wishing to process a sub-part of the initial image can modify the **Init** and **End** values of the converted images rows and columns.

Note: init and end values have to remain within the range defined by the input image dimensions.

Filtering Parameters:

Window size (Patch and Search)	Users have to set the size of the (N*N) sliding window used to compute the local estimate of the average matrix. The default value of N is set to 3 for the Patch Window and to 15 for the Search Window.
Number of Looks	Users have to set the Input data equivalent number of looks used to compute the a priori input speckle noise variance. The default value of N is set to 1.

Note : The W. AN & J. YANG - Non Local Pretest Filter functionality is a contribution by :

*J. Chen, W. An, Y. Cui, J. Yang
Department of Electronic Engineering
Tsinghua University
Beijing 100084
China*

*Y. Chen
Department of Electrical Engineering and Computer Science
University of Michigan
Ann Arbor
MI 48109-2122 USA*