Routee DB 구조 - YB 20242220 이나연

```sql
-- ============================================================
-- 1. 사용자 테이블
-- ============================================================
CREATE TABLE users (
    user_id        BIGINT AUTO_INCREMENT PRIMARY KEY,
    username       VARCHAR(50)  NOT NULL UNIQUE,
    password       VARCHAR(255),
    email          VARCHAR(100) NOT NULL UNIQUE,
    role           VARCHAR(20)  NOT NULL DEFAULT 'ROLE_USER',
    provider       VARCHAR(20)  NOT NULL DEFAULT 'local',
    provider_id    VARCHAR(255),
    profile_image  VARCHAR(512),
    created_at     DATETIME NOT NULL,
    updated_at     DATETIME NOT NULL
);
```

```sql
-- ============================================================
-- 2. 장소 캐싱 테이블
-- ============================================================
CREATE TABLE places (
    place_id                BIGINT AUTO_INCREMENT PRIMARY KEY,
    google_place_id         VARCHAR(255) NOT NULL UNIQUE,
    place_name              VARCHAR(150) NOT NULL,
    address                 VARCHAR(255),
    latitude                DOUBLE NOT NULL,
    longitude               DOUBLE NOT NULL,
    category                VARCHAR(100),
    phone_number            VARCHAR(30),
    website                 VARCHAR(500),
    rating                  DOUBLE,
    opening_hours_json      TEXT,
    opening_hours_updated_at DATETIME
);
```

```sql
-- ============================================================
-- 3. 북마크 커스텀 폴더 테이블
-- ============================================================
CREATE TABLE folders (
    folder_id   BIGINT AUTO_INCREMENT PRIMARY KEY,
    folder_name VARCHAR(100) NOT NULL,
    user_id     BIGINT NOT NULL,
    created_at  DATETIME NOT NULL,
    FOREIGN KEY (user_id) REFERENCES users(user_id) ON DELETE CASCADE
);

-- ============================================================
-- 4. 폴더별 저장된 장소 매핑 테이블
-- ============================================================
CREATE TABLE folder_places (
    folder_place_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    folder_id       BIGINT NOT NULL,
    place_id        BIGINT NOT NULL,
    created_at      DATETIME NOT NULL,
    FOREIGN KEY (folder_id) REFERENCES folders(folder_id) ON DELETE CASCADE,
    FOREIGN KEY (place_id)  REFERENCES places(place_id)   ON DELETE CASCADE,
    UNIQUE KEY unique_folder_place (folder_id, place_id)
);


-- ============================================================
-- 5. 일정 메인 테이블
-- ============================================================
CREATE TABLE schedules (
    schedule_id  BIGINT AUTO_INCREMENT PRIMARY KEY,
    title        VARCHAR(150) NOT NULL,
    destination  VARCHAR(100),
    member_count INT NOT NULL DEFAULT 1,
    start_date   DATE NOT NULL,
    end_date     DATE NOT NULL,
    user_id      BIGINT NOT NULL,
    created_at   DATETIME NOT NULL,
    updated_at   DATETIME NOT NULL,
    FOREIGN KEY (user_id) REFERENCES users(user_id) ON DELETE CASCADE
);
```

```sql
-- ============================================================
-- 6. 일정별 상세 타임라인 테이블
-- ============================================================
CREATE TABLE timeline_items (
    timeline_item_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    schedule_id      BIGINT NOT NULL,
    place_id         BIGINT NOT NULL,
    visit_order      INT    NOT NULL,
    visit_date       DATE   NOT NULL,
    visit_time       TIME,
    end_time         TIME,
    conflict_warning TINYINT(1) NOT NULL DEFAULT 0,
    memo             VARCHAR(500),
    FOREIGN KEY (schedule_id) REFERENCES schedules(schedule_id) ON DELETE CASCADE,
    FOREIGN KEY (place_id)    REFERENCES places(place_id)       ON DELETE CASCADE
);


-- ============================================================
-- 7. 일정별 임시 보관함 (좋아요 → 일정으로 불러올 장소)
-- ============================================================
CREATE TABLE schedule_tmp_places (
    tmp_place_id BIGINT AUTO_INCREMENT PRIMARY KEY,
    schedule_id  BIGINT NOT NULL,
    place_id     BIGINT NOT NULL,
    created_at   DATETIME NOT NULL,
    FOREIGN KEY (schedule_id) REFERENCES schedules(schedule_id) ON DELETE CASCADE,
    FOREIGN KEY (place_id)    REFERENCES places(place_id)       ON DELETE CASCADE,
    UNIQUE KEY unique_schedule_place (schedule_id, place_id)
);
```

```sql
-- ============================================================
-- 8. 여행 다이어리 테이블
-- ============================================================
CREATE TABLE diaries (
    diary_id     BIGINT AUTO_INCREMENT PRIMARY KEY,
    user_id      BIGINT       NOT NULL,
    schedule_id  BIGINT       NOT NULL UNIQUE,  -- 일정당 다이어리 1개
    content      TEXT,                          -- 본문
    emoji        VARCHAR(10)  DEFAULT '✈',      -- 대표 이모지
    cover_color  VARCHAR(50)  DEFAULT '#4F46E5', -- 커버 색상
    photos_json  LONGTEXT,                      -- base64 사진 JSON 배열
    created_at   DATETIME     NOT NULL,
    updated_at   DATETIME     NOT NULL,
    FOREIGN KEY (user_id)     REFERENCES users(user_id)         ON DELETE CASCADE,
    FOREIGN KEY (schedule_id) REFERENCES schedules(schedule_id) ON DELETE CASCADE
);
```