			892.	4				le	owbw.ini	load be		bration				213	5				def	fault lime	e calibrat	tion	
	88	72	48		1	0	-16	88	72	48	24	0	-16	88	72	48	24	0	-16	88	72	48	24	0	-1
40 39					۵	600						24000						24000							3100
36					6	900						16000						16000							2400
33 32						000						10000						10000							1600
30 28						500						6800						6800							1000
27 24				40000 36000) 1	.800					36000	4300					36000	4300							650
21				24000		200					29000	2300	620				27000	2700	555						440
18 16				16400)	950	145				26000	1700	390				23000	1744	350						310
15 12				11800 8400		680 470	100				20400	1230	246				16600	1111	230				32000		200
9 8				6000)	333					13900		152				10700	705	150				22000		132
6				4200)	235					8900	510					6800	450						36000	83
3			34000 28700			169 125					5700	320	70				4300	280	68				10000	2400	51
-3 -4			20000			90				31100	3680	200	70			32400	2700	185	50				6500	1600	32
-6			14500	1070)																	05000			
-8 -9			10200							19700	2350	83				20250	1680	120	36			35000	4100	1000	21
-12 -15			7260 5100													12000	1050	80				22000	2600	650	15
-16 -18		40000	3000	250)					12300	900					8000	660					11000	1600	400	
-20 -21		34000	2500	186	õ					7800	550					5100	422					8900	1000	260	
-24 -27		26700 18900	1800 1260							4900	340				32000	3220	277					5600	630	160	
-28 -30		13500	890	72	2				38000	3200	220				28000	2020	177					3500	400	100	
-32 -33		9600	633						27900	1950	145				18000	1200	116					2200	250		
-36 -39		6900 5000	440 300	45	5				17800	1250	95				11500	830	75					1400	160		
-40 -42		3500	220						11200	750	65				7300	520					1300	870	100		
-44	35000	2600	150						7200	500				30000	4600	350					8400	550	70		
-48	26300	1900	150						4900	333				25000	2900	222					5300	360	50		
-52	18600	1400						29000	3400	222				16000	1800	150					3400	230			
-56	13200	1135						19000	2400	111				10000	1200	111				3200	2200	160			
-57 -60	9400 6800	900 700						12000	1800					6300	830	78				2000	1400				
-63 -64	4900							7800	1500					4000	650	58				12500	980				
-66 -68	3500							5200	1300					2500	590					8000	700				
-69 -72	2500 1900							3500						1600	490					5000					
-75 -76	1400							2500						1050						3200					
-78 -80	1000							1900						700						2100					
-81 -84	900 700							1500						500						1400					
-87	500																								
-88 -90	500							1100						400						1000					
-92 -96 -120																				700 500					