

Patrick S. Li psli@eecs.berkeley.edu

Adam M. Izraelevitz adamiz@eecs.berkeley.edu

Jonathan Bachrach

jrb@eecs.berkeley.edu

June 23, 2015

Contents

1	Introduction - IN PROGRESS 1.1 Background	
2	Acknowledgements - IN PROGRESS	5
3	FIRRTL Language Definition 3.1 Abstract Syntax Tree	
4	Circuits and Modules	8
5	Types 5.1 Ground Types	Ć

6	Stat	tements	10						
	6.1	Wires	11						
	6.2	Registers	11						
	6.3	Memories	11						
	6.4	Nodes	12						
	6.5	Accessors	12						
	6.6	Instances	13						
	6.7	The Connect Statement	15						
	6.8	The On-Reset Connect Statement	15						
	6.9	The Bulk Connect Statement	16						
	6.10	The Sub-Word Connect Statement	16						
	6.11	The Conditional Statement	17						
		6.11.1 Initialization Coverage	17						
		6.11.2 Scoping	17						
		6.11.3 Connect Semantics - IN PROGRESS	18						
	6.12	Statement Groups	18						
		6.12.1 Last Connect Semantics	18						
	6.13	The Assert Statement	18						
	6.14	The Empty Statement	19						
7	Expressions 19								
	7.1	Unsigned Integers	19						
	7.2	Signed Integers	19						
	7.3	References	20						
	7.4	Subfields	20						
	7.5	Subindex	20						
	7.6	Primitive Operation	20						
8	Prir	mitive Operations	20						
	8.1	Add Operation	21						
	8.2	Subtract Operation	21						
	8.3	Add Wrap Operation							
	8.4	Subtract Wrap Operation	22						
	8.5	Multiply Operation	22						
	8.6	Divide Operation	22						
	8.7	Modulus Operation	23						
	8.8	Quotient Operation	23						
	8.9	Remainder Operation	23						
	0.0								

	8.10	Comparison Operations	24		
	8.11	Equality Comparison	24		
	8.12	Not-Equality Comparison	24		
	8.13	Multiplex	25		
	8.14	Padding Operation	25		
	8.15	Reinterpret Bits as UInt	25		
	8.16	Reinterpret Bits as SInt	26		
	8.17	Shift Left Operation	26		
	8.18	Shift Right Operation	26		
		Dynamic Shift Left Operation			
		Dynamic Shift Right Operation	27		
	8.21	Logical Convert to Signed	27		
		Negate	27		
		Bitwise Operations			
		Reduce Bitwise Operations	28		
	8.25	Concatenation	28		
		Bit Extraction Operation	28		
	8.27	Bit Range Extraction Operation	29		
9	FIR	RTL Forms	29		
	9.1	Resolved Form	29		
	9.2	Lowered Form	29		
10	Ann	notations - IN PROGRESS	31		
11	Con	crete Syntax	31		
12 Design Justification - IN PROGRESS					

1 Introduction - IN PROGRESS

1.1 Background

The ideas for FIRRTL originated from a different UC Berkeley project, Chisel, which embedded a hardware description language in Scala and was used to write highly-parameterized circuit designs. (TODO - explain how the concepts of Chisel are great)

At UC Berkeley, Chisel provided the infrastructure to support computer architecture research, including vector machines, out-of-order processors, silicon photonics and cache coherency. Many of these projects were successfully taped-out in actual silicon - our research productivity proved to us the validity of our design methodology. (TODO - Number of students and timeline) However, Chisel's external rate of adoption was slow for the following reasons:

- 1. Learning a functional language (Scala) was a large barrier to entry
- 2. Conceptually separating the Chisel HDL from the host language was difficult for new users
- 3. Verilog generation was unreadable and slow
- 4. Writing transformational passes required insider knowledge of the Chisel compiler
- 5. Compiler design was unstructured, making error checking difficult and error messages often uncomprehensible
- 6. Chisel IR semantics were ill-defined and thus impossible to target from other languages

As a consequence, we felt Chisel needed to be redesigned from its ground up to standardize its IR and semantics, modularize its compilation process for robustness, and cleanly separate its frontend (Chisel + Scala), internal representation (FIRRTL), and backends.

1.2 Design Philosophy

FIRRTL represents the formalized elaborated graph that the Chisel DSL produces, prior to any simplification. By including complicated constructs like vector types, bundle types, and when statements in FIRRTL, the Chisel/Scala frontend can be very light-weight. In addition, other front-ends written in languages other than Scala could be simple to write and increase external adoption.

Lowered FIRRTL represents a simplified FIRRTL circuit with structural invariants, making it essentially a netlist. This form enables straightforward translation into another language (e.g. Verilog) by a light-weight backend.

By defining low FIRRTL as a structured subset of FIRRTL, an external user can write a transformational pass whose input is restricted, but whose output is full-featured. After a custom pass, the resulting circuit should undergo lowering prior to passing it to a backend or another custom pass.

2 Acknowledgements - IN PROGRESS

The FIRRTL language could not have been developed without the help of many of the faculty and students in the ASPIRE lab, including but not limited to XXXX. We'd also like to thank our sponsors XXXX, and the UC Berkeley University.

3 FIRRTL Language Definition

3.1 Abstract Syntax Tree

```
circuit id : (module*)
                                                      Circuit
                 [info] module id : (port* stmt)
                                                      Module
   module
              | [info] exmodule id : (port*)
                                                      External Module
             = [info] kind id : type
                                                      Port
      port
             = input|output|clk
                                                      Port Kind
      kind
             = UInt < width >
                                                      Unsigned Integer
      type
                SInt<width>
                                                      Signed Integer
                 \{field*\}
                                                      Bundle
                 type[int]
                                                      Vector
             = orientation id : type
                                                      Bundle Field
      field
orientation
             = default|reverse
                                                      Orientation
             = int|?
                                                      Known/Unknown Integer Width
     width
                [info] wire id : type
                                                      Wire Declaration
      stmt
                 [info] reg id: type, id, exp
                                                      Register Declaration
                                                      Sequential Memory Declaration
                 [info] smem id : type, id
                                                      Combinational Memory Declaration
                 [info] cmem id : type, id
                 [info] inst id : id , id*
                                                      Instance Declaration
                                                      Node Declaration
                 [info] node id = exp
                 [info] dir accessor id = exp[exp]
                                                      Accessor Declaration
                 [info] exp := exp
                                                      Connect
                                                      On-Reset Connect
                 [info] onreset exp := exp
                 [info] exp <> exp
                                                      Bulk Connect
                 [info] exp[int through int] := exp
                                                      Sub-Word Connect
                 [info] when exp : stmt else : stmt
                                                      Conditional
                 [info] assert exp
                                                      Assert Statement
                 [info] skip
                                                      Empty Statement
                 [info] (stmt*)
                                                      Statement Group
             = infer|read|write|rdwr
                                                      Accessor Direction
        dir
                 [info] UInt < width > (ints)
                                                      Literal Unsigned Integer
                 [info] SInt < width > (ints)
                                                      Literal Signed Integer
                 [info] id
                                                      Reference
                 [info] exp.id
                                                      Subfield
                 [info] exp[int]
                                                      Subindex
                 [info] primop(exp*, int*)
                                                      Primitive Operation
       info
                 filename: line.col
                                                      File Location
                 noinfo
                                                      No File Location
```

primop	=	add	Unsigned/Signed Add
		sub	Unsigned/Signed Subtract
	ĺ	addw	Unsigned/Signed Add Wrap
	ĺ	\mathbf{subw}	Unsigned/Signed Subtract Wrap
	ĺ	\mathbf{mul}	Unsigned/Signed Multiply
	Ì	\mathbf{div}	Unsigned/Signed Divide
	ĺ	mod	Unsigned/Signed Modulo
	ĺ	quo	Unsigned/Signed Quotient
	ĺ	rem	Unsigned/Signed Remainder
	ĺ	\mathbf{lt}	Unsigned/Signed Less Than
	ĺ	\mathbf{leq}	Unsigned/Signed Less or Equal
		${f gt}$	Unsigned/Signed Greater Than
		\mathbf{geq}	Unsigned/Signed Greater or Equal
		$\mathbf{e}\mathbf{q}$	Unsigned/Signed Equal
		\mathbf{neq}	Unsigned/Signed Not-Equal
		mux	Unsigned/Signed Multiplex
		pad	Unsigned/Signed Pad to Length
		\mathbf{asUInt}	Unsigned/Signed Reinterpret Bits as UInt
		\mathbf{asSInt}	Unsigned/Signed Reinterpret Bits as SInt
		\mathbf{shl}	Unsigned/Signed Shift Left
		${f shr}$	Unsigned/Signed Shift Right
		dshl	Unsigned/Signed Dynamic Shift Left
		dshr	Unsigned/Signed Dynamic Shift Right
		\mathbf{cvt}	Unsigned/Signed to Signed Logical Conversion
		\mathbf{neg}	Unsigned/Signed Negate
		\mathbf{not}	Unsigned Not
		and	Unsigned And
		\mathbf{or}	Unsigned Or
		xor	Unsigned Xor
		andr	Unsigned And Reduce
		orr	Unsigned Or Reduce
	ĺ	xorr	Unsigned Xor Reduce
		\mathbf{cat}	Unsigned Concatenation
		\mathbf{bit}	Single Bit Extraction
		\mathbf{bits}	Multiple Bit Extraction

3.2 Notation

The above definition specifies the structure of the abstract syntax tree corresponding to a FIRRTL circuit. Nodes in the abstract syntax tree are *italicized*. Keywords are shown in **bold**. The special productions, id and int, indicates an identifier and an integer literal respectively. Tokens followed by an asterisk, *e.g.* field*, indicates a list formed from repeated occurences of the token.

Keep in the mind that the above definition is only the *abstract* syntax tree, and is a representation of the in-memory FIRRTL datastructure. Readers and writers are provided for converting a FIRRTL datastructure into a purely textual representation, which is defined in Section 11.

4 Circuits and Modules

All FIRRTL circuits are comprised of a flat list of modules, each representing one hardware block. Each module has a given name, a list of ports, and a statement representing the circuit connections within the module. Externally defined modules consist of a given name, and a list of ports, whose types must match the types defined in the associated Verilog. Module names exist in their own namespace, and all modules must have a unique name. The name of the top-level module must be specified for a circuit.

A module port is specified by its kind, which may be input or output or clock, a name, and the data type for the port. The port names exist in the identifier namespace for the module, and must be unique. In addition, all references within a module must be unique.

The clock port kind is special in that it cannot be used to connect to any element in the circuit. However, a clock port can be referenced in the **reg**, **cmem**, **smem**, and **inst** declarations, as explained in Section 6.

The following example shows how a module can span two clock domains:

```
module TwoClock:
clock clk1
clock clk2
input ...
```

5 Types

5.1 Ground Types

There are only two ground types in FIRRTL, an unsigned and a signed integer type. Both of these types require a given bitwidth, which may be some known integer width, which must be non-negative and greater than zero, or an unknown width. Unknown widths are a declaration for the width to be computed by the FIRRTL width inferencer, instead of manually given by the programmer. Zero-valued widths are currently not supported, but future versions will likely support them.

5.2 Vector Types

$$type = type[int]$$

Vector types in FIRRTL indicate a structure consisting of multiple elements of some given type. This is akin to array types in the C programming language. Note that the number of elements must be known, and non-negative.

As an example, the type **UInt**<16>[10] indicates a ten element vector of 16-bit unsigned integers. The type **UInt**<?>[10] indicates a ten element vector of unsigned integers, with unknown but the same bitwidths.

Vector types may be nested ad infinitum. The type $\mathbf{UInt} < 16 > [10][5]$ indicates a five element vector of ten element vectors of 16-bit unsigned integers.

5.3 Bundle Types

```
type = {field*}
field = orientation name: type
orientation = default|reverse
```

Bundle types in FIRRTL are composite types formed from an ordered sequence of named, nested types. All fields in a bundle must have a given orientation, name, and type.

The following is an example of a possible type for representing a complex number.

```
{default real : SInt<10>, default imag : SInt<10>}
```

It has two fields, real, and imag, both 10-bit signed integers. By convention, we specify the directions within a bundle type with their relative orientation. For this reason, the real and imag fields for the complex number bundle type are both specified to be *default*.

The following bundle type has a data field that is specified to be a 10-bit unsigned integer type, a valid signal that must be a 1-bit unsigned integer type, and a reversed ready signal that must be a 1-bit unsigned integer type.

```
{default data: UInt<10>,
default valid: UInt<1>,
reverse ready: UInt<1>}
```

If an output port had this bundle type, the *ready* field would be an input to the module.

Note that all field names within a bundle type must be unique.

As in the case of vector types, bundle types may also be nested ad infinitum. I.e., the types of the fields themselves may also be bundle types, which will in turn contain more fields, etc.

6 Statements

FIRRTL circuit components are instantiated and connected together using *statements*.

6.1 Wires

A wire is a named combinational circuit element that can be connected to using the connect statement. A wire with a given name and type can be instantiated with the following statement.

wire name: type

Declared wires are *bidirectional*, which means that they can be used as both an input (by being on the left-hand side of a connect statement), or as an output (by being on the right-hand side of a connect statement).

6.2 Registers

A register is a named stateful circuit element. A register with a given name, type, clock port name, and reset reference, can be instantiated with the following statement.

reg name: type, clk, reset

Like wires, registers are also *bidirectional*, which means that they can be used as both an input (by being on the left-hand side of a connect statement), or as an output (by being on the right-hand side of a connect statement).

The on reset statement is used to specify the initialization value for a register, which is assigned to the register when the declared *reset* signal is asserted.

6.3 Memories

A memory is a stateful circuit element containing multiple elements. Unlike registers, memories can *only* be read from or written to through *accessors*. Memories always have a synchronous write, but can either be declared to be read combinatorially or synchronously. A synchronously read memory with a given name, type and clock port name can be instantiated with the following statement.

smem name : type, clk

A combinatorially read memory with a given name, type and clock port name can be instantiated with the following statement.

cmem name : type, clk

Note that, by definition, memories contain multiple elements, and hence must be declared with a vector type. Additionally, the type for a memory must be completely specified and cannot contain any unknown widths. It is an error to specify any other type for a memory. However, the internal type to the vector type may be a non-ground type, with the caveat that the internal type, if a bundle type, cannot contain any reverse fields.

A memory cannot be explicitly initialized using a special FIRRTL construct - the circuit itself must contain the proper logic to initialize the memory.

6.4 Nodes

A node is simply a named intermediate value in a circuit, and is akin to a pointer in the C programming language. A node with a given name and value can be instantiated with the following statement.

node name
$$= exp$$

Unlike wires, nodes can only be used in *output* directions. They can be connected from, but not connected to. Consequentially, their expression cannot be a bundle type with any reversed fields.

6.5 Accessors

Accessors are used for either connecting to or from a vector-typed expression, from some *variable* index.

$$dir \ \mathbf{accessor} \ \mathrm{name} = exp[\mathrm{index}]$$

 $dir = \mathbf{infer}|\mathbf{read}|\mathbf{write}|\mathbf{rdwr}$

Given an accessor direction, a name, an expression to access, and the index at which to access, the above statement creates an accessor that may be used for connecting to or from the expression. The expression must have a vector type, and the index must be an variable of UInt type.

A read, write, and inferred accessor is conceptually one-way; it must be consistently used to connect to, or to connect from, but not both.

A rdwr is conceptually two-way; it can be used to connect to, to connect from, or both, but not on the same cycle. If it is written to and read from on the same cycle, its behavior is undefined.

The following example demonstrates using accessors to read and write to a memory. The accessor, reader, acts as a memory read port that reads from the index specified by the wire i. The accessor, writer, acts as a memory write port that writes 42 to the index specified by wire j.

```
wire i: UInt<5>
wire j: UInt<5>
cmem m: UInt<10>[10]
read accessor reader = m[i]
write accessor writer = m[j]
writer := UInt<?>(42)
node temp = reader
```

As mentioned previously, the only way to read from or write to a memory is through an accessor. However, accessors are not restricted to accessing memories. They can be used to access *any* vector-valued type.

6.6 Instances

An instance refers to a particular instantiation of a FIRRTL module. An instance is constructed with a given name, a given module name, and a list of clock ports.

```
inst name: module, clk*
```

The instance's clock ports are assigned in order of the specified list of enclosing module clock ports. A mismatch in number of clock ports results in an error.

The resulting instance has a bundle type, where the given module's non-clock ports are fields and can be accessed using the subfield expression. The orientation of the *output* ports are *default*, and the orientation of the *input* ports are *reverse*. An instance may be directly connected to another element, but it must be on the right-hand side of the connect statement.

The following example illustrates directly connecting an instance to a wire:

```
exmodule Queue:
    clock clk: UInt<1>
    input in: UInt<16>
    output out: UInt<16>
module Top:
    clock clk: UInt<1>
    inst queue: Queue, clk
    wire connect: {default out: UInt<16>, reverse in: UInt<16>}
    connect:= queue
```

The output ports of an instance may only be connected from, e.g. the right-hand side of a connect statement. Conversely, the input ports of an instance may only be connected to, e.g. the left-hand side of a connect statement.

The following example illustrates a proper use of creating instances with different clock domains:

```
exmodule A syncQueue:
  clock \ clk1 : UInt < 1 >
  clock clk2: UInt<1>
  input in: {default data: UInt<16>, reverse ready: UInt<1>}
  output out: {default data: UInt<16>, reverse ready: UInt<1>}
exmodule Source:
  clock clk: UInt<1>
  output packet: {default data: UInt<16>, reverse ready: UInt<1>}
exmodule Sink:
  clock \ clk : UInt < 1 >
  input packet: {default data: UInt<16>, reverse ready: UInt<1>}
module \ TwoClock:
  clock clk1 : UInt<1>
  clock clk2: UInt<1>
  inst\ src: Source, clk1
  inst \ snk : Sink, clk2
  inst queue: AsynchQueue, clk1, clk2
  queue.in := src.packet
  snk.packet := queue.out
```

There are restrictions upon which modules the user is allowed to instantiate, so as not to create infinitely recursive hardware. We define a module with no instances as a level 0 module. A module containing only instances of level 0 modules is a level 1 module, and a module containing only instances of level 1 or below modules is a level 2 module. In general, a level n module is only allowed to contain instances of modules of level n-1 or below.

6.7 The Connect Statement

The connect statement is used to specify a physical wired connection between one hardware component to another, and is the most important statement in FIRRTL. The following statement is used to connect the output of some component, to the input of another component.

For a connection to be legal, the types of the two expressions must match exactly, including all field orientations if the elements contain bundle types.

However, the widths of the types do not need to be equivalent. If the *output* expression has a smaller width than the *input* expression, the *output* is padded according to its type. If the *output* expression has a larger width than the *input* expression, the lower bits of the *output* are extracted and assigned to the *input*.

If the *input* width is unknown, it is inferred to be the width of the largest *output* that it is connected to. If the *output* width is unknown, it cannot inferred from this connection.

The component on the right-hand side must be able to be used as an output, and the component on the left-hand side must be able to be used as an input.

6.8 The On-Reset Connect Statement

The on reset connect statement is used to specify the default value for a **reg** element.

$$onreset r := output$$

For a connection to be legal, the types of the two expressions must match exactly, including all field orientations if the elements contain bundle types.

The component on the right-hand side must be able to be used as an output, and the component on the left-hand side must be a **reg** element. The widths of the types may mismatch, and the semantics are the same as the connect statements. Memories cannot be initialized with this construct.

By default, a **reg** will not have a initialization value and will maintain its current value under the reset signal specified in their declaration. The following example demonstrates declaring a **reg**, and changing its initialization value to forty two.

reg
$$r : UInt < 10 > (clk, reset)$$

onreset $r := UInt < ? > (42)$

6.9 The Bulk Connect Statement

The bulk connect statement is a connect statement that does not require both expressions to be the same type. During the lowering pass, the bulk connect will expand to some number of connect statements, possibly zero statements. The following statement is used to connect the output of some component, to the input of another component.

For a bulk connect between two components of a bundle-type, fields that are of the same type, orientation, and name will be connected. Fields that do not match will not be connected. For a bulk connect between two components of a vector-type, the number of connected elements will be equal to the length of the shorter vector. A bulk connect between two components of the same ground type is equivalent to a normal connect statement. All other combinations of types will not error, but will not generate any connect statements.

6.10 The Sub-Word Connect Statement

The subword connect statement is used to assigned to a range of bits within a ground-typed element. It is specified by two integers that indicate the high and low bounds of the range, inclusively.

$$\exp[\text{hi through lo}] := \text{output}$$

The subword is always UInt type, so for a connection to be legal, the expression on the right must also be of UInt type. The expression on the right-hand side must be able to be used as an output, and the component on the left-hand side must be able to be used as an input. In addition, the expression on the left-hand side must be a ground type, although this restriction may be relaxed in future spec releases.

6.11 The Conditional Statement

The conditional statement is used to specify a condition that must be asserted under which a list of statements hold. The condition must be a 1-bit unsigned integer. The following statement states that the *conseq* statements hold only when *condition* is assert high, otherwise the *alt* statements hold instead.

when condition: conseq else: alt

Notationally, for convenience, we omit the **else** branch if it is an empty statement.

6.11.1 Initialization Coverage

Because of the conditional statement, it is possible for wires to be only partially connected to an expression. In the following example, the wire w is connected to 42 when enable is asserted high, but it is not specified what w is connected to when enable is low. This is an illegal FIRRTL circuit, and will throw a wire not initialized error during compilation.

wire w : UInt <?>when enable :w := UInt <?>(42)

6.11.2 Scoping

The conditional statement creates a new *scope* within its consequent and alternative branches. It is an error to refer to any component declared within a branch after the branch has ended.

Note that there is still only a single identifier namespace in a module. Thus, there cannot be two components with identical names in the same module, *even if* they are in separate scopes. This is to facilitate writing

transformational passes, by ensuring that the component name and module name is sufficient to uniquely identify a component.

6.11.3 Connect Semantics - IN PROGRESS

6.12 Statement Groups

Several statements can be grouped into one using the following construct.

$$(stmt*)$$

Ordering is important in a statement group. Later connect statements take precedence over earlier connect statements, and circuit components cannot be referred to before they are instantiated.

6.12.1 Last Connect Semantics

Because of the connect statement, FIRRTL statements are *ordering* dependent. Later connections take precendence over earlier connections. In the following example, the wire w is connected to 42, not 20.

wire
$$w : UInt$$

 $w := UInt (20)$
 $w := UInt (42)$

By coupling the conditional statement with last connect semantics, many circuits can be expressed in a natural style. In the following example, the wire w is connected to 20 unless the enable expression is asserted high, in which case w is connected to 42.

wire
$$w : UInt$$

 $w := UInt (20)$
when $enable :$
 $w := UInt (42)$

6.13 The Assert Statement

The assert statement is used to specify a dynamic assertion on an expression in a circuit.

The assertion expression must be a one-bit UInt type.

6.14 The Empty Statement

The empty statement is specified using the following.

skip

The empty statement does nothing and is used simply as a placeholder where a statement is expected. It is typically used as the alternative branch in a conditional statement. In addition, it is useful for transformation pass writers.

7 Expressions

FIRRTL expressions are used for creating values corresponding to the ground types, for referring to a declared circuit component, for accessing a nested element within a component, and for performing primitive operations.

7.1 Unsigned Integers

A value of type **UInt** can be directly created using the following expression.

The given value must be non-negative, and the given width, if known, must be large enough to hold the value. If the width is specified as unknown, then FIRRTL infers the minimum possible width necessary to hold the value.

7.2 Signed Integers

A value of type **SInt** can be directly created using the following expression.

The given width, if known, must be large enough to hold the given value in two's complement format. If the width is specified as unknown, then FIRRTL infers the minimum possible width necessary to hold the value.

7.3 References

name

A reference is simply a name that refers to some declared circuit component. A reference may refer to a port, a node, a wire, a register, an instance, a memory, a node, or a structural register.

7.4 Subfields

exp.name

The subfield expression may be used for one of two purposes:

- 1. To refer to a specific port of an instance, using instance-name.port-name.
- 2. To refer to a specific field within a bundle-typed expression.

7.5 Subindex

exp[index]

The subindex expression is used for referring to a specific element within a vector-valued expression. It is legal to use the subindex expression on any vector-valued expression, except for memories.

7.6 Primitive Operation

primop(exp*, int*)

There are a number of different primitive operations supported by FIRRTL. Each operation takes some number of expressions, along with some number of integer literals. Section 8 will describe the format and semantics of each operation.

8 Primitive Operations

All primitive operations expression operands must be ground types. In addition, some allow all permutations of operand ground types, while others on allow subsets. When well defined, input arguments are allowed to be differing widths.

max(width(op1), width(op2)) + 1

8.1 Add Operation

$\begin{array}{ccccc} \textbf{Input Types} & \textbf{Resultant Type} & \textbf{Resultant Width} \\ \textbf{add}(\textit{op1}: UInt, \textit{op2}: UInt) & UInt & max(width(\textit{op1}), width(\textit{op2})) + 1 \\ \textbf{add}(\textit{op1}: UInt, \textit{op2}: SInt) & SInt & max(width(\textit{op1}), width(\textit{op2})) + 1 \\ \textbf{add}(\textit{op1}: SInt, \textit{op2}: UInt) & SInt & max(width(\textit{op1}), width(\textit{op2})) + 1 \\ \end{array}$

The resultant's value is 1-bit larger than the wider of the two operands and has a signed type if either operand is signed (otherwise is unsigned).

8.2 Subtract Operation

add(op1: SInt, op2: SInt) SInt

primop Resultant Type Resultant Width

```
\begin{array}{lll} \mathbf{sub}(\mathit{op1}:\mathit{UInt},\mathit{op2}:\mathit{UInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) + 1 \\ \mathbf{sub}(\mathit{op1}:\mathit{UInt},\mathit{op2}:\mathit{SInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) + 1 \\ \mathbf{sub}(\mathit{op1}:\mathit{SInt},\mathit{op2}:\mathit{UInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) + 1 \\ \mathbf{sub}(\mathit{op1}:\mathit{SInt},\mathit{op2}:\mathit{SInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) + 1 \\ \end{array}
```

The subtraction operation works similarly to the add operation, but always returns a signed integer with a width that is 1-bit wider than the max of the widths of the two operands.

8.3 Add Wrap Operation

primop Resultant Type Resultant Width

```
 \begin{array}{lll} \mathbf{addw}(op1:UInt,op2:UInt) & UInt \\ \mathbf{addw}(op1:UInt,op2:SInt) & SInt \\ \mathbf{addw}(op1:SInt,op2:UInt) & SInt \\ \mathbf{addw}(op1:SInt,op2:UInt) & SInt \\ \mathbf{addw}(op1:SInt,op2:SInt) & SInt \\ \end{array} \begin{array}{lll} max(width(op1),width(op2)) \\ max(width(op1),width(op2)) \\ max(width(op1),width(op2)) \\ max(width(op1),width(op2)) \\ \end{array}
```

The add wrap operation works identically to the normal add operation except that the resultant width is the maximum of the width of the two operands, instead of 1 bit greater than the maximum. In the case of overflow, the result silently rolls over.

8.4 Subtract Wrap Operation

primop Resultant Type Resultant Width

```
\begin{array}{lll} \mathbf{subw}(\mathit{op1}:\mathit{UInt},\mathit{op2}:\mathit{UInt}) & \mathit{UInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) \\ \mathbf{subw}(\mathit{op1}:\mathit{UInt},\mathit{op2}:\mathit{SInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) \\ \mathbf{subw}(\mathit{op1}:\mathit{SInt},\mathit{op2}:\mathit{UInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) \\ \mathbf{subw}(\mathit{op1}:\mathit{SInt},\mathit{op2}:\mathit{SInt}) & \mathit{SInt} & \mathit{max}(\mathit{width}(\mathit{op1}),\mathit{width}(\mathit{op2})) \\ \end{array}
```

Similarly to the add wrap operation, the subtract wrap operation works identically to the normal subtract operation except that the resultant width is the maximum of the width of the two operands. In the case of overflow, the result silently rolls over.

8.5 Multiply Operation

primop Resultant Type Resultant Width

```
\begin{array}{lll} \mathbf{mul}(op1:UInt,op2:UInt) & UInt & width(op1) + width(op2) \\ \mathbf{mul}(op1:UInt,op2:SInt) & SInt & width(op1) + width(op2) \\ \mathbf{mul}(op1:SInt,op2:UInt) & SInt & width(op1) + width(op2) \\ \mathbf{mul}(op1:SInt,op2:SInt) & SInt & width(op1) + width(op2) \\ \end{array}
```

The resultant value has width equal to the sum of the widths of its two operands.

8.6 Divide Operation

primop Resultant Type Resultant Width

```
\begin{array}{lll} \mathbf{div}(op1:UInt,op2:UInt) & UInt & width(op1) \\ \mathbf{div}(op1:UInt,op2:SInt) & SInt & width(op1) + 1 \\ \mathbf{div}(op1:SInt,op2:UInt) & SInt & width(op1) \\ \mathbf{div}(op1:SInt,op2:SInt) & SInt & width(op1) + 1 \end{array}
```

The first argument is the dividend, the second argument is the divisor. The resultant width of a divide operation is equal to the width of the dividend, plus one if the divisor is an SInt. The resultant value follows the following formula: $\operatorname{div}(a,b) = \operatorname{round-towards-zero}(a/b) + \operatorname{mod}(a,b)$

8.7 Modulus Operation

$\begin{array}{ccccc} \mathbf{primop} & \mathbf{Resultant} & \mathbf{Type} & \mathbf{Resultant} & \mathbf{Width} \\ \mathbf{mod}(op1:UInt,op2:UInt) & UInt & width(op2) \\ \mathbf{mod}(op1:UInt,op2:SInt) & UInt & width(op2) \\ \mathbf{mod}(op1:SInt,op2:UInt) & SInt & width(op2) + 1 \\ \mathbf{mod}(op1:SInt,op2:SInt) & SInt & width(op2) \end{array}$

The first argument is the dividend, the second argument is the divisor. The resultant width of a modulus operation is equal to the width of the divisor, except when the modulus is positive and the result can be negative. The resultant value follows the following formula: $\operatorname{div}(a,b) = \operatorname{round-towards-zero}(a/b) + \operatorname{mod}(a,b)$

8.8 Quotient Operation

$\begin{array}{ccccc} \mathbf{primop} & \mathbf{Resultant} & \mathbf{Type} & \mathbf{Resultant} & \mathbf{Width} \\ \mathbf{quo}(\mathit{op1}:UInt,\mathit{op2}:UInt) & UInt & \mathit{width}(\mathit{op1}) + 1 \\ \mathbf{quo}(\mathit{op1}:UInt,\mathit{op2}:SInt) & SInt & \mathit{width}(\mathit{op1}) \\ \mathbf{quo}(\mathit{op1}:SInt,\mathit{op2}:UInt) & SInt & \mathit{width}(\mathit{op1}) + 1 \\ \mathbf{quo}(\mathit{op1}:SInt,\mathit{op2}:SInt) & SInt & \mathit{width}(\mathit{op1}) \end{array}$

The first argument is the dividend, the second argument is the divisor. The resultant width of a quotient operation is equal to the width of the dividend, plus one if the divisor is an SInt. The resultant value follows the following formula: quo(a,b) = floor(a/b) + rem(a,b)

8.9 Remainder Operation

primop	Resultant Type	Resultant Width
$\mathbf{rem}(\mathit{op1}:UInt,\mathit{op2}:UInt)$	UInt	width(op2)
$\mathbf{rem}(op1:UInt,op2:SInt)$	SInt	width(op2)
$\mathbf{rem}(op1:SInt,op2:UInt)$	UInt	width(op2) + 1
$\mathbf{rem}(\mathit{op1}:SInt,\mathit{op2}:SInt)$	SInt	width(op2)

The first argument is the dividend, the second argument is the divisor. The resultant width of a modulus operation is equal to the width of the divisor, except when the divisor is positive and the result can be negative. The resultant value follows the following formula : quo(a,b) = floor(a/b) + rem(a,b)

8.10 Comparison Operations

primop	Resultant Type	Resultant Width
$\mathbf{lt}(\mathit{op1}:UInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{lt}(\mathit{op1}:UInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{lt}(\mathit{op1}:SInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{lt}(\mathit{op1}:SInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{leq}(\mathit{op1}:UInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{leq}(\mathit{op1}:UInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{leq}(\mathit{op1}:SInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{leq}(\mathit{op1}:SInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{gt}(\mathit{op1}:UInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{gt}(\mathit{op1}:UInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{gt}(\mathit{op1}:SInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{gt}(\mathit{op1}:SInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{geq}(\mathit{op1}:UInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{geq}(\mathit{op1}:UInt,\mathit{op2}:SInt)$	UInt	1
$\mathbf{geq}(\mathit{op1}:SInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{geq}(\mathit{op1}:SInt,\mathit{op2}:SInt)$	UInt	1

Each operation accept any combination of SInt or UInt input arguments, and always returns a single-bit unsigned integer.

8.11 Equality Comparison

primop	Resultant Type	Resultant Width
eq(op1:UInt,op2:UInt)	UInt	1
eq(op1: SInt, op2: SInt)	UInt	1

The equality comparison operator accepts either two unsigned or two signed integers and checks whether they are bitwise equivalent. The resulting value is a 1-bit unsigned integer.

If an arithmetic equals between a signed and unsigned integer is desired, one must first use convert on the unsigned integer, then use the equal primop.

8.12 Not-Equality Comparison

primop	Resultant Type	Resultant Width
$\mathbf{neq}(\mathit{op1}:UInt,\mathit{op2}:UInt)$	UInt	1
$\mathbf{neq}(\mathit{op1}:SInt,\mathit{op2}:SInt)$	UInt	1

The not-equality comparison operator accepts either two unsigned or two signed integers and checks whether they are not bitwise equivalent. The resulting value is a 1-bit unsigned integer.

If an arithmetic not-equals between a signed and unsigned integer is desired, one must first use convert on the unsigned integer, then use the not-equal primop.

8.13 Multiplex

primop Resultant Type Resultant Width

The multiplex operation accepts three signals, a 1-bit unsigned integer for the condition expression, followed by either two unsigned integers, or two signed integers. If the condition is high, then the result is equal to the first of the two following operands. If the condition is low, then the result is the second of the two following operands.

The output is of the same width as the max width of the inputs.

8.14 Padding Operation

primop Resultant Type Resultant Width

pad(op:UInt,num)	UInt	num
pad(op : SInt, num)	SInt	num

A pad operation is provided which either zero-extends or sign-extends an expression to a specified width. The given width, num, must be equal to or greater than the existing width of the expression.

8.15 Reinterpret Bits as UInt

primop Resultant Type Resultant Width

```
\mathbf{asUInt}(op1:UInt) \quad UInt \quad width(op1) \\ \mathbf{asUInt}(op1:SInt) \quad UInt \quad width(op1)
```

Regardless of input type, primop returns a UInt with the same width as the operand.

8.16 Reinterpret Bits as SInt

primop Resultant Type Resultant Width

```
 \begin{array}{lll} \mathbf{asSInt}(op1:UInt) & SInt & width(op1) \\ \mathbf{asSInt}(op1:SInt) & SInt & width(op1) \\ \end{array}
```

Regardless of input type, primop returns a SInt with the same width as the operand.

8.17 Shift Left Operation

primop Resultant Type Resultant Width

$\mathbf{shl}(\mathit{op}:UInt,\mathit{num})$	UInt	width(op) + num
$\mathbf{shl}(\mathit{op}:SInt,\mathrm{num})$	SInt	width(op) + num

The shift left operation accepts either an unsigned or a signed integer, plus a non-negative integer literal specifying the number of bits to shift. The resultant value has the same type as the operand. The output of a shift left operation is equal to the original signal concatenated with n zeros at the end, where n is the shift amount.

8.18 Shift Right Operation

primop Resultant Type Resultant Width

$\mathbf{shr}(\mathit{op}:UInt,\mathrm{num})$	UInt	width(op) - num
$\mathbf{shr}(op:SInt, \text{num})$	SInt	width(op) - num

The shift right operation accepts either an unsigned or a signed integer, plus a non-negative integer literal specifying the number of bits to shift. The resultant value has the same type as the operand. The shift amount must be less than or equal to the width of the operand. The output of a shift right operation is equal to the original signal with the least significant num bits truncated, where num is the shift amount.

8.19 Dynamic Shift Left Operation

primop Resultant Type Resultant Width

```
 \begin{aligned} \mathbf{dshl}(op1:UInt,op2:UInt) & UInt & width(op1) + pow(2,width(op2)) \\ \mathbf{dshl}(op1:SInt,op2:UInt) & SInt & width(op1) + pow(2,width(op2)) \end{aligned}
```

The dynamic shift left operation accepts either an unsigned or a signed integer, plus an unsigned integer dynamically specifying the number of bits to shift. The resultant value has the same type as the operand. The output of a dynamic shift left operation is equal to the original signal concatenated with n zeros at the end, where n is the dynamic shift amount. The output width of a dynamic shift left operation is the width of the original signal plus 2 raised to the width of the dynamic shift amount.

8.20 Dynamic Shift Right Operation

primop Resultant Type Resultant Width

 $\mathbf{dshr}(op:UInt,op2:UInt)$ UInt width(op) $\mathbf{dshr}(op:SInt,op2:UInt)$ SInt width(op)

The shift right operation accepts either an unsigned or a signed integer, plus a non-negative integer literal specifying the number of bits to shift. The resultant value has the same type as the operand. The shift amount must be less than or equal to the width of the operand. The output of a shift right operation is equal to the original signal with the least significant n bits truncated, where n is the dynamic shift amount. The output width of a dynamic shift right operation is the width of the original signal.

8.21 Logical Convert to Signed

primop Resultant Type Resultant Width

 $egin{array}{lll} \mathbf{cvt}(op:UInt) & SInt & width(op)+1 \\ \mathbf{cvt}(op:SInt) & SInt & width(op) \end{array}$

The convert operation accepts either an unsigned or a signed integer. The resultant value is always a signed integer. The output of a convert operation will be the same arithmetic value as the input value. The output width is the same as the input width if the input is signed, and increased by one if the input is unsigned.

8.22 Negate

primop Resultant Type Resultant Width

 $egin{array}{lll} \mathbf{neg}(\mathit{op1}:UInt) & SInt & width(\mathit{op1})+1 \\ \mathbf{neg}(\mathit{op1}:SInt) & SInt & width(\mathit{op1}) \end{array}$

If the input type is UInt, primop returns the negative value as an SInt with the width of the operand plus one. If the input type is SInt, primop returns -1 * input value, as an SInt with the same width of the operand.

8.23 Bitwise Operations

primop Resultant Type Resultant Width

```
\begin{array}{cccc} \mathbf{not}(op1:UInt) & UInt & width(op1) \\ \mathbf{and}(op1:UInt, op2:UInt) & UInt & max(width(op1), width(op2)) \\ \mathbf{or}(op1:UInt, op2:UInt) & UInt & max(width(op1), width(op2)) \\ \mathbf{xor}(op1:UInt, op2:UInt) & UInt & max(width(op1), width(op2)) \end{array}
```

The above operations correspond to bitwise not, and, or, and exclusive or respectively. The operands must be unsigned integers, and the resultant width is equal to the width of the wider of the two operands.

8.24 Reduce Bitwise Operations

primop Resultant Type Resultant Width

$\mathbf{andr}(\mathit{op:UInt})$	UInt	1
$\mathbf{orr}(\mathit{op:UInt})$	UInt	1
xorr (op:UInt)	UInt	1

The above operations correspond to bitwise not, and, or, and exclusive or respectively, reduced over every bit of a single unsigned integer. The resultant width is always one.

8.25 Concatenation

primop Resultant Type Resultant Width

```
\mathbf{cat}(\mathit{op1}:UInt,\mathit{op2}:UInt) \quad UInt \qquad \qquad width(\mathit{op1}) + width(\mathit{op2})
```

The concatenation operator accepts two unsigned integers and returns the bitwise concatenation of the two values as an unsigned integer. The resultant width is the sum of the widths of the two operands.

8.26 Bit Extraction Operation

primop Resultant Type Resultant Width

$\mathbf{bit}(\mathit{op}:UInt,\mathrm{index})$	UInt	1
$\mathbf{bit}(op:SInt, index)$	UInt	1

The bit extraction operation accepts either an unsigned or a signed integer, plus an integer literal specifying the index of the bit to extract. The resultant value is a 1-bit unsigned integer. The index must be non-negative and less than the width of the operand. An index of zero indicates the least significant bit in the operand, and an index of one less than the width the operand indicates the most significant bit in the operand.

8.27 Bit Range Extraction Operation

primop Resultant Type Resultant Width

$\mathbf{bits}(op:UInt, \mathbf{high}, \mathbf{low})$	UInt	high-low
$\mathbf{bits}(op: SInt, \mathbf{high}, \mathbf{low})$	UInt	high - low

The bit range extraction operation accepts either an unsigned or a signed integer, plus two integer literals that specify the high (inclusive) and low (inclusive) index of the bit range to extract. The index must be non-negative and less than the width of the operand. Regardless of the type of the operand, the resultant value is a n-bit unsigned integer, where n = high - low + 1.

9 FIRRTL Forms

To simplify the writing of transformation passes, any FIRRTL implementation will provide a *resolving* pass, which resolves all types, widths, and checks the legality of the circuit, and a *lowering* pass, which rewrites any FIRRTL circuit into an equivalent *lowered form*.

9.1 Resolved Form

The resolved form is guaranteed to be well-formed, meaning all restrictions to a FIRRTL circuit have been checked. In addition, all unknown widths and inferred accessor directions have been resolved.

9.2 Lowered Form

The lowered form is a structured subset of FIRRTL, making it a minimal representation that is convenient for low-level transforms.

The body of a lowered module consists of a list of declarations, connect statements, and *predicated single connect statements*. A predicated single

connect statement is a conditional statement containing a single connect statement and no else branch.

The following circuit is lowered:

```
module MyCounter:
   clock clk: UInt<1>
   input reset: UInt<1>
   input inc: UInt<1>
   output out: UInt<3>
   reg counter: UInt<3>, clk, reset
   when inc: counter:= addw(counter, UInt<1>(1))
   out:= counter
```

The following restrictions also hold for modules in lowered form.

- No Nested Expressions: In the declaration of the structural elements, the only nested expressions allowed are references, and unsigned and signed literals. All other nested expressions must be lifted to a named node, and referred to through a reference.
- No Composite Types: No module port or wire may be declared with a bundle or vector type. The lowering pass will recursively expand ports into its constituent elements until all ports are declared with ground types.
- Single Connect: Every declared component can only be connected to once within a module. This connect could be a predicated single connect.
- No Nested Whens: Other than predicated single connect statements, no other conditional statements are allowed.
- Inlined Lowered Form: A further (and optional) pass provided by FIRRTL is the inlining pass, which recursively inlines all instances in the top-level module until the top-level module is the only remaining module in the circuit. Inlined lowered form is essentially a flat netlist which specifies every component used in a circuit and their input connections.

10 Annotations - IN PROGRESS

- 1. Writing a correct compiler is difficult.
- 2. To make it easier, make things as brittle as possible
- 3. If annotations are kept in the FIRRTL graph, it is unclear how they propagate.
- 4. If improperly propagated, you either have annotations where they shouldn't be, or lack annotations where they should be.
- 5. This is impossible to detect, so turns into a silent failure
- 6. If annotations are used for actual manipulations of circuits later on, this could be the cause of a bug that is exceptionally hard to solve
- 7. Thus, annotation producer/consumer keeps external datastructure mapping names to annotations
- 8. Pass writers must do all they can to preserve names can provide transform for names that annotation users can run on their tables
- 9. If a name is mangled, the annotation consumer can ERROR. Then, they need to look at the pass to see how their annotations should propagate.

11 Concrete Syntax

This section describes the text format for FIRRTL that is supported by the provided readers and writers.

General Principles

FIRRTL's text format is human-readable and uses indentation to indicate block structuring. The following characters are allowed in identifiers: upper and lower case letters, digits, as well as the punctuation characters ~!@#\$%^*-_+=?/. Identifiers cannot begin with a digit.

Comments begin with a semicolon and extend until the end of the line. Commas are treated as whitespace, and may be used by the user for clarity if desired.

Statements are grouped into statement groups using parenthesis, however a colon at the end of a line will automatically assume the next indented region is a statement group. This mechanism is used for indicating block structuring.

The following circuit, module, port and statement examples all exclude the info token @[filename:line.col], which can be optionally included at the beginning of the first line of each elements' concrete syntax.

Circuits and Modules

A circuit is specified the following way.

```
circuit name : (modules ...)
```

Or by taking advantage of indentation structuring:

```
circuit name : modules ...
```

A module is specified the following way.

```
module name : (ports ... stmts ...)
```

The module body consists of a sequence of ports followed immediately by a sequence of statements. If there is more than one statement they are grouped into a statement group by the parser. By using indentation structuring:

```
module name :
   ports ...
   stmts ...
```

The following shows an example of a simple module.

```
module mymodule :
```

```
input a: UInt<1>
output b: UInt<1>
clock clk: UInt<1>
b := a
```

Types

The unsigned and signed integer types are specified the following way. The following examples demonstrate a unsigned integer with known bitwidth, signed integer with known bitwidth, an unsigned integer with unknown bitwidth, and signed integer with unknown bitwidth.

```
UInt<42>
SInt<42>
UInt<?>
SInt<?>
```

The bundle type consists of a number of fields surrounded with braces. The following shows an example of a decoupled bundle type. Note that the commas are for clarity only and are not necessary.

```
{default data: UInt<10>,
  default valid: UInt<1>,
  reverse ready: UInt<1>}
```

The vector type is specified by immediately postfixing a type with a bracketed integer literal. The following example demonstrates a ten-element vector of 16-bit unsigned integers.

```
UInt<16>[10]
```

Statements

The following examples demonstrate declaring wires, registers, memories, nodes, instances, and accessors.

```
wire mywire : UInt<10>
reg myreg : UInt<10>, clk, reset
cmem mycombmem : UInt<10>[16], clk2
smem myseqmem : UInt<10>[16], clk2
inst myinst : MyModule
infer accessor myaccessor = e[i]
```

The connect statement is specified using the := operator.

```
x := y
```

The on reset connect statement is specified using the onreset keyword and the := operator.

```
onreset x := y
```

The bulk connect statement is specified using the <> operator.

```
x <> y
```

The subword connect statement is specified with [] brackets after the expression on the left of the := operator. Within the brackets is the high bit index, followed by the keyword through, followed by the low bit index.

```
x[3 through 0] := y
```

The assert statement is specified using the assert keyword.

assert x

The conditional statement is specified with the when keyword.

```
when x : x := y else : x := z
```

Or by using indentation structuring:

```
when x :
```

x := y

else :

x := z

If there is no alternative branch specified, the parser will automatically insert an empty statement.

```
when x :
```

x := y

For convenience when expressing nested conditional statements, the colon following the else keyword may be elided if the next statement is another conditional statement.

```
when x:
```

x := y

else when y :

x := z

else :

x := w

Expressions

The UInt and SInt constructors create literal integers from a given value and bitwidth. The following examples demonstrate creating literal integers of both known and unknown bitwidth.

```
UInt<4>(42)
SInt<4>(-42)
UInt<?>(42)
SInt<?>(-42)
```

References are specified with a identifier.

х

Subfields are expressed using the dot operator.

x.data

Subindicies are expressed using the [] operator.

x[10]

Primitive operations are expressed by following the name of the primitive with a list containing the operands.

```
add(x, y)
add(x, add(x, y))
shl(x, 42)
```

12 Design Justification - IN PROGRESS

Some choices were made during the design of this specification which were intentionally conservative, so that future versions could lift the restrictions if suitable semantics and implementations are determined. By restricting this version and potentially lifting them in future versions, all existing FIRRTL circuits will remain valid.

The follow design decisions could potentially be changed in future spec revisions:

1. Disallowing subword assignments to non-ground-typed elements.

- 2. Disallowing zero-width types
- 3. Always expanding memories into smaller memories (if the type within the vector type is a non-ground-type)
- 4. Not including a **printf** node
- 5. Not including a **ROM** node
- 6. Custom annotations are not held in FIRRTL nodes
- 7. Not requiring that all names are unique

13 FAQ - IN PROGRESS

- 1. Why allow operations to allow inputs of differing widths? We tried restricting widths, but it actually complicated width inference and made supporting frontends with more lax width restrictions very difficult. Because there is perfectly well defined semantics, we opted to allow differing widths.
- 2. Why require all names unique? Passes usually need unique names, so there needs to be a renaming pass somewhere. Standardizing how names gets mangled requires a lot of thought, and we didn't feel comfortable putting this into the spec at the moment and potentially regretting it later. For now, names have to be unique, and it is the frontend's responsibility to do this.
- 3. Why allow declaring components in when statements? Have had a huge amount of discussion, with some progress. Talk to me in person.
- 4. Why not just have low firrtl? For performance backends, we will need to emit arrays and structs. Naturally, you would want to write a backend that operates on a resolved firrtl circuit, not a lowered one. If there is only a lowered circuit, we lose that ability. The final difference between resolved and lowered circuit is the when statement. When statements + last connect semantics make it very difficult to remove whens without removing the complex types as well.