



# **Thunder Loan Initial Audit Report**

Version 0.1

*Cyfrin.io*

September 24, 2023

# Thunder Loan Audit Report

YOUR\_NAME\_HERE

September 1, 2023

## Thunder Loan Audit Report

Prepared by: YOUR\_NAME\_HERE Lead Auditors:

- YOUR\_NAME\_HERE

Assisting Auditors:

- None

## Table of contents

See table

- Thunder Loan Audit Report
- Table of contents
- About YOUR\_NAME\_HERE
- Disclaimer
- Risk Classification
- Audit Details
  - Scope
- Protocol Summary
  - Roles
- Executive Summary

- Issues found
- Findings
  - High
    - \* [H-1] Mixing up variable location causes storage collisions in `ThunderLoan::s_flashLoanFee` and `ThunderLoan::s_currentlyFlashLoaning`
    - \* [H-2] Unnecessary `updateExchangeRate` in `deposit` function incorrectly updates `exchangeRate` preventing withdrawals and unfairly changing reward distribution
  - Medium
    - \* [M-1] Centralization risk for trusted owners
      - Impact:
    - \* [M-2] Using TSwap as price oracle leads to price and oracle manipulation attacks
  - Low
    - \* [L-1] Empty Function Body - Consider commenting why
    - \* [L-2] Initializers could be front-run
    - \* [L-3] Missing critical event emissions
  - Informational
    - \* [I-1] Poor Test Coverage
  - Gas
    - \* [GAS-1] Using bools for storage incurs overhead
    - \* [GAS-2] Using `private` rather than `public` for constants, saves gas

## About YOUR\_NAME\_HERE

## Disclaimer

The YOUR\_NAME\_HERE team makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the solidity implementation of the contracts.

## Risk Classification

|            |        | Impact |        |     |
|------------|--------|--------|--------|-----|
|            |        | High   | Medium | Low |
| Likelihood | High   | H      | H/M    | M   |
|            | Medium | H/M    | M      | M/L |
|            | Low    | M      | M/L    | L   |

## Executive Summary

### Issues found

| Severity | Number of issues found |
|----------|------------------------|
| High     | 2                      |
| Medium   | 2                      |
| Low      | 3                      |
| Info     | 1                      |
| Gas      | 2                      |
| Total    | 10                     |

## Findings

### High

#### [H-1] Mixing up variable location causes storage collisions in ThunderLoan::s\_flashLoanFee and ThunderLoan::s\_currentlyFlashLoaning

**Description:** ThunderLoan.sol has two variables in the following order:

```
1    uint256 private s_feePrecision;  
2    uint256 private s_flashLoanFee; // 0.3% ETH fee
```

However, the expected upgraded contract ThunderLoanUpgraded.sol has them in a different order.

```
1    uint256 private s_flashLoanFee; // 0.3% ETH fee  
2    uint256 public constant FEE_PRECISION = 1e18;
```

Due to how solidity storage works, after the upgrade, the s\_flashLoanFee will have the value of s\_feePrecision. You cannot adjust the positions of storage variables when working with upgradeable contracts.

**Impact:** After upgrade, the s\_flashLoanFee will have the value of s\_feePrecision. This means that users who take out flash loans right after an upgrade will be charged the wrong fee. Additionally the s\_currentlyFlashLoaning mapping will start on the wrong storage slot.

**Proof of Code:**

Code

Add the following code to the `ThunderLoanTest.t.sol` file.

```
1 // You'll need to import `ThunderLoanUpgraded` as well
2 import { ThunderLoanUpgraded } from "../src/upgradedProtocol/
  ThunderLoanUpgraded.sol";
3
4 function testUpgradeBreaks() public {
5     uint256 feeBeforeUpgrade = thunderLoan.getFee();
6     vm.startPrank(thunderLoan.owner());
7     ThunderLoanUpgraded upgraded = new ThunderLoanUpgraded();
8     thunderLoan.upgradeTo(address(upgraded));
9     uint256 feeAfterUpgrade = thunderLoan.getFee();
10
11     assert(feeBeforeUpgrade != feeAfterUpgrade);
12 }
```

You can also see the storage layout difference by running `forge inspect ThunderLoan storage` and `forge inspect ThunderLoanUpgraded storage`

**Recommended Mitigation:** Do not switch the positions of the storage variables on upgrade, and leave a blank if you're going to replace a storage variable with a constant. In `ThunderLoadUpgraded.sol`

```
1 - uint256 private s_flashLoanFee; // 0.3% ETH fee
2 - uint256 public constant FEE_PRECISION = 1e18;
3 + uint256 private s_blank;
4 + uint256 private s_flashLoanFee;
5 + uint256 public constant FEE_PRECISION = 1e18;
```

**[H-2] Unnecessary updateExchangeRate in deposit function incorrectly updates exchangeRate preventing withdraws and unfairly changing reward distribution****Description:**

```
1 function deposit(IERC20 token, uint256 amount) external
  revertIfZero(amount) revertIfNotAllowedToken(token) {
2     AssetToken assetToken = s_tokenToAssetToken[token];
3     uint256 exchangeRate = assetToken.getExchangeRate();
4     uint256 mintAmount = (amount * assetToken.
      EXCHANGE_RATE_PRECISION()) / exchangeRate;
5     emit Deposit(msg.sender, token, amount);
6     assetToken.mint(msg.sender, mintAmount);
7     uint256 calculatedFee = getCalculatedFee(token, amount);
8     assetToken.updateExchangeRate(calculatedFee);
```

```
9         token.safeTransferFrom(msg.sender, address(assetToken), amount)
10     }
    ;
```

**Impact:****Proof of Concept:****Recommended Mitigation:****Medium****[M-1] Centralization risk for trusted owners**

**Impact:** Contracts have owners with privileged rights to perform admin tasks and need to be trusted to not perform malicious updates or drain funds.

*Instances (2):*

```
1 File: src/protocol/ThunderLoan.sol
2
3 223:     function setAllowedToken(IERC20 token, bool allowed) external
         onlyOwner returns (AssetToken) {
4
5 261:     function _authorizeUpgrade(address newImplementation) internal
         override onlyOwner { }
```

**[M-2] Using TSwap as price oracle leads to price and oracle manipulation attacks**

**Description:** The TSwap protocol is a constant product formula based AMM (automated market maker). The price of a token is determined by how many reserves are on either side of the pool. Because of this, it is easy for malicious users to manipulate the price of a token by buying or selling a large amount of the token in the same transaction, essentially ignoring protocol fees.

**Impact:** Liquidity providers will drastically reduced fees for providing liquidity.

**Proof of Concept:**

The following all happens in 1 transaction.

1. User takes a flash loan from [ThunderLoan](#) for 1000 [tokenA](#). They are charged the original fee [fee1](#). During the flash loan, they do the following:
  1. User sells 1000 [tokenA](#), tanking the price.

2. Instead of repaying right away, the user takes out another flash loan for another 1000 `tokenA`.
  1. Due to the fact that the way `ThunderLoan` calculates price based on the `TSwapPool` this second flash loan is substantially cheaper.

```
1 function getPriceInWeth(address token) public view returns (
    uint256) {
2     address swapPoolOfToken = IPoolFactory(s_poolFactory).
        getPool(token);
3     @> return ITSwapPool(swapPoolOfToken).
        getPriceOfOnePoolTokenInWeth();
4 }
```

3. The user then repays the first flash loan, and then repays the second flash loan.

I have created a proof of code located in my `audit-data` folder. It is too large to include here.

**Recommended Mitigation:** Consider using a different price oracle mechanism, like a Chainlink price feed with a Uniswap TWAP fallback oracle.

## Low

### [L-1] Empty Function Body - Consider commenting why

*Instances (1):*

```
1 File: src/protocol/ThunderLoan.sol
2
3 261:     function _authorizeUpgrade(address newImplementation) internal
        override onlyOwner { }
```

### [L-2] Initializers could be front-run

Initializers could be front-run, allowing an attacker to either set their own values, take ownership of the contract, and in the best case forcing a re-deployment

*Instances (6):*

```
1 File: src/protocol/OracleUpgradeable.sol
2
3 11:     function __Oracle_init(address poolFactoryAddress) internal
        onlyInitializing { }
```

```
1 File: src/protocol/ThunderLoan.sol
2
```



```

3 138:     function initialize(address tswapAddress) external initializer
      {
4
5 138:     function initialize(address tswapAddress) external initializer
      {
6
7 139:         __Ownable_init();
8
9 140:         __UUPSUpgradeable_init();
10
11 141:         __Oracle_init(tswapAddress);

```

### [L-3] Missing critical event emissions

**Description:** When the `ThunderLoan::s_flashLoanFee` is updated, there is no event emitted.

**Recommended Mitigation:** Emit an event when the `ThunderLoan::s_flashLoanFee` is updated.

```

1 +     event FlashLoanFeeUpdated(uint256 newFee);
2 .
3 .
4 .
5     function updateFlashLoanFee(uint256 newFee) external onlyOwner {
6         if (newFee > s_feePrecision) {
7             revert ThunderLoan__BadNewFee();
8         }
9         s_flashLoanFee = newFee;
10 +     emit FlashLoanFeeUpdated(newFee);
11 }

```

## Informational

### [I-1] Poor Test Coverage

|   |                                    |  |               |                |
|---|------------------------------------|--|---------------|----------------|
| 1 | Running tests...                   |  |               |                |
| 2 | File                               |  | % Lines       | % Statements   |
| 3 | % Branches   % Funcs               |  |               |                |
| 4 | src/protocol/AssetToken.sol        |  | 70.00% (7/10) | 76.92% (10/13) |
| 5 | src/protocol/OracleUpgradeable.sol |  | 100.00% (6/6) | 100.00% (9/9)  |
|   | 50.00% (1/2)   66.67% (4/6)        |  |               |                |
|   | 100.00% (0/0)   80.00% (4/5)       |  |               |                |

|   |  |                              |  |                |  |                |
|---|--|------------------------------|--|----------------|--|----------------|
| 6 |  | src/protocol/ThunderLoan.sol |  | 64.52% (40/62) |  | 68.35% (54/79) |
|   |  | 37.50% (6/16)                |  | 71.43% (10/14) |  |                |

**Recommended Mitigation:** Aim to get test coverage up to over 90% for all files.

## Gas

### [GAS-1] Using bools for storage incurs overhead

Use uint256(1) and uint256(2) for true/false to avoid a Gwarmaccess (100 gas), and to avoid Gsset (20000 gas) when changing from 'false' to 'true', after having been 'true' in the past. See source.

*Instances (1):*

```
1 File: src/protocol/ThunderLoan.sol
2
3 98:      mapping(IERC20 token => bool currentlyFlashLoaning) private
      s_currentlyFlashLoaning;
```

### [GAS-2] Using private rather than public for constants, saves gas

If needed, the values can be read from the verified contract source code, or if there are multiple values there can be a single getter function that returns a tuple of the values of all currently-public constants. Saves **3406-3606 gas** in deployment gas due to the compiler not having to create non-payable getter functions for deployment calldata, not having to store the bytes of the value outside of where it's used, and not adding another entry to the method ID table

*Instances (3):*

```
1 File: src/protocol/AssetToken.sol
2
3 25:      uint256 public constant EXCHANGE_RATE_PRECISION = 1e18;
```

```
1 File: src/protocol/ThunderLoan.sol
2
3 95:      uint256 public constant FLASH_LOAN_FEE = 3e15; // 0.3% ETH fee
4
5 96:      uint256 public constant FEE_PRECISION = 1e18;
```