

深圳市昱申科技有限公司

CHINA YOUNG SUN LED TECHNOLOGY CO., LTD.

TEL: (86) 755-28079401 28079402 28079403 28079404 28079405

Model No.: YSD-439AB4B-35

Applications:

■Full Color Display

■Banking Board

☐Digital Display

LED Chip Absolute Maximum Ratings: $(Ta=25^{\circ}C)$

Pararmeter	Symbol	Red	Unit	
Forward curret	IF	20	mA	
Peak forward current(Duty Cycle=10, 10KHz)	Ipf	30	mA	
Reverse voltage (V _R =5V)	IR	10	μА	
Operating temp	Topr	-25 - 85	$^{\circ}$	
Storage temp	Тѕтс	-30 - 85	$^{\circ}$ C	
Peak Emission Wavelenength	λРн	463	nm	

^{*} Soldering Bath: not more than 5 seconds @260 $^{\circ}$ C.The bottom ends of the plastic reflector should be at least 2mm above the solder surface

Soldering Iron: not more than 3 seconds @300 ℃ under 30W

LED Chip Typical Electircal & Optical Chara Qeristics: (Ta=25 ℃)

ITEMS	Symbol	Condition	Min.	Тур.	Max.	Unit	
Forward Voltage	VF	I _F =20mA	3.2	3.4	3.5	V	
Luminous Intensity	Iv	I _F =20mA	150	200	250	mcd	
Wavelenength	Δλ	I _F =20mA	460	463	465	nm	
Light Degradation after 1000 hours		-4.68% ~ -8.27%					

Address: 5/F, Building B, Anzhilong Indl., Qinghua East Road., Longhua Town, Shenzhen CHINA. 518109



深圳市昱申科技有限公司


CHINA YOUNG SUN LED TECHNOLOGY CO., LTD.


TEL: (86) 755-28079401 28079402 28079403 28079404 28079405


Mechanical Dimensions:


. All dimension are in mm, tolerance is ± 0.2 mm unless otherwise noted


. An epoxy meniscus may extend about 1.5mm down the leads.











Address F/F Building B. Angleing India Objective Feet Book Learning Trans Objective OUBLA F40400

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

SparkFun Electronics: COM-09481