	₽Logo
(ETAILS Name Ref 16 27 1. Sept. 16 25 1. Sept. 16
RATECH	STUDENT REPORT CONTRICT CONTRI
NG P	Name Referring to the standard of the standard
D,	FTAILS CSELOST TEMBERS SELECTED STEMBERS SECURIOR TEMBERS SELECTED SELECTION WAS SELECTED SEL
	Elles Period Sept.
50	
	ABDUL REHAMAN
S	Roll Number My Co Letter Letter 1000 1000 1000 1000 1000 1000 1000 10
Lech'	TEMPBTech-CSE065
E)	XPERIMENT OF THE SECOND
S LEW TI	une state to the state of the s
S)	ANT ON RAIL SELLOS TEMPETERINGS TO SELLOS TE
(estronger energy and the second secon
,chr.cst.o	Description of the second of t
, ch	There is a ant on your balcony. It wants to leave the rail so sometimes it moves right and sometimes it moves left until it gets exhausted. Given an integer array A of size N which consists of integer 1 and -1 only representing ant's moves.
	exhausted.Given an integer array A of size N which consists of integer 1 and -1 only representing ant's moves.
EMPBIC	Where 1 means ant moved unit distance towards the right side and -1 means it moved unit distance towards the left . Your task
EM	
	Note:
(6)	Assume 1-based indexing
cstobb	Assume that the railing extends infinitely on the either sides Input Format:
	Input Format:
ch.	
MPBTech	input1 : An integer value N representing the number of moves made by the ant. input2 : An integer array A consisting of the ant's moves towards either side
7	76.3
	Sample input
£065 [E]	5 1-11-11
	1-11-11 _{ctr} . C ⁵
c	Sample Output
atechice.	2
8	
4	Source Code: Source Code: Sourc
EMP	The state of the s
	The state of the s
	The real of the second of the
	The property of the state of th
	Source Code: Source Code: Sourc
	Thurst for the street of the s
	Source Code: Source Code: Sourc
	TEMP 85. THE FLOOR TEMP 81 COLUMN STEP SELD STEP 1 SELD SELD STEP 1 SELD STEP 1 SELD SELD SELD STEP 1 SELD SELD SELD SELD SELD SELD SELD SELD
	Source Code: Source Code: Sourc

```
def count_returns_to_start(N, A):
    current_position = 0
    return_count = 0

for move in A:
        current_position += move
        if current_position == 0:
            return_count += 1

    return return_count

# Example usage:
    N = int(input())
    A = list(map(int,input().split())) # Example moves
    result = count_returns_to_start(N, A)
    print(result) # Output: 3

RESULT

5/5 Test Cases Passed | 100 %
```