



COMVERSE
UNIVERSITY

SAPI Preventive Maintenance

Lesson Objectives

By the end of this lesson you will be able to:

- Extract data on SAPI settings and usage
- Perform UPA checks
- Extract Score-related data
- Monitor SAPI time zone settings
- Monitor SAPI processes, configuration and connectivity settings
- Perform SAPI health checks
- Monitor ASYNC activity

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

Basic Data

- Check the hostname.

=> **sapi1: hostname**

```
sapi1
```

- Verify that it is Linux.

=> **sapi1: uname -a**

```
Linux sapi1 2.6.18-53.el5PAE #1 SMP Wed Oct 10 16:48:18 EDT  
2007 i686 i686 i386 GNU/Linux
```

Check Score Version

=> **sapi1: version**

```
MASTER_DISK_RELEASE: CMV1 LNX SCORE
MD_VERSION: 2.1.0
INSTALLATION_TYPE: CMV1 SAPI
CMV1_COMPONENT: SAPI
SIZING: NORMAL
KICKSTART_FILE: ksLNX2sapi.cfg
CMV1_MD_BUILD_DATE: 24-Apr-2009
CMV1_LNX_SCORE: 2.1.0
HW_TYPE: DPM3
KERNEL_VERSION: 2.6.18-53.el5
INSTALL_DATE: 07-Jun-2010 at 07:36:26
RED_HAT: Red Hat Enterprise Linux Server 5 update 1
CMV1-ENV: 2.1.0-2
```

Check SAPI Packages Installed on this Host

=> sapi1: rpm -qa|grep -iE

'CBS_SAPI|CBS_RHT|CBS_ASYNC|CBS_WORKFLOW|weblogic'

```
CMV1-Oracle-BEA-WebLogic-10.3-2
```

```
CBS_SAPI-3.5.20.0-1.40.0_5.0.0_1
```

Check Installed UPA Packages

=> sapi1: cat /home/jboss/conf/version.properties| grep -v '^#'

```
base.package=3.5.15.4
command.package=3.5.15.4
configuration.package=3.5.15.4
inventory.package=3.5.15.4
job.package=3.5.15.4
monitor.package=3.5.15.4
process.package=3.5.15.4
rules.package=3.5.15.4
sysaudit.package=3.5.15.4
workflow.package=3.5.15.4
```

Check Installed UPA Version

=> **sapi1: mshell secadmin/***** version**

COMMAND :

NodeClass	NodeName	NodeInstance	BuildID	Platform
OS Version	OS Model	OS Arch	Base	
SAPI	sapi1	10.20.64.86	05/13/2010 04:39	Linux
2.6.18-53.el5PAE	i686	i386	3.5. 15.4	

LD Packages

- Check LD Packages Installed on this Host
=> **sapi1: rpm -qa|grep -i lnxLD**

```
CMV1-lnxLD-2.11-1
```

- Check Status of LD
=> **sapi1: lnxLD status**

```
Locking lnxLD. PID 30413 ...locked. [ OK ]
Checking for LNX-SCORE [ OK ]
LD2 is the active LD and is in runlevel N 3 [ OK ]
Host supports LD operations [ OK ]
iLD is not mounted [ OK ]
/XDISK is not mounted [ OK ]
Default boot is: LD # (2) LNX SCORE [ OK ]
Un-mounting /XDISK [ OK ]
LD-enabled disk layout [ OK ]
Detected DPM3 hardware [ OK ]
```

Check iLDs

- Try to enter the iLD shell environment.
=> **sapi1: InxLD ild**
- Check the iLD environment.
=> **sapi1: env|grep LD**
- Try to exit from the iLD shell environment.
=> **sapi1 [LNX_SCORE_2_LD:ILD_ENV:mount]: exit**

```
exit
Disabling the /dev filesystem in the iLD [    OK    ]
Disabling the /proc filesystem in the iLD [    OK    ]
Inactive logical disk (iLD) unmounted [    OK    ]
```

Validate /etc/hosts File

- Validate the /etc/hosts file entries for remote hosts.

=> sapi1: **grep -vE "^\$|^#|^hostname`" /etc/hosts|awk '{print \$1" "\$2" "\$3" "\$4}'|sort**

- Validate the /etc/hosts file entries for the host itself.

=> sapi1: **grep -v '^#' /etc/hosts|grep `hostname`|awk '{print \$1" "\$2" "\$3}'|sort**

```
10.20.64.77  rht1.plus.c1  rht1
10.20.64.78  rht2.plus.c1  rht2
10.20.64.79  omsapi1.plus.c1  omsapi1
10.20.64.86  sapi1.plus.c1  sapi1
10.20.66.101 sapi1-1
```

Resource Utilization (1)

- Check for the last host reboot.

=> **sapi1: uptime**

```
12:20:58 up 18 days, 9:15, 3 users, load average: 0.30, 0.11, 0.12
```

- Check the memory usage.

=> **sapi1: free -m**

total	used	free	shared	buffers	cached	
Mem:	3925	3769	155	0	32	1423
-/+ buffers/cache:		2314	1610			
Swap:	2384	0	2384			

Resource Utilization (2)

Check the 5 processes that are using the most memory.

=> **sapi1: ps -eo user,pid,size,rss,args | sort -k 4nr | cut -C1-100 | head -5**

```
apiuser 20501 1597332 1400868 /usr/java/jdk1.6.0_12/bin/java -
server -XX:MaxPermSize=256m -XX:+UseP
apiuser 25613 964740 718728 /usr/java/jdk1.6.0_12/bin/java -server
-XX:MaxPermSize=256m -XX:+UsePar
root 20826 427928 254108 /usr/java/jdk1.5.0_14/bin/java -
Dprogram.name=run.sh -Dmy.hostname=sapi
ntp 2063 832 4216 ntpd -u ntp -p /var/run/ntpd.pid -g
root 19625 756 2804 sshd: root@pts/4
```

Resource Utilization (3)

Check the CPU utilization.

=> **sapi1: sar 3 3**

```
Linux 2.6.18-53.el5PAE (sapi1) 06/07/2011
```

12:20:58 PM	CPU	%user	%nice	%system	%iowait
%steal	%idle				
12:21:01 PM	all	1.00	0.00	0.33	7.15
0.00	91.51				
12:21:04 PM	all	2.00	0.00	0.33	0.00
0.00	97.67				
12:21:07 PM	all	3.83	0.00	5.32	0.17
0.00	90.68				
Average:	all	2.27	0.00	2.00	2.44
0.00	93.29				

Resource Utilization (4)

Check the disk usage.

=> **sapi1: df -k**

Filesystem	1K-blocks	Used	Available	Use%	Mounted on
/dev/sda2	2885812	1831548	907672	67%	/
/dev/sda5	18922876	9115020	8831108	51%	/data
/dev/sda3	43264176	29427848	11638636	72%	/home
tmpfs	2009648	0	2009648	0%	/dev/shm

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

UPA Tests (1)

- Check the UPA maintenance mode.

=> `sapi1 [LNX_UPA_3:UPA_VERSION:version]: mshell
secadmin/***** maintenance_mode`

Should be disabled

COMMAND :				
Site name	NodeClass	NodeName	NodeInstance	Message
M4AL	SAPI	sapi1	10.20.64.86	Maintenance
Mode is disabled				

- Verify that inittab contains the agentStartup entry.

=> `sapi1: cat /etc/rc.d/rc.local|grep agent`

/home/jboss/bin/**agentStartup**

UPA Tests (2)

- Verify that the agent is running on the node.

=> **sapi1 [LNX_UPA_3:UPA_VERSION:version]: mshell
secadmin/***** status**

- Verify the active events.

=> **sapi1 [LNX_UPA_3:UPA_VERSION:version]: mshell
secadmin/***** list_active_events**

COMMAND :

SiteID	NodeClass	NodeName	EventID
Severity	Instance	TimeStamp	Escalated
Acknowledged			

UPA Tests (3)

- Verify that the monitors are enabled and that there is no blackout.

```
=> sapi1 [LNX_UPA_3:UPA_VERSION:version]: mshell  
secadmin/***** list_monitors
```

- Verify that workflows are enabled on the node.

```
=> sapi1 [LNX_UPA_3:UPA_VERSION:version]: mshell  
secadmin/***** list_workflows
```

- Verify that jobs and tasks are enabled on the node

```
=> 1 [LNX_UPA_3:UPA_VERSION:version]: mshell  
secadmin/***** list_jobs
```

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

Check Installed Packages

Check the packages that are installed on this host.

=> `sapi1: rpm -qa --last|grep -Ei 'CMV|RTB|CBS|comverse'`

Verify File Limits

Verify the Hard and Soft open file limits.

=> **sapi1: ulimit -Sn;ulimit -Hn**

Should be more than 2000 as required for UP Manager and SAPI, ASU

8192

8192

Checking LD Configuration

Check the LD config file.

=> **sapi1: cat /etc/sysconfig/ldconf**

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

NTP Configuration

Output NTP Configuration

=> **sapi1: /usr/sbin/ntpq -p**

remote	refid	st	t	when	poll	reach	delay	offset	jitter
=====	=====	=====	=====	=====	=====	=====	=====	=====	=====
upm1	10.20.115.32	3	u	16d	1024	0	8.748	2.880	0.000
*upm2	10.20.115.32	3	u	287	1024	377	7.500	0.384	3.021

Time Zone Checks (1)

- Compare between nodes where the ZONE and date outputs are the same.

=> sapi1: `grep -v '^#' /etc/sysconfig/clock;date +"%a %b %d %H:%M %Z %Y"`

```
ZONE="Europe/Tirane"  
UTC=false  
ARC=false  
Tue Jun 07 12:21 CEST 2011
```

=> sapi2: `grep -v '^#' /etc/sysconfig/clock;date +"%a %b %d %H:%M %Z %Y"`

```
ZONE="Europe/Tirane"  
UTC=false  
ARC=false  
Tue Jun 07 12:21 CEST 2011
```

Time Zone Checks (2)

Check that /etc/localtime is linked to a proper file, and not to a copy of a file.

=> **sapi1: ls -l /etc/localtime**

```
-rw-r--r-- 4 root root 2084 Mar 23 2007 /etc/localtime
```

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

Check SAPI Processes (1)

Verify that the SAPI processes are running.

=> **sapi1: ps -ef |grep bea |grep -v grep**

```
apiuser  20501      1   6 05:28 ?                00:27:49 /usr/java/jdk1.6.0_12/bin/java -server -XX:MaxPermSize=256m -
XX:+UseParNewGC -XX:MaxNewSize=256m -XX:NewSize=256m -Xms1024m -Xmx1024m -XX:SurvivorRatio=128 -
XX:MaxTenuringThreshold=0 -XX:+UseTLAB -XX:+UseConcMarkSweepGC -XX:+CMSClassUnloadingEnabled -
Dweblogic.security.SSL.trustedCAKeyStore=/home/bea10.3/wlserver_10.3/server/lib/cacerts -Xverify:none -
Xverify:none -da -Dplatform.home=/home/bea/wlserver_10.3 -Dwls.home=/home/bea/wlserver_10.3/server -
Dweblogic.home=/home/bea/wlserver_10.3/server -Dwli.home=/home/bea/wlserver_10.3/integration -
Dweblogic.management.discover=false -Dweblogic.management.server=http://sapi1.plus.cl:7001 -Dwlw.iterativeDev=
-Dwlw.testConsole= -Dwlw.logErrorsToConsole= -
Dweblogic.ext.dirs=/home/bea/patch_wls1030/profiles/default/sysexm_manifest_classpath:/home/bea/patch_cie660/p
rofiles/default/sysexm_manifest_classpath -Dweblogic.ProductionModeEnabled=true -
Dweblogic.management.username=weblogic -Dweblogic.management.password=weblogic -Djava.endorsed.dirs=/endorsed
-Djava.security.auth.login.config=/home/sapi/server/domain/config/securityframework_config/sec_jaas.conf -
Dbea.home=/home/bea -Dweblogic.webservice.client.ssl.adapterclass=weblogic.webservice.client.JSSEAdapter -
Dweblogic.webservice.client.ssl.strictcertchecking=false -Dweblogic.security.SSL.enforceConstraints=off -
Dweblogic.security.SSL.allowSmallRSAExponent=true -Dweblogic.Name=MS_sapi1.plus.cl -
Djava.security.policy=/home/bea/wlserver_10.3/server/lib/weblogic.policy -
Djava.security.egd=file:///dev/urandom weblogic.Server
apiuser  25613      1   0 May20 ?                01:34:37 /usr/java/jdk1.6.0_12/bin/java -server -XX:MaxPermSize=256m -
XX:+UseParNewGC -XX:MaxNewSize=256m -XX:NewSize=256m -Xms512m -Xmx512m -XX:SurvivorRatio=128 -
XX:MaxTenuringThreshold=0 -XX:+UseTLAB -XX:+UseConcMarkSweepGC -XX:+CMSClassUnloadingEnabled -Xverify:none -
Xverify:none -da -Dplatform.home=/home/bea/wlserver_10.3 -Dwls.home=/home/bea/wlserver_10.3/server -
Dweblogic.home=/home/bea/wlserver_10.3/server -Dwli.home=/home/bea/wlserver_10.3/integration -
Dweblogic.management.discover=true -Dwlw.iterativeDev= -Dwlw.testConsole= -Dwlw.logErrorsToConsole= -
Dweblogic.ext.dirs=/home/bea/patch_wls1030/profiles/default/sysexm_manifest_classpath:/home/bea/patch_cie660/p
rofiles/default/sysexm_manifest_classpath -Dweblogic.ProductionModeEnabled=true -Djava.endorsed.dirs=/endorsed
-Djava.security.auth.login.config=/home/sapi/server/domain/config/securityframework_config/sec_jaas.conf -
Dbea.home=/home/bea -Dweblogic.webservice.client.ssl.adapterclass=weblogic.webservice.client.JSSEAdapter -
Dweblogic.webservice.client.ssl.strictcertchecking=false -Dweblogic.security.SSL.enforceConstraints=off -
Dweblogic.security.SSL.allowSmallRSAExponent=true -Dweblogic.Name=ADMIN -
Djava.security.policy=/home/bea/wlserver_10.3/server/lib/weblogic.policy -
Djava.security.egd=file:///dev/urandom weblogic.Server
```

Check SAPI Processes (2)

Verify that the SAPI processes are enabled and running on the node.

=> **sapi1 [LNX_UPA_3:UPA_VERSION:version]: mshell
secadmin/***** list_processes**

COMMAND :

Process Listing

SiteID	NodeClass	NodeName	NodeInstance	Group
Name	Pid	State	Status	Type
ModuleName	StartTime		Valid	ServerID
M4AL	sapi	sapi1	10.20.64.86	
application	sapi_admin	--	ENABLED	scheduled
non-instrumented	--	--		VALID
--				

Check LAN Status

- Check the LAN interfaces. Verify the IP address, netmask.

=> **sapi1: ifconfig -a**

- Check the LAN routing.

=> **sapi1: netstat -nr**

```
Kernel IP routing table
Destination      Gateway          Genmask          Flags        MSS Window
 irtt Iface
10.20.16.160     10.20.64.65     255.255.255.240 UG           0  0
0 eth4
10.20.16.0       10.20.64.65     255.255.255.192 UG           0  0
0 eth4
10.20.64.64      0.0.0.0         255.255.255.192 U            0  0
0 eth4
10.20.66.0       0.0.0.0         255.255.255.0   U            0  0
0 eth0
0.0.0.0         10.20.64.68    0.0.0.0        UG           0  0
0 eth4
```

Verify Ping Success

Verify that a ping succeeds with no loss of packets.

=> **sapi1: ping -c 20 -f localhost**

```
PING localhost.localdomain (127.0.0.1) 56(84) bytes of data.  
. . . . .  
.  
--- localhost.localdomain ping statistics ---  
20 packets transmitted, 20 received, 0% packet loss, time 0ms  
rtt min/avg/max/mdev = 0.002/0.003/0.016/0.003 ms, ipg/ewma  
0.012/0.004 ms
```


Checking TNSNames File

- Check the tnsnames file content.

```
=> sapi1: su - oracle -c "cat  
$ORACLE_HOME/network/admin/tnsnames.ora|grep -v  
'^#'"
```

Check SAPI Environment

- Check the Apiuser environment.

=> **sapi1: su - apiuser -c "env|grep -Ei 'SAPI|JAVA'"**

```
HOSTNAME=sapi1
PATH=/home/oracle/product/10.2.0/client_1/bin:/usr/java/jdk1.6.0_12/
bin:/usr/java/jdk1.5.0_14/bin:/home/jboss/bin:/usr/kerberos/bin:/usr
/local/bin:/bin:/usr/bin:/home/apiuser/bin
JAVA_HOME=/usr/java/jdk1.6.0_12
CBS_SAPI_SERVER_INSTALLDIR=/home/sapi/server
```

- Check the installed SAPI environment.

=> **sapi1 [LNX_SAPI_SERVER:SAPI_ENV:sapi_home]: cat
/home/sapi/server/bin/install.env|grep -v '^#';cat
/home/sapi/server/bin/configure_sapi.sh|grep -v '^#'**

Check SAPI Configuration Files

- config.xml file
=> sapi1 [LNX_SAPI_SERVER:SAPI_INSTALL_ENV:domain_dir]: cat /home/sapi/server/domain/config/config.xml
- CCBSSConfiguration.properties file
=> sapi1 [LNX_SAPI_SERVER:SAPI_INSTALL_ENV:domain_dir]: cat /home/sapi/server/domain/config/CCBSSConfiguration.properties|grep -v '^#'
- workpoint-client.properties file. N/A for PREPAID.
=> sapi1 [LNX_SAPI_SERVER:SAPI_INSTALL_ENV:domain_dir]: cat /home/sapi/server/domain/config/workpoint-client.properties|grep -v '^#'

Check SAPI Connectivity

- Check the SAPI deployed mode and the connected databases.

```
=> sapi1: wget -O - sapi1.plus.c1:7001/sapi/db_info.jsp;for i  
in `echo "sapi1.plus.c1:8001,sapi2.plus.c1:8001"|sed 's/,/ /g';  
do wget -O - $i/sapi/db_info.jsp; done
```

- Check the SAPI connection to Workpoint (n/a for Prepaid).

```
=> sapi1  
[LNX_SAPI_SERVER:SAPI_WORKPOINT:naming_provider]:  
for i in `echo "rht1.plus.c1:8051,rht2.plus.c1:8051"|sed 's/,/  
/g'; do wget -O - $i/wpConsole; done
```

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

SAPI Health Check

Check SAPI health.

```
=> sapi1: wget -O - sapi1.plus.c1:7001/H.jsp;for i in `echo  
"sapi1.plus.c1:8001,sapi2.plus.c1:8001"|sed 's/,/ /g`; do wget  
-O - $i/H.jsp; done
```

Agenda

Settings and Usage

UPA

Score

Time Zone

Processes, Configuration, and Connectivity

Health Checks

ASYNC

ASYNCH Configuration

Check the cbsuser environment for ASYNCH.

=> **sapi1 [LNX_SAPI:SAPI_RPM:cbs_asynch]: N/A**

Check the workpoint-client.properties file for ASYNCH. (n/a for Prepaid).

=> **sapi1 [LNX_SAPI_SERVER:ASYNCH_ENV:batch_home]: N/A**

ASYNCH connection to Workpoint. (n/a for Prepaid).

=> **sapi1**

**[LNX_SAPI_SERVER:ASYNCH_WORKPOINT:naming_provider]:
N/A**

Verify the ASYNCH process is running.

=> **sapi1 [LNX_SAPI_SERVER:ASYNCH_ENV:batch_home]: N/A**

Summary

This lesson has covered:

- SAPI settings and usage
- UPA checks
- Score checks
- Time Zone monitoring
- SAPI processes, configuration and connectivity settings
- SAPI health checks
- ASYNCH activity monitoring

Thank
You!



COMVERSE
UNIVERSITY