

Complexity

Asai Asaithambi

Fall 2016

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis
 - Based on Pseudocode Notation

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis
 - Based on Pseudocode Notation
 - Based on TM Descriptions

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis
 - Based on Pseudocode Notation
 - Based on TM Descriptions
- Classes P and NP

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis
 - Based on Pseudocode Notation
 - Based on TM Descriptions
- Classes P and NP
 - Example Problems in P

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis
 - Based on Pseudocode Notation
 - Based on TM Descriptions
- Classes P and NP
 - Example Problems in P
 - Example Problems in NP

Topic Overview

Complexity

Asai
Asaithambi

What does this topic cover?

- Terminology
 - TM Recognizable/Decidable
 - Algorithms and Complexity
 - Big O and Small o Notation
- Some Algorithm Analysis
 - Based on Pseudocode Notation
 - Based on TM Descriptions
- Classes P and NP
 - Example Problems in P
 - Example Problems in NP
 - NP Completeness

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT
Never deciding whether to accept/reject.

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT
Never deciding whether to accept/reject.
- A TM that halts on all inputs is called a *decider*.

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT
Never deciding whether to accept/reject.
- A TM that halts on all inputs is called a *decider*.
- A decider recognizing a language:

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT
Never deciding whether to accept/reject.
- A TM that halts on all inputs is called a *decider*.
- A decider recognizing a language:
is also said to “decide” that language.

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT
Never deciding whether to accept/reject.
- A TM that halts on all inputs is called a *decider*.
- A decider recognizing a language:
is also said to “decide” that language.
- A language is said to be “Decidable”

Terminology: TM Recognizable/Decidable

Complexity

Asai
Asaithambi

- A language is “Turing-Recognizable”:
If some TM recognizes it.
- On processing an input string, a TM may:
 - Reach an ACCEPT state
Accepting the string; or
 - Reach a REJECT state
Rejecting the string; or
 - Never HALT
Never deciding whether to accept/reject.
- A TM that halts on all inputs is called a *decider*.
- A decider recognizing a language:
is also said to “decide” that language.
- A language is said to be “Decidable”
if some TM decides it.

The Language Onion


Complexity

Asai
Asaithambi

The Language Onion

Complexity


Asai
Asaithambi



The Language Onion

Complexity

Asai
Asaithambi




- Every decidable language is Turing-Recognizable,

The Language Onion

Complexity

Asai
Asaithambi




- Every decidable language is Turing-Recognizable, but not conversely.

The Language Onion

Complexity

Asai
Asaithambi



- Every decidable language is Turing-Recognizable, but not conversely.
- All examples of the languages we have seen are decidable.

Why Study Complexity?

Complexity

Asai
Asaithambi

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:
 - the function $f : \mathbb{N} \mapsto \mathbb{N}$,

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:
 - the function $f : \mathbb{N} \mapsto \mathbb{N}$,
 - where $f(n)$ is the maximum number of steps that

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:
 - the function $f : \mathbb{N} \mapsto \mathbb{N}$,
 - where $f(n)$ is the maximum number of steps that M uses on any input of length n .

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:
 - the function $f : \mathbb{N} \mapsto \mathbb{N}$,
 - where $f(n)$ is the maximum number of steps that M uses on any input of length n .
- If the running time of M is $f(n)$, then we say that

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:
 - the function $f : \mathbb{N} \mapsto \mathbb{N}$,
 - where $f(n)$ is the maximum number of steps that M uses on any input of length n .
- If the running time of M is $f(n)$, then we say that
- M runs in time $f(n)$ and that M is an $f(n)$ time TM.

Why Study Complexity?

Complexity

Asai
Asaithambi

- Is a TM looping or simply taking a long time to decide?
- Knowing how much time a TM will need may be useful.
- How do we characterize the time that may be required?
 - Let M be a deterministic TM that halts on all inputs.
 - The *running time* or *time complexity* of M is:
 - the function $f : \mathbb{N} \mapsto \mathbb{N}$,
 - where $f(n)$ is the maximum number of steps that M uses on any input of length n .
- If the running time of M is $f(n)$, then we say that
- M runs in time $f(n)$ and that M is an $f(n)$ time TM.
- Customarily we use n to represent the length of the input.

Big O Notation

Complexity

Asai
Asaithambi

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function,

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$,

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
- positive integers c and n_0 exist such that:

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.
- When $f(n) = O(g(n))$, we say that:

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.
- When $f(n) = O(g(n))$, we say that:
 $g(n)$ is an

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.
- When $f(n) = O(g(n))$, we say that:
 $g(n)$ is an *upper bound* for $f(n)$.

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.
- When $f(n) = O(g(n))$, we say that:
 - $g(n)$ is an *upper bound* for $f(n)$.
- More precisely:

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.
- When $f(n) = O(g(n))$, we say that:
 - $g(n)$ is an *upper bound* for $f(n)$.
- More precisely:
 - $g(n)$ is an *asymptotic upper bound* for $f(n)$.

Big O Notation

Complexity

Asai
Asaithambi

- It is not necessary to know the *exact* amount of time.
- How fast does $f(n)$ grow as n grows?
- Compare $f(n)$ with another *standard* function, say, $g(n)$.
- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = O(g(n))$, (read $f(n)$ is Big O of $g(n)$), if:
 - positive integers c and n_0 exist such that:
 - for every integer $n \geq n_0$, it is true that $f(n) \leq c g(n)$.
- When $f(n) = O(g(n))$, we say that:
 - $g(n)$ is an *upper bound* for $f(n)$.
- More precisely:
 - $g(n)$ is an *asymptotic upper bound* for $f(n)$.
- We suppress constant factors.

Big O Notation: Example

Complexity

Asai
Asaithambi

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.
- This means that $n^3 - 2n^2 - 22n - 6 \geq 0$.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.
- This means that $n^3 - 2n^2 - 22n - 6 \geq 0$.
- The above inequality holds for $n \geq 6$.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.
- This means that $n^3 - 2n^2 - 22n - 6 \geq 0$.
- The above inequality holds for $n \geq 6$.
- Thus, we have $f(n) \leq 6n^3$ for $n \geq 6$.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.
- This means that $n^3 - 2n^2 - 22n - 6 \geq 0$.
- The above inequality holds for $n \geq 6$.
- Thus, we have $f(n) \leq 6n^3$ for $n \geq 6$.
- Therefore $f(n) = O(n^3)$.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.
- This means that $n^3 - 2n^2 - 22n - 6 \geq 0$.
- The above inequality holds for $n \geq 6$.
- Thus, we have $f(n) \leq 6n^3$ for $n \geq 6$.
- Therefore $f(n) = O(n^3)$.
- Note that $f(n) = O(n^k)$ for all $k \geq 3$.

Big O Notation: Example

Complexity

Asai
Asaithambi

- Let $f(n) = 5n^3 + 2n^2 + 22n + 6$
- Then, $f(n) = O(n^3)$
- Note that $5n^3$ is the fastest growing term.
- All the other terms can be bounded by n^3 .
- In other words, we could show that
- $f(n) = 5n^3 + 2n^2 + 22n + 6 \leq 6n^3$ for some $n \geq n_0$.
- This means that $n^3 - 2n^2 - 22n - 6 \geq 0$.
- The above inequality holds for $n \geq 6$.
- Thus, we have $f(n) \leq 6n^3$ for $n \geq 6$.
- Therefore $f(n) = O(n^3)$.
- Note that $f(n) = O(n^k)$ for all $k \geq 3$.
- Note also that $f(n) \neq O(n^k)$ for any $k < 3$.

Big O Notation (cont.)

Complexity

Asai
Asaithambi

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.
- Other forms of growth functions:

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.
- Other forms of growth functions:

$$f(n) = O(n^2) + O(n) \Rightarrow f(n) = O(n^2)$$

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.
- Other forms of growth functions:
$$f(n) = O(n^2) + O(n) \Rightarrow f(n) = O(n^2)$$
$$f(n) = 2^{O(n)} \Rightarrow f(n) = 2^{cn} \text{ for some constant } c > 0.$$

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.
- Other forms of growth functions:

$$f(n) = O(n^2) + O(n) \Rightarrow f(n) = O(n^2)$$

$$f(n) = 2^{O(n)} \Rightarrow f(n) = 2^{cn} \text{ for some constant } c > 0.$$

$$n = 2^{\log_2 n} \Rightarrow n^c = 2^{c \log_2 n} = 2^{O(\log n)}.$$

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.
- Other forms of growth functions:
 - $f(n) = O(n^2) + O(n) \Rightarrow f(n) = O(n^2)$
 - $f(n) = 2^{O(n)} \Rightarrow f(n) = 2^{cn}$ for some constant $c > 0$.
 - $n = 2^{\log_2 n} \Rightarrow n^c = 2^{c \log_2 n} = 2^{O(\log n)}$.
- *Polynomial Bounds:* n^c for $c > 0$.

Big O Notation (cont.)

Complexity

Asai
Asaithambi

- Note $\log_a n = \log_b n / \log_b a$
- $\log_a n = O(\log n)$ as they differ by a constant factor.
- Suppose $f(n) = 3n \log_2 n + \log_2 \log_2 n + 2$.
- Then, $f(n) = O(n \log n)$.
- Other forms of growth functions:
 - $f(n) = O(n^2) + O(n) \Rightarrow f(n) = O(n^2)$
 - $f(n) = 2^{O(n)} \Rightarrow f(n) = 2^{cn}$ for some constant $c > 0$.
 - $n = 2^{\log_2 n} \Rightarrow n^c = 2^{c \log_2 n} = 2^{O(\log n)}$.
- *Polynomial Bounds:* n^c for $c > 0$.
- *Exponential Bounds:* 2^{n^δ} for $\delta > 0$.

Small o Notation

Complexity

Asai
Asaithambi

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = o(g(n))$,

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = o(g(n))$, (read $f(n)$ is Small o of $g(n)$), if:

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = o(g(n))$, (read $f(n)$ is Small o of $g(n)$), if:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = o(g(n))$, (read $f(n)$ is Small o of $g(n)$), if:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

- Equivalently, for any real number $c > 0$,

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = o(g(n))$, (read $f(n)$ is Small o of $g(n)$), if:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

- Equivalently, for any real number $c > 0$,
there exists an integer n_0 such that:

Small o Notation

Complexity

Asai
Asaithambi

- Let f and g be functions, $f, g : \mathbb{N} \mapsto \mathbb{R}^+$.
- We say $f(n) = o(g(n))$, (read $f(n)$ is Small o of $g(n)$), if:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = 0.$$

- Equivalently, for any real number $c > 0$,
there exists an integer n_0 such that:
- For every integer $n \geq n_0$, it is true that $f(n) < c g(n)$.

Analysis of Algorithms

Complexity

Asai
Asaithambi

Analysis of Algorithms

Complexity

Asai
Asaithambi

- Size or problem (n)

Analysis of Algorithms

Complexity

Asai
Asaithambi

- Size or problem (n)
- Basic operation (varies with algorithm)

Analysis of Algorithms

Complexity

Asai
Asaithambi

- Size or problem (n)
- Basic operation (varies with algorithm)
- Number of times the basic operation gets executed

Analysis of Algorithms

Complexity

Asai
Asaithambi

- Size or problem (n)
- Basic operation (varies with algorithm)
- Number of times the basic operation gets executed
- Express as a function of n

Analysis of Algorithms

Complexity

Asai
Asaithambi

- Size of problem (n)
- Basic operation (varies with algorithm)
- Number of times the basic operation gets executed
- Express as a function of n
- Analyze the growth of $f(n)$ as n is increased

Analysis of Algorithms

Complexity

Asai
Asaithambi

- Size of problem (n)
- Basic operation (varies with algorithm)
- Number of times the basic operation gets executed
- Express as a function of n
- Analyze the growth of $f(n)$ as n is increased
- Use Big O notation

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

This is expressed as $O(n)$.

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

This is expressed as $O(n)$.

Consider another example:

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

This is expressed as $O(n)$.

Consider another example:

```
for (i = 1; i < n; i *= 2)  
    print "Hello"
```

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

This is expressed as $O(n)$.

Consider another example:

```
for (i = 1; i < n; i *= 2)  
    print "Hello"
```

Hello is printed k times, with $2^{k-1} < n \leq 2^k$.

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

This is expressed as $O(n)$.

Consider another example:

```
for (i = 1; i < n; i *= 2)  
    print "Hello"
```

Hello is printed k times, with $2^{k-1} < n \leq 2^k$.

This amounts to $\lceil \log_2 n \rceil$ times.

Algorithm Analysis: Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = 0; i < n; i++)  
    print "Hello"
```

Hello is printed n times.

This is expressed as $O(n)$.

Consider another example:

```
for (i = 1; i < n; i *= 2)  
    print "Hello"
```

Hello is printed k times, with $2^{k-1} < n \leq 2^k$.

This amounts to $\lceil \log_2 n \rceil$ times.

This is expressed as $O(\log n)$.

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

Algorithm Analysis: Examples (cont.)

Complexity

How many times is Hello printed?

Asai
Asaithambi

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)  
    print "Hello"
```

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

This is expressed as $O(\log n)$.

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

This is expressed as $O(\log n)$.

Consider another example:

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

This is expressed as $O(\log n)$.

Consider another example:

```
for (i = n; i > 0; i /= 3)
    print "Hello"
```

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

This is expressed as $O(\log n)$.

Consider another example:

```
for (i = n; i > 0; i /= 3)
    print "Hello"
```

Hello is printed k times, with $3^{k-1} \leq n < 3^k$.

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

This is expressed as $O(\log n)$.

Consider another example:

```
for (i = n; i > 0; i /= 3)
    print "Hello"
```

Hello is printed k times, with $3^{k-1} \leq n < 3^k$.

This amounts to $\lfloor \log_3 n \rfloor + 1$ times.

Algorithm Analysis: Examples (cont.)

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (i = n; i > 0; i /= 2)
    print "Hello"
```

Hello is printed k times, with $2^{k-1} \leq n < 2^k$.

This amounts to $\lfloor \log_2 n \rfloor + 1$ times.

This is expressed as $O(\log n)$.

Consider another example:

```
for (i = n; i > 0; i /= 3)
    print "Hello"
```

Hello is printed k times, with $3^{k-1} \leq n < 3^k$.

This amounts to $\lfloor \log_3 n \rfloor + 1$ times.

This is also expressed as $O(\log n)$.

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

Algorithm Analysis: More Examples

Complexity

How many times is Hello printed?

Asai
Asaithambi

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Hello is printed n^2 times.

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Hello is printed n^2 times.

This is expressed as $O(n^2)$.

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Hello is printed n^2 times.

This is expressed as $O(n^2)$.

Consider another example:

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Hello is printed n^2 times.

This is expressed as $O(n^2)$.

Consider another example:

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= k; i++)  
    print "Hello"
```


Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Hello is printed n^2 times.

This is expressed as $O(n^2)$.

Consider another example:

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= k; i++)  
    print "Hello"
```

Hello is printed $(n^2 + n)/2$ times.

Algorithm Analysis: More Examples

Complexity

Asai
Asaithambi

How many times is Hello printed?

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= n; i++)  
    print "Hello"
```

Hello is printed n^2 times.

This is expressed as $O(n^2)$.

Consider another example:

```
for (k = 1; k <= n; k++)  
  for (i = 1; i <= k; i++)  
    print "Hello"
```

Hello is printed $(n^2 + n)/2$ times.

This is also expressed as $O(n^2)$.

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Trace Table: Integer Multiplication

Complexity

Algorithm A:

Asai
Asaithambi

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes			

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes			

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes			

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No			

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No			

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes			

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001		

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0
No				

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0
No	-	-	-	-

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    p = p + m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 0
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p + m}
```

```
    m = m * 2
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0
No	-	-	-	-

p=p+m executed 77 times by A.

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0
No	-	-	-	-

p=p+m executed 77 times by A.

p=p+m executed 4 times by B.

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0
No	-	-	-	-

p=p+m executed 77 times by A.

p=p+m executed 4 times by B.

A is of time complexity $O(n)$.

Trace Table: Integer Multiplication

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 0

while (n > 0)

 p = p + m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 0

while (n > 0)

 if (odd(n))

 {p = p + m}

 m = m * 2

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	0	13	77
Yes	Yes	13	26	38
Yes	No	13	52	19
Yes	Yes	65	104	9
Yes	Yes	169	208	4
Yes	No	169	416	2
Yes	No	169	832	1
Yes	Yes	1001	1664	0
No	-	-	-	-

p=p+m executed 77 times by A.

p=p+m executed 4 times by B.

A is of time complexity $O(n)$.

B is of time complexity of $O(\log n)$.

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Trace Table: Integer Exponentiation

Complexity

Algorithm A:

Asai
Asaithambi

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

```
-----
```

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes			

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes			

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes			

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No			

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No			

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes			

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}		

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0
No				

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0
No	-	-	-	-

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0
No	-	-	-	-

p=p*m executed 77 times by A.

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0
No	-	-	-	-

p=p*m executed 77 times by A.

p=p*m executed 4 times by B.

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    p = p * m
```

```
    n = n - 1
```

Algorithm B:

```
m = 13; n = 77
```

```
p = 1
```

```
while (n > 0)
```

```
    if (odd(n))
```

```
        {p = p * m}
```

```
    m = m * m
```

```
    n = n / 2
```

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0
No	-	-	-	-

p=p*m executed 77 times by A.

p=p*m executed 4 times by B.

A is of time complexity $O(n)$.

Trace Table: Integer Exponentiation

Complexity

Asai
Asaithambi

Algorithm A:

m = 13; n = 77

p = 1

while (n > 0)

 p = p * m

 n = n - 1

Algorithm B:

m = 13; n = 77

p = 1

while (n > 0)

 if (odd(n))

 {p = p * m}

 m = m * m

 n = n / 2

n>0?	odd(n)	c	m	n
-	-	1	13	77
Yes	Yes	13^1	13^2	38
Yes	No	13^1	13^4	19
Yes	Yes	13^5	13^8	9
Yes	Yes	13^{13}	13^{16}	4
Yes	No	13^{13}	13^{32}	2
Yes	No	13^{13}	13^{64}	1
Yes	Yes	13^{77}	13^{128}	0
No	-	-	-	-

p=p*m executed 77 times by A.

p=p*m executed 4 times by B.

A is of time complexity $O(n)$.

B is of time complexity of $O(\log n)$.

The GCD Algorithm

Complexity

Asai
Asaithambi

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .
- There may be several common divisors.

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .
- There may be several common divisors.
- Which is the greatest?

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .
- There may be several common divisors.
- Which is the greatest?
- For example, $\gcd(18, 12) = 6$.

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .
- There may be several common divisors.
- Which is the greatest?
- For example, $\gcd(18, 12) = 6$.
- The divisors of 18 are 1, 2, 3, 6, 9, and 18.

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .
- There may be several common divisors.
- Which is the greatest?
- For example, $\gcd(18, 12) = 6$.
- The divisors of 18 are 1, 2, 3, 6, 9, and 18.
- The divisors of 12 are 1, 2, 3, 6, and 12.

The GCD Algorithm

Complexity

Asai
Asaithambi

- Computing the *greatest common divisor*
- $\gcd(n, m)$ = greatest integer d such that $d|n$ and $d|m$.
- List all the divisors n and all the divisors of m .
- There may be several common divisors.
- Which is the greatest?
- For example, $\gcd(18, 12) = 6$.
- The divisors of 18 are 1, 2, 3, 6, 9, and 18.
- The divisors of 12 are 1, 2, 3, 6, and 12.
- Of the common divisors 1, 2, 3, and 6, 6 is the greatest.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) =$

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) =$

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) =$

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) =$

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106, 30,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106, 30, 16,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106, 30, 16, 14,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106, 30, 16, 14, 2,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106, 30, 16, 14, 2, 0,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- If d divides n and m , d also divides $n \bmod m$.

$$\gcd(n, m) = \begin{cases} n, & \text{if } m = 0; \\ \gcd(m, n \bmod m), & \text{if } m \neq 0. \end{cases}$$

- $\gcd(18, 12) = \gcd(12, 18 \bmod 12) = \gcd(12, 6)$.
- $\gcd(6, 18 \bmod 6) = \gcd(6, 0) = 6$.
- Remainder sequence: 18, 12, 6, 0.
- For $n = 7366$ and $m = 242$, the remainder sequence is:
- 7366, 242, 106, 30, 16, 14, 2, 0,
- so that $\gcd(7366, 242) = 2$.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1,

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
- 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0
- Thus, $\gcd(987, 610) = 1$

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0
- Thus, $\gcd(987, 610) = 1$
- The quotient is 1 at each step.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0
- Thus, $\gcd(987, 610) = 1$
- The quotient is 1 at each step.
- The remainder sequence is the

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
 - when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
 - 987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0
- Thus, $\gcd(987, 610) = 1$
- The quotient is 1 at each step.
- The remainder sequence is the Fibonacci sequence in reverse order.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
- when the quotient for each division is no greater than 1.
- Consider $n = 987$, $m = 610$.
- The remainder sequence is:
987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0
- Thus, $\gcd(987, 610) = 1$
- The quotient is 1 at each step.
- The remainder sequence is the
Fibonacci sequence in reverse order.
- The number of division steps is k , such that $F_k \approx n$.

The GCD Algorithm (cont.)

Complexity

Asai
Asaithambi

- The basic operation here is the division.
- The maximum number of division steps will occur
 - when the quotient for each division is no greater than 1.
 - Consider $n = 987$, $m = 610$.
 - The remainder sequence is:
987, 610, 377, 233, 144, 89, 55,
34, 21, 13, 8, 5, 3, 2, 1, 0
 - Thus, $\gcd(987, 610) = 1$
 - The quotient is 1 at each step.
 - The remainder sequence is the
Fibonacci sequence in reverse order.
- The number of division steps is k , such that $F_k \approx n$.
- Since $F_k \approx (\phi)^k$, where $\phi \approx 1.618$, $k \approx \log_{\phi} n = O(\log n)$.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form $0^*1^* \Rightarrow O(n)$ time.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form $0^*1^* \Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form $0^*1^* \Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

To cross out one 0 and one 1 $\Rightarrow O(n)$ time per scan.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form $0^*1^* \Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

To cross out one 0 and one 1 $\Rightarrow O(n)$ time per scan.

Each scan reduces the number of symbols in half $\Rightarrow n/2$ scans.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form $0^*1^* \Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

To cross out one 0 and one 1 $\Rightarrow O(n)$ time per scan.

Each scan reduces the number of symbols in half $\Rightarrow n/2$ scans.

Steps 2 and 3 require $O(n^2)$ time together.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form 0^*1^* $\Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

To cross out one 0 and one 1 $\Rightarrow O(n)$ time per scan.

Each scan reduces the number of symbols in half $\Rightarrow n/2$ scans.

Steps 2 and 3 require $O(n^2)$ time together.

Step 4 decides to accept/reject $\Rightarrow O(n)$ time.

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form 0^*1^* $\Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

To cross out one 0 and one 1 $\Rightarrow O(n)$ time per scan.

Each scan reduces the number of symbols in half $\Rightarrow n/2$ scans.

Steps 2 and 3 require $O(n^2)$ time together.

Step 4 decides to accept/reject $\Rightarrow O(n)$ time.

Total time:

Algorithm Analysis: TM for 0^k1^k

Complexity

Asai
Asaithambi

1. Scan across the tape and *reject* if a 0 is found to the right of a 1.
2. Repeat if both 0s and 1s remain on the tape:
3. Scan across the tape, crossing off a single 0 and a single 1.
4. If 0s still remain after all the 1s have been crossed off, or if 1s still remain after all the 0s have been crossed off, *reject*. Otherwise, if neither 0s nor 1s remain on the tape, *accept*.

Step 1 check if input is of the form $0^*1^* \Rightarrow O(n)$ time.

Steps 2 and 3 repeatedly scan the tape:

To cross out one 0 and one 1 $\Rightarrow O(n)$ time per scan.

Each scan reduces the number of symbols in half $\Rightarrow n/2$ scans.

Steps 2 and 3 require $O(n^2)$ time together.

Step 4 decides to accept/reject $\Rightarrow O(n)$ time.

Total time: $O(n) + O(n^2) + O(n) = O(n^2)$.

Complexity Classes

Complexity

Asai
Asaithambi

Complexity Classes

Complexity

Asai
Asaithambi

- Choice of model affects time complexity.

Complexity Classes

Complexity

Asai
Asaithambi

- Choice of model affects time complexity.
- Deterministic vs. Nondeterministic models.

Complexity Classes

Complexity

Asai
Asaithambi

- Choice of model affects time complexity.
- Deterministic vs. Nondeterministic models.

Let $t: \mathcal{N} \rightarrow \mathcal{R}^+$ be a function. Define the *time complexity class*, $\text{TIME}(t(n))$, to be the collection of all languages that are decidable by an $O(t(n))$ time Turing machine.

Complexity Classes

Complexity

Asai
Asaithambi

- Choice of model affects time complexity.
- Deterministic vs. Nondeterministic models.

Let $t: \mathcal{N} \rightarrow \mathcal{R}^+$ be a function. Define the *time complexity class*, $\text{TIME}(t(n))$, to be the collection of all languages that are decidable by an $O(t(n))$ time Turing machine.

$\text{NTIME}(t(n)) = \{L \mid L \text{ is a language decided by an } O(t(n)) \text{ time nondeterministic Turing machine}\}.$

Class P

Complexity

Asai
Asaithambi

Class P

Complexity

Asai
Asaithambi

P is the class of languages that are decidable in polynomial time on a deterministic single-tape Turing machine. In other words,

$$P = \bigcup_k \text{TIME}(n^k).$$

Class P

Complexity

Asai
Asaithambi

P is the class of languages that are decidable in polynomial time on a deterministic single-tape Turing machine. In other words,

$$P = \bigcup_k \text{TIME}(n^k).$$

1. P is invariant for all models of computation that are polynomially equivalent to the deterministic single-tape Turing machine, and
2. P roughly corresponds to the class of problems that are realistically solvable on a computer.

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.
 - encoding \Rightarrow polynomial in the size of the string

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.
 - encoding \Rightarrow polynomial in the size of the string
- However, unary encoding of integers is not appropriate

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.
 - encoding \Rightarrow polynomial in the size of the string
- However, unary encoding of integers is not appropriate
 - because it is exponential in length

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.
 - encoding \Rightarrow polynomial in the size of the string
- However, unary encoding of integers is not appropriate
 - because it is exponential in length compared to binary

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.
 - encoding \Rightarrow polynomial in the size of the string
- However, unary encoding of integers is not appropriate
 - because it is exponential in length compared to binary
- Pose a computation problem as a

Analysis of Pseudocode vs. TM

Complexity

Asai
Asaithambi

- Algorithm analysis based on pseudocode
 - should be considered as analyzing an encoding of a corresponding string on a TM.
 - encoding \Rightarrow polynomial in the size of the string
- However, unary encoding of integers is not appropriate
 - because it is exponential in length compared to binary
- Pose a computation problem as a string acceptance problem

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime
if and only if $\gcd(x, y) = 1$.

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime
if and only if $\gcd(x, y) = 1$.
- From previous analysis,

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime
if and only if $\gcd(x, y) = 1$.
- From previous analysis,
 \gcd takes $O(\log x)$ time

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime
if and only if $\gcd(x, y) = 1$.
- From previous analysis,
 \gcd takes $O(\log x)$ time (assume $x > y$).

Some Problems in P: $RELPRIME(x, y)$

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime
if and only if $\gcd(x, y) = 1$.
- From previous analysis,
 \gcd takes $O(\log x)$ time (assume $x > y$).
- Binary encoding of x has length $n = \log_2 x$.

Some Problems in P: *RELPRIME*(x, y)

Complexity

Asai
Asaithambi

- Given two integers x and y ,
determine whether x and y are relatively prime.
- x and y are relatively prime
if and only if $\gcd(x, y) = 1$.
- From previous analysis,
 \gcd takes $O(\log x)$ time (assume $x > y$).
- Binary encoding of x has length $n = \log_2 x$.
- Thus, *RELPRIME* takes $O(n)$ time, and thus in P.

Some Problems in P: $PATH(s, t)$

Complexity

Asai
Asaithambi

Some Problems in P: $PATH(s, t)$

Complexity

Asai
Asaithambi

- Given a directed graph G and two vertices s, t

Some Problems in P: $PATH(s, t)$

Complexity

Asai
Asaithambi

- Given a directed graph G and two vertices s, t
Determine whether there is a directed path from s to t .

Some Problems in P: $PATH(s, t)$

Complexity

Asai
Asaithambi

- Given a directed graph G and two vertices s, t
Determine whether there is a directed path from s to t .
 1. Place a mark on node s .
 2. Repeat the following until no additional nodes are marked:
 3. Scan all the edges of G . If an edge (a, b) is found going from a marked node a to an unmarked node b , mark node b .
 4. If t is marked, *accept*. Otherwise, *reject*.

Some Problems in P: $PATH(s, t)$

Complexity

Asai
Asaithambi

- Given a directed graph G and two vertices s, t
Determine whether there is a directed path from s to t .
 1. Place a mark on node s .
 2. Repeat the following until no additional nodes are marked:
 3. Scan all the edges of G . If an edge (a, b) is found going from a marked node a to an unmarked node b , mark node b .
 4. If t is marked, *accept*. Otherwise, *reject*.

Takes polynomial time in the size of G

Some Problems in P: $PATH(s, t)$

Complexity

Asai
Asaithambi

- Given a directed graph G and two vertices s, t
Determine whether there is a directed path from s to t .
 1. Place a mark on node s .
 2. Repeat the following until no additional nodes are marked:
 3. Scan all the edges of G . If an edge (a, b) is found going from a marked node a to an unmarked node b , mark node b .
 4. If t is marked, *accept*. Otherwise, *reject*.

Takes polynomial time in the size of G
size = m , number of edges

- Thus $PATH \in P$

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

- Given an undirected graph G

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

- Given an undirected graph G
Determine whether it is connected.

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

- Given an undirected graph G
Determine whether it is connected.
 1. Select the first node of G and mark it.
 2. Repeat the following stage until no new nodes are marked:
 3. For each node in G , mark it if it is attached by an edge to a node that is already marked.
 4. Scan all the nodes of G to determine whether they all are marked. If they are, *accept*; otherwise, *reject*.

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

- Given an undirected graph G
Determine whether it is connected.
 1. Select the first node of G and mark it.
 2. Repeat the following stage until no new nodes are marked:
 3. For each node in G , mark it if it is attached by an edge to a node that is already marked.
 4. Scan all the nodes of G to determine whether they all are marked. If they are, *accept*; otherwise, *reject*.

Takes polynomial time in the order of G ,

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

- Given an undirected graph G
Determine whether it is connected.
 1. Select the first node of G and mark it.
 2. Repeat the following stage until no new nodes are marked:
 3. For each node in G , mark it if it is attached by an edge to a node that is already marked.
 4. Scan all the nodes of G to determine whether they all are marked. If they are, *accept*; otherwise, *reject*.

Takes polynomial time in the order of G , $O(n^2)$

Some Problems in P: *CONNECTED*(G)

Complexity

Asai
Asaithambi

- Given an undirected graph G
Determine whether it is connected.
 1. Select the first node of G and mark it.
 2. Repeat the following stage until no new nodes are marked:
 3. For each node in G , mark it if it is attached by an edge to a node that is already marked.
 4. Scan all the nodes of G to determine whether they all are marked. If they are, *accept*; otherwise, *reject*.

Takes polynomial time in the order of G , $O(n^2)$
order = n , number of vertices

- Thus *CONNECTED* \in P

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:
 - Polynomial time algorithms are yet to be discovered.

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:
 - Polynomial time algorithms are yet to be discovered.
 - These problems *cannot* be solved in polynomial time.

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:
 - Polynomial time algorithms are yet to be discovered.
 - These problems *cannot* be solved in polynomial time.
- Important: Complexity of many problems are linked.

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:
 - Polynomial time algorithms are yet to be discovered.
 - These problems *cannot* be solved in polynomial time.
- Important: Complexity of many problems are linked.
- A class of problems exist such that

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:
 - Polynomial time algorithms are yet to be discovered.
 - These problems *cannot* be solved in polynomial time.
- Important: Complexity of many problems are linked.
- A class of problems exist such that if a polynomial time algorithm may be devised for one of these problems,

Towards Defining Class NP and NP-Complete

Complexity

Asai
Asaithambi

- Polynomial time algorithms avoid brute-force searching.
- Can brute-force searching be avoided for all problems?
- Some problems exist for which:
 - Avoiding brute-force search has not succeeded.
 - No polynomial time algorithms are currently known.
- For such problems, it may be true that:
 - Polynomial time algorithms are yet to be discovered.
 - These problems *cannot* be solved in polynomial time.
- Important: Complexity of many problems are linked.
- A class of problems exist such that if a polynomial time algorithm may be devised for one of these problems, all such problems can be solved in polynomial time.

The Hamilton Path Problem

Complexity

Asai
Asaithambi

The Hamilton Path Problem

Complexity

Asai
Asaithambi


- A Hamilton path in a directed graph is a directed path that goes through each vertex exactly once.

The Hamilton Path Problem

Complexity

Asai
Asaithambi

- A Hamilton path in a directed graph is a directed path that goes through each vertex exactly once.




The Hamilton Path Problem

Complexity

Asai
Asaithambi

- A Hamilton path in a directed graph is a directed path that goes through each vertex exactly once.




- Given an directed graph G and vertices s and t , does there exist a Hamilton path from s to t ?

The Hamilton Path Problem

Complexity

Asai
Asaithambi

- A Hamilton path in a directed graph is a directed path that goes through each vertex exactly once.




- Given an directed graph G and vertices s and t , does there exist a Hamilton path from s to t ?
- This problem is referred to as *HAMPATH*.

The Hamilton Path Problem

Complexity

Asai
Asaithambi

- A Hamilton path in a directed graph is a directed path that goes through each vertex exactly once.



- Given an directed graph G and vertices s and t , does there exist a Hamilton path from s to t ?
- This problem is referred to as *HAMPATH*.
- It is not known whether a polynomial time algorithm exists for solving this problem.

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
Verify/Check if a potential path is Hamiltonian.

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
 - Verify/Check if a potential path is Hamiltonian.
- Note that such verification can be done in

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
 - Verify/Check if a potential path is Hamiltonian.
- Note that such verification can be done in polynomial time.

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
 - Verify/Check if a potential path is Hamiltonian.
- Note that such verification can be done in polynomial time.
- Verifying if a given path is Hamiltonian is much easier than

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
 - Verify/Check if a potential path is Hamiltonian.
- Note that such verification can be done in polynomial time.
- Verifying if a given path is Hamiltonian is much easier than Determining whether a Hamilton path exists.

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
 - Verify/Check if a potential path is Hamiltonian.
- Note that such verification can be done in polynomial time.
- Verifying if a given path is Hamiltonian is much easier than Determining whether a Hamilton path exists.
- Thus *HAMPATH* has the property we will call

Polynomial Verifiability: *HAMPATH*

Complexity

Asai
Asaithambi

- *PATH* can be used to devise an algorithm for *HAMPATH*.
- Such an algorithm will take exponential time.
- Add a step that will:
 - Verify/Check if a potential path is Hamiltonian.
- Note that such verification can be done in polynomial time.
- Verifying if a given path is Hamiltonian is much easier than Determining whether a Hamilton path exists.
- Thus *HAMPATH* has the property we will call *polynomial verifiability*.

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.
- A polynomial time algorithm is known for this problem

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.
- A polynomial time algorithm is known for this problem
But it is somewhat more complicated than verification.

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.
- A polynomial time algorithm is known for this problem
But it is somewhat more complicated than verification.
- Given a number x , it is much easier to verify

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.
- A polynomial time algorithm is known for this problem
But it is somewhat more complicated than verification.
- Given a number x , it is much easier to verify if another number is a divisor of x

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.
- A polynomial time algorithm is known for this problem
But it is somewhat more complicated than verification.
- Given a number x , it is much easier to verify if another number is a divisor of x than it is to determine the divisors of x .

Polynomial Verifiability: *COMPOSITES*

Complexity

Asai
Asaithambi

- A natural number is said be composite if it is a product of two integers greater than 1.
- A composite number is not prime.
- *COMPOSITES*:
Determine whether a given natural number is composite.
- A polynomial time algorithm is known for this problem
But it is somewhat more complicated than verification.
- Given a number x , it is much easier to verify if another number is a divisor of x than it is to determine the divisors of x .
- *COMPOSITES* is polynomially verifiable.

Classes NP and coNP

Complexity

Asai
Asaithambi

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine
that a graph is not Hamiltonian

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine
that a graph is not Hamiltonian
- there is no known method to verify the

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine
that a graph is not Hamiltonian
- there is no known method to verify the
nonexistence of a Hamiltonian path

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine
that a graph is not Hamiltonian
- there is no known method to verify the
nonexistence of a Hamiltonian path
without using the exponential time algorithm
- Problems whose potential solutions can be

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm
- Problems whose potential solutions can be verified in polynomial time are said to in class NP.

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm
- Problems whose potential solutions can be verified in polynomial time are said to be in class NP.
- Another way to state this:

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm
- Problems whose potential solutions can be verified in polynomial time are said to in class NP.
- Another way to state this:
NP is the class of languages

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm
- Problems whose potential solutions can be verified in polynomial time are said to in class NP.
- Another way to state this:
NP is the class of languages that have polynomial verifiers.

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm
- Problems whose potential solutions can be verified in polynomial time are said to in class NP.
- Another way to state this:
NP is the class of languages that have polynomial verifiers.
- $HAMPATH \in NP$,

Classes NP and coNP

Complexity

Asai
Asaithambi

- Not all problems can be verified in polynomial time.
- For example, consider $\overline{HAMPATH}$
- Even though we may determine that a graph is not Hamiltonian
- there is no known method to verify the nonexistence of a Hamiltonian path without using the exponential time algorithm
- Problems whose potential solutions can be verified in polynomial time are said to in class NP.
- Another way to state this:
NP is the class of languages that have polynomial verifiers.
- $HAMPATH \in NP$, and $\overline{HAMPATH} \in coNP$.

Running Time for Nondeterministic TMs

Complexity

Asai
Asaithambi

Running Time for Nondeterministic TMs

Complexity

Asai
Asaithambi


Let N be a nondeterministic Turing machine that is a decider. The *running time* of N is the function $f: \mathcal{N} \rightarrow \mathcal{N}$, where $f(n)$ is the maximum number of steps that N uses on any branch of its computation on any input of length n , as shown in the following figure.

Running Time for Nondeterministic TMs

Complexity

Asai
Asaithambi

Let N be a nondeterministic Turing machine that is a decider. The *running time* of N is the function $f: \mathcal{N} \rightarrow \mathcal{N}$, where $f(n)$ is the maximum number of steps that N uses on any branch of its computation on any input of length n , as shown in the following figure.



Relationship of NP to TMs

Complexity

Asai
Asaithambi

Relationship of NP to TMs

Complexity

Asai
Asaithambi

$\text{NTIME}(t(n)) = \{L \mid L \text{ is a language decided by an } O(t(n)) \text{ time nondeterministic Turing machine}\}.$

Relationship of NP to TMs

Complexity

Asai
Asaithambi

$\text{NTIME}(t(n)) = \{L \mid L \text{ is a language decided by an } O(t(n)) \text{ time nondeterministic Turing machine}\}.$

$$\text{NP} = \bigcup_k \text{NTIME}(n^k).$$

Relationship of NP to TMs

Complexity

Asai
Asaithambi

$\text{NTIME}(t(n)) = \{L \mid L \text{ is a language decided by an } O(t(n)) \text{ time nondeterministic Turing machine}\}.$

$$\text{NP} = \bigcup_k \text{NTIME}(n^k).$$

- NP comes from nondeterministic polynomial time

Relationship of NP to TMs

Complexity

Asai
Asaithambi

$\text{NTIME}(t(n)) = \{L \mid L \text{ is a language decided by an } O(t(n)) \text{ time nondeterministic Turing machine}\}.$

$$\text{NP} = \bigcup_k \text{NTIME}(n^k).$$

- NP comes from nondeterministic polynomial time
- A language is in NP if and only if it is

Relationship of NP to TMs

Complexity

Asai
Asaithambi

$\text{NTIME}(t(n)) = \{L \mid L \text{ is a language decided by an } O(t(n)) \text{ time nondeterministic Turing machine}\}.$

$$\text{NP} = \bigcup_k \text{NTIME}(n^k).$$

- NP comes from nondeterministic polynomial time
- A language is in NP if and only if it is decided by a nondeterministic polynomial time TM.

$HAMPATH \in NP$

Complexity

Asai
Asaithambi

HAMPATH \in NP

Complexity

Asai
Asaithambi

1. Write a list of m numbers, p_1, \dots, p_m , where m is the number of nodes in G . Each number in the list is nondeterministically selected to be between 1 and m .
2. Check for repetitions in the list. If any are found, *reject*.
3. Check whether $s = p_1$ and $t = p_m$. If either fail, *reject*.
4. For each i between 1 and $m - 1$, check whether (p_i, p_{i+1}) is an edge of G . If any are not, *reject*. Otherwise, all tests have been passed, so *accept*.

CLIQUE \in NP

Complexity

Asai
Asaithambi

$CLIQUE \in NP$

Complexity

Asai
Asaithambi

- A *clique* in an undirected graph is a subgraph in which

$CLIQUE \in NP$

Complexity

Asai
Asaithambi

- A *clique* in an undirected graph is a subgraph in which every two nodes are connected by an edge.

$CLIQUE \in NP$

Complexity

Asai
Asaithambi


- A *clique* in an undirected graph is a subgraph in which every two nodes are connected by an edge.
- A *k-clique* is a clique with k nodes.

$CLIQUE \in NP$

Complexity

Asai
Asaithambi

- A *clique* in an undirected graph is a subgraph in which every two nodes are connected by an edge.
- A *k-clique* is a clique with k nodes.




CLIQUE \in NP

Complexity

Asai
Asaithambi

- A *clique* in an undirected graph is a subgraph in which every two nodes are connected by an edge.
- A *k-clique* is a clique with k nodes.




CLIQUE: Given an undirected graph G and an integer k ,

CLIQUE \in NP

Complexity

Asai
Asaithambi

- A *clique* in an undirected graph is a subgraph in which every two nodes are connected by an edge.
- A *k-clique* is a clique with k nodes.



CLIQUE: Given an undirected graph G and an integer k ,
Determine whether G contains a k -clique.

$CLIQUE \in NP$ (cont.)

Complexity

Asai
Asaithambi

$CLIQUE \in NP$ (cont.)

Complexity

Asai
Asaithambi

1. Nondeterministically select a subset c of k nodes of G .
2. Test whether G contains all edges connecting nodes in c .
3. If yes, *accept*; otherwise, *reject*.

$CLIQUE \in NP$ (cont.)

Complexity

Asai
Asaithambi

1. Nondeterministically select a subset c of k nodes of G .
2. Test whether G contains all edges connecting nodes in c .
3. If yes, *accept*; otherwise, *reject*.
 - Step 1 is the nondeterministic part.

$CLIQUE \in NP$ (cont.)

Complexity

Asai
Asaithambi

1. Nondeterministically select a subset c of k nodes of G .
2. Test whether G contains all edges connecting nodes in c .
3. If yes, *accept*; otherwise, *reject*.
 - Step 1 is the nondeterministic part.
 - Step 2 is the polynomial part.

$CLIQUE \in NP$ (cont.)

Complexity

Asai
Asaithambi

1. Nondeterministically select a subset c of k nodes of G .
2. Test whether G contains all edges connecting nodes in c .
3. If yes, *accept*; otherwise, *reject*.
 - Step 1 is the nondeterministic part.
 - Step 2 is the polynomial part.

$\overline{CLIQUE} \in \text{coNP}$.

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

$SUBSET-SUM \in NP$

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
- Determine whether the collection contains

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
- Determine whether the collection contains a sub-collection that adds up to t .

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
- Determine whether the collection contains a sub-collection that adds up to t .
- Example:

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
- Determine whether the collection contains a sub-collection that adds up to t .
- Example: For $S = \{1, 4, 15, 20, 22, 27\}$ and $t = 41$,

SUBSET-SUM \in NP

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
- Determine whether the collection contains a sub-collection that adds up to t .
- Example: For $S = \{1, 4, 15, 20, 22, 27\}$ and $t = 41$, the sub-collection $\{4, 15, 22\}$ adds up to 41.

$SUBSET-SUM \in NP$

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
 - Determine whether the collection contains a sub-collection that adds up to t .
 - Example: For $S = \{1, 4, 15, 20, 22, 27\}$ and $t = 41$, the sub-collection $\{4, 15, 22\}$ adds up to 41.
-
1. Nondeterministically select a subset c of the numbers in S .
 2. Test whether c is a collection of numbers that sum to t .
 3. If the test passes, *accept*; otherwise, *reject*.

$SUBSET-SUM \in NP$

Complexity

Asai
Asaithambi

- Given a collection of numbers x_1, x_2, \dots, x_k and a target number t
 - Determine whether the collection contains a sub-collection that adds up to t .
 - Example: For $S = \{1, 4, 15, 20, 22, 27\}$ and $t = 41$, the sub-collection $\{4, 15, 22\}$ adds up to 41.
-
1. Nondeterministically select a subset c of the numbers in S .
 2. Test whether c is a collection of numbers that sum to t .
 3. If the test passes, *accept*; otherwise, *reject*.

$\overline{SUBSET-SUM} \in \text{coNP}$.

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$\text{NP} \subseteq \text{EXPTIME} = \bigcup_k \text{TIME}(2^{n^k})$$

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s
- Some Problems in NP whose individual complexity

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s
- Some Problems in NP whose individual complexity is related to the complexity of the entire class NP

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s
- Some Problems in NP whose individual complexity is related to the complexity of the entire class NP
- These problems are called *NP-complete* problems.

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s
- Some Problems in NP whose individual complexity is related to the complexity of the entire class NP
- These problems are called *NP-complete* problems.
- If a polynomial algorithm exists

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s
- Some Problems in NP whose individual complexity is related to the complexity of the entire class NP
- These problems are called *NP-complete* problems.
- If a polynomial algorithm exists for any NP-complete problem, then all NP problems

P versus NP and NP Completeness

Complexity

Asai
Asaithambi

- P is the class of languages which can be *decided* quickly.
- NP is the class of languages which can be *verified* quickly.

$$NP \subseteq EXPTIME = \bigcup_k TIME(2^{n^k})$$

- Cook-Levin discovered in the 1970s
- Some Problems in NP whose individual complexity is related to the complexity of the entire class NP
- These problems are called *NP-complete* problems.
- If a polynomial algorithm exists
for any NP-complete problem, then all NP problems
would be polynomial time solvable.

The 3-SAT Problem

Complexity

Asai
Asaithambi

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains
exactly three literals, it is called a *3-cnf formula*.

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains
exactly three literals, it is called a *3-cnf formula*.
- A Boolean formula is *satisfiable*,

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains
exactly three literals, it is called a *3-cnf formula*.
- A Boolean formula is *satisfiable*, if there is a choice of

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains
exactly three literals, it is called a *3-cnf formula*.
- A Boolean formula is *satisfiable*, if there is a choice of
values for the variables that make its value equal 1.

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains
exactly three literals, it is called a *3-cnf formula*.
- A Boolean formula is *satisfiable*, if there is a choice of
values for the variables that make its value equal 1.
- The 3-SAT Problem: Decide whether

The 3-SAT Problem

Complexity

Asai
Asaithambi

- A *literal* is a Boolean variable x ,
or a negated Boolean variable, \bar{x} .
- A *clause* is several literals connected using \vee s, such as:
 $x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4$
- A Boolean formula in *conjunctive normal form* (*cnf*)
contains several clauses connected by \wedge s:
 $(x_1 \vee x_2 \vee \bar{x}_3 \vee \bar{x}_4) \wedge (\bar{x}_1 \vee x_2 \vee \bar{x}_3) \wedge (\bar{x}_2 \vee \bar{x}_4)$
- If every clause in a *cnf* formula contains
exactly three literals, it is called a *3-cnf formula*.
- A Boolean formula is *satisfiable*, if there is a choice of
values for the variables that make its value equal 1.
- The 3-SAT Problem: Decide whether
a given 3-cnf formula is satisfiable.

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause
- Each node in a triple corresponds to

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause
- Each node in a triple corresponds to
a literal in the associated clause.

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause
- Each node in a triple corresponds to
a literal in the associated clause.
- The edges of G connect all pairs of nodes, except:

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause
- Each node in a triple corresponds to
a literal in the associated clause.
- The edges of G connect all pairs of nodes, except:
 - No edge exists between nodes of the same triple.

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause
- Each node in a triple corresponds to
a literal in the associated clause.
- The edges of G connect all pairs of nodes, except:
 - No edge exists between nodes of the same triple.
 - No edge exists between nodes with

3-SAT is Polynomially Reducible to *CLIQUE*

Complexity

Asai
Asaithambi

- Given a 3-cnf formula with k clauses,
an undirected graph G is constructed as follows:
- The nodes of G are organized into k groups of three nodes
call them *triples*, t_1, t_2, \dots, t_k .
- Each triple corresponds to a clause
- Each node in a triple corresponds to
a literal in the associated clause.
- The edges of G connect all pairs of nodes, except:
 - No edge exists between nodes of the same triple.
 - No edge exists between nodes with
contradictory labels, like x_3 and \bar{x}_3 .

3-SAT to *CLIQUE* (cont.)

Complexity

Asai
Asaithambi

3-SAT to *CLIQUE* (cont.)

Complexity

Asai
Asaithambi


$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$$

3-SAT to *CLIQUE* (cont.)

Complexity

Asai
Asaithambi

$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$$




3-SAT to *CLIQUE* (cont.)

Complexity

Asai
Asaithambi

$$\phi = (x_1 \vee x_1 \vee x_2) \wedge (\overline{x_1} \vee \overline{x_2} \vee \overline{x_2}) \wedge (\overline{x_1} \vee x_2 \vee x_2)$$



HAMPATH and *SUBSET-SUM* are NP-complete.