

# COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

March 1, 2023

Lecture 16: Context-Free Languages

# Recap

## Definition

A non-deterministic pushdown automaton (NPDA)

$A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$ , where

$Q$ : set of states       $\Sigma$ : input alphabet

$\Gamma$ : stack alphabet       $q_0$ : start state

$\perp$ : start symbol       $F$ : set of final states

$\delta \subseteq Q \times \Sigma \times \Gamma \times Q \times \Gamma^*$ .

## Understanding $\delta$

For  $q \in Q, a \in \Sigma$  and  $X \in \Gamma$ , if  $\delta(q, a, X) = (p, \gamma)$ ,

then  $p$  is the new state and  $\gamma$  replaces  $X$  in the stack.

if  $\gamma = \epsilon$  then  $X$  is popped.

if  $\gamma = X$  then  $X$  stays unchanged on the top of the stack.

if  $\gamma = \gamma_1\gamma_2 \dots \gamma_k$  then  $X$  is replaced by  $\gamma_k$

and  $\gamma_1\gamma_2 \dots \gamma_{k-1}$  are pushed on top of that.

# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$

# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$ ,  $w \in \Sigma^*$

# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$ ,  $w \in \Sigma^*$ , and  $\gamma \in \Gamma^*$ .

if  $(p, \gamma) \in \delta(q, a, X)$  then

# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$ ,  $w \in \Sigma^*$ , and  $\gamma \in \Gamma^*$ .

if  $(p, \gamma) \in \delta(q, a, X)$  then  $\forall w \in \Sigma^*$  and  $\gamma' \in \Gamma^*$

# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$ ,  $w \in \Sigma^*$ , and  $\gamma \in \Gamma^*$ .

if  $(p, \gamma) \in \delta(q, a, X)$  then  $\forall w \in \Sigma^*$  and  $\gamma' \in \Gamma^*$ ,

$$(q, a \cdot w, X\gamma') \vdash (p, w, \gamma \cdot \gamma')$$

# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$ ,  $w \in \Sigma^*$ , and  $\gamma \in \Gamma^*$ .

if  $(p, \gamma) \in \delta(q, a, X)$  then  $\forall w \in \Sigma^*$  and  $\gamma' \in \Gamma^*$ ,

$$(q, a \cdot w, X\gamma') \vdash (p, w, \gamma \cdot \gamma')$$

Let  $I, J$  are two configurations of  $A$ .

We say that  $I \vdash^k J$  iff  $\exists I'$  such that  $I \vdash I'$



# Configuration of an NPDA

## *Definition (Configurations)*

A configuration of an NPDA  $A = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a three tuple  $(q, w, \gamma)$ , where  $q \in Q$ ,  $w \in \Sigma^*$ , and  $\gamma \in \Gamma^*$ .

if  $(p, \gamma) \in \delta(q, a, X)$  then  $\forall w \in \Sigma^*$  and  $\gamma' \in \Gamma^*$ ,

$$(q, a \cdot w, X\gamma') \vdash (p, w, \gamma \cdot \gamma')$$

Let  $I, J$  are two configurations of  $A$ .

We say that  $I \vdash^k J$  iff  $\exists I'$  such that  $I \vdash I'$  and  $I' \vdash^{k-1} J$ .

# Language recognized by pushdown automata

## *Definition*

We say that a word is accepted by an NPDA  $A$  if  
 $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$

# Language recognized by pushdown automata

## *Definition*

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ .

# Language recognized by pushdown automata

## *Definition*

We say that a word is accepted by an NPDA  $A$  if

$(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

The class of languages recognized by NPDAs is called Context-free languages.

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

The class of languages recognized by NPDAs is called Context-free languages.

Another notion of acceptance of words:



# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

The class of languages recognized by NPDAs is called Context-free languages.

Another notion of acceptance of words:

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \epsilon)$

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

The class of languages recognized by NPDAs is called Context-free languages.

Another notion of acceptance of words:

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \epsilon)$ , where  $q \in Q$ .

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

The class of languages recognized by NPDAs is called Context-free languages.

Another notion of acceptance of words:

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \epsilon)$ , where  $q \in Q$ . acceptance by an empty stack.

# Language recognized by pushdown automata

## Definition

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \gamma)$ , where  $q \in F$ . acceptance by a final state.

A language  $L$  is said to be recognized by an NPDA  $A$  if the set  $\{w \mid w \text{ is accepted by } A\}$  is the same as  $L$ .

The class of languages recognized by NPDAs is called Context-free languages.

Another notion of acceptance of words:

We say that a word is accepted by an NPDA  $A$  if  $(q_0, w, \perp) \vdash^* (q, \epsilon, \epsilon)$ , where  $q \in Q$ . acceptance by an empty stack.

# Equivalence of two notions

# Equivalence of two notions

## Acceptance by PDA

Let  $P = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  be a PDA.

- ▶ If  $L$  is the language accepted of  $P$  by final state, there exists PDA  $P'$  such that its language accepted by empty stack is  $L$ .
- ▶ If  $L$  is the language accepted of  $P$  by empty stack, there exists PDA  $P'$  such that its language accepted by final state is  $L$ .

# Equivalence of two notions

## Acceptance by PDA

Let  $P = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  be a PDA.

- ▶ If  $L$  is the language accepted of  $P$  by final state, there exists PDA  $P'$  such that its language accepted by empty stack is  $L$ .
- ▶ If  $L$  is the language accepted of  $P$  by empty stack, there exists PDA  $P'$  such that its language accepted by final state is  $L$ .

**Proof:** Exercise (Kozen Supplementary lecture E)

# Deterministic PDA

## Definition

A PDA  $P = (Q, \Sigma, \Gamma, \delta, q_0, \perp, F)$  is a DPDA if for each  $q \in Q$  and  $X \in \Gamma$

- ▶  $|\delta(q, a, X)| \leq 1$  for each  $a \in \Sigma \cup \{\epsilon\}$
- ▶ if  $|\delta(q, a, X)| = 1$  for some  $a \in \Sigma$ , then  $|\delta(q, \epsilon, X)| = 0$



# Context-free languages

- ▶ Are context-free languages closed under union? intersection? complement? concatenation?

# Context-free languages

- ▶ Are context-free languages closed under union? intersection? complement? concatenation?
- ▶ Recall: for regular languages we had regular expressions to write rules.
- ▶ Are there similar rules for languages beyond regular?

# Context-free languages

- ▶ Are context-free languages closed under union? intersection? complement? concatenation?
- ▶ Recall: for regular languages we had regular expressions to write rules.
- ▶ Are there similar rules for languages beyond regular?
- ▶ Are there non-context free languages?

# Context-free languages

- ▶ Are context-free languages closed under union? intersection? complement? concatenation?
- ▶ Recall: for regular languages we had regular expressions to write rules.
- ▶ Are there similar rules for languages beyond regular?
- ▶ Are there non-context free languages?

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

Context-free grammar for PAL.

$S \rightarrow \epsilon$ .



# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

Context-free grammar for PAL.

$S \rightarrow \epsilon$ .

$S \rightarrow 0$ .

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

Context-free grammar for PAL.

$S \rightarrow \epsilon$ .

$S \rightarrow 0$ .

$S \rightarrow 1$ .

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

Context-free grammar for PAL.

$S \rightarrow \epsilon$ .

$S \rightarrow 0$ .

$S \rightarrow 1$ .

$S \rightarrow 0S0$ .

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

Context-free grammar for PAL.

$S \rightarrow \epsilon.$

$S \rightarrow 0.$

$S \rightarrow 1.$

$S \rightarrow 0S0.$

$S \rightarrow 1S1.$

# Context-free grammars

Inductive definition of PAL.

$\epsilon$  is in PAL.

If  $w$  is in PAL then  $0 \cdot w \cdot 0 \in \text{PAL}$ .

If  $w$  is in PAL then  $1 \cdot w \cdot 1 \in \text{PAL}$ .

Context-free grammar for PAL.

$S \rightarrow \epsilon.$

$S \rightarrow 0.$

$S \rightarrow 1.$

$S \rightarrow 0S0.$

$S \rightarrow 1S1.$

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .



# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

Context-free grammar for  $\text{PAL}'$ .

$S \rightarrow \epsilon$ .

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

Context-free grammar for  $\text{PAL}'$ .

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

Context-free grammar for  $\text{PAL}'$ .

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

Context-free grammar for  $\text{PAL}'$ .

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$

$$S \rightarrow 0S0.$$

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

Context-free grammar for  $\text{PAL}'$ .

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$

$$S \rightarrow 0S0.$$

$$S \rightarrow 1S1.$$

# Context-free grammars

$$\text{PAL}' = \{w \cdot c \cdot w^R \mid w \in \{0, 1\}^*, c \in \{0, 1, \epsilon\}\}$$

Inductive definition of  $\text{PAL}'$ .

$\epsilon, 0, 1$  is in  $\text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $0 \cdot w \cdot 0 \in \text{PAL}'$ .

If  $w$  is in  $\text{PAL}'$  then  $1 \cdot w \cdot 1 \in \text{PAL}'$ .

Context-free grammar for  $\text{PAL}'$ .

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$

$$S \rightarrow 0S0.$$

$$S \rightarrow 1S1.$$

# Formal Grammars informally..

A (formal) grammar consists of



# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)
- 3 A finite set of symbols stand for “words” of the language called terminal vocabulary.

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)
- 3 A finite set of symbols stand for “words” of the language called terminal vocabulary.
- 4 Other symbols stand for “phrases” and are called non-terminal vocabulary.

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)
- 3 A finite set of symbols stand for “words” of the language called terminal vocabulary.
- 4 Other symbols stand for “phrases” and are called non-terminal vocabulary.

Given such a grammar, a valid sentence can be generated by

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)
- 3 A finite set of symbols stand for “words” of the language called terminal vocabulary.
- 4 Other symbols stand for “phrases” and are called non-terminal vocabulary.

Given such a grammar, a valid sentence can be generated by

- 1 Starting from the initial symbol  $S$ ,

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)
- 3 A finite set of symbols stand for “words” of the language called terminal vocabulary.
- 4 Other symbols stand for “phrases” and are called non-terminal vocabulary.

Given such a grammar, a valid sentence can be generated by

- 1 Starting from the initial symbol  $S$ ,
- 2 Applying one of the rewriting rules to form a new string  $\phi$  by applying a rule  $S \rightarrow \phi_1$ ,

# Formal Grammars informally..

A (formal) grammar consists of

- 1 A finite set of rewriting rules of the form

$$\phi \rightarrow \psi$$

where  $\phi$  and  $\psi$  are strings of symbols.

- 2 A special “initial” symbol  $S$  ( $S$  standing for sentence)
- 3 A finite set of symbols stand for “words” of the language called terminal vocabulary.
- 4 Other symbols stand for “phrases” and are called non-terminal vocabulary.

Given such a grammar, a valid sentence can be generated by

- 1 Starting from the initial symbol  $S$ ,
- 2 Applying one of the rewriting rules to form a new string  $\phi$  by applying a rule  $S \rightarrow \phi_1$ ,
- 3 and apply another rule to form a new string  $\phi_2$  and so on,
- 4 until we reach a string  $\phi_n$  that consists only of terminal symbols.



# Context-free grammar

## *Definition*

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

# Context-free grammar

## *Definition*

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where  
 $V$  is a set of variables (non-terminals/vocabulary)

# Context-free grammar

## *Definition*

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet

# Context-free grammar

## *Definition*

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions

# Context-free grammar

## *Definition*

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$

# Context-free grammar

## *Definition*

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start (“sentence”) symbol.

Example: Grammar for PAL.

$$S \rightarrow \epsilon.$$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start (“sentence”) symbol.

Example: Grammar for PAL.

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start ("sentence") symbol.

Example: Grammar for PAL.

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$



# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start (“sentence”) symbol.

Example: Grammar for PAL.

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$

$$S \rightarrow 0S0.$$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start (“sentence”) symbol.

Example: Grammar for PAL.

$$S \rightarrow \epsilon.$$

$$S \rightarrow 0.$$

$$S \rightarrow 1.$$

$$S \rightarrow 0S0.$$

$$S \rightarrow 1S1.$$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start ("sentence") symbol.

Example: Grammar for PAL.

$S \rightarrow \epsilon.$                        $G_{pal} = (V, T, P, S_0)$  such that

$S \rightarrow 0.$

$S \rightarrow 1.$

$S \rightarrow 0S0.$

$S \rightarrow 1S1.$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start ("sentence") symbol.

Example: Grammar for PAL.

$S \rightarrow \epsilon.$   $G_{pal} = (V, T, P, S_0)$  such that

$S \rightarrow 0.$   $V = \{S\}$

$S \rightarrow 1.$

$S \rightarrow 0S0.$

$S \rightarrow 1S1.$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start ("sentence") symbol.

Example: Grammar for PAL.

$S \rightarrow \epsilon.$   $G_{pal} = (V, T, P, S_0)$  such that

$S \rightarrow 0.$   $V = \{S\},$

$S \rightarrow 1.$   $T = \{0, 1\}$

$S \rightarrow 0S0.$

$S \rightarrow 1S1.$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start ("sentence") symbol.

Example: Grammar for PAL.

$$\begin{array}{ll} S \rightarrow \epsilon. & G_{pal} = (V, T, P, S_0) \text{ such that} \\ S \rightarrow 0. & V = \{S\}, \\ S \rightarrow 1. & T = \{0, 1\}, \\ S \rightarrow 0S0. & P = \{S \rightarrow \epsilon, S \rightarrow 0, S \rightarrow 1, S \rightarrow 0S0, S \rightarrow 1S1\} \\ S \rightarrow 1S1. & \end{array}$$

# Context-free grammar

## Definition

A context-free grammar (CFG)  $G$  is given by  $(V, T, P, S_0)$ , where

$V$  is a set of variables (non-terminals/vocabulary),

$T$  is a set of terminal symbols or the alphabet,

$P$  is a set of (rewriting rules) productions,  $P \subseteq V \times (V \cup T)^*$ ,

$S_0 \in V$ , a start ("sentence") symbol.

Example: Grammar for PAL.

$$\begin{array}{ll} S \rightarrow \epsilon. & G_{pal} = (V, T, P, S_0) \text{ such that} \\ S \rightarrow 0. & V = \{S\}, \\ S \rightarrow 1. & T = \{0, 1\}, \\ S \rightarrow 0S0. & P = \{S \rightarrow \epsilon, S \rightarrow 0, S \rightarrow 1, S \rightarrow 0S0, S \rightarrow 1S1\}, \\ S \rightarrow 1S1. & S_0 = S. \end{array}$$

# Context-free grammars

Example:



# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:  $L'' = \{a^i b^j \mid i > j\}$

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:  $L'' = \{a^i b^j \mid i > j\}$

$$S'' \rightarrow a \mid aS''b \mid aS''$$

Example:

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:  $L'' = \{a^i b^j \mid i > j\}$

$$S'' \rightarrow a \mid aS''b \mid aS''$$

Example:  $L = \{a^i b^j \mid i \neq j\}$



# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:  $L'' = \{a^i b^j \mid i > j\}$

$$S'' \rightarrow a \mid aS''b \mid aS''$$

Example:  $L = \{a^i b^j \mid i \neq j\}$

$$S \rightarrow S' \mid S''$$

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:  $L'' = \{a^i b^j \mid i > j\}$

$$S'' \rightarrow a \mid aS''b \mid aS''$$

Example:  $L = \{a^i b^j \mid i \neq j\}$

$$S \rightarrow S' \mid S''$$

$$S' \rightarrow b \mid aS'b \mid S'b$$

# Context-free grammars

Example:  $L_{a,b} = \{a^n b^n \mid n \geq 0\}$

$$S \rightarrow \epsilon \mid aSb$$

Example:  $L' = \{a^i b^j \mid i < j\}$

$$S' \rightarrow b \mid aS'b \mid S'b$$

Example:  $L'' = \{a^i b^j \mid i > j\}$

$$S'' \rightarrow a \mid aS''b \mid aS''$$

Example:  $L = \{a^i b^j \mid i \neq j\}$

$$S \rightarrow S' \mid S''$$

$$S' \rightarrow b \mid aS'b \mid S'b$$

$$S'' \rightarrow a \mid aS''b \mid aS''.$$

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .



# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## *Definition ( $\Rightarrow^*$ )*

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## *Definition ( $\Rightarrow^*$ )*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

# Derivations of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## *Definition ( $\Rightarrow^*$ )*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

For all  $\alpha \in (V \cup T)^*$ , we say that  $\alpha \Rightarrow^0 \alpha$ .

# Derivations of a CFG

## Definition

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## Definition ( $\Rightarrow^*$ )

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

For all  $\alpha \in (V \cup T)^*$ , we say that  $\alpha \Rightarrow^0 \alpha$ .

For all  $\alpha, \beta, \gamma \in (V \cup T)^*$

# Derivations of a CFG

## Definition

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## Definition ( $\Rightarrow^*$ )

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

For all  $\alpha \in (V \cup T)^*$ , we say that  $\alpha \Rightarrow^0 \alpha$ .

For all  $\alpha, \beta, \gamma \in (V \cup T)^*$ ,

if  $\alpha \Rightarrow^{k-1} \beta$  and  $\beta \Rightarrow \gamma$

# Derivations of a CFG

## Definition

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## Definition ( $\Rightarrow^*$ )

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

For all  $\alpha \in (V \cup T)^*$ , we say that  $\alpha \Rightarrow^0 \alpha$ .

For all  $\alpha, \beta, \gamma \in (V \cup T)^*$ ,

if  $\alpha \Rightarrow^{k-1} \beta$  and  $\beta \Rightarrow \gamma$  then  $\alpha \Rightarrow^k \gamma$ .

For all  $\alpha, \beta \in (V \cup T)^*$

# Derivations of a CFG

## Definition

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

Let  $w, w' \in (V \cup T)^*$ ,

let  $A \in V$  and let  $(A \rightarrow v) \in P$  be a production in the grammar, where  $v \in (V \cup T)^*$ .

Then we say that  $w \cdot A \cdot w'$  **derives**  $w \cdot v \cdot w'$  **in one step**.

We denote it as follows:  $w \cdot A \cdot w' \Rightarrow w \cdot v \cdot w'$ .

## Definition ( $\Rightarrow^*$ )

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

For all  $\alpha \in (V \cup T)^*$ , we say that  $\alpha \Rightarrow^0 \alpha$ .

For all  $\alpha, \beta, \gamma \in (V \cup T)^*$ ,

if  $\alpha \Rightarrow^{k-1} \beta$  and  $\beta \Rightarrow \gamma$  then  $\alpha \Rightarrow^k \gamma$ .

For all  $\alpha, \beta \in (V \cup T)^*$ , we say that  $\alpha \Rightarrow^* \beta$ , if  $\exists k \geq 0$  s.t.  $\alpha \Rightarrow^k \beta$ .



# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ .

# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$

# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of**  $G$ ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$

# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$ , i.e.

$$L(G) = \{w \in T^* \mid S \Rightarrow^* w\}.$$

## *Lemma*

$L(G_{pal})$  is equal to  $PAL$ .

# Language of a CFG

## Definition

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$ , i.e.

$$L(G) = \{w \in T^* \mid S \Rightarrow^* w\}.$$

## Lemma

$L(G_{pal})$  is equal to  $PAL$ .

$\forall w \in \{0, 1\}^*, w \in L(G_{Pal})$  if and only if  $w = w^R$ .

# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$ , i.e.

$$L(G) = \{w \in T^* \mid S \Rightarrow^* w\}.$$

## *Lemma*

$L(G_{pal})$  is equal to  $PAL$ .

$\forall w \in \{0, 1\}^*, w \in L(G_{Pal})$  if and only if  $w = w^R$ .

# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$ , i.e.

$$L(G) = \{w \in T^* \mid S \Rightarrow^* w\}.$$

## *Lemma*

$L(G_{pal})$  is equal to  $PAL$ .

$\forall w \in \{0,1\}^*, w \in L(G_{Pal})$  if and only if  $w = w^R$ .

## *Proof.*

$(\Leftarrow)$ : If  $w = w^R$ ,  $w \in L(G_{Pal})$

# Language of a CFG

## *Definition*

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$ , i.e.

$$L(G) = \{w \in T^* \mid S \Rightarrow^* w\}.$$

## *Lemma*

$L(G_{pal})$  is equal to  $PAL$ .

$\forall w \in \{0,1\}^*, w \in L(G_{Pal})$  if and only if  $w = w^R$ .

## *Proof.*

$(\Leftarrow)$ : If  $w = w^R$ ,  $w \in L(G_{Pal})$

By Induction on  $|w|$ .



# Language of a CFG

## Definition

Let  $G$  be a CFG given by  $(V, T, P, S_0)$ . The **language of  $G$** ,  $L(G)$ , is the set of all the strings over  $T$  which can be derived from  $S_0$ , i.e.

$$L(G) = \{w \in T^* \mid S \Rightarrow^* w\}.$$

## Lemma

$L(G_{pal})$  is equal to  $PAL$ .

$\forall w \in \{0, 1\}^*, w \in L(G_{Pal})$  if and only if  $w = w^R$ .

## Proof.

( $\Leftarrow$ ): If  $w = w^R$ ,  $w \in L(G_{Pal})$

By Induction on  $|w|$ .

( $\Rightarrow$ ): If  $w \in L(G_{Pal})$  then  $w = w^R$ .

By Induction on  $|w|$ .



# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

$$S \rightarrow S' C \mid S'' C$$

# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

$$S \rightarrow S' C \mid S'' C$$

$$S' \rightarrow b \mid a S' b \mid S' b$$

# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

$$S \rightarrow S' C \mid S'' C$$

$$S' \rightarrow b \mid a S' b \mid S' b$$

$$S'' \rightarrow a \mid a S'' b \mid a S''.$$

$$C \rightarrow c C \mid \epsilon$$

Now we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid j \neq k\}$ .

# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

$$S \rightarrow S' C \mid S'' C$$

$$S' \rightarrow b \mid a S' b \mid S' b$$

$$S'' \rightarrow a \mid a S'' b \mid a S''.$$

$$C \rightarrow c C \mid \epsilon$$

Now we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid j \neq k\}$ .

$$S \rightarrow A S' \mid A S''$$

# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

$$S \rightarrow S' C \mid S'' C$$

$$S' \rightarrow b \mid a S' b \mid S' b$$

$$S'' \rightarrow a \mid a S'' b \mid a S''.$$

$$C \rightarrow c C \mid \epsilon$$

Now we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid j \neq k\}$ .

$$S \rightarrow A S' \mid A S''$$

$$S' \rightarrow c \mid b S' c \mid S' c$$



# Examples

Give context-free grammars for the following languages.

$$\{a^i \cdot b^j \cdot c^k \mid \text{either } i \neq j \text{ or } j \neq k\}.$$

First we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid i \neq j\}$ .

$$S \rightarrow S' C \mid S'' C$$

$$S' \rightarrow b \mid a S' b \mid S' b$$

$$S'' \rightarrow a \mid a S'' b \mid a S''.$$

$$C \rightarrow c C \mid \epsilon$$

Now we give a grammar for  $\{a^i \cdot b^j \cdot c^k \mid j \neq k\}$ .

$$S \rightarrow A S' \mid A S''$$

$$S' \rightarrow c \mid b S' c \mid S' c$$

$$S'' \rightarrow b \mid b S'' c \mid b S''.$$

$$C \rightarrow a A \mid \epsilon$$

Now simply take the union.

# Exercises

- ▶ Give a grammar for the language of all valid regular expressions.
- ▶ Give a grammar for any regular language (given as a DFA).

# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

$$A \rightarrow BC$$

# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

where  $a \in T$ ,  $A, B, C \in V$ , neither  $B$  nor  $C$  is the start variable, i.e. start variable does not appear on the right of any rule.

# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

where  $a \in T$ ,  $A, B, C \in V$ , neither  $B$  nor  $C$  is the start variable, i.e. start variable does not appear on the right of any rule. Moreover, epsilon does not appear on the right of any rule except as  $S \rightarrow \epsilon$ .

# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

where  $a \in T$ ,  $A, B, C \in V$ , neither  $B$  nor  $C$  is the start variable, i.e. start variable does not appear on the right of any rule. Moreover, epsilon does not appear on the right of any rule except as  $S \rightarrow \epsilon$ .

## *Lemma*

*Any context-free grammar  $G$  can be converted into another context-free grammar  $G'$*



# Chomsky normal form

## *Definition*

A context-free grammar is said to be in Chomsky normal form if every rule is of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

where  $a \in T$ ,  $A, B, C \in V$ , neither  $B$  nor  $C$  is the start variable, i.e. start variable does not appear on the right of any rule. Moreover, epsilon does not appear on the right of any rule except as  $S \rightarrow \epsilon$ .

## *Lemma*

*Any context-free grammar  $G$  can be converted into another context-free grammar  $G'$  such that  $L(G) = L(G')$  and  $G'$  is in the Chomsky normal form.*