

COL 352 Introduction to Automata and Theory of Computation


Nikhil Balaji

Bharti 420
Indian Institute of Technology, Delhi
nbalaji@cse.iitd.ac.in

March 22, 2023

Lecture 24: Turing Machines: Variants, CT Thesis (Part 3)

Enumerators



- ▶ Turing machine with an attached printer.
- ▶ **Exercise:** Formally define it.
- ▶ An enumerator E starts with a blank input on its work tape.
- ▶ If the enumerator doesn't halt, it may print an infinite list of strings.
- ▶ The language enumerated by E is the collection of all the strings that it eventually prints out.
- ▶ E may generate the strings of the language in any order, possibly with repetitions.

Enumerators vs Recognizers

Theorem

A language is Turing-recognizable if and only if some enumerator enumerates it.

Proof.

Enumerators vs Recognizers

Theorem

A language is Turing-recognizable if and only if some enumerator enumerates it.

Proof.

(\Rightarrow) On input w :

- 1 Run E . Every time that E outputs a string, compare it with w .
- 2 If w ever appears in the output of E , accept.

(\Leftarrow)

Enumerators vs Recognizers

Theorem

A language is Turing-recognizable if and only if some enumerator enumerates it.

Proof.

(\Rightarrow) On input w :

- ➊ Run E . Every time that E outputs a string, compare it with w .
- ➋ If w ever appears in the output of E , accept.

(\Leftarrow) Ignore the input. Repeat the following for $i = 1, 2, 3, \dots$

Enumerators vs Recognizers

Theorem

A language is Turing-recognizable if and only if some enumerator enumerates it.

Proof.

(\Rightarrow) On input w :

- 1 Run E . Every time that E outputs a string, compare it with w .
- 2 If w ever appears in the output of E , accept.

(\Leftarrow) Ignore the input. Repeat the following for $i = 1, 2, 3, \dots$

- 1 Run M for i steps on each input, s_1, s_2, \dots, s_i .
- 2 If any computations accepts, print out the corresponding s_j .



Remark: Turing Recognizable = Recursively Enumerable languages.

Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.

Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.

Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.
- ▶ Each write operation (called a push) adds a symbol to the left-hand end of the queue.

Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.
- ▶ Each write operation (called a push) adds a symbol to the left-hand end of the queue.
- ▶ Each read operation (called a pull) reads and removes a symbol at the right-hand end.

Queue automata

- ▶ A DQA is like a push-down automaton except that the stack is replaced by a queue.
- ▶ A queue is a tape allowing symbols to be written only on the left-hand end and read only at the right hand-end.
- ▶ Each write operation (called a push) adds a symbol to the left-hand end of the queue.
- ▶ Each read operation (called a pull) reads and removes a symbol at the right-hand end.
- ▶ **Initial condition:** the input tape contains a cell with a blank symbol following the input, to detect end of the input.
- ▶ **Computation:** Acceptance by entering a special accept state at any time.

Note: As with a PDA, the input of a DQA is placed on a separate read-only input tape, and the head on the input tape can move only from left to right

Queues are more powerful than stacks

Theorem

Language can be recognized by a DQA, iff it is Turing-recognizable

Proof Sketch.

Idea: Show any DQA Q can be simulated with a 2-tape TM M .

Queues are more powerful than stacks

Theorem

Language can be recognized by a DQA, iff it is Turing-recognizable

Proof Sketch.

Idea: Show any DQA Q can be simulated with a 2-tape TM M . Show that any single-tape deterministic TM D can be simulated by a DQA Q . □

Simulating a DQA by a TM

- ▶ The first tape of M holds the input, second tape holds the queue.
- ▶ To simulate reading Q 's next input symbol, M reads the symbol under the first head and moves to the right.

Simulating a DQA by a TM

- ▶ The first tape of M holds the input, second tape holds the queue.
- ▶ To simulate reading Q 's next input symbol, M reads the symbol under the first head and moves to the right.
- ▶ To simulate a *push* a , M writes a on the leftmost blank cell of the second tape.

Simulating a DQA by a TM

- ▶ The first tape of M holds the input, second tape holds the queue.
- ▶ To simulate reading Q 's next input symbol, M reads the symbol under the first head and moves to the right.
- ▶ To simulate a *push* a , M writes a on the leftmost blank cell of the second tape.
- ▶ To simulate a *pull*, M reads the rightmost symbol on the second tape and shifts the tape one symbol leftward.

Simulating a TM by DQA

$$M = (S_M, \Sigma, \Gamma_M, \delta_M, q_0^M, q_a^M, q_r^M)$$

$$Q = (S_Q, \Sigma, \Gamma_M \cup \hat{\Gamma}_M, \delta_Q, q_0^Q, \{q_a^M, q_r^M\})$$

Simulating a TM by DQA

$$M = (S_M, \Sigma, \Gamma_M, \delta_M, q_0^M, q_a^M, q_r^M)$$

$$Q = (S_Q, \Sigma, \Gamma_M \cup \hat{\Gamma}_M, \delta_Q, q_0^Q, \{q_a^M, q_r^M\})$$

- ▶ For each symbol $c \in \Gamma_M$, Q also has the corresponding \hat{c} to denote the head.
- ▶ Let Q also have an end of tape marker \$.

Simulating a TM by DQA

$$M = (S_M, \Sigma, \Gamma_M, \delta_M, q_0^M, q_a^M, q_r^M)$$

$$Q = (S_Q, \Sigma, \Gamma_M \cup \hat{\Gamma}_M, \delta_Q, q_0^Q, \{q_a^M, q_r^M\})$$

- ▶ For each symbol $c \in \Gamma_M$, Q also has the corresponding \hat{c} to denote the head.
- ▶ Let Q also have an end of tape marker \$.
- ▶ Q simulates M by maintaining a copy of M 's tape in the queue.
- ▶ Q can scan the tape from right to left by pulling symbols from the right-hand end of the queue and pushing them back on the left-hand end side, until \$ is seen.
- ▶ When a \hat{c} symbol is encountered, Q can determine M 's next move, because Q can record M 's current state in its control.

Computation Simulation

- ▶ If M 's tape head moves leftwards, the updating of the queue is done by writing the new symbol c instead of the old \hat{c} and moving the $\hat{}$ one symbol left.

Computation Simulation

- ▶ If M 's tape head moves leftwards, the updating of the queue is done by writing the new symbol c instead of the old \hat{c} and moving the $\hat{}$ one symbol left.
- ▶ Formally, if current configuration is $u\hat{a}b^{\wedge}tv$ and $\delta(q, b) = (q', c, L)$ then the next configuration is $u\hat{a}ctv$ and is obtained by:

Computation Simulation

- ▶ If M 's tape head moves leftwards, the updating of the queue is done by writing the new symbol c instead of the old \hat{c} and moving the \hat{c} one symbol left.
- ▶ Formally, if current configuration is $u\hat{a}b\hat{t}v$ and $\delta(q, b) = (q', c, L)$ then the next configuration is $u\hat{a}c\hat{t}v$ and is obtained by:
 - ▶ *pull v ; push v ;*
 - ▶ *pull t ; push t ;*
 - ▶ *pull \hat{b} ; push c ; pull a ; push \hat{a} ;*
 - ▶ *pull u ; push u ;*

Computation Simulation

- ▶ If M 's tape head moves leftwards, the updating of the queue is done by writing the new symbol c instead of the old \hat{c} and moving the $\hat{}$ one symbol left.
- ▶ Formally, if current configuration is $u\hat{a}b\hat{t}v$ and $\delta(q, b) = (q', c, L)$ then the next configuration is $u\hat{a}c\hat{t}v$ and is obtained by:
 - ▶ *pull v ; push v ;*
 - ▶ *pull t ; push t ;*
 - ▶ *pull \hat{b} ; push c ; pull a ; push \hat{a} ;*
 - ▶ *pull u ; push u ;*
- ▶ How about move right? (Exercise!)

2 stacks?


- ▶ Same as the regular PDA but now you have two stacks

2 stacks?


- ▶ Same as the regular PDA but now you have two stacks
- ▶ As powerful as TMs.

2 stacks?

- ▶ Same as the regular PDA but now you have two stacks
- ▶ As powerful as TMs.



is simulated by



Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

- ▶ Computation performed by a NTM is a tree whose branches correspond to different possibilities for the machine

Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

- ▶ Computation performed by a NTM is a tree whose branches correspond to different possibilities for the machine
- ▶ If some branch of the computation tree leads to the accept state, the machine accepts the input
- ▶ Can nondeterministic Turing machines compute more functions than deterministic Turing machines?

Nondeterministic Turing Machines

A NTM is defined in the expected way: at any point in a computation the machine may proceed according to several possibilities

$$\delta : Q \times \Gamma \rightarrow 2^{Q \times \Gamma \times \{L,R\}}$$

- ▶ Computation performed by a NTM is a tree whose branches correspond to different possibilities for the machine
- ▶ If some branch of the computation tree leads to the accept state, the machine accepts the input
- ▶ Can nondeterministic Turing machines compute more functions than deterministic Turing machines?

Theorem

Every nondeterministic Turing machine, N has an equivalent deterministic Turing machine D .

Example: Finding Integer roots of Polynomials

- ▶ Given polynomial

$$p(x) = a_1x^n + a_2x^{n-1} + \cdots + a_nx + a_{n+1}$$

where $a_i \in \mathbb{Z}$, find an integer root.

Example: Finding Integer roots of Polynomials

- ▶ Given polynomial

$$p(x) = a_1x^n + a_2x^{n-1} + \cdots + a_nx + a_{n+1}$$

where $a_i \in \mathbb{Z}$, find an integer root.

- ▶ **Exercise:** Let there be a root at $x = x_0$ and a_{max} be the largest absolute value of a a_i . Show that

$$|x_0| < (n+1) \frac{a_{max}}{|a_1|}$$

Proof of $L(N) = L(D)$

Proof Idea.

Show that a NTM N can be simulated with a DTM D .

Proof of $L(N) = L(D)$

Proof Idea.

Show that a NTM N can be simulated with a DTM D . In this simulation D tries all possible branches of N 's computation. If D ever finds the accept state on one of these branches then it accepts. Otherwise D 's simulation will not terminate.

- ▶ N 's computation on an input w is a tree, $N(w)$.
- ▶ Each branch of $N(w)$ represents one of the branches of the nondeterminism.

Proof of $L(N) = L(D)$

Proof Idea.

Show that a NTM N can be simulated with a DTM D . In this simulation D tries all possible branches of N 's computation. If D ever finds the accept state on one of these branches then it accepts. Otherwise D 's simulation will not terminate.

- ▶ N 's computation on an input w is a tree, $N(w)$.
- ▶ Each branch of $N(w)$ represents one of the branches of the nondeterminism.
- ▶ Each node of $N(w)$ is a configuration of N .
- ▶ The root of $N(w)$ is the start configuration.

Proof of $L(N) = L(D)$

Proof Idea.

Show that a NTM N can be simulated with a DTM D . In this simulation D tries all possible branches of N 's computation. If D ever finds the accept state on one of these branches then it accepts. Otherwise D 's simulation will not terminate.

- ▶ N 's computation on an input w is a tree, $N(w)$.
- ▶ Each branch of $N(w)$ represents one of the branches of the nondeterminism.
- ▶ Each node of $N(w)$ is a configuration of N .
- ▶ The root of $N(w)$ is the start configuration.
- ▶ D searches $N(w)$ for an accepting configuration.



A tempting bad idea

- ▶ Design D to explore the tree $N(w)$ using DFS.
- ▶

A tempting bad idea

- ▶ Design D to explore the tree $N(w)$ using DFS.
- ▶ A depth-first search goes all the way down on one branch before backing up to explore next branch. Hence, D could go forever down on an infinite branch and miss an accepting configuration on an other branch.

A better idea

- ▶ Design D to explore the tree by using a breadth-first search
- ▶ This strategy explores all branches at the same depth before going to explore any branch at the next depth.
- ▶ Hence, this method guarantees that D will visit every node of $N(w)$ until it encounters an accepting configuration.

Proof.

D has three tapes:

- ▶ Tape 1 always contains the input and is never altered
- ▶ Tape 2 (called the simulation tape) maintains a copy of N 's tape on some branch of its nondeterministic computation
- ▶ Tape 3 (called address tape) keeps track of D 's location in N 's nondeterministic computation tree



Other variants

- ▶ Multi-dimensional tapes.

Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines

Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines
- ▶ Your favorite programming language ("Turing-completeness")

Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines
- ▶ Your favorite programming language ("Turing-completeness")
- ▶ Cellular automata

Other variants

- ▶ Multi-dimensional tapes.
- ▶ Counter machines
- ▶ Your favorite programming language ("Turing-completeness")
- ▶ Cellular automata
- ▶ ...
- ▶ ...

What is computation?



- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.

What is computation?



- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.
- ▶ 10th problem: Devise an algorithm (a process doable using a finite no.of operations) to test if a (multivariate) polynomial has integral roots.

What is computation?



"HILBERT's TENTH PROBLEM"

a book written by [Yuri MATTYASEVICH](#)



Russian original:

Десятая проблема Гильберта

Наука, Москва, 1993



English translation:

Hilbert's Tenth Problem

[The MIT Press](#), Cambridge, London, 1993

The Publisher's [page of the book](#)



Traduction française:

- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.
- ▶ 10th problem: Devise an algorithm (a process doable using a finite no. of operations) to test if a (multivariate) polynomial has integral roots.

What is computation?



"HILBERT's TENTH PROBLEM"

a book written by [Yuri MATYASEVICH](#)



Russian original:

Десятая проблема Гильберта

Наука, Москва, 1993



English translation:

Hilbert's Tenth Problem

[The MIT Press](#), Cambridge, London, 1993

The Publisher's [page of the book](#)



Traduction française:

- ▶ In 1900, David Hilbert listed out 23 problems as challenges for 20th century at the Int. Cong. of Mathematicians in Paris.
- ▶ 10th problem: Devise an algorithm (a process doable using a finite no. of operations) to test if a (multivariate) polynomial has integral roots.
- ▶ Now we know that no such algorithm exists. But how to prove this without a mathematical definition of an algorithm?

Church-Turing thesis



Alonso Church
(1903–1995)



Alan Turing
(1912–1954)

Turing's paper

230

A. M. TURING

[Nov. 12,

ON COMPUTABLE NUMBERS, WITH AN APPLICATION TO THE ENTSCHEIDUNGSPROBLEM

By A. M. TURING.

[Received 28 May, 1936.—Read 12 November, 1936.]

The “computable” numbers may be described briefly as the real numbers whose expressions as a decimal are calculable by finite means. Although the subject of this paper is ostensibly the computable *numbers*, it is almost equally concerned with the definition and investigation of the computable *functions*.