

# COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

April 20, 2023

Lecture 33: Computational Complexity Theory (Part 2)

# Time complexity and complexity classes

Let  $t : \mathbb{N} \rightarrow \mathbb{N}$ .

## *Definition*

A language  $L \subseteq \Sigma^*$  is said to be in class  $\text{NTIME}(t(n))$  if there exists a non-deterministic Turing machine  $M$  such that  $\forall x \in \Sigma^*$ ,

each run of  $M$  halts on  $x$  in time  $O(t(|x|))$ , where  $|x|$  indicates the length of  $x$ .

if  $x \in L$  then  $M$  accepts  $x$  on at least one run.

if  $x \notin L$  then  $M$  rejects  $x$  on all runs.

$$NP = \bigcup_k \text{NTIME}(n^k)$$

# Time complexity and complexity classes

Let  $t : \mathbb{N} \rightarrow \mathbb{N}$ .

## *Definition*

A language  $L \subseteq \Sigma^*$  is said to be in class  $\text{NTIME}(t(n))$  if there exists a non-deterministic Turing machine  $M$  such that  $\forall x \in \Sigma^*$ ,

- each run of  $M$  halts on  $x$  in time  $O(t(|x|))$ , where  $|x|$  indicates the length of  $x$ .
- if  $x \in L$  then  $M$  accepts  $x$  on at least one run.
- if  $x \notin L$  then  $M$  rejects  $x$  on all runs.

$$NP = \bigcup_k \text{NTIME}(n^k)$$

$$NEXP = \bigcup_k \text{NTIME}(2^{n^k})$$

# Relationships between complexity classes

How are  $P$ ,  $NP$ ,  $EXP$ , and  $NEXP$  related?

# Relationships between complexity classes

How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

# Relationships between complexity classes

How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

# Relationships between complexity classes

How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

# Relationships between complexity classes

How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.



# Relationships between complexity classes

How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.

$P \longrightarrow NP$

EXP

NEXP

# Relationships between complexity classes


How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.



# Relationships between complexity classes


How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.



# Relationships between complexity classes


How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.



# Relationships between complexity classes


How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.



# Relationships between complexity classes


How are P, NP, EXP, and NEXP related?

$P \subseteq NP$  by definition.

$P \subseteq EXP$  again by definition.

Similarly,  $NP \subseteq NEXP$  by definition.

Finally,  $NP \subseteq EXP$  due to the previous lemma.



# P vs. NP

# P vs. NP

P     the class of languages where membership can be decided quickly.



# P vs. NP

P the class of languages where membership can be decided quickly.

NP the class of languages where membership can be verified quickly.

## *Definition*

A verifier for a language  $A$  is an algorithm  $V$ , where

$$A = \{w \mid V \text{ accepts } (w, c) \text{ for some string } c\}$$

# P vs. NP

P the class of languages where membership can be decided quickly.

NP the class of languages where membership can be verified quickly.

## *Definition*

A verifier for a language  $A$  is an algorithm  $V$ , where

$$A = \{w \mid V \text{ accepts } (w, c) \text{ for some string } c\}$$

NP is the class of languages that have polynomial time verifiers.  $c$  is the “certificate” or “witness” or “proof” that  $w \in A$ .

# Examples

$$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}.$$

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ .

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$\text{3-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ .



# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$\text{3-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$3\text{-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$2\text{-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ .

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$\text{3-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$\text{2-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ . in P

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$3\text{-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$2\text{-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ . in P

$\text{Factoring} = \{(k, n) \mid n \text{ has a factor } \leq k\}$ .

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$3\text{-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$2\text{-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ . in P

$\text{Factoring} = \{(k, n) \mid n \text{ has a factor } \leq k\}$ . Google it!

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$\text{3-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$\text{2-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ . in P

$\text{Factoring} = \{(k, n) \mid n \text{ has a factor } \leq k\}$ . Google it!

$\text{Clique} = \{(G, k) \mid G \text{ has a clique of size } \geq k\}$ .

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$3\text{-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$2\text{-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ . in P

$\text{Factoring} = \{(k, n) \mid n \text{ has a factor } \leq k\}$ . Google it!

$\text{Clique} = \{(G, k) \mid G \text{ has a clique of size } \geq k\}$ . in NP (and not known to be in P)

# Examples

$\text{SAT} = \{\phi \mid \phi \text{ is satisfiable}\}$ . in NP (and not known to be in P)

$\text{Reach} = \{(G, s, t) \mid t \text{ is reachable from } s \text{ in } G\}$ . in P

On input  $(G, s, t)$ , where  $G$  is a directed graph with nodes  $s$  and  $t$ :

- ▶ Place a mark on node  $s$ .
- ▶ Repeat the following until no additional nodes are marked:
  - ▶ Scan all the edges of  $G$ . If an edge  $(a, b)$  is found going from a marked node  $a$  to an unmarked node  $b$ , mark node  $b$ .
- ▶ If  $t$  is marked, accept. Otherwise, reject.

$3\text{-SAT} = \{\phi \mid \phi \text{ is a 3-CNF and satisfiable}\}$ . in NP (and not known to be in P)

$2\text{-SAT} = \{\phi \mid \phi \text{ is a 2-CNF and satisfiable}\}$ . in P

$\text{Factoring} = \{(k, n) \mid n \text{ has a factor } \leq k\}$ . Google it!

$\text{Clique} = \{(G, k) \mid G \text{ has a clique of size } \geq k\}$ . in NP (and not known to be in P)



# Lower Bounds

How do we separate NP from P?

# Lower Bounds

How do we separate NP from P?

To prove

Method used

# Lower Bounds

How do we separate NP from P?

To prove

Method used

not regular

# Lower Bounds

How do we separate NP from P?

To prove

Method used

not regular

pumping lemma for REG

# Lower Bounds

How do we separate NP from P?

To prove

Method used

not regular

pumping lemma for REG

non-context-free

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	diagonalization



# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	diagonalization
not decidable	

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	diagonalization
not decidable	Rice's theorem

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	diagonalization
not decidable	Rice's theorem or diagonalization and reduction

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	diagonalization
not decidable	Rice's theorem or diagonalization and reduction
not in P	

# Lower Bounds

How do we separate NP from P?

To prove	Method used
not regular	pumping lemma for REG
non-context-free	pumping lemma or CFLs
not recognizable	diagonalization
not decidable	Rice's theorem or diagonalization and reduction
not in P	???

# Finer structure inside P

## *Definition*

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible

# Finer structure inside P

## *Definition*

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible if there exists a TM that on input  $1^n$ , it outputs  $t(n)$  in time  $O(t(n))$ .

# Finer structure inside P

## *Definition*

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible if there exists a TM that on input  $1^n$ , it outputs  $t(n)$  in time  $O(t(n))$ .

## Examples



# Finer structure inside P

## *Definition*

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible if there exists a TM that on input  $1^n$ , it outputs  $t(n)$  in time  $O(t(n))$ .

## Examples

$$n^2$$

# Finer structure inside P

## *Definition*

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible if there exists a TM that on input  $1^n$ , it outputs  $t(n)$  in time  $O(t(n))$ .

## Examples

$$n^2, n \log n.$$

# Finer structure inside P

## *Definition*

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible if there exists a TM that on input  $1^n$ , it outputs  $t(n)$  in time  $O(t(n))$ .

## Examples

$$n^2, n \log n.$$

## *Theorem*

Let  $t : \mathbb{N} \rightarrow \mathbb{N}$  be a time constructible function. There exists a language  $L$  such that  $L \in \text{TIME}(t(n)^2)$ , but  $L \notin \text{TIME}(o(t(n)))$ .

# Finer structure inside P

## Definition

A function  $t : \mathbb{N} \rightarrow \mathbb{N}$  is said to be time constructible if there exists a TM that on input  $1^n$ , it outputs  $t(n)$  in time  $O(t(n))$ .

## Examples

$$n^2, n \log n.$$

## Theorem

Let  $t : \mathbb{N} \rightarrow \mathbb{N}$  be a time constructible function. There exists a language  $L$  such that  $L \in \text{TIME}(t(n)^2)$ , but  $L \notin \text{TIME}(o(t(n)))$ .

**Idea:** On input  $x$ , simulate the execution of  $M_x$  on  $x$  for  $|x|^{1.5}$  steps using a Universal TM. If  $U$  outputs some bit  $b \in \{0, 1\}$  in this time, then output the opposite answer (i.e., output  $1 - b$ ). Else output 0.

# Efficient simulation

# Efficient simulation

## *Theorem (Efficient universal Turing machine)*

*There exists a TM  $U$  such that for every  $x, \alpha \in \{0, 1\}^*$ ,  $U(x, \alpha) = M_\alpha(x)$ , where  $M_\alpha$  denotes the TM represented by  $\alpha$ . Moreover, if  $M_\alpha$  halts on input  $x$  within  $T$  steps then  $U(x, \alpha)$  halts within  $CT \log T$  steps, where  $C$  is a number independent of  $|x|$  and depending only on  $M_\alpha$ 's alphabet size, number of tapes, and number of states.*

# Polynomial time reductions and NP-hardness

## *Definition*

A function  $f : \Sigma^* \rightarrow \Sigma^*$  is polynomial time computable if there is a polynomial time Turing machine TM, say  $M$ , such that on any input  $w \in \Sigma^*$ ,  $M$  stops with only  $f(w)$  on its tape.

# Polynomial time reductions and NP-hardness

## *Definition*

A function  $f : \Sigma^* \rightarrow \Sigma^*$  is polynomial time computable if there is a polynomial time Turing machine TM, say  $M$ , such that on any input  $w \in \Sigma^*$ ,  $M$  stops with only  $f(w)$  on its tape.



# Polynomial time reductions and NP-hardness

## *Definition*

A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$

# Polynomial time reductions and NP-hardness

## *Definition*

A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$

# Polynomial time reductions and NP-hardness


## *Definition*

A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$ , if there exists a polynomial time computable function  $f$  such that for all  $w \in \Sigma^*$ ,  $w \in L_1 \Leftrightarrow f(w) \in L_2$ .

# Polynomial time reductions and NP-hardness

## *Definition*


A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$ , if there exists a polynomial time computable function  $f$  such that for all  $w \in \Sigma^*$ ,  $w \in L_1 \Leftrightarrow f(w) \in L_2$ .



# Polynomial time reductions and NP-hardness

## Definition


A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$ , if there exists a polynomial time computable function  $f$  such that for all  $w \in \Sigma^*$ ,  $w \in L_1 \Leftrightarrow f(w) \in L_2$ .



# Polynomial time reductions and NP-hardness

## Definition


A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$ , if there exists a polynomial time computable function  $f$  such that for all  $w \in \Sigma^*$ ,  $w \in L_1 \Leftrightarrow f(w) \in L_2$ .



# Polynomial time reductions and NP-hardness

## Definition

A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$ , if there exists a polynomial time computable function  $f$  such that for all  $w \in \Sigma^*$ ,  $w \in L_1 \Leftrightarrow f(w) \in L_2$ .



# Polynomial time reductions and NP-hardness

## Definition

A language  $L_1$  is said to be polynomial time reducible to another language  $L_2$ , denoted as  $L_1 \leq_m L_2$ , if there exists a polynomial time computable function  $f$  such that for all  $w \in \Sigma^*$ ,  $w \in L_1 \Leftrightarrow f(w) \in L_2$ .

