

COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420
Indian Institute of Technology, Delhi
nbalaji@cse.iitd.ac.in

April 12, 2023

Lecture 29: Rice's Theorem

More undecidable languages

The following languages are undecidable.

More undecidable languages

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

More undecidable languages

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

More undecidable languages

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

More undecidable languages

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

More undecidable languages

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

$$\{M \mid M \text{ does not have a left move}\}.$$

More undecidable languages

The following languages are undecidable.

$$\{M \mid L(M) \text{ is regular}\}.$$

$$\{M \mid L(M) \text{ is context-free}\}.$$

$$\{M \mid L(M) = \emptyset\}.$$

The following languages are decidable.

$$\{M \mid M \text{ has more than 10 states}\}.$$

$$\{M \mid M \text{ does not have a left move}\}.$$

Undecidability is the not an exception - it is the rule!

Rice's theorem: A systematic way of proving undecidability of languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$.

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$. ✓

Property P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Examples

Set of regular languages. ✓

Set of context-free languages. ✓

$\{\emptyset\}$. ✓

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Examples

Set of all TMs whose language is Σ^*

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Examples

Set of all TMs whose language is Σ^* ✓

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Examples

Set of all TMs whose language is Σ^* ✓

Set of all Turing recognizable languages such that a TM recognising it has at least 10 states.

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Examples

Set of all TMs whose language is Σ^* ✓

Set of all Turing recognizable languages such that a TM recognising it has at least 10 states. ✗

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Examples

Set of all TMs whose language is Σ^* ✓

Set of all Turing recognizable languages such that a TM recognising it has at least 10 states. ✗

Rice's theorem

Theorem

Let P be a non-trivial property of Turing recognizable languages. Let $\mathcal{L}_P = \{M \mid L(M) \in P\}$.

Rice's theorem

Definition

A property P of Turing recognizable languages is called a non-trivial property if

there exists a TM M such that $L(M) \in P$, and

there exists a TM M' such that $L(M') \notin P$.

Examples

Set of all TMs whose language is Σ^* ✓

Set of all Turing recognizable languages such that a TM recognising it has at least 10 states. ✗

Rice's theorem

Theorem

Let P be a non-trivial property of Turing recognizable languages. Let $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

For any property P , let $\mathcal{L}_P = \{M \mid L(M) \in P\}$

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

For any property P , let $\mathcal{L}_P = \{M \mid L(M) \in P\}$, i.e. the set of all Turing machine such that $L(M) \in P$.

Property P and \mathcal{L}_P

Definition

A property P is simply a subset of Turing recognizable languages. We say that a language L satisfies a property P , if $L \in P$.

For any property P , let $\mathcal{L}_P = \{M \mid L(M) \in P\}$, i.e. the set of all Turing machine such that $L(M) \in P$.

We say that a property P is trivial if either $\mathcal{L}_P = \emptyset$ or \mathcal{L}_P is the set of all the Turing recognizable languages.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}.$

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$?

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting a^*b^* is in \mathcal{L}_P .

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting a^*b^* is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$?

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting a^*b^* is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$? No.

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting a^*b^* is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$? No. For example, a TM accepting $\{a^n b^n \mid n \geq 0\}$ is not in \mathcal{L}_P .

Examples of properties

Examples

1. $\mathcal{L}_P = \{M \mid L(M) \text{ is regular}\}$.

\mathcal{L}_P is collection of TMs M such that $L(M)$ is regular.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM accepting a^*b^* is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$? No. For example, a TM accepting $\{a^n b^n \mid n \geq 0\}$ is not in \mathcal{L}_P .

Therefore, P is not trivial.

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$?

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No.

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$?

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$? No.

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$? No. For example, a TM M that accepts a single string $\{a\}$ is not in \mathcal{L}_P .

Examples of properties

Examples

2. $\mathcal{L}_P = \{M \mid L(M) = \emptyset\}.$

Here \mathcal{L}_P is a collection of TMs M such that $L(M) = \emptyset$.

Is $\mathcal{L}_P = \emptyset$? No. For example, a TM M that rejects any string is in \mathcal{L}_P .

Is $\mathcal{L}_P = \text{all TMs}$? No. For example, a TM M that accepts a single string $\{a\}$ is not in \mathcal{L}_P .

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

But any TM can be converted into another one that has even number of states.

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

But any TM can be converted into another one that has even number of states.

Therefore, any Turing recognizable language has property P .

Example of a trivial property

Examples

$$3. \mathcal{L}_P = \left\{ M \mid \begin{array}{l} M \text{ is a TM and } L(M) \text{ is accepted by} \\ \text{a TM that has even number of states} \end{array} \right\}.$$

Here P is a property of Turing recognizable languages.

But any TM can be converted into another one that has even number of states.

Therefore, any Turing recognizable language has property P .

Therefore, P is in fact all Turing recognizable languages.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

It is only used to prove undecidability.

Rice's theorem

Theorem

Let P be a property such that it is not trivial. Recall that $\mathcal{L}_P = \{M \mid L(M) \in P\}$. Then \mathcal{L}_P is undecidable.

When is the theorem NOT applicable?

When P is a property about TMs and not about Turing recognizable languages.

$\{\langle M \rangle \mid M \text{ has at least ten states}\}$.

$\{\langle M \rangle \mid M \text{ never moves left on any input string}\}$.

$\{\langle M \rangle \mid M \text{ has no useless state}\}$.

To prove non-recognizability of a property of languages.

Rice's theorem cannot be used to prove non-recognizability of languages.

It is only used to prove undecidability.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ runs for at most 10 steps on } aab\}$.

Not applicable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at least 10 states}\}.$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at least 10 states}\}.$

Applicable, but property is trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at least 10 states}\}.$

Applicable, but property is trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at most 10 states}\}.$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at most 10 states}\}.$

Applicable and property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized by a TM with at most 10 states}\}.$

Applicable and property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}$.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}$.

Not applicable, but the language is decidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid M \text{ has at most 10 states}\}$.

Not applicable, but the language is decidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid L(M) \text{ contains } \langle M \rangle\}$.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid L(M) \text{ contains } \langle M \rangle\}$.

Applicable, the property is not trivial

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid L(M) \text{ contains } \langle M \rangle\}$.

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{M \mid L(M) \text{ contains } \langle M \rangle\}$.

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$$\{\langle M \rangle \mid L(M) \text{ contains } \langle M \rangle\}.$$

Applicable, the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}$.

Applicable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

This is doable if we allow for the tape alphabet size to grow.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}$.

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

This is doable if we allow for the tape alphabet size to grow.

In that case, the property is trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

This is doable if we allow for the tape alphabet size to grow.

In that case, the property is trivial.

Textbooks usually consider this property to be not trivial.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

This is doable if we allow for the tape alphabet size to grow.

In that case, the property is trivial.

Textbooks usually consider this property to be not trivial.

This is because the usual assumption is that you always fix the tape alphabet.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

This is doable if we allow for the tape alphabet size to grow.

In that case, the property is trivial.

Textbooks usually consider this property to be not trivial.

This is because the usual assumption is that you always fix the tape alphabet.

In that case, Rice's theorem is applicable and the property is not trivial, therefore undecidable.

Applications of Rice's theorem

We now learn how to apply Rice's theorem

$\{\langle M \rangle \mid L(M) \text{ is recognized a TM with atmost 10 states}\}.$

Applicable.

If we can simulate any TM with another with less than 10 states, then the property will be trivial.

This is doable if we allow for the tape alphabet size to grow.

In that case, the property is trivial.

Textbooks usually consider this property to be not trivial.

This is because the usual assumption is that you always fix the tape alphabet.

In that case, Rice's theorem is applicable and the property is not trivial, therefore undecidable.