

# COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

February 15, 2023

Lecture 12: DFA Minimization

# DFA Minimization

- ▶ Given a DFA when can we say there are redundant states?

# DFA Minimization

- ▶ Given a DFA when can we say there are redundant states?
- ▶ Every regular language has a unique minimal DFA (upto isomorphism)


# DFA Minimization

- ▶ Given a DFA when can we say there are redundant states?
- ▶ Every regular language has a unique minimal DFA (upto isomorphism)
- ▶ Rough idea: Given  $M = (Q, \Sigma, q_0, \delta, F)$ 
  - ▶ Get rid of inaccessible states.


# DFA Minimization

- ▶ Given a DFA when can we say there are redundant states?
- ▶ Every regular language has a unique minimal DFA (upto isomorphism)
- ▶ Rough idea: Given  $M = (Q, \Sigma, q_0, \delta, F)$ 
  - ▶ Get rid of inaccessible states.
  - ▶ Collapse “equivalent” states.

# Minimization : Example 1




## Minimization : Example 1




$$L = \{\text{Strings of length } \geq 2\}$$

## Minimization : Example 1





$L = \{\text{Strings of length } \geq 2\}$







## Minimization : Example 2



## Minimization : Example 2



$$L = \{a^m \mid m \equiv 1 \pmod{3}\}$$

# A few pressing questions

# A few pressing questions

- ▶ How do we know two states can be collapsed without changing the language of the DFA?
- ▶ Can we do this formally?
- ▶ Is there an efficient algorithm for doing this?
- ▶ How do we know we can't collapse further?

# A few pressing questions

- ▶ How do we know two states can be collapsed without changing the language of the DFA?
- ▶ Can we do this formally?
- ▶ Is there an efficient algorithm for doing this?
- ▶ How do we know we can't collapse further?

# A few pressing questions

- ▶ How do we know two states can be collapsed without changing the language of the DFA?
  - ▶ Can we do this formally?
  - ▶ Is there an efficient algorithm for doing this?
  - ▶ How do we know we can't collapse further?
- 1 Should not collapse an accept and a reject state!  
If  $\hat{\delta}(s, x) = p \in F$  and  $\hat{\delta}(s, y) = q \notin F$ , so cannot collapse  $p$  and  $q$ !
  - 2 If we are collapsing  $p$  and  $q$ , better also collapse  $\delta(p, a)$  and  $\delta(q, a)$  for all  $a \in \Sigma$ .

Inductively, these two imply that we cannot collapse  $p$  and  $q$  if  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  for some string  $x$ .

# A few pressing questions

- ▶ How do we know two states can be collapsed without changing the language of the DFA?
  - ▶ Can we do this formally?
  - ▶ Is there an efficient algorithm for doing this?
  - ▶ How do we know we can't collapse further?
- 1 Should not collapse an accept and a reject state!  
If  $\hat{\delta}(s, x) = p \in F$  and  $\hat{\delta}(s, y) = q \notin F$ , so cannot collapse  $p$  and  $q$ !
  - 2 If we are collapsing  $p$  and  $q$ , better also collapse  $\delta(p, a)$  and  $\delta(q, a)$  for all  $a \in \Sigma$ .

Inductively, these two imply that we cannot collapse  $p$  and  $q$  if  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  for some string  $x$ . Turns out this is necessary and sufficient to decide if a pair of states can be collapsed or not!

# Quotient Construction



# Quotient Construction

Define a relation  $\equiv$  on the set of states:

# Quotient Construction

Define a relation  $\equiv$  on the set of states:

$$p \equiv q \iff \forall x \in \Sigma^* (\hat{\delta}(p, x) \in F \iff \hat{\delta}(q, x) \in F)$$

**Exercise:** Show that  $\equiv$  is an equivalence relation.

# Quotient Construction

Define a relation  $\equiv$  on the set of states:

$$p \equiv q \iff \forall x \in \Sigma^* (\hat{\delta}(p, x) \in F \iff \hat{\delta}(q, x) \in F)$$

**Exercise:** Show that  $\equiv$  is an equivalence relation.

$$[p] := \{q \mid q \equiv p\} \quad \text{Equivalence classes}$$

Every element  $p \in Q$  is contained in exactly one equivalence class  $[p]$ .

$$p \equiv q \iff [p] = [q]$$

# Quotient Construction

Define a relation  $\equiv$  on the set of states:

$$p \equiv q \iff \forall x \in \Sigma^* (\hat{\delta}(p, x) \in F \iff \hat{\delta}(q, x) \in F)$$

**Exercise:** Show that  $\equiv$  is an equivalence relation.

$$[p] := \{q \mid q \equiv p\} \quad \text{Equivalence classes}$$

Every element  $p \in Q$  is contained in exactly one equivalence class  $[p]$ .

$$p \equiv q \iff [p] = [q]$$

Why not define an automaton whose states are just these equivalence classes?

# Quotient Construction

Define a relation  $\equiv$  on the set of states:

$$p \equiv q \iff \forall x \in \Sigma^* (\hat{\delta}(p, x) \in F \iff \hat{\delta}(q, x) \in F)$$

**Exercise:** Show that  $\equiv$  is an equivalence relation.

$$[p] := \{q \mid q \equiv p\} \quad \text{Equivalence classes}$$

Every element  $p \in Q$  is contained in exactly one equivalence class  $[p]$ .

$$p \equiv q \iff [p] = [q]$$

Why not define an automaton whose states are just these equivalence classes? (This is exactly the “collapsing states” we wanted!)

# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$

# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$
- ▶  $\delta'([p], a) := [\delta(p, a)]$

# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$
- ▶  $\delta'([p], a) := [\delta(p, a)]$
- ▶  $s' = [s]$
- ▶  $F' = \{[p] \mid p \in F\}$



# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$
- ▶  $\delta'([p], a) := [\delta(p, a)]$
- ▶  $s' = [s]$
- ▶  $F' = \{[p] \mid p \in F\}$

Is the definition of  $\delta'$  well-defined?

# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$
- ▶  $\delta'([p], a) := [\delta(p, a)]$
- ▶  $s' = [s]$
- ▶  $F' = \{[p] \mid p \in F\}$

Is the definition of  $\delta'$  well-defined?

**Claim:** If  $p \equiv q$  then is  $[\delta(p, a)] = [\delta(q, a)]$

# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$
- ▶  $\delta'([p], a) := [\delta(p, a)]$
- ▶  $s' = [s]$
- ▶  $F' = \{[p] \mid p \in F\}$

Is the definition of  $\delta'$  well-defined?

**Claim:** If  $p \equiv q$  then is  $[\delta(p, a)] = [\delta(q, a)]$  Let  $p \equiv q$ ,  $a \in \Sigma$  and  $y \in \Sigma^*$

$$\hat{\delta}(\delta(p, a), y) \in F \iff \hat{\delta}(p, ay) \in F$$

# Quotient Construction

## Quotient Automaton

$M / \equiv := (Q', \Sigma, \delta', s', F')$ , where

- ▶  $Q' := \{[p] \mid p \in Q\}$
- ▶  $\delta'([p], a) := [\delta(p, a)]$
- ▶  $s' = [s]$
- ▶  $F' = \{[p] \mid p \in F\}$

Is the definition of  $\delta'$  well-defined?

**Claim:** If  $p \equiv q$  then is  $[\delta(p, a)] = [\delta(q, a)]$  Let  $p \equiv q$ ,  $a \in \Sigma$  and  $y \in \Sigma^*$

$$\begin{aligned}\hat{\delta}(\delta(p, a), y) \in F &\iff \hat{\delta}(p, ay) \in F \\ &\iff \hat{\delta}(q, ay) \in F \\ &\iff \hat{\delta}(\delta(q, a), y) \in F \quad \square\end{aligned}$$

# Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

# Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

**Proof.** By induction on  $|x|$ .

*Basis:* For  $x = \varepsilon$ ,

$$\begin{aligned}\hat{\delta}'([p], \varepsilon) &= [p] && \text{(by definition of } \hat{\delta}')} \\ &= [\hat{\delta}(p, \varepsilon)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

*Induction step:* Assume  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$  and let  $a \in \Sigma$ .

$$\hat{\delta}'([p], xa) = \hat{\delta}'(\hat{\delta}'([p], x), a) \quad \text{(by definition of } \hat{\delta}')$$

# Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

**Proof.** By induction on  $|x|$ .

*Basis:* For  $x = \varepsilon$ ,

$$\begin{aligned}\hat{\delta}'([p], \varepsilon) &= [p] && \text{(by definition of } \hat{\delta}')} \\ &= [\hat{\delta}(p, \varepsilon)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

*Induction step:* Assume  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$  and let  $a \in \Sigma$ .

$$\begin{aligned}\hat{\delta}'([p], xa) &= \hat{\delta}'(\hat{\delta}'([p], x), a) && \text{(by definition of } \hat{\delta}')} \\ &= \hat{\delta}'([\hat{\delta}(p, x)], a) && \text{(by induction hypothesis)}\end{aligned}$$

# Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

**Proof.** By induction on  $|x|$ .

*Basis:* For  $x = \varepsilon$ ,

$$\begin{aligned}\hat{\delta}'([p], \varepsilon) &= [p] && \text{(by definition of } \hat{\delta}')} \\ &= [\hat{\delta}(p, \varepsilon)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

*Induction step:* Assume  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$  and let  $a \in \Sigma$ .

$$\begin{aligned}\hat{\delta}'([p], xa) &= \hat{\delta}'(\hat{\delta}'([p], x), a) && \text{(by definition of } \hat{\delta}')} \\ &= \delta'([\hat{\delta}(p, x)], a) && \text{(by induction hypothesis)} \\ &= [\delta(\hat{\delta}(p, x), a)] && \text{(by definition of } \delta')\end{aligned}$$



# Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

**Proof.** By induction on  $|x|$ .

*Basis:* For  $x = \varepsilon$ ,

$$\begin{aligned}\hat{\delta}'([p], \varepsilon) &= [p] && \text{(by definition of } \hat{\delta}')} \\ &= [\hat{\delta}(p, \varepsilon)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

*Induction step:* Assume  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$  and let  $a \in \Sigma$ .

$$\begin{aligned}\hat{\delta}'([p], xa) &= \hat{\delta}'(\hat{\delta}'([p], x), a) && \text{(by definition of } \hat{\delta}')} \\ &= \delta'([\hat{\delta}(p, x)], a) && \text{(by induction hypothesis)} \\ &= [\delta(\hat{\delta}(p, x), a)] && \text{(by definition of } \delta') \\ &= [\hat{\delta}(p, xa)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

## Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

**Proof.** By induction on  $|x|$ .

*Basis:* For  $x = \varepsilon$ ,

$$\begin{aligned}\hat{\delta}'([p], \varepsilon) &= [p] && \text{(by definition of } \hat{\delta}')} \\ &= [\hat{\delta}(p, \varepsilon)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

*Induction step:* Assume  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$  and let  $a \in \Sigma$ .

$$\begin{aligned}\hat{\delta}'([p], xa) &= \hat{\delta}'(\hat{\delta}'([p], x), a) && \text{(by definition of } \hat{\delta}')} \\ &= \delta'([\hat{\delta}(p, x)], a) && \text{(by induction hypothesis)} \\ &= [\delta(\hat{\delta}(p, x), a)] && \text{(by definition of } \delta') \\ &= [\hat{\delta}(p, xa)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

**Claim:**  $L(M/\equiv) = L(M)$

## Quotient Construction: Correctness

**Claim:** For all  $x \in \Sigma^*$ ,  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$

**Proof.** By induction on  $|x|$ .

*Basis:* For  $x = \varepsilon$ ,

$$\begin{aligned}\hat{\delta}'([p], \varepsilon) &= [p] && \text{(by definition of } \hat{\delta}')} \\ &= [\hat{\delta}(p, \varepsilon)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

*Induction step:* Assume  $\hat{\delta}'([p], x) = [\hat{\delta}(p, x)]$  and let  $a \in \Sigma$ .

$$\begin{aligned}\hat{\delta}'([p], xa) &= \hat{\delta}'(\hat{\delta}'([p], x), a) && \text{(by definition of } \hat{\delta}')} \\ &= \delta'([\hat{\delta}(p, x)], a) && \text{(by induction hypothesis)} \\ &= [\delta(\hat{\delta}(p, x), a)] && \text{(by definition of } \delta') \\ &= [\hat{\delta}(p, xa)] && \text{(by definition of } \hat{\delta})\end{aligned}$$

**Claim:**  $L(M/\equiv) = L(M)$  Exercise!

# Cannot Collapse Further

Define

$$[p] \approx [q] \iff \forall x \in \Sigma^* (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F')$$

Apply this relation on  $M/\equiv$ .

$$\begin{array}{ccc} [p] & \approx & [q] \\ \implies & & \forall x (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F') \end{array}$$

# Cannot Collapse Further

Define

$$[p] \approx [q] \iff \forall x \in \Sigma^* (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F')$$

Apply this relation on  $M/\equiv$ .

$$\begin{aligned} [p] &\approx [q] \\ \implies &\forall x (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F') \\ \implies &\forall x ([\hat{\delta}(p, x)] \in F' \iff [\hat{\delta}(q, x)] \in F') \end{aligned}$$

# Cannot Collapse Further

Define

$$[p] \approx [q] \iff \forall x \in \Sigma^* (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F')$$

Apply this relation on  $M/\equiv$ .

$$\begin{aligned} [p] &\approx [q] \\ \implies &\forall x (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F') \\ \implies &\forall x ([\hat{\delta}(p, x)] \in F' \iff [\hat{\delta}(q, x)] \in F') \\ \implies &\forall x (\hat{\delta}(p, x) \in F \iff \hat{\delta}(q, x) \in F) \end{aligned}$$

# Cannot Collapse Further

Define

$$[p] \approx [q] \iff \forall x \in \Sigma^* (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F')$$

Apply this relation on  $M/\equiv$ .

$$\begin{aligned} [p] &\approx [q] \\ \implies \forall x (\hat{\delta}'([p], x) \in F' &\iff \hat{\delta}'([q], x) \in F') \\ \implies \forall x ([\hat{\delta}(p, x)] \in F' &\iff [\hat{\delta}(q, x)] \in F') \\ \implies \forall x (\hat{\delta}(p, x) \in F &\iff \hat{\delta}(q, x) \in F) \\ \implies p \equiv q \end{aligned}$$

# Cannot Collapse Further

Define

$$[p] \approx [q] \iff \forall x \in \Sigma^* (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F')$$

Apply this relation on  $M/\equiv$ .

$$\begin{aligned} [p] &\approx [q] \\ \implies &\forall x (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F') \\ \implies &\forall x ([\hat{\delta}(p, x)] \in F' \iff [\hat{\delta}(q, x)] \in F') \\ \implies &\forall x (\hat{\delta}(p, x) \in F \iff \hat{\delta}(q, x) \in F) \\ \implies &p \equiv q \\ \implies &[p] = [q] \end{aligned}$$



# Cannot Collapse Further

Define

$$[p] \approx [q] \iff \forall x \in \Sigma^* (\hat{\delta}'([p], x) \in F' \iff \hat{\delta}'([q], x) \in F')$$

Apply this relation on  $M/\equiv$ .

$$\begin{aligned} [p] &\approx [q] \\ \implies \forall x (\hat{\delta}'([p], x) \in F' &\iff \hat{\delta}'([q], x) \in F') \\ \implies \forall x ([\hat{\delta}(p, x)] \in F' &\iff [\hat{\delta}(q, x)] \in F') \\ \implies \forall x (\hat{\delta}(p, x) \in F &\iff \hat{\delta}(q, x) \in F) \\ \implies p &\equiv q \\ \implies [p] &= [q] \end{aligned}$$

The relation  $\approx$  is just equality (=)!

# An algorithm for DFA minimization

Let  $M$  be a DFA with no inaccessible states. We will mark (unordered) pairs of states  $\{p, q\}$  if we discover a reason why they are not equivalent.

- 1 Write down a table of pairs  $\{p, q\}$ , initially unmarked.
- 2 Mark  $\{p, q\}$  if  $p \in F$  and  $q \notin F$ , or vice-versa.
- 3 Repeat until no change occurs: if there exists an unmarked pair  $\{p, q\}$  such that  $\{\delta(p, a), \delta(q, a)\}$  is marked for some  $a \in \Sigma$  then mark  $\{p, q\}$ .
- 4 When done,  $p \equiv q$  iff  $\{p, q\}$  is not marked.

# An algorithm for DFA minimization

Let  $M$  be a DFA with no inaccessible states. We will mark (unordered) pairs of states  $\{p, q\}$  if we discover a reason why they are not equivalent.

- 1 Write down a table of pairs  $\{p, q\}$ , initially unmarked.
- 2 Mark  $\{p, q\}$  if  $p \in F$  and  $q \notin F$ , or vice-versa.
- 3 Repeat until no change occurs: if there exists an unmarked pair  $\{p, q\}$  such that  $\{\delta(p, a), \delta(q, a)\}$  is marked for some  $a \in \Sigma$  then mark  $\{p, q\}$ .
- 4 When done,  $p \equiv q$  iff  $\{p, q\}$  is not marked.

## Remarks:

- ▶ If  $p$  and  $q$  are marked in Step 2 then definitely they are not equivalent as witnessed by the empty string!

# An algorithm for DFA minimization

Let  $M$  be a DFA with no inaccessible states. We will mark (unordered) pairs of states  $\{p, q\}$  if we discover a reason why they are not equivalent.

- 1 Write down a table of pairs  $\{p, q\}$ , initially unmarked.
- 2 Mark  $\{p, q\}$  if  $p \in F$  and  $q \notin F$ , or vice-versa.
- 3 Repeat until no change occurs: if there exists an unmarked pair  $\{p, q\}$  such that  $\{\delta(p, a), \delta(q, a)\}$  is marked for some  $a \in \Sigma$  then mark  $\{p, q\}$ .
- 4 When done,  $p \equiv q$  iff  $\{p, q\}$  is not marked.

## Remarks:

- ▶ If  $p$  and  $q$  are marked in Step 2 then definitely they are not equivalent as witnessed by the empty string!
- ▶ Same pair  $\{p, q\}$  has to be visited by the algorithm multiple times (status might change because of other  $\checkmark$  filled in the table)

# Finding equivalent states



# Finding equivalent states

Given: DFA  $A$

# Finding equivalent states

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other



# Finding equivalent states

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |



# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| - | ✓ | 2 |   |   |   |  |
| - | ✓ | - | 3 |   |   |  |
| ✓ | - | ✓ | ✓ | 4 |   |  |
| - | ✓ | - | - | ✓ | 5 |  |

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| - | ✓ | 2 |   |   |   |  |
| - | ✓ | - | 3 |   |   |  |
| ✓ | - | ✓ | ✓ | 4 |   |  |
| - | ✓ | - | - | ✓ | 5 |  |

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| - | ✓ | 2 |   |   |   |  |
| - | ✓ | - | 3 |   |   |  |
| ✓ | - | ✓ | ✓ | 4 |   |  |
| - | ✓ | - | - | ✓ | 5 |  |

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| – | 1 |   |   |   |   |  |
| – | – | 2 |   |   |   |  |
| – | – | – | 3 |   |   |  |
| – | – | – | – | 4 |   |  |
| – | – | – | – | – | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| ✓ | ✓ | 2 |   |   |   |  |
| – | ✓ | – | 3 |   |   |  |
| ✓ | – | ✓ | ✓ | 4 |   |  |
| – | ✓ | – | – | ✓ | 5 |  |

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| ✓ | ✓ | 2 |   |   |   |  |
| - | ✓ | - | 3 |   |   |  |
| ✓ | - | ✓ | ✓ | 4 |   |  |
| ✓ | ✓ | - | - | ✓ | 5 |  |

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| ✓ | ✓ | 2 |   |   |   |  |
| - | ✓ | ✓ | 3 |   |   |  |
| ✓ | - | ✓ | ✓ | 4 |   |  |
| ✓ | ✓ | - | - | ✓ | 5 |  |

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Example


|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 2 | 3 | 4 | 5 | 0 |

(Red color indicates final states.)

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| - | 1 |   |   |   |   |  |
| - | - | 2 |   |   |   |  |
| - | - | - | 3 |   |   |  |
| - | - | - | - | 4 |   |  |
| - | - | - | - | - | 5 |  |

|   |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| 0 |   |   |   |   |   |  |
| ✓ | 1 |   |   |   |   |  |
| ✓ | ✓ | 2 |   |   |   |  |
| - | ✓ | ✓ | 3 |   |   |  |
| ✓ | - | ✓ | ✓ | 4 |   |  |
| ✓ | ✓ | - | ✓ | ✓ | 5 |  |

# Example



|       |       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|-------|
| $q_1$ | ✓     |       |       |       |       |       |       |
| $q_2$ | ✓     | ✓     |       |       |       |       |       |
| $q_3$ | ✓     | ✓     | ✓     |       |       |       |       |
| $q_4$ |       | ✓     | ✓     | ✓     |       |       |       |
| $q_5$ | ✓     | ✓     | ✓     |       | ✓     |       |       |
| $q_6$ | ✓     | ✓     | ✓     | ✓     | ✓     | ✓     |       |
| $q_7$ | ✓     |       | ✓     | ✓     | ✓     | ✓     | ✓     |
| $D$   | $q_0$ | $q_1$ | $q_2$ | $q_3$ | $q_4$ | $q_5$ | $q_6$ |



# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Algorithm

Let  $Q = \{q_1, \dots, q_n\}$ .

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Algorithm

Let  $Q = \{q_1, \dots, q_n\}$ .

1. For each  $1 \leq i < j \leq n$ , initialize  $T(i, j) = --$

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Algorithm

Let  $Q = \{q_1, \dots, q_n\}$ .

1. For each  $1 \leq i < j \leq n$ , initialize  $T(i, j) = --$
2. For each  $1 \leq i < j \leq n$

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Algorithm

Let  $Q = \{q_1, \dots, q_n\}$ .

1. For each  $1 \leq i < j \leq n$ , initialize  $T(i, j) = --$
2. For each  $1 \leq i < j \leq n$   
If  $(q_i \in F \text{ AND } q_j \notin F) \text{ OR } (q_i \notin F \text{ AND } q_j \in F)$   
 $T(i, j) \leftarrow \checkmark$
3. Repeat

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Algorithm

Let  $Q = \{q_1, \dots, q_n\}$ .

1. For each  $1 \leq i < j \leq n$ , initialize  $T(i, j) = --$
2. For each  $1 \leq i < j \leq n$   
If  $(q_i \in F \text{ AND } q_j \notin F) \text{ OR } (q_i \notin F \text{ AND } q_j \in F)$   
 $T(i, j) \leftarrow \checkmark$
3. Repeat  
    { For each  $1 \leq i < j \leq n$

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: sets of states of  $A$  equivalent to each other

Algorithm

Let  $Q = \{q_1, \dots, q_n\}$ .

1. For each  $1 \leq i < j \leq n$ , initialize  $T(i, j) = --$

2. For each  $1 \leq i < j \leq n$

If  $(q_i \in F \text{ AND } q_j \notin F) \text{ OR } (q_i \notin F \text{ AND } q_j \in F)$   
 $T(i, j) \leftarrow \checkmark$

3. Repeat

{ For each  $1 \leq i < j \leq n$   
If  $\exists a \in \Sigma, T(\delta(q_i, a), \delta(q_j, a)) = \checkmark$   
then  $T(i, j) \leftarrow \checkmark$   
}

Untill  $T$  stays unchanged.

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).



# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

$$\mathcal{Q} = \{\{p, q\} \mid p, q \in Q, p \neq q\}$$

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

$$\mathcal{Q} = \{\{p, q\} \mid p, q \in Q, p \neq q\}$$

$$\Delta : \mathcal{Q} \rightarrow 2^{\mathcal{Q}} \text{ defined as}$$

$$\Delta(\{p, q\}, a) := \{\{p', q'\} \mid p = \delta(p', a), q = \delta(q', a)\}$$

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

$$\mathcal{Q} = \{\{p, q\} \mid p, q \in Q, p \neq q\}$$

$$\Delta : \mathcal{Q} \rightarrow 2^{\mathcal{Q}} \text{ defined as}$$

$$\Delta(\{p, q\}, a) := \{\{p', q'\} \mid p = \delta(p', a), q = \delta(q', a)\}$$

$$\mathcal{S} := \{\{p, q\} \mid p \in F, q \notin F\}$$

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

$$\mathcal{Q} = \{\{p, q\} \mid p, q \in Q, p \neq q\}$$

$$\Delta : \mathcal{Q} \rightarrow 2^{\mathcal{Q}} \text{ defined as}$$

$$\Delta(\{p, q\}, a) := \{\{p', q'\} \mid p = \delta(p', a), q = \delta(q', a)\}$$

$$\mathcal{S} := \{\{p, q\} \mid p \in F, q \notin F\}$$

- Step 2 marks elements of  $\mathcal{S}$ .

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

$$\mathcal{Q} = \{\{p, q\} \mid p, q \in Q, p \neq q\}$$

$$\Delta : \mathcal{Q} \rightarrow 2^{\mathcal{Q}} \text{ defined as}$$

$$\Delta(\{p, q\}, a) := \{\{p', q'\} \mid p = \delta(p', a), q = \delta(q', a)\}$$

$$\mathcal{S} := \{\{p, q\} \mid p \in F, q \notin F\}$$

- ▶ Step 2 marks elements of  $\mathcal{S}$ .
- ▶ Step 3 marks pairs in  $\Delta(\{p, q\}, a)$  when  $\{p, q\}$  is marked for some  $a \in \Sigma$ .

# Proof of Correctness

**Claim:** The pair  $\{p, q\}$  is not marked by the algorithm if and only if there exists  $x \in \Sigma^*$  such that  $\hat{\delta}(p, x) \in F$  and  $\hat{\delta}(q, x) \notin F$  or vice-versa, i.e., if and only if  $p \neq q$ .

**Proof.** By induction (Exercise!).

An automaton view of the algorithm:

$$\mathcal{Q} = \{\{p, q\} \mid p, q \in Q, p \neq q\}$$

$$\Delta : \mathcal{Q} \rightarrow 2^{\mathcal{Q}} \text{ defined as}$$

$$\Delta(\{p, q\}, a) := \{\{p', q'\} \mid p = \delta(p', a), q = \delta(q', a)\}$$

$$\mathcal{S} := \{\{p, q\} \mid p \in F, q \notin F\}$$

- ▶ Step 2 marks elements of  $\mathcal{S}$ .
- ▶ Step 3 marks pairs in  $\Delta(\{p, q\}, a)$  when  $\{p, q\}$  is marked for some  $a \in \Sigma$ .
- ▶ Claim above says  $p \neq q \iff \{p, q\}$  if and only if  $\{p, q\}$  is reachable from  $\mathcal{S}$ .

# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: DFA  $B$  s.t.  $L(A) = L(B)$  and  $B$  has the smallest number of states possible for recognizing  $L(A)$

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 3 | 4 | 5 | 5 | 5 |
| b | 2 | 4 | 3 | 5 | 5 | 5 |

(Red color indicates final states.)



# Minimization problem

Minimization problem (for fixed  $\Sigma$ )

Given: DFA  $A$

Output: DFA  $B$  s.t.  $L(A) = L(B)$  and  $B$  has the smallest number of states possible for recognizing  $L(A)$

Example

|   | 0 | 1 | 2 | 3 | 4 | 5 |
|---|---|---|---|---|---|---|
| a | 1 | 3 | 4 | 5 | 5 | 5 |
| b | 2 | 4 | 3 | 5 | 5 | 5 |

(Red color indicates final states.)

| 0 |   |   |   |   |   |  |
|---|---|---|---|---|---|--|
| ✓ | 1 |   |   |   |   |  |
| ✓ | - | 2 |   |   |   |  |
| - | ✓ | ✓ | 3 |   |   |  |
| - | ✓ | ✓ | - | 4 |   |  |
| ✓ | - | - | ✓ | ✓ | 5 |  |

DIY!