

# COL 352 Introduction to Automata and Theory of Computation

Nikhil Balaji

Bharti 420  
Indian Institute of Technology, Delhi  
[nbalaji@cse.iitd.ac.in](mailto:nbalaji@cse.iitd.ac.in)

April 9, 2023

Lecture 28: Reductions 3

# Universality of CFG

*Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{ \langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^* \}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ )

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .



# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

$$\text{Input } (M, w) \longrightarrow N_{M,w}$$

# Universality of CFG

## *Lemma*

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

# Universality of CFG

## Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

# Universality of CFG

## Lemma

$ALL_{CFG} = \{\langle M \rangle \mid M \text{ is a PDA and } L(M) = \Sigma^*\}$  is undecidable.

## Proof Strategy

For a TM  $M$  and input  $w$  we create a PDA  $N_{M,w}$  such that

$N_{M,w}$  accepts all strings (i.e. accepts  $\Sigma^*$ ) if  $M$  accepts  $w$ , and

$N_{M,w}$  rejects at least one string if  $M$  does not accept  $w$ .

Formally,

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

# Filling in the details

The following two details need to be addressed.

$Q_1$  How should we design  $N_{M,w}$ ?

## Filling in the details

The following two details need to be addressed.

$Q_1$  How should we design  $N_{M,w}$ ?

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$



## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that  $ALL_{CFL}$  is decidable.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  
 $C$ .

Assume that  $ALL_{CFL}$  is decidable.  
 $C$  be the TM deciding it.

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  
 $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

If  $C$  accepts then  
reject;

## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  
 $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

If  $C$  accepts then  
reject;

else accept.



## Details for $Q_2$

$Q_2$  If such an  $N_{M,w}$  is designed then why have we proved that  $ALL_{CFL}$  is undecidable?

Design  $A$  as follows:

Input  $(M, w) \longrightarrow N_{M,w}$

if  $w \in L(M) \longrightarrow \exists x \in \Sigma^*, \text{ s.t. } x \notin L(N_{M,w})$

if  $w \notin L(M) \longrightarrow L(N_{M,w}) = \Sigma^*$

For an  $M, w$  pair,  
create  $N_{M,w}$ .

Feed  $\langle N_{M,w} \rangle$  to  
 $C$ .

Assume that  $ALL_{CFL}$  is decidable.

$C$  be the TM deciding it.

If  $C$  accepts then  
reject;

else accept.

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:  
 $C_1, C_2, \dots, C_\ell$  such that

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:  
 $C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is an accepting configuration.

for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:  
 $C_1, C_2, \dots, C_\ell$  such that

# Details for $Q_1$ : reduction via computation history

$Q_1$  How should we design  $N_{M,w}$ ?

Main idea

Use computational history of  $M$  on  $w$ .

*Accepting computation history* is a sequence of configurations:  
 $C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is an accepting configuration.

for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

*Rejecting computation history* is a sequence of configurations:  
 $C_1, C_2, \dots, C_\ell$  such that

$C_1$  is a start configuration.

$C_\ell$  is a rejecting configuration.

for each  $1 \leq i \leq \ell$ ,  $C_i$  yields  $C_{i+1}$ .

# Universality of CFLs is undecidable!

- Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:



# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .
- ▶ If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .

$N_{M,w}$  will reject  $\tilde{x}$

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .
- ▶ If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .

$N_{M,w}$  will reject  $\tilde{x}$ , i.e.  $\tilde{x} \notin L(N_{M,w})$ .

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .
- ▶ If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .  
 $N_{M,w}$  will reject  $\tilde{x}$ , i.e.  $\tilde{x} \notin L(N_{M,w})$ .
- ▶ If  $M$  does not accept  $w$ , then  
no matter what  $x$  is,  $N_{M,w}$  will accept  $x$

# Universality of CFLs is undecidable!

- ▶ Interpret input  $x$  to  $N_{M,w}$  as a computational history of  $M$  on  $w$ .
- ▶ Design  $N_{M,w}$  s.t. it accepts  $x$  if any of the following conditions holds:
  - ▶  $x$  does not have the pattern of a computational history of  $x$  OR
  - ▶  $x$  is a computational history, but  $C_1$  is not a start configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration, but  $C_\ell$  is not an accepting configuration OR
  - ▶  $x$  is a computational history,  $C_1$  is a start configuration,  $C_\ell$  is an accepting configuration, but there exists an  $i$  s.t.  $1 \leq i \leq \ell - 1$  and  $C_i$  does not yield  $C_{i+1}$ .
- ▶ If  $M$  accepts  $w$ , let  $\tilde{x}$  be a accepting computation history of  $M$  on  $w$ .  
 $N_{M,w}$  will reject  $\tilde{x}$ , i.e.  $\tilde{x} \notin L(N_{M,w})$ .
- ▶ If  $M$  does not accept  $w$ , then  
no matter what  $x$  is,  $N_{M,w}$  will accept  $x$ , i.e.  $L(N_{M,w}) = \Sigma^*$ .



# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists.

# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

**Example:** Consider the lists  $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$  and  $B = \langle \text{110110}, \text{00}, \text{110} \rangle$ .

# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

**Example:** Consider the lists  $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$  and  $B = \langle \text{110110}, \text{00}, \text{110} \rangle$ . **Solution:** There is a sequence  $i = 2, 3, 1$  such that  $s_2 s_3 s_1 = t_2 t_3 t_1$ ,

**Witness:**  $s_2 s_3 s_1 = \text{00110110110}$  and  $t_2 t_3 t_1 = \text{00110110110}$

# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

**Example:** Consider the lists  $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$  and  $B = \langle \text{110110}, \text{00}, \text{110} \rangle$ . **Solution:** There is a sequence  $i = 2, 3, 1$  such that  $s_2 s_3 s_1 = t_2 t_3 t_1$ ,

**Witness:**  $s_2 s_3 s_1 = \text{00110110110}$  and  $t_2 t_3 t_1 = \text{00110110110}$

- ▶ What about  $A = \{0011, 11, 1101\}$  and  $B = \{101, 1, 110\}$ ?

# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

**Example:** Consider the lists  $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$  and  $B = \langle \text{110110}, \text{00}, \text{110} \rangle$ . **Solution:** There is a sequence  $i = 2, 3, 1$  such that  $s_2 s_3 s_1 = t_2 t_3 t_1$ ,

**Witness:**  $s_2 s_3 s_1 = \text{00110110110}$  and  $t_2 t_3 t_1 = \text{00110110110}$

- ▶ What about  $A = \{0011, 11, 1101\}$  and  $B = \{101, 1, 110\}$ ?
- ▶ What about  $A = \{100, 0, 1\}$  and  $B = \{1, 100, 0\}$ ?

# A String Matching Problem

## String List Matching Problem

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

**Example:** Consider the lists  $A = \langle \text{110}, \text{0011}, \text{0110} \rangle$  and  $B = \langle \text{110110}, \text{00}, \text{110} \rangle$ . **Solution:** There is a sequence  $i = 2, 3, 1$  such that  $s_2 s_3 s_1 = t_2 t_3 t_1$ ,

**Witness:**  $s_2 s_3 s_1 = \text{00110110110}$  and  $t_2 t_3 t_1 = \text{00110110110}$

- ▶ What about  $A = \{0011, 11, 1101\}$  and  $B = \{101, 1, 110\}$ ?
- ▶ What about  $A = \{100, 0, 1\}$  and  $B = \{1, 100, 0\}$ ? (Shortest solution length = 75)

# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists.

# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Can you design an algorithm to solve this problem? A semi-algorithm?



# A String Matching Problem

## *String List Matching Problem*

Given two lists  $A = \langle s_1, s_2, \dots, s_n \rangle$  and  $B = \langle t_1, t_2, \dots, t_n \rangle$  of strings of equal length, decide whether there is a sequence of combining elements that produces same string for both lists. Formally, does there exist a finite sequence  $1 \leq i_1, i_2, \dots, i_m \leq n$  (no limit on length) such that

$$s_{i_1} s_{i_2} \dots s_{i_n} = t_{i_1} t_{i_2} \dots t_{i_n}$$

Can you design an algorithm to solve this problem? A semi-algorithm?

## *Theorem*

*There is no algorithm for the string-list matching problem. In other words, this problem is undecidable.*

# Post's Correspondence Problem

## *A Domino game*

Given a collection of dominos  $\begin{bmatrix} b \\ ca \end{bmatrix}$   $\begin{bmatrix} a \\ ab \end{bmatrix}$   $\begin{bmatrix} ca \\ a \end{bmatrix}$   $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.

# Post's Correspondence Problem

## *A Domino game*

Given a collection of dominos  $\begin{bmatrix} b \\ ca \end{bmatrix}$   $\begin{bmatrix} a \\ ab \end{bmatrix}$   $\begin{bmatrix} ca \\ a \end{bmatrix}$   $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.
- ▶ Does this collection of dominos have a match?

# Post's Correspondence Problem

## *A Domino game*

Given a collection of dominos  $\begin{bmatrix} b \\ ca \end{bmatrix}$   $\begin{bmatrix} a \\ ab \end{bmatrix}$   $\begin{bmatrix} ca \\ a \end{bmatrix}$   $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.
- ▶ Does this collection of dominos have a match?
- ▶ Same as the string matching problem

# Post's Correspondence Problem

## *A Domino game*

Given a collection of dominos  $\begin{bmatrix} b \\ ca \end{bmatrix}$   $\begin{bmatrix} a \\ ab \end{bmatrix}$   $\begin{bmatrix} ca \\ a \end{bmatrix}$   $\begin{bmatrix} abc \\ c \end{bmatrix}$

- ▶ A match is a list of these dominos (with possible repetitions) such that the string formed in top is same as string formed by bottom row.
- ▶ Does this collection of dominos have a match?
- ▶ Same as the string matching problem
- ▶ Called Post's Correspondence Problem or PCP.

## *Theorem*

*PCP is undecidable.*

- ▶ Encode TM computation histories!
- ▶ Each transition as a domino!
- ▶ Simulate the run using the dominos.

# Proof of Undecidability of PCP

*Simplifying assumptions*

# Proof of Undecidability of PCP

## *Simplifying assumptions*

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.

# Proof of Undecidability of PCP

## *Simplifying assumptions*

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If  $w = \varepsilon$ , then use  $\sqcup$  instead of  $w$ .



# Proof of Undecidability of PCP

## *Simplifying assumptions*

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If  $w = \varepsilon$ , then use  $\sqcup$  instead of  $w$ .
- ▶  $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

# Proof of Undecidability of PCP

## *Simplifying assumptions*

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If  $w = \varepsilon$ , then use  $\sqcup$  instead of  $w$ .
- ▶  $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

We define a reduction from  $A_{TM}$  to (M)PCP.

# Proof of Undecidability of PCP

## *Simplifying assumptions*

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If  $w = \varepsilon$ , then use  $\sqcup$  instead of  $w$ .
- ▶  $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

We define a reduction from  $A_{TM}$  to (M)PCP. Let an instance of  $A_{TM}$  be

- ▶  $M = (Q, \Sigma, \Gamma, \delta, q_0, q_f, q_r)$
- ▶  $w = w_1 \dots w_n$

# Proof of Undecidability of PCP

## *Simplifying assumptions*

- ▶ Assume that the tape of TM is one-way infinite and never attempts to move left of its left-end.
- ▶ If  $w = \varepsilon$ , then use  $\sqcup$  instead of  $w$ .
- ▶  $P = \left\{ \begin{bmatrix} t_1 \\ b_1 \end{bmatrix}, \begin{bmatrix} t_2 \\ b_2 \end{bmatrix}, \dots, \begin{bmatrix} t_k \\ b_k \end{bmatrix} \right\}$
- ▶ Modify PCP so that match must start with a given domino, say the first one.

We define a reduction from  $A_{TM}$  to (M)PCP. Let an instance of  $A_{TM}$  be

- ▶  $M = (Q, \Sigma, \Gamma, \delta, q_0, q_f, q_r)$
- ▶  $w = w_1 \dots w_n$

We build instance  $P'$  of MPCP in several steps.

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every  $a, b, c \in \Gamma$  and every  $q, q' \in Q$ ,  $q \neq q_r$ ,
  - ▶ If  $\delta(q, a) = (q', b, R)$ , then add domino to  $P'$



# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every  $a, b, c \in \Gamma$  and every  $q, q' \in Q$ ,  $q \neq q_r$ ,
  - ▶ If  $\delta(q, a) = (q', b, R)$ , then add domino to  $P'$

$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every  $a, b, c \in \Gamma$  and every  $q, q' \in Q$ ,  $q \neq q_r$ ,
  - ▶ If  $\delta(q, a) = (q', b, R)$ , then add domino to  $P'$ 
$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$
  - ▶ If  $\delta(q, a) = (q', b, L)$ , then add domino to  $P'$

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.
- ▶ For every  $a, b, c \in \Gamma$  and every  $q, q' \in Q$ ,  $q \neq q_r$ ,

- ▶ If  $\delta(q, a) = (q', b, R)$ , then add domino to  $P'$

$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$

- ▶ If  $\delta(q, a) = (q', b, L)$ , then add domino to  $P'$

$$\begin{bmatrix} cqa \\ q'cb \end{bmatrix}$$

# Proof of Undecidability of PCP

- ▶ Step 1: fix first domino in  $P'$

$$\begin{bmatrix} t_1 \\ b_1 \end{bmatrix} = \begin{bmatrix} \# \\ \#q_0w_1w_2\dots w_n\# \end{bmatrix}$$

- ▶ Step 2: Encode transitions of TM into dominos.

- ▶ For every  $a, b, c \in \Gamma$  and every  $q, q' \in Q$ ,  $q \neq q_r$ ,

- ▶ If  $\delta(q, a) = (q', b, R)$ , then add domino to  $P'$

$$\begin{bmatrix} qa \\ bq' \end{bmatrix}$$

- ▶ If  $\delta(q, a) = (q', b, L)$ , then add domino to  $P'$

$$\begin{bmatrix} cqa \\ q'cb \end{bmatrix}$$

- ▶ add all dominos (i.e, for all  $a \in \Gamma \cup \{\#\}$ ) to  $P'$ .

$$\begin{bmatrix} a \\ a \end{bmatrix} \quad \begin{bmatrix} \# \\ \sqcup\# \end{bmatrix}$$

# Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos

# Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
  - ▶ For every  $a \in \Gamma$ , we add all dominos to  $P'$

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

# Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
  - ▶ For every  $a \in \Gamma$ , we add all dominos to  $P'$

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

# Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
  - ▶ For every  $a \in \Gamma$ , we add all dominos to  $P'$

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

- ▶ Step 4: Complete the match

$$\begin{bmatrix} q_a \# \# \\ \# \end{bmatrix}$$



# Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
  - ▶ For every  $a \in \Gamma$ , we add all dominos to  $P'$

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

- ▶ Step 4: Complete the match

$$\begin{bmatrix} q_a \# \# \\ \# \end{bmatrix}$$

- ▶ This completes the reduction, i.e., map from instance of  $A_{TM}$  to PCP.
- ▶  $M$  accepts  $w$  if and only if  $P'$  gives a solution to PCP.

# Proof of Undecidability of PCP

- ▶ Step 3: Acceptance in to eating dominos
  - ▶ For every  $a \in \Gamma$ , we add all dominos to  $P'$

$$\begin{bmatrix} q_a a \\ q_a \end{bmatrix} \quad \begin{bmatrix} a q_a \\ q_a \end{bmatrix}$$

- ▶ Step 4: Complete the match

$$\begin{bmatrix} q_a \# \# \\ \# \end{bmatrix}$$

- ▶ This completes the reduction, i.e., map from instance of  $A_{TM}$  to PCP.
- ▶  $M$  accepts  $w$  if and only if  $P'$  gives a solution to PCP.
- ▶ MPCP to PCP?