

# 1 GeNN Documentation

GeNN is a software package to enable neuronal network simulations on NVIDIA GPUs by code generation. [Models](#) are defined in a simple C-style API and the code for running them on either GPU or CPU hardware is generated by GeNN. GeNN can also be used through external interfaces. Currently there are interfaces for [SpineML](#) and [SpineCreator](#), a [Python interface \(PyGeNN\)](#) and a [Brian](#) interface via [Brian2GeNN](#).

GeNN is currently developed and maintained by

[Dr James Knight](#) ([contact James](#))  
[James Turner](#) ([contact James](#))  
[Prof. Thomas Nowotny](#) ([contact Thomas](#))

Project homepage is <http://genn-team.github.io/genn/>.

The development of GeNN is partially supported by the EPSRC (grant numbers [EP/P006094/1 - Brains on Board](#) and [EP/J019690/1 - Green Brain Project](#)).

## Note

This documentation is under construction. If you cannot find what you are looking for, please contact the project developers.

[Next](#)

## 2 Installation

You can download GeNN either as a zip file of a stable release or a snapshot of the most recent stable version or the unstable development version using the Git version control system.

### 2.1 Downloading a release

Point your browser to <https://github.com/genn-team/genn/releases> and download a release from the list by clicking the relevant source code button. Note that GeNN is only distributed in the form of source code due to its code generation design. Binary distributions would not make sense in this framework and are not provided. After downloading continue to install GeNN as described in the [Installing GeNN](#) section below.

### 2.2 Obtaining a Git snapshot

If it is not yet installed on your system, download and install Git (<http://git-scm.com/>). Then clone the GeNN repository from Github

```
git clone https://github.com/genn-team/genn.git
```

The github url of GeNN in the command above can be copied from the HTTPS clone URL displayed on the GeNN Github page (<https://github.com/genn-team/genn>).

This will clone the entire repository, including all open branches. By default git will check out the master branch which contains the source version upon which the next release will be based. There are other branches in the repository that are used for specific development purposes and are opened and closed without warning.

As an alternative to using git you can also download the full content of GeNN sources clicking on the "Download ZIP" button on the bottom right of the GeNN Github page (<https://github.com/genn-team/genn>).

## 2.3 Installing GeNN

Installing GeNN comprises a few simple steps to create the GeNN development environment.

### Note

While GeNN models are normally simulated using CUDA on NVIDIA GPUs, if you want to use GeNN on a machine without an NVIDIA GPU, you can skip steps v and vi and use GeNN in "CPU\_ONLY" mode.

(i) If you have downloaded a zip file, unpack GeNN.zip in a convenient location. Otherwise enter the directory where you downloaded the Git repository.

(ii) Add GeNN's "bin" directory to your path, e.g. if you are running Linux or Mac OS X and extracted/downloaded GeNN to \$HOME/GeNN, then you can add:

```
export PATH=$PATH:$HOME/GeNN/bin
```

to your login script (e.g. `.profile` or `.bashrc`). If you are using WINDOWS, the path should be a windows path as it will be interpreted by the Visual C++ compiler `cl`, and environment variables are best set using `SETX` in a Windows cmd window. To do so, open a Windows cmd window by typing `cmd` in the search field of the start menu, followed by the `enter` key. In the `cmd` window type:

```
setx PATH "C:\Users\me\GeNN\bin;%PATH%"
```

where `C:\Users\me\GeNN` is the path to your GeNN directory.

(iv) Install the C++ compiler on the machine, if not already present. For Windows, download Microsoft Visual Studio Community Edition from <https://www.visualstudio.com/en-us/downloads/download-visual-studio-vs.aspx>. When installing Visual Studio, one should select the 'Desktop development with C++' configuration and the 'Windows 8.1 SDK' and 'Windows Universal CRT' individual components. Mac users should download and set up Xcode from <https://developer.apple.com/xcode/index.html>. Linux users should install the GNU compiler collection gcc and g++ from their Linux distribution repository, or alternatively from <https://gcc.gnu.org/index.html>. Be sure to pick CUDA and C++ compiler versions which are compatible with each other. The latest C++ compiler is not necessarily compatible with the latest CUDA toolkit.

(v) If your machine has a GPU and you haven't installed CUDA already, obtain a fresh installation of the NVIDIA CUDA toolkit from <https://developer.nvidia.com/cuda-downloads>. Again, be sure to pick CUDA and C++ compiler versions which are compatible with each other. The latest C++ compiler is not necessarily compatible with the latest CUDA toolkit.

(vi) Set the `CUDA_PATH` variable if it is not already set by the system, by putting

```
export CUDA_PATH=/usr/local/cuda
```

in your login script (or, if CUDA is installed in a non-standard location, the appropriate path to the main CUDA directory). For most people, this will be done by the CUDA install script and the default value of `/usr/local/cuda` is fine. In Windows, `CUDA_PATH` is normally already set after installing the CUDA toolkit. If not, set this variable with:

```
setx CUDA_PATH C:\path\to\cuda
```

This normally completes the installation. Windows users must close and reopen their command window to ensure variables set using `SETX` are initialised.

If you are using GeNN in Windows, the Visual Studio development environment must be set up within every instance of the `CMD.EXE` command window used. One can open an instance of `CMD.EXE` with the development environment already set up by navigating to Start - All Programs - Microsoft Visual Studio - Visual Studio Tools - x64 Native Tools Command Prompt. You may wish to create a shortcut for this tool on the desktop, for convenience.

[Top](#) | [Next](#)

## 3 Quickstart

GeNN is based on the idea of code generation for the involved GPU or CPU simulation code for neuronal network models but leaves a lot of freedom how to use the generated code in the final application. To facilitate the use of GeNN on the background of this philosophy, it comes with a number of complete examples containing both the model description code that is used by GeNN for code generation and the "user side code" to run the generated model and save the results. Some of the example models such as the [Insect olfaction model](#) use an `generate_run` executable which automates the building and simulation of the model. Using these executables, running these complete examples should be achievable in a few minutes. The necessary steps are described below.

### 3.1 Running an Example Model

#### 3.1.1 Unix

In order to build the `generate_run` executable as well as any additional tools required for the model, open a shell and navigate to the `userproject/MBody1_project` directory. Then type

```
make
```

to generate an executable that you can invoke with

```
./generate_run test1
```

or, if you don't have an NVIDIA GPU and are running GeNN in CPU\_ONLY mode, you can instead invoke this executable with

```
./generate_run --cpu-only test1
```

#### 3.1.2 Windows

While GeNN can be used from within Visual Studio, in this example we will use a `cmd` window. Open a Visual Studio `cmd` window via Start: All Programs: Visual Studio: Tools: x86 Native Tools Command Prompt, and navigate to the `userproject\tools` directory. Then compile the additional tools and the `generate_run` executable for creating and running the project:

```
msbuild ..\userprojects.sln /t:generate_mbody1_runner /p:Configuration=Release
```

to generate an executable that you can invoke with

```
generate_run test1
```

or, if you don't have an NVIDIA GPU and are running GeNN in CPU\_ONLY mode, you can instead invoke this executable with

```
generate_run --cpu-only test1
```

#### 3.1.3 Visualising results

These steps will build and simulate a model of the locust olfactory system with default parameters of 100 projection neurons, 1000 Kenyon cells, 20 lateral horn interneurons and 100 output neurons in the mushroom body lobes.

**Note**

If the model isn't build in CPU\_ONLY mode it will be simulated on an automatically chosen GPU.

The `generate_run` tool generates input patterns and writes them to file, compiles and runs the model using these files as inputs and finally output the resulting spiking activity. For more information of the options passed to this command see the [Insect olfaction model](#) section. The results of the simulation can be plotted with

```
python plot.py test1
```

The MBody1 example is already a highly integrated example that showcases many of the features of GeNN and how to program the user-side code for a GeNN application. More details in the [User Manual](#).

### 3.2 How to use GeNN for New Projects

Creating and running projects in GeNN involves a few steps ranging from defining the fundamentals of the model, inputs to the model, details of the model like specific connectivity matrices or initial values, running the model, and analyzing or saving the data.

GeNN code is generally created by passing the C++ model file (see [below](#)) directly to the `genn-buildmodel` script. Another way to use GeNN is to create or modify a script or executable such as `userproject/MBody1_↵project/generate_run.cc` that wraps around the other programs that are used for each of the steps listed above. In more detail, the GeNN workflow consists of:

1. Either use external programs to generate connectivity and input files to be loaded into the user side code at runtime or generate these matrices directly inside the user side code.
2. Generating the model simulation code using `genn-buildmodel.sh` (On Linux or Mac) or `genn-buildmodel.bat` (on Windows). For example, inside the `generate_run` engine used by the MBody1\_project, the following command is executed on Linux:

```
genn-buildmodel.sh MBody1.cc
```

or, if you don't have an NVIDIA GPU and are running GeNN in CPU\_ONLY mode, the following command is executed:

```
genn-buildmodel.sh -c MBody1.cc
```

The `genn-buildmodel` script compiles the GeNN code generator in conjunction with the user-provided model description `model/MBody1.cc`. It then executes the GeNN code generator to generate the complete model simulation code for the model.

3. Provide a build script to compile the generated model simulation and the user side code into a simulator executable (in the case of the MBody1 example this consists the file `MBody1Sim.cc`). On Linux or Mac a suitable GNU makefile can be created by running:

```
genn-create-user-project.sh MBody1 MBody1Sim.cc
```

And on Windows an MSBuild project can be created by running:

```
genn-create-user-project.bat MBody1 MBody1Sim.cc
```

4. Compile the simulator executable by invoking GNU make on Linux or Mac:

```
make clean all
```

or MSbuild on Windows:

```
msbuild MBody1.sln /t:MBody1 /p:Configuration=Release
```

5. Finally, run the resulting stand-alone simulator executable. In the MBody1 example, this is called `MBody1` on Linux and `MBody1_Release.exe` on Windows.

### 3.3 Defining a New Model in GeNN

According to the work flow outlined above, there are several steps to be completed to define a neuronal network model.

1. The neuronal network of interest is defined in a model definition file, e.g. `Example1.cc`.
2. Within the the model definition file `Example1.cc`, the following tasks need to be completed:
  - a) The GeNN file `modelSpec.h` needs to be included,

```
#include "modelSpec.h"
```

- b) The values for initial variables and parameters for neuron and synapse populations need to be defined, e.g.

```
NeuronModels::PoissonNew::ParamValues poissonParams(  
    10.0); // 0 - firing rate
```

would define the (homogeneous) parameters for a population of Poisson neurons.

#### Note

The number of required parameters and their meaning is defined by the neuron or synapse type. Refer to the [User Manual](#) for details. We recommend, however, to use comments like in the above example to achieve maximal clarity of each parameter's meaning.

If heterogeneous parameter values are required for a particular population of neurons (or synapses), they need to be defined as "variables" rather than parameters. See the [User Manual](#) for how to define new neuron (or synapse) types and the [Defining a new variable initialisation snippet](#) section for more information on initialising these variables to hetererogenous values.

- c) The actual network needs to be defined in the form of a function `modelDefinition`, i.e.

```
void modelDefinition(ModelSpec &model);
```

#### Note

The name `modelDefinition` and its parameter of type `ModelSpec&` are fixed and cannot be changed if GeNN is to recognize it as a model definition.

- d) Inside `modelDefinition()`, The time step `DT` needs to be defined, e.g.

```
model.setDT(0.1);
```

#### Note

All provided examples and pre-defined model elements in GeNN work with units of mV, ms, nF and muS. However, the choice of units is entirely left to the user if custom model elements are used.

`MBody1.cc` shows a typical example of a model definition function. In its core it contains calls to [ModelSpec::addNeuronPopulation](#) and [ModelSpec::addSynapsePopulation](#) to build up the network. For a full range of options for defining a network, refer to the [User Manual](#).

3. The programmer defines their own "user-side" modeling code similar to the code in `userproject/MBody1_project/model/MBody1Sim.cc`. In this code,
  - a) They manually define the connectivity matrices between neuron groups. Refer to the [Synaptic matrix types](#) section for the required format of connectivity matrices for dense or sparse connectivities.
  - b) They define input patterns (e.g. for Poisson neurons like in the `MBody1` example) or individual initial values for neuron and / or synapse variables.

**Note**

The initial values given in the `modelDefinition` are automatically applied homogeneously to every individual neuron or synapse in each of the neuron or synapse groups.

- c) They use `stepTime()` to run one time step on either the CPU or GPU depending on the options passed to `genn-buildmodel`.
- d) They use functions like `copyStateFromDevice()` etc to transfer the results from GPU calculations to the main memory of the host computer for further processing.
- e) They analyze the results. In the most simple case this could just be writing the relevant data to output files.

[Previous](#) | [Top](#) | [Next](#)

## 4 Examples

GeNN comes with a number of complete examples. At the moment, there are seven such example projects provided with GeNN.

### 4.1 Single compartment Izhikevich neuron(s)

Izhikevich neuron(s) without any connections  
=====

This is a minimal example, with only one neuron population (with more or less neurons depending on the command line, but without any synapses). The neurons are Izhikevich neurons with homogeneous parameters across the neuron population. This example project contains a helper executable called "generate\_run", which compiles and executes the model.

To compile it, navigate to `genn/userproject/OneComp_project` and type:

```
msbuild ..\userprojects.sln /t:generate_one_comp_runner /p:Configuration=Release
```

for Windows users, or:

```
make
```

for Linux, Mac and other UNIX users.

USAGE

-----

```
generate_run [OPTIONS] <outname>
```

Mandatory arguments:

`outname`: The base name of the output location and output files

Optional arguments:

`--debug`: Builds a debug version of the simulation and attaches the debugger

`--cpu-only`: Uses CPU rather than CUDA backend for GeNN

`--timing`: Uses GeNN's timing mechanism to measure performance and displays it at the end of the simulation

`--ftype`: Sets the floating point precision of the model to either float or double (defaults to float)

`--gpu-device`: Sets which GPU device to use for the simulation (defaults to -1 which picks automatically)

`--num-neurons`: Number of neurons to simulate (defaults to 1)

For a first minimal test, using these defaults and recording results with a base name of 'test', the system may

```
generate_run.exe test
```

for Windows users, or:

```
./generate_run test
```

for Linux, Mac and other UNIX users.

This would create a set of tonic spiking Izhikevich neurons with no connectivity, receiving a constant identical 4 nA input.

Another example of an invocation that runs the simulation using the CPU rather than GPU, records timing information and 4 neurons would be:

```
generate_run.exe --cpu-only --timing --num_neurons=4 test
```

for Windows users, or:

```
./generate_run --cpu-only --timing --num_neurons=4 test
```

for Linux, Mac and other UNIX users.

Izhikevich neuron model: [\[1\]](#)

## 4.2 Izhikevich neurons driven by Poisson input spike trains:

Izhikevich network receiving Poisson input spike trains  
=====

In this example project there is again a pool of non-connected Izhikevich model neurons that are connected to a pool of Poisson input neurons with a fixed probability. This example project contains a helper executable called "generate\_run", which compiles and executes the model.

To compile it, navigate to genn/userproject/PoissonIzh\_project and type:

```
msbuild ..\userprojects.sln /t:generate_poisson_izh_runner /p:Configuration=Release
```

for Windows users, or:

```
make
```

for Linux, Mac and other UNIX users.

USAGE

-----

```
generate_run [OPTIONS] <outname>
```

Mandatory arguments:

outname: The base name of the output location and output files

Optional arguments:

--debug: Builds a debug version of the simulation and attaches the debugger

--cpu-only: Uses CPU rather than CUDA backend for GeNN

--timing: Uses GeNN's timing mechanism to measure performance and displays it at the end of the simulation

--ftype: Sets the floating point precision of the model to either float or double (defaults to float)

--gpu-device: Sets which GPU device to use for the simulation (defaults to -1 which picks automatically)

--num-poisson: Number of Poisson sources to simulate (defaults to 100)

--num-izh: Number of Izhikievich neurons to simulate (defaults to 10)

--pconn: Probability of connection between each pair of poisson sources and neurons (defaults to 0.5)

--gscale: Scaling of synaptic conductances (defaults to 2)

--sparse: Use sparse rather than dense data structure to represent connectivity

An example invocation of generate\_run using these defaults and recording results with a base name of 'test':

```
generate_run.exe test
```

for Windows users, or:

```
./generate_run test
```

for Linux, Mac and other UNIX users.

This will generate a network of 100 Poisson neurons with 20 Hz firing rate connected to 10 Izhikevich neurons with a 0.5 probability.

The same network with sparse connectivity can be used by adding the `--sparse` flag to the command line.

Another example of an invocation that runs the simulation using the CPU rather than GPU, records timing information and uses sparse connectivity would be:

```
generate_run.exe --cpu-only --timing --sparse test
```

for Windows users, or:

```
./generate_run --cpu-only --timing --sparse test
```

for Linux, Mac and other UNIX users.

Izhikevich neuron model: [\[1\]](#)

### 4.3 Pulse-coupled Izhikevich network

Pulse-coupled Izhikevich network  
=====

This example model is inspired by simple thalamo-cortical network of Izhikevich with an excitatory and an inhibitory population of spiking neurons that are randomly connected. It creates a pulse-coupled network with 80% excitatory 20% inhibitory connections, each connecting to a fixed number of neurons with sparse connectivity.

To compile it, navigate to `genn/userproject/Izh_sparse_project` and type:

```
msbuild ..\userprojects.sln /t:generate_izh_sparse_runner /p:Configuration=Release
```

for Windows users, or:

```
make
```

for Linux, Mac and other UNIX users.

USAGE  
-----

```
generate_run [OPTIONS] <outname>
```

Mandatory arguments:

outname: The base name of the output location and output files

Optional arguments:

--debug: Builds a debug version of the simulation and attaches the debugger

--cpu-only: Uses CPU rather than CUDA backend for GeNN

--timing: Uses GeNN's timing mechanism to measure performance and displays it at the end of the simulation

--ftype: Sets the floating point precision of the model to either float or double (defaults to float)

--gpu-device: Sets which GPU device to use for the simulation (defaults to -1 which picks automatically)

--num-neurons: Number of neurons (defaults to 10000)

--num-connections: Number of connections per neuron (defaults to 1000)

--gscale: General scaling of synaptic conductances (defaults to 1.0)

An example invocation of `generate_run` using these defaults and recording results with a base name of `'test'` would be:

```
generate_run.exe test
```

for Windows users, or:

```
./generate_run test
```

for Linux, Mac and other UNIX users.

This would create a pulse coupled network of 8000 excitatory 2000 inhibitory Izhikevich neurons, each making 1000 connections with other neurons, generating



a mixed alpha and gamma regime. For larger input factor, there is more input current and more irregular activity, for smaller factors less and less and more sparse activity. The synapses are of a simple pulse-coupling type. The results of the simulation are saved in the directory 'outdir\_output'.

Another example of an invocation that runs the simulation using the CPU rather than GPU, records timing information and doubles the number of neurons would be:

```
generate_run.exe --cpu-only --timing --num_neurons=20000 test
```

for Windows users, or:

```
./generate_run --cpu-only --timing --num_neurons=20000 test
```

for Linux, Mac and other UNIX users.

Izhikevich neuron model: [\[1\]](#)

## 4.4 Izhikevich network with delayed synapses

Izhikevich network with delayed synapses

=====

This example project demonstrates the synaptic delay feature of GeNN. It creates a network of three Izhikevich neuron groups, connected all-to-all with fast, medium and slow synapse groups. Neurons in the output group only spike if they are simultaneously innervated by the input neurons, via slow synapses, and the interneurons, via faster synapses.

COMPILE (WINDOWS)

-----

To run this example project, first build the model into CUDA code by typing:

```
genn-buildmodel.bat SynDelay.cc
```

then compile the project by typing:

```
msbuild SynDelay.sln /t:SynDelay /p:Configuration=Release
```

COMPILE (MAC AND LINUX)

-----

To run this example project, first build the model into CUDA code by typing:

```
genn-buildmodel.sh SynDelay.cc
```

then compile the project by typing:

```
make
```

USAGE

-----

```
syn_delay [directory to save output]
```

Izhikevich neuron model: [\[1\]](#)

## 4.5 Insect olfaction model

Locust olfactory system (Nowotny et al. 2005)

=====

This project implements the insect olfaction model by Nowotny et al. that demonstrates self-organized clustering of odours in a simulation of the insect antennal lobe and mushroom body. As provided the model works with conductance based Hodgkin-Huxley neurons and several different synapse types, conductance based (but pulse-coupled) excitatory synapses, graded inhibitory synapses and synapses with a simplified STDP rule. This example project contains a helper executable called "generate\_run", which prepares input pattern data, before compiling and executing the model.

To compile it, navigate to `genn/userproject/MBody1_project` and type:

```
msbuild ..\userprojects.sln /t:generate_mbody1_runner /p:Configuration=Release
```

for Windows users, or:

```
make
```

for Linux, Mac and other UNIX users.

#### USAGE

-----

```
generate_run [OPTIONS] <outname>
```

##### Mandatory arguments:

outname: The base name of the output location and output files

##### Optional arguments:

--debug: Builds a debug version of the simulation and attaches the debugger

--cpu-only: Uses CPU rather than CUDA backend for GeNN

--timing: Uses GeNN's timing mechanism to measure performance and displays it at the end of the simulation

--ftype: Sets the floating point precision of the model to either float or double (defaults to float)

--gpu-device: Sets which GPU device to use for the simulation (defaults to -1 which picks automatically)

--num-al: Number of neurons in the antennal lobe (AL), the input neurons to this model (defaults to 100)

--num-kc: Number of Kenyon cells (KC) in the "hidden layer" (defaults to 1000)

--num-lhi: Number of lateral horn interneurons, implementing gain control (defaults to 20)

--num-dn: Number of decision neurons (DN) in the output layer (defaults to 100)

--gscale: A general rescaling factor for synaptic strength (defaults to 0.0025)

--bitmask: Use bitmasks to represent sparse PN->KC connectivity rather than dense connectivity

--delayed-synapses: Rather than use constant delays of DT throughout, use delays of (5 \* DT) ms on KC->DN and

An example invocation of `generate_run` using these defaults and recording results with a base name of 'test' would be:

```
generate_run.exe test
```

for Windows users, or:

```
./generate_run test
```

for Linux, Mac and other UNIX users.

Such a command would generate a locust olfaction model with 100 antennal lobe neurons, 1000 mushroom body Kenyon cells, 20 lateral horn interneurons and 100 mushroom body output neurons, and launch a simulation of it on a CUDA-enabled GPU using single precision floating point numbers. All output files will be prefixed with "test" and will be created under the "test" directory. The model that is run is defined in 'model/MBody1.cc', debugging is switched off and the model would be simulated using float (single precision floating point) variables.

In more details, what `generate_run` program does is:

a) use another tools to generate input patterns.

b) build the source code for the model by writing neuron numbers into `./model/sizes.h`, and executing `"genn-buildmodel.sh ./model/MBody1.cc"`.

c) compile the generated code by invoking `"make clean && make"` running the code, e.g. `"./classol_sim rl"`.

Another example of an invocation that runs the simulation using the CPU rather than GPU, records timing information and uses bitmask connectivity would be:

```
generate_run.exe --cpu-only --timing --bitmask test
```

for Windows users, or:

```
./generate_run --cpu-only --timing --bitmask test
```

for Linux, Mac and other UNIX users.

As provided, the model outputs 'test.dn.st', 'test.kc.st', 'test.lhi.st' and 'test.pn.st' files which contain the spiking activity observed in each population in the simulation. There are two columns in this ASCII file, the first one containing the time of a spike and the second one the ID of the neuron that spiked. Users of matlab can use the scripts in the 'matlab' directory to plot the results of a simulation and users of python can use the plot\_spikes.py script in userproject/python. For more about the model itself and the scientific insights gained from it see Nowotny et al. referenced below

#### MODEL INFORMATION -----

For information regarding the locust olfaction model implemented in this example project, see:

T. Nowotny, R. Huerta, H. D. I. Abarbanel, and M. I. Rabinovich Self-organization in the olfactory system: One shot odor recognition in insects, Biol Cyber, 93 (6): 436-446 (2005), doi:10.1007/s00422-005-0019-7

Nowotny insect olfaction model: [4]; Traub-Miles Hodgkin-Huxley neuron model: [7]

## 4.6 Voltage clamp simulation to estimate Hodgkin-Huxley parameters

Genetic algorithm for tracking parameters in a HH model cell  
=====

This example simulates a population of Hodgkin-Huxley neuron models using GeNN and evolves them with a simple guided random search (simple GA) to mimic the dynamics of a separate Hodgkin-Huxley neuron that is simulated on the CPU. The parameters of the CPU simulated "true cell" are drifting according to a user-chosen protocol: Either one of the parameters gNa, ENa, gKd, EKd, gleak, Eleak, Cmem are modified by a sinusoidal addition (voltage parameters) or factor (conductance or capacitance) protocol 0-6. For protocol 7 all 7 parameters undergo a random walk concurrently.

To compile it, navigate to genn/userproject/HHVclampGA\_project and type:

```
msbuild ..\userprojects.sln /t:generate_hhvclamp_runner /p:Configuration=Release
```

for Windows users, or:s

```
make
```

for Linux, Mac and other UNIX users.

#### USAGE -----

```
generate_run [OPTIONS] <outname>
```

Mandatory arguments:

outname: The base name of the output location and output files

Optional arguments:

--debug: Builds a debug version of the simulation and attaches the debugger

--cpu-only: Uses CPU rather than CUDA backend for GeNN

--timing: Uses GeNN's timing mechanism to measure performance and displays it at the end of the simulation

--ftype: Sets the floating point precision of the model to either float or double (defaults to float)

--gpu-device: Sets which GPU device to use for the simulation (defaults to -1 which picks automatically)

--protocol: Which changes to apply during the run to the parameters of the "true cell" (defaults to -1 which means all)

--num-pops: Number of neurons in the tracking population (defaults to 5000)

--total-time: Time in ms how long to run the simulation (defaults to 1000 ms)

An example invocation of `generate_run` is:

```
generate_run.exe test1
```

for Windows users, or:

```
./generate_run test1
```

for Linux, Mac and other UNIX users.

This will simulate 5000 Hodgkin-Huxley neurons on the GPU which will, for 1000 ms, be matched to a Hodgkin-Huxley neuron. The output files will be written into a directory of the name `test1_output`, which will be created if it does not yet exist.

Another example of an invocation that records timing information for the the simulation and runs it for 10000

```
generate_run.exe --timing --total-time 10000
```

for Windows users, or:

```
./generate_run --timing --total-time 10000
```

for Linux, Mac and other UNIX users.

Traub-Miles Hodgkin-Huxley neuron model: [\[7\]](#)

## 4.7 A neuromorphic network for generic multivariate data classification

Author: Alan Diamond, University of Sussex, 2014

This project recreates using GeNN the spiking classifier design used in the paper

"A neuromorphic network for generic multivariate data classification"

Authors: Michael Schmuker, Thomas Pfeil, Martin Paul Nawrota

The classifier design is based on an abstraction of the insect olfactory system.

This example uses the IRIS stadard data set as a test for the classifier

BUILD / RUN INSTRUCTIONS

Install GeNN from the internet released build, following instruction on setting your PATH etc

Start a terminal session

cd to this project directory (userproject/Model\_Schmuker\_2014\_project)

To build the model using the GeNN meta compiler type:

```
genn-buildmodel.sh Model_Schmuker_2014_classifier.cc
```

for Linux, Mac and other UNIX systems, or:

```
genn-buildmodel.bat Model_Schmuker_2014_classifier.cc
```

for Windows systems (add `-d` for a debug build).

You should only have to do this at the start, or when you change your actual network model (i.e. editing the

Then to compile the experiment plus the GeNN created C/CUDA code type:-

```
make
```

for Linux, Mac and other UNIX users (add `DEBUG=1` if using debug mode), or:

```
msbuild Schmuker2014_classifier.vcxproj /p:Configuration=Release
```

for Windows users (change Release to Debug if using debug mode).

Once it compiles you should be able to run the classifier against the included Iris dataset.

type

```
./experiment .
```

for Linux, Mac and other UNIX systems, or:

```
Schmuker2014_classifier .
```

for Windows systems.

This is how it works roughly.

The experiment (experiment.cu) controls the experiment at a high level. It mostly does this by instructing the

So the experiment first tells the classifier to set up the GPU with the model and synapse data.

Then it chooses the training and test set data.

It runs through the training set , with plasticity ON , telling the classifier to run with the specified observ

Then it runs through the test set with plasticity OFF and collects the results in various reporting files.

At the highest level it also has a loop where you can cycle through a list of parameter values e.g. some thresh


You should also note there is no option currently to run on CPU, this is not due to the demanding task, it jus

[Previous](#) | [Top](#) | [Next](#)

## 5 SpineML and SpineCreator

GeNN now supports simulating models built using [SpineML](#) and includes scripts to fully integrate it with the [SpineCreator](#) graphical editor on Linux, Mac and Windows. After installing GeNN using the instructions in [Installation](#), [build SpineCreator for your platform](#).


From SpineCreator, select Edit->Settings->Simulators and add a new simulator using the following settings (replacing "/home/j/jk/jk421/genn" with the GeNN installation directory on your own system):



If you would like SpineCreator to use GeNN in CPU only mode, add an environment variable called "GENN\_SPI↵NEML\_CPU\_ONLY".

The best way to get started using SpineML with GeNN is to experiment with some example models. A number are available [here](#) although the "Striatum model" uses features not currently supported by GeNN and the two "Brette

Benchmark" models use a legacy syntax no longer supported by SpineCreator (or GeNN). Once you have loaded a model, click "Expts" from the menu on the left hand side of SpineCreator, choose the experiment you would like to run and then select your newly created GeNN simulator in the "Setup Simulator" panel:



Now click "Run experiment" and, after a short time, the results of your GeNN simulation will be available for plotting by clicking the "Graphs" option in the menu on the left hand side of SpineCreator.

[Previous](#) | [Top](#) | [Next](#)

## 6 Brian interface (Brian2GeNN)

GeNN can simulate models written for the [Brian simulator](#) via the [Brian2GeNN](#) interface [6]. In order for Brian2GeNN to find GeNN, GeNN must either be in your path with the location of the CUDA libraries configured via the `CUDA_PATH` environment variable (as described in [Installation](#)) or the `devices.genn.path` and `devices.genn.cuda_backend.cuda_path` [Brian preferences](#) should be set.

To use GeNN to simulate a Brian script, import the `brian2genn` package and switch Brian to the `genn` device. As an example, the following Python script will simulate Leaky-integrate-and-fire neurons with varying input currents to construct an f/I curve:

```
from brian2 import *
import brian2genn
set_device('genn')

n = 1000
duration = 1*second
tau = 10*ms
eqs = '''
dv/dt = (v0 - v) / tau : volt (unless refractory)
v0 : volt
'''
group = NeuronGroup(n, eqs, threshold='v > 10*mV', reset='v = 0*mV',
                    refractory=5*ms, method='exact')
group.v = 0*mV
group.v0 = '20*mV * i / (n-1)'
monitor = SpikeMonitor(group)

run(duration)
```

Of course, your simulation should be more complex than the example above to actually benefit from the performance gains of using a GPU via GeNN.

[Previous](#) | [Top](#) | [Next](#)

## 7 Python interface (PyGeNN)

As well as being able to build GeNN models and user code directly from C++, you can also access all Ge↔NN features from Python. The `pygenn.genn_model.GeNNModel` class provides a thin wrapper around `ModelSpec` as well as providing support for loading and running simulations; and accessing their state. `SynapseGroup`, `NeuronGroup` and `CurrentSource` are similarly wrapped by the `pygenn.genn↔_groups.SynapseGroup`, `pygenn.genn_groups.NeuronGroup` and `pygenn.genn_groups.↔CurrentSource` classes respectively.

PyGeNN can be built from source on Windows, Mac and Linux following the instructions in the README file in the `pygenn` directory of the GeNN repository. However, if you have a relatively recent version of Python and CUDA,

we recommend that you instead downloading a suitable 'wheel' from our releases page (all wheels are build for CUDA 10 except for on Mac OS which is built for CUDA 9). These can then be installed using e.g. `pip install pygenn-0.2.1-cp27-cp27mu-linux_x86_64.whl` for a Linux system with Python 2.7. On Windows we recommend using the Python 3 version of [Anaconda](#).

The following example shows how PyGeNN can be easily interfaced with standard Python packages such as numpy and matplotlib to plot 4 different Izhikevich neuron regimes:

```
import numpy as np
import matplotlib.pyplot as plt
from pygenn.genn_model import GeNNModel

# Create a single-precision GeNN model
model = GeNNModel("float", "pygenn")

# Set simulation timestep to 0.1ms
model.dT = 0.1

# Initialise IzhikevichVariable parameters - arrays will be automatically uploaded
izk_init = {"V": -65.0,
            "U": -20.0,
            "a": [0.02, 0.1, 0.02, 0.02],
            "b": [0.2, 0.2, 0.2, 0.2],
            "c": [-65.0, -65.0, -50.0, -55.0],
            "d": [8.0, 2.0, 2.0, 4.0]}

# Add neuron populations and current source to model
pop = model.add_neuron_population("Neurons", 4, "IzhikevichVariable", {}, izk_init)
model.add_current_source("CurrentSource", "DC", "Neurons", {"amp": 10.0}, {})

# Build and load model
model.build()
model.load()

# Create a numpy view to efficiently access the membrane voltage from Python
voltage_view = pop.vars["V"].view

# Simulate
v = None
while model.t < 200.0:
    model.step_time()
    model.pull_state_from_device("Neurons")
    v = np.copy(voltage_view) if v is None else np.vstack((v, voltage_view))

# Create plot
figure, axes = plt.subplots(4, sharex=True)

# Plot voltages
for i, t in enumerate(["RS", "FS", "CH", "IB"]):
    axes[i].set_title(t)
    axes[i].set_ylabel("V [mV]")
    axes[i].plot(np.arange(0.0, 200.0, 0.1), v[:,i])

axes[-1].set_xlabel("Time [ms]")

# Show plot
plt.show()
```

[Previous](#) | [Top](#) | [Next](#)

## 8 Release Notes

### Release Notes for GeNN v4.2.1 (PyGeNN 0.3.1)

This release fixes several small issues including several relating to Brian2GeNN compatibility.

#### User Side Changes

1. Added `-s` option to `genn-buildmodel.bat` on Windows to turn off Visual C++ additional security checks (SDL), allowing Brian2GeNN libraries to be included in code generator.

**Bug fixes:**

1. Fixed bug where \$(sT\_pre) and \$(sT\_post) were incorrect when accessed in weight update model pre and postsynaptic spike code respectively when using the single-threaded CPU backend.
2. Fixed a corner case where valid models might result in compiler errors about `Isyn` not being defined.
3. Fixed a bug preventing multiple include paths being passed to `genn-buildmodel.bat` on Windows.

**Release Notes for GeNN v4.2.0 (PyGeNN 0.3)**

This release adds a number of new features to GeNN and its Python interface as well as fixing a number of bugs that have been identified since the 4.1.0 release.

**User Side Changes**

1. Kernel timings can now be enabled from python with `pygenn.genn_model.GeNNModel.timing_enabled` and subsequently accessed with `pygenn.genn_model.GeNNModel.neuron_update_time`, `pygenn.genn_model.GeNNModel.init_time`, `pygenn.genn_model.GeNNModel.presynaptic_update_time`, `pygenn.genn_model.GeNNModel.postsynaptic_update_time`, `pygenn.genn_model.GeNNModel.synapse_dynamics_time` and `pygenn.genn_model.GeNNModel.init_sparse_time`.
2. Backends now generate `getFreeDeviceMemBytes()` function to allow free device memory to be queried from user simulation code. This is also exposed to Python via `GeNNModel.free_device_mem_bytes` property.
3. GeNN preferences are now fully exposed to PyGeNN by passing kwargs to `pygenn.genn_model.GeNNModel.__init__`.
4. **Logging** level can now be separately specified for GeNN, the code generator, the SpineML generator and the backend and is accessible from PyGeNN.
5. `CodeGenerator::PreferencesBase::enableBitmaskOptimisations` flag enables an alternative algorithm for updating synaptic matrices implemented with `SynapseMatrixConnectivity::BITMASK` which performs better on smaller GPUs and CPUs. If you are manually initialising matrices this adds padding to align words to rows of the matrix.
6. `SynapseMatrixConnectivity::PROCEDURAL` and `SynapseMatrixWeight::PROCEDURAL` allow connectivity and synaptic weights to be generated on the fly rather than stored in memory.
7. `CodeGenerator::PreferencesBase::automaticCopy` flag allows models to be built without the need for explicitly copying data between host and device. For CUDA backend this uses unified memory (<https://devblogs.nvidia.com/unified-memory-cuda-beginners/>).
8. Speed of code compilation can be improved by building using multiple threads. This is now done everywhere where `make` or `MSBuild` is invoked automatically.

**Bug fixes:**

1. Fixed several bugs in extra global parameter implementation in PyGeNN.
2. Floating point min and max should be calculated with `fmax` and `fmin` in code snippets - fixed in several models and user projects.
3. Fixed issues with version of numpy required in PyGeNN (previously held back by an issue with PyNN)



## Release Notes for GeNN v4.1.0

This release adds a number of new features to GeNN and its SpineML interface as well as fixing a number of bugs that have been identified since the 4.0.2 release.

### User Side Changes

1. The SpineML simulator could previously only be used as a standalone application. This functionality is now provided by the `spineml_simulator` library and can be used via the `SpineMLSimulator::Simulator` class.
2. When declaring a model's variables using `SET_VAR`, they can be marked as read-only by adding a 3rd parameter set to `VarAccess::READ_ONLY` to enable further optimisations. See [Defining your own neuron type](#) for more details.
3. Previously, unless models were very large or had very high spike rates, using `SynapseGroup::SpanType::PRESYNAPTIC` typically resulted in poor performance. When using the CUDA backend, `SynapseGroup::setNumThreadsPerSpike` can now be used to increase parallelism.
4. There were useful helpers for recording spikes (`SpikeRecorder`) and timing (`Timer`, `TimerAccumulate`) in "userproject\include" which were not easily usable to user projects. `genn-create-userproject.sh` and `genn-create-userproject.bat` now have a "-u" option which puts this in the include path of the generated project.
5. Timing information generated when `ModelSpec::setTiming` is enabled was not accesible to SpineML models. This is now exposed through the `SpineMLSimulator::Simulator` class.
6. Neuron population state variables were not easily accessible if the populations had incoming or outgoing connections with synaptic delays. Additional helper functions are now generated. See [Creating and simulating a network model](#) for more details.
7. SpineML interface will now use heterogeneous dendritic delay system introduced in GeNN 3.2.0 if required.
8. Add `CodeGenerator::CUDA::Preferences::generateLineInfo` option to output CUDA line info for profiling.
9. CUDA backend supports `half` datatype allowing memory savings through reduced precision. Host C++ code does not support half-precision types so such state variables must have their location set to `VarLocation::DEVICE`.
10. If `ModelSpec::setDefaultNarrowSparseIndEnabled` is set on a model or `SynapseGroup::setNarrowSparseIndEnabled` is set on an individual synapse population with sparse connectivity, 16-bit numbers will be used for postsynaptic indices, almost halving memory requirements.
11. Manual selection of CUDA devices is now exposed to PyGeNN via the `pygenn.genn_model.GeNNModel.selected_gpu` property.

### Bug fixes:

1. Fixed incompatibilities with GCC 4.9
2. Fixed bug that occurred if derived parameters were used in spike-like-event threshold conditions.
3. Fixed bug that occurred when merging of postsynaptic models is enabled and GeNN decides to employ specific CUDA optimizations.
4. Increase maximum supported CUDA kernel grid size - a bug was limiting this to 65536.
5. Fixed bugs in timing system when used with synapse dynamics kernels.

## Release Notes for GeNN v4.0.2

This release fixes several small issues with the generation of binary wheels for Python:

### Bug fixes:

1. There was a conflict between the versions of numpy used to build the wheels and the version required for the PyGeNN packages
2. Wheels were renamed to include the CUDA version which broke them.

## Release Notes for GeNN v4.0.1

This release fixes several small bugs found in GeNN 4.0.0 and implements some small features:

### User Side Changes

1. Improved detection and handling of errors when specifying model parameters and values in PyGeNN.
2. SpineML simulator is now implemented as a library which can be used directly from user applications as well as from command line tool.

### Bug fixes:

1. Fixed typo in `pygenn.genn_model.GeNNModel.push_var_to_device` function in PyGeNN.
2. Fixed broken support for Visual C++ 2013.
3. Fixed zero-copy mode.
4. Fixed typo in tutorial 2.

## Release Notes for GeNN v4.0.0

This release is the result of a second round of fairly major refactoring which we hope will make GeNN easier to use and allow it to be extended more easily in future. However, especially if you have been using GeNN 2.XX syntax, it breaks backward compatibility.

### User Side Changes

1. Totally new build system - `make install` can be used to install GeNN to a system location on Linux and Mac and Windows projects work much better in the Visual Studio IDE.
2. Python interface now supports Windows and can be installed using binary 'wheels' (see [Python interface \(PyGeNN\)](#) for more details).
3. No need to call `initGeNN()` at start and `model.finalize()` at end of all models.
4. Initialisation system simplified - if you specify a value or initialiser for a variable or sparse connectivity, it will be initialised by your chosen backend. If you mark it as uninitialised, it is up to you to initialize it in user code between the calls to `initialize()` and `initializeSparse()` (where it will be copied to device).
5. `genn-create-user-project` helper scripts to create Makefiles or MSBuild projects for building user code
6. State variables can now be pushed and pulled individually using the `pull<var name><neuron or synapse name>FromDevice()` and `push<var name><neuron or synapse name>ToDevice()` functions.

7. Management of extra global parameter arrays has been somewhat automated (see [Extra Global Parameters](#) for more details).
8. `GENN_PREFERENCES` is no longer a namespace - it's a global struct so members need to be accessed with `.` rather than `::`.
9. [NeuronGroup](#), [SynapseGroup](#), [CurrentSource](#) and `NNmodel` all previously exposed a lot of methods that the user wasn't *supposed* to call but could. These have now all been made protected and are exposed to GeNN internals using derived classes ([NeuronGroupInternal](#), [SynapseGroupInternal](#), [CurrentSourceInternal](#), [ModelSpecInternal](#)) that make them public using `using` directives.
10. Auto-refractory behaviour was controlled using `GENN_PREFERENCES::autoRefractory`, this is now controlled on a per-neuron-model basis using the `SET_NEEDS_AUTO_REFRACTORY` macro.
11. The functions used for pushing and pulling have been unified somewhat this means that `copyStateToDevice` and `copyStateFromDevice` functions no longer copy spikes and `push<neuron or synapse name>SpikesToDevice` and `pull<neuron or synapse name>SpikesFromDevice` no longer copy spike times or spike-like events.
12. Standard models of leaky-integrate-and-fire neuron ([NeuronModels::LIF](#)) and of exponentially shaped postsynaptic current ([PostsynapticModels::ExpCurr](#)) have been added.
13. When a model is built using the CUDA backend, the device it was built for is stored using its PCI bus ID so it will always use the same device.

#### Deprecations

1. Yale-format sparse matrices are no longer supported.
2. GeNN 2.X syntax for implementing neuron and synapse models is no longer supported.
3. `$(addToInSyn) = X; $(updateInSyn);` idiom in weight update models has been replaced by function style `$(addToInSyn, X);`.

### Release Notes for GeNN v3.3.0

This release is intended as the last service release for GeNN 3.X.X. Fixes for serious bugs **may** be backported if requested but, otherwise, development will be switching to GeNN 4.

#### User Side Changes

1. Postsynaptic models can now have Extra Global Parameters.
2. Gamma distribution can now be sampled using `$(gennrand_gamma, a)`. This can be used to initialise variables using [InitVarSnippet::Gamma](#).
3. Experimental Python interface - All features of GeNN are now exposed to Python through the [pygenn](#) module (see [Python interface \(PyGeNN\)](#) for more details).

#### Bug fixes:

1. Devices with Streaming Multiprocessor version 2.1 (compute capability 2.0) now work correctly in Windows.
2. Seeding of on-device RNGs now works correctly.
3. Improvements to accuracy of memory usage estimates provided by code generator.

## Release Notes for GeNN v3.2.0

This release extends the initialisation system introduced in 3.1.0 to support the initialisation of sparse synaptic connectivity, adds support for networks with more sophisticated models of synaptic plasticity and delay as well as including several other small features, optimisations and bug fixes for certain system configurations. This release supports GCC  $\geq$  4.9.1 on Linux, Visual Studio  $\geq$  2013 on Windows and recent versions of Clang on Mac OS X.

### User Side Changes

1. Sparse synaptic connectivity can now be initialised using small *snippets* of code run either on GPU or CPU. This can save significant amounts of initialisation time for large models. See [Sparse connectivity initialisation](#) for more details.
2. New 'ragged matrix' data structure for representing sparse synaptic connections – supports initialisation using new sparse synaptic connectivity initialisation system and enables future optimisations. See [Synaptic matrix types](#) for more details.
3. Added support for pre and postsynaptic state variables for weight update models to allow more efficient implementation of trace based STDP rules. See [Defining a new weight update model](#) for more details.
4. Added support for devices with Compute Capability 7.0 (Volta) to block-size optimizer.
5. Added support for a new class of 'current source' model which allows non-synaptic input to be efficiently injected into neurons. See [Current source models](#) for more details.
6. Added support for heterogeneous dendritic delays. See [Defining a new weight update model](#) for more details.
7. Added support for (homogeneous) synaptic back propagation delays using `SynapseGroup::setBackPropDelaySteps`.
8. For long simulations, using single precision to represent simulation time does not work well. Added `Nmodel::setTimePrecision` to allow data type used to represent time to be set independently.

### Optimisations

1. `GENN_PREFERENCES::mergePostsynapticModels` flag can be used to enable the merging together of postsynaptic models from a neuron population's incoming synapse populations - improves performance and saves memory.
2. On devices with compute capability  $> 3.5$  GeNN now uses the read only cache to improve performance of postsynaptic learning kernel.

### Bug fixes:

1. Fixed bug enabling support for CUDA 9.1 and 9.2 on Windows.
2. Fixed bug in SynDelay example where membrane voltage went to NaN.
3. Fixed bug in code generation of `SCALAR_MIN` and `SCALAR_MAX` values.
4. Fixed bug in substitution of transcendental functions with single-precision variants.
5. Fixed various issues involving using spike times with delayed synapse projections.

## Release Notes for GeNN v3.1.1

This release fixes several small bugs found in GeNN 3.1.0 and implements some small features:

### User Side Changes

1. Added new synapse matrix types `SPARSE_GLOBALG_INDIVIDUAL_PSM`, `DENSE_GLOBALG_INDIVIDUAL_PSM` and `BITMASK_GLOBALG_INDIVIDUAL_PSM` to handle case where synapses with no individual state have a postsynaptic model with state variables e.g. an alpha synapse. See [Synaptic matrix types](#) for more details.

### Bug fixes

1. Correctly handle aliases which refer to other aliases in SpineML models.
2. Fixed issues with presynaptically parallelised synapse populations where the postsynaptic population is small enough for input to be accumulated in shared memory.

## Release Notes for GeNN v3.1.0

This release builds on the changes made in 3.0.0 to further streamline the process of building models with GeNN and includes several bug fixes for certain system configurations.

### User Side Changes

1. Support for simulating models described using the [SpineML](#) model description language with GeNN (see [SpineML and SpineCreator](#) for more details).
2. Neuron models can now sample from uniform, normal, exponential or log-normal distributions - these calls are translated to `cuRAND` when run on GPUs and calls to the C++11 `<random>` library when run on CPU. See [Defining your own neuron type](#) for more details.
3. Model state variables can now be initialised using small *snippets* of code run either on GPU or CPU. This can save significant amounts of initialisation time for large models. See [Defining a new variable initialisation snippet](#) for more details.
4. New `MSBuild` build system for Windows - makes developing user code from within Visual Studio much more streamlined. See [Debugging suggestions](#) for more details.

### Bug fixes:

1. Workaround for [bug](#) found in Glibc 2.23 and 2.24 which causes poor performance on some 64-bit Linux systems (namely on Ubuntu 16.04 LTS).
2. Fixed bug encountered when using extra global variables in weight updates.

## Release Notes for GeNN v3.0.0

This release is the result of some fairly major refactoring of GeNN which we hope will make it more user-friendly and maintainable in the future.

### User Side Changes

1. Entirely new syntax for defining models - hopefully terser and less error-prone (see updated documentation and examples for details).
2. Continuous integration testing using Jenkins - automated testing and code coverage calculation calculated automatically for Github pull requests etc.
3. Support for using Zero-copy memory for model variables. Especially on devices such as NVIDIA Jetson TX1 with no physical GPU memory this can significantly improve performance when recording data or injecting it to the simulation from external sensors.

## Release Notes for GeNN v2.2.3

This release includes minor new features and several bug fixes for certain system configurations.

### User Side Changes

1. Transitioned feature tests to use Google Test framework.
2. Added support for CUDA shader model 6.X

### Bug fixes:

1. Fixed problem using GeNN on systems running 32-bit Linux kernels on a 64-bit architecture (Nvidia Jetson modules running old software for example).
2. Fixed problem linking against CUDA on Mac OS X El Capitan due to SIP (System Integrity Protection).
3. Fixed problems with support code relating to its scope and usage in spike-like event threshold code.
4. Disabled use of C++ regular expressions on older versions of GCC.

## Release Notes for GeNN v2.2.2

This release includes minor new features and several bug fixes for certain system configurations.

### User Side Changes

1. Added support for the new version (2.0) of the Brian simulation package for Python.
2. Added a mechanism for setting user-defined flags for the C++ compiler and NVCC compiler, via `GENN_PREPROCESSOR_FLAGS`.

### Bug fixes:

1. Fixed a problem with `atomicAdd()` redefinitions on certain CUDA runtime versions and GPU configurations.
2. Fixed an incorrect bracket placement bug in code generation for certain models.
3. Fixed an incorrect neuron group indexing bug in the learning kernel, for certain models.
4. The dry-run compile phase now stores temporary files in the current directory, rather than the temp directory, solving issues on some systems.
5. The `LINK_FLAGS` and `INCLUDE_FLAGS` in the common windows makefile include 'makefile\_common\_win.mk' are now appended to, rather than being overwritten, fixing issues with custom user makefiles on Windows.

## Release Notes for GeNN v2.2.1

This bugfix release fixes some critical bugs which occur on certain system configurations.

**Bug fixes:**

1. (important) Fixed a Windows-specific bug where the CL compiler terminates, incorrectly reporting that the nested scope limit has been exceeded, when a large number of device variables need to be initialised.
2. (important) Fixed a bug where, in certain circumstances, outdated generateALL objects are used by the Makefiles, rather than being cleaned and replaced by up-to-date ones.
3. (important) Fixed an 'atomicAdd' redeclared or missing bug, which happens on certain CUDA architectures when using the newest CUDA 8.0 RC toolkit.
4. (minor) The SynDelay example project now correctly reports spike indexes for the input group.

Please refer to the [full documentation](#) for further details, tutorials and complete code documentation.

**Release Notes for GeNN v2.2**

This release includes minor new features, some core code improvements and several bug fixes on GeNN v2.1.

**User Side Changes**

1. GeNN now analyses automatically which parameters each kernel needs access to and these and only these are passed in the kernel argument list in addition to the global time `t`. These parameters can be a combination of `extraGlobalNeuronKernelParameters` and `extraGlobalSynapseKernelParameters` in either neuron or synapse kernel. In the unlikely case that users wish to call kernels directly, the correct call can be found in the `stepTimeGPU()` function.  
Reflecting these changes, the predefined Poisson neurons now simply have two `extraGlobalNeuronKernelParameters` `rates` and `offset` which replace the previous custom pointer to the array of input rates and integer offset to indicate the current input pattern. These `extraGlobalNeuronKernelParameters` are passed to the neuron kernel automatically, but the rates themselves within the array are of course not updated automatically (this is exactly as before with the specifically generated kernel arguments for Poisson neurons).  
The concept of "directInput" has been removed. Users can easily achieve the same functionality by adding an additional variable (if there are individual inputs to neurons), an `extraGlobalNeuronParameter` (if the input is homogeneous but time dependent) or, obviously, a simple parameter if it's homogeneous and constant.

**Note**

The global time variable "`t`" is now provided by GeNN; please make sure that you are not duplicating its definition or shadowing it. This could have severe consequences for simulation correctness (e.g. time not advancing in cases of over-shadowing).

2. We introduced the namespace `GENN_PREFERENCES` which contains variables that determine the behaviour of GeNN.
3. We introduced a new code snippet called "supportCode" for neuron models, weightupdate models and post-synaptic models. This code snippet is intended to contain user-defined functions that are used from the other code snippets. We advise where possible to define the support code functions with the CUDA keywords "`__host__ __device__`" so that they are available for both GPU and CPU version. Alternatively one can define separate versions for **host** and **device** in the snippet. The snippets are automatically made available to the relevant code parts. This is regulated through namespaces so that name clashes between different models do not matter. An exception are hash defines. They can in principle be used in the supportCode snippet but need to be protected specifically using `ifndef`. For example

```
#ifndef clip(x)
#define clip(x) x > 10.0? 10.0 : x
#endif
```

## Note

If there are conflicting definitions for hash defines, the one that appears first in the GeNN generated code will then prevail.

4. The new convenience macros `spikeCount_XX` and `spike_XX` where "XX" is the name of the neuron group are now also available for events: `spikeEventCount_XX` and `spikeEvent_XX`. They access the values for the current time step even if there are synaptic delays and spikes events are stored in circular queues.
5. The old `buildmodel.[sh|bat]` scripts have been superseded by new `genn-buildmodel.[sh|bat]` scripts. These scripts accept UNIX style option switches, allow both relative and absolute model file paths, and allow the user to specify the directory in which all output files are placed (`-o <path>`). Debug (`-d`), CPU-only (`-c`) and show help (`-h`) are also defined.
6. We have introduced a CPU-only "`-c`" `genn-buildmodel` switch, which, if it's defined, will generate a GeNN version that is completely independent from CUDA and hence can be used on computers without CUDA installation or CUDA enabled hardware. Obviously, this then can also only run on CPU. CPU only mode can either be switched on by defining `CPU_ONLY` in the model description file or by passing appropriate parameters during the build, in particular

```
genn-buildmodel.[sh|bat] \<modelfile\> -c
make release CPU_ONLY=1
```

7. The new `genn-buildmodel "-o"` switch allows the user to specify the output directory for all generated files - the default is the current directory. For example, a user project could be in `'/home/genn_project'`, whilst the GeNN directory could be `'/usr/local/genn'`. The GeNN directory is kept clean, unless the user decides to build the sample projects inside of it without copying them elsewhere. This allows the deployment of GeNN to a read-only directory, like `'/usr/local'` or `'C:\Program Files'`. It also allows multiple users - i.e. on a compute cluster - to use GeNN simultaneously, without overwriting each other's code-generation files, etcetera.
8. The ARM architecture is now supported - e.g. the NVIDIA Jetson development platform.
9. The NVIDIA CUDA SM\_5\* (Maxwell) architecture is now supported.
10. An error is now thrown when the user tries to use double precision floating-point numbers on devices with architecture older than SM\_13, since these devices do not support double precision.
11. All GeNN helper functions and classes, such as `toString()` and `NNmodel`, are defined in the header files at `genn/lib/include/`, for example `stringUtils.h` and `modelSpec.h`, which should be individually included before the functions and classes may be used. The functions and classes are actually implemented in the static library `genn\lib\lib\genn.lib` (Windows) or `genn/lib/lib/libgenn.a` (Mac, Linux), which must be linked into the final executable if any GeNN functions or classes are used.
12. In the `modelDefinition()` file, only the header file `modelSpec.h` should be included - i.e. not the source file `modelSpec.cc`. This is because the declaration and definition of `NNmodel`, and associated functions, has been separated into `modelSpec.h` and `modelSpec.cc`, respectively. This is to enable `NNmodel` code to be precompiled separately. *Henceforth, only the header file `modelSpec.h` should be included in model definition files!*
13. In the `modelDefinition()` file, `DT` is now preferably defined using `model.setDT(<val>);`, rather than `#define DT <val>`, in order to prevent problems with `DT` macro redefinition. For backward-compatibility reasons, the old `#define DT <val>` method may still be used, however users are advised to adopt the new method.
14. In preparation for multi-GPU support in GeNN, we have separated out the compilation of generated code from user-side code. This will eventually allow us to optimise and compile different parts of the model with different CUDA flags, depending on the CUDA device chosen to execute that particular part of the model. As such, we have had to use a header file `definitions.h` as the generated code interface, rather than the `runner.cc` file. In practice, this means that *user-side code should include `myModel_CODE/definitions.h`, rather than `myModel_CODE/runner.cc`. Including `runner.cc` will likely result in pages of linking errors at best!*



### Developer Side Changes

1. Blocksize optimization and device choice now obtain the ptxas information on memory usage from a CUDA driver API call rather than from parsing ptxas output of the nvcc compiler. This adds robustness to any change in the syntax of the compiler output.
2. The information about device choice is now stored in variables in the namespace `GENN_PREFERENCES`. This includes `chooseDevice`, `optimiseBlockSize`, `optimizeCode`, `debugCode`, `showPtxasInfo`, `defaultDevice`. `asGoodAsZero` has also been moved into this namespace.
3. We have also introduced the namespace `GENN_FLAGS` that contains unsigned int variables that attach names to numeric flags that can be used within GeNN.
4. The definitions of all generated variables and functions such as `pullXXXStateFromDevice` etc, are now generated into `definitions.h`. This is useful where one wants to compile separate object files that cannot all include the full definitions in e.g. "runnerGPU.cc". One example where this is useful is the `brian2genn` interface.
5. A number of feature tests have been added that can be found in the `featureTests` directory. They can be run with the respective `runTests.sh` scripts. The `cleanTests.sh` scripts can be used to remove all generated code after testing.

### Improvements

1. Improved method of obtaining ptxas compiler information on register and shared memory usage and an improved algorithm for estimating shared memory usage requirements for different block sizes.
2. Replaced pageable CPU-side memory with **page-locked memory**. This can significantly speed up simulations in which a lot of data is regularly copied to and from a CUDA device.
3. GeNN library objects and the main `generateALL` binary objects are now compiled separately, and only when a change has been made to an object's source, rather than recompiling all software for a minor change in a single source file. This should speed up compilation in some instances.

### Bug fixes:

1. Fixed a minor bug with delayed synapses, where `delaySlot` is declared but not referenced.
2. We fixed a bug where on rare occasions a synchronisation problem occurred in sparse synapse populations.
3. We fixed a bug where the combined spike event condition from several synapse populations was not assembled correctly in the code generation phase (the parameter values of the first synapse population over-rode the values of all other populations in the combined condition).

Please refer to the **full documentation** for further details, tutorials and complete code documentation.

### Release Notes for GeNN v2.1

This release includes some new features and several bug fixes on GeNN v2.0.

### User Side Changes

1. Block size debugging flag and the `asGoodAsZero` variables are moved into `include/global.h`.
2. NGRADSYNAPSES dynamics have changed (See Bug fix #4) and this change is applied to the example projects. If you are using this synapse model, you may want to consider changing model parameters.
3. The delay slots are now such that `NO_DELAY` is 0 delay slots (previously 1) and 1 means an actual delay of 1 time step.

4. The convenience function `convertProbabilityToRandomNumberThreshold(float *, uint64_t *, int)` was changed so that it actually converts firing probability/timestep into a threshold value for the GeNN random number generator (as its name always suggested). The previous functionality of converting a *rate* in kHz into a firing threshold number for the GeNN random number generator is now provided with the name `convertRateToRandomNumberThreshold(float *, uint64_t *, int)`
5. Every model definition function `modelDefinition()` now needs to end with calling `NNmodel->::finalize()` for the defined network model. This will lock down the model and prevent any further changes to it by the supported methods. It also triggers necessary analysis of the model structure that should only be performed once. If the `finalize()` function is not called, GeNN will issue an error and exit before code generation.
6. To be more consistent in function naming the `pull\<SYNAPSENAME\>FromDevice` and `push\<SYNAPSENAME\>ToDevice` have been renamed to `pull\<SYNAPSENAME\>StateFromDevice` and `push\<SYNAPSENAME\>StateToDevice`. The old versions are still supported through macro definitions to make the transition easier.
7. New convenience macros are now provided to access the current spike numbers and identities of neurons that spiked. These are called `spikeCount_XX` and `spike_XX` where "XX" is the name of the neuron group. They access the values for the current time step even if there are synaptic delays and spikes are stored in circular queues.
8. There is now a pre-defined neuron type "SPIKECOURSE" which is empty and can be used to define PyNN style spike source arrays.
9. The macros `FLOAT` and `DOUBLE` were replaced with `GENN_FLOAT` and `GENN_DOUBLE` due to name clashes with typedefs in Windows that define `FLOAT` and `DOUBLE`.

#### Developer Side Changes

1. We introduced a file `definitions.h`, which is generated and filled with useful macros such as `spkQuePtrShift` which tells users where in the circular spike queue their spikes start.

#### Improvements

1. Improved debugging information for block size optimisation and device choice.
2. Changed the device selection logic so that device occupancy has larger priority than device capability version.
3. A new HH model called `TRAUBMILES_PSTEP` where one can set the number of inner loops as a parameter is introduced. It uses the `TRAUBMILES_SAFE` method.
4. An alternative method is added for the insect olfaction model in order to fix the number of connections to a maximum of 10K in order to avoid negative conductance tails.
5. We introduced a preprocessor define directive for an `"int_"` function that translates floating points to integers.

#### Bug fixes:

1. `AtomicAdd` replacement for old GPUs were used by mistake if the model runs in double precision.
2. Timing of individual kernels is fixed and improved.
3. More careful setting of maximum number of connections in sparse connectivity, covering mixed dense/sparse network scenarios.
4. `NGRADSYNAPSES` was not scaling correctly with varying time step.
5. Fixed a bug where learning kernel with sparse connectivity was going out of range in an array.
6. Fixed synapse kernel name substitutions where the `"dd_"` prefix was omitted by mistake.

Please refer to the [full documentation](#) for further details, tutorials and complete code documentation.

## Release Notes for GeNN v2.0

Version 2.0 of GeNN comes with a lot of improvements and added features, some of which have necessitated some changes to the structure of parameter arrays among others.

### User Side Changes

1. Users are now required to call `initGeNN()` in the model definition function before adding any populations to the neuronal network model.
2. `glbscnt` is now call `glbSpkCnt` for consistency with `glbSpkEvtCnt`.
3. There is no longer a privileged parameter `Epre`. Spike type events are now defined by a code string `spk←EvtntThreshold`, the same way proper spikes are. The only difference is that Spike type events are specific to a synapse type rather than a neuron type.
4. The function `setSynapseG` has been deprecated. In a `GLOBALG` scenario, the variables of a synapse group are set to the initial values provided in the `modeldefinition` function.
5. Due to the split of synaptic models into `weightUpdateModel` and `postSynModel`, the parameter arrays used during model definition need to be carefully split as well so that each side gets the right parameters. For example, previously

```
float myPNKC_p[3]= {
0.0,          // 0 - Erev: Reversal potential
-20.0,        // 1 - Epre: Presynaptic threshold potential
1.0           // 2 - tau_S: decay time constant for S [ms]
};
```

would define the parameter array of three parameters, `Erev`, `Epre`, and `tau_S` for a synapse of type `NSYNAPSE`. This now needs to be "split" into

```
float *myPNKC_p= NULL;
float postExpPNKC[2]={
1.0,          // 0 - tau_S: decay time constant for S [ms]
0.0           // 1 - Erev: Reversal potential
};
```

i.e. parameters `Erev` and `tau_S` are moved to the post-synaptic model and its parameter array of two parameters. `Epre` is discontinued as a parameter for `NSYNAPSE`. As a consequence the `weightupdate` model of `NSYNAPSE` has no parameters and one can pass `NULL` for the parameter array in `addSynapse←Population`. The correct parameter lists for all defined neuron and synapse model types are listed in the [User Manual](#).

### Note

If the parameters are not redefined appropriately this will lead to uncontrolled behaviour of models and likely to segmentation faults and crashes.

6. Advanced users can now define variables as type `scalar` when introducing new neuron or synapse types. This will at the code generation stage be translated to the model's floating point type (`ftype`), `float` or `double`. This works for defining variables as well as in all code snippets. Users can also use the expressions `SCALAR_MAX` and `SCALAR_MIN` for `FLT_MIN`, `FLT_MAX`, `DBL_MIN` and `DBL_MAX`, respectively. Corresponding definitions of `scalar`, `SCALAR_MIN` and `SCALAR_MAX` are also available for user-side code whenever the code-generated file `runner.cc` has been included.
7. The example projects have been re-organized so that wrapper scripts of the `generate_run` type are now all located together with the models they run instead of in a common `tools` directory. Generally the structure now is that each example project contains the wrapper script `generate_run` and a `model` subdirectory which contains the model description file and the user side code complete with Makefiles for Unix and Windows operating systems. The generated code will be deposited in the `model` subdirectory in its own `modelname_CODE` folder. Simulation results will always be deposited in a new sub-folder of the main project directory.

8. The `addSynapsePopulation(...)` function has now more mandatory parameters relating to the introduction of separate weightupdate models (pre-synaptic models) and postynaptic models. The correct syntax for the `addSynapsePopulation(...)` can be found with detailed explanations in the [User Manual](#).
9. We have introduced a simple performance profiling method that users can employ to get an overview over the differential use of time by different kernels. To enable the timers in GeNN generated code, one needs to declare

```
networkmodel.setTiming(TRUE);
```

This will make available and operate GPU-side cudaEvent based timers whose cumulative value can be found in the double precision variables `neuron_tme`, `synapse_tme` and `learning_tme`. They measure the accumulated time that has been spent calculating the neuron kernel, synapse kernel and learning kernel, respectively. CPU-side timers for the simulation functions are also available and their cumulative values can be obtained through

```
float x= sdkGetTimerValue(&neuron_timer);
float y= sdkGetTimerValue(&synapse_timer);
float z= sdkGetTimerValue(&learning_timer);
```

The [Insect olfaction model](#) example shows how these can be used in the user-side code. To enable timing profiling in this example, simply enable it for GeNN:

```
model.setTiming(TRUE);
```

in `MBody1.cc`'s `modelDefinition` function and define the macro `TIMING` in `classol_sim.h`

```
#define TIMING
```

This will have the effect that timing information is output into `OUTNAME_output/OUTNAME.timingprofile`.

## Developer Side Changes

1. `allocateSparseArrays()` has been changed to take the number of connections, `connN`, as an argument rather than expecting it to have been set in the `Connetion` struct before the function is called as was the arrangement previously.
2. For the case of sparse connectivity, there is now a reverse mapping implemented with `revers` index arrays and a `remap` array that points to the original positions of variable values in the forward array. By this mechanism, `revers` lookups from post to pre synaptic indices are possible but value changes in the sparse array values do only need to be done once.
3. `SpkEvt` code is no longer generated whenever it is not actually used. That is also true on a somewhat finer granularity where variable queues for synapse delays are only maintained if the corresponding variables are used in synaptic code. True spikes on the other hand are always detected in case the user is interested in them.

Please refer to the [full documentation](#) for further details, tutorials and complete code documentation.

[Previous](#) | [Top](#) | [Next](#)

## 9 User Manual

## 9.1 Contents

- [Introduction](#)
- [Defining a network model](#)
- [Neuron models](#)
- [Weight update models](#)
- [Postsynaptic integration methods](#)
- [Current source models](#)
- [Synaptic matrix types](#)
- [Variable initialisation](#)
- [Sparse connectivity initialisation](#)

## 9.2 Introduction

GeNN is a software library for facilitating the simulation of neuronal network models on NVIDIA CUDA enabled GPU hardware. It was designed with computational neuroscience models in mind rather than artificial neural networks. The main philosophy of GeNN is two-fold:

1. GeNN relies heavily on code generation to make it very flexible and to allow adjusting simulation code to the model of interest and the GPU hardware that is detected at compile time.
2. GeNN is lightweight in that it provides code for running models of neuronal networks on GPU hardware but it leaves it to the user to write a final simulation engine. It so allows maximal flexibility to the user who can use any of the provided code but can fully choose, inspect, extend or otherwise modify the generated code. They can also introduce their own optimisations and in particular control the data flow from and to the GPU in any desired granularity.

This manual gives an overview of how to use GeNN for a novice user and tries to lead the user to more expert use later on. With that we jump right in.

[Previous](#) | [Top](#) | [Next](#)

## 9.3 Defining a network model

A network model is defined by the user by providing the function

```
void modelDefinition(ModelSpec &model)
```

in a separate file, such as `MyModel.cc`. In this function, the following tasks must be completed:

1. The name of the model must be defined:

```
model.setName("MyModel");
```

2. Neuron populations (at least one) must be added (see [Defining neuron populations](#)). The user may add as many neuron populations as they wish. If resources run out, there will not be a warning but GeNN will fail. However, before this breaking point is reached, GeNN will make all necessary efforts in terms of block size optimisation to accommodate the defined models. All populations must have a unique name.
3. Synapse populations (zero or more) can be added (see [Defining synapse populations](#)). Again, the number of synaptic connection populations is unlimited other than by resources.

### 9.3.1 Defining neuron populations

Neuron populations are added using the function

```
model.addNeuronPopulation<NeuronModel>(name, num, paramValues, varInitialisers);
```

where the arguments are:

- `NeuronModel`: Template argument specifying the type of neuron model. These should be derived off [NeuronModels::Base](#) and can either be one of the standard models or user-defined (see [Neuron models](#)).
- `const string &name`: Unique name of the neuron population
- `unsigned int size`: number of neurons in the population
- `NeuronModel::ParamValues paramValues`: Parameters of this neuron type
- `NeuronModel::VarValues varInitialisers`: Initial values or initialisation snippets for variables of this neuron type

The user may add as many neuron populations as the model necessitates. They must all have unique names. The possible values for the arguments, predefined models and their parameters and initial values are detailed [Neuron models](#) below.

### 9.3.2 Defining synapse populations

Synapse populations are added with the function

```
model.addSynapsePopulation<WeightUpdateModel, PostsynapticModel>(name, mType, delay,
    preName, postName,
    weightPreVarInitialisers, weightPostVarInitialisers, weightParamValues, weightVarValues,
    postsynapticParamValues,
    postsynapticVarValues, connectivityInitialiser);
```

where the arguments are

- `WeightUpdateModel`: Template parameter specifying the type of weight update model. These should be derived off [WeightUpdateModels::Base](#) and can either be one of the standard models or user-defined (see [Weight update models](#)).
- `PostsynapticModel`: Template parameter specifying the type of postsynaptic integration model. These should be derived off [PostsynapticModels::Base](#) and can either be one of the standard models or user-defined (see [Postsynaptic integration methods](#)).
- `const string &name`: The name of the synapse population
- `unsigned int mType`: How the synaptic matrix is stored. See [Synaptic matrix types](#) for available options.
- `unsigned int delay`: Homogeneous (axonal) delay for synapse population (in terms of the simulation time step DT).
- `const string preName`: Name of the (existing!) pre-synaptic neuron population.
- `const string postName`: Name of the (existing!) post-synaptic neuron population.
- `WeightUpdateModel::ParamValues weightParamValues`: The parameter values (common to all synapses of the population) for the weight update model.
- `WeightUpdateModel::VarValues weightVarInitialisers`: Initial values or initialisation snippets for the weight update model's state variables

- `WeightUpdateModel::PreVarValues weightPreVarInitialisers`: Initial values or initialisation snippets for the weight update model's presynaptic state variables
- `WeightUpdateModel::PostVarValues weightPostVarInitialisers`: Initial values or initialisation snippets for the weight update model's postsynaptic state variables
- `PostsynapticModel::ParamValues postsynapticParamValues`: The parameter values (common to all postsynaptic neurons) for the postsynaptic model.
- `PostsynapticModel::VarValues postsynapticVarInitialisers`: Initial values or initialisation snippets for variables for the postsynaptic model's state variables
- `InitSparseConnectivitySnippet::Init connectivityInitialiser`: Optional argument, specifying the initialisation snippet for synapse population's sparse connectivity (see [Sparse connectivity initialisation](#)).

The `ModelSpec::addSynapsePopulation()` function returns a pointer to the newly created `SynapseGroup` object which can be further configured, namely with:

- `SynapseGroup::setMaxConnections()` and `SynapseGroup::setMaxSourceConnections()` to configure the maximum number of rows and columns respectively allowed in the synaptic matrix - this can improve performance and reduce memory usage when using `SynapseMatrixConnectivity::SPARSE` connectivity (see [Synaptic matrix types](#)).

#### Note

When using a sparse connectivity initialisation snippet, these values are set automatically.

- `SynapseGroup::setMaxDendriticDelayTimesteps()` sets the maximum dendritic delay (in terms of the simulation time step `DT`) allowed for synapses in this population. No values larger than this should be passed to the delay parameter of the `addToDenDelay` function in user code (see [Defining a new weight update model](#)).
- `SynapseGroup::setSpanType()` sets how incoming spike processing is parallelised for this synapse group. The default `SynapseGroup::SpanType::POSTSYNAPTIC` is nearly always the best option, but `SynapseGroup::SpanType::PRESYNAPTIC` may perform better when there are large numbers of spikes every timestep or very few postsynaptic neurons.

#### Note

If the synapse matrix uses one of the "GLOBALG" types then the global value of the synapse parameters are taken from the initial value provided in `weightVarInitialisers` therefore these must be constant rather than sampled from a distribution etc.

[Previous](#) | [Top](#) | [Next](#)

## 9.4 Neuron models

There is a number of predefined models which can be used with the `ModelSpec::addNeuronGroup` function:

- `NeuronModels::RulkovMap`
- `NeuronModels::Izhikevich`
- `NeuronModels::IzhikevichVariable`
- `NeuronModels::LIF`
- `NeuronModels::SpikeSource`
- `NeuronModels::PoissonNew`
- `NeuronModels::TraubMiles`

- [NeuronModels::TraubMilesFast](#)
- [NeuronModels::TraubMilesAlt](#)
- [NeuronModels::TraubMilesNStep](#)

#### 9.4.1 Defining your own neuron type

In order to define a new neuron type for use in a GeNN application, it is necessary to define a new class derived from [NeuronModels::Base](#). For convenience the methods this class should implement can be implemented using macros:

- [DECLARE\\_MODEL\(TYPE, NUM\\_PARAMS, NUM\\_VARS\)](#): declared the boilerplate code required for the model e.g. the correct specialisations of [NewModels::ValueBase](#) used to wrap the neuron model parameters and values.
- [SET\\_SIM\\_CODE\(SIM\\_CODE\)](#): where `SIM_CODE` contains the code for executing the integration of the model for one time step. Within this code string, variables need to be referred to by `$(NAME)`, where `NAME` is the name of the variable as defined in the vector `varNames`. The code may refer to the predefined primitives `DT` for the time step size and `I_syn` for the total incoming synaptic current. It can also refer to a unique ID (within the population) using `ID`.
- [SET\\_THRESHOLD\\_CONDITION\\_CODE\(THRESHOLD\\_CONDITION\\_CODE\)](#) defines the condition for true spike detection.
- [SET\\_PARAM\\_NAMES\(\)](#) defines the names of the model parameters. If defined as `NAME` here, they can then be referenced as `$(NAME)` in the code string. The length of this list should match the `NUM_PARAM` specified in [DECLARE\\_MODEL](#). Parameters are assumed to be always of type double.
- [SET\\_VARS\(\)](#) defines the names, type strings (e.g. "float", "double", etc) and (optionally) access mode of the neuron state variables. The type string "scalar" can be used for variables which should be implemented using the precision set globally for the model with [ModelSpec::setPrecision](#). The variables defined here as `NAME` can then be used in the syntax `$(NAME)` in the code string. If the access mode is set to [VarAccess::READ\\_WRITE](#), GeNN applies additional optimisations and models should not write to it.
- [SET\\_NEEDS\\_AUTO\\_REFRACTORY\(\)](#) defines whether the neuron should include an automatic refractory period to prevent it emitting spikes in successive timesteps.

For example, using these macros, we can define a leaky integrator  $\tau \frac{dV}{dt} = -V + I_{\text{syn}}$  solved using Euler's method:

```
class LeakyIntegrator : public NeuronModels::Base
{
public:
    DECLARE_MODEL(LeakyIntegrator, 1, 1);

    SET_SIM_CODE ("$(V) += (-$(V) + $(I_syn)) * (DT/$(tau));");

    SET_THRESHOLD_CONDITION_CODE ("$(V) >= 1.0");

    SET_PARAM_NAMES ({ "tau" });

    SET_VARS ({ { "V", "scalar", VarAccess::READ_WRITE } });
};
```

Additionally "dependent parameters" can be defined. Dependent parameters are a mechanism for enhanced efficiency when running neuron models. If parameters with model-side meaning, such as time constants or conductances always appear in a certain combination in the model, then it is more efficient to pre-compute this combination and define it as a dependent parameter.

For example, because the equation defining the previous leaky integrator example has an algebraic solution, it can be more accurately solved as follows - using a derived parameter to calculate  $\exp\left(-\frac{t}{\tau}\right)$ :



```

class LeakyIntegrator2 : public NeuronModels::Base
{
public:
    DECLARE_MODEL(LeakyIntegrator2, 1, 1);

    SET_SIM_CODE("$ (V) = $ (Isyn) - $ (ExpTC) * ($ (Isyn) - $ (V));");

    SET_THRESHOLD_CONDITION_CODE("$ (V) >= 1.0");

    SET_PARAM_NAMES({"tau"});

    SET_VARS({{"V", "scalar", VarAccess::READ_WRITE}});

    SET_DERIVED_PARAMS({
        {"ExpTC", [] (const vector<double> &pars, double dt) { return std::exp(-dt / pars[0]); }}});
};

```

GeNN provides several additional features that might be useful when defining more complex neuron models.

#### 9.4.1.1 Support code

Support code enables a code block to be defined that contains supporting code that will be utilized in multiple pieces of user code. Typically, these are functions that are needed in the sim code or threshold condition code. If possible, these should be defined as `__host__ __device__` functions so that both GPU and CPU versions of GeNN code have an appropriate support code function available. The support code is protected with a namespace so that it is exclusively available for the neuron population whose neurons define it. Support code is added to a model using the `SET_SUPPORT_CODE()` macro, for example:

```

SET_SUPPORT_CODE("__device__ __host__ scalar mysin(float x){ return sin(x); }");

```

#### 9.4.1.2 Extra global parameters

Extra global parameters are parameters common to all neurons in the population. However, unlike the standard neuron parameters, they can be varied at runtime meaning they could, for example, be used to provide a global reward signal. These parameters are defined by using the `SET_EXTRA_GLOBAL_PARAMS()` macro to specify a list of variable names and type strings (like the `SET_VARS()` macro). For example:

```

SET_EXTRA_GLOBAL_PARAMS({{"R", "float"}});

```

These variables are available to all neurons in the population. They can also be used in synaptic code snippets; in this case it need to be addressed with a `_pre` or `_post` postfix.

For example, if the model with the "R" parameter was used for the pre-synaptic neuron population, the weight update model of a synapse population could have simulation code like:

```

SET_SIM_CODE("$ (x) = $ (x) + $ (R_pre);");

```

where we have assumed that the weight update model has a variable `x` and our synapse type will only be used in conjunction with pre-synaptic neuron populations that do have the extra global parameter `R`. If the pre-synaptic population does not have the required variable/parameter, GeNN will fail when compiling the kernels.

#### 9.4.1.3 Additional input variables

Normally, neuron models receive the linear sum of the inputs coming from all of their synaptic inputs through the `$(inSyn)` variable. However neuron models can define additional input variables - allowing input from different synaptic inputs to be combined non-linearly. For example, if we wanted our leaky integrator to operate on the product of two input currents, it could be defined as follows:

```

SET_ADDITIONAL_INPUT_VARS({{"Isyn2", "scalar", 1.0}});
SET_SIM_CODE("const scalar input = $(Isyn) * $(Isyn2);\n"
    "$ (V) = input - $(ExpTC) * (input - $ (V));");

```

Where the `SET_ADDITIONAL_INPUT_VARS()` macro defines the name, type and its initial value before postsynaptic inputs are applied (see section [Postsynaptic integration methods](#) for more details).

#### 9.4.1.4 Random number generation

Many neuron models have probabilistic terms, for example a source of noise or a probabilistic spiking mechanism. In GeNN this can be implemented by using the following functions in blocks of model code:

- `$(gennrand_uniform)` returns a number drawn uniformly from the interval  $[0.0, 1.0]$
- `$(gennrand_normal)` returns a number drawn from a normal distribution with a mean of 0 and a standard deviation of 1.
- `$(gennrand_exponential)` returns a number drawn from an exponential distribution with  $\lambda = 1$ .
- `$(gennrand_log_normal, MEAN, STDDEV)` returns a number drawn from a log-normal distribution with the specified mean and standard deviation.
- `$(gennrand_gamma, ALPHA)` returns a number drawn from a gamma distribution with the specified shape.

Once defined in this way, new neuron models classes, can be used in network descriptions by referring to their type e.g.

```
networkModel.addNeuronPopulation<LeakyIntegrator>("Neurons", 1,
                                                LeakyIntegrator::ParamValues(20.0), // tau
                                                LeakyIntegrator::VarValues(0.0)); // V
```

[Previous](#) | [Top](#) | [Next](#)

## 9.5 Weight update models

Currently 4 predefined weight update models are available:

- [WeightUpdateModels::StaticPulse](#)
- [WeightUpdateModels::StaticPulseDendriticDelay](#)
- [WeightUpdateModels::StaticGraded](#)
- [WeightUpdateModels::PiecewiseSTDP](#)

For more details about these built-in synapse models, see [\[3\]](#).

### 9.5.1 Defining a new weight update model

Like the neuron models discussed in [Defining your own neuron type](#), new weight update models are created by defining a class. Weight update models should all be derived from `WeightUpdateModel::Base` and, for convenience, the methods a new weight update model should implement can be implemented using macros:

- `SET_DERIVED_PARAMS()`, `SET_PARAM_NAMES()`, `SET_VARS()` and `SET_EXTRA_GLOBAL_PARAM_S()` perform the same roles as they do in the neuron models discussed in [Defining your own neuron type](#).
- `DECLARE_WEIGHT_UPDATE_MODEL(TYPE, NUM_PARAMS, NUM_VARS, NUM_PRE_VARS, NUM_POST_VARS)` is an extended version of `DECLARE_MODEL()` which declares the boilerplate code required for a weight update model with pre and postsynaptic as well as per-synapse state variables.
- `SET_PRE_VARS()` and `SET_POST_VARS()` define state variables associated with pre or postsynaptic neurons rather than synapses. These are typically used to efficiently implement *trace* variables for use in STDP learning rules [\[2\]](#). Like other state variables, variables defined here as `NAME` can be accessed in weight update model code strings using the `$(NAME)` syntax.

- [SET\\_SIM\\_CODE\(SIM\\_CODE\)](#): defines the simulation code that is used when a true spike is detected. The update is performed only in timesteps after a neuron in the presynaptic population has fulfilled its threshold detection condition. Typically, spikes lead to update of synaptic variables that then lead to the activation of input into the post-synaptic neuron. Most of the time these inputs add linearly at the post-synaptic neuron. This is assumed in GeNN and the term to be added to the activation of the post-synaptic neuron should be applied using the `$(addToInSyn, weight)` function. For example

```
SET_SIM_CODE (
    "$ (addToInSyn, $(inc));\n"
```

where "inc" is the increment of the synaptic input to a post-synaptic neuron for each pre-synaptic spike. The simulation code also typically contains updates to the internal synapse variables that may have contributed to . For an example, see [WeightUpdateModels::StaticPulse](#) for a simple synapse update model and [WeightUpdateModels::PiecewiseSTDP](#) for a more complicated model that uses STDP. To apply input to the post-synaptic neuron with a dendritic (i.e. between the synapse and the postsynaptic neuron) delay you can instead use the `$(addToInSynDelay, weight, delay)` function. For example

```
SET_SIM_CODE (
    "$ (addToInSynDelay, $(inc), $(delay));");
```

where, once again, `inc` is the magnitude of the input step to apply and `delay` is the length of the dendritic delay in timesteps. By implementing `delay` as a weight update model variable, heterogeneous synaptic delays can be implemented. For an example, see [WeightUpdateModels::StaticPulseDendriticDelay](#) for a simple synapse update model with heterogeneous dendritic delays.

#### Note

When using dendritic delays, the **maximum** dendritic delay for a synapse populations must be specified using the `SynapseGroup::setMaxDendriticDelayTimesteps()` function.

- [SET\\_EVENT\\_THRESHOLD\\_CONDITION\\_CODE\(EVENT\\_THRESHOLD\\_CONDITION\\_CODE\)](#) defines a condition for a synaptic event. This typically involves the pre-synaptic variables, e.g. the membrane potential:

```
SET_EVENT_THRESHOLD_CONDITION_CODE ("$(V_pre) > -0.02");
```

Whenever this expression evaluates to true, the event code set using the `SET_EVENT_CODE()` macro is executed. For an example, see [WeightUpdateModels::StaticGraded](#).

- [SET\\_EVENT\\_CODE\(EVENT\\_CODE\)](#) defines the code that is used when the event threshold condition is met (as set using the `SET_EVENT_THRESHOLD_CONDITION_CODE()` macro).
- [SET\\_LEARN\\_POST\\_CODE\(LEARN\\_POST\\_CODE\)](#) defines the code which is used in the `learnSynapses()` Post kernel/function, which performs updates to synapses that are triggered by post-synaptic spikes. This is typically used in STDP-like models e.g. [WeightUpdateModels::PiecewiseSTDP](#).
- [SET\\_SYNAPSE\\_DYNAMICS\\_CODE\(SYNAPSE\\_DYNAMICS\\_CODE\)](#) defines code that is run for each synapse, each timestep i.e. unlike the others it is not event driven. This can be used where synapses have internal variables and dynamics that are described in continuous time, e.g. by ODEs. However using this mechanism is typically computationally very costly because of the large number of synapses in a typical network. By using the `$(addtoInSyn)`, `$(updateInSyn)` and `$(addToDenDelay)` mechanisms discussed in the context of [SET\\_SIM\\_CODE\(\)](#), the synapse dynamics can also be used to implement continuous synapses for rate-based models.
- [SET\\_PRE\\_SPIKE\\_CODE\(\)](#) and [SET\\_POST\\_SPIKE\\_CODE\(\)](#) define code that is called whenever there is a pre or postsynaptic spike. Typically these code strings are used to update any pre or postsynaptic state variables.
- [SET\\_NEEDS\\_PRE\\_SPIKE\\_TIME\(PRE\\_SPIKE\\_TIME\\_REQUIRED\)](#) and [SET\\_NEEDS\\_POST\\_SPIKE\\_TIME\(POST\\_SPIKE\\_TIME\\_REQUIRED\)](#) define whether the weight update needs to know the times of the spikes emitted from the pre and postsynaptic populations. For example an STDP rule would be likely to require:

```
SET_NEEDS_PRE_SPIKE_TIME(true);
SET_NEEDS_POST_SPIKE_TIME(true);
```

All code snippets, aside from those defined with `SET_PRE_SPIKE_CODE()` and `SET_POST_SPIKE_CODE()`, can be used to manipulate any synapse variable and so learning rules can combine both time-driven and event-driven processes.

[Previous](#) | [Top](#) | [Next](#)

## 9.6 Postsynaptic integration methods

There are currently 3 built-in postsynaptic integration methods:

- [PostsynapticModels::ExpCurr](#)
- [PostsynapticModels::ExpCond](#)
- [PostsynapticModels::DeltaCurr](#)

### 9.6.1 Defining a new postsynaptic model

The postsynaptic model defines how synaptic activation translates into an input current (or other input term for models that are not current based). It also can contain equations defining dynamics that are applied to the (summed) synaptic activation, e.g. an exponential decay over time.

In the same manner as to both the neuron and weight update models discussed in [Defining your own neuron type](#) and [Defining a new weight update model](#), postsynaptic model definitions are encapsulated in a class derived from `PostsynapticModels::Base`. Again, the methods that a postsynaptic model should implement can be implemented using the following macros:

- `DECLARE_MODEL(TYPE, NUM_PARAMS, NUM_VARS)`, `SET_DERIVED_PARAMS()`, `SET_PARAM_NAMES()`, `SET_VARS()` perform the same roles as they do in the neuron models discussed in [Defining your own neuron type](#).
- `SET_DECAY_CODE(DECAY_CODE)` defines the code which provides the continuous time dynamics for the summed presynaptic inputs to the postsynaptic neuron. This usually consists of some kind of decay function.
- `SET_APPLY_INPUT_CODE(APPLY_INPUT_CODE)` defines the code specifying the conversion from synaptic inputs to a postsynaptic neuron input current. e.g. for a conductance model:

```
SET_APPLY_INPUT_CODE("$ (Isyn) += $ (inSyn) * ($ (E) - $ (V)) ");
```

where `$(E)` is a postsynaptic model parameter specifying reversal potential and `$(V)` is the variable containing the postsynaptic neuron's membrane potential. As discussed in [Built-in Variables in GeNN](#), `$(Isyn)` is the built in variable used to sum neuron input. However additional input variables can be added to a neuron model using the `SET_ADDITIONAL_INPUT_VARS()` macro (see [Defining your own neuron type](#) for more details).

[Previous](#) | [Top](#) | [Next](#)

## 9.7 Current source models

There is a number of predefined models which can be used with the `ModelSpec::addCurrentSource` function:

- [CurrentSourceModels::DC](#)
- [CurrentSourceModels::GaussianNoise](#)

## 9.7.1 Defining your own current source model

In order to define a new current source type for use in a GeNN application, it is necessary to define a new class derived from `CurrentSourceModels::Base`. For convenience the methods this class should implement can be implemented using macros:

- `DECLARE_MODEL(TYPE, NUM_PARAMS, NUM_VARS), SET_DERIVED_PARAMS(), SET_PARAM_NAMES(), SET_VARS()` perform the same roles as they do in the neuron models discussed in [Defining your own neuron type](#).
- `SET_INJECTION_CODE(INJECTION_CODE)`: where `INJECTION_CODE` contains the code for injecting current into the neuron every simulation timestep. The `$(injectCurrent, )` function is used to inject current.

For example, using these macros, we can define a uniformly distributed noisy current source:

```
class UniformNoise : public CurrentSourceModels::Base
{
public:
    DECLARE_MODEL(UniformNoise, 1, 0);

    SET_SIM_CODE("$(injectCurrent, $(gennrand_uniform) * $(magnitude));");

    SET_PARAM_NAMES({"magnitude"});
};
```

[Previous](#) | [Top](#) | [Next](#)

## 9.8 Synaptic matrix types

Synaptic matrix types are made up of two components: `SynapseMatrixConnectivity` and `SynapseMatrixWeight`. `SynapseMatrixConnectivity` defines what data structure is used to store the synaptic matrix:

- `SynapseMatrixConnectivity::DENSE` stores synaptic matrices as a dense matrix. Large dense matrices require a large amount of memory and if they contain a lot of zeros it may be inefficient.
- `SynapseMatrixConnectivity::SPARSE` stores synaptic matrices in a (padded) 'ragged array' format. In general, this is less efficient to traverse using a GPU than the dense matrix format but does result in significant memory savings for large matrices. Ragged matrix connectivity is stored using several variables whose names, like state variables, have the name of the synapse population appended to them:
  1. `const unsigned int maxRowLength`: a constant set via the `SynapseGroup::setMaxConnections` method which specifies the maximum number of connections in any given row (this is the width the structure is padded to).
  2. `unsigned int *rowLength` (sized to number of presynaptic neurons): actual length of the row of connections associated with each presynaptic neuron
  3. `unsigned int *ind` (sized to `maxRowLength * number of presynaptic neurons`): Indices of corresponding postsynaptic neurons concatenated for each presynaptic neuron. For example, consider a network of two presynaptic neurons connected to three postsynaptic neurons: 0th presynaptic neuron connected to 1st and 2nd postsynaptic neurons, the 1st presynaptic neuron connected only to the 0th neuron. The struct `RaggedProjection` should have these members, with indexing from 0 (where X represents a padding value):

```
maxRowLength = 2
ind = [1 2 0 X]
rowLength = [2 1]
```

Weight update model variables associated with the sparsely connected synaptic population will be kept in an array using the same indexing as `ind`. For example, a variable called `g` will be kept in an array such as: `g=[g_Pre0-Post1 g_pre0-post2 g_pre1-post0 X]`

- [SynapseMatrixConnectivity::BITMASK](#) is an alternative sparse matrix implementation where which synapses within the matrix are present is specified as a binary array (see [Insect olfaction model](#)). This structure is somewhat less efficient than the [SynapseMatrixConnectivity::SPARSE](#) and [SynapseMatrixConnectivity::RAGGED](#) formats and doesn't allow individual weights per synapse. However it does require the smallest amount of GPU memory for large networks.

Furthermore the [SynapseMatrixWeight](#) defines how

- [SynapseMatrixWeight::INDIVIDUAL](#) allows each individual synapse to have unique weight update model variables. Their values must be initialised at runtime and, if running on the GPU, copied across from the user side code, using the `pushXXXXXStateToDevice` function, where XXXX is the name of the synapse population.
- [SynapseMatrixWeight::INDIVIDUAL\\_PSM](#) allows each postsynaptic neuron to have unique post synaptic model variables. Their values must be initialised at runtime and, if running on the GPU, copied across from the user side code, using the `pushXXXXXStateToDevice` function, where XXXX is the name of the synapse population.
- [SynapseMatrixWeight::GLOBAL](#) saves memory by only maintaining one copy of the weight update model variables. This is automatically initialized to the initial value passed to [ModelSpec::addSynapsePopulation](#).

Only certain combinations of [SynapseMatrixConnectivity](#) and [SynapseMatrixWeight](#) are sensible therefore, to reduce confusion, the [SynapseMatrixType](#) enumeration defines the following options which can be passed to [ModelSpec::addSynapsePopulation](#):

- [SynapseMatrixType::SPARSE\\_GLOBALG](#)
- [SynapseMatrixType::SPARSE\\_GLOBALG\\_INDIVIDUAL\\_PSM](#)
- [SynapseMatrixType::SPARSE\\_INDIVIDUALG](#)
- [SynapseMatrixType::DENSE\\_GLOBALG](#)
- [SynapseMatrixType::DENSE\\_GLOBALG\\_INDIVIDUAL\\_PSM](#)
- [SynapseMatrixType::DENSE\\_INDIVIDUALG](#)
- [SynapseMatrixType::BITMASK\\_GLOBALG](#)
- [SynapseMatrixType::BITMASK\\_GLOBALG\\_INDIVIDUAL\\_PSM](#)

[Previous](#) | [Top](#) | [Next](#)

## 9.9 Variable initialisation

Neuron, weight update and postsynaptic models all have state variables which GeNN can automatically initialise.

Previously we have shown variables being initialised to constant values such as:

```
NeuronModels::TraubMiles::VarValues ini(
    0.0529324,      // 1 - prob. for Na channel activation m
    ...
);
```

state variables can also be left *uninitialised* leaving it up to the user code to initialise them between the calls to `initialize()` and `initializeSparse()`:

```
NeuronModels::TraubMiles::VarValues ini(
    uninitialisedVar(),      // 1 - prob. for Na channel activation m
    ...
);
```

or initialised using one of a number of predefined *variable initialisation snippets*:

- [InitVarSnippet::Uniform](#)
- [InitVarSnippet::Normal](#)
- [InitVarSnippet::Exponential](#)
- [InitVarSnippet::Gamma](#)

For example, to initialise a parameter using values drawn from the normal distribution:

```
InitVarSnippet::Normal::ParamValues params(
    0.05,    // 0 - mean
    0.01);  // 1 - standard deviation

NeuronModels::TraubMiles::VarValues ini(
    initVar<InitVarSnippet::Normal>(params),    // 1 - prob. for Na channel activation m
    ...
);
```

### 9.9.1 Defining a new variable initialisation snippet

Similarly to neuron, weight update and postsynaptic models, new variable initialisation snippets can be created by simply defining a class in the model description. For example, when initialising excitatory (positive) synaptic weights with a normal distribution they should be clipped at 0 so the long tail of the normal distribution doesn't result in negative weights. This could be implemented using the following variable initialisation snippet which redraws until samples are within the desired bounds:

```
class NormalPositive : public InitVarSnippet::Base
{
public:
    DECLARE_SNIPPET(NormalPositive, 2);

    SET_CODE(
        "scalar normal;"
        "do\n"
        "{\n"
        "    normal = $(mean) + ($(gennrand_normal) * $(sd));\n"
        "} while (normal < 0.0);\n"
        "$ (value) = normal;\n");

    SET_PARAM_NAMES({"mean", "sd"});
};
IMPLEMENT_SNIPPET(NormalPositive);
```

Within the snippet of code specified using the `SET_CODE()` macro, when initialising neuron and postsynaptic model state variables, the `$(id)` variable can be used to access the id of the neuron being initialised. Similarly, when initialising weight update model state variables, the `$(id_pre)` and `$(id_post)` variables can be used to access the ids of the pre and postsynaptic neurons connected by the synapse being initialised.

### 9.9.2 Variable locations

Once you have defined **how** your variables are going to be initialised you need to configure **where** they will be allocated. By default memory is allocated for variables on both the GPU and the host. However, the following alternative 'variable locations' are available:

- [VarLocation::DEVICE](#) - Variables are only allocated on the GPU, saving memory but meaning that they can't easily be copied to the host - best for internal state variables.
- [VarLocation::HOST\\_DEVICE](#) - Variables are allocated on both the GPU and the host - the default.
- [VarLocation::HOST\\_DEVICE\\_ZERO\\_COPY](#) - Variables are allocated as 'zero-copy' memory accessible to the host and GPU - useful on devices such as Jetson TX1 where physical memory is shared between the GPU and CPU.

**Note**

'Zero copy' memory is only supported on newer embedded systems such as the Jetson TX1 where there is no physical separation between GPU and host memory and thus the same block of memory can be shared between them.

These modes can be set as a model default using `ModelSpec::setDefaultVarLocation` or on a per-variable basis using one of the following functions:

- `NeuronGroup::setSpikeLocation`
- `NeuronGroup::setSpikeEventLocation`
- `NeuronGroup::setSpikeTimeLocation`
- `NeuronGroup::setVarLocation`
- `SynapseGroup::setWUVarLocation`
- `SynapseGroup::setWUPreVarLocation`
- `SynapseGroup::setWUPostVarLocation`
- `SynapseGroup::setPSVarLocation`
- `SynapseGroup::setInSynVarLocation`

[Previous](#) | [Top](#) | [Next](#)

## 9.10 Sparse connectivity initialisation

Synaptic connectivity implemented using `SynapseMatrixConnectivity::SPARSE` and `SynapseMatrixConnectivity::BITMASK` can be automatically initialised.

This can be done using one of a number of predefined *sparse connectivity initialisation snippets*:

- `InitSparseConnectivitySnippet::OneToOne`
- `InitSparseConnectivitySnippet::FixedProbability`
- `InitSparseConnectivitySnippet::FixedProbabilityNoAutapse`

For example, to initialise synaptic connectivity with a 10% connection probability (allowing connections between neurons with the same id):

```
InitSparseConnectivitySnippet::FixedProbability::ParamValues fixedProb(0.1);  
model.addSynapsePopulation<...>(  
    ...  
    initConnectivity<InitSparseConnectivitySnippet::FixedProbability>(fixedProb));
```

### 9.10.1 Defining a new sparse connectivity snippet

Similarly to variable initialisation snippets, sparse connectivity initialisation snippets can be created by simply defining a class in the model description.

For example, the following sparse connectivity initialisation snippet could be used to initialise a 'ring' of connectivity where each neuron is connected to a number of subsequent neurons specified using the `numNeighbours` parameter:



```

class Ring : public InitSparseConnectivitySnippet::Base
{
public:
    DECLARE_SNIPPET(Ring, 1);

    SET_ROW_BUILD_STATE_VARS({{"offset", {"unsigned int", 1}}});
    SET_ROW_BUILD_CODE(
        "const unsigned int target = $(id_pre) + offset % $(num_post);\n"
        "$ (addSynapse, target);\n"
        "offset++;\n"
        "if(offset > (unsigned int)$ (numNeighbours)) {\n"
        "    $ (endRow);\n"
        "}\n");

    SET_PARAM_NAMES({"numNeighbours"});
    SET_CALC_MAX_ROW_LENGTH_FUNC(
        [](unsigned int numPre, unsigned int numPost, const std::vector<double> &pars)
        {
            return (unsigned int)pars[0];
        });
    SET_CALC_MAX_COL_LENGTH_FUNC(
        [](unsigned int numPre, unsigned int numPost, const std::vector<double> &pars)
        {
            return (unsigned int)pars[0];
        });
};
IMPLEMENT_SNIPPET(Ring);

```

Each *row* of sparse connectivity is initialised independantly by running the snippet of code specified using the `SET_ROW_BUILD_CODE()` macro within a loop. The `$(num_post)` variable can be used to access the number of neurons in the postsynaptic population and the `$(id_pre)` variable can be used to access the index of the presynaptic neuron associated with the row being generated. The `SET_ROW_BUILD_STATE_VARS()` macro can be used to initialise state variables outside of the loop - in this case `offset` which is used to count the number of synapses created in each row. Synapses are added to the row using the `$(addSynapse, target)` function and iteration is stopped using the `$(endRow)` function. To avoid having to manually call `SynapseGroup::setMaxConnections` and `SynapseGroup::setMaxSourceConnections`, sparse connectivity snippets can also provide code to calculate the maximum row and column lengths this connectivity will result in using the `SET_CALC_MAX_ROW_LENGTH_FUNC()` and `SET_CALC_MAX_COL_LENGTH_FUNC()` macros. Alternatively, if the maximum row or column length is constant, the `SET_MAX_ROW_LENGTH()` and `SET_MAX_COL_LENGTH()` shorthand macros can be used.

### 9.10.2 Sparse connectivity locations

Once you have defined **how** sparse connectivity is going to be initialised, similarly to variables, you can control **where** it is allocated. This is controlled using the same `VarLocations` options described in section [Variable locations](#) and can either be set using the model default specified with `ModelSpec::setDefaultSparseConnectivityLocation` or on a per-synapse group basis using `SynapseGroup::setSparseConnectivityLocation`.

[Previous](#) | [Top](#) | [Next](#)

## 10 Tutorial 1

In this tutorial we will go through step by step instructions how to create and run your first GeNN simulation from scratch.

### 10.1 The Model Definition

In this tutorial we will use a pre-defined Hodgkin-Huxley neuron model ([NeuronModels::TraubMiles](#)) and create a simulation consisting of ten such neurons without any synaptic connections. We will run this simulation on a GPU and save the results - firstly to stdout and then to file.

The first step is to write a model definition function in a model definition file. Create a new directory and, within that, create a new empty file called `tenHHModel.cc` using your favourite text editor, e.g.

```
>> emacs tenHHModel.cc &
```

**Note**

The ">>" in the example code snippets refers to a shell prompt in a unix shell, do not enter them as part of your shell commands.

The model definition file contains the definition of the network model we want to simulate. First, we need to include the GeNN model specification code `modelSpec.h`. Then the model definition takes the form of a function named `modelDefinition` that takes one argument, passed by reference, of type `ModelSpec`. Type in your `tenHHModel.cc` file:

```
// Model definition file tenHHModel.cc

#include "modelSpec.h"

void modelDefinition(ModelSpec &model)
{
    // definition of tenHHModel
}
```

Two standard elements to the `modelDefinition` function are setting the simulation step size and setting the name of the model:

```
model.setDT(0.1);
model.setName("tenHHModel");
```

**Note**

With this we have fixed the integration time step to 0.1 in the usual time units. The typical units in GeNN are ms, mV, nF, and  $\mu$ S. Therefore, this defines  $DT = 0.1$  ms.

Making the actual model definition makes use of the `ModelSpec::addNeuronPopulation` and `ModelSpec::addSynapsePopulation` member functions of the `ModelSpec` object. The arguments to a call to `ModelSpec::addNeuronPopulation` are

- `NeuronModel`: template parameter specifying the neuron model class to use
- `const std::string &name`: the name of the population
- `unsigned int size`: The number of neurons in the population
- `const NeuronModel::ParamValues &paramValues`: Parameter values for the neurons in the population
- `const NeuronModel::VarValues &varInitialisers`: Initial values or initialisation snippets for variables of this neuron type

We first create the parameter and initial variable arrays,

```
// definition of tenHHModel
NeuronModels::TraubMiles::ParamValues p(
    7.15,      // 0 - gNa: Na conductance in muS
    50.0,      // 1 - ENa: Na equi potential in mV
    1.43,      // 2 - gK: K conductance in muS
    -95.0,     // 3 - EK: K equi potential in mV
    0.02672,   // 4 - gl: leak conductance in muS
    -63.563,   // 5 - El: leak equi potential in mV
    0.143);    // 6 - Cmem: membr. capacity density in nF

NeuronModels::TraubMiles::VarValues ini(
    -60.0,     // 0 - membrane potential V
    0.0529324, // 1 - prob. for Na channel activation m
    0.3176767, // 2 - prob. for not Na channel blocking h
    0.5961207); // 3 - prob. for K channel activation n
```

**Note**

The comments are obviously only for clarity, they can in principle be omitted. To avoid any confusion about the meaning of parameters and variables, however, we recommend strongly to always include comments of this type.

Having defined the parameter values and initial values we can now create the neuron population,

```
model.addNeuronPopulation<NeuronModels::TraubMiles>("Pop1", 10,
p, ini);
```

This completes the model definition in this example. The complete `tenHHModel.cc` file now should look like this:

```
// Model definition file tenHHModel.cc

#include "modelSpec.h"

void modelDefinition(ModelSpec &model)
{
    // definition of tenHHModel
    model.setDT(0.1);
    model.setName("tenHHModel");

    NeuronModels::TraubMiles::ParamValues p(
        7.15,          // 0 - gNa: Na conductance in muS
        50.0,          // 1 - ENa: Na equi potential in mV
        1.43,          // 2 - gK: K conductance in muS
        -95.0,         // 3 - EK: K equi potential in mV
        0.02672,       // 4 - gl: leak conductance in muS
        -63.563,       // 5 - El: leak equi potential in mV
        0.143);        // 6 - Cmem: membr. capacity density in nF

    NeuronModels::TraubMiles::VarValues ini(
        -60.0,         // 0 - membrane potential V
        0.0529324,     // 1 - prob. for Na channel activation m
        0.3176767,     // 2 - prob. for not Na channel blocking h
        0.5961207);    // 3 - prob. for K channel activation n

    model.addNeuronPopulation<NeuronModels::TraubMiles>("Pop1",
        10, p, ini);
}
```

This model definition suffices to generate code for simulating the ten Hodgkin-Huxley neurons on the a GPU or CPU. The second part of a GeNN simulation is the user code that sets up the simulation, does the data handling for input and output and generally defines the numerical experiment to be run.

**10.2 Building the model**

To use GeNN to build your model description into simulation code, use a terminal to navigate to the directory containing your `tenHHModel.cc` file and, on Linux or Mac, type:

```
>> genn-buildmodel.sh tenHHModel.cc
```

Alternatively, on Windows, type:

```
>> genn-buildmodel.bat tenHHModel.cc
```

If you don't have an NVIDIA GPU and are running GeNN in CPU\_ONLY mode, you can invoke `genn-buildmodel` with a `-c` option so, on Linux or Mac:

```
>> genn-buildmodel.sh -c tenHHModel.cc
```

or on Windows:

```
>> genn-buildmodel.bat -c tenHHModel.cc
```

If GeNN has been added to your path and `CUDA_PATH` is correctly configured, you should see some compile output ending in `Model build complete ....`

### 10.3 User Code

GeNN will now have generated the code to simulate the model for one timestep using a function `stepTime()`. To make use of this code, we need to define a minimal C/C++ main function. For the purposes of this tutorial we will initially simply run the model for one simulated second and record the final neuron variables into a file. Open a new empty file `tenHHSimulation.cc` in an editor and type

```
// tenHHModel simulation code
#include "tenHHModel_CODE/definitions.h"

int main()
{
    allocateMem();
    initialize();
    return 0;
}
```

This boiler plate code includes the header file for the generated code `definitions.h` in the subdirectory `tenHHModel_CODE` where GeNN deposits all generated code (this corresponds to the name passed to the `ModelSpec::setName` function). Calling `allocateMem()` allocates the memory structures for all neuron variables and `initialize()` launches a GPU kernel which initialise all state variables to their initial values. Now we can use the generated code to integrate the neuron equations provided by GeNN for 1000ms. To do so, we add after `initialize()`;

#### Note

The `t` variable is provided by GeNN to keep track of the current simulation time in milliseconds.

```
while (t < 1000.0f) {
    stepTime();
}
```

and we need to copy the result back to the host before outputting it to stdout (this will do nothing if you are running the model on a CPU),

```
pullPop1StateFromDevice();
for (int j= 0; j < 10; j++) {
    std::cout << VPop1[j] << " ";
    std::cout << mPop1[j] << " ";
    std::cout << hPop1[j] << " ";
    std::cout << nPop1[j] << std::endl;
}
```

`pullPop1StateFromDevice()` copies all relevant state variables of the `Pop1` neuron group from the GPU to the CPU main memory. Then we can output the results to stdout by looping through all 10 neurons and outputting the state variables `VPop1`, `mPop1`, `hPop1`, `nPop1`.

#### Note

The naming convention for variables in GeNN is the variable name defined by the neuron type, here `TraubMiles` defining `V`, `m`, `h`, and `n`, followed by the population name, here `Pop1`.

This completes the user code. The complete `tenHHSimulation.cc` file should now look like

```
// tenHHModel simulation code
#include "tenHHModel_CODE/definitions.h"

int main()
{
    allocateMem();
    initialize();

    while (t < 1000.0f) {
        stepTime();
    }
    pullPop1StateFromDevice();

    for (int j= 0; j < 10; j++) {
        std::cout << VPop1[j] << " ";
    }
}
```

```

        std::cout << mPop1[j] << " ";
        std::cout << hPop1[j] << " ";
        std::cout << nPop1[j] << std::endl;
    }
    return 0;
}

```

## 10.4 Building the simulator (Linux or Mac)

On Linux and Mac, GeNN simulations are typically built using a simple Makefile which can be generated with the following command:

```
genn-create-user-project.sh tennHHModel tenHHSimulation.cc
```

This defines that the model is named `tennHHModel` and the simulation code is given in the file `tenHHSimulation.cc` that we completed above. Now type

```
make
```

## 10.5 Building the simulator (Windows)

So that projects can be easily debugged within the Visual Studio IDE (see section [Debugging suggestions](#) for more details), Windows projects are built using an MSBuild script typically with the same title as the final executable. A suitable solution and project can be generated automatically with the following command:

```
genn-create-user-project.bat tennHHModel tenHHSimulation.cc
```

This defines that the model is named `tennHHModel` and the simulation code is given in the file `tenHHSimulation.cc` that we completed above. Now type

```
msbuild tennHHModel.sln /p:Configuration=Release /t:tennHHModel
```

## 10.6 Running the Simulation

You can now execute your newly-built simulator on Linux or Mac with

```
./tennHHModel
```

Or on Windows with

```
tennHHModel_Release
```

The output you obtain should look like

```

-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243
-63.7838 0.0350042 0.336314 0.563243

```

## 10.7 Reading

This is not particularly interesting as we are just observing the final value of the membrane potentials. To see what is going on in the meantime, we need to copy intermediate values from the device and save them into a file. This can be done in many ways but one sensible way of doing this is to replace the calls to `stepTime` in `tenHHSimulation.cc` with something like this:

```
std::ofstream os("tenHH_output.V.dat");
while (t < 1000.0f) {
    stepTime();

    pullVPop1FromDevice();

    os << t << " ";
    for (int j= 0; j < 10; j++) {
        os << VPop1[j] << " ";
    }
    os << std::endl;
}
os.close();
```


### Note

`t` is a global variable updated by the GeNN code to keep track of elapsed simulation time in ms.  
 we switched from using `pullPop1StateFromDevice()` to `pullVPop1FromDevice()` as we are now only interested in the membrane voltage of the neuron.

You will also need to add:

```
#include <fstream>
```

to the top of `tenHHSimulation.cc`. After building the model; and building and running the simulator as described above there should be a file `tenHH_output.V.dat` in the same directory. If you plot column one (time) against the subsequent 10 columns (voltage of the 10 neurons), you should observe dynamics like this:



However so far, the neurons are not connected and do not receive input. As the [NeuronModels::TraubMiles](#) model is silent in such conditions, the membrane voltages of the 10 neurons will simply drift from the -60mV they were initialised at to their resting potential.

[Previous](#) | [Top](#) | [Next](#)

## 11 Tutorial 2

In this tutorial we will learn to add synapsePopulations to connect neurons in neuron groups to each other with synaptic models. As an example we will connect the ten Hodgkin-Huxley neurons from tutorial 1 in a ring of excitatory synapses.

First, copy the files from Tutorial 1 into a new directory and rename the `tenHHModel.cc` to `tenHHRingModel.cc` and `tenHHSimulation.cc` to `tenHHRingSimulation.cc`, e.g. on Linux or Mac:

```
>> cp -r tenHH_project tenHHRing_project
>> cd tenHHRing_project
>> mv tenHHModel.cc tenHHRingModel.cc
>> mv tenHHSimulation.cc tenHHRingSimulation.cc
```

Finally, to reduce confusion we should rename the model itself. Open `tenHHRingModel.cc`, change the model name inside,

```
model.setName("tenHHRing");
```

### 11.1 Defining the Detailed Synaptic Connections

We want to connect our ten neurons into a ring where each neuron connects to its neighbours. In order to initialise this connectivity we need to add a sparse connectivity initialisation snippet at the top of `tenHHRingModel.cc`:

```
class Ring : public InitSparseConnectivitySnippet::Base
{
public:
    DECLARE_SNIPPET(Ring, 0);
    SET_ROW_BUILD_CODE(
        "$ (addSynapse, ($ (id_pre) + 1) % $ (num_post));\n"
        "$ (endRow);\n");
    SET_MAX_ROW_LENGTH(1);
};
IMPLEMENT_SNIPPET(Ring);
```

The `SET_ROW_BUILD_CODE` code string will be called to generate each row of the synaptic matrix (connections coming from a single presynaptic neuron) and, in this case, each row consists of a single synapses from the presynaptic neuron `$(id_pre)` to `$(id_pre) + 1` (the modulus operator is used to ensure that the final connection between neuron 9 and 0 is made correctly). In order to allow GeNN to better optimise the generated code we also provide a maximum row length. In this case each row always contains only one synapse but, when more complex connectivity is used, the number of neurons in the pre and postsynaptic population as well as any parameters used to configure the snippet can be accessed from this function.

#### Note

When defining GeNN code strings, the `$(VariableName)` syntax is used to refer to variables provided by GeNN and the `$(FunctionName, Parameter1,...)` syntax is used to call functions provided by GeNN.

### 11.2 Adding Synaptic connections

Now we need additional initial values and parameters for the synapse and post-synaptic models. We will use the standard `WeightUpdateModels::StaticPulse` weight update model and `PostsynapticModels::ExpCond` post-synaptic model. They need the following initial variables and parameters:

```
WeightUpdateModels::StaticPulse::VarValues s_ini(
    -0.2); // 0 - g: the synaptic conductance value

PostsynapticModels::ExpCond::ParamValues ps_p(
    1.0, // 0 - tau_S: decay time constant for S [ms]
    -80.0); // 1 - Erev: Reversal potential
```

## Note

the `WeightUpdateModels::StaticPulse` weight update model has no parameters and the `PostsynapticModels::ExpCond` post-synaptic model has no state variables.

We can then add a synapse population at the end of the `modelDefinition(...)` function,

```
model.addSynapsePopulation<WeightUpdateModels::StaticPulse
, PostsynapticModels::ExpCond>(
    "Pop1self", SynapseMatrixType::SPARSE_GLOBALG, 10,
    "Pop1", "Pop1",
    {}, s_ini,
    ps_p, {},
    initConnectivity<Ring>());
```

The `addSynapsePopulation` parameters are

- `WeightUpdateModel`: template parameter specifying the type of weight update model (derived from `WeightUpdateModels::Base`).
- `PostsynapticModel`: template parameter specifying the type of postsynaptic model (derived from `PostsynapticModels::Base`).
- name string containing unique name of synapse population.
- `mtype` how the synaptic matrix associated with this synapse population should be represented. Here `SynapseMatrixType::SPARSE_GLOBALG` means that there will be sparse connectivity and each connection will have the same weight (-0.2 as specified previously).
- `delayStep` integer specifying number of timesteps of propagation delay that spikes travelling through this synapses population should incur (or `NO_DELAY` for none)
- `src` string specifying name of presynaptic (source) population
- `trg` string specifying name of postsynaptic (target) population
- `weightParamValues` parameters for weight update model wrapped in `WeightUpdateModel::ParamValues` object.
- `weightVarInitialisers` initial values or initialisation snippets for the weight update model's state variables wrapped in a `WeightUpdateModel::VarValues` object.
- `postsynapticParamValues` parameters for postsynaptic model wrapped in `PostsynapticModel::ParamValues` object.
- `postsynapticVarInitialisers` initial values or initialisation snippets for the postsynaptic model wrapped in `PostsynapticModel::VarValues` object.
- `connectivityInitialiser` snippet and any paramaters (in this case there are none) used to initialise the synapse population's sparse connectivity.

Adding the `addSynapsePopulation` command to the model definition informs GeNN that there will be synapses between the named neuron populations, here between population `Pop1` and itself. At this point our model definition file `tenHHRingModel.cc` should look like this

```
// Model definition file tenHHRing.cc
#include "modelSpec.h"

class Ring : public InitSparseConnectivitySnippet::Base
{
public:
    DECLARE_SNIPPET(Ring, 0);
    SET_ROW_BUILD_CODE(
        "$(addSynapse, ($(id_pre) + 1) % $(num_post));\n"
        "$ (endRow);\n");
    SET_MAX_ROW_LENGTH(1);
};
IMPLEMENT_SNIPPET(Ring);
```



```

void modelDefinition(ModelSpec &model)
{
    // definition of tenHHRing
    model.setDT(0.1);
    model.setName("tenHHRing");

    NeuronModels::TraubMiles::ParamValues p(
        7.15,          // 0 - gNa: Na conductance in muS
        50.0,          // 1 - ENa: Na equi potential in mV
        1.43,          // 2 - gK: K conductance in muS
        -95.0,         // 3 - EK: K equi potential in mV
        0.02672,       // 4 - gl: leak conductance in muS
        -63.563,       // 5 - El: leak equi potential in mV
        0.143);        // 6 - Cmem: membr. capacity density in nF

    NeuronModels::TraubMiles::VarValues ini(
        -60.0,         // 0 - membrane potential V
        0.0529324,     // 1 - prob. for Na channel activation m
        0.3176767,     // 2 - prob. for not Na channel blocking h
        0.5961207);    // 3 - prob. for K channel activation n

    model.addNeuronPopulation<NeuronModels::TraubMiles>("Pop1",
        10, p, ini);

    WeightUpdateModels::StaticPulse::VarValues s_ini(
        -0.2); // 0 - g: the synaptic conductance value

    PostsynapticModels::ExpCond::ParamValues ps_p(
        1.0,         // 0 - tau_S: decay time constant for S [ms]
        -80.0);      // 1 - Erev: Reversal potential

    model.addSynapsePopulation<
        WeightUpdateModels::StaticPulse,
        PostsynapticModels::ExpCond>(
        "Pop1self", SynapseMatrixType::SPARSE_GLOBALG, 100,
        "Pop1", "Pop1",
        {}, s_ini,
        ps_p, {});
    initConnectivity<Ring>();
}

```

We can now build our new model:

```
>> genn-buildmodel.sh tenHHRingModel.cc
```

### Note

Again, if you don't have an NVIDIA GPU and are running GeNN in CPU\_ONLY mode, you can instead build with the `-c` option as described in [Tutorial 1](#).

Now we can open the `tenHHRingSimulation.cc` file and update the file name of the model includes to match the name we set previously:

```


// tenHHRingModel simulation code
#include "tenHHRing_CODE/definitions.h"

```

Additionally, we need to add a call to a second initialisation function to `main()` after we call `initialize()`:

```
initializeSparse();
```

This initializes any variables associated with the sparse connectivity we have added (and will also copy any manually initialised variables to the GPU). Then, after using the `genn-create-user-project` tool to create a new project with a model name of `tenHHRing` and using `tenHHRingSimulation.cc` rather than `tenHHRingSimulation.cc`, we can build and run our new simulator in the same way we did in [Tutorial 1](#). However, even after all our hard work, if we plot the content of the first column against the subsequent 10 columns of `tenHHRingExample.V.dat` it looks very similar to the plot we obtained at the end of [Tutorial 1](#).



This is because none of the neurons are spiking so there are no spikes to propagate around the ring.

### 11.3 Providing initial stimuli

We can use a [NeuronModels::SpikeSource](#) to inject an initial spike into the first neuron in the ring during the first timestep to start spikes propagating. Firstly we need to define another sparse connectivity initialisation snippet at the top of `tenHHRingModel.cc` which simply creates a single synapse on the first row of the synaptic matrix:

```
class FirstToFirst : public InitSparseConnectivitySnippet::Base
{
public:
    DECLARE_SNIPPET(FirstToFirst, 0);
    SET_ROW_BUILD_CODE(
        "if($(id_pre) == 0) {\n"
        "    $(addSynapse, $(id_pre));\n"
        "}\n"
        " $(endRow);\n");
    SET_MAX_ROW_LENGTH(1);
};
IMPLEMENT_SNIPPET(FirstToFirst);
```

We then need to add it to the network by adding the following to the end of the `modelDefinition(...)` function:

```
model.addNeuronPopulation<NeuronModels::SpikeSource>("Stim", 1,
    {}, {});
model.addSynapsePopulation<WeightUpdateModels::StaticPulse
    , PostsynapticModels::ExpCond>(
    "StimPop1", SynapseMatrixType::SPARSE_GLOBALG,
    NO_DELAY,
    "Stim", "Pop1",
    {}, s_ini,
    ps_p, {},
    initConnectivity<FirstToFirst>());
```

and finally inject a spike in the first timestep (in the same way that the `t` variable is provided by GeNN to keep track of the current simulation time in milliseconds, `iT` is provided to keep track of it in timesteps):

```
if(iT == 0) {
    spikeCount_Stim = 1;
    spike_Stim[0] = 0;
    pushStimCurrentSpikesToDevice();
}
```

**Note**

`spike_Stim[n]` is used to specify the indices of the neurons in population `Stim` spikes which should emit spikes where  $n \in [0, \text{spikeCount\_Stim})$ .

At this point our user code `tenHHRingModel.cc` should look like this

```
// Model definition file tenHHRing.cc
#include "modelSpec.h"

class Ring : public InitSparseConnectivitySnippet::Base
{
public:
    DECLARE_SNIPPET(Ring, 0);
    SET_ROW_BUILD_CODE(
        "$ (addSynapse, ($ (id_pre) + 1) % $ (num_post));\n"
        "$ (endRow);\n");
    SET_MAX_ROW_LENGTH(1);
};
IMPLEMENT_SNIPPET(Ring);

class FirstToFirst : public InitSparseConnectivitySnippet::Base
{
public:
    DECLARE_SNIPPET(FirstToFirst, 0);
    SET_ROW_BUILD_CODE(
        "if ($ (id_pre) == 0) {\n"
        "    $ (addSynapse, $ (id_pre));\n"
        "}\n"
        "$ (endRow);\n");
    SET_MAX_ROW_LENGTH(1);
};
IMPLEMENT_SNIPPET(FirstToFirst);

void modelDefinition(ModelSpec &model)
{
    // definition of tenHHRing
    model.setDT(0.1);
    model.setName("tenHHRing");

    NeuronModels::TraubMiles::ParamValues p(
        7.15,        // 0 - gNa: Na conductance in muS
        50.0,        // 1 - ENa: Na equi potential in mV
        1.43,        // 2 - gK: K conductance in muS
        -95.0,       // 3 - EK: K equi potential in mV
        0.02672,     // 4 - gl: leak conductance in muS
        -63.563,     // 5 - El: leak equi potential in mV
        0.143);      // 6 - Cmem: membr. capacity density in nF

    NeuronModels::TraubMiles::VarValues ini(
        -60.0,       // 0 - membrane potential V
        0.0529324,   // 1 - prob. for Na channel activation m
        0.3176767,   // 2 - prob. for not Na channel blocking h
        0.5961207);  // 3 - prob. for K channel activation n

    model.addNeuronPopulation<NeuronModels::TraubMiles>("Pop1",
        10, p, ini);
    model.addNeuronPopulation<NeuronModels::SpikeSource>("Stim"
        , 1, {}, {});

    WeightUpdateModels::StaticPulse::VarValues s_ini(
        -0.2); // 0 - g: the synaptic conductance value

    PostsynapticModels::ExpCond::ParamValues ps_p(
        1.0,      // 0 - tau_S: decay time constant for S [ms]
        -80.0);   // 1 - Erev: Reversal potential

    model.addSynapsePopulation<
        WeightUpdateModels::StaticPulse,
        PostsynapticModels::ExpCond>(
        "Pop1self", SynapseMatrixType::SPARSE_GLOBALG, 100,
        "Pop1", "Pop1",
        {}, s_ini,
        ps_p, {},
        initConnectivity<Ring>());

    model.addSynapsePopulation<
        WeightUpdateModels::StaticPulse,
        PostsynapticModels::ExpCond>(
        "StimPop1", SynapseMatrixType::SPARSE_GLOBALG,
        NO_DELAY,
        "Stim", "Pop1",
        {}, s_ini,
        ps_p, {},
        initConnectivity<FirstToFirst>());
}
```

```

}
```

and `tenHHRingSimulation.cc` should look like this:

```

// Standard C++ includes
#include <fstream>

// tenHHRing simulation code
#include "tenHHRing_CODE/definitions.h"


int main()
{
    allocateMem();
    initialize();
    initializeSparse();

    std::ofstream os("tenHHRing_output.V.dat");
    while(t < 200.0f) {
        if(iT == 0) {
            glbSpkStim[0] = 0;
            glbSpkCntStim[0] = 1;
            pushStimCurrentSpikesToDevice();
        }

        stepTimeU();
        pullVPoplFromDevice();

        os << t << " ";
        for (int j= 0; j < 10; j++) {
            os << VPopl[j] << " ";
        }
        os << std::endl;
    }
    os.close();
    return 0;
}
```

Finally if we build, make and run this model; and plot the first 200 ms of the ten neurons' membrane voltages - they now looks like this:



[Previous](#) | [Top](#) | [Next](#)

## 12 Best practices guide

GeNN generates code according to the network model defined by the user, and allows users to include the generated code in their programs as they want. Here we provide a guideline to setup GeNN and use generated functions. We recommend users to also have a look at the [Examples](#), and to follow the tutorials [Tutorial 1](#) and [Tutorial 2](#).

## 12.1 Creating and simulating a network model

The user is first expected to create an object of class `ModelSpec` by creating the function `modelDefinition()` which includes calls to following methods:

- `ModelSpec::setDT();`
- `ModelSpec::setName();`

Then add neuron populations by:

- `ModelSpec::addNeuronPopulation();`

for each neuron population. Add synapse populations by:

- `ModelSpec::addSynapsePopulation();`

for each synapse population.

Other optional functions are explained in `ModelSpec` class reference. At the end the function should look like this:

```
void modelDefinition(ModelSpec &model) {
    model.setDT(0.5);
    model.setName("YourModelName");
    model.addNeuronPopulation(...);
    ...
    model.addSynapsePopulation(...);
    ...
}
```

`modelSpec.h` should be included in the file where this function is defined.

This function will be called by `generateALL.cc` to create corresponding CPU and GPU simulation codes under the `<YourModelName>_CODE` directory.

These functions can then be used in a `.cc` file which runs the simulation. This file should include `<YourModelName>_CODE/definitions.h`. Generated code differ from one model to the other, but core functions are the same and they should be called in correct order. First, the following variables should be defined and initialized:

- `ModelSpec` model // initialized by calling `modelDefinition(model)`
- Array containing current input (if any)

Any variables marked as uninitialised using the `uninitialisedVar()` function or sparse connectivity not initialised using a snippet must be initialised by the user between calls to `initialize()` and `initializeSparse()`. Core functions generated by GeNN to be included in the user code include:

- `allocateMem()`
- `initialize()`
- `initializeSparse()`
- `get<neuron name>CurrentSpikes()`
- `get<neuron name>CurrentSpikeCount()`
- `stepTime()`
- `freeMem()`

In order to correctly access neuron state and spikes for the current timestep, correctly accounting for delay buffering etc, you can use the `getCurrent<var name><neuron name>()`, `get<neuron name>CurrentSpikes()` and `'get<neuron name>CurrentSpikeCount()` functions. By setting `GENN_PREFERENCES::automaticCopy`, GeNN can be used in a simple mode where CUDA automatically transfers data between the GPU and CPU when required (see <https://devblogs.nvidia.com/unified-memory-cuda-beginners/>). However, copying elements between the GPU and the host memory is costly in terms of performance and the automatic copying operates on a fairly coarse grain (pages are approximately 4 bytes). Therefore, in order to maximise performance, we recommend you do not use automatic copying and instead manually call the following functions when required:

- `push<neuron or synapse name>StateToDevice()`
- `pull<neuron or synapse name>StateFromDevice()`
- `push<neuron name>SpikesToDevice()`
- `pull<neuron name>SpikesFromDevice()`
- `push<neuron name>SpikesEventsToDevice()`
- `pull<neuron name>SpikesEventsFromDevice()`
- `push<neuron name>SpikeTimesToDevice()`
- `pull<neuron name>SpikeTimesFromDevice()`
- `push<neuron name>CurrentSpikesToDevice()`
- `pull<neuron name>CurrentSpikesFromDevice()`
- `push<neuron name>CurrentSpikesEventsToDevice()`
- `pull<neuron name>CurrentSpikesEventsFromDevice()`
- `pull<synapse name>ConnectivityFromDevice()`
- `push<synapse name>ConnectivityToDevice()`
- `pull<var name><neuron or synapse name>FromDevice()`
- `push<var name><neuron or synapse name>ToDevice()`
- `pushCurrent<var name><neuron name>ToDevice()`
- `pullCurrent<var name><neuron name>FromDevice()`
- `getCurrent<var name><neuron name>()`
- `copyStateToDevice()`
- `copyStateFromDevice()`
- `copyCurrentSpikesFromDevice()`
- `copyCurrentSpikesEventsFromDevice()`

You can use the `push<neuron or synapse name>StateToDevice()` to copy from the host to the GPU. At the end of your simulation, if you want to access the variables you need to copy them back from the device using the `pull<neuron or synapse name>StateFromDevice()` function or one of the more fine-grained functions listed above.

### 12.1.1 Extra Global Parameters

If extra global parameters have a "scalar" type such as `float` they can be set directly from simulation code. For example the extra global parameter "reward" of population "Pop" could be set with:

```
rewardPop = 5.0f;
```

However, if extra global parameters have a pointer type such as `float*`, GeNN generates additional functions to allocate, free and copy these variables between host and device:

- `allocate<var name><neuron or synapse name>`
- `free<var name><neuron or synapse name>`
- `push<var name><neuron or synapse name>ToDevice`
- `pull<var name><neuron or synapse name>FromDevice` These operate in much the same manner as the functions for interacting with standard variables described above but the `allocate`, `push` and `pull` functions all take a "count" parameter specifying how many entries the extra global parameter array should be.

## 12.2 Floating point precision

Double precision floating point numbers are supported by devices with compute capability 1.3 or higher. If you have an older GPU, you need to use single precision floating point in your models and simulation.

GPUs are designed to work better with single precision while double precision is the standard for CPUs. This difference should be kept in mind while comparing performance.

While setting up the network for GeNN, double precision floating point numbers are used as this part is done on the CPU. For the simulation, GeNN lets users choose between single or double precision. Overall, new variables in the generated code are defined with the precision specified by `ModelSpec::setPrecision(unsigned int)`, providing `GENN_FLOAT` or `GENN_DOUBLE` as argument. `GENN_FLOAT` is the default value. The keyword `scalar` can be used in the user-defined model codes for a variable that could either be single or double precision. This keyword is detected at code generation and substituted with "float" or "double" according to the precision set by `ModelSpec::setPrecision(unsigned int)`.

There may be ambiguities in arithmetic operations using explicit numbers. Standard C compilers presume that any number defined as "X" is an integer and any number defined as "X.Y" is a double. Make sure to use the same precision in your operations in order to avoid performance loss.

## 12.3 Working with variables in GeNN

### 12.3.1 Model variables

User-defined model variables originate from classes derived off the `NeuronModels::Base`, `WeightUpdateModels::Base` or `PostsynapticModels::Base` classes. The name of model variable is defined in the model type, i.e. with a statement such as

```
SET_VARS({{"V", "scalar"}});
```

When a neuron or synapse population using this model is added to the model, the full GeNN name of the variable will be obtained by concatenating the variable name with the name of the population. For example if we add a population called `Pop` using a model which contains our `V` variable, a variable `VPop` of type `scalar*` will be available in the global namespace of the simulation program. GeNN will pre-allocate this C array to the correct size of elements corresponding to the size of the neuron population. GeNN will also free these variables when the provided function `freeMem()` is called. Users can otherwise manipulate these variable arrays as they wish. For convenience, GeNN provides functions to copy each state variable from the device into host memory and vice versa e.g. `pullVPopFromDevice()` and `pushVPoptoDevice()`. Alternatively, all state variables associated with a population can be copied using a single call E.g.

```
pullPopStateFromDevice();
```

These conventions also apply to the the variables of postsynaptic and weight update models.

#### Note

Be aware that the above naming conventions do assume that variables from the weightupdate models and the postSynModels that are used together in a synapse population are unique. If both the weightupdate model and the postSynModel have a variable of the same name, the behaviour is undefined.

### 12.3.2 Built-in Variables in GeNN

GeNN has no explicitly hard-coded synapse and neuron variables. Users are free to name the variable of their models as they want. However, there are some reserved variables that are used for intermediary calculations and communication between different parts of the generated code. They can be used in the user defined code but no other variables should be defined with these names.

- `DT` : Time step (typically in ms) for simulation; Neuron integration can be done in multiple sub-steps inside the neuron model for numerical stability (see Traub-Miles and Izhikevich neuron model variations in [Neuron models](#)).
- `inSyn` : This is an intermediary synapse variable which contains the summed input into a postsynaptic neuron (originating from the `addtoinSyn` variables of the incoming synapses) .
- `Isyn` : This is a local variable which contains the (summed) input current to a neuron. It is typically the sum of any explicit current input and all synaptic inputs. The way its value is calculated during the update of the postsynaptic neuron is defined by the code provided in the postsynaptic model. For example, the standard [PostsynapticModels::ExpCond](#) postsynaptic model defines

```
SET_APPLY_INPUT_CODE ("$(Isyn) += $(inSyn) * ($ (E) - $ (V)) ");
```

which implements a conductance based synapse in which the postsynaptic current is given by  $I_{\text{syn}} = g * s * (V_{\text{rev}} - V_{\text{post}})$ .

The value resulting from the current converter code is assigned to `Isyn` and can then be used in neuron sim code like so:

```
$(V) += (-$(V) + $(Isyn)) * DT
```

- `sT` : This is a neuron variable containing the last spike time of each neuron and is automatically generated for pre and postsynaptic neuron groups if they are connected using a synapse population with a weight update model that has [SET\\_NEEDS\\_PRE\\_SPIKE\\_TIME\(true\)](#) or [SET\\_NEEDS\\_POST\\_SPIKE\\_TIME\(true\)](#) set.

In addition to these variables, neuron variables can be referred to in the synapse models by calling `$(<neuronVarName>_pre)` for the presynaptic neuron population, and `$(<neuronVarName>_post)` for the postsynaptic population. For example, `$(sT_pre)`, `$(sT_post)`, `$(V_pre)`, etc.

## 12.4 Debugging suggestions

In Linux, users can call `cuda-gdb` to debug on the GPU. Example projects in the `userproject` directory come with a flag to enable debugging (`-debug`). `genn-buildmodel.sh` has a debug flag (`-d`) to generate debugging data. If you are executing a project with debugging on, the code will be compiled with `-g -G` flags. In CPU mode the executable will be run in `gdb`, and in GPU mode it will be run in `cuda-gdb` in `tui` mode.



**Note**

Do not forget to switch debugging flags -g and -G off after debugging is complete as they may negatively affect performance.

On Mac, some versions of `clang` aren't supported by the CUDA toolkit. This is a recurring problem on Fedora as well, where CUDA doesn't keep up with GCC releases. You can either hack the CUDA header which checks compiler versions - `cuda/include/host_config.h` - or just use an older XCode version (6.4 works fine).

On Windows models can also be debugged and developed by opening the `sln` file used to build the model in Visual Studio. From here files can be added to the project, build settings can be adjusted and the full suite of Visual Studio debugging and profiling tools can be used.

**Note**

When opening the models in the `userproject` directory in Visual Studio, right-click on the project in the solution explorer, select 'Properties'. Then, making sure the desired configuration is selected, navigate to 'Debugging' under 'Configuration Properties', set the 'Working Directory' to `'.'` and the 'Command Arguments' to match those passed to `genn-buildmodel` e.g. `'outdir'` to use an output directory called `outdir`.

[Previous](#) | [Top](#) | [Next](#)

## 13 Credits

GeNN was created by Thomas Nowotny.

GeNN is currently maintained and developed by James Knight.

Current sources and PyGeNN were first implemented by Anton Komissarov.

Izhikevich model and sparse connectivity by Esin Yavuz.

Block size optimisations, delayed synapses and page-locked memory by James Turner.

Automatic brackets and dense-to-sparse network conversion helper tools by Alan Diamond.

User-defined synaptic and postsynaptic methods by Alex Cope and Esin Yavuz.

Example projects were provided by Alan Diamond, James Turner, Esin Yavuz and Thomas Nowotny.

MPI support was largely developed by Mengchi Zhang.

[Previous](#)

## 14 Namespace Index

### 14.1 Namespace List

Here is a list of all namespaces with brief descriptions:

<b><a href="#">CodeGenerator</a></b>	
Helper class for generating code - automatically inserts brackets, indents etc	<b>71</b>
<b><a href="#">CodeGenerator::CUDA</a></b>	<b>78</b>
<b><a href="#">CodeGenerator::CUDA::Optimiser</a></b>	<b>80</b>
<b><a href="#">CodeGenerator::CUDA::PresynapticUpdateStrategy</a></b>	<b>80</b>

<a href="#">CodeGenerator::SingleThreadedCPU</a>	80
<a href="#">CodeGenerator::SingleThreadedCPU::Optimiser</a>	81
<a href="#">CurrentSourceModels</a>	81
<a href="#">filesystem</a>	81
<a href="#">InitSparseConnectivitySnippet</a>	
Base class for all sparse connectivity initialisation snippets	81
<a href="#">InitVarSnippet</a>	
Base class for all value initialisation snippets	82
<a href="#">Logging</a>	82
<a href="#">Models</a>	83
<a href="#">NeuronModels</a>	83
<a href="#">plog</a>	84
<a href="#">PostsynapticModels</a>	84
<a href="#">pugi</a>	84
<a href="#">pygenn</a>	84
<a href="#">pygenn.genn_groups</a>	84
<a href="#">pygenn.genn_model</a>	85
<a href="#">pygenn.model_preprocessor</a>	92
<a href="#">Snippet</a>	97
<a href="#">SpineMLSimulator</a>	97
<a href="#">SpineMLSimulator::Connectors</a>	98
<a href="#">SpineMLSimulator::Input</a>	98
<a href="#">SpineMLSimulator::InputValue</a>	98
<a href="#">SpineMLSimulator::LogOutput</a>	99
<a href="#">SpineMLSimulator::ModelProperty</a>	99
<a href="#">Utils</a>	100
<a href="#">WeightUpdateModels</a>	101

## 15 Hierarchical Index

### 15.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

<a href="#">AnalogueRecorder&lt; T &gt;</a>	107
<a href="#">CodeGenerator::BackendBase</a>	134

CodeGenerator::CUDA::Backend	107
CodeGenerator::SingleThreadedCPU::Backend	122
Snippet::Base	156
InitSparseConnectivitySnippet::Base	150
InitSparseConnectivitySnippet::FixedProbabilityBase	200
InitSparseConnectivitySnippet::FixedProbability	199
InitSparseConnectivitySnippet::FixedProbabilityNoAutapse	201
InitSparseConnectivitySnippet::OneToOne	263
InitSparseConnectivitySnippet::Uninitialised	362
InitVarSnippet::Base	151
InitVarSnippet::Constant	172
InitVarSnippet::Exponential	192
InitVarSnippet::Gamma	204
InitVarSnippet::Normal	261
InitVarSnippet::Uniform	359
InitVarSnippet::Uninitialised	361
Models::Base	152
CurrentSourceModels::Base	149
CurrentSourceModels::DC	182
CurrentSourceModels::GaussianNoise	205
NeuronModels::Base	153
NeuronModels::Izhikevich	223
NeuronModels::IzhikevichVariable	225
NeuronModels::LIF	227
NeuronModels::Poisson	269
NeuronModels::PoissonNew	272
NeuronModels::RulkovMap	290
NeuronModels::SpikeSource	305
NeuronModels::SpikeSourceArray	307
NeuronModels::TraubMiles	351
NeuronModels::TraubMilesAlt	354
NeuronModels::TraubMilesFast	356

NeuronModels::TraubMilesNStep	358
PostsynapticModels::Base	158
PostsynapticModels::DeltaCurr	184
PostsynapticModels::ExpCond	187
PostsynapticModels::ExpCurr	190
WeightUpdateModels::Base	161
WeightUpdateModels::PiecewiseSTDP	265
WeightUpdateModels::StaticGraded	314
WeightUpdateModels::StaticPulse	316
WeightUpdateModels::StaticPulseDendriticDelay	317
CodeGenerator::CUDA::PresynapticUpdateStrategy::Base	159
CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan	276
CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask	278
CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan	284
CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural	286
SpineMLSimulator::Input::Base	164
SpineMLSimulator::Input::Analogue	101
SpineMLSimulator::Input::SpikeBase	303
SpineMLSimulator::Input::InterSpikeIntervalBase	221
SpineMLSimulator::Input::PoissonSpikeRate	274
SpineMLSimulator::Input::RegularSpikeRate	289
SpineMLSimulator::Input::SpikeTime	310
SpineMLSimulator::InputValue::Base	166
SpineMLSimulator::InputValue::ConstantArray	174
SpineMLSimulator::InputValue::External	193
SpineMLSimulator::InputValue::ExternalNetwork	195
SpineMLSimulator::InputValue::ScalarBase	293
SpineMLSimulator::InputValue::Constant	173
SpineMLSimulator::InputValue::TimeVarying	349
SpineMLSimulator::InputValue::TimeVaryingArray	350
SpineMLSimulator::LogOutput::Base	167
SpineMLSimulator::LogOutput::AnalogueBase	102

SpineMLSimulator::LogOutput::AnalogueExternal	103
SpineMLSimulator::LogOutput::AnalogueNetwork	106
SpineMLSimulator::LogOutput::AnalogueFile	105
SpineMLSimulator::LogOutput::Event	186
SpineMLSimulator::ModelProperty::Base	168
SpineMLSimulator::ModelProperty::ExponentialDistribution	193
SpineMLSimulator::ModelProperty::Fixed	198
SpineMLSimulator::ModelProperty::NormalDistribution	262
SpineMLSimulator::ModelProperty::UniformDistribution	361
SpineMLSimulator::ModelProperty::ValueList	365
CodeGenerator::CodeStream::CB	169
CurrentSource	178
CurrentSourceInternal	181
Snippet::Base::DerivedParam	185
Snippet::Base::EGP	186
CodeGenerator::FunctionTemplate	202
GenerateRunBase	207
Snippet::Init< SnippetBase >	220
Snippet::Init< InitSparseConnectivitySnippet::Base >	220
InitSparseConnectivitySnippet::Init	220
Snippet::Init< InitVarSnippet::Base >	220
Models::VarInit	369
std::ios_base	
std::basic_ios	
std::basic_ostream	
std::ostream	
CodeGenerator::CodeStream	170
CodeGenerator::TeeStream	346
CodeGenerator::MemAlloc	230
ModelSpec	232
ModelSpecInternal	245
SpineMLSimulator::NetworkClient	245
NeuronGroup	252
NeuronGroupInternal	260

<b>CodeGenerator::CodeStream::OB</b>	<b>263</b>
object	
<b>pygenn.genn_groups.Group</b>	<b>218</b>
<b>pygenn.genn_groups.CurrentSource</b>	<b>175</b>
<b>pygenn.genn_groups.NeuronGroup</b>	<b>248</b>
<b>pygenn.genn_groups.SynapseGroup</b>	<b>321</b>
<b>pygenn.genn_model.GeNNModel</b>	<b>208</b>
<b>pygenn.model_preprocessor.ExtraGlobalVariable</b>	<b>196</b>
<b>pygenn.model_preprocessor.Variable</b>	<b>367</b>
<b>Snippet::Base::ParamVal</b>	<b>265</b>
<b>CodeGenerator::PreferencesBase</b>	<b>282</b>
<b>CodeGenerator::CUDA::Preferences</b>	<b>280</b>
<b>CodeGenerator::SingleThreadedCPU::Preferences</b>	<b>282</b>
<b>CodeGenerator::CodeStream::Scope</b>	<b>293</b>
<b>SharedLibraryModel&lt; scalar &gt;</b>	<b>294</b>
<b>SpineMLSimulator::Simulator</b>	<b>300</b>
<b>SpikeWriterText</b>	<b>311</b>
<b>SpikeWriterTextCached</b>	<b>312</b>
<b>SpineMLSimulator::StateVar&lt; T &gt;</b>	<b>313</b>
<b>SpineMLSimulator::StateVar&lt; scalar &gt;</b>	<b>313</b>
streambuf	
<b>CodeGenerator::TeeBuf</b>	<b>345</b>
<b>CodeGenerator::Substitutions</b>	<b>319</b>
<b>SynapseGroup</b>	<b>331</b>
<b>SynapseGroupInternal</b>	<b>344</b>
<b>Timer</b>	<b>346</b>
<b>SpineMLSimulator::Timer</b>	<b>347</b>
<b>TimerAccumulate</b>	<b>348</b>
<b>SpineMLSimulator::TimerAccumulate</b>	<b>349</b>
<b>Snippet::ValueBase&lt; NumVars &gt;</b>	<b>363</b>
<b>Snippet::ValueBase&lt; 0 &gt;</b>	<b>364</b>
<b>Models::Base::Var</b>	<b>365</b>
<b>Models::VarInitContainerBase&lt; NumVars &gt;</b>	<b>369</b>

<b>Models::VarInitContainerBase&lt; 0 &gt;</b>	<b>370</b>
Writer	
<b>SpikeRecorder&lt; Writer &gt;</b>	<b>304</b>

## 16 Class Index

### 16.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<b>SpineMLSimulator::Input::Analogue</b>	<b>101</b>
<b>SpineMLSimulator::LogOutput::AnalogueBase</b>	<b>102</b>
<b>SpineMLSimulator::LogOutput::AnalogueExternal</b>	<b>103</b>
<b>SpineMLSimulator::LogOutput::AnalogueFile</b>	<b>105</b>
<b>SpineMLSimulator::LogOutput::AnalogueNetwork</b>	<b>106</b>
<b>AnalogueRecorder&lt; T &gt;</b>	<b>107</b>
<b>CodeGenerator::CUDA::Backend</b>	<b>107</b>
<b>CodeGenerator::SingleThreadedCPU::Backend</b>	<b>122</b>
<b>CodeGenerator::BackendBase</b>	<b>134</b>
<b>CurrentSourceModels::Base</b>	
Base class for all current source models	<b>149</b>
<b>InitSparseConnectivitySnippet::Base</b>	<b>150</b>
<b>InitVarSnippet::Base</b>	<b>151</b>
<b>Models::Base</b>	
Base class for all models - in addition to the parameters snippets have, models can have state variables	<b>152</b>
<b>NeuronModels::Base</b>	
Base class for all neuron models	<b>153</b>
<b>Snippet::Base</b>	
Base class for all code snippets	<b>156</b>
<b>PostsynapticModels::Base</b>	
Base class for all postsynaptic models	<b>158</b>
<b>CodeGenerator::CUDA::PresynapticUpdateStrategy::Base</b>	<b>159</b>
<b>WeightUpdateModels::Base</b>	
Base class for all weight update models	<b>161</b>
<b>SpineMLSimulator::Input::Base</b>	<b>164</b>
<b>SpineMLSimulator::InputValue::Base</b>	<b>166</b>
<b>SpineMLSimulator::LogOutput::Base</b>	<b>167</b>

<a href="#">SpineMLSimulator::ModelProperty::Base</a>	168
<a href="#">CodeGenerator::CodeStream::CB</a> A close bracket marker	169
<a href="#">CodeGenerator::CodeStream</a>	170
<a href="#">InitVarSnippet::Constant</a> Initialises variable to a constant value	172
<a href="#">SpineMLSimulator::InputValue::Constant</a>	173
<a href="#">SpineMLSimulator::InputValue::ConstantArray</a>	174
<a href="#">pygenn.genn_groups.CurrentSource</a> Class representing a current injection into a group of neurons	175
<a href="#">CurrentSource</a>	178
<a href="#">CurrentSourceInternal</a>	181
<a href="#">CurrentSourceModels::DC</a> DC source	182
<a href="#">PostsynapticModels::DeltaCurr</a> Simple delta current synapse	184
<a href="#">Snippet::Base::DerivedParam</a> A derived parameter has a name and a function for obtaining its value	185
<a href="#">Snippet::Base::EGP</a> An extra global parameter has a name and a type	186
<a href="#">SpineMLSimulator::LogOutput::Event</a>	186
<a href="#">PostsynapticModels::ExpCond</a> Exponential decay with synaptic input treated as a conductance value	187
<a href="#">PostsynapticModels::ExpCurr</a> Exponential decay with synaptic input treated as a current value	190
<a href="#">InitVarSnippet::Exponential</a> Initialises variable by sampling from the exponential distribution	192
<a href="#">SpineMLSimulator::ModelProperty::ExponentialDistribution</a>	193
<a href="#">SpineMLSimulator::InputValue::External</a>	193
<a href="#">SpineMLSimulator::InputValue::ExternalNetwork</a>	195
<a href="#">pygenn.model_preprocessor.ExtraGlobalVariable</a> Class holding information about GeNN extra global pointer variable	196
<a href="#">SpineMLSimulator::ModelProperty::Fixed</a>	198
<a href="#">InitSparseConnectivitySnippet::FixedProbability</a>	199
<a href="#">InitSparseConnectivitySnippet::FixedProbabilityBase</a>	200
<a href="#">InitSparseConnectivitySnippet::FixedProbabilityNoAutapse</a>	201
<a href="#">CodeGenerator::FunctionTemplate</a>	202



<a href="#">InitVarSnippet::Gamma</a>	204
Initialises variable by sampling from the exponential distribution	
<a href="#">CurrentSourceModels::GaussianNoise</a>	205
Noisy current source with noise drawn from normal distribution	
<a href="#">GenerateRunBase</a>	207
<a href="#">pygenn.genn_model.GeNNModel</a>	208
<a href="#">GeNNModel</a> class This class helps to define, build and run a GeNN model from python	
<a href="#">pygenn.genn_groups.Group</a>	218
Parent class of <a href="#">NeuronGroup</a> , <a href="#">SynapseGroup</a> and <a href="#">CurrentSource</a>	
<a href="#">InitSparseConnectivitySnippet::Init</a>	220
<a href="#">Snippet::Init&lt; SnippetBase &gt;</a>	220
<a href="#">SpineMLSimulator::Input::InterSpikeIntervalBase</a>	221
<a href="#">NeuronModels::Izhikevich</a>	223
<a href="#">Izhikevich</a> neuron with fixed parameters [1]	
<a href="#">NeuronModels::IzhikevichVariable</a>	225
<a href="#">Izhikevich</a> neuron with variable parameters [1]	
<a href="#">NeuronModels::LIF</a>	227
<a href="#">CodeGenerator::MemAlloc</a>	230
<a href="#">ModelSpec</a>	232
Object used for specifying a neuronal network model	
<a href="#">ModelSpecInternal</a>	245
<a href="#">SpineMLSimulator::NetworkClient</a>	245
<a href="#">pygenn.genn_groups.NeuronGroup</a>	248
Class representing a group of neurons	
<a href="#">NeuronGroup</a>	252
<a href="#">NeuronGroupInternal</a>	260
<a href="#">InitVarSnippet::Normal</a>	261
Initialises variable by sampling from the normal distribution	
<a href="#">SpineMLSimulator::ModelProperty::NormalDistribution</a>	262
<a href="#">CodeGenerator::CodeStream::OB</a>	263
An open bracket marker	
<a href="#">InitSparseConnectivitySnippet::OneToOne</a>	263
Initialises connectivity to a 'one-to-one' diagonal matrix	
<a href="#">Snippet::Base::ParamVal</a>	265
Additional input variables, row state variables and other things have a name, a type and an initial value	
<a href="#">WeightUpdateModels::PiecewiseSTDP</a>	265
This is a simple STDP rule including a time delay for the finite transmission speed of the synapse	

<b>NeuronModels::Poisson</b>	
Poisson neurons	269
<b>NeuronModels::PoissonNew</b>	
Poisson neurons	272
<b>SpineMLSimulator::Input::PoissonSpikeRate</b>	274
<b>CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan</b>	
Postsynaptic parallelism	276
<b>CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask</b>	
Postsynaptic parallelism	278
<b>CodeGenerator::CUDA::Preferences</b>	
Preferences for CUDA backend	280
<b>CodeGenerator::SingleThreadedCPU::Preferences</b>	282
<b>CodeGenerator::PreferencesBase</b>	
Base class for backend preferences - can be accessed via a global in 'classic' C++ code generator	282
<b>CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan</b>	
Presynaptic parallelism	284
<b>CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural</b>	
Presynaptic parallelism with procedural connectivity	286
<b>SpineMLSimulator::Input::RegularSpikeRate</b>	289
<b>NeuronModels::RulkovMap</b>	
Rulkov Map neuron	290
<b>SpineMLSimulator::InputValue::ScalarBase</b>	293
<b>CodeGenerator::CodeStream::Scope</b>	293
<b>SharedLibraryModel&lt; scalar &gt;</b>	294
<b>SpineMLSimulator::Simulator</b>	300
<b>SpineMLSimulator::Input::SpikeBase</b>	303
<b>SpikeRecorder&lt; Writer &gt;</b>	
Class to read spikes from neuron groups	304
<b>NeuronModels::SpikeSource</b>	
Empty neuron which allows setting spikes from external sources	305
<b>NeuronModels::SpikeSourceArray</b>	
Spike source array	307
<b>SpineMLSimulator::Input::SpikeTime</b>	310
<b>SpikeWriterText</b>	
Class to write spikes to text file	311
<b>SpikeWriterTextCached</b>	
Class to write spikes to text file, caching in memory before writing	312
<b>SpineMLSimulator::StateVar&lt; T &gt;</b>	313

<a href="#">WeightUpdateModels::StaticGraded</a>	
Graded-potential, static synapse	314
<a href="#">WeightUpdateModels::StaticPulse</a>	
Pulse-coupled, static synapse	316
<a href="#">WeightUpdateModels::StaticPulseDendriticDelay</a>	
Pulse-coupled, static synapse with heterogenous dendritic delays	317
<a href="#">CodeGenerator::Substitutions</a>	319
<a href="#">pygenn.genn_groups.SynapseGroup</a>	
Class representing synaptic connection between two groups of neurons	321
<a href="#">SynapseGroup</a>	331
<a href="#">SynapseGroupInternal</a>	344
<a href="#">CodeGenerator::TeeBuf</a>	345
<a href="#">CodeGenerator::TeeStream</a>	346
<a href="#">Timer</a>	
A generic timer which can give the current elapsed time	346
<a href="#">SpineMLSimulator::Timer</a>	347
<a href="#">TimerAccumulate</a>	
A timer which adds its elapsed time to an accumulator variable on destruction	348
<a href="#">SpineMLSimulator::TimerAccumulate</a>	349
<a href="#">SpineMLSimulator::InputValue::TimeVarying</a>	349
<a href="#">SpineMLSimulator::InputValue::TimeVaryingArray</a>	350
<a href="#">NeuronModels::TraubMiles</a>	
Hodgkin-Huxley neurons with Traub & Miles algorithm	351
<a href="#">NeuronModels::TraubMilesAlt</a>	
Hodgkin-Huxley neurons with Traub & Miles algorithm	354
<a href="#">NeuronModels::TraubMilesFast</a>	
Hodgkin-Huxley neurons with Traub & Miles algorithm: Original fast implementation, using 25 inner iterations	356
<a href="#">NeuronModels::TraubMilesNStep</a>	
Hodgkin-Huxley neurons with Traub & Miles algorithm	358
<a href="#">InitVarSnippet::Uniform</a>	
Initialises variable by sampling from the uniform distribution	359
<a href="#">SpineMLSimulator::ModelProperty::UniformDistribution</a>	361
<a href="#">InitVarSnippet::Uninitialised</a>	
Used to mark variables as uninitialised - no initialisation code will be run	361
<a href="#">InitSparseConnectivitySnippet::Uninitialised</a>	
Used to mark connectivity as uninitialised - no initialisation code will be run	362
<a href="#">Snippet::ValueBase&lt; NumVars &gt;</a>	363

<a href="#">Snippet::ValueBase&lt; 0 &gt;</a>	364
<a href="#">SpineMLSimulator::ModelProperty::ValueList</a>	365
<a href="#">Models::Base::Var</a>	
A variable has a name, a type and an access type	365
<a href="#">pygenn.model_preprocessor.Variable</a>	
Class holding information about GeNN variables	367
<a href="#">Models::VarInit</a>	369
<a href="#">Models::VarInitContainerBase&lt; NumVars &gt;</a>	369
<a href="#">Models::VarInitContainerBase&lt; 0 &gt;</a>	370

## 17 File Index

### 17.1 File List

Here is a list of all files with brief descriptions:

<a href="#">__init__.py</a>	372
<a href="#">analogueRecorder.h</a>	372
<a href="#">cuda/backend.cc</a>	372
<a href="#">single_threaded_cpu/backend.cc</a>	373
<a href="#">cuda/backend.h</a>	373
<a href="#">single_threaded_cpu/backend.h</a>	374
<a href="#">backendBase.cc</a>	374
<a href="#">backendBase.h</a>	375
<a href="#">backendExport.h</a>	375
<a href="#">binomial.cc</a>	375
<a href="#">binomial.h</a>	376
<a href="#">codeGenUtils.cc</a>	376
<a href="#">codeGenUtils.h</a>	377
<a href="#">codeStream.cc</a>	379
<a href="#">codeStream.h</a>	379
<a href="#">connectors.cc</a>	379
<a href="#">connectors.h</a>	380
<a href="#">currentSource.cc</a>	380
<a href="#">currentSource.h</a>	380
<a href="#">currentSourceInternal.h</a>	381

<a href="#">currentSourceModels.cc</a>	381
<a href="#">currentSourceModels.h</a>	381
<a href="#">generateAll.cc</a>	382
<a href="#">generateAll.h</a>	382
<a href="#">generateInit.cc</a>	383
<a href="#">generateInit.h</a>	383
<a href="#">generateMakefile.cc</a>	383
<a href="#">generateMakefile.h</a>	383
<a href="#">generateMPI.cc</a>	
Contains functions to generate code for running the simulation with MPI. Part of the code generation section	384
<a href="#">generateMPI.h</a>	
Contains functions to generate code for running the simulation with MPI. Part of the code generation section	384
<a href="#">generateMSBuild.cc</a>	384
<a href="#">generateMSBuild.h</a>	384
<a href="#">generateNeuronUpdate.cc</a>	385
<a href="#">generateNeuronUpdate.h</a>	385
<a href="#">generateRun.h</a>	385
<a href="#">generateRunner.cc</a>	386
<a href="#">generateRunner.h</a>	386
<a href="#">generateSupportCode.cc</a>	386
<a href="#">generateSupportCode.h</a>	386
<a href="#">generateSynapseUpdate.cc</a>	386
<a href="#">generateSynapseUpdate.h</a>	387
<a href="#">genn_groups.py</a>	387
<a href="#">genn_model.py</a>	387
<a href="#">gennExport.h</a>	388
<a href="#">gennUtils.cc</a>	389
<a href="#">gennUtils.h</a>	389
<a href="#">initSparseConnectivitySnippet.cc</a>	390
<a href="#">initSparseConnectivitySnippet.h</a>	390
<a href="#">initVarSnippet.cc</a>	392
<a href="#">initVarSnippet.h</a>	393

<a href="#">input.cc</a>	394
<a href="#">input.h</a>	394
<a href="#">inputValue.cc</a>	394
<a href="#">inputValue.h</a>	395
<a href="#">logging.cc</a>	395
<a href="#">logging.h</a>	395
<a href="#">logOutput.cc</a>	398
<a href="#">logOutput.h</a>	398
<a href="#">logWriter.h</a>	399
<a href="#">model_preprocessor.py</a>	399
<a href="#">modelProperty.cc</a>	400
<a href="#">modelProperty.h</a>	400
<a href="#">models.h</a>	400
<a href="#">modelSpec.cc</a>	402
<a href="#">modelSpec.h</a>	
Header file that contains the class (struct) definition of <code>neuronModel</code> for defining a neuron model and the class definition of <code>ModelSpec</code> for defining a neuronal network model. Part of the code generation and generated code sections	402
<a href="#">modelSpecInternal.h</a>	406
<a href="#">networkClient.cc</a>	406
<a href="#">networkClient.h</a>	406
<a href="#">neuronGroup.cc</a>	407
<a href="#">neuronGroup.h</a>	407
<a href="#">neuronGroupInternal.h</a>	407
<a href="#">neuronModels.cc</a>	407
<a href="#">neuronModels.h</a>	409
<a href="#">cuda/optimiser.cc</a>	411
<a href="#">single_threaded_cpu/optimiser.cc</a>	412
<a href="#">cuda/optimiser.h</a>	412
<a href="#">single_threaded_cpu/optimiser.h</a>	412
<a href="#">postsynapticModels.cc</a>	413
<a href="#">postsynapticModels.h</a>	413
<a href="#">presynapticUpdateStrategy.cc</a>	414

<a href="#">presynapticUpdateStrategy.h</a>	415
<a href="#">sharedLibraryModel.h</a>	415
<a href="#">simulator.cc</a>	416
<a href="#">simulator.h</a>	416
<a href="#">snippet.h</a>	417
<a href="#">spikeRecorder.h</a>	418
<a href="#">stateVar.h</a>	418
<a href="#">substitutions.h</a>	419
<a href="#">synapseGroup.cc</a>	419
<a href="#">synapseGroup.h</a>	419
<a href="#">synapseGroupInternal.h</a>	420
<a href="#">synapseMatrixType.h</a>	420
<a href="#">teeStream.h</a>	422
<a href="#">include/spinemi/simulator/timer.h</a>	422
<a href="#">userproject/include/timer.h</a>	423
<a href="#">utils.h</a>	423
<a href="#">variableMode.h</a>	424
<a href="#">weightUpdateModels.cc</a>	424
<a href="#">weightUpdateModels.h</a>	425

## 18 Namespace Documentation

### 18.1 CodeGenerator Namespace Reference

Helper class for generating code - automatically inserts brackets, indents etc.

#### Namespaces

- [CUDA](#)
- [SingleThreadedCPU](#)

#### Classes

- class [BackendBase](#)
- class [CodeStream](#)
- struct [FunctionTemplate](#)
- class [MemAlloc](#)
- struct [PreferencesBase](#)

*Base class for backend preferences - can be accessed via a global in 'classic' C++ code generator.*

- class [Substitutions](#)
- class [TeeBuf](#)
- class [TeeStream](#)

## Functions

- void [substitute](#) (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting strings in the neuron code strings or other templates.*
- bool [regexVarSubstitute](#) (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting variable names in the neuron code strings or other templates using regular expressions.*
- bool [regexFuncSubstitute](#) (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting function names in the neuron code strings or other templates using regular expressions.*
- void [functionSubstitute](#) (std::string &code, const std::string &funcName, unsigned int numParams, const std::string &replaceFuncTemplate)  
*This function substitutes function calls in the form:*
- template<class T, typename std::enable\_if< std::is\_floating\_point< T >::value >::type \* = nullptr>  
void [writePreciseString](#) (std::ostream &os, T value)  
*This function writes a floating point value to a stream -setting the precision so no digits are lost.*
- template<class T, typename std::enable\_if< std::is\_floating\_point< T >::value >::type \* = nullptr>  
std::string [writePreciseString](#) (T value)  
*This function writes a floating point value to a string - setting the precision so no digits are lost.*
- size\_t [ceilDivide](#) (size\_t numerator, size\_t denominator)  
*Divide two integers, rounding up i.e. effectively taking ceil.*
- size\_t [padSize](#) (size\_t size, size\_t blockSize)  
*Pad an integer to a multiple of another.*
- std::string [ensureFtype](#) (const std::string &oldcode, const std::string &type)  
*This function implements a parser that converts any floating point constant in a code snippet to a floating point constant with an explicit precision (by appending "f" or removing it).*
- void [checkUnreplacedVariables](#) (const std::string &code, const std::string &codeName)  
*This function checks for unknown variable definitions and returns a `gennError` if any are found.*
- void [preNeuronSubstitutionsInSynapticCode](#) ([Substitutions](#) &substitutions, const [SynapseGroupInternal](#) &sg, const std::string &offset, const std::string &axonalDelayOffset, const std::string &postIdx, const std::string &devPrefix, const std::string &preVarPrefix="", const std::string &preVarSuffix="")  
*suffix to be used for presynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`*
- void [postNeuronSubstitutionsInSynapticCode](#) ([Substitutions](#) &substitutions, const [SynapseGroupInternal](#) &sg, const std::string &offset, const std::string &backPropDelayOffset, const std::string &preIdx, const std::string &devPrefix, const std::string &postVarPrefix="", const std::string &postVarSuffix="")  
*suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`*
- void [neuronSubstitutionsInSynapticCode](#) ([Substitutions](#) &substitutions, const [SynapseGroupInternal](#) &sg, const std::string &preIdx, const std::string &postIdx, const std::string &devPrefix, double dt, const std::string &preVarPrefix="", const std::string &preVarSuffix="", const std::string &postVarPrefix="", const std::string &postVarSuffix="")  
*Function for performing the code and value substitutions necessary to insert neuron related variables, parameters, and extraGlobal parameters into synaptic code.*
- [GENN\\_EXPORT](#) std::ostream & [operator<<](#) (std::ostream &s, const [CodeStream::OB](#) &ob)
- [GENN\\_EXPORT](#) std::ostream & [operator<<](#) (std::ostream &s, const [CodeStream::CB](#) &cb)
- [GENN\\_EXPORT](#) std::vector< std::string > [generateAll](#) (const [ModelSpecInternal](#) &model, const [BackendBase](#) &backend, const filesystem::path &outputPath, bool standaloneModules=false)
- void [generateInit](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [BackendBase](#) &backend, bool standaloneModules)
- void [GENN\\_EXPORT generateMakefile](#) (std::ostream &os, const [BackendBase](#) &backend, const std::vector< std::string > &moduleNames)



- void `GENN_EXPORT generateMPI` (`CodeStream` &os, const `ModelSpecInternal` &model, const `BackendBase` &backend, bool standaloneModules)  
*A function that generates predominantly MPI infrastructure code.*
- void `GENN_EXPORT generateMSBuild` (std::ostream &os, const `BackendBase` &backend, const std::string &projectGUID, const std::vector< std::string > &moduleNames)
- void `generateNeuronUpdate` (`CodeStream` &os, const `ModelSpecInternal` &model, const `BackendBase` &backend, bool standaloneModules)
- `MemAlloc generateRunner` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, const `ModelSpecInternal` &model, const `BackendBase` &backend, int localhostID)
- void `generateSupportCode` (`CodeStream` &os, const `ModelSpecInternal` &model)
- void `generateSynapseUpdate` (`CodeStream` &os, const `ModelSpecInternal` &model, const `BackendBase` &backend, bool standaloneModules)

### 18.1.1 Detailed Description

Helper class for generating code - automatically inserts brackets, indents etc.

Based heavily on: <https://stackoverflow.com/questions/15053753/writing-a-manipulator-for-a-cus>

### 18.1.2 Function Documentation

#### 18.1.2.1 `ceilDivide()`

```
size_t CodeGenerator::ceilDivide (
    size_t numerator,
    size_t denominator ) [inline]
```

Divide two integers, rounding up i.e. effectively taking ceil.

#### 18.1.2.2 `checkUnreplacedVariables()`

```
void CodeGenerator::checkUnreplacedVariables (
    const std::string & code,
    const std::string & codeName )
```

This function checks for unknown variable definitions and returns a `gennError` if any are found.

#### 18.1.2.3 `ensureFtype()`

```
std::string CodeGenerator::ensureFtype (
    const std::string & oldcode,
    const std::string & type )
```

This function implements a parser that converts any floating point constant in a code snippet to a floating point constant with an explicit precision (by appending "f" or removing it).

#### 18.1.2.4 `functionSubstitute()`

```
void CodeGenerator::functionSubstitute (
    std::string & code,
    const std::string & funcName,
    unsigned int numParams,
    const std::string & replaceFuncTemplate )
```

This function substitutes function calls in the form:

`$(functionName, parameter1, param2Function(0.12, "string"))`

with replacement templates in the form:

`actualFunction(CONSTANT, $(0), $(1))`

#### 18.1.2.5 generateAll()

```
std::vector< std::string > CodeGenerator::generateAll (
    const ModelSpecInternal & model,
    const BackendBase & backend,
    const filesystem::path & outputPath,
    bool standaloneModules = false )
```

#### 18.1.2.6 generateInit()

```
void CodeGenerator::generateInit (
    CodeStream & os,
    const ModelSpecInternal & model,
    const BackendBase & backend,
    bool standaloneModules )
```

#### 18.1.2.7 generateMakefile()

```
void CodeGenerator::generateMakefile (
    std::ostream & os,
    const BackendBase & backend,
    const std::vector< std::string > & moduleNames )
```

#### 18.1.2.8 generateMPI()

```
void CodeGenerator::generateMPI (
    CodeStream & os,
    const ModelSpecInternal & model,
    const BackendBase & backend,
    bool standaloneModules )
```

A function that generates predominantly MPI infrastructure code.

In this function MPI infrastructure code are generated, including: MPI send and receive functions.

#### 18.1.2.9 generateMSBuild()

```
void CodeGenerator::generateMSBuild (
    std::ostream & os,
    const BackendBase & backend,
    const std::string & projectGUID,
    const std::vector< std::string > & moduleNames )
```

#### 18.1.2.10 generateNeuronUpdate()

```
void CodeGenerator::generateNeuronUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const BackendBase & backend,
```

```
bool standaloneModules )
```

#### 18.1.2.11 generateRunner()

```
CodeGenerator::MemAlloc CodeGenerator::generateRunner (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    const ModelSpecInternal & model,
    const BackendBase & backend,
    int localHostID )
```

#### 18.1.2.12 generateSupportCode()

```
void CodeGenerator::generateSupportCode (
    CodeStream & os,
    const ModelSpecInternal & model )
```

#### 18.1.2.13 generateSynapseUpdate()

```
void CodeGenerator::generateSynapseUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const BackendBase & backend,
    bool standaloneModules )
```

#### 18.1.2.14 neuronSubstitutionsInSynapticCode()

```
void CodeGenerator::neuronSubstitutionsInSynapticCode (
    Substitutions & substitutions,
    const SynapseGroupInternal & sg,
    const std::string & preIdx,
    const std::string & postIdx,
    const std::string & devPrefix,
    double dt,
    const std::string & preVarPrefix = "",
    const std::string & preVarSuffix = "",
    const std::string & postVarPrefix = "",
    const std::string & postVarSuffix = "" )
```

Function for performing the code and value substitutions necessary to insert neuron related variables, parameters, and extraGlobal parameters into synaptic code.

suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`

#### Parameters

<i>substitutions</i>	the code string to work on
<i>sg</i>	the synapse group connecting the pre and postsynaptic neuron populations whose parameters might need to be substituted
<i>preIdx</i>	index of the pre-synaptic neuron to be accessed for <code>_pre</code> variables; differs for different Span)
<i>postIdx</i>	index of the post-synaptic neuron to be accessed for <code>_post</code> variables; differs for different Span)
<i>devPrefix</i>	device prefix, "dd_" for GPU, nothing for CPU

## Parameters

<i>dt</i>	simulation timestep (ms)
<i>preVarPrefix</i>	prefix to be used for presynaptic variable accesses - typically combined with suffix to wrap in function call such as <code>__ldg(&amp;XXX)</code>
<i>preVarSuffix</i>	suffix to be used for presynaptic variable accesses - typically combined with prefix to wrap in function call such as <code>__ldg(&amp;XXX)</code>
<i>postVarPrefix</i>	prefix to be used for postsynaptic variable accesses - typically combined with suffix to wrap in function call such as <code>__ldg(&amp;XXX)</code>
<i>postVarSuffix</i>	suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as <code>__ldg(&amp;XXX)</code>

18.1.2.15 `operator<<()` [1/2]

```
std::ostream & CodeGenerator::operator<< (
    std::ostream & s,
    const CodeStream::OB & ob )
```

18.1.2.16 `operator<<()` [2/2]

```
std::ostream & CodeGenerator::operator<< (
    std::ostream & s,
    const CodeStream::CB & cb )
```

18.1.2.17 `padSize()`

```
size_t CodeGenerator::padSize (
    size_t size,
    size_t blockSize ) [inline]
```

Pad an integer to a multiple of another.

18.1.2.18 `postNeuronSubstitutionsInSynapticCode()`

```
void CodeGenerator::postNeuronSubstitutionsInSynapticCode (
    Substitutions & substitutions,
    const SynapseGroupInternal & sg,
    const std::string & offset,
    const std::string & backPropDelayOffset,
    const std::string & preIdx,
    const std::string & devPrefix,
    const std::string & postVarPrefix = "",
    const std::string & postVarSuffix = "" )
```

suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`

## Parameters

<i>substitutions</i>	the code string to work on
<i>devPrefix</i>	device prefix, "dd_" for GPU, nothing for CPU
<i>postVarPrefix</i>	prefix to be used for postsynaptic variable accesses - typically combined with suffix to wrap in function call such as <code>__ldg(&amp;XXX)</code>

## Parameters

<i>postVarSuffix</i>	suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as <code>__ldg(&amp;XXX)</code>
----------------------	---

## 18.1.2.19 preNeuronSubstitutionsInSynapticCode()

```
void CodeGenerator::preNeuronSubstitutionsInSynapticCode (
    Substitutions & substitutions,
    const SynapseGroupInternal & sg,
    const std::string & offset,
    const std::string & axonalDelayOffset,
    const std::string & postIdx,
    const std::string & devPrefix,
    const std::string & preVarPrefix = "",
    const std::string & preVarSuffix = "" )
```

suffix to be used for presynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`

Function for performing the code and value substitutions necessary to insert neuron related variables, parameters, and extraGlobal parameters into synaptic code.

## Parameters

<i>substitutions</i>	the code string to work on
<i>devPrefix</i>	device prefix, "dd_" for GPU, nothing for CPU
<i>preVarPrefix</i>	prefix to be used for presynaptic variable accesses - typically combined with suffix to wrap in function call such as <code>__ldg(&amp;XXX)</code>
<i>preVarSuffix</i>	suffix to be used for presynaptic variable accesses - typically combined with prefix to wrap in function call such as <code>__ldg(&amp;XXX)</code>

## 18.1.2.20 regexFuncSubstitute()

```
bool CodeGenerator::regexFuncSubstitute (
    std::string & s,
    const std::string & trg,
    const std::string & rep )
```

Tool for substituting function names in the neuron code strings or other templates using regular expressions.

## 18.1.2.21 regexVarSubstitute()

```
bool CodeGenerator::regexVarSubstitute (
    std::string & s,
    const std::string & trg,
    const std::string & rep )
```

Tool for substituting variable names in the neuron code strings or other templates using regular expressions.

#### 18.1.2.22 `substitute()`

```
void CodeGenerator::substitute (
    std::string & s,
    const std::string & trg,
    const std::string & rep )
```

Tool for substituting strings in the neuron code strings or other templates.

#### 18.1.2.23 `writePreciseString()` [1/2]

```
template<class T , typename std::enable_if< std::is_floating_point< T >::value >::type * =
nullptr>
void CodeGenerator::writePreciseString (
    std::ostream & os,
    T value )
```

This function writes a floating point value to a stream -setting the precision so no digits are lost.

#### 18.1.2.24 `writePreciseString()` [2/2]

```
template<class T , typename std::enable_if< std::is_floating_point< T >::value >::type * =
nullptr>
std::string CodeGenerator::writePreciseString (
    T value )
```

This function writes a floating point value to a string - setting the precision so no digits are lost.

## 18.2 `CodeGenerator::CUDA` Namespace Reference

### Namespaces

- [Optimiser](#)
- [PresynapticUpdateStrategy](#)

### Classes

- class [Backend](#)
- struct [Preferences](#)  
*[Preferences](#) for [CUDA](#) backend.*

### Typedefs

- using [KernelBlockSize](#) = `std::array< size_t, KernelMax >`  
*Array of block sizes for each kernel.*

### Enumerations

- enum [DeviceSelect](#) { [DeviceSelect::OPTIMAL](#), [DeviceSelect::MOST\\_MEMORY](#), [DeviceSelect::MANUAL](#) }  
*Methods for selecting [CUDA](#) device.*
- enum [BlockSizeSelect](#) { [BlockSizeSelect::OCCUPANCY](#), [BlockSizeSelect::MANUAL](#) }  
*Methods for selecting [CUDA](#) kernel block size.*

- enum [Kernel](#) {  
[KernelNeuronUpdate](#), [KernelPresynapticUpdate](#), [KernelPostsynapticUpdate](#), [KernelSynapseDynamicsUpdate](#),  
[KernelInitialize](#), [KernelInitializeSparse](#), [KernelPreNeuronReset](#), [KernelPreSynapseReset](#),  
[KernelMax](#) }  
*Kernels generated by CUDA backend.*

### 18.2.1 Typedef Documentation

#### 18.2.1.1 KernelBlockSize

using [CodeGenerator::CUDA::KernelBlockSize](#) = typedef std::array<size\_t, [KernelMax](#)>

Array of block sizes for each kernel.

### 18.2.2 Enumeration Type Documentation

#### 18.2.2.1 BlockSizeSelect

enum [CodeGenerator::CUDA::BlockSizeSelect](#) [strong]

Methods for selecting [CUDA](#) kernel block size.

##### Enumerator

OCCUPANCY	Pick optimal blocksize for each kernel based on occupancy.
MANUAL	Use block sizes specified by user.

#### 18.2.2.2 DeviceSelect

enum [CodeGenerator::CUDA::DeviceSelect](#) [strong]

Methods for selecting [CUDA](#) device.

##### Enumerator

OPTIMAL	Pick optimal device based on how well kernels can be simultaneously simulated and occupancy.
MOST_MEMORY	Pick device with most global memory.
MANUAL	Use device specified by user.

#### 18.2.2.3 Kernel

enum [CodeGenerator::CUDA::Kernel](#)

Kernels generated by [CUDA](#) backend.

##### Enumerator

<a href="#">KernelNeuronUpdate</a>	
------------------------------------	--

#### Enumerator

KernelPresynapticUpdate	
KernelPostsynapticUpdate	
KernelSynapseDynamicsUpdate	
KernellInitialize	
KernellInitializeSparse	
KernelPreNeuronReset	
KernelPreSynapseReset	
KernelMax	

### 18.3 CodeGenerator::CUDA::Optimiser Namespace Reference

#### Functions

- [BACKEND\\_EXPORT Backend createBackend](#) (const [ModelSpecInternal](#) &model, const filesystem::path &outputPath, plog::Severity backendLevel, plog::IAppender \*backendAppender, int localHostID, const [Preferences](#) &preferences)

#### 18.3.1 Function Documentation

##### 18.3.1.1 createBackend()

```
Backend CodeGenerator::CUDA::Optimiser::createBackend (
    const ModelSpecInternal & model,
    const filesystem::path & outputPath,
    plog::Severity backendLevel,
    plog::IAppender * backendAppender,
    int localHostID,
    const Preferences & preferences )
```

### 18.4 CodeGenerator::CUDA::PresynapticUpdateStrategy Namespace Reference

#### Classes

- class [Base](#)
- class [PostSpan](#)  
*Postsynaptic parallelism.*
- class [PostSpanBitmask](#)  
*Postsynaptic parallelism.*
- class [PreSpan](#)  
*Presynaptic parallelism.*
- class [PreSpanProcedural](#)  
*Presynaptic parallelism with procedural connectivity.*

### 18.5 CodeGenerator::SingleThreadedCPU Namespace Reference

#### Namespaces

- [Optimiser](#)



## Classes

- class [Backend](#)
- struct [Preferences](#)

## 18.6 CodeGenerator::SingleThreadedCPU::Optimiser Namespace Reference

## Functions

- [BACKEND\\_EXPORT Backend createBackend](#) (const [ModelSpecInternal](#) &model, const filesystem::path &outputPath, plog::Severity backendLevel, plog::IAppender \*backendAppender, int localhostID, const [Preferences](#) &preferences)

## 18.6.1 Function Documentation

## 18.6.1.1 createBackend()

```
Backend CodeGenerator::SingleThreadedCPU::Optimiser::createBackend (
    const ModelSpecInternal & model,
    const filesystem::path & outputPath,
    plog::Severity backendLevel,
    plog::IAppender * backendAppender,
    int localhostID,
    const Preferences & preferences )
```

## 18.7 CurrentSourceModels Namespace Reference

## Classes

- class [Base](#)  
*[Base](#) class for all current source models.*
- class [DC](#)  
*[DC](#) source.*
- class [GaussianNoise](#)  
*Noisy current source with noise drawn from normal distribution.*

## 18.8 filesystem Namespace Reference

## 18.9 InitSparseConnectivitySnippet Namespace Reference

[Base](#) class for all sparse connectivity initialisation snippets.

## Classes

- class [Base](#)
- class [FixedProbability](#)
- class [FixedProbabilityBase](#)
- class [FixedProbabilityNoAutapse](#)
- class [Init](#)
- class [OneToOne](#)  
*Initialises connectivity to a 'one-to-one' diagonal matrix.*

- class [Uninitialised](#)

*Used to mark connectivity as uninitialised - no initialisation code will be run.*

#### 18.9.1 Detailed Description

[Base](#) class for all sparse connectivity initialisation snippets.

### 18.10 InitVarSnippet Namespace Reference

[Base](#) class for all value initialisation snippets.

#### Classes

- class [Base](#)
- class [Constant](#)  
*Initialises variable to a constant value.*
- class [Exponential](#)  
*Initialises variable by sampling from the exponential distribution.*
- class [Gamma](#)  
*Initialises variable by sampling from the exponential distribution.*
- class [Normal](#)  
*Initialises variable by sampling from the normal distribution.*
- class [Uniform](#)  
*Initialises variable by sampling from the uniform distribution.*
- class [Uninitialised](#)  
*Used to mark variables as uninitialised - no initialisation code will be run.*

#### 18.10.1 Detailed Description

[Base](#) class for all value initialisation snippets.

### 18.11 Logging Namespace Reference

#### Enumerations

- enum [Channel](#) { [CHANNEL\\_GENN](#) = 0, [CHANNEL\\_CODE\\_GEN](#) = 1, [CHANNEL\\_BACKEND](#) = 2, [CHANNEL\\_EL\\_MAX](#) }

#### Functions

- [GENN\\_EXPORT](#) void [init](#) (plog::Severity gennLevel, plog::Severity codeGeneratorLevel, plog::IAppender \*gennAppender, plog::IAppender \*codeGeneratorAppender)

#### 18.11.1 Enumeration Type Documentation

##### 18.11.1.1 Channel

```
enum Logging::Channel
```

## Enumerator

CHANNEL_GENN	
CHANNEL_CODE_GEN	
CHANNEL_BACKEND	
CHANNEL_MAX	

## 18.11.2 Function Documentation

## 18.11.2.1 init()

```
void Logging::init (
    plog::Severity gennLevel,
    plog::Severity codeGeneratorLevel,
    plog::IAppender * gennAppender,
    plog::IAppender * codeGeneratorAppender )
```

## 18.12 Models Namespace Reference

## Classes

- class [Base](#)  
*Base class for all models - in addition to the parameters snippets have, models can have state variables.*
- class [VarInit](#)
- class [VarInitContainerBase](#)
- class [VarInitContainerBase< 0 >](#)

## 18.12.1 Detailed Description

Class used to bind together everything required to initialise a variable:

1. A pointer to a variable initialisation snippet
2. The parameters required to control the variable initialisation snippet

## 18.13 NeuronModels Namespace Reference

## Classes

- class [Base](#)  
*Base class for all neuron models.*
- class [Izhikevich](#)  
*Izhikevich neuron with fixed parameters [1].*
- class [IzhikevichVariable](#)  
*Izhikevich neuron with variable parameters [1].*
- class [LIF](#)
- class [Poisson](#)  
*Poisson neurons.*
- class [PoissonNew](#)  
*Poisson neurons.*

- class [RulkovMap](#)  
*Rulkov Map neuron.*
- class [SpikeSource](#)  
*Empty neuron which allows setting spikes from external sources.*
- class [SpikeSourceArray](#)  
*Spike source array.*
- class [TraubMiles](#)  
*Hodgkin-Huxley neurons with Traub & Miles algorithm.*
- class [TraubMilesAlt](#)  
*Hodgkin-Huxley neurons with Traub & Miles algorithm.*
- class [TraubMilesFast](#)  
*Hodgkin-Huxley neurons with Traub & Miles algorithm: Original fast implementation, using 25 inner iterations.*
- class [TraubMilesNStep](#)  
*Hodgkin-Huxley neurons with Traub & Miles algorithm.*

## 18.14 plog Namespace Reference

## 18.15 PostsynapticModels Namespace Reference

### Classes

- class [Base](#)  
*Base class for all postsynaptic models.*
- class [DeltaCurr](#)  
*Simple delta current synapse.*
- class [ExpCond](#)  
*Exponential decay with synaptic input treated as a conductance value.*
- class [ExpCurr](#)  
*Exponential decay with synaptic input treated as a current value.*

## 18.16 pugi Namespace Reference

## 18.17 pygenn Namespace Reference

### Namespaces

- [genn\\_groups](#)
- [genn\\_model](#)
- [model\\_preprocessor](#)

## 18.18 pygenn.genn\_groups Namespace Reference

### Classes

- class [CurrentSource](#)  
*Class representing a current injection into a group of neurons.*
- class [Group](#)  
*Parent class of [NeuronGroup](#), [SynapseGroup](#) and [CurrentSource](#).*
- class [NeuronGroup](#)  
*Class representing a group of neurons.*
- class [SynapseGroup](#)  
*Class representing synaptic connection between two groups of neurons.*

## Variables

- [xrange](#) = range

*GeNNGroups* This module provides classes which automatize model checks and parameter convesions for GeNN Groups.

## 18.18.1 Variable Documentation

## 18.18.1.1 xrange

```
pygenn.genn_groups.xrange = range
```

*GeNNGroups* This module provides classes which automatize model checks and parameter convesions for GeNN Groups.

## 18.19 pygenn.genn\_model Namespace Reference

## Classes

- class [GeNNModel](#)

*GeNNModel* class This class helps to define, build and run a GeNN model from python.

## Functions

- def [init\\_var](#) (init\_var\_snippet, param\_space)

This helper function creates a *VarInit* object to easily initialise a variable using a snippet.

- def [init\\_connectivity](#) (init\_sparse\_connect\_snippet, param\_space)

This helper function creates a *InitSparseConnectivitySnippet::Init* object to easily initialise connectivity using a snippet.

- def [create\\_custom\\_neuron\\_class](#) (class\_name, param\_names=None, var\_name\_types=None, derived\_params=None, sim\_code=None, threshold\_condition\_code=None, reset\_code=None, support\_code=None, extra\_global\_params=None, additional\_input\_vars=None, is\_auto\_refractory\_required=None, custom\_body=None)

This helper function creates a custom *NeuronModel* class.

- def [create\\_custom\\_postsynaptic\\_class](#) (class\_name, param\_names=None, var\_name\_types=None, derived\_params=None, decay\_code=None, apply\_input\_code=None, support\_code=None, custom\_body=None)

This helper function creates a custom *PostsynapticModel* class.

- def [create\\_custom\\_weight\\_update\\_class](#) (class\_name, param\_names=None, var\_name\_types=None, pre\_var\_name\_types=None, post\_var\_name\_types=None, derived\_params=None, sim\_code=None, event\_code=None, learn\_post\_code=None, synapse\_dynamics\_code=None, event\_threshold\_condition\_code=None, pre\_spike\_code=None, post\_spike\_code=None, sim\_support\_code=None, learn\_post\_support\_code=None, synapse\_dynamics\_suppport\_code=None, extra\_global\_params=None, is\_pre\_spike\_time\_required=None, is\_post\_spike\_time\_required=None, custom\_body=None)

This helper function creates a custom *WeightUpdateModel* class.

- def [create\\_custom\\_current\\_source\\_class](#) (class\_name, param\_names=None, var\_name\_types=None, derived\_params=None, injection\_code=None, extra\_global\_params=None, custom\_body=None)

This helper function creates a custom *NeuronModel* class.

- def [create\\_custom\\_model\\_class](#) (class\_name, base, param\_names, var\_name\_types, derived\_params, custom\_body)

This helper function completes a custom model class creation.

- def [create\\_dpfc\\_class](#) (dp\_func)

Helper function to create derived parameter function class.

- def [create\\_cmlf\\_class](#) (cml\_func)

*Helper function to create function class for calculating sizes of matrices initialised with sparse connectivity initialisation snippet.*

- def [create\\_custom\\_init\\_var\\_snippet\\_class](#) (class\_name, param\_names=None, derived\_params=None, var\_init\_code=None, custom\_body=None)

*This helper function creates a custom [InitVarSnippet](#) class.*

- def [create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#) (class\_name, param\_names=None, derived\_params=None, row\_build\_code=None, row\_build\_state\_vars=None, calc\_max\_row\_len\_func=None, calc\_max\_col\_len\_func=None, extra\_global\_params=None, custom\_body=None)

*This helper function creates a custom [InitSparseConnectivitySnippet](#) class.*

## Variables

- [backend\\_modules](#) = OrderedDict()
- [m](#) = import\_module(".genn\_wrapper." + b + "Backend", "pygenn")

## 18.19.1 Function Documentation

### 18.19.1.1 [create\\_cmlf\\_class\(\)](#)

```
def pygenn.genn_model.create_cmlf_class (
    cml_func )
```

Helper function to create function class for calculating sizes of matrices initialised with sparse connectivity initialisation snippet.

#### Parameters

<i>cml_func</i>	a function which computes the length and takes three args "num_pre" (unsigned int), "num_post" (unsigned int) and "pars" (vector of double)
-----------------	---

### 18.19.1.2 [create\\_custom\\_current\\_source\\_class\(\)](#)

```
def pygenn.genn_model.create_custom_current_source_class (
    class_name,
    param_names = None,
    var_name_types = None,
    derived_params = None,
    injection_code = None,
    extra_global_params = None,
    custom_body = None )
```

This helper function creates a custom NeuronModel class.

#### See also

[create\\_custom\\_neuron\\_class](#)  
[create\\_custom\\_weight\\_update\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_init\\_var\\_snippet\\_class](#)  
[create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#)

## Parameters

<i>class_name</i>	name of the new class
<i>param_names</i>	list of strings with param names of the model
<i>var_name_types</i>	list of pairs of strings with variable names and types of the model
<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of the class which inherits from <code>pygenn.genn_wrapper.DerivedParamFunc</code>
<i>injection_code</i>	string with the current injection code
<i>extra_global_params</i>	list of pairs of strings with names and types of additional parameters
<i>custom_body</i>	dictionary with additional attributes and methods of the new class

18.19.1.3 `create_custom_init_var_snippet_class()`

```
def pygenn.genn_model.create_custom_init_var_snippet_class (
    class_name,
    param_names = None,
    derived_params = None,
    var_init_code = None,
    custom_body = None )
```

This helper function creates a custom [InitVarSnippet](#) class.

## See also

[create\\_custom\\_neuron\\_class](#)  
[create\\_custom\\_weight\\_update\\_class](#)  
[create\\_custom\\_postsynaptic\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#)

## Parameters

<i>class_name</i>	name of the new class
<i>param_names</i>	list of strings with param names of the model
<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of the <code>pygenn.genn_wrapper.DerivedParamFunc</code> class
<i>var_init_code</i>	string with the variable initialization code
<i>custom_body</i>	dictionary with additional attributes and methods of the new class

18.19.1.4 `create_custom_model_class()`

```
def pygenn.genn_model.create_custom_model_class (
    class_name,
    base,
    param_names,
    var_name_types,
    derived_params,
    custom_body )
```

This helper function completes a custom model class creation.

This part is common for all model classes and is nearly useless on its own unless you specify `custom_body`.

#### See also

[create\\_custom\\_neuron\\_class](#)  
[create\\_custom\\_weight\\_update\\_class](#)  
[create\\_custom\\_postsynaptic\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_init\\_var\\_snippet\\_class](#)  
[create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#)

#### Parameters

<i>class_name</i>	name of the new class
<i>base</i>	base class
<i>param_names</i>	list of strings with param names of the model
<i>var_name_types</i>	list of pairs of strings with variable names and types of the model
<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of the class which inherits from the <code>pygenn.genn_wrapper.DerivedParamFunc</code> class
<i>custom_body</i>	dictionary with attributes and methods of the new class

#### 18.19.1.5 create\_custom\_neuron\_class()

```
def pygenn.genn_model.create_custom_neuron_class (
    class_name,
    param_names = None,
    var_name_types = None,
    derived_params = None,
    sim_code = None,
    threshold_condition_code = None,
    reset_code = None,
    support_code = None,
    extra_global_params = None,
    additional_input_vars = None,
    is_auto_refractory_required = None,
    custom_body = None )
```

This helper function creates a custom `NeuronModel` class.

#### See also

[create\\_custom\\_postsynaptic\\_class](#)  
[create\\_custom\\_weight\\_update\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_init\\_var\\_snippet\\_class](#)  
[create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#)

#### Parameters

<i>class_name</i>	name of the new class
<i>param_names</i>	list of strings with param names of the model
<i>var_name_types</i>	list of pairs of strings with variable names and types of the model



## Parameters

<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of a class which inherits from <code>pygenn.genn_wrapper.Snippet.DerivedParamFunc</code>
<i>sim_code</i>	string with the simulation code
<i>threshold_condition_code</i>	string with the threshold condition code
<i>reset_code</i>	string with the reset code
<i>support_code</i>	string with the support code
<i>extra_global_params</i>	list of pairs of strings with names and types of additional parameters
<i>additional_input_vars</i>	list of tuples with names and types as strings and initial values of additional local input variables
<i>is_auto_refractory_required</i>	does this model require auto-refractory logic to be generated?
<i>custom_body</i>	dictionary with additional attributes and methods of the new class

18.19.1.6 `create_custom_postsynaptic_class()`

```
def pygenn.genn_model.create_custom_postsynaptic_class (
    class_name,
    param_names = None,
    var_name_types = None,
    derived_params = None,
    decay_code = None,
    apply_input_code = None,
    support_code = None,
    custom_body = None )
```

This helper function creates a custom PostsynapticModel class.

## See also

[create\\_custom\\_neuron\\_class](#)  
[create\\_custom\\_weight\\_update\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_init\\_var\\_snippet\\_class](#)  
[create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#)

## Parameters

<i>class_name</i>	name of the new class
<i>param_names</i>	list of strings with param names of the model
<i>var_name_types</i>	list of pairs of strings with variable names and types of the model
<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of a class which inherits from <code>pygenn.genn_wrapper.DerivedParamFunc</code>
<i>decay_code</i>	string with the decay code
<i>apply_input_code</i>	string with the apply input code
<i>support_code</i>	string with the support code
<i>custom_body</i>	dictionary with additional attributes and methods of the new class

### 18.19.1.7 `create_custom_sparse_connect_init_snippet_class()`

```
def pygenn.genn_model.create_custom_sparse_connect_init_snippet_class (
    class_name,
    param_names = None,
    derived_params = None,
    row_build_code = None,
    row_build_state_vars = None,
    calc_max_row_len_func = None,
    calc_max_col_len_func = None,
    extra_global_params = None,
    custom_body = None )
```

This helper function creates a custom [InitSparseConnectivitySnippet](#) class.

See also

[create\\_custom\\_neuron\\_class](#)  
[create\\_custom\\_weight\\_update\\_class](#)  
[create\\_custom\\_postsynaptic\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_init\\_var\\_snippet\\_class](#)

#### Parameters

<i>class_name</i>	name of the new class
<i>param_names</i>	list of strings with param names of the model
<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of the class which inherits from <code>pygenn.genn_wrapper.DerivedParamFunc</code>
<i>row_build_code</i>	string with row building initialization code
<i>row_build_state_vars</i>	list of tuples of state variables, their types and their initial values to use across row building loop
<i>calc_max_row_len_func</i>	instance of class inheriting from <code>CalcMaxLengthFunc</code> used to calculate maximum row length of synaptic matrix
<i>calc_max_col_len_func</i>	instance of class inheriting from <code>CalcMaxLengthFunc</code> used to calculate maximum col length of synaptic matrix
<i>extra_global_params</i>	list of pairs of strings with names and types of additional parameters
<i>custom_body</i>	dictionary with additional attributes and methods of the new class

### 18.19.1.8 `create_custom_weight_update_class()`

```
def pygenn.genn_model.create_custom_weight_update_class (
    class_name,
    param_names = None,
    var_name_types = None,
    pre_var_name_types = None,
    post_var_name_types = None,
    derived_params = None,
    sim_code = None,
    event_code = None,
    learn_post_code = None,
    synapse_dynamics_code = None,
    event_threshold_condition_code = None,
    pre_spike_code = None,
```

```

    post_spike_code = None,
    sim_support_code = None,
    learn_post_support_code = None,
    synapse_dynamics_support_code = None,
    extra_global_params = None,
    is_pre_spike_time_required = None,
    is_post_spike_time_required = None,
    custom_body = None )

```

This helper function creates a custom WeightUpdateModel class.

See also

[create\\_custom\\_neuron\\_class](#)  
[create\\_custom\\_postsynaptic\\_class](#)  
[create\\_custom\\_current\\_source\\_class](#)  
[create\\_custom\\_init\\_var\\_snippet\\_class](#)  
[create\\_custom\\_sparse\\_connect\\_init\\_snippet\\_class](#)

#### Parameters

<i>class_name</i>	name of the new class
<i>param_names</i>	list of strings with param names of the model
<i>var_name_types</i>	list of pairs of strings with variable names and types of the model
<i>pre_var_name_types</i>	list of pairs of strings with presynaptic variable names and types of the model
<i>post_var_name_types</i>	list of pairs of strings with postsynaptic variable names and types of the model
<i>derived_params</i>	list of pairs, where the first member is string with name of the derived parameter and the second MUST be an instance of a class which inherits from <code>pygenn.genn_wrapper.DerivedParamFunc</code>
<i>sim_code</i>	string with the simulation code
<i>event_code</i>	string with the event code
<i>learn_post_code</i>	string with the code to include in <code>learn_synapse_post</code> kernel/function
<i>synapse_dynamics_code</i>	string with the synapse dynamics code
<i>event_threshold_condition_code</i>	string with the event threshold condition code
<i>pre_spike_code</i>	string with the code run once per spiking presynaptic neuron
<i>post_spike_code</i>	string with the code run once per spiking postsynaptic neuron
<i>sim_support_code</i>	string with simulation support code
<i>learn_post_support_code</i>	string with support code for <code>learn_synapse_post</code> kernel/function
<i>synapse_dynamics_support_code</i>	string with synapse dynamics support code
<i>extra_global_params</i>	list of pairs of strings with names and types of additional parameters
<i>is_pre_spike_time_required</i>	boolean, is presynaptic spike time required in any weight update kernels?
<i>is_post_spike_time_required</i>	boolean, is postsynaptic spike time required in any weight update kernels?
<i>custom_body</i>	dictionary with additional attributes and methods of the new class

#### 18.19.1.9 create\_dpf\_class()

```

def pygenn.genn_model.create_dpf_class (
    dp_func )

```

Helper function to create derived parameter function class.

#### Parameters

<i>dp_func</i>	a function which computes the derived parameter and takes two args "pars" (vector of double) and "dt" (double)
----------------	--

#### 18.19.1.10 init\_connectivity()

```
def pygenn.genn_model.init_connectivity (
    init_sparse_connect_snippet,
    param_space )
```

This helper function creates a [InitSparseConnectivitySnippet::Init](#) object to easily initialise connectivity using a snippet.

#### Parameters

<i>init_sparse_connect_snippet</i>	type of the <a href="#">InitSparseConnectivitySnippet</a> class as string or instance of class derived from <a href="#">InitSparseConnectivitySnippet::Custom</a> .
<i>param_space</i>	dict with param values for the <a href="#">InitSparseConnectivitySnippet</a> class

#### 18.19.1.11 init\_var()

```
def pygenn.genn_model.init_var (
    init_var_snippet,
    param_space )
```

This helper function creates a [VarInit](#) object to easily initialise a variable using a snippet.

#### Parameters

<i>init_var_snippet</i>	type of the <a href="#">InitVarSnippet</a> class as string or instance of class derived from <a href="#">InitVarSnippet::Custom</a> class.
<i>param_space</i>	dict with param values for the <a href="#">InitVarSnippet</a> class

### 18.19.2 Variable Documentation

#### 18.19.2.1 backend\_modules

```
pygenn.genn_model.backend_modules = OrderedDict()
```

#### 18.19.2.2 m

```
pygenn.genn_model.m = import_module(".genn_wrapper." + b + "Backend", "pygenn")
```

## 18.20 pygenn.model\_preprocessor Namespace Reference

## Classes

- class [ExtraGlobalVariable](#)  
*Class holding information about GeNN extra global pointer variable.*
- class [Variable](#)  
*Class holding information about GeNN variables.*

## Functions

- def [prepare\\_model](#) (model, param\_space, var\_space, pre\_var\_space=None, post\_var\_space=None, model\_family=None)  
*Prepare a model by checking its validity and extracting information about variables and parameters.*
- def [prepare\\_snippet](#) (snippet, param\_space, snippet\_family)  
*Prepare a snippet by checking its validity and extracting information about parameters.*
- def [is\\_model\\_valid](#) (model, model\_family)  
*Check whether the model is valid, i.e is native or derived from model\_family.Custom.*
- def [param\\_space\\_to\\_vals](#) (model, param\_space)  
*Convert a param\_space dict to ParamValues.*
- def [param\\_space\\_to\\_val\\_vec](#) (model, param\_space)  
*Convert a param\_space dict to a std::vector<double>*
- def [var\\_space\\_to\\_vals](#) (model, var\_space)  
*Convert a var\_space dict to VarValues.*
- def [pre\\_var\\_space\\_to\\_vals](#) (model, var\_space)  
*Convert a var\_space dict to PreVarValues.*
- def [post\\_var\\_space\\_to\\_vals](#) (model, var\_space)  
*Convert a var\_space dict to PostVarValues.*

## Variables

- [GeNNType](#) = namedtuple("GeNNType", ["np\_dtype", "assign\_ext\_ptr\_array", "assign\_ext\_ptr\_single"])
- dictionary [genn\\_types](#)

## 18.20.1 Function Documentation

18.20.1.1 [is\\_model\\_valid\(\)](#)

```
def pygenn.model_preprocessor.is_model_valid (
    model,
    model_family )
```

Check whether the model is valid, i.e is native or derived from model\_family.Custom.

## Parameters

<i>model</i>	string or instance of model_family.Custom
<i>model_family</i>	model family ( <a href="#">NeuronModels</a> , <a href="#">WeightUpdateModels</a> or <a href="#">PostsynapticModels</a> ) to which model should belong to

**Returns**

instance of the model and its type as string

Raises ValueError if model is not valid (i.e. is not custom and is not natively available)

**18.20.1.2 param\_space\_to\_val\_vec()**

```
def pygenn.model_preprocessor.param_space_to_val_vec (
    model,
    param_space )
```

Convert a param\_space dict to a std::vector<double>

**Parameters**

<i>model</i>	instance of the model
<i>param_space</i>	dict with parameters

**Returns**

native vector of parameters

**18.20.1.3 param\_space\_to\_vals()**

```
def pygenn.model_preprocessor.param_space_to_vals (
    model,
    param_space )
```

Convert a param\_space dict to ParamValues.

**Parameters**

<i>model</i>	instance of the model
<i>param_space</i>	dict with parameters

**Returns**

native model's ParamValues

**18.20.1.4 post\_var\_space\_to\_vals()**

```
def pygenn.model_preprocessor.post_var_space_to_vals (
    model,
    var_space )
```

Convert a var\_space dict to PostVarValues.

**Parameters**

<i>model</i>	instance of the weight update model
<i>var_space</i>	dict with Variables

**Returns**

native model's VarValues

**18.20.1.5 pre\_var\_space\_to\_vals()**

```
def pygenn.model_preprocessor.pre_var_space_to_vals (
    model,
    var_space )
```

Convert a var\_space dict to PreVarValues.

**Parameters**

<i>model</i>	instance of the weight update model
<i>var_space</i>	dict with Variables

**Returns**

native model's VarValues

**18.20.1.6 prepare\_model()**

```
def pygenn.model_preprocessor.prepare_model (
    model,
    param_space,
    var_space,
    pre_var_space = None,
    post_var_space = None,
    model_family = None )
```

Prepare a model by checking its validity and extracting information about variables and parameters.

**Parameters**

<i>model</i>	string or instance of a class derived from pygenn.genn_wrapper.NeuronModels.Custom or pygenn.genn_wrapper.WeightUpdateModels.Custom or pygenn.genn_wrapper.CurrentSourceModels.Custom
<i>param_space</i>	dict with model parameters
<i>var_space</i>	dict with model variables
<i>pre_var_space</i>	optional dict with (weight update) model presynaptic variables
<i>post_var_space</i>	optional dict with (weight update) model postsynaptic variables
<i>model_family</i>	pygenn.genn_wrapper.NeuronModels or pygenn.genn_wrapper.WeightUpdateModels or pygenn.genn_wrapper.CurrentSourceModels

**Returns**

tuple consisting of (model instance, model type, model parameter names, model parameters, list of variable names, dict mapping names of variables to instances of class [Variable](#))

### 18.20.1.7 prepare\_snippet()

```
def pygenn.model_preprocessor.prepare_snippet (
    snippet,
    param_space,
    snippet_family )
```

Prepare a snippet by checking its validity and extracting information about parameters.

#### Parameters

<i>snippet</i>	string or instance of a class derived from pygenn.genn_wrapper.InitVarSnippet.Custom or pygenn.genn_wrapper.InitSparseConnectivitySnippet.Custom
<i>param_space</i>	dict with model parameters
<i>snippet_family</i>	pygenn.genn_wrapper.InitVarSnippet or pygenn.genn_wrapper.InitSparseConnectivitySnippet

#### Returns

tuple consisting of (snippet instance, snippet type, snippet parameter names, snippet parameters)

### 18.20.1.8 var\_space\_to\_vals()

```
def pygenn.model_preprocessor.var_space_to_vals (
    model,
    var_space )
```

Convert a `var_space` dict to `VarValues`.

#### Parameters

<i>model</i>	instance of the model
<i>var_space</i>	dict with Variables

#### Returns

native model's `VarValues`

## 18.20.2 Variable Documentation

### 18.20.2.1 genn\_types

dictionary `pygenn.model_preprocessor.genn_types`

#### Initial value:

```
1 = {
2   "scalar":      GeNNType(np.float32, slm.assign_external_pointer_array_f,
3   "float":       GeNNType(np.float32, slm.assign_external_pointer_array_f,
4   "double":      GeNNType(np.float64, slm.assign_external_pointer_array_d,
5   "int":         GeNNType(np.int32, slm.assign_external_pointer_array_i,
6   "unsigned int": GeNNType(np.uint32, slm.assign_external_pointer_array_ui,
```



```

    slm.assign_external_pointer_single_ui),
7  "short":      GeNNType(np.int16, slm.assign_external_pointer_array_s,
    slm.assign_external_pointer_single_s),
8  "unsigned short": GeNNType(np.uint16, slm.assign_external_pointer_array_us,
    slm.assign_external_pointer_single_us),
9  "char":      GeNNType(np.int8, slm.assign_external_pointer_array_sc,
    slm.assign_external_pointer_single_sc),
10 "unsigned char": GeNNType(np.uint8, slm.assign_external_pointer_array_uc,
    slm.assign_external_pointer_single_uc),
11 "uint64_t":    GeNNType(np.uint64, None, None),
12 "int64_t":     GeNNType(np.int64, None, None),
13 "uint32_t":    GeNNType(np.uint32, slm.assign_external_pointer_array_ui,
    slm.assign_external_pointer_single_ui),
14 "int32_t":     GeNNType(np.int32, slm.assign_external_pointer_array_i,
    slm.assign_external_pointer_single_i),
15 "uint16_t":    GeNNType(np.uint16, slm.assign_external_pointer_array_us,
    slm.assign_external_pointer_single_us),
16 "int16_t":     GeNNType(np.int16, slm.assign_external_pointer_array_s,
    slm.assign_external_pointer_single_s),
17 "uint8_t":     GeNNType(np.uint8, slm.assign_external_pointer_array_uc,
    slm.assign_external_pointer_single_uc),
18 "int8_t":      GeNNType(np.int8, slm.assign_external_pointer_array_sc,
    slm.assign_external_pointer_single_sc)}

```

### 18.20.2.2 GeNNType

```

pygenn.model_preprocessor.GeNNType = namedtuple("GeNNType", ["np_dtype", "assign_ext_ptr_↵
array", "assign_ext_ptr_single"])

```

## 18.21 Snippet Namespace Reference

### Classes

- class [Base](#)  
*Base class for all code snippets.*
- class [Init](#)
- class [ValueBase](#)
- class [ValueBase< 0 >](#)

### 18.21.1 Detailed Description

Wrapper to ensure at compile time that correct number of values are used when specifying the values of a model's parameters and initial state.

## 18.22 SpineMLSimulator Namespace Reference

### Namespaces

- [Connectors](#)
- [Input](#)
- [InputValue](#)
- [LogOutput](#)
- [ModelProperty](#)

### Classes

- class [NetworkClient](#)
- class [Simulator](#)
- class [StateVar](#)
- class [Timer](#)
- class [TimerAccumulate](#)

## Typedefs

- typedef float [scalar](#)

### 18.22.1 Typedef Documentation

#### 18.22.1.1 scalar

```
typedef float SpineMLSimulator::scalar
```

## 18.23 SpineMLSimulator::Connectors Namespace Reference

### Functions

- unsigned int [create](#) (const pugi::xml\_node &node, double dt, unsigned int numPre, unsigned int numPost, unsigned int \*\*rowLength, unsigned int \*\*ind, uint8\_t \*\*delay, const unsigned int \*maxRowLength, const filesystem::path &basePath, std::vector< unsigned int > &remapIndices)

### 18.23.1 Function Documentation

#### 18.23.1.1 create()

```
unsigned int SpineMLSimulator::Connectors::create (
    const pugi::xml_node & node,
    double dt,
    unsigned int numPre,
    unsigned int numPost,
    unsigned int ** rowLength,
    unsigned int ** ind,
    uint8_t ** delay,
    const unsigned int * maxRowLength,
    const filesystem::path & basePath,
    std::vector< unsigned int > & remapIndices )
```

## 18.24 SpineMLSimulator::Input Namespace Reference

### Classes

- class [Analogue](#)
- class [Base](#)
- class [InterSpikeIntervalBase](#)
- class [PoissonSpikeRate](#)
- class [RegularSpikeRate](#)
- class [SpikeBase](#)
- class [SpikeTime](#)

## 18.25 SpineMLSimulator::InputValue Namespace Reference

### Classes

- class [Base](#)

- class [Constant](#)
- class [ConstantArray](#)
- class [External](#)
- class [ExternalNetwork](#)
- class [ScalarBase](#)
- class [TimeVarying](#)
- class [TimeVaryingArray](#)

## Functions

- `std::unique_ptr< Base > create` (double dt, unsigned int numNeurons, const pugi::xml\_node &node, std::map< std::string, [InputValue::External](#) \*> &externalInputs)

### 18.25.1 Function Documentation

#### 18.25.1.1 create()

```
std::unique_ptr< SpineMLSimulator::InputValue::Base > SpineMLSimulator::InputValue::create (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node,
    std::map< std::string, InputValue::External *> & externalInputs )
```

## 18.26 SpineMLSimulator::LogOutput Namespace Reference

### Classes

- class [AnalogueBase](#)
- class [AnalogueExternal](#)
- class [AnalogueFile](#)
- class [AnalogueNetwork](#)
- class [Base](#)
- class [Event](#)

## 18.27 SpineMLSimulator::ModelProperty Namespace Reference

### Classes

- class [Base](#)
- class [ExponentialDistribution](#)
- class [Fixed](#)
- class [NormalDistribution](#)
- class [UniformDistribution](#)
- class [ValueList](#)

## Functions

- `std::unique_ptr< Base > create` (const pugi::xml\_node &node, const [StateVar](#)< [scalar](#) > &stateVar, unsigned int size, bool skipGeNNInitialised, const filesystem::path &basePath, const std::string &valueNamespace, const std::vector< unsigned int > \*remapIndices)

## 18.27.1 Function Documentation

### 18.27.1.1 create()

```
std::unique_ptr< SpineMLSimulator::ModelProperty::Base > SpineMLSimulator::ModelProperty←
::create (
    const pugi::xml_node & node,
    const StateVar< scalar > & stateVar,
    unsigned int size,
    bool skipGeNNInitialised,
    const filesystem::path & basePath,
    const std::string & valueNamespace,
    const std::vector< unsigned int > * remapIndices )
```

## 18.28 Utils Namespace Reference

### Functions

- **GENN\_EXPORT** bool **isRNGRequired** (const std::string &code)  
*Does the code string contain any functions requiring random number generator.*
- **GENN\_EXPORT** bool **isRNGRequired** (const std::vector< **Models::VarInit** > &varInitialisers)  
*Does the model with the vectors of variable initialisers and modes require an RNG for the specified init location i.e. host or device.*
- **GENN\_EXPORT** bool **isTypePointer** (const std::string &type)  
*Function to determine whether a string containing a type is a pointer.*
- **GENN\_EXPORT** std::string **getUnderlyingType** (const std::string &type)  
*Assuming type is a string containing a pointer type, function to return the underlying type.*

## 18.28.1 Function Documentation

### 18.28.1.1 getUnderlyingType()

```
std::string Utils::getUnderlyingType (
    const std::string & type )
```

Assuming type is a string containing a pointer type, function to return the underlying type.

### 18.28.1.2 isRNGRequired() [1/2]

```
bool Utils::isRNGRequired (
    const std::string & code )
```

Does the code string contain any functions requiring random number generator.

### 18.28.1.3 isRNGRequired() [2/2]

```
bool Utils::isRNGRequired (
    const std::vector< Models::VarInit > & varInitialisers )
```

Does the model with the vectors of variable initialisers and modes require an RNG for the specified init location i.e. host or device.

## 18.28.1.4 isTypePointer()

```
bool Utils::isTypePointer (
    const std::string & type )
```

Function to determine whether a string containing a type is a pointer.

## 18.29 WeightUpdateModels Namespace Reference

## Classes


- class [Base](#)  
*Base class for all weight update models.*
- class [PiecewiseSTDP](#)  
*This is a simple STDP rule including a time delay for the finite transmission speed of the synapse.*
- class [StaticGraded](#)  
*Graded-potential, static synapse.*
- class [StaticPulse](#)  
*Pulse-coupled, static synapse.*
- class [StaticPulseDendriticDelay](#)  
*Pulse-coupled, static synapse with heterogenous dendritic delays.*

## 19 Class Documentation

## 19.1 SpineMLSimulator::Input::Analogue Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::Analogue:



## Public Member Functions

- [Analogue](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value, [ModelProperty::Base](#) \*modelProperty)
- virtual void [apply](#) (double dt, unsigned long long timestep) override

## Additional Inherited Members

## 19.1.1 Constructor &amp; Destructor Documentation

### 19.1.1.1 Analogue()

```
SpineMLSimulator::Input::Analogue::Analogue (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value,
    ModelProperty::Base * modelProperty )
```

## 19.1.2 Member Function Documentation

### 19.1.2.1 apply()

```
void SpineMLSimulator::Input::Analogue::apply (
    double dt,
    unsigned long long timestep ) [override], [virtual]
```

Implements [SpineMLSimulator::Input::Base](#).


The documentation for this class was generated from the following files:

- [input.h](#)
- [input.cc](#)

## 19.2 SpineMLSimulator::LogOutput::AnalogueBase Class Reference

```
#include <logOutput.h>
```

Inheritance diagram for SpineMLSimulator::LogOutput::AnalogueBase:



### Public Member Functions

- [AnalogueBase](#) (const pugi::xml\_node &node, double dt, const [ModelProperty::Base](#) \*modelProperty)
- const scalar \* [getStateVarBegin](#) () const
- const scalar \* [getStateVarEnd](#) () const
- unsigned int [getModelPropertySize](#) () const
- const std::vector< unsigned int > & [getIndices](#) () const

### Protected Member Functions

- void [pullModelPropertyFromDevice](#) () const

### 19.2.1 Constructor & Destructor Documentation

## 19.2.1.1 AnalogueBase()

```
SpineMLSimulator::LogOutput::AnalogueBase::AnalogueBase (
    const pugi::xml_node & node,
    double dt,
    const ModelProperty::Base * modelProperty )
```

## 19.2.2 Member Function Documentation

## 19.2.2.1 getIndices()

```
const std::vector<unsigned int>& SpineMLSimulator::LogOutput::AnalogueBase::getIndices ( )
const [inline]
```

## 19.2.2.2 getModelPropertySize()

```
unsigned int SpineMLSimulator::LogOutput::AnalogueBase::getModelPropertySize ( ) const [inline]
```

## 19.2.2.3 getStateVarBegin()

```
const scalar* SpineMLSimulator::LogOutput::AnalogueBase::getStateVarBegin ( ) const [inline]
```

## 19.2.2.4 getStateVarEnd()

```
const scalar* SpineMLSimulator::LogOutput::AnalogueBase::getStateVarEnd ( ) const [inline]
```

## 19.2.2.5 pullModelPropertyFromDevice()

```
void SpineMLSimulator::LogOutput::AnalogueBase::pullModelPropertyFromDevice ( ) const [inline],
[protected]
```


The documentation for this class was generated from the following files:

- [logOutput.h](#)
- [logOutput.cc](#)

## 19.3 SpineMLSimulator::LogOutput::AnalogueExternal Class Reference

```
#include <logOutput.h>
```

Inheritance diagram for SpineMLSimulator::LogOutput::AnalogueExternal:



### Public Member Functions

- [AnalogueExternal](#) (const `pugi::xml_node &node`, double `dt`, const `std::string &port`, unsigned int `popSize`, const `filesystem::path &logPath`, const [ModelProperty::Base](#) \*`modelProperty`)
- virtual void [record](#) (double `dt`, unsigned long long `timestep`) final

### Protected Member Functions

- virtual void [recordInternal](#) ()

## 19.3.1 Constructor & Destructor Documentation

### 19.3.1.1 AnalogueExternal()

```

SpineMLSimulator::LogOutput::AnalogueExternal::AnalogueExternal (
    const pugi::xml_node & node,
    double dt,
    const std::string & port,
    unsigned int popSize,
    const filesystem::path & logPath,
    const ModelProperty::Base * modelProperty )

```

## 19.3.2 Member Function Documentation

### 19.3.2.1 record()

```

void SpineMLSimulator::LogOutput::AnalogueExternal::record (
    double dt,
    unsigned long long timestep ) [final], [virtual]

```

Implements [SpineMLSimulator::LogOutput::Base](#).

### 19.3.2.2 recordInternal()

```

virtual void SpineMLSimulator::LogOutput::AnalogueExternal::recordInternal ( ) [inline],
[protected], [virtual]

```

Reimplemented in [SpineMLSimulator::LogOutput::AnalogueNetwork](#).

The documentation for this class was generated from the following files:




- [logOutput.h](#)
- [logOutput.cc](#)

## 19.4 SpineMLSimulator::LogOutput::AnalogueFile Class Reference

```
#include <logOutput.h>
```

Inheritance diagram for SpineMLSimulator::LogOutput::AnalogueFile:



### Public Member Functions

- [AnalogueFile](#) (const pugi::xml\_node &node, double dt, unsigned long long numTimeSteps, const std::string &port, unsigned int popSize, const filesystem::path &logPath, const [ModelProperty::Base](#) \*modelProperty)
- virtual void [record](#) (double dt, unsigned long long timestep) override

### Additional Inherited Members

#### 19.4.1 Constructor & Destructor Documentation

##### 19.4.1.1 AnalogueFile()

```
SpineMLSimulator::LogOutput::AnalogueFile::AnalogueFile (
    const pugi::xml_node & node,
    double dt,
    unsigned long long numTimeSteps,
    const std::string & port,
    unsigned int popSize,
    const filesystem::path & logPath,
    const ModelProperty::Base * modelProperty )
```

#### 19.4.2 Member Function Documentation

##### 19.4.2.1 record()

```
void SpineMLSimulator::LogOutput::AnalogueFile::record (
    double dt,
    unsigned long long timestep ) [override], [virtual]
```

Implements [SpineMLSimulator::LogOutput::Base](#).


The documentation for this class was generated from the following files:

- [logOutput.h](#)
- [logOutput.cc](#)

## 19.5 SpineMLSimulator::LogOutput::AnalogueNetwork Class Reference

```
#include <logOutput.h>
```

Inheritance diagram for SpineMLSimulator::LogOutput::AnalogueNetwork:



### Public Member Functions

- [AnalogueNetwork](#) (const pugi::xml\_node &node, double dt, const std::string &port, unsigned int popSize, const filesystem::path &logPath, const [ModelProperty::Base](#) \*modelProperty)

### Protected Member Functions

- virtual void [recordInternal](#) () override

### 19.5.1 Constructor & Destructor Documentation

#### 19.5.1.1 AnalogueNetwork()

```
SpineMLSimulator::LogOutput::AnalogueNetwork::AnalogueNetwork (
    const pugi::xml_node & node,
    double dt,
    const std::string & port,
    unsigned int popSize,
    const filesystem::path & logPath,
    const ModelProperty::Base * modelProperty )
```

### 19.5.2 Member Function Documentation

#### 19.5.2.1 recordInternal()

```
void SpineMLSimulator::LogOutput::AnalogueNetwork::recordInternal ( ) [override], [protected], [virtual]
```

Reimplemented from [SpineMLSimulator::LogOutput::AnalogueExternal](#).

The documentation for this class was generated from the following files:

- [logOutput.h](#)
- [logOutput.cc](#)

## 19.6 AnalogueRecorder< T > Class Template Reference

```
#include <analogueRecorder.h>
```

### Public Member Functions

- [AnalogueRecorder](#) (const std::string &filename, std::initializer\_list< T \*> variables, unsigned int popSize, const std::string &delimiter=" ")
- [AnalogueRecorder](#) (const std::string &filename, T \*variable, unsigned int popSize, const std::string &delimiter=" ")
- void [record](#) (double t)

### 19.6.1 Constructor & Destructor Documentation

#### 19.6.1.1 AnalogueRecorder() [1/2]

```
template<typename T >
AnalogueRecorder< T >::AnalogueRecorder (
    const std::string & filename,
    std::initializer_list< T *> variables,
    unsigned int popSize,
    const std::string & delimiter = " " ) [inline]
```

#### 19.6.1.2 AnalogueRecorder() [2/2]

```
template<typename T >
AnalogueRecorder< T >::AnalogueRecorder (
    const std::string & filename,
    T * variable,
    unsigned int popSize,
    const std::string & delimiter = " " ) [inline]
```

### 19.6.2 Member Function Documentation

#### 19.6.2.1 record()

```
template<typename T >
void AnalogueRecorder< T >::record (
    double t ) [inline]
```


The documentation for this class was generated from the following file:

- [analogueRecorder.h](#)

## 19.7 CodeGenerator::CUDA::Backend Class Reference

```
#include <backend.h>
```

Inheritance diagram for CodeGenerator::CUDA::Backend:



## Public Member Functions

- **Backend** (const [KernelBlockSize](#) &kernelBlockSizes, const [Preferences](#) &preferences, int localHostID, const std::string &scalarType, int device)
- virtual void **genNeuronUpdate** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [NeuronGroupSimHandler](#) simHandler, [NeuronGroupHandler](#) wuVarUpdateHandler) const override  
*Generate platform-specific function to update the state of all neurons.*
- virtual void **genSynapseUpdate** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [SynapseGroupHandler](#) wumThreshHandler, [SynapseGroupHandler](#) wumSimHandler, [SynapseGroupHandler](#) wumEventHandler, [SynapseGroupHandler](#) wumProceduralConnectHandler, [SynapseGroupHandler](#) postLearnHandler, [SynapseGroupHandler](#) synapseDynamicsHandler) const override  
*Generate platform-specific function to update the state of all synapses.*
- virtual void **genInit** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [NeuronGroupHandler](#) localNGHandler, [NeuronGroupHandler](#) remoteNGHandler, [SynapseGroupHandler](#) sgDenseInitHandler, [SynapseGroupHandler](#) sgSparseConnectHandler, [SynapseGroupHandler](#) sgSparseInitHandler) const override
- virtual size\_t **getSynapticMatrixRowStride** (const [SynapseGroupInternal](#) &sg) const override  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual void **genDefinitionsPreamble** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override  
*Definitions is the usercode-facing header file for the generated code. This function generates a 'preamble' to this header file.*
- virtual void **genDefinitionsInternalPreamble** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override  
*Definitions internal is the internal header file for the generated code. This function generates a 'preamble' to this header file.*
- virtual void **genRunnerPreamble** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override
- virtual void **genAllocateMemPreamble** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override
- virtual void **genStepTimeFinalisePreamble** ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override  
*After all timestep logic is complete.*
- virtual void **genVariableDefinition** ([CodeStream](#) &definitions, [CodeStream](#) &definitionsInternal, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genVariableImplementation** ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual [MemAlloc](#) **genVariableAllocation** ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, size\_t count) const override
- virtual void **genVariableFree** ([CodeStream](#) &os, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genExtraGlobalParamDefinition** ([CodeStream](#) &definitions, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genExtraGlobalParamImplementation** ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genExtraGlobalParamAllocation** ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genExtraGlobalParamPush** ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genExtraGlobalParamPull** ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void **genPopVariableInit** ([CodeStream](#) &os, [VarLocation](#) loc, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const override

- virtual void `genVariableInit` (`CodeStream` &os, `VarLocation` loc, `size_t` count, const std::string &indexVarName, const `Substitutions` &kernelSubs, `Handler` handler) const override
- virtual void `genSynapseVariableRowInit` (`CodeStream` &os, `VarLocation` loc, const `SynapseGroupInternal` &sg, const `Substitutions` &kernelSubs, `Handler` handler) const override
- virtual void `genVariablePush` (`CodeStream` &os, const std::string &type, const std::string &name, `VarLocation` loc, bool autoInitialized, `size_t` count) const override  
*Generate code for pushing a variable to the 'device'.*
- virtual void `genVariablePull` (`CodeStream` &os, const std::string &type, const std::string &name, `VarLocation` loc, `size_t` count) const override  
*Generate code for pulling a variable from the 'device'.*
- virtual void `genCurrentVariablePush` (`CodeStream` &os, const `NeuronGroupInternal` &ng, const std::string &type, const std::string &name, `VarLocation` loc) const override  
*Generate code for pushing a variable's value in the current timestep to the 'device'.*
- virtual void `genCurrentVariablePull` (`CodeStream` &os, const `NeuronGroupInternal` &ng, const std::string &type, const std::string &name, `VarLocation` loc) const override  
*Generate code for pulling a variable's value in the current timestep from the 'device'.*
- virtual void `genCurrentTrueSpikePush` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const override  
*Generate code for pushing true spikes emitted by a neuron group in the current timestep to the 'device'.*
- virtual void `genCurrentTrueSpikePull` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const override  
*Generate code for pulling true spikes emitted by a neuron group in the current timestep from the 'device'.*
- virtual void `genCurrentSpikeLikeEventPush` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const override  
*Generate code for pushing spike-like events emitted by a neuron group in the current timestep to the 'device'.*
- virtual void `genCurrentSpikeLikeEventPull` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const override  
*Generate code for pulling spike-like events emitted by a neuron group in the current timestep from the 'device'.*
- virtual `MemAlloc` `genGlobalRNG` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free) const override  
*Generate a single RNG instance.*
- virtual `MemAlloc` `genPopulationRNG` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free, const std::string &name, `size_t` count) const override  
*Generate an RNG with a state per population member.*
- virtual void `genTimer` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free, `CodeStream` &stepTimeFinalise, const std::string &name, bool updateInStepTime) const override
- virtual void `genReturnFreeDeviceMemoryBytes` (`CodeStream` &os) const override  
*Generate code to return amount of free 'device' memory in bytes.*
- virtual void `genMakefilePreamble` (std::ostream &os) const override  
*This function can be used to generate a preamble for the GNU makefile used to build.*
- virtual void `genMakefileLinkRule` (std::ostream &os) const override
- virtual void `genMakefileCompileRule` (std::ostream &os) const override
- virtual void `genMSBuildConfigProperties` (std::ostream &os) const override
- virtual void `genMSBuildImportProps` (std::ostream &os) const override
- virtual void `genMSBuildItemDefinitions` (std::ostream &os) const override
- virtual void `genMSBuildCompileModule` (const std::string &moduleName, std::ostream &os) const override
- virtual void `genMSBuildImportTarget` (std::ostream &os) const override
- virtual std::string `getVarPrefix` () const override
- virtual bool `isGlobalRNGRequired` (const `ModelSpecInternal` &model) const override  
*Different backends use different RNGs for different things. Does this one require a global RNG for the specified model?*
- virtual bool `isSynRemapRequired` () const override  
*Different backends may implement synapse dynamics differently. Does this one require a synapse remapping data structure?*

- virtual bool `isPostsynapticRemapRequired` () const override  
*Different backends may implement synaptic plasticity differently. Does this one require a postsynaptic remapping data structure?*
- virtual bool `isAutomaticCopyEnabled` () const override  
*Is automatic copy mode enabled in the preferences?*
- virtual size\_t `getDeviceMemoryBytes` () const override  
*How many bytes of memory does 'device' have.*
- const cudaDeviceProp & `getChosenCUDADevice` () const
- int `getChosenDeviceID` () const
- int `getRuntimeVersion` () const
- std::string `getNVCCFlags` () const
- std::string `getFloatAtomicAdd` (const std::string &ftype) const
- size\_t `getNumInitialisationRNGStreams` (const `ModelSpecInternal` &model) const  
*Get total number of RNG streams potentially used to initialise model.*
- size\_t `getKernelBlockSize` (`Kernel` kernel) const

### Static Public Member Functions

- static size\_t `getNumPresynapticUpdateThreads` (const `SynapseGroupInternal` &sg, const cudaDeviceProp &deviceProps, const `Preferences` &preferences)
- static size\_t `getNumPostsynapticUpdateThreads` (const `SynapseGroupInternal` &sg)
- static size\_t `getNumSynapseDynamicsThreads` (const `SynapseGroupInternal` &sg)
- static void `addPresynapticUpdateStrategy` (`PresynapticUpdateStrategy::Base` \*strategy)  
*Register a new presynaptic update strategy.*

### Static Public Attributes

- static const char \* `KernelNames` [`KernelMax`]

### Additional Inherited Members

## 19.7.1 Constructor & Destructor Documentation

### 19.7.1.1 Backend()

```
CodeGenerator::CUDA::Backend::Backend (
    const KernelBlockSize & kernelBlockSizes,
    const Preferences & preferences,
    int localHostID,
    const std::string & scalarType,
    int device )
```

## 19.7.2 Member Function Documentation

### 19.7.2.1 addPresynapticUpdateStrategy()

```
void CodeGenerator::CUDA::Backend::addPresynapticUpdateStrategy (
    PresynapticUpdateStrategy::Base * strategy ) [static]
```

Register a new presynaptic update strategy.

This function should be called with strategies in ascending order of preference

### 19.7.2.2 genAllocateMemPreamble()

```
void CodeGenerator::CUDA::Backend::genAllocateMemPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Allocate memory is the first function in GeNN generated code called by usercode and it should only ever be called once. Therefore it's a good place for any global initialisation. This function generates a 'preamble' to this function.

Implements [CodeGenerator::BackendBase](#).

### 19.7.2.3 genCurrentSpikeLikeEventPull()

```
virtual void CodeGenerator::CUDA::Backend::genCurrentSpikeLikeEventPull (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [inline], [override], [virtual]
```

Generate code for pulling spike-like events emitted by a neuron group in the current timestep from the 'device'.

Implements [CodeGenerator::BackendBase](#).

### 19.7.2.4 genCurrentSpikeLikeEventPush()

```
virtual void CodeGenerator::CUDA::Backend::genCurrentSpikeLikeEventPush (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [inline], [override], [virtual]
```

Generate code for pushing spike-like events emitted by a neuron group in the current timestep to the 'device'.

Implements [CodeGenerator::BackendBase](#).

### 19.7.2.5 genCurrentTrueSpikePull()

```
virtual void CodeGenerator::CUDA::Backend::genCurrentTrueSpikePull (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [inline], [override], [virtual]
```

Generate code for pulling true spikes emitted by a neuron group in the current timestep from the 'device'.

Implements [CodeGenerator::BackendBase](#).

### 19.7.2.6 genCurrentTrueSpikePush()

```
virtual void CodeGenerator::CUDA::Backend::genCurrentTrueSpikePush (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [inline], [override], [virtual]
```

Generate code for pushing true spikes emitted by a neuron group in the current timestep to the 'device'.

Implements [CodeGenerator::BackendBase](#).

### 19.7.2.7 genCurrentVariablePull()

```
void CodeGenerator::CUDA::Backend::genCurrentVariablePull (
    CodeStream & os,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
```

```
VarLocation loc ) const [override], [virtual]
```

Generate code for pulling a variable's value in the current timestep from the 'device'.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.8 genCurrentVariablePush()

```
void CodeGenerator::CUDA::Backend::genCurrentVariablePush (
    CodeStream & os,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Generate code for pushing a variable's value in the current timestep to the 'device'.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.9 genDefinitionsInternalPreamble()

```
void CodeGenerator::CUDA::Backend::genDefinitionsInternalPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Definitions internal is the internal header file for the generated code. This function generates a 'preamble' to this header file.

This will only be included by the platform-specific compiler used to build this backend so can include platform-specific types or headers

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.10 genDefinitionsPreamble()

```
void CodeGenerator::CUDA::Backend::genDefinitionsPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Definitions is the usercode-facing header file for the generated code. This function generates a 'preamble' to this header file.

This will be included from a standard C++ compiler so shouldn't include any platform-specific types or headers

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.11 genExtraGlobalParamAllocation()

```
void CodeGenerator::CUDA::Backend::genExtraGlobalParamAllocation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).



#### 19.7.2.12 genExtraGlobalParamDefinition()

```
void CodeGenerator::CUDA::Backend::genExtraGlobalParamDefinition (
    CodeStream & definitions,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.13 genExtraGlobalParamImplementation()

```
void CodeGenerator::CUDA::Backend::genExtraGlobalParamImplementation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.14 genExtraGlobalParamPull()

```
void CodeGenerator::CUDA::Backend::genExtraGlobalParamPull (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.15 genExtraGlobalParamPush()

```
void CodeGenerator::CUDA::Backend::genExtraGlobalParamPush (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.16 genGlobalRNG()

```
MemAlloc CodeGenerator::CUDA::Backend::genGlobalRNG (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free ) const [override], [virtual]
```

Generate a single RNG instance.

On single-threaded platforms this can be a standard RNG like M.T. but, on parallel platforms, it is likely to be a counter-based RNG

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.17 genInit()

```
void CodeGenerator::CUDA::Backend::genInit (
    CodeStream & os,
    const ModelSpecInternal & model,
    NeuronGroupHandler localNGHandler,
    NeuronGroupHandler remoteNGHandler,
    SynapseGroupHandler sgDenseInitHandler,
    SynapseGroupHandler sgSparseConnectHandler,
    SynapseGroupHandler sgSparseInitHandler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.18 genMakefileCompileRule()

```
void CodeGenerator::CUDA::Backend::genMakefileCompileRule (
    std::ostream & os ) const [override], [virtual]
```

The GNU make build system uses 'pattern rules' ([https://www.gnu.org/software/make/manual/html\\_node/Pattern-Intro.html](https://www.gnu.org/software/make/manual/html_node/Pattern-Intro.html)) to build backend modules into objects. This function should generate a GNU make pattern rule capable of building each module (i.e. compiling .cc file \$< into .o file \$@).

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.19 genMakefileLinkRule()

```
void CodeGenerator::CUDA::Backend::genMakefileLinkRule (
    std::ostream & os ) const [override], [virtual]
```

The GNU make build system will populate a variable called with a list of objects to link. This function should generate a GNU make rule to build these objects into a shared library.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.20 genMakefilePreamble()

```
void CodeGenerator::CUDA::Backend::genMakefilePreamble (
    std::ostream & os ) const [override], [virtual]
```

This function can be used to generate a preamble for the GNU makefile used to build.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.21 genMSBuildCompileModule()

```
void CodeGenerator::CUDA::Backend::genMSBuildCompileModule (
    const std::string & moduleName,
    std::ostream & os ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.22 genMSBuildConfigProperties()

```
void CodeGenerator::CUDA::Backend::genMSBuildConfigProperties (
    std::ostream & os ) const [override], [virtual]
```

In MSBuild, 'properties' are used to configure global project settings e.g. whether the MSBuild project builds a static

or dynamic library This function can be used to add additional XML properties to this section.

see <https://docs.microsoft.com/en-us/visualstudio/msbuild/msbuild-properties> for more information.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.23 genMSBuildImportProps()

```
void CodeGenerator::CUDA::Backend::genMSBuildImportProps (
    std::ostream & os ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.24 genMSBuildImportTarget()

```
void CodeGenerator::CUDA::Backend::genMSBuildImportTarget (
    std::ostream & os ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.25 genMSBuildItemDefinitions()

```
void CodeGenerator::CUDA::Backend::genMSBuildItemDefinitions (
    std::ostream & os ) const [override], [virtual]
```

In MSBuild, the 'item definitions' are used to override the default properties of 'items' such as <ClCompile> or <Link>. This function should generate XML to correctly configure the 'items' required to build the generated code, taking into account etc.

see <https://docs.microsoft.com/en-us/visualstudio/msbuild/msbuild-items#item-definitions> for more information.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.26 genNeuronUpdate()

```
void CodeGenerator::CUDA::Backend::genNeuronUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    NeuronGroupSimHandler simHandler,
    NeuronGroupHandler wuVarUpdateHandler ) const [override], [virtual]
```

Generate platform-specific function to update the state of all neurons.

##### Parameters

<i>os</i>	<a href="#">CodeStream</a> to write function to
<i>model</i>	model to generate code for
<i>simHandler</i>	callback to write platform-independent code to update an individual <a href="#">NeuronGroup</a>
<i>wuVarUpdateHandler</i>	callback to write platform-independent code to update pre and postsynaptic weight update model variables when neuron spikes

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.27 genPopulationRNG()

```
MemAlloc CodeGenerator::CUDA::Backend::genPopulationRNG (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free,
    const std::string & name,
    size_t count ) const [override], [virtual]
```

Generate an RNG with a state per population member.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.28 genPopVariableInit()

```
void CodeGenerator::CUDA::Backend::genPopVariableInit (
    CodeStream & os,
    VarLocation loc,
    const Substitutions & kernelSubs,
    Handler handler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.29 genReturnFreeDeviceMemoryBytes()

```
void CodeGenerator::CUDA::Backend::genReturnFreeDeviceMemoryBytes (
    CodeStream & os ) const [override], [virtual]
```

Generate code to return amount of free 'device' memory in bytes.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.30 genRunnerPreamble()

```
void CodeGenerator::CUDA::Backend::genRunnerPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.31 genStepTimeFinalisePreamble()

```
void CodeGenerator::CUDA::Backend::genStepTimeFinalisePreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

After all timestep logic is complete.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.32 genSynapseUpdate()

```
void CodeGenerator::CUDA::Backend::genSynapseUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
```

```

SynapseGroupHandler wumThreshHandler,
SynapseGroupHandler wumSimHandler,
SynapseGroupHandler wumEventHandler,
SynapseGroupHandler wumProceduralConnectHandler,
SynapseGroupHandler postLearnHandler,
SynapseGroupHandler synapseDynamicsHandler ) const [override], [virtual]

```

Generate platform-specific function to update the state of all synapses.

#### Parameters

<i>os</i>	<a href="#">CodeStream</a> to write function to
<i>model</i>	model to generate code for
<i>wumThreshHandler</i>	callback to write platform-independent code to update an individual <a href="#">NeuronGroup</a>
<i>wumSimHandler</i>	callback to write platform-independent code to process presynaptic spikes. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .
<i>wumEventHandler</i>	callback to write platform-independent code to process presynaptic spike-like events. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .
<i>wumProceduralConnectHandler</i>	callback to write platform-indepent code to procedurally generate connectivity "id_pre" variable and "addSynapse" function will be provided to callback via <a href="#">Substitutions</a> . callback needs to implement loop over synapses in row, providing "synAddress" variable if INDIVIDUALG
<i>postLearnHandler</i>	callback to write platform-independent code to process postsynaptic spikes. "id_pre", "id_post" and "id_syn" variables will be provided to callback via <a href="#">Substitutions</a> .
<i>synapseDynamicsHandler</i>	callback to write platform-independent code to update time-driven synapse dynamics. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.33 genSynapseVariableRowInit()

```

void CodeGenerator::CUDA::Backend::genSynapseVariableRowInit (
    CodeStream & os,
    VarLocation loc,
    const SynapseGroupInternal & sg,
    const Substitutions & kernelSubs,
    Handler handler ) const [override], [virtual]

```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.34 genTimer()

```

void CodeGenerator::CUDA::Backend::genTimer (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free,

```

```
CodeStream & stepTimeFinalise,  
const std::string & name,  
bool updateInStepTime ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.35 genVariableAllocation()

```
MemAlloc CodeGenerator::CUDA::Backend::genVariableAllocation (  
CodeStream & os,  
const std::string & type,  
const std::string & name,  
VarLocation loc,  
size_t count ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.36 genVariableDefinition()

```
void CodeGenerator::CUDA::Backend::genVariableDefinition (  
CodeStream & definitions,  
CodeStream & definitionsInternal,  
const std::string & type,  
const std::string & name,  
VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.37 genVariableFree()

```
void CodeGenerator::CUDA::Backend::genVariableFree (  
CodeStream & os,  
const std::string & name,  
VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.38 genVariableImplementation()

```
void CodeGenerator::CUDA::Backend::genVariableImplementation (  
CodeStream & os,  
const std::string & type,  
const std::string & name,  
VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.39 genVariableInit()

```
void CodeGenerator::CUDA::Backend::genVariableInit (  
CodeStream & os,  
VarLocation loc,  
size_t count,  
const std::string & indexVarName,  
const Substitutions & kernelSubs,
```

```
Handler handler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.40 genVariablePull()

```
void CodeGenerator::CUDA::Backend::genVariablePull (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    size_t count ) const [override], [virtual]
```

Generate code for pulling a variable from the 'device'.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.41 genVariablePush()

```
void CodeGenerator::CUDA::Backend::genVariablePush (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    bool autoInitialized,
    size_t count ) const [override], [virtual]
```

Generate code for pushing a variable to the 'device'.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.42 getChosenCUDADevice()

```
const cudaDeviceProp& CodeGenerator::CUDA::Backend::getChosenCUDADevice ( ) const [inline]
```

#### 19.7.2.43 getChosenDeviceID()

```
int CodeGenerator::CUDA::Backend::getChosenDeviceID ( ) const [inline]
```

#### 19.7.2.44 getDeviceMemoryBytes()

```
virtual size_t CodeGenerator::CUDA::Backend::getDeviceMemoryBytes ( ) const [inline], [override],
[virtual]
```

How many bytes of memory does 'device' have.

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.45 getFloatAtomicAdd()

```
std::string CodeGenerator::CUDA::Backend::getFloatAtomicAdd (
    const std::string & ftype ) const
```

**19.7.2.46 getKernelBlockSize()**

```
size_t CodeGenerator::CUDA::Backend::getKernelBlockSize (
    Kernel kernel ) const [inline]
```

**19.7.2.47 getNumInitialisationRNGStreams()**

```
size_t CodeGenerator::CUDA::Backend::getNumInitialisationRNGStreams (
    const ModelSpecInternal & model ) const
```

Get total number of RNG streams potentially used to initialise model.

**NOTE** because RNG supports  $2^{64}$  streams, we are overly conservative

**19.7.2.48 getNumPostsynapticUpdateThreads()**

```
size_t CodeGenerator::CUDA::Backend::getNumPostsynapticUpdateThreads (
    const SynapseGroupInternal & sg ) [static]
```

**19.7.2.49 getNumPresynapticUpdateThreads()**

```
size_t CodeGenerator::CUDA::Backend::getNumPresynapticUpdateThreads (
    const SynapseGroupInternal & sg,
    const cudaDeviceProp & deviceProps,
    const Preferences & preferences ) [static]
```

**19.7.2.50 getNumSynapseDynamicsThreads()**

```
size_t CodeGenerator::CUDA::Backend::getNumSynapseDynamicsThreads (
    const SynapseGroupInternal & sg ) [static]
```

**19.7.2.51 getNVCCFlags()**

```
std::string CodeGenerator::CUDA::Backend::getNVCCFlags ( ) const
```

**19.7.2.52 getRuntimeVersion()**

```
int CodeGenerator::CUDA::Backend::getRuntimeVersion ( ) const [inline]
```

**19.7.2.53 getSynapticMatrixRowStride()**

```
size_t CodeGenerator::CUDA::Backend::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implements [CodeGenerator::BackendBase](#).

**19.7.2.54 getVarPrefix()**

```
virtual std::string CodeGenerator::CUDA::Backend::getVarPrefix ( ) const [inline], [override],
[virtual]
```



When backends require separate 'device' and 'host' versions of variables, they are identified with a prefix. This function returns this prefix so it can be used in otherwise platform-independent code.

Reimplemented from [CodeGenerator::BackendBase](#).

#### 19.7.2.55 isAutomaticCopyEnabled()

```
virtual bool CodeGenerator::CUDA::Backend::isAutomaticCopyEnabled ( ) const [inline], [override], [virtual]
```

Is automatic copy mode enabled in the preferences?

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.56 isGlobalRNGRequired()

```
bool CodeGenerator::CUDA::Backend::isGlobalRNGRequired (
    const ModelSpecInternal & model ) const [override], [virtual]
```

Different backends use different RNGs for different things. Does this one require a global RNG for the specified model?

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.57 isPostsynapticRemapRequired()

```
virtual bool CodeGenerator::CUDA::Backend::isPostsynapticRemapRequired ( ) const [inline], [override], [virtual]
```

Different backends may implement synaptic plasticity differently. Does this one require a postsynaptic remapping data structure?

Implements [CodeGenerator::BackendBase](#).

#### 19.7.2.58 isSynRemapRequired()

```
virtual bool CodeGenerator::CUDA::Backend::isSynRemapRequired ( ) const [inline], [override], [virtual]
```

Different backends may implement synapse dynamics differently. Does this one require a synapse remapping data structure?

Implements [CodeGenerator::BackendBase](#).

### 19.7.3 Member Data Documentation

#### 19.7.3.1 KernelNames

```
const char * CodeGenerator::CUDA::Backend::KernelNames [static]
```

**Initial value:**

```
= {
    "updateNeuronsKernel",
    "updatePresynapticKernel",
    "updatePostsynapticKernel",
    "updateSynapseDynamicsKernel",
    "initializeKernel",
}
```

```
"initializeSparseKernel",
"preNeuronResetKernel",
"preSynapseResetKernel"}

```

The documentation for this class was generated from the following files:


- [cuda/backend.h](#)
- [cuda/backend.cc](#)

## 19.8 CodeGenerator::SingleThreadedCPU::Backend Class Reference

```
#include <backend.h>

```

Inheritance diagram for CodeGenerator::SingleThreadedCPU::Backend:



### Public Member Functions

- [Backend](#) (int localhostID, const std::string &scalarType, const [Preferences](#) &preferences)
- virtual void [genNeuronUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [NeuronGroupSimHandler](#) simHandler, [NeuronGroupHandler](#) wuVarUpdateHandler) const override  
*Generate platform-specific function to update the state of all neurons.*
- virtual void [genSynapseUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [SynapseGroupHandler](#) wumThreshHandler, [SynapseGroupHandler](#) wumSimHandler, [SynapseGroupHandler](#) wumEventHandler, [SynapseGroupHandler](#) wumProceduralConnectHandler, [SynapseGroupHandler](#) postLearnHandler, [SynapseGroupHandler](#) synapseDynamicsHandler) const override  
*Generate platform-specific function to update the state of all synapses.*
- virtual void [genInit](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [NeuronGroupHandler](#) localNGHandler, [NeuronGroupHandler](#) remoteNGHandler, [SynapseGroupHandler](#) sgDenseInitHandler, [SynapseGroupHandler](#) sgSparseConnectHandler, [SynapseGroupHandler](#) sgSparseInitHandler) const override
- virtual size\_t [getSynapticMatrixRowStride](#) (const [SynapseGroupInternal](#) &sg) const override  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual void [genDefinitionsPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override  
*Definitions is the usercode-facing header file for the generated code. This function generates a 'preamble' to this header file.*
- virtual void [genDefinitionsInternalPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override  
*Definitions internal is the internal header file for the generated code. This function generates a 'preamble' to this header file.*
- virtual void [genRunnerPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override
- virtual void [genAllocateMemPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override
- virtual void [genStepTimeFinalisePreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const override  
*After all timestep logic is complete.*
- virtual void [genVariableDefinition](#) ([CodeStream](#) &definitions, [CodeStream](#) &definitionsInternal, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genVariableImplementation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual [MemAlloc](#) [genVariableAllocation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, size\_t count) const override

- virtual void [genVariableFree](#) ([CodeStream](#) &os, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genExtraGlobalParamDefinition](#) ([CodeStream](#) &definitions, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genExtraGlobalParamImplementation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genExtraGlobalParamAllocation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genExtraGlobalParamPush](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genExtraGlobalParamPull](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- virtual void [genPopVariableInit](#) ([CodeStream](#) &os, [VarLocation](#) loc, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const override
- virtual void [genVariableInit](#) ([CodeStream](#) &os, [VarLocation](#) loc, size\_t count, const std::string &indexVarName, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const override
- virtual void [genSynapseVariableRowInit](#) ([CodeStream](#) &os, [VarLocation](#) loc, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const override
- virtual void [genVariablePush](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, bool autoInitialized, size\_t count) const override
- Generate code for pushing a variable to the 'device'.*
- virtual void [genVariablePull](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, size\_t count) const override
- Generate code for pulling a variable from the 'device'.*
- virtual void [genCurrentVariablePush](#) ([CodeStream](#) &os, const [NeuronGroupInternal](#) &ng, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- Generate code for pushing a variable's value in the current timestep to the 'device'.*
- virtual void [genCurrentVariablePull](#) ([CodeStream](#) &os, const [NeuronGroupInternal](#) &ng, const std::string &type, const std::string &name, [VarLocation](#) loc) const override
- Generate code for pulling a variable's value in the current timestep from the 'device'.*
- virtual void [genCurrentTrueSpikePush](#) ([CodeStream](#) &os, const [NeuronGroupInternal](#) &ng) const override
- Generate code for pushing true spikes emitted by a neuron group in the current timestep to the 'device'.*
- virtual void [genCurrentTrueSpikePull](#) ([CodeStream](#) &os, const [NeuronGroupInternal](#) &ng) const override
- Generate code for pulling true spikes emitted by a neuron group in the current timestep from the 'device'.*
- virtual void [genCurrentSpikeLikeEventPush](#) ([CodeStream](#) &os, const [NeuronGroupInternal](#) &ng) const override
- Generate code for pushing spike-like events emitted by a neuron group in the current timestep to the 'device'.*
- virtual void [genCurrentSpikeLikeEventPull](#) ([CodeStream](#) &os, const [NeuronGroupInternal](#) &ng) const override
- Generate code for pulling spike-like events emitted by a neuron group in the current timestep from the 'device'.*
- virtual [MemAlloc](#) [genGlobalRNG](#) ([CodeStream](#) &definitions, [CodeStream](#) &definitionsInternal, [CodeStream](#) &runner, [CodeStream](#) &allocations, [CodeStream](#) &free) const override
- Generate a single RNG instance.*
- virtual [MemAlloc](#) [genPopulationRNG](#) ([CodeStream](#) &definitions, [CodeStream](#) &definitionsInternal, [CodeStream](#) &runner, [CodeStream](#) &allocations, [CodeStream](#) &free, const std::string &name, size\_t count) const override
- Generate an RNG with a state per population member.*
- virtual void [genTimer](#) ([CodeStream](#) &definitions, [CodeStream](#) &definitionsInternal, [CodeStream](#) &runner, [CodeStream](#) &allocations, [CodeStream](#) &free, [CodeStream](#) &stepTimeFinalise, const std::string &name, bool updateInStepTime) const override
- virtual void [genReturnFreeDeviceMemoryBytes](#) ([CodeStream](#) &os) const override
- Generate code to return amount of free 'device' memory in bytes.*
- virtual void [genMakefilePreamble](#) (std::ostream &os) const override
- This function can be used to generate a preamble for the GNU makefile used to build.*
- virtual void [genMakefileLinkRule](#) (std::ostream &os) const override
- virtual void [genMakefileCompileRule](#) (std::ostream &os) const override

- virtual void [genMSBuildConfigProperties](#) (std::ostream &os) const override
- virtual void [genMSBuildImportProps](#) (std::ostream &os) const override
- virtual void [genMSBuildItemDefinitions](#) (std::ostream &os) const override
- virtual void [genMSBuildCompileModule](#) (const std::string &moduleName, std::ostream &os) const override
- virtual void [genMSBuildImportTarget](#) (std::ostream &os) const override
- virtual std::string [getVarPrefix](#) () const override
- virtual bool [isGlobalRNGRequired](#) (const [ModelSpecInternal](#) &model) const override  
*Different backends use different RNGs for different things. Does this one require a global RNG for the specified model?*
- virtual bool [isSynRemapRequired](#) () const override  
*Different backends may implement synapse dynamics differently. Does this one require a synapse remapping data structure?*
- virtual bool [isPostsynapticRemapRequired](#) () const override  
*Different backends may implement synaptic plasticity differently. Does this one require a postsynaptic remapping data structure?*
- virtual bool [isAutomaticCopyEnabled](#) () const override  
*Is automatic copy mode enabled in the preferences?*
- virtual size\_t [getDeviceMemoryBytes](#) () const override  
*How many bytes of memory does 'device' have.*

## Additional Inherited Members

### 19.8.1 Constructor & Destructor Documentation

#### 19.8.1.1 Backend()

```
CodeGenerator::SingleThreadedCPU::Backend::Backend (
    int localHostID,
    const std::string & scalarType,
    const Preferences & preferences ) [inline]
```

### 19.8.2 Member Function Documentation

#### 19.8.2.1 genAllocateMemPreamble()

```
void CodeGenerator::SingleThreadedCPU::Backend::genAllocateMemPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Allocate memory is the first function in GeNN generated code called by usercode and it should only ever be called once. Therefore it's a good place for any global initialisation. This function generates a 'preamble' to this function.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.2 genCurrentSpikeLikeEventPull()

```
void CodeGenerator::SingleThreadedCPU::Backend::genCurrentSpikeLikeEventPull (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [override], [virtual]
```

Generate code for pulling spike-like events emitted by a neuron group in the current timestep from the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.3 genCurrentSpikeLikeEventPush()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genCurrentSpikeLikeEventPush (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [override], [virtual]
```

Generate code for pushing spike-like events emitted by a neuron group in the current timestep to the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.4 genCurrentTrueSpikePull()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genCurrentTrueSpikePull (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [override], [virtual]
```

Generate code for pulling true spikes emitted by a neuron group in the current timestep from the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.5 genCurrentTrueSpikePush()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genCurrentTrueSpikePush (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [override], [virtual]
```

Generate code for pushing true spikes emitted by a neuron group in the current timestep to the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.6 genCurrentVariablePull()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genCurrentVariablePull (
    CodeStream & os,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Generate code for pulling a variable's value in the current timestep from the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.7 genCurrentVariablePush()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genCurrentVariablePush (
    CodeStream & os,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Generate code for pushing a variable's value in the current timestep to the 'device'.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.8 genDefinitionsInternalPreamble()

```
void CodeGenerator::SingleThreadedCPU::Backend::genDefinitionsInternalPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Definitions internal is the internal header file for the generated code. This function generates a 'preamble' to this header file.

This will only be included by the platform-specific compiler used to build this backend so can include platform-specific types or headers

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.9 genDefinitionsPreamble()

```
void CodeGenerator::SingleThreadedCPU::Backend::genDefinitionsPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Definitions is the usercode-facing header file for the generated code. This function generates a 'preamble' to this header file.

This will be included from a standard C++ compiler so shouldn't include any platform-specific types or headers

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.10 genExtraGlobalParamAllocation()

```
void CodeGenerator::SingleThreadedCPU::Backend::genExtraGlobalParamAllocation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.11 genExtraGlobalParamDefinition()

```
void CodeGenerator::SingleThreadedCPU::Backend::genExtraGlobalParamDefinition (
    CodeStream & definitions,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.12 genExtraGlobalParamImplementation()

```
void CodeGenerator::SingleThreadedCPU::Backend::genExtraGlobalParamImplementation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.13 genExtraGlobalParamPull()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genExtraGlobalParamPull (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.14 genExtraGlobalParamPush()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genExtraGlobalParamPush (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.15 genGlobalRNG()**

```
MemAlloc CodeGenerator::SingleThreadedCPU::Backend::genGlobalRNG (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free ) const [override], [virtual]
```

Generate a single RNG instance.

On single-threaded platforms this can be a standard RNG like M.T. but, on parallel platforms, it is likely to be a counter-based RNG

Implements [CodeGenerator::BackendBase](#).

**19.8.2.16 genInit()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genInit (
    CodeStream & os,
    const ModelSpecInternal & model,
    NeuronGroupHandler localNGHandler,
    NeuronGroupHandler remoteNGHandler,
    SynapseGroupHandler sgDenseInitHandler,
    SynapseGroupHandler sgSparseConnectHandler,
    SynapseGroupHandler sgSparseInitHandler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.17 genMakefileCompileRule()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genMakefileCompileRule (
    std::ostream & os ) const [override], [virtual]
```

The GNU make build system uses 'pattern rules' ([https://www.gnu.org/software/make/manual/html\\_node/Pattern-Intro.html](https://www.gnu.org/software/make/manual/html_node/Pattern-Intro.html)) to build backend modules into objects. This function should generate a GNU make pattern rule capable of building each module (i.e. compiling .cc file \$< into .o file \$@).

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.18 genMakefileLinkRule()

```
void CodeGenerator::SingleThreadedCPU::Backend::genMakefileLinkRule (
    std::ostream & os ) const [override], [virtual]
```

The GNU make build system will populate a variable called `LIBS` with a list of objects to link. This function should generate a GNU make rule to build these objects into a shared library.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.19 genMakefilePreamble()

```
void CodeGenerator::SingleThreadedCPU::Backend::genMakefilePreamble (
    std::ostream & os ) const [override], [virtual]
```

This function can be used to generate a preamble for the GNU makefile used to build.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.20 genMSBuildCompileModule()

```
void CodeGenerator::SingleThreadedCPU::Backend::genMSBuildCompileModule (
    const std::string & moduleName,
    std::ostream & os ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.21 genMSBuildConfigProperties()

```
void CodeGenerator::SingleThreadedCPU::Backend::genMSBuildConfigProperties (
    std::ostream & os ) const [override], [virtual]
```

In MSBuild, 'properties' are used to configure global project settings e.g. whether the MSBuild project builds a static or dynamic library. This function can be used to add additional XML properties to this section.

see <https://docs.microsoft.com/en-us/visualstudio/msbuild/msbuild-properties> for more information.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.22 genMSBuildImportProps()

```
void CodeGenerator::SingleThreadedCPU::Backend::genMSBuildImportProps (
    std::ostream & os ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.23 genMSBuildImportTarget()

```
void CodeGenerator::SingleThreadedCPU::Backend::genMSBuildImportTarget (
    std::ostream & os ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).



**19.8.2.24 genMSBuildItemDefinitions()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genMSBuildItemDefinitions (
    std::ostream & os ) const [override], [virtual]
```

In MSBuild, the 'item definitions' are used to override the default properties of 'items' such as <ClCompile> or <Link>. This function should generate XML to correctly configure the 'items' required to build the generated code, taking into account etc.

see <https://docs.microsoft.com/en-us/visualstudio/msbuild/msbuild-items#item-definitions> for more information.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.25 genNeuronUpdate()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genNeuronUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    NeuronGroupSimHandler simHandler,
    NeuronGroupHandler wuVarUpdateHandler ) const [override], [virtual]
```

Generate platform-specific function to update the state of all neurons.

**Parameters**

<i>os</i>	<a href="#">CodeStream</a> to write function to
<i>model</i>	model to generate code for
<i>simHandler</i>	callback to write platform-independent code to update an individual <a href="#">NeuronGroup</a>
<i>wuVarUpdateHandler</i>	callback to write platform-independent code to update pre and postsynaptic weight update model variables when neuron spikes

Implements [CodeGenerator::BackendBase](#).

**19.8.2.26 genPopulationRNG()**

```
MemAlloc CodeGenerator::SingleThreadedCPU::Backend::genPopulationRNG (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free,
    const std::string & name,
    size_t count ) const [override], [virtual]
```

Generate an RNG with a state per population member.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.27 genPopVariableInit()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genPopVariableInit (
    CodeStream & os,
    VarLocation loc,
    const Substitutions & kernelSubs,
    Handler handler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.28 genReturnFreeDeviceMemoryBytes()

```
void CodeGenerator::SingleThreadedCPU::Backend::genReturnFreeDeviceMemoryBytes (
    CodeStream & os ) const [override], [virtual]
```

Generate code to return amount of free 'device' memory in bytes.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.29 genRunnerPreamble()

```
void CodeGenerator::SingleThreadedCPU::Backend::genRunnerPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.30 genStepTimeFinalisePreamble()

```
void CodeGenerator::SingleThreadedCPU::Backend::genStepTimeFinalisePreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [override], [virtual]
```

After all timestep logic is complete.

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.31 genSynapseUpdate()

```
void CodeGenerator::SingleThreadedCPU::Backend::genSynapseUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    SynapseGroupHandler wumThreshHandler,
    SynapseGroupHandler wumSimHandler,
    SynapseGroupHandler wumEventHandler,
    SynapseGroupHandler wumProceduralConnectHandler,
    SynapseGroupHandler postLearnHandler,
    SynapseGroupHandler synapseDynamicsHandler ) const [override], [virtual]
```

Generate platform-specific function to update the state of all synapses.

##### Parameters

<i>os</i>	<a href="#">CodeStream</a> to write function to
<i>model</i>	model to generate code for
<i>wumThreshHandler</i>	callback to write platform-independent code to update an individual <a href="#">NeuronGroup</a>
<i>wumSimHandler</i>	callback to write platform-independent code to process presynaptic spikes. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .
<i>wumEventHandler</i>	callback to write platform-independent code to process presynaptic spike-like events. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .

## Parameters

<i>wumProceduralConnectHandler</i>	callback to write platform-indepent code to procedurally generate connectivity "id_pre" variable and "addSynapse" function will be provided to callback via <a href="#">Substitutions</a> . callback needs to implement loop over synapses in row, providing "synAddress" variable if INDIVIDUALG
<i>postLearnHandler</i>	callback to write platform-independent code to process postsynaptic spikes. "id_pre", "id_post" and "id_syn" variables will be provided to callback via <a href="#">Substitutions</a> .
<i>synapseDynamicsHandler</i>	callback to write platform-independent code to update time-driven synapse dynamics. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .

Implements [CodeGenerator::BackendBase](#).

## 19.8.2.32 genSynapseVariableRowInit()

```
void CodeGenerator::SingleThreadedCPU::Backend::genSynapseVariableRowInit (
    CodeStream & os,
    VarLocation loc,
    const SynapseGroupInternal & sg,
    const Substitutions & kernelSubs,
    Handler handler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

## 19.8.2.33 genTimer()

```
void CodeGenerator::SingleThreadedCPU::Backend::genTimer (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free,
    CodeStream & stepTimeFinalise,
    const std::string & name,
    bool updateInStepTime ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

## 19.8.2.34 genVariableAllocation()

```
MemAlloc CodeGenerator::SingleThreadedCPU::Backend::genVariableAllocation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    size_t count ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.35 genVariableDefinition()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genVariableDefinition (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.36 genVariableFree()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genVariableFree (
    CodeStream & os,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.37 genVariableImplementation()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genVariableImplementation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.38 genVariableInit()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genVariableInit (
    CodeStream & os,
    VarLocation loc,
    size_t count,
    const std::string & indexVarName,
    const Substitutions & kernelSubs,
    Handler handler ) const [override], [virtual]
```

Implements [CodeGenerator::BackendBase](#).

**19.8.2.39 genVariablePull()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genVariablePull (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    size_t count ) const [override], [virtual]
```

Generate code for pulling a variable from the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.40 genVariablePush()**

```
void CodeGenerator::SingleThreadedCPU::Backend::genVariablePush (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    bool autoInitialized,
    size_t count ) const [override], [virtual]
```

Generate code for pushing a variable to the 'device'.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.41 getDeviceMemoryBytes()**

```
virtual size_t CodeGenerator::SingleThreadedCPU::Backend::getDeviceMemoryBytes ( ) const [inline],
[override], [virtual]
```

How many bytes of memory does 'device' have.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.42 getSynapticMatrixRowStride()**

```
size_t CodeGenerator::SingleThreadedCPU::Backend::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implements [CodeGenerator::BackendBase](#).

**19.8.2.43 getVarPrefix()**

```
virtual std::string CodeGenerator::SingleThreadedCPU::Backend::getVarPrefix ( ) const [inline],
[override], [virtual]
```

When backends require separate 'device' and 'host' versions of variables, they are identified with a prefix. This function returns this prefix so it can be used in otherwise platform-independent code.

Reimplemented from [CodeGenerator::BackendBase](#).

**19.8.2.44 isAutomaticCopyEnabled()**

```
virtual bool CodeGenerator::SingleThreadedCPU::Backend::isAutomaticCopyEnabled ( ) const [inline],
[override], [virtual]
```

Is automatic copy mode enabled in the preferences?

Implements [CodeGenerator::BackendBase](#).

**19.8.2.45 isGlobalRNGRequired()**

```
bool CodeGenerator::SingleThreadedCPU::Backend::isGlobalRNGRequired (
    const ModelSpecInternal & model ) const [override], [virtual]
```

Different backends use different RNGs for different things. Does this one require a global RNG for the specified model?

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.46 isPostsynapticRemapRequired()

```
virtual bool CodeGenerator::SingleThreadedCPU::Backend::isPostsynapticRemapRequired ( ) const
[inline], [override], [virtual]
```

Different backends may implement synaptic plasticity differently. Does this one require a postsynaptic remapping data structure?

Implements [CodeGenerator::BackendBase](#).

#### 19.8.2.47 isSynRemapRequired()

```
virtual bool CodeGenerator::SingleThreadedCPU::Backend::isSynRemapRequired ( ) const [inline],
[override], [virtual]
```

Different backends may implement synapse dynamics differently. Does this one require a synapse remapping data structure?

Implements [CodeGenerator::BackendBase](#).


The documentation for this class was generated from the following files:

- [single\\_threaded\\_cpu/backend.h](#)
- [single\\_threaded\\_cpu/backend.cc](#)

## 19.9 CodeGenerator::BackendBase Class Reference

```
#include <backendBase.h>
```

Inheritance diagram for CodeGenerator::BackendBase:



### Public Types

- typedef std::function< void([CodeStream](#) &, [Substitutions](#) &)> [Handler](#)
- template<typename T >  
using [GroupHandler](#) = std::function< void([CodeStream](#) &, const T &, [Substitutions](#) &)>
- typedef [GroupHandler](#)< [NeuronGroupInternal](#) > [NeuronGroupHandler](#)  
*Standard callback type which provides a [CodeStream](#) to write platform-independent code for the specified [NeuronGroup](#) to.*
- typedef [GroupHandler](#)< [SynapseGroupInternal](#) > [SynapseGroupHandler](#)  
*Standard callback type which provides a [CodeStream](#) to write platform-independent code for the specified [SynapseGroup](#) to.*
- typedef std::function< void([CodeStream](#) &, const [NeuronGroupInternal](#) &, [Substitutions](#) &, [NeuronGroupHandler](#), [NeuronGroupHandler](#))> [NeuronGroupSimHandler](#)  
*Callback function type for generation neuron group simulation code.*

## Public Member Functions

- [BackendBase](#) (int localHostID, const std::string &scalarType)
- virtual [~BackendBase](#) ()
- virtual void [genNeuronUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [NeuronGroupSimHandler](#) simHandler, [NeuronGroupHandler](#) wuVarUpdateHandler) const =0  
*Generate platform-specific function to update the state of all neurons.*
- virtual void [genSynapseUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [SynapseGroupHandler](#) wumThreshHandler, [SynapseGroupHandler](#) wumSimHandler, [SynapseGroupHandler](#) wumEventHandler, [SynapseGroupHandler](#) wumProceduralConnectHandler, [SynapseGroupHandler](#) postLearnHandler, [SynapseGroupHandler](#) synapseDynamicsHandler) const =0  
*Generate platform-specific function to update the state of all synapses.*
- virtual void [genInit](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, [NeuronGroupHandler](#) localNGHandler, [NeuronGroupHandler](#) remoteNGHandler, [SynapseGroupHandler](#) sgDenseInitHandler, [SynapseGroupHandler](#) sgSparseConnectHandler, [SynapseGroupHandler](#) sgSparseInitHandler) const =0
- virtual size\_t [getSynapticMatrixRowStride](#) (const [SynapseGroupInternal](#) &sg) const =0  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual void [genDefinitionsPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const =0  
*Definitions is the usercode-facing header file for the generated code. This function generates a 'preamble' to this header file.*
- virtual void [genDefinitionsInternalPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const =0  
*Definitions internal is the internal header file for the generated code. This function generates a 'preamble' to this header file.*
- virtual void [genRunnerPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const =0
- virtual void [genAllocateMemPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const =0
- virtual void [genStepTimeFinalisePreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model) const =0  
*After all timestep logic is complete.*
- virtual void [genVariableDefinition](#) ([CodeStream](#) &definitions, [CodeStream](#) &definitionsInternal, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genVariableImplementation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual [MemAlloc](#) [genVariableAllocation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, size\_t count) const =0
- virtual void [genVariableFree](#) ([CodeStream](#) &os, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genExtraGlobalParamDefinition](#) ([CodeStream](#) &definitions, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genExtraGlobalParamImplementation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genExtraGlobalParamAllocation](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genExtraGlobalParamPush](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genExtraGlobalParamPull](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc) const =0
- virtual void [genPopVariableInit](#) ([CodeStream](#) &os, [VarLocation](#) loc, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const =0
- virtual void [genVariableInit](#) ([CodeStream](#) &os, [VarLocation](#) loc, size\_t count, const std::string &indexVarName, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const =0
- virtual void [genSynapseVariableRowInit](#) ([CodeStream](#) &os, [VarLocation](#) loc, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &kernelSubs, [Handler](#) handler) const =0
- virtual void [genVariablePush](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, bool autoInitialized, size\_t count) const =0  
*Generate code for pushing a variable to the 'device'.*
- virtual void [genVariablePull](#) ([CodeStream](#) &os, const std::string &type, const std::string &name, [VarLocation](#) loc, size\_t count) const =0

*Generate code for pulling a variable from the 'device'.*

- virtual void `genCurrentVariablePush` (`CodeStream` &os, const `NeuronGroupInternal` &ng, const std::string &type, const std::string &name, `VarLocation` loc) const =0

*Generate code for pushing a variable's value in the current timestep to the 'device'.*

- virtual void `genCurrentVariablePull` (`CodeStream` &os, const `NeuronGroupInternal` &ng, const std::string &type, const std::string &name, `VarLocation` loc) const =0

*Generate code for pulling a variable's value in the current timestep from the 'device'.*

- virtual void `genCurrentTrueSpikePush` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const =0

*Generate code for pushing true spikes emitted by a neuron group in the current timestep to the 'device'.*

- virtual void `genCurrentTrueSpikePull` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const =0

*Generate code for pulling true spikes emitted by a neuron group in the current timestep from the 'device'.*

- virtual void `genCurrentSpikeLikeEventPush` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const =0

*Generate code for pushing spike-like events emitted by a neuron group in the current timestep to the 'device'.*

- virtual void `genCurrentSpikeLikeEventPull` (`CodeStream` &os, const `NeuronGroupInternal` &ng) const =0

*Generate code for pulling spike-like events emitted by a neuron group in the current timestep from the 'device'.*

- virtual `MemAlloc` `genGlobalRNG` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free) const =0

*Generate a single RNG instance.*

- virtual `MemAlloc` `genPopulationRNG` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free, const std::string &name, size\_t count) const =0

*Generate an RNG with a state per population member.*

- virtual void `genTimer` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free, `CodeStream` &stepTimeFinalise, const std::string &name, bool updateInStepTime) const =0
- virtual void `genReturnFreeDeviceMemoryBytes` (`CodeStream` &os) const =0

*Generate code to return amount of free 'device' memory in bytes.*

- virtual void `genMakefilePreamble` (std::ostream &os) const =0

*This function can be used to generate a preamble for the GNU makefile used to build.*

- virtual void `genMakefileLinkRule` (std::ostream &os) const =0
- virtual void `genMakefileCompileRule` (std::ostream &os) const =0
- virtual void `genMSBuildConfigProperties` (std::ostream &os) const =0
- virtual void `genMSBuildImportProps` (std::ostream &os) const =0
- virtual void `genMSBuildItemDefinitions` (std::ostream &os) const =0
- virtual void `genMSBuildCompileModule` (const std::string &moduleName, std::ostream &os) const =0
- virtual void `genMSBuildImportTarget` (std::ostream &os) const =0
- virtual std::string `getVarPrefix` () const
- virtual bool `isGlobalRNGRequired` (const `ModelSpecInternal` &model) const =0

*Different backends use different RNGs for different things. Does this one require a global RNG for the specified model?*

- virtual bool `isSynRemapRequired` () const =0

*Different backends may implement synapse dynamics differently. Does this one require a synapse remapping data structure?*

- virtual bool `isPostsynapticRemapRequired` () const =0

*Different backends may implement synaptic plasticity differently. Does this one require a postsynaptic remapping data structure?*

- virtual bool `isAutomaticCopyEnabled` () const =0

*Is automatic copy mode enabled in the preferences?*

- virtual size\_t `getDeviceMemoryBytes` () const =0

*How many bytes of memory does 'device' have.*

- void `genVariablePushPull` (`CodeStream` &push, `CodeStream` &pull, const std::string &type, const std::string &name, `VarLocation` loc, bool autoInitialized, size\_t count) const

*Helper function to generate matching push and pull functions for a variable.*



- void `genCurrentVariablePushPull` (`CodeStream` &push, `CodeStream` &pull, const `NeuronGroupInternal` &ng, const std::string &type, const std::string &name, `VarLocation` loc) const  
*Helper function to generate matching push and pull functions for the current state of a variable.*
- `MemAlloc` `genArray` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, `CodeStream` &allocations, `CodeStream` &free, const std::string &type, const std::string &name, `VarLocation` loc, size\_t count) const  
*Helper function to generate matching definition, declaration, allocation and free code for an array.*
- void `genScalar` (`CodeStream` &definitions, `CodeStream` &definitionsInternal, `CodeStream` &runner, const std::string &type, const std::string &name, `VarLocation` loc) const  
*Helper function to generate matching definition and declaration code for a scalar variable.*
- int `getLocalHostID` () const  
*Gets ID of local host backend is building code for.*

### Protected Member Functions

- void `addType` (const std::string &type, size\_t size)
- size\_t `getSize` (const std::string &type) const

## 19.9.1 Member Typedef Documentation

### 19.9.1.1 GroupHandler

```
template<typename T >
using CodeGenerator::BackendBase::GroupHandler = std::function <void(CodeStream &, const T &,
Substitutions&)>
```

### 19.9.1.2 Handler

```
typedef std::function<void(CodeStream &, Substitutions&)> CodeGenerator::BackendBase::Handler
```

### 19.9.1.3 NeuronGroupHandler

```
typedef GroupHandler<NeuronGroupInternal> CodeGenerator::BackendBase::NeuronGroupHandler
```

Standard callback type which provides a `CodeStream` to write platform-independent code for the specified `NeuronGroup` to.

### 19.9.1.4 NeuronGroupSimHandler

```
typedef std::function<void(CodeStream &, const NeuronGroupInternal &, Substitutions&, NeuronGroupHandler, NeuronGroupHandler)> CodeGenerator::BackendBase::NeuronGroupSimHandler
```

Callback function type for generation neuron group simulation code.

Provides additional callbacks to insert code to emit spikes

### 19.9.1.5 SynapseGroupHandler

```
typedef GroupHandler<SynapseGroupInternal> CodeGenerator::BackendBase::SynapseGroupHandler
```

Standard callback type which provides a `CodeStream` to write platform-independent code for the specified `SynapseGroup` to.

## 19.9.2 Constructor & Destructor Documentation

### 19.9.2.1 BackendBase()

```
CodeGenerator::BackendBase::BackendBase (
    int localHostID,
    const std::string & scalarType )
```

### 19.9.2.2 ~BackendBase()

```
virtual CodeGenerator::BackendBase::~~BackendBase ( ) [inline], [virtual]
```

## 19.9.3 Member Function Documentation

### 19.9.3.1 addType()

```
void CodeGenerator::BackendBase::addType (
    const std::string & type,
    size_t size ) [inline], [protected]
```

### 19.9.3.2 genAllocateMemPreamble()

```
virtual void CodeGenerator::BackendBase::genAllocateMemPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [pure virtual]
```

Allocate memory is the first function in GeNN generated code called by usercode and it should only ever be called once. Therefore it's a good place for any global initialisation. This function generates a 'preamble' to this function.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

### 19.9.3.3 genArray()

```
MemAlloc CodeGenerator::BackendBase::genArray (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    size_t count ) const [inline]
```

Helper function to generate matching definition, declaration, allocation and free code for an array.

### 19.9.3.4 genCurrentSpikeLikeEventPull()

```
virtual void CodeGenerator::BackendBase::genCurrentSpikeLikeEventPull (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [pure virtual]
```

Generate code for pulling spike-like events emitted by a neuron group in the current timestep from the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.5 genCurrentSpikeLikeEventPush()

```
virtual void CodeGenerator::BackendBase::genCurrentSpikeLikeEventPush (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [pure virtual]
```

Generate code for pushing spike-like events emitted by a neuron group in the current timestep to the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.6 genCurrentTrueSpikePull()

```
virtual void CodeGenerator::BackendBase::genCurrentTrueSpikePull (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [pure virtual]
```

Generate code for pulling true spikes emitted by a neuron group in the current timestep from the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.7 genCurrentTrueSpikePush()

```
virtual void CodeGenerator::BackendBase::genCurrentTrueSpikePush (
    CodeStream & os,
    const NeuronGroupInternal & ng ) const [pure virtual]
```

Generate code for pushing true spikes emitted by a neuron group in the current timestep to the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.8 genCurrentVariablePull()

```
virtual void CodeGenerator::BackendBase::genCurrentVariablePull (
    CodeStream & os,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Generate code for pulling a variable's value in the current timestep from the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.9 genCurrentVariablePush()

```
virtual void CodeGenerator::BackendBase::genCurrentVariablePush (
    CodeStream & os,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Generate code for pushing a variable's value in the current timestep to the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.10 genCurrentVariablePushPull()

```
void CodeGenerator::BackendBase::genCurrentVariablePushPull (
    CodeStream & push,
    CodeStream & pull,
    const NeuronGroupInternal & ng,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [inline]
```

Helper function to generate matching push and pull functions for the current state of a variable.

#### 19.9.3.11 genDefinitionsInternalPreamble()

```
virtual void CodeGenerator::BackendBase::genDefinitionsInternalPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [pure virtual]
```

Definitions internal is the internal header file for the generated code. This function generates a 'preamble' to this header file.

This will only be included by the platform-specific compiler used to build this backend so can include platform-specific types or headers

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.12 genDefinitionsPreamble()

```
virtual void CodeGenerator::BackendBase::genDefinitionsPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [pure virtual]
```

Definitions is the usercode-facing header file for the generated code. This function generates a 'preamble' to this header file.

This will be included from a standard C++ compiler so shouldn't include any platform-specific types or headers

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.13 genExtraGlobalParamAllocation()

```
virtual void CodeGenerator::BackendBase::genExtraGlobalParamAllocation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.14 genExtraGlobalParamDefinition()

```
virtual void CodeGenerator::BackendBase::genExtraGlobalParamDefinition (
    CodeStream & definitions,
    const std::string & type,
```

```
const std::string & name,
VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.15 genExtraGlobalParamImplementation()

```
virtual void CodeGenerator::BackendBase::genExtraGlobalParamImplementation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.16 genExtraGlobalParamPull()

```
virtual void CodeGenerator::BackendBase::genExtraGlobalParamPull (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.17 genExtraGlobalParamPush()

```
virtual void CodeGenerator::BackendBase::genExtraGlobalParamPush (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.18 genGlobalRNG()

```
virtual MemAlloc CodeGenerator::BackendBase::genGlobalRNG (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free ) const [pure virtual]
```

Generate a single RNG instance.

On single-threaded platforms this can be a standard RNG like M.T. but, on parallel platforms, it is likely to be a counter-based RNG

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.19 genInit()

```
virtual void CodeGenerator::BackendBase::genInit (
    CodeStream & os,
    const ModelSpecInternal & model,
```

```

NeuronGroupHandler localNGHandler,
NeuronGroupHandler remoteNGHandler,
SynapseGroupHandler sgDenseInitHandler,
SynapseGroupHandler sgSparseConnectHandler,
SynapseGroupHandler sgSparseInitHandler ) const [pure virtual]

```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.20 genMakefileCompileRule()

```

virtual void CodeGenerator::BackendBase::genMakefileCompileRule (
    std::ostream & os ) const [pure virtual]

```

The GNU make build system uses 'pattern rules' ([https://www.gnu.org/software/make/manual/html\\_node/Pattern-Intro.html](https://www.gnu.org/software/make/manual/html_node/Pattern-Intro.html)) to build backend modules into objects. This function should generate a GNU make pattern rule capable of building each module (i.e. compiling .cc file \$< into .o file \$@).

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.21 genMakefileLinkRule()

```

virtual void CodeGenerator::BackendBase::genMakefileLinkRule (
    std::ostream & os ) const [pure virtual]

```

The GNU make build system will populate a variable called with a list of objects to link. This function should generate a GNU make rule to build these objects into a shared library.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.22 genMakefilePreamble()

```

virtual void CodeGenerator::BackendBase::genMakefilePreamble (
    std::ostream & os ) const [pure virtual]

```

This function can be used to generate a preamble for the GNU makefile used to build.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.23 genMSBuildCompileModule()

```

virtual void CodeGenerator::BackendBase::genMSBuildCompileModule (
    const std::string & moduleName,
    std::ostream & os ) const [pure virtual]

```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.24 genMSBuildConfigProperties()

```

virtual void CodeGenerator::BackendBase::genMSBuildConfigProperties (
    std::ostream & os ) const [pure virtual]

```

In MSBuild, 'properties' are used to configure global project settings e.g. whether the MSBuild project builds a static or dynamic library. This function can be used to add additional XML properties to this section.

see <https://docs.microsoft.com/en-us/visualstudio/msbuild/msbuild-properties> for more information.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.25 genMSBuildImportProps()**

```
virtual void CodeGenerator::BackendBase::genMSBuildImportProps (
    std::ostream & os ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.26 genMSBuildImportTarget()**

```
virtual void CodeGenerator::BackendBase::genMSBuildImportTarget (
    std::ostream & os ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.27 genMSBuildItemDefinitions()**

```
virtual void CodeGenerator::BackendBase::genMSBuildItemDefinitions (
    std::ostream & os ) const [pure virtual]
```

In MSBuild, the 'item definitions' are used to override the default properties of 'items' such as <ClCompile> or <Link>. This function should generate XML to correctly configure the 'items' required to build the generated code, taking into account etc.

see <https://docs.microsoft.com/en-us/visualstudio/msbuild/msbuild-items#item-definitions> for more information.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.28 genNeuronUpdate()**

```
virtual void CodeGenerator::BackendBase::genNeuronUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    NeuronGroupSimHandler simHandler,
    NeuronGroupHandler wuVarUpdateHandler ) const [pure virtual]
```

Generate platform-specific function to update the state of all neurons.

**Parameters**

<i>os</i>	<a href="#">CodeStream</a> to write function to
<i>model</i>	model to generate code for
<i>simHandler</i>	callback to write platform-independent code to update an individual <a href="#">NeuronGroup</a>
<i>wuVarUpdateHandler</i>	callback to write platform-independent code to update pre and postsynaptic weight update model variables when neuron spikes

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.29 genPopulationRNG()**

```
virtual MemAlloc CodeGenerator::BackendBase::genPopulationRNG (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
```

```

    CodeStream & allocations,
    CodeStream & free,
    const std::string & name,
    size_t count ) const [pure virtual]

```

Generate an RNG with a state per population member.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.30 genPopVariableInit()

```

virtual void CodeGenerator::BackendBase::genPopVariableInit (
    CodeStream & os,
    VarLocation loc,
    const Substitutions & kernelSubs,
    Handler handler ) const [pure virtual]

```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.31 genReturnFreeDeviceMemoryBytes()

```

virtual void CodeGenerator::BackendBase::genReturnFreeDeviceMemoryBytes (
    CodeStream & os ) const [pure virtual]

```

Generate code to return amount of free 'device' memory in bytes.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.32 genRunnerPreamble()

```

virtual void CodeGenerator::BackendBase::genRunnerPreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [pure virtual]

```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.33 genScalar()

```

void CodeGenerator::BackendBase::genScalar (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [inline]

```

Helper function to generate matching definition and declaration code for a scalar variable.

#### 19.9.3.34 genStepTimeFinalisePreamble()

```

virtual void CodeGenerator::BackendBase::genStepTimeFinalisePreamble (
    CodeStream & os,
    const ModelSpecInternal & model ) const [pure virtual]

```

After all timestep logic is complete.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).



## 19.9.3.35 genSynapseUpdate()

```
virtual void CodeGenerator::BackendBase::genSynapseUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    SynapseGroupHandler wumThreshHandler,
    SynapseGroupHandler wumSimHandler,
    SynapseGroupHandler wumEventHandler,
    SynapseGroupHandler wumProceduralConnectHandler,
    SynapseGroupHandler postLearnHandler,
    SynapseGroupHandler synapseDynamicsHandler ) const [pure virtual]
```

Generate platform-specific function to update the state of all synapses.

## Parameters

<i>os</i>	<a href="#">CodeStream</a> to write function to
<i>model</i>	model to generate code for
<i>wumThreshHandler</i>	callback to write platform-independent code to update an individual <a href="#">NeuronGroup</a>
<i>wumSimHandler</i>	callback to write platform-independent code to process presynaptic spikes. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .
<i>wumEventHandler</i>	callback to write platform-independent code to process presynaptic spike-like events. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .
<i>wumProceduralConnectHandler</i>	callback to write platform-independent code to procedurally generate connectivity "id_pre" variable and "addSynapse" function will be provided to callback via <a href="#">Substitutions</a> . callback needs to implement loop over synapses in row, providing "synAddress" variable if INDIVIDUALG
<i>postLearnHandler</i>	callback to write platform-independent code to process postsynaptic spikes. "id_pre", "id_post" and "id_syn" variables will be provided to callback via <a href="#">Substitutions</a> .
<i>synapseDynamicsHandler</i>	callback to write platform-independent code to update time-driven synapse dynamics. "id_pre", "id_post" and "id_syn" variables; and either "addToInSynDelay" or "addToInSyn" function will be provided to callback via <a href="#">Substitutions</a> .

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

## 19.9.3.36 genSynapseVariableRowInit()

```
virtual void CodeGenerator::BackendBase::genSynapseVariableRowInit (
    CodeStream & os,
    VarLocation loc,
    const SynapseGroupInternal & sg,
    const Substitutions & kernelSubs,
    Handler handler ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.37 genTimer()**

```
virtual void CodeGenerator::BackendBase::genTimer (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    CodeStream & runner,
    CodeStream & allocations,
    CodeStream & free,
    CodeStream & stepTimeFinalise,
    const std::string & name,
    bool updateInStepTime ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.38 genVariableAllocation()**

```
virtual MemAlloc CodeGenerator::BackendBase::genVariableAllocation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    size_t count ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.39 genVariableDefinition()**

```
virtual void CodeGenerator::BackendBase::genVariableDefinition (
    CodeStream & definitions,
    CodeStream & definitionsInternal,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.40 genVariableFree()**

```
virtual void CodeGenerator::BackendBase::genVariableFree (
    CodeStream & os,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.41 genVariableImplementation()**

```
virtual void CodeGenerator::BackendBase::genVariableImplementation (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.42 genVariableInit()**

```
virtual void CodeGenerator::BackendBase::genVariableInit (
    CodeStream & os,
    VarLocation loc,
    size_t count,
    const std::string & indexVarName,
    const Substitutions & kernelSubs,
    Handler handler ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.43 genVariablePull()**

```
virtual void CodeGenerator::BackendBase::genVariablePull (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    size_t count ) const [pure virtual]
```

Generate code for pulling a variable from the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.44 genVariablePush()**

```
virtual void CodeGenerator::BackendBase::genVariablePush (
    CodeStream & os,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    bool autoInitialized,
    size_t count ) const [pure virtual]
```

Generate code for pushing a variable to the 'device'.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

**19.9.3.45 genVariablePushPull()**

```
void CodeGenerator::BackendBase::genVariablePushPull (
    CodeStream & push,
    CodeStream & pull,
    const std::string & type,
    const std::string & name,
    VarLocation loc,
    bool autoInitialized,
    size_t count ) const [inline]
```

Helper function to generate matching push and pull functions for a variable.

**19.9.3.46 getDeviceMemoryBytes()**

```
virtual size_t CodeGenerator::BackendBase::getDeviceMemoryBytes ( ) const [pure virtual]
```

How many bytes of memory does 'device' have.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.47 `getLocalHostID()`

```
int CodeGenerator::BackendBase::getLocalHostID ( ) const [inline]
```

Gets ID of local host backend is building code for.

#### 19.9.3.48 `getSize()`

```
size_t CodeGenerator::BackendBase::getSize (
    const std::string & type ) const [protected]
```

#### 19.9.3.49 `getSynapticMatrixRowStride()`

```
virtual size_t CodeGenerator::BackendBase::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [pure virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.50 `getVarPrefix()`

```
virtual std::string CodeGenerator::BackendBase::getVarPrefix ( ) const [inline], [virtual]
```

When backends require separate 'device' and 'host' versions of variables, they are identified with a prefix. This function returns this prefix so it can be used in otherwise platform-independent code.

Reimplemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.51 `isAutomaticCopyEnabled()`

```
virtual bool CodeGenerator::BackendBase::isAutomaticCopyEnabled ( ) const [pure virtual]
```

Is automatic copy mode enabled in the preferences?

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.52 `isGlobalRNGRequired()`

```
virtual bool CodeGenerator::BackendBase::isGlobalRNGRequired (
    const ModelSpecInternal & model ) const [pure virtual]
```

Different backends use different RNGs for different things. Does this one require a global RNG for the specified model?

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.53 `isPostsynapticRemapRequired()`

```
virtual bool CodeGenerator::BackendBase::isPostsynapticRemapRequired ( ) const [pure virtual]
```

Different backends may implement synaptic plasticity differently. Does this one require a postsynaptic remapping data structure?

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

#### 19.9.3.54 isSynRemapRequired()

```
virtual bool CodeGenerator::BackendBase::isSynRemapRequired ( ) const [pure virtual]
```

Different backends may implement synapse dynamics differently. Does this one require a synapse remapping data structure?

Implemented in [CodeGenerator::CUDA::Backend](#), and [CodeGenerator::SingleThreadedCPU::Backend](#).

The documentation for this class was generated from the following files:


- [backendBase.h](#)
- [backendBase.cc](#)

## 19.10 CurrentSourceModels::Base Class Reference

[Base](#) class for all current source models.

```
#include <currentSourceModels.h>
```

Inheritance diagram for CurrentSourceModels::Base:



### Public Member Functions

- virtual std::string [getInjectionCode](#) ( ) const  
*Gets the code that defines current injected each timestep.*

### Additional Inherited Members

#### 19.10.1 Detailed Description

[Base](#) class for all current source models.

#### 19.10.2 Member Function Documentation

##### 19.10.2.1 getInjectionCode()

```
virtual std::string CurrentSourceModels::Base::getInjectionCode ( ) const [inline], [virtual]
```

Gets the code that defines current injected each timestep.


The documentation for this class was generated from the following file:

- [currentSourceModels.h](#)

## 19.11 InitSparseConnectivitySnippet::Base Class Reference

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::Base:



### Public Types

- typedef std::function< unsigned int(unsigned int, unsigned int, const std::vector< double > &)> [CalcMaxLengthFunc](#)

### Public Member Functions

- virtual std::string [getRowBuildCode](#) () const
- virtual [ParamValVec](#) [getRowBuildStateVars](#) () const
- virtual [CalcMaxLengthFunc](#) [getCalcMaxRowLengthFunc](#) () const  
*Get function to calculate the maximum row length of this connector based on the parameters and the size of the pre and postsynaptic population.*
- virtual [CalcMaxLengthFunc](#) [getCalcMaxColLengthFunc](#) () const  
*Get function to calculate the maximum column length of this connector based on the parameters and the size of the pre and postsynaptic population.*
- virtual [EGPVec](#) [getExtraGlobalParams](#) () const
- size\_t [getExtraGlobalParamIndex](#) (const std::string &paramName) const  
*Find the index of a named extra global parameter.*

### Additional Inherited Members

#### 19.11.1 Member Typedef Documentation

##### 19.11.1.1 CalcMaxLengthFunc

```
typedef std::function<unsigned int(unsigned int, unsigned int, const std::vector<double> &)>  
InitSparseConnectivitySnippet::Base::CalcMaxLengthFunc
```

#### 19.11.2 Member Function Documentation

##### 19.11.2.1 getCalcMaxColLengthFunc()

```
virtual CalcMaxLengthFunc InitSparseConnectivitySnippet::Base::getCalcMaxColLengthFunc ( )  
const [inline], [virtual]
```

Get function to calculate the maximum column length of this connector based on the parameters and the size of the pre and postsynaptic population.

## 19.11.2.2 getCalcMaxRowLengthFunc()

```
virtual CalcMaxLengthFunc InitSparseConnectivitySnippet::Base::getCalcMaxRowLengthFunc ( )
const [inline], [virtual]
```

Get function to calculate the maximum row length of this connector based on the parameters and the size of the pre and postsynaptic population.

## 19.11.2.3 getExtraGlobalParamIndex()

```
size_t InitSparseConnectivitySnippet::Base::getExtraGlobalParamIndex (
    const std::string & paramName ) const [inline]
```

Find the index of a named extra global parameter.

## 19.11.2.4 getExtraGlobalParams()

```
virtual EGPVec InitSparseConnectivitySnippet::Base::getExtraGlobalParams ( ) const [inline],
[virtual]
```

Gets names and types (as strings) of additional per-population parameters for the connection initialisation snippet

## 19.11.2.5 getRowBuildCode()

```
virtual std::string InitSparseConnectivitySnippet::Base::getRowBuildCode ( ) const [inline],
[virtual]
```

Reimplemented in [InitSparseConnectivitySnippet::FixedProbabilityBase](#).

## 19.11.2.6 getRowBuildStateVars()

```
virtual ParamValVec InitSparseConnectivitySnippet::Base::getRowBuildStateVars ( ) const [inline],
[virtual]
```


The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)

## 19.12 InitVarSnippet::Base Class Reference

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Base:



## Public Member Functions

- virtual std::string [getCode](#) () const

## Additional Inherited Members

## 19.12.1 Member Function Documentation

### 19.12.1.1 getCode()

```
virtual std::string InitVarSnippet::Base::getCode ( ) const [inline], [virtual]
```

The documentation for this class was generated from the following file:


- [initVarSnippet.h](#)

## 19.13 Models::Base Class Reference

[Base](#) class for all models - in addition to the parameters snippets have, models can have state variables.

```
#include <models.h>
```

Inheritance diagram for Models::Base:



### Classes

- struct [Var](#)  
*A variable has a name, a type and an access type.*

### Public Types

- typedef std::vector< [Var](#) > [VarVec](#)

### Public Member Functions

- virtual [VarVec](#) [getVars](#) () const  
*Gets names and types (as strings) of model variables.*
- virtual [EGPVec](#) [getExtraGlobalParams](#) () const
- size\_t [getVarIndex](#) (const std::string &varName) const  
*Find the index of a named variable.*
- size\_t [getExtraGlobalParamIndex](#) (const std::string &paramName) const  
*Find the index of a named extra global parameter.*

### Additional Inherited Members

#### 19.13.1 Detailed Description

[Base](#) class for all models - in addition to the parameters snippets have, models can have state variables.



## 19.13.2 Member Typedef Documentation

## 19.13.2.1 VarVec

```
typedef std::vector<Var> Models::Base::VarVec
```

## 19.13.3 Member Function Documentation

## 19.13.3.1 getExtraGlobalParamIndex()

```
size_t Models::Base::getExtraGlobalParamIndex (
    const std::string & paramName ) const [inline]
```

Find the index of a named extra global parameter.

## 19.13.3.2 getExtraGlobalParams()

```
virtual EGPVec Models::Base::getExtraGlobalParams ( ) const [inline], [virtual]
```

Gets names and types (as strings) of additional per-population parameters for the weight update model.

Reimplemented in [NeuronModels::Poisson](#), and [NeuronModels::SpikeSourceArray](#).

## 19.13.3.3 getVarIndex()

```
size_t Models::Base::getVarIndex (
    const std::string & varName ) const [inline]
```

Find the index of a named variable.

## 19.13.3.4 getVars()

```
virtual VarVec Models::Base::getVars ( ) const [inline], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented in [NeuronModels::TraubMiles](#), [NeuronModels::PoissonNew](#), [NeuronModels::Poisson](#), [NeuronModels::SpikeSourceArray](#), [WeightUpdateModels::PiecewiseSTDP](#), [NeuronModels::LIF](#), [WeightUpdateModels::StaticGraded](#), [NeuronModels::IzhikevichVariable](#), [WeightUpdateModels::StaticPulseDendriticDelay](#), [NeuronModels::Izhikevich](#), [WeightUpdateModels::StaticPulse](#), and [NeuronModels::RulkovMap](#).

The documentation for this class was generated from the following file:


- [models.h](#)

## 19.14 NeuronModels::Base Class Reference

[Base](#) class for all neuron models.

```
#include <neuronModels.h>
```

Inheritance diagram for [NeuronModels::Base](#):



### Public Member Functions

- virtual std::string [getSimCode](#) () const  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) () const  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual std::string [getResetCode](#) () const  
*Gets code that defines the reset action taken after a spike occurred. This can be empty.*
- virtual std::string [getSupportCode](#) () const  
*Gets support code to be made available within the neuron kernel/function.*
- virtual [Models::Base::ParamValVec](#) [getAdditionalInputVars](#) () const
- virtual bool [isAutoRefractoryRequired](#) () const  
*Does this model require auto-refractory logic?*

### Additional Inherited Members

#### 19.14.1 Detailed Description

[Base](#) class for all neuron models.

#### 19.14.2 Member Function Documentation

19.14.2.1 `getAdditionalInputVars()`

```
virtual Models::Base::ParamValVec NeuronModels::Base::getAdditionalInputVars ( ) const [inline], [virtual]
```

Gets names, types (as strings) and initial values of local variables into which the 'apply input code' of (potentially) multiple postsynaptic input models can apply input

19.14.2.2 `getResetCode()`

```
virtual std::string NeuronModels::Base::getResetCode ( ) const [inline], [virtual]
```

Gets code that defines the reset action taken after a spike occurred. This can be empty.

Reimplemented in [NeuronModels::SpikeSourceArray](#), and [NeuronModels::LIF](#).

19.14.2.3 `getSimCode()`

```
virtual std::string NeuronModels::Base::getSimCode ( ) const [inline], [virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented in [NeuronModels::TraubMilesNStep](#), [NeuronModels::TraubMilesAlt](#), [NeuronModels::TraubMilesFast](#), [NeuronModels::TraubMiles](#), [NeuronModels::PoissonNew](#), [NeuronModels::Poisson](#), [NeuronModels::SpikeSourceArray](#), [NeuronModels::LIF](#), [NeuronModels::Izhikevich](#), and [NeuronModels::RulkovMap](#).

19.14.2.4 `getSupportCode()`

```
virtual std::string NeuronModels::Base::getSupportCode ( ) const [inline], [virtual]
```

Gets support code to be made available within the neuron kernel/function.

This is intended to contain user defined device functions that are used in the neuron codes. Preprocessor defines are also allowed if appropriately safeguarded against multiple definition by using `ifndef`; functions should be declared as `"__host__ __device__"` to be available for both GPU and CPU versions.

19.14.2.5 `getThresholdConditionCode()`

```
virtual std::string NeuronModels::Base::getThresholdConditionCode ( ) const [inline], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. `"V > 20"`).

Reimplemented in [NeuronModels::TraubMiles](#), [NeuronModels::PoissonNew](#), [NeuronModels::Poisson](#), [NeuronModels::SpikeSourceArray](#), [NeuronModels::SpikeSource](#), [NeuronModels::LIF](#), [NeuronModels::Izhikevich](#), and [NeuronModels::RulkovMap](#).

19.14.2.6 `isAutoRefractoryRequired()`

```
virtual bool NeuronModels::Base::isAutoRefractoryRequired ( ) const [inline], [virtual]
```

Does this model require auto-refractory logic?

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.15 Snippet::Base Class Reference

[Base](#) class for all code snippets.

```
#include <snippet.h>
```

Inheritance diagram for Snippet::Base:



### Classes

- struct [DerivedParam](#)  
A derived parameter has a name and a function for obtaining its value.
- struct [EGP](#)  
An extra global parameter has a name and a type.
- struct [ParamVal](#)  
Additional input variables, row state variables and other things have a name, a type and an initial value.

### Public Types

- typedef std::vector< std::string > [StringVec](#)
- typedef std::vector< [EGP](#) > [EGPVec](#)
- typedef std::vector< [ParamVal](#) > [ParamValVec](#)
- typedef std::vector< [DerivedParam](#) > [DerivedParamVec](#)

### Public Member Functions

- virtual [~Base](#) ()
- virtual [StringVec](#) [getParamNames](#) () const  
Gets names of of (independent) model parameters.
- virtual [DerivedParamVec](#) [getDerivedParams](#) () const

### Static Protected Member Functions

- template<typename T >  
static size\_t [getNamedVecIndex](#) (const std::string &name, const std::vector< T > &vec)

#### 19.15.1 Detailed Description

[Base](#) class for all code snippets.

#### 19.15.2 Member Typedef Documentation

### 19.15.2.1 DerivedParamVec

```
typedef std::vector<DerivedParam> Snippet::Base::DerivedParamVec
```

### 19.15.2.2 EGPVec

```
typedef std::vector<EGP> Snippet::Base::EGPVec
```

### 19.15.2.3 ParamValVec

```
typedef std::vector<ParamVal> Snippet::Base::ParamValVec
```

### 19.15.2.4 StringVec

```
typedef std::vector<std::string> Snippet::Base::StringVec
```

## 19.15.3 Constructor & Destructor Documentation

### 19.15.3.1 ~Base()

```
virtual Snippet::Base::~~Base ( ) [inline], [virtual]
```

## 19.15.4 Member Function Documentation

### 19.15.4.1 getDerivedParams()

```
virtual DerivedParamVec Snippet::Base::getDerivedParams ( ) const [inline], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented in [NeuronModels::PoissonNew](#), [WeightUpdateModels::PiecewiseSTDP](#), [NeuronModels::LIF](#), [NeuronModels::RulkovMap](#), [InitSparseConnectivitySnippet::FixedProbabilityBase](#), [PostsynapticModels::ExpCond](#), and [PostsynapticModels::ExpCurr](#).

### 19.15.4.2 getNamedVecIndex()

```
template<typename T >
static size_t Snippet::Base::getNamedVecIndex (
    const std::string & name,
    const std::vector< T > & vec ) [inline], [static], [protected]
```

### 19.15.4.3 getParamNames()

```
virtual StringVec Snippet::Base::getParamNames ( ) const [inline], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented in [NeuronModels::TraubMilesNStep](#), [NeuronModels::TraubMiles](#), [NeuronModels::PoissonNew](#), [NeuronModels::Poisson](#), [WeightUpdateModels::PiecewiseSTDP](#), [NeuronModels::LIF](#), [WeightUpdateModels::LIF](#)

[StaticGraded](#), [NeuronModels::IzhikevichVariable](#), [NeuronModels::Izhikevich](#), [InitVarSnippet::Gamma](#), [InitSparseConnectivitySnippet::FixedProbabilityBase](#), [NeuronModels::RulkovMap](#), [InitVarSnippet::Exponential](#), [InitVarSnippet::Normal](#), [InitVarSnippet::Uniform](#), [PostsynapticModels::ExpCond](#), [CurrentSourceModels::GaussianNoise](#), [InitVarSnippet::Constant](#), [CurrentSourceModels::DC](#), and [PostsynapticModels::ExpCurr](#).

The documentation for this class was generated from the following file:


- [snippet.h](#)

## 19.16 PostsynapticModels::Base Class Reference

[Base](#) class for all postsynaptic models.

```
#include <postsynapticModels.h>
```

Inheritance diagram for PostsynapticModels::Base:



### Public Member Functions

- virtual std::string [getDecayCode](#) () const
- virtual std::string [getApplyInputCode](#) () const
- virtual std::string [getSupportCode](#) () const

### Additional Inherited Members

#### 19.16.1 Detailed Description

[Base](#) class for all postsynaptic models.

#### 19.16.2 Member Function Documentation

##### 19.16.2.1 getApplyInputCode()

```
virtual std::string PostsynapticModels::Base::getApplyInputCode ( ) const [inline], [virtual]
```

Reimplemented in [PostsynapticModels::DeltaCurr](#), [PostsynapticModels::ExpCond](#), and [PostsynapticModels::ExpCurr](#).

##### 19.16.2.2 getDecayCode()

```
virtual std::string PostsynapticModels::Base::getDecayCode ( ) const [inline], [virtual]
```

Reimplemented in [PostsynapticModels::ExpCond](#), and [PostsynapticModels::ExpCurr](#).

## 19.16.2.3 getSupportCode()

```
virtual std::string PostsynapticModels::Base::getSupportCode ( ) const [inline], [virtual]
```


The documentation for this class was generated from the following file:

- [postsynapticModels.h](#)

## 19.17 CodeGenerator::CUDA::PresynapticUpdateStrategy::Base Class Reference

```
#include <presynapticUpdateStrategy.h>
```

Inheritance diagram for CodeGenerator::CUDA::PresynapticUpdateStrategy::Base:



## Public Member Functions

- virtual size\_t [getNumThreads](#) (const [SynapseGroupInternal](#) &sg) const =0  
*Get the number of threads that presynaptic updates should be parallelised across.*
- virtual size\_t [getSynapticMatrixRowStride](#) (const [SynapseGroupInternal](#) &sg) const =0  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual bool [isCompatible](#) (const [SynapseGroupInternal](#) &sg, const cudaDeviceProp &deviceProps, const [Preferences](#) &preferences) const =0  
*Is this presynaptic update strategy compatible with a given synapse group?*
- virtual size\_t [getSharedMemoryPerThread](#) (const [SynapseGroupInternal](#) &sg, const [Backend](#) &backend) const =0  
*How many neurons does each thread accumulate the outputs of into shared memory.*
- virtual void [genPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const =0
- virtual void [genUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, bool trueSpike, size\_t idStart, [BackendBase::SynapseGroupHandler](#) wumThreshHandler, [BackendBase::SynapseGroupHandler](#) wumSimHandler, [BackendBase::SynapseGroupHandler](#) wumProceduralConnectHandler) const =0  
*Generate presynaptic update code.*
- virtual void [genPostamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const =0

## 19.17.1 Member Function Documentation

## 19.17.1.1 genPostamble()

```
virtual void CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::genPostamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).

### 19.17.1.2 genPreamble()

```
virtual void CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::genPreamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [pure virtual]
```

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).

### 19.17.1.3 genUpdate()

```
virtual void CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::genUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    bool trueSpike,
    size_t idStart,
    BackendBase::SynapseGroupHandler wumThreshHandler,
    BackendBase::SynapseGroupHandler wumSimHandler,
    BackendBase::SynapseGroupHandler wumProceduralConnectHandler ) const [pure virtual]
```

Generate presynaptic update code.

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).

### 19.17.1.4 getNumThreads()

```
virtual size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::getNumThreads (
    const SynapseGroupInternal & sg ) const [pure virtual]
```

Get the number of threads that presynaptic updates should be parallelised across.

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).

### 19.17.1.5 getSharedMemoryPerThread()

```
virtual size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::getSharedMemoryPerThread (
    const SynapseGroupInternal & sg,
    const Backend & backend ) const [pure virtual]
```

How many neurons does each thread accumulate the outputs of into shared memory.

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).



## 19.17.1.6 getSynapticMatrixRowStride()

```
virtual size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [pure virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).

## 19.17.1.7 isCompatible()

```
virtual bool CodeGenerator::CUDA::PresynapticUpdateStrategy::Base::isCompatible (
    const SynapseGroupInternal & sg,
    const cudaDeviceProp & deviceProps,
    const Preferences & preferences ) const [pure virtual]
```

Is this presynaptic update strategy compatible with a given synapse group?

Implemented in [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#), [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#), and [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#).

The documentation for this class was generated from the following file:


- [presynapticUpdateStrategy.h](#)

## 19.18 WeightUpdateModels::Base Class Reference

[Base](#) class for all weight update models.

```
#include <weightUpdateModels.h>
```

Inheritance diagram for WeightUpdateModels::Base:



## Public Member Functions

- virtual std::string [getSimCode](#) () const  
*Gets simulation code run when 'true' spikes are received.*
- virtual std::string [getEventCode](#) () const  
*Gets code run when events (all the instances where event threshold condition is met) are received.*
- virtual std::string [getLearnPostCode](#) () const  
*Gets code to include in the learnSynapsesPost kernel/function.*
- virtual std::string [getSynapseDynamicsCode](#) () const  
*Gets code for synapse dynamics which are independent of spike detection.*
- virtual std::string [getEventThresholdConditionCode](#) () const  
*Gets codes to test for events.*

- virtual std::string [getSimSupportCode](#) () const  
*Gets support code to be made available within the synapse kernel/function.*
- virtual std::string [getLearnPostSupportCode](#) () const  
*Gets support code to be made available within learnSynapsesPost kernel/function.*
- virtual std::string [getSynapseDynamicsSupportCode](#) () const  
*Gets support code to be made available within the synapse dynamics kernel/function.*
- virtual std::string [getPreSpikeCode](#) () const
- virtual std::string [getPostSpikeCode](#) () const
- virtual [VarVec](#) [getPreVars](#) () const
- virtual [VarVec](#) [getPostVars](#) () const
- virtual bool [isPreSpikeTimeRequired](#) () const  
*Whether presynaptic spike times are needed or not.*
- virtual bool [isPostSpikeTimeRequired](#) () const  
*Whether postsynaptic spike times are needed or not.*
- size\_t [getPreVarIndex](#) (const std::string &varName) const  
*Find the index of a named presynaptic variable.*
- size\_t [getPostVarIndex](#) (const std::string &varName) const  
*Find the index of a named postsynaptic variable.*

## Additional Inherited Members

### 19.18.1 Detailed Description

[Base](#) class for all weight update models.

### 19.18.2 Member Function Documentation

#### 19.18.2.1 [getEventCode\(\)](#)

```
virtual std::string WeightUpdateModels::Base::getEventCode ( ) const [inline], [virtual]
```

Gets code run when events (all the instances where event threshold condition is met) are received.

Reimplemented in [WeightUpdateModels::StaticGraded](#).

#### 19.18.2.2 [getEventThresholdConditionCode\(\)](#)

```
virtual std::string WeightUpdateModels::Base::getEventThresholdConditionCode ( ) const [inline], [virtual]
```

Gets codes to test for events.

Reimplemented in [WeightUpdateModels::StaticGraded](#).

#### 19.18.2.3 [getLearnPostCode\(\)](#)

```
virtual std::string WeightUpdateModels::Base::getLearnPostCode ( ) const [inline], [virtual]
```

Gets code to include in the learnSynapsesPost kernel/function.

For examples when modelling STDP, this is where the effect of postsynaptic spikes which occur *after* presynaptic spikes are applied.

Reimplemented in [WeightUpdateModels::PiecewiseSTDP](#).

**19.18.2.4 getLearnPostSupportCode()**

```
virtual std::string WeightUpdateModels::Base::getLearnPostSupportCode ( ) const [inline], [virtual]
```

Gets support code to be made available within learnSynapsesPost kernel/function.

Preprocessor defines are also allowed if appropriately safeguarded against multiple definition by using ifndef; functions should be declared as "\_\_host\_\_ \_\_device\_\_" to be available for both GPU and CPU versions.

**19.18.2.5 getPostSpikeCode()**

```
virtual std::string WeightUpdateModels::Base::getPostSpikeCode ( ) const [inline], [virtual]
```

Gets code to be run once per spiking postsynaptic neuron before learn post code is run on synapses

This is typically for the code to update postsynaptic variables. Presynaptic and synapse variables are not accessible from within this code

**19.18.2.6 getPostVarIndex()**

```
size_t WeightUpdateModels::Base::getPostVarIndex (
    const std::string & varName ) const [inline]
```

Find the index of a named postsynaptic variable.

**19.18.2.7 getPostVars()**

```
virtual VarVec WeightUpdateModels::Base::getPostVars ( ) const [inline], [virtual]
```

Gets names and types (as strings) of state variables that are common across all synapses going to the same postsynaptic neuron

**19.18.2.8 getPreSpikeCode()**

```
virtual std::string WeightUpdateModels::Base::getPreSpikeCode ( ) const [inline], [virtual]
```

Gets code to be run once per spiking presynaptic neuron before sim code is run on synapses

This is typically for the code to update presynaptic variables. Postsynaptic and synapse variables are not accessible from within this code

**19.18.2.9 getPreVarIndex()**

```
size_t WeightUpdateModels::Base::getPreVarIndex (
    const std::string & varName ) const [inline]
```

Find the index of a named presynaptic variable.

**19.18.2.10 getPreVars()**

```
virtual VarVec WeightUpdateModels::Base::getPreVars ( ) const [inline], [virtual]
```

Gets names and types (as strings) of state variables that are common across all synapses coming from the same presynaptic neuron

**19.18.2.11 getSimCode()**

```
virtual std::string WeightUpdateModels::Base::getSimCode ( ) const [inline], [virtual]
```

Gets simulation code run when 'true' spikes are received.

Reimplemented in [WeightUpdateModels::PiecewiseSTDP](#), [WeightUpdateModels::StaticPulseDendriticDelay](#), and [WeightUpdateModels::StaticPulse](#).

#### 19.18.2.12 `getSimSupportCode()`

```
virtual std::string WeightUpdateModels::Base::getSimSupportCode ( ) const [inline], [virtual]
```

Gets support code to be made available within the synapse kernel/function.

This is intended to contain user defined device functions that are used in the weight update code. Preprocessor defines are also allowed if appropriately safeguarded against multiple definition by using `ifndef`; functions should be declared as "`__host__ __device__`" to be available for both GPU and CPU versions; note that this support code is available to sim, event threshold and event code

#### 19.18.2.13 `getSynapseDynamicsCode()`

```
virtual std::string WeightUpdateModels::Base::getSynapseDynamicsCode ( ) const [inline],  
[virtual]
```

Gets code for synapse dynamics which are independent of spike detection.

#### 19.18.2.14 `getSynapseDynamicsSupportCode()`

```
virtual std::string WeightUpdateModels::Base::getSynapseDynamicsSupportCode ( ) const [inline],  
[virtual]
```

Gets support code to be made available within the synapse dynamics kernel/function.

Preprocessor defines are also allowed if appropriately safeguarded against multiple definition by using `ifndef`; functions should be declared as "`__host__ __device__`" to be available for both GPU and CPU versions.

#### 19.18.2.15 `isPostSpikeTimeRequired()`

```
virtual bool WeightUpdateModels::Base::isPostSpikeTimeRequired ( ) const [inline], [virtual]
```

Whether postsynaptic spike times are needed or not.

Reimplemented in [WeightUpdateModels::PiecewiseSTDP](#).

#### 19.18.2.16 `isPreSpikeTimeRequired()`

```
virtual bool WeightUpdateModels::Base::isPreSpikeTimeRequired ( ) const [inline], [virtual]
```

Whether presynaptic spike times are needed or not.

Reimplemented in [WeightUpdateModels::PiecewiseSTDP](#).


The documentation for this class was generated from the following file:

- [weightUpdateModels.h](#)

### 19.19 SpineMLSimulator::Input::Base Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::Base:



### Public Member Functions

- virtual [~Base](#) ()
- virtual void [apply](#) (double dt, unsigned long long timestep)=0

### Protected Member Functions

- [Base](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value)
- bool [shouldApply](#) (unsigned long long timestep) const
- void [updateValues](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc) const

## 19.19.1 Constructor & Destructor Documentation

### 19.19.1.1 ~Base()

```
SpineMLSimulator::Input::Base::~~Base ( ) [virtual]
```

### 19.19.1.2 Base()

```
SpineMLSimulator::Input::Base::Base (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value ) [protected]
```

## 19.19.2 Member Function Documentation

### 19.19.2.1 apply()

```
virtual void SpineMLSimulator::Input::Base::apply (
    double dt,
    unsigned long long timestep ) [pure virtual]
```

Implemented in [SpineMLSimulator::Input::Analogue](#), [SpineMLSimulator::Input::SpikeTime](#), and [SpineMLSimulator::Input::InterSpikeIntervalBase](#).

### 19.19.2.2 shouldApply()

```
bool SpineMLSimulator::Input::Base::shouldApply (
    unsigned long long timestep ) const [inline], [protected]
```

### 19.19.2.3 updateValues()

```
void SpineMLSimulator::Input::Base::updateValues (
    double dt,
    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) const [protected]
```


The documentation for this class was generated from the following files:

- [input.h](#)
- [input.cc](#)

## 19.20 SpineMLSimulator::InputValue::Base Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::Base:



### Public Member Functions

- virtual [~Base](#) ()
- virtual void [update](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc)=0

### Protected Member Functions

- [Base](#) (unsigned int numNeurons, const pugi::xml\_node &node)
- const std::vector< unsigned int > & [getTargetIndices](#) () const
- unsigned int [getNumNeurons](#) () const

## 19.20.1 Constructor & Destructor Documentation

### 19.20.1.1 ~Base()

```
virtual SpineMLSimulator::InputValue::Base::~~Base ( ) [inline], [virtual]
```

### 19.20.1.2 Base()

```
SpineMLSimulator::InputValue::Base::Base (
    unsigned int numNeurons,
    const pugi::xml_node & node ) [protected]
```

## 19.20.2 Member Function Documentation

## 19.20.2.1 getNumNeurons()

```
unsigned int SpineMLSimulator::InputValue::Base::getNumNeurons ( ) const [inline], [protected]
```

## 19.20.2.2 getTargetIndices()

```
const std::vector<unsigned int>& SpineMLSimulator::InputValue::Base::getTargetIndices ( )
const [inline], [protected]
```

## 19.20.2.3 update()

```
virtual void SpineMLSimulator::InputValue::Base::update (
    double dt,
    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) [pure virtual]
```

Implemented in [SpineMLSimulator::InputValue::External](#), [SpineMLSimulator::InputValue::TimeVaryingArray](#), [SpineMLSimulator::InputValue::TimeVarying](#), [SpineMLSimulator::InputValue::ConstantArray](#), and [SpineMLSimulator::InputValue::Constant](#).


The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

## 19.21 SpineMLSimulator::LogOutput::Base Class Reference

```
#include <logOutput.h>
```

Inheritance diagram for SpineMLSimulator::LogOutput::Base:



## Public Member Functions

- [Base](#) (const pugi::xml\_node &node, double dt)
- virtual [~Base](#) ()
- virtual void [record](#) (double dt, unsigned long long timestep)=0

## Protected Member Functions

- bool [shouldRecord](#) (unsigned long long timestep) const
- unsigned long long [getEndTimeStep](#) () const

## 19.21.1 Constructor &amp; Destructor Documentation

### 19.21.1.1 Base()

```
SpineMLSimulator::LogOutput::Base::Base (
    const pugi::xml_node & node,
    double dt )
```

### 19.21.1.2 ~Base()

```
virtual SpineMLSimulator::LogOutput::Base::~~Base ( ) [inline], [virtual]
```

## 19.21.2 Member Function Documentation

### 19.21.2.1 getEndTimestep()

```
unsigned long long SpineMLSimulator::LogOutput::Base::getEndTimestep ( ) const [inline],
[protected]
```

### 19.21.2.2 record()

```
virtual void SpineMLSimulator::LogOutput::Base::record (
    double dt,
    unsigned long long timestep ) [pure virtual]
```

Implemented in [SpineMLSimulator::LogOutput::Event](#), [SpineMLSimulator::LogOutput::AnalogueExternal](#), and [SpineMLSimulator::LogOutput::AnalogueFile](#).

### 19.21.2.3 shouldRecord()

```
bool SpineMLSimulator::LogOutput::Base::shouldRecord (
    unsigned long long timestep ) const [inline], [protected]
```


The documentation for this class was generated from the following files:

- [logOutput.h](#)
- [logOutput.cc](#)

## 19.22 SpineMLSimulator::ModelProperty::Base Class Reference

```
#include <modelProperty.h>
```

Inheritance diagram for SpineMLSimulator::ModelProperty::Base:



### Public Member Functions

- [Base](#) (const [StateVar](#)< [scalar](#) > &stateVar, unsigned int size)
- virtual [~Base](#) ()
- [scalar](#) \* [getHostStateVar](#) ()
- const [scalar](#) \* [getHostStateVar](#) () const



- void [pushToDevice](#) () const
- void [pullFromDevice](#) () const
- unsigned int [getSize](#) () const

### 19.22.1 Constructor & Destructor Documentation

#### 19.22.1.1 Base()

```
SpineMLSimulator::ModelProperty::Base::Base (
    const StateVar< scalar > & stateVar,
    unsigned int size ) [inline]
```

#### 19.22.1.2 ~Base()

```
virtual SpineMLSimulator::ModelProperty::Base::~~Base ( ) [inline], [virtual]
```

### 19.22.2 Member Function Documentation

#### 19.22.2.1 getHostStateVar() [1/2]

```
scalar* SpineMLSimulator::ModelProperty::Base::getHostStateVar ( ) [inline]
```

#### 19.22.2.2 getHostStateVar() [2/2]

```
const scalar* SpineMLSimulator::ModelProperty::Base::getHostStateVar ( ) const [inline]
```

#### 19.22.2.3 getSize()

```
unsigned int SpineMLSimulator::ModelProperty::Base::getSize ( ) const [inline]
```

#### 19.22.2.4 pullFromDevice()

```
void SpineMLSimulator::ModelProperty::Base::pullFromDevice ( ) const [inline]
```

#### 19.22.2.5 pushToDevice()

```
void SpineMLSimulator::ModelProperty::Base::pushToDevice ( ) const [inline]
```

The documentation for this class was generated from the following file:

- [modelProperty.h](#)

### 19.23 CodeGenerator::CodeStream::CB Struct Reference

A close bracket marker.

```
#include <codeStream.h>
```

## Public Member Functions

- [CB](#) (unsigned int level)

## Public Attributes

- const unsigned int [Level](#)

### 19.23.1 Detailed Description

A close bracket marker.

Write to code stream `os` using:

```
os << CB(16);
```

### 19.23.2 Constructor & Destructor Documentation

#### 19.23.2.1 CB()

```
CodeGenerator::CodeStream::CB::CB (  
    unsigned int level ) [inline]
```

### 19.23.3 Member Data Documentation

#### 19.23.3.1 Level

```
const unsigned int CodeGenerator::CodeStream::CB::Level
```


The documentation for this struct was generated from the following file:

- [codeStream.h](#)

## 19.24 CodeGenerator::CodeStream Class Reference

```
#include <codeStream.h>
```

Inheritance diagram for CodeGenerator::CodeStream:



## Classes

- struct [CB](#)  
*A close bracket marker.*
- struct [OB](#)  
*An open bracket marker.*
- class [Scope](#)

## Public Member Functions

- [CodeStream](#) ()
- [CodeStream](#) (std::ostream &stream)
- void [setSink](#) (std::ostream &stream)

## Friends

- [GENN\\_EXPORT](#) friend std::ostream & [operator<<](#) (std::ostream &s, const [OB](#) &ob)
- [GENN\\_EXPORT](#) friend std::ostream & [operator<<](#) (std::ostream &s, const [CB](#) &cb)

### 19.24.1 Constructor & Destructor Documentation

#### 19.24.1.1 CodeStream() [1/2]

```
CodeGenerator::CodeStream::CodeStream ( ) [inline]
```

#### 19.24.1.2 CodeStream() [2/2]

```
CodeGenerator::CodeStream::CodeStream (
    std::ostream & stream ) [inline]
```

### 19.24.2 Member Function Documentation

#### 19.24.2.1 setSink()

```
void CodeGenerator::CodeStream::setSink (
    std::ostream & stream ) [inline]
```

### 19.24.3 Friends And Related Function Documentation

#### 19.24.3.1 operator<< [1/2]

```
GENN\_EXPORT friend std::ostream& operator<< (
    std::ostream & s,
    const OB & ob ) [friend]
```

### 19.24.3.2 operator<< [2/2]

```
GENN_EXPORT friend std::ostream& operator<< (
    std::ostream & s,
    const CB & cb ) [friend]
```

The documentation for this class was generated from the following file:


- [codeStream.h](#)

## 19.25 InitVarSnippet::Constant Class Reference

Initialises variable to a constant value.

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Constant:



### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitVarSnippet::Constant](#), 1)
- [SET\\_CODE](#) ("\$(value) = \$(constant);")
- virtual [StringVec](#) [getParamNames](#) () const override

*Gets names of of (independent) model parameters.*

### Additional Inherited Members

#### 19.25.1 Detailed Description

Initialises variable to a constant value.

This snippet takes 1 parameter:

- `value` - The value to initialise the variable to

### Note

This snippet type is seldom used directly - [Models::VarInit](#) has an implicit constructor that, internally, creates one of these snippets

#### 19.25.2 Member Function Documentation

## 19.25.2.1 DECLARE\_SNIPPET()

```
InitVarSnippet::Constant::DECLARE_SNIPPET (
    InitVarSnippet::Constant ,
    1 )
```

## 19.25.2.2 getParamNames()

```
virtual StringVec InitVarSnippet::Constant::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

## 19.25.2.3 SET\_CODE()

```
InitVarSnippet::Constant::SET_CODE ( )
```


The documentation for this class was generated from the following file:

- [initVarSnippet.h](#)

## 19.26 SpineMLSimulator::InputValue::Constant Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::Constant:



## Public Member Functions

- [Constant](#) (double dt, unsigned int numNeurons, const pugi::xml\_node &node)
- virtual void [update](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc) override

## Additional Inherited Members

## 19.26.1 Constructor &amp; Destructor Documentation

## 19.26.1.1 Constant()

```
SpineMLSimulator::InputValue::Constant::Constant (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node )
```

## 19.26.2 Member Function Documentation

### 19.26.2.1 update()

```
void SpineMLSimulator::InputValue::Constant::update (
    double dt,
    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) [override], [virtual]
```

Implements [SpineMLSimulator::InputValue::Base](#).


The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

## 19.27 SpineMLSimulator::InputValue::ConstantArray Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::ConstantArray:



### Public Member Functions

- [ConstantArray](#) (double dt, unsigned int numNeurons, const pugi::xml\_node &node)
- virtual void [update](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc) override

### Additional Inherited Members

## 19.27.1 Constructor & Destructor Documentation

### 19.27.1.1 ConstantArray()

```
SpineMLSimulator::InputValue::ConstantArray::ConstantArray (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node )
```

## 19.27.2 Member Function Documentation

### 19.27.2.1 update()

```
void SpineMLSimulator::InputValue::ConstantArray::update (
    double dt,
```

```

    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) [override], [virtual]

```

Implements [SpineMLSimulator::InputValue::Base](#).


The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

## 19.28 pygenn.genn\_groups.CurrentSource Class Reference

Class representing a current injection into a group of neurons.

Inheritance diagram for pygenn.genn\_groups.CurrentSource:



### Public Member Functions

- `def \_\_init\_\_ (self, name)`  
*Init [CurrentSource](#).*
- `def size (self)`  
*Number of neuron in the injected population.*
- `def size (self, _)`
- `def set\_current\_source\_model (self, model, param_space, var_space)`  
*Set curront source model, its parameters and initial variables.*
- `def add\_to (self, nn_model, pop)`  
*Inject this [CurrentSource](#) into population and add it to the GeNN NNmodel.*
- `def add\_extra\_global\_param (self, param_name, param_values)`  
*Set extra global parameter.*
- `def set\_extra\_global\_param (self, param_name, param_values)`  
*Set extra global parameter.*
- `def load (self, slm, scalar)`
- `def reinitialise (self, slm, scalar)`  
*Reinitialise current source.*

### Public Attributes

- [current\\_source\\_model](#)
- [target\\_pop](#)
- [pop](#)

#### 19.28.1 Detailed Description

Class representing a current injection into a group of neurons.

## 19.28.2 Constructor & Destructor Documentation

### 19.28.2.1 `__init__()`

```
def pygenn.genn_groups.CurrentSource.__init__ (
    self,
    name )
```

Init [CurrentSource](#).

#### Parameters

<i>name</i>	string name of the current source
-------------	-----------------------------------

## 19.28.3 Member Function Documentation

### 19.28.3.1 `add_extra_global_param()`

```
def pygenn.genn_groups.CurrentSource.add_extra_global_param (
    self,
    param_name,
    param_values )
```

Set extra global parameter.

#### Parameters

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

### 19.28.3.2 `add_to()`

```
def pygenn.genn_groups.CurrentSource.add_to (
    self,
    nn_model,
    pop )
```

Inject this [CurrentSource](#) into population and add it to the GeNN NNmodel.

#### Parameters

<i>pop</i>	instance of <a href="#">NeuronGroup</a> into which this <a href="#">CurrentSource</a> should be injected
<i>nn_model</i>	GeNN NNmodel

### 19.28.3.3 `load()`

```
def pygenn.genn_groups.CurrentSource.load (
    self,
    slm,
```



```
scalar )
```

#### 19.28.3.4 reinitialise()

```
def pygenn.genn_groups.CurrentSource.reinitialise (
    self,
    slm,
    scalar )
```

Reinitialise current source.

##### Parameters

<i>slm</i>	<a href="#">SharedLibraryModel</a> instance for accessing variables
<i>scalar</i>	String specifying "scalar" type

#### 19.28.3.5 set\_current\_source\_model()

```
def pygenn.genn_groups.CurrentSource.set_current_source_model (
    self,
    model,
    param_space,
    var_space )
```

Set curront source model, its parameters and initial variables.

##### Parameters

<i>model</i>	type as string of intance of the model
<i>param_space</i>	dict with model parameters
<i>var_space</i>	dict with model variables

#### 19.28.3.6 set\_extra\_global\_param()

```
def pygenn.genn_groups.CurrentSource.set_extra_global_param (
    self,
    param_name,
    param_values )
```

Set extra global parameter.

##### Parameters

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

#### 19.28.3.7 size() [1/2]

```
def pygenn.genn_groups.CurrentSource.size (
    self )
```

Number of neuron in the injected population.

#### 19.28.3.8 size() [2/2]

```
def pygenn.genn_groups.CurrentSource.size (
    self,
    _ )
```

### 19.28.4 Member Data Documentation

#### 19.28.4.1 current\_source\_model

```
pygenn.genn_groups.CurrentSource.current_source_model
```

#### 19.28.4.2 pop

```
pygenn.genn_groups.CurrentSource.pop
```

#### 19.28.4.3 target\_pop

```
pygenn.genn_groups.CurrentSource.target_pop
```


The documentation for this class was generated from the following file:

- [genn\\_groups.py](#)

### 19.29 CurrentSource Class Reference

```
#include <currentSource.h>
```

Inheritance diagram for CurrentSource:



#### Public Member Functions

- [CurrentSource](#) (const [CurrentSource](#) &)=delete
- [CurrentSource](#) ()=delete
- void [setVarLocation](#) (const std::string &varName, [VarLocation](#) loc)  
*Set location of current source state variable.*
- void [setExtraGlobalParamLocation](#) (const std::string &paramName, [VarLocation](#) loc)  
*Set location of extra global parameter.*
- const std::string & [getName](#) () const
- const [CurrentSourceModels::Base](#) \* [getCurrentSourceModel](#) () const  
*Gets the current source model used by this group.*
- const std::vector< double > & [getParams](#) () const

- `const std::vector< Models::VarInit > & getVarInitialisers () const`
- `VarLocation getVarLocation (const std::string &varName) const`  
*Get variable location for current source model state variable.*
- `VarLocation getVarLocation (size_t index) const`  
*Get variable location for current source model state variable.*
- `VarLocation getExtraGlobalParamLocation (const std::string &paramName) const`  
*Get location of neuron model extra global parameter by name.*
- `VarLocation getExtraGlobalParamLocation (size_t index) const`  
*Get location of neuron model extra global parameter by index.*

### Protected Member Functions

- `CurrentSource (const std::string &name, const CurrentSourceModels::Base *currentSourceModel, const std::vector< double > &params, const std::vector< Models::VarInit > &varInitialisers, VarLocation defaultVarLocation, VarLocation defaultExtraGlobalParamLocation)`
- `void initDerivedParams (double dt)`
- `const std::vector< double > & getDerivedParams () const`
- `bool isSimRNGRequired () const`  
*Does this current source require an RNG to simulate.*
- `bool isInitRNGRequired () const`  
*Does this current source group require an RNG for its init code.*

## 19.29.1 Constructor & Destructor Documentation

### 19.29.1.1 [CurrentSource\(\)](#) [1/3]

```
CurrentSource::CurrentSource (
    const CurrentSource & ) [delete]
```

### 19.29.1.2 [CurrentSource\(\)](#) [2/3]

```
CurrentSource::CurrentSource ( ) [delete]
```

### 19.29.1.3 [CurrentSource\(\)](#) [3/3]

```
CurrentSource::CurrentSource (
    const std::string & name,
    const CurrentSourceModels::Base * currentSourceModel,
    const std::vector< double > & params,
    const std::vector< Models::VarInit > & varInitialisers,
    VarLocation defaultVarLocation,
    VarLocation defaultExtraGlobalParamLocation ) [inline], [protected]
```

## 19.29.2 Member Function Documentation

**19.29.2.1** `getCurrentSourceModel()`

```
const CurrentSourceModels::Base* CurrentSource::getCurrentSourceModel ( ) const [inline]
```

Gets the current source model used by this group.

**19.29.2.2** `getDerivedParams()`

```
const std::vector<double>& CurrentSource::getDerivedParams ( ) const [inline], [protected]
```

**19.29.2.3** `getExtraGlobalParamLocation()` [1/2]

```
VarLocation CurrentSource::getExtraGlobalParamLocation (
    const std::string & paramName ) const
```

Get location of neuron model extra global parameter by name.

This is only used by extra global parameters which are pointers

**19.29.2.4** `getExtraGlobalParamLocation()` [2/2]

```
VarLocation CurrentSource::getExtraGlobalParamLocation (
    size_t index ) const [inline]
```

Get location of neuron model extra global parameter by omdex.

This is only used by extra global parameters which are pointers

**19.29.2.5** `getName()`

```
const std::string& CurrentSource::getName ( ) const [inline]
```

**19.29.2.6** `getParams()`

```
const std::vector<double>& CurrentSource::getParams ( ) const [inline]
```

**19.29.2.7** `getVarInitialisers()`

```
const std::vector<Models::VarInit>& CurrentSource::getVarInitialisers ( ) const [inline]
```

**19.29.2.8** `getVarLocation()` [1/2]

```
VarLocation CurrentSource::getVarLocation (
    const std::string & varName ) const
```

Get variable location for current source model state variable.

**19.29.2.9** `getVarLocation()` [2/2]

```
VarLocation CurrentSource::getVarLocation (
    size_t index ) const [inline]
```

Get variable location for current source model state variable.

**19.29.2.10 initDerivedParams()**

```
void CurrentSource::initDerivedParams (
    double dt ) [protected]
```

**19.29.2.11 isInitRNGRequired()**

```
bool CurrentSource::isInitRNGRequired ( ) const [protected]
```

Does this current source group require an RNG for it's init code.

**19.29.2.12 isSimRNGRequired()**

```
bool CurrentSource::isSimRNGRequired ( ) const [protected]
```

Does this current source require an RNG to simulate.

**19.29.2.13 setExtraGlobalParamLocation()**

```
void CurrentSource::setExtraGlobalParamLocation (
    const std::string & paramName,
    VarLocation loc )
```

Set location of extra global parameter.

This is ignored for simulations on hardware with a single memory space and only applies to extra global parameters which are pointers.

**19.29.2.14 setVarLocation()**

```
void CurrentSource::setVarLocation (
    const std::string & varName,
    VarLocation loc )
```

Set location of current source state variable.


The documentation for this class was generated from the following files:

- [currentSource.h](#)
- [currentSource.cc](#)

**19.30 CurrentSourceInternal Class Reference**

```
#include <currentSourceInternal.h>
```

Inheritance diagram for CurrentSourceInternal:

**Public Member Functions**

- [CurrentSourceInternal](#) (const std::string &name, const [CurrentSourceModels::Base](#) \*currentSourceModel, const std::vector< double > &params, const std::vector< [Models::VarInit](#) > &varInitialisers, [VarLocation](#)

defaultVarLocation, [VarLocation](#) defaultExtraGlobalParamLocation)

## Additional Inherited Members

### 19.30.1 Constructor & Destructor Documentation

#### 19.30.1.1 CurrentSourceInternal()

```
CurrentSourceInternal::CurrentSourceInternal (
    const std::string & name,
    const CurrentSourceModels::Base * currentSourceModel,
    const std::vector< double > & params,
    const std::vector< Models::VarInit > & varInitialisers,
    VarLocation defaultVarLocation,
    VarLocation defaultExtraGlobalParamLocation ) [inline]
```

The documentation for this class was generated from the following file:


- [currentSourceInternal.h](#)

### 19.31 CurrentSourceModels::DC Class Reference

[DC](#) source.

```
#include <currentSourceModels.h>
```

Inheritance diagram for CurrentSourceModels::DC:



## Public Types

- typedef [Snippet::ValueBase](#)< 1 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- [SET\\_INJECTION\\_CODE](#) ("\$(injectCurrent, \$(amp));\n")
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*

## Static Public Member Functions

- static const [DC](#) \* [getInstance](#) ()

## Additional Inherited Members

## 19.31.1 Detailed Description

[DC](#) source.

It has a single parameter:

- `amp` - amplitude of the current [nA]

## 19.31.2 Member Typedef Documentation

## 19.31.2.1 ParamValues

```
typedef Snippet::ValueBase< 1 > CurrentSourceModels::DC::ParamValues
```

## 19.31.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> CurrentSourceModels::DC::PostVarValues
```

## 19.31.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> CurrentSourceModels::DC::PreVarValues
```

## 19.31.2.4 VarValues

```
typedef Models::VarInitContainerBase< 0 > CurrentSourceModels::DC::VarValues
```

## 19.31.3 Member Function Documentation

## 19.31.3.1 getInstance()

```
static const DC* CurrentSourceModels::DC::getInstance ( ) [inline], [static]
```

## 19.31.3.2 getParamNames()

```
virtual StringVec CurrentSourceModels::DC::getParamNames ( ) const [inline], [override],  
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

### 19.31.3.3 SET\_INJECTION\_CODE()

```
CurrentSourceModels::DC::SET_INJECTION_CODE (
    "$(injectCurrent, $(amp));\ " )
```

The documentation for this class was generated from the following file:


- [currentSourceModels.h](#)

## 19.32 PostsynapticModels::DeltaCurr Class Reference

Simple delta current synapse.

```
#include <postsynapticModels.h>
```

Inheritance diagram for PostsynapticModels::DeltaCurr:



### Public Types

- typedef [Snippet::ValueBase< 0 >](#) [ParamValues](#)
- typedef [Models::VarInitContainerBase< 0 >](#) [VarValues](#)
- typedef [Models::VarInitContainerBase< 0 >](#) [PreVarValues](#)
- typedef [Models::VarInitContainerBase< 0 >](#) [PostVarValues](#)

### Public Member Functions

- virtual std::string [getApplyInputCode](#) () const override

### Static Public Member Functions

- static const [DeltaCurr](#) \* [getInstance](#) ()

### Additional Inherited Members

#### 19.32.1 Detailed Description

Simple delta current synapse.

Synaptic input provides a direct inject of instantaneous current

#### 19.32.2 Member Typedef Documentation



#### 19.32.2.1 ParamValues

```
typedef Snippet::ValueBase< 0 > PostsynapticModels::DeltaCurr::ParamValues
```

#### 19.32.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> PostsynapticModels::DeltaCurr::PostVarValues
```

#### 19.32.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> PostsynapticModels::DeltaCurr::PreVarValues
```

#### 19.32.2.4 VarValues

```
typedef Models::VarInitContainerBase< 0 > PostsynapticModels::DeltaCurr::VarValues
```

### 19.32.3 Member Function Documentation

#### 19.32.3.1 getApplyInputCode()

```
virtual std::string PostsynapticModels::DeltaCurr::getApplyInputCode ( ) const [inline],  
[override], [virtual]
```

Reimplemented from [PostsynapticModels::Base](#).

#### 19.32.3.2 getInstance()

```
static const DeltaCurr* PostsynapticModels::DeltaCurr::getInstance ( ) [inline], [static]
```

The documentation for this class was generated from the following file:

- [postsynapticModels.h](#)

### 19.33 Snippet::Base::DerivedParam Struct Reference

A derived parameter has a name and a function for obtaining its value.

```
#include <snippet.h>
```

#### Public Attributes

- std::string [name](#)
- std::function< double(const std::vector< double > &, double)> [func](#)

#### 19.33.1 Detailed Description

A derived parameter has a name and a function for obtaining its value.

### 19.33.2 Member Data Documentation

#### 19.33.2.1 func

```
std::function<double(const std::vector<double> &, double)> Snippet::Base::DerivedParam::func
```

#### 19.33.2.2 name

```
std::string Snippet::Base::DerivedParam::name
```

The documentation for this struct was generated from the following file:

- [snippet.h](#)

### 19.34 Snippet::Base::EGP Struct Reference

An extra global parameter has a name and a type.

```
#include <snippet.h>
```

#### Public Attributes

- std::string [name](#)
- std::string [type](#)

#### 19.34.1 Detailed Description

An extra global parameter has a name and a type.

### 19.34.2 Member Data Documentation

#### 19.34.2.1 name

```
std::string Snippet::Base::EGP::name
```

#### 19.34.2.2 type

```
std::string Snippet::Base::EGP::type
```


The documentation for this struct was generated from the following file:

- [snippet.h](#)

### 19.35 SpineMLSimulator::LogOutput::Event Class Reference

```
#include <logOutput.h>
```

Inheritance diagram for SpineMLSimulator::LogOutput::Event:



### Public Member Functions

- [Event](#) (const pugi::xml\_node &node, double dt, unsigned long long numTimeSteps, const std::string &port, unsigned int popSize, const filesystem::path &logPath, unsigned int \*spikeQueuePtr, unsigned int \*hostSpikeCount, unsigned int \*hostSpikes, void(\*pullCurrentSpikesFunc)(void))
- virtual void [record](#) (double dt, unsigned long long timestep) override

### Additional Inherited Members

#### 19.35.1 Constructor & Destructor Documentation

##### 19.35.1.1 Event()

```

SpineMLSimulator::LogOutput::Event::Event (
    const pugi::xml_node & node,
    double dt,
    unsigned long long numTimeSteps,
    const std::string & port,
    unsigned int popSize,
    const filesystem::path & logPath,
    unsigned int * spikeQueuePtr,
    unsigned int * hostSpikeCount,
    unsigned int * hostSpikes,
    void(*) (void) pullCurrentSpikesFunc )

```

#### 19.35.2 Member Function Documentation

##### 19.35.2.1 record()

```

void SpineMLSimulator::LogOutput::Event::record (
    double dt,
    unsigned long long timestep ) [override], [virtual]

```

Implements [SpineMLSimulator::LogOutput::Base](#).

The documentation for this class was generated from the following files:


- [logOutput.h](#)
- [logOutput.cc](#)

## 19.36 PostsynapticModels::ExpCond Class Reference

Exponential decay with synaptic input treated as a conductance value.

```
#include <postsynapticModels.h>
```

Inheritance diagram for PostsynapticModels::ExpCond:



### Public Types

- typedef [Snippet::ValueBase](#)< 2 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

### Public Member Functions

- virtual std::string [getDecayCode](#) () const override
- virtual std::string [getApplyInputCode](#) () const override
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [DerivedParamVec](#) [getDerivedParams](#) () const override

### Static Public Member Functions

- static const [ExpCond](#) \* [getInstance](#) ()

### Additional Inherited Members

#### 19.36.1 Detailed Description

Exponential decay with synaptic input treated as a conductance value.

This model has no variables and two parameters:

- $\tau$  : Decay time constant
- $E$  : Reversal potential

$\tau$  is used by the derived parameter `expdecay` which returns  $\exp(-dt/\tau)$ .

#### 19.36.2 Member Typedef Documentation

##### 19.36.2.1 ParamValues

```
typedef Snippet::ValueBase< 2 > PostsynapticModels::ExpCond::ParamValues
```

### 19.36.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> PostsynapticModels::ExpCond::PostVarValues
```

### 19.36.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> PostsynapticModels::ExpCond::PreVarValues
```

### 19.36.2.4 VarValues

```
typedef Models::VarInitContainerBase< 0 > PostsynapticModels::ExpCond::VarValues
```

## 19.36.3 Member Function Documentation

### 19.36.3.1 getApplyInputCode()

```
virtual std::string PostsynapticModels::ExpCond::getApplyInputCode ( ) const [inline], [override], [virtual]
```

Reimplemented from [PostsynapticModels::Base](#).

### 19.36.3.2 getDecayCode()

```
virtual std::string PostsynapticModels::ExpCond::getDecayCode ( ) const [inline], [override], [virtual]
```

Reimplemented from [PostsynapticModels::Base](#).

### 19.36.3.3 getDerivedParams()

```
virtual DerivedParamVec PostsynapticModels::ExpCond::getDerivedParams ( ) const [inline], [override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented from [Snippet::Base](#).

### 19.36.3.4 getInstance()

```
static const ExpCond* PostsynapticModels::ExpCond::getInstance ( ) [inline], [static]
```

### 19.36.3.5 getParamNames()

```
virtual StringVec PostsynapticModels::ExpCond::getParamNames ( ) const [inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

The documentation for this class was generated from the following file:


- [postsynapticModels.h](#)

### 19.37 PostsynapticModels::ExpCurr Class Reference

Exponential decay with synaptic input treated as a current value.

```
#include <postsynapticModels.h>
```

Inheritance diagram for PostsynapticModels::ExpCurr:



#### Public Types

- typedef [Snippet::ValueBase](#)< 1 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

#### Public Member Functions

- virtual std::string [getDecayCode](#) () const override
- virtual std::string [getApplyInputCode](#) () const override
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of (independent) model parameters.*
- virtual [DerivedParamVec](#) [getDerivedParams](#) () const override

#### Static Public Member Functions

- static const [ExpCurr](#) \* [getInstance](#) ()

#### Additional Inherited Members

##### 19.37.1 Detailed Description

Exponential decay with synaptic input treated as a current value.

##### 19.37.2 Member Typedef Documentation

###### 19.37.2.1 ParamValues

```
typedef Snippet::ValueBase< 1 > PostsynapticModels::ExpCurr::ParamValues
```

### 19.37.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> PostsynapticModels::ExpCurr::PostVarValues
```

### 19.37.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> PostsynapticModels::ExpCurr::PreVarValues
```

### 19.37.2.4 VarValues

```
typedef Models::VarInitContainerBase< 0 > PostsynapticModels::ExpCurr::VarValues
```

## 19.37.3 Member Function Documentation

### 19.37.3.1 getApplyInputCode()

```
virtual std::string PostsynapticModels::ExpCurr::getApplyInputCode ( ) const [inline], [override], [virtual]
```

Reimplemented from [PostsynapticModels::Base](#).

### 19.37.3.2 getDecayCode()

```
virtual std::string PostsynapticModels::ExpCurr::getDecayCode ( ) const [inline], [override], [virtual]
```

Reimplemented from [PostsynapticModels::Base](#).

### 19.37.3.3 getDerivedParams()

```
virtual DerivedParamVec PostsynapticModels::ExpCurr::getDerivedParams ( ) const [inline], [override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented from [Snippet::Base](#).

### 19.37.3.4 getInstance()

```
static const ExpCurr* PostsynapticModels::ExpCurr::getInstance ( ) [inline], [static]
```

### 19.37.3.5 getParamNames()

```
virtual StringVec PostsynapticModels::ExpCurr::getParamNames ( ) const [inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

The documentation for this class was generated from the following file:


- [postsynapticModels.h](#)

### 19.38 InitVarSnippet::Exponential Class Reference

Initialises variable by sampling from the exponential distribution.

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Exponential:



#### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitVarSnippet::Exponential](#), 1)
- [SET\\_CODE](#) ("\$(value) = \$(lambda) \* \$(gennrand\_exponential);")
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*

#### Additional Inherited Members

##### 19.38.1 Detailed Description

Initialises variable by sampling from the exponential distribution.

This snippet takes 1 parameter:

- `lambda` - mean event rate (events per unit time/distance)

##### 19.38.2 Member Function Documentation

###### 19.38.2.1 DECLARE\_SNIPPET()

```
InitVarSnippet::Exponential::DECLARE_SNIPPET (
    InitVarSnippet::Exponential ,
    1 )
```

###### 19.38.2.2 getParamNames()

```
virtual StringVec InitVarSnippet::Exponential::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).



## 19.38.2.3 SET\_CODE()

```
InitVarSnippet::Exponential::SET_CODE ( )
```


The documentation for this class was generated from the following file:

- [initVarSnippet.h](#)

## 19.39 SpineMLSimulator::ModelProperty::ExponentialDistribution Class Reference

```
#include <modelProperty.h>
```

Inheritance diagram for SpineMLSimulator::ModelProperty::ExponentialDistribution:



## Public Member Functions

- [ExponentialDistribution](#) (const pugi::xml\_node &node, const [StateVar](#)< [scalar](#) > &stateVar, unsigned int size)
- void [setValue](#) ([scalar](#) lambda)

## 19.39.1 Constructor &amp; Destructor Documentation

## 19.39.1.1 ExponentialDistribution()

```
SpineMLSimulator::ModelProperty::ExponentialDistribution::ExponentialDistribution (
    const pugi::xml_node & node,
    const StateVar< scalar > & stateVar,
    unsigned int size )
```

## 19.39.2 Member Function Documentation

## 19.39.2.1 setValue()

```
void SpineMLSimulator::ModelProperty::ExponentialDistribution::setValue (
    scalar lambda )
```


The documentation for this class was generated from the following files:

- [modelProperty.h](#)
- [modelProperty.cc](#)

## 19.40 SpineMLSimulator::InputValue::External Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::External:



### Public Member Functions

- [External](#) (double dt, unsigned int numNeurons, const pugi::xml\_node &node)
- virtual void [update](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc) final
- std::vector< double >::iterator [getBufferBegin](#) ()
- std::vector< double >::iterator [getBufferEnd](#) ()

### Protected Member Functions

- virtual void [updateInternal](#) ()
- unsigned int [getSize](#) () const
- std::vector< double > & [getBuffer](#) ()

## 19.40.1 Constructor & Destructor Documentation

### 19.40.1.1 External()

```

SpineMLSimulator::InputValue::External::External (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node )
  
```

## 19.40.2 Member Function Documentation

### 19.40.2.1 getBuffer()

```

std::vector<double>& SpineMLSimulator::InputValue::External::getBuffer ( ) [inline], [protected]
  
```

### 19.40.2.2 getBufferBegin()

```

std::vector<double>::iterator SpineMLSimulator::InputValue::External::getBufferBegin ( ) [inline]
  
```

### 19.40.2.3 getBufferEnd()

```

std::vector<double>::iterator SpineMLSimulator::InputValue::External::getBufferEnd ( ) [inline]
  
```

## 19.40.2.4 getSize()

```
unsigned int SpineMLSimulator::InputValue::External::getSize ( ) const [inline], [protected]
```

## 19.40.2.5 update()

```
void SpineMLSimulator::InputValue::External::update (
    double dt,
    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) [final], [virtual]
```

Implements [SpineMLSimulator::InputValue::Base](#).

## 19.40.2.6 updateInternal()

```
virtual void SpineMLSimulator::InputValue::External::updateInternal ( ) [inline], [protected],
[virtual]
```

Reimplemented in [SpineMLSimulator::InputValue::ExternalNetwork](#).


The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

## 19.41 SpineMLSimulator::InputValue::ExternalNetwork Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::ExternalNetwork:



## Public Member Functions

- [ExternalNetwork](#) (double dt, unsigned int numNeurons, const pugi::xml\_node &node)

## Protected Member Functions

- virtual void [updateInternal](#) () override

## 19.41.1 Constructor &amp; Destructor Documentation

### 19.41.1.1 ExternalNetwork()

```
SpineMLSimulator::InputValue::ExternalNetwork::ExternalNetwork (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node )
```

## 19.41.2 Member Function Documentation

### 19.41.2.1 updateInternal()

```
void SpineMLSimulator::InputValue::ExternalNetwork::updateInternal ( ) [override], [protected],
[virtual]
```

Reimplemented from [SpineMLSimulator::InputValue::External](#).


The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

## 19.42 pygenn.model\_preprocessor.ExtraGlobalVariable Class Reference

Class holding information about GeNN extra global pointer variable.

Inheritance diagram for pygenn.model\_preprocessor.ExtraGlobalVariable:



### Public Member Functions

- def [\\_\\_init\\_\\_](#) (self, variable\_name, variable\_type, [values](#)=None)  
*Init [Variable](#).*
- def [set\\_values](#) (self, [values](#))  
*Set [Variable](#)'s values.*

### Public Attributes

- [is\\_scalar](#)
- [type](#)
- [name](#)
- [view](#)
- [values](#)

### 19.42.1 Detailed Description

Class holding information about GeNN extra global pointer variable.

## 19.42.2 Constructor & Destructor Documentation

### 19.42.2.1 \_\_init\_\_()

```
def pygenn.model_preprocessor.ExtraGlobalVariable.__init__ (
    self,
    variable_name,
    variable_type,
    values = None )
```

Init [Variable](#).

#### Parameters

<i>variable_name</i>	string name of the variable
<i>variable_type</i>	string type of the variable
<i>values</i>	iterable

## 19.42.3 Member Function Documentation

### 19.42.3.1 set\_values()

```
def pygenn.model_preprocessor.ExtraGlobalVariable.set_values (
    self,
    values )
```

Set [Variable](#)'s values.

#### Parameters

<i>values</i>	iterable or single value
---------------	--------------------------

## 19.42.4 Member Data Documentation

### 19.42.4.1 is\_scalar

`pygenn.model_preprocessor.ExtraGlobalVariable.is_scalar`

### 19.42.4.2 name

`pygenn.model_preprocessor.ExtraGlobalVariable.name`

### 19.42.4.3 type

`pygenn.model_preprocessor.ExtraGlobalVariable.type`

#### 19.42.4.4 values

`pygenn.model_preprocessor.ExtraGlobalVariable.values`

#### 19.42.4.5 view

`pygenn.model_preprocessor.ExtraGlobalVariable.view`


The documentation for this class was generated from the following file:

- [model\\_preprocessor.py](#)

### 19.43 SpineMLSimulator::ModelProperty::Fixed Class Reference

```
#include <modelProperty.h>
```

Inheritance diagram for SpineMLSimulator::ModelProperty::Fixed:



#### Public Member Functions

- [Fixed](#) (const `pugi::xml_node` &`node`, const [StateVar](#)< [scalar](#) > &`stateVar`, unsigned int `size`)
- [Fixed](#) (double `value`, const [StateVar](#)< [scalar](#) > &`stateVar`, unsigned int `size`)
- void [setValue](#) ([scalar](#) `value`)

#### 19.43.1 Constructor & Destructor Documentation

##### 19.43.1.1 Fixed() [1/2]

```
SpineMLSimulator::ModelProperty::Fixed::Fixed (
    const pugi::xml_node & node,
    const StateVar< scalar > & stateVar,
    unsigned int size )
```

##### 19.43.1.2 Fixed() [2/2]

```
SpineMLSimulator::ModelProperty::Fixed::Fixed (
    double value,
    const StateVar< scalar > & stateVar,
    unsigned int size )
```

#### 19.43.2 Member Function Documentation

## 19.43.2.1 setValue()

```
void SpineMLSimulator::ModelProperty::Fixed::setValue (
    scalar value )
```


The documentation for this class was generated from the following files:

- [modelProperty.h](#)
- [modelProperty.cc](#)

## 19.44 InitSparseConnectivitySnippet::FixedProbability Class Reference

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::FixedProbability:



## Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitSparseConnectivitySnippet::FixedProbability](#), 1)
- [SET\\_ROW\\_BUILD\\_CODE](#) ("const scalar u = \$(gennrand\_uniform);\n "prevJ+=(1+(int)(log(u) \*\$(probLogRecip))));\n "if(prevJ< \$(num\_post)) {\n " \$(addSynapse, prevJ+\$(id\_post\_begin));\n "}" "else {\n " \$(endRow);\n "}")

## Additional Inherited Members

## 19.44.1 Detailed Description

Initialises connectivity with a fixed probability of a synapse existing between a pair of pre and postsynaptic neurons.

Whether a synapse exists between a pair of pre and a postsynaptic neurons can be modelled using a Bernoulli distribution. While this COULD be sampling directly by repeatedly drawing from the uniform distribution, this is inefficient. Instead we sample from the geometric distribution which describes "the probability distribution of the number of Bernoulli trials needed to get one success" – essentially the distribution of the 'gaps' between synapses. We do this using the "inversion method" described by Devroye (1986) – essentially inverting the CDF of the equivalent continuous distribution (in this case the exponential distribution)

## 19.44.2 Member Function Documentation

## 19.44.2.1 DECLARE\_SNIPPET()

```
InitSparseConnectivitySnippet::FixedProbability::DECLARE_SNIPPET (
    InitSparseConnectivitySnippet::FixedProbability ,
    1 )
```

### 19.44.2.2 SET\_ROW\_BUILD\_CODE()

```
InitSparseConnectivitySnippet::FixedProbability::SET_ROW_BUILD_CODE ( )
```


The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)

## 19.45 InitSparseConnectivitySnippet::FixedProbabilityBase Class Reference

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::FixedProbabilityBase:



### Public Member Functions

- virtual std::string [getRowBuildCode](#) () const override=0
- [SET\\_ROW\\_BUILD\\_STATE\\_VARS](#) ({{"prevJ", "int", -1}})
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [DerivedParamVec](#) [getDerivedParams](#) () const override
- [SET\\_CALC\\_MAX\\_ROW\\_LENGTH\\_FUNC](#) ([](unsigned int numPre, unsigned int numPost, const std::vector< double > &pars) { const double quantile=pow(0.9999, 1.0/(double) numPre);return [binomialInverseCDF](#)(quantile, numPost, pars[0]);})
- [SET\\_CALC\\_MAX\\_COL\\_LENGTH\\_FUNC](#) ([](unsigned int numPre, unsigned int numPost, const std::vector< double > &pars) { const double quantile=pow(0.9999, 1.0/(double) numPost);return [binomialInverseCDF](#)(quantile, numPre, pars[0]);})

### Additional Inherited Members

#### 19.45.1 Detailed Description

**Base** class for snippets which initialise connectivity with a fixed probability of a synapse existing between a pair of pre and postsynaptic neurons.

#### 19.45.2 Member Function Documentation

##### 19.45.2.1 getDerivedParams()

```
virtual DerivedParamVec InitSparseConnectivitySnippet::FixedProbabilityBase::getDerivedParams  
( ) const [inline], [override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values



Reimplemented from [Snippet::Base](#).

#### 19.45.2.2 getParamNames()

```
virtual StringVec InitSparseConnectivitySnippet::FixedProbabilityBase::getParamNames ( ) const
[inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

#### 19.45.2.3 getRowBuildCode()

```
virtual std::string InitSparseConnectivitySnippet::FixedProbabilityBase::getRowBuildCode ( )
const [override], [pure virtual]
```

Reimplemented from [InitSparseConnectivitySnippet::Base](#).

#### 19.45.2.4 SET\_CALC\_MAX\_COL\_LENGTH\_FUNC()

```
InitSparseConnectivitySnippet::FixedProbabilityBase::SET_CALC_MAX_COL_LENGTH_FUNC (
    [] (unsigned int numPre, unsigned int numPost, const std::vector< double > &pars)
{ const double quantile=pow(0.9999, 1.0/(double) numPost);return binomialInverseCDF(quantile,
numPre, pars[0]);} )
```

#### 19.45.2.5 SET\_CALC\_MAX\_ROW\_LENGTH\_FUNC()

```
InitSparseConnectivitySnippet::FixedProbabilityBase::SET_CALC_MAX_ROW_LENGTH_FUNC (
    [] (unsigned int numPre, unsigned int numPost, const std::vector< double > &pars)
{ const double quantile=pow(0.9999, 1.0/(double) numPre);return binomialInverseCDF(quantile,
numPost, pars[0]);} )
```

#### 19.45.2.6 SET\_ROW\_BUILD\_STATE\_VARS()

```
InitSparseConnectivitySnippet::FixedProbabilityBase::SET_ROW_BUILD_STATE_VARS (
    {"prevJ", "int", -1} )
```


The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)

## 19.46 InitSparseConnectivitySnippet::FixedProbabilityNoAutapse Class Reference

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::FixedProbabilityNoAutapse:



## Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitSparseConnectivitySnippet::FixedProbabilityNoAutapse](#), 1)
- [SET\\_ROW\\_BUILD\\_CODE](#) ("int nextJ;\n"do {\n" const scalar u=\$(gennrand\_uniform);\n" nextJ=prevJ+(1+(int)(log(u)\*\$(probLogRecip)));\n" } while(nextJ==\$(id\_pre));\n" prevJ=nextJ;\n" if(prevJ< \$(num\_post)) {\n" " \$(add↵  
Synapse, prevJ+\$(id\_post\_begin));\n" }\n" else {\n" " \$(endRow);\n" }\n")

## Additional Inherited Members

### 19.46.1 Detailed Description

Initialises connectivity with a fixed probability of a synapse existing between a pair of pre and postsynaptic neurons. This version ensures there are no autapses - connections between neurons with the same id so should be used for recurrent connections.

Whether a synapse exists between a pair of pre and a postsynaptic neurons can be modelled using a Bernoulli distribution. While this COULD be sampling directly by repeatedly drawing from the uniform distribution, this is inefficient. Instead we sample from the geometric distribution which describes "the probability distribution of the number of Bernoulli trials needed to get one success" – essentially the distribution of the 'gaps' between synapses. We do this using the "inversion method" described by Devroye (1986) – essentially inverting the CDF of the equivalent continuous distribution (in this case the exponential distribution)

### 19.46.2 Member Function Documentation

#### 19.46.2.1 DECLARE\_SNIPPET()

```
InitSparseConnectivitySnippet::FixedProbabilityNoAutapse::DECLARE_SNIPPET (
    InitSparseConnectivitySnippet::FixedProbabilityNoAutapse ,
    1 )
```

#### 19.46.2.2 SET\_ROW\_BUILD\_CODE()

```
InitSparseConnectivitySnippet::FixedProbabilityNoAutapse::SET_ROW_BUILD_CODE ( )
```

The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)

## 19.47 CodeGenerator::FunctionTemplate Struct Reference

```
#include <codeGenUtils.h>
```

## Public Member Functions

- [FunctionTemplate operator=](#) (const [FunctionTemplate](#) &o)

## Public Attributes

- const std::string [genericName](#)  
*Generic name used to refer to function in user code.*
- const unsigned int [numArguments](#)  
*Number of function arguments.*
- const std::string [doublePrecisionTemplate](#)  
*The function template (for use with [functionSubstitute](#)) used when model uses double precision.*
- const std::string [singlePrecisionTemplate](#)  
*The function template (for use with [functionSubstitute](#)) used when model uses single precision.*

## 19.47.1 Detailed Description

Immutable structure for specifying how to implement a generic function e.g. gennrand\_uniform

**NOTE** for the sake of easy initialisation first two parameters of GenericFunction are repeated (C++17 fixes)

## 19.47.2 Member Function Documentation

## 19.47.2.1 operator=()

```
FunctionTemplate CodeGenerator::FunctionTemplate::operator= (
    const FunctionTemplate & o ) [inline]
```

## 19.47.3 Member Data Documentation

## 19.47.3.1 doublePrecisionTemplate

```
const std::string CodeGenerator::FunctionTemplate::doublePrecisionTemplate
```

The function template (for use with [functionSubstitute](#)) used when model uses double precision.

## 19.47.3.2 genericName

```
const std::string CodeGenerator::FunctionTemplate::genericName
```

Generic name used to refer to function in user code.

## 19.47.3.3 numArguments

```
const unsigned int CodeGenerator::FunctionTemplate::numArguments
```

Number of function arguments.

### 19.47.3.4 singlePrecisionTemplate

```
const std::string CodeGenerator::FunctionTemplate::singlePrecisionTemplate
```

The function template (for use with [functionSubstitute](#)) used when model uses single precision.

The documentation for this struct was generated from the following file:


- [codeGenUtils.h](#)

## 19.48 InitVarSnippet::Gamma Class Reference

Initialises variable by sampling from the exponential distribution.

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Gamma:



### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitVarSnippet::Gamma](#), 2)
- [SET\\_CODE](#) ("\$(value) = \$(b) \* \$(gennrand\_gamma, \$(a));")
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*

### Additional Inherited Members

#### 19.48.1 Detailed Description

Initialises variable by sampling from the exponential distribution.

This snippet takes 1 parameter:

- `lambda` - mean event rate (events per unit time/distance)

#### 19.48.2 Member Function Documentation

##### 19.48.2.1 DECLARE\_SNIPPET()

```
InitVarSnippet::Gamma::DECLARE_SNIPPET (
    InitVarSnippet::Gamma ,
    2 )
```

## 19.48.2.2 getParamNames()

```
virtual StringVec InitVarSnippet::Gamma::getParamNames ( ) const \[inline\], \[override\], \[virtual\]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

## 19.48.2.3 SET\_CODE()

```
InitVarSnippet::Gamma::SET_CODE ( )
```

The documentation for this class was generated from the following file:


- [initVarSnippet.h](#)

## 19.49 CurrentSourceModels::GaussianNoise Class Reference

Noisy current source with noise drawn from normal distribution.

```
#include <currentSourceModels.h>
```

Inheritance diagram for CurrentSourceModels::GaussianNoise:



## Public Types

- typedef [Snippet::ValueBase](#)< 2 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- [SET\\_INJECTION\\_CODE](#) ("\$(injectCurrent, \$(mean) + \$(gennrand\_normal) \* \$(sd));\n")
- virtual [StringVec](#) [getParamNames](#) ( ) const override

*Gets names of of (independent) model parameters.*

## Static Public Member Functions

- static const [GaussianNoise](#) \* [getInstance](#) ( )

## Additional Inherited Members

### 19.49.1 Detailed Description

Noisy current source with noise drawn from normal distribution.

It has 2 parameters:

- `mean` - mean of the normal distribution [nA]
- `sd` - standard deviation of the normal distribution [nA]

### 19.49.2 Member Typedef Documentation

#### 19.49.2.1 ParamValues

```
typedef Snippet::ValueBase< 2 > CurrentSourceModels::GaussianNoise::ParamValues
```

#### 19.49.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> CurrentSourceModels::GaussianNoise::PostVarValues
```

#### 19.49.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> CurrentSourceModels::GaussianNoise::PreVarValues
```

#### 19.49.2.4 VarValues

```
typedef Models::VarInitContainerBase< 0 > CurrentSourceModels::GaussianNoise::VarValues
```

### 19.49.3 Member Function Documentation

#### 19.49.3.1 getInstance()

```
static const GaussianNoise\* CurrentSourceModels::GaussianNoise::getInstance ( ) [inline],  
[static]
```

#### 19.49.3.2 getParamNames()

```
virtual StringVec CurrentSourceModels::GaussianNoise::getParamNames ( ) const [inline], [override],  
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

#### 19.49.3.3 SET\_INJECTION\_CODE()

```
CurrentSourceModels::GaussianNoise::SET\_INJECTION\_CODE (
```

```
"$(injectCurrent, $(mean) + $(gennrand_normal) * $(sd));\  )
```

The documentation for this class was generated from the following file:

- [currentSourceModels.h](#)

## 19.50 GenerateRunBase Class Reference

```
#include <generateRun.h>
```

### Public Member Functions

- [GenerateRunBase](#) (const std::string &projectName)
- virtual void [writeSizes](#) (std::ofstream &sizes) const
- int [getExitCode](#) (const CLI::ParseError &e)
- void [parseCommandLine](#) (int argc, char \*\*argv)
- int [buildAndRun](#) (std::initializer\_list< std::string > runParams={}) const

### Protected Member Functions

- virtual int [runTools](#) () const
- CLI::App & [getApp](#) ()
- std::string [getOutDir](#) () const
- const std::string & [getExperimentName](#) () const

## 19.50.1 Constructor & Destructor Documentation

### 19.50.1.1 GenerateRunBase()

```
GenerateRunBase::GenerateRunBase (
    const std::string & projectName ) [inline]
```

## 19.50.2 Member Function Documentation

### 19.50.2.1 buildAndRun()

```
int GenerateRunBase::buildAndRun (
    std::initializer_list< std::string > runParams = {} ) const [inline]
```

### 19.50.2.2 getApp()

```
CLI::App& GenerateRunBase::getApp ( ) [inline], [protected]
```

### 19.50.2.3 getExitCode()

```
int GenerateRunBase::getExitCode (
    const CLI::ParseError & e ) [inline]
```

#### 19.50.2.4 `getExperimentName()`

```
const std::string& GenerateRunBase::getExperimentName ( ) const [inline], [protected]
```

#### 19.50.2.5 `getOutDir()`

```
std::string GenerateRunBase::getOutDir ( ) const [inline], [protected]
```

#### 19.50.2.6 `parseCommandLine()`

```
void GenerateRunBase::parseCommandLine (
    int argc,
    char ** argv ) [inline]
```

#### 19.50.2.7 `runTools()`

```
virtual int GenerateRunBase::runTools ( ) const [inline], [protected], [virtual]
```

#### 19.50.2.8 `writeSizes()`

```
virtual void GenerateRunBase::writeSizes (
    std::ofstream & sizes ) const [inline], [virtual]
```


The documentation for this class was generated from the following file:

- [generateRun.h](#)

### 19.51 `pygenn.genn_model.GeNNModel` Class Reference

**`GeNNModel`** class This class helps to define, build and run a GeNN model from python.

Inheritance diagram for `pygenn.genn_model.GeNNModel`:



#### Public Member Functions

- `def __init__ (self, precision=None, model\_name="GeNNModel", backend=None, genn_log_level=genn_wrapper.warning, code_gen_log_level=genn_wrapper.warning, backend\_log\_level=genn_wrapper.warning, preference_kwargs)`

*Init `GeNNModel`.*

- `def use\_backend (self)`
- `def use\_backend (self, backend)`
- `def timing\_enabled (self)`
- `def timing\_enabled (self, timing)`
- `def default\_var\_location (self)`

*Default variable location - defines where state variables are initialised.*



- def [default\\_var\\_location](#) (self, location)
- def [default\\_sparse\\_connectivity\\_location](#) (location)  
*Default sparse connectivity mode - where connectivity is initialised.*
- def [default\\_sparse\\_connectivity\\_location](#) (self, location)
- def [model\\_name](#) (self)  
*Name of the model.*
- def [model\\_name](#) (self, model\_name)
- def [t](#) (self)  
*Simulation time in ms.*
- def [t](#) (self, t)
- def [timestep](#) (self)  
*Simulation time step.*
- def [timestep](#) (self, timestep)
- def [free\\_device\\_mem\\_bytes](#) (self)
- def [dT](#) (self)  
*Step size.*
- def [dT](#) (self, dt)
- def [neuron\\_update\\_time](#) (self)
- def [init\\_time](#) (self)
- def [presynaptic\\_update\\_time](#) (self)
- def [postsynaptic\\_update\\_time](#) (self)
- def [synapse\\_dynamics\\_time](#) (self)
- def [init\\_sparse\\_time](#) (self)
- def [add\\_neuron\\_population](#) (self, pop\_name, num\_neurons, neuron, param\_space, var\_space)  
*Add a neuron population to the GeNN model.*
- def [add\\_synapse\\_population](#) (self, pop\_name, matrix\_type, delay\_steps, source, target, w\_update\_model, wu\_param\_space, wu\_var\_space, wu\_pre\_var\_space, wu\_post\_var\_space, postsyn\_model, ps\_param\_space, ps\_var\_space, connectivity\_initialiser=None)  
*Add a synapse population to the GeNN model.*
- def [add\\_current\\_source](#) (self, cs\_name, current\_source\_model, pop\_name, param\_space, var\_space)  
*Add a current source to the GeNN model.*
- def [build](#) (self, path\_to\_model=".")  
*Finalize and build a GeNN model.*
- def [load](#) (self)  
*import the model as shared library and initialize it*
- def [reinitialise](#) (self)  
*reinitialise model to its original state without re-loading*
- def [step\\_time](#) (self)
- def [pull\\_state\\_from\\_device](#) (self, pop\_name)  
*Pull state from the device for a given population.*
- def [pull\\_spikes\\_from\\_device](#) (self, pop\_name)  
*Pull spikes from the device for a given population.*
- def [pull\\_current\\_spikes\\_from\\_device](#) (self, pop\_name)  
*Pull spikes from the device for a given population.*
- def [pull\\_connectivity\\_from\\_device](#) (self, pop\_name)  
*Pull connectivity from the device for a given population.*
- def [pull\\_var\\_from\\_device](#) (self, pop\_name, var\_name)  
*Pull variable from the device for a given population.*
- def [push\\_state\\_to\\_device](#) (self, pop\_name)  
*Push state to the device for a given population.*
- def [push\\_spikes\\_to\\_device](#) (self, pop\_name)  
*Push spikes to the device for a given population.*

- def `push_current_spikes_to_device` (self, pop\_name)  
*Push current spikes to the device for a given population.*
- def `push_connectivity_to_device` (self, pop\_name)  
*Push connectivity to the device for a given population.*
- def `push_var_to_device` (self, pop\_name, var\_name)  
*Push variable to the device for a given population.*
- def `end` (self)  
*Free memory.*

#### Public Attributes

- `use_backend`
- `backend_log_level`
- `default_var_location`
- `model_name`
- `neuron_populations`
- `synapse_populations`
- `current_sources`
- `dT`

#### 19.51.1 Detailed Description

`GeNNModel` class This class helps to define, build and run a GeNN model from python.

#### 19.51.2 Constructor & Destructor Documentation

##### 19.51.2.1 `__init__()`

```
def pygenn.genn_model.GeNNModel.__init__ (
    self,
    precision = None,
    model_name = "GeNNModel",
    backend = None,
    genn_log_level = genn_wrapper.warning,
    code_gen_log_level = genn_wrapper.warning,
    backend_log_level = genn_wrapper.warning,
    preference_kwargs )
```

Init `GeNNModel`.

#### Parameters

<i>precision</i>	string precision as string ("float", "double" or "long double"). defaults to float.
<i>model_name</i>	string name of the model. Defaults to "GeNNModel".
<i>backend</i>	string specifying name of backend module to use Defaults to None to pick 'best' backend for your system
<i>selected_gpu</i>	integer specifying the id of the gpu in which the simulator wil run; None will select automatically

#### 19.51.3 Member Function Documentation

## 19.51.3.1 add\_current\_source()

```
def pygenn.genn_model.GeNNModel.add_current_source (
    self,
    cs_name,
    current_source_model,
    pop_name,
    param_space,
    var_space )
```

Add a current source to the GeNN model.

## Parameters

<i>cs_name</i>	name of the new current source
<i>current_source_model</i>	type of the <a href="#">CurrentSourceModels</a> class as string or instance of <a href="#">CurrentSourceModels</a> class derived from <code>pygenn.genn_wrapper.CurrentSourceModels.Custom</code> (see also <a href="#">pygenn.genn_model.create_custom_current_source_class</a> )
<i>pop_name</i>	name of the population into which the current source should be injected
<i>param_space</i>	dict with param values for the <a href="#">CurrentSourceModels</a> class
<i>var_space</i>	dict with initial variable values for the <a href="#">CurrentSourceModels</a> class

## 19.51.3.2 add\_neuron\_population()

```
def pygenn.genn_model.GeNNModel.add_neuron_population (
    self,
    pop_name,
    num_neurons,
    neuron,
    param_space,
    var_space )
```

Add a neuron population to the GeNN model.

## Parameters

<i>pop_name</i>	name of the new population
<i>num_neurons</i>	number of neurons in the new population
<i>neuron</i>	type of the <a href="#">NeuronModels</a> class as string or instance of neuron class derived from <code>pygenn.genn_wrapper.NeuronModels.Custom</code> (see also <a href="#">pygenn.genn_model.create_custom_neuron_class</a> )
<i>param_space</i>	dict with param values for the <a href="#">NeuronModels</a> class
<i>var_space</i>	dict with initial variable values for the <a href="#">NeuronModels</a> class

## 19.51.3.3 add\_synapse\_population()

```
def pygenn.genn_model.GeNNModel.add_synapse_population (
    self,
    pop_name,
    matrix_type,
    delay_steps,
    source,
```

```

    target,
    w_update_model,
    wu_param_space,
    wu_var_space,
    wu_pre_var_space,
    wu_post_var_space,
    postsyn_model,
    ps_param_space,
    ps_var_space,
    connectivity_initializer = None )

```

Add a synapse population to the GeNN model.

#### Parameters

<i>pop_name</i>	name of the new population
<i>matrix_type</i>	type of the matrix as string
<i>delay_steps</i>	delay in number of steps
<i>source</i>	source neuron group
<i>target</i>	target neuron group
<i>w_update_model</i>	type of the <a href="#">WeightUpdateModels</a> class as string or instance of weight update model class derived from <code>pygenn.genn_wrapper.WeightUpdateModels.Custom</code> (see also <a href="#">pygenn.genn_model.create_custom_weight_update_class</a> )
<i>wu_param_space</i>	dict with param values for the <a href="#">WeightUpdateModels</a> class
<i>wu_var_space</i>	dict with initial values for <a href="#">WeightUpdateModels</a> state variables
<i>wu_pre_var_space</i>	dict with initial values for <a href="#">WeightUpdateModels</a> presynaptic variables
<i>wu_post_var_space</i>	dict with initial values for <a href="#">WeightUpdateModels</a> postsynaptic variables
<i>postsyn_model</i>	type of the <a href="#">PostsynapticModels</a> class as string or instance of postsynaptic model class derived from <code>pygenn.genn_wrapper.PostsynapticModels.Custom</code> (see also <a href="#">pygenn.genn_model.create_custom_postsynaptic_class</a> )
<i>ps_param_space</i>	dict with param values for the <a href="#">PostsynapticModels</a> class
<i>ps_var_space</i>	dict with initial variable values for the <a href="#">PostsynapticModels</a> class
<i>connectivity_initializer</i>	<a href="#">InitSparseConnectivitySnippet::Init</a> for connectivity

#### 19.51.3.4 build()

```

def pygenn.genn_model.GeNNModel.build (
    self,
    path_to_model = "/" )

```

Finalize and build a GeNN model.

#### Parameters

<i>path_to_model</i>	path where to place the generated model code. Defaults to the local directory.
----------------------	--

#### 19.51.3.5 default\_sparse\_connectivity\_location() [1/2]

```

def pygenn.genn_model.GeNNModel.default_sparse_connectivity_location (
    location )

```

Default sparse connectivity mode - where connectivity is initialised.

#### 19.51.3.6 default\_sparse\_connectivity\_location() [2/2]

```
def pygenn.genn_model.GeNNModel.default_sparse_connectivity_location (
    self,
    location )
```

#### 19.51.3.7 default\_var\_location() [1/2]

```
def pygenn.genn_model.GeNNModel.default_var_location (
    self )
```

Default variable location - defines where state variables are initialised.

#### 19.51.3.8 default\_var\_location() [2/2]

```
def pygenn.genn_model.GeNNModel.default_var_location (
    self,
    location )
```

#### 19.51.3.9 dT() [1/2]

```
def pygenn.genn_model.GeNNModel.dT (
    self )
```

Step size.

#### 19.51.3.10 dT() [2/2]

```
def pygenn.genn_model.GeNNModel.dT (
    self,
    dt )
```

#### 19.51.3.11 end()

```
def pygenn.genn_model.GeNNModel.end (
    self )
```

Free memory.

#### 19.51.3.12 free\_device\_mem\_bytes()

```
def pygenn.genn_model.GeNNModel.free_device_mem_bytes (
    self )
```

#### 19.51.3.13 init\_sparse\_time()

```
def pygenn.genn_model.GeNNModel.init_sparse_time (
    self )
```

**19.51.3.14 init\_time()**

```
def pygenn.genn_model.GeNNModel.init_time (
    self )
```

**19.51.3.15 load()**

```
def pygenn.genn_model.GeNNModel.load (
    self )
```

import the model as shared library and initialize it

**19.51.3.16 model\_name()** [1/2]

```
def pygenn.genn_model.GeNNModel.model_name (
    self )
```

Name of the model.

**19.51.3.17 model\_name()** [2/2]

```
def pygenn.genn_model.GeNNModel.model_name (
    self,
    model_name )
```

**19.51.3.18 neuron\_update\_time()**

```
def pygenn.genn_model.GeNNModel.neuron_update_time (
    self )
```

**19.51.3.19 postsynaptic\_update\_time()**

```
def pygenn.genn_model.GeNNModel.postsynaptic_update_time (
    self )
```

**19.51.3.20 presynaptic\_update\_time()**

```
def pygenn.genn_model.GeNNModel.presynaptic_update_time (
    self )
```

**19.51.3.21 pull\_connectivity\_from\_device()**

```
def pygenn.genn_model.GeNNModel.pull_connectivity_from_device (
    self,
    pop_name )
```

Pull connectivity from the device for a given population.

**19.51.3.22 pull\_current\_spikes\_from\_device()**

```
def pygenn.genn_model.GeNNModel.pull_current_spikes_from_device (
    self,
    pop_name )
```

Pull spikes from the device for a given population.

**19.51.3.23 pull\_spikes\_from\_device()**

```
def pygenn.genn_model.GeNNModel.pull_spikes_from_device (
    self,
    pop_name )
```

Pull spikes from the device for a given population.

**19.51.3.24 pull\_state\_from\_device()**

```
def pygenn.genn_model.GeNNModel.pull_state_from_device (
    self,
    pop_name )
```

Pull state from the device for a given population.

**19.51.3.25 pull\_var\_from\_device()**

```
def pygenn.genn_model.GeNNModel.pull_var_from_device (
    self,
    pop_name,
    var_name )
```

Pull variable from the device for a given population.

**19.51.3.26 push\_connectivity\_to\_device()**

```
def pygenn.genn_model.GeNNModel.push_connectivity_to_device (
    self,
    pop_name )
```

Push connectivity to the device for a given population.

**19.51.3.27 push\_current\_spikes\_to\_device()**

```
def pygenn.genn_model.GeNNModel.push_current_spikes_to_device (
    self,
    pop_name )
```

Push current spikes to the device for a given population.

**19.51.3.28 push\_spikes\_to\_device()**

```
def pygenn.genn_model.GeNNModel.push_spikes_to_device (
    self,
    pop_name )
```

Push spikes to the device for a given population.

#### 19.51.3.29 `push_state_to_device()`

```
def pygenn.genn_model.GeNNModel.push_state_to_device (
    self,
    pop_name )
```

Push state to the device for a given population.

#### 19.51.3.30 `push_var_to_device()`

```
def pygenn.genn_model.GeNNModel.push_var_to_device (
    self,
    pop_name,
    var_name )
```

Push variable to the device for a given population.

#### 19.51.3.31 `reinitialise()`

```
def pygenn.genn_model.GeNNModel.reinitialise (
    self )
```

reinitialise model to its original state without re-loading

#### 19.51.3.32 `step_time()`

```
def pygenn.genn_model.GeNNModel.step_time (
    self )
```

#### 19.51.3.33 `synapse_dynamics_time()`

```
def pygenn.genn_model.GeNNModel.synapse_dynamics_time (
    self )
```

#### 19.51.3.34 `t()` [1/2]

```
def pygenn.genn_model.GeNNModel.t (
    self )
```

Simulation time in ms.

#### 19.51.3.35 `t()` [2/2]

```
def pygenn.genn_model.GeNNModel.t (
    self,
    t )
```



**19.51.3.36 timestep()** [1/2]

```
def pygenn.genn_model.GeNNModel.timestep (
    self )
```

Simulation time step.

**19.51.3.37 timestep()** [2/2]

```
def pygenn.genn_model.GeNNModel.timestep (
    self,
    timestep )
```

**19.51.3.38 timing\_enabled()** [1/2]

```
def pygenn.genn_model.GeNNModel.timing_enabled (
    self )
```

**19.51.3.39 timing\_enabled()** [2/2]

```
def pygenn.genn_model.GeNNModel.timing_enabled (
    self,
    timing )
```

**19.51.3.40 use\_backend()** [1/2]

```
def pygenn.genn_model.GeNNModel.use_backend (
    self )
```

**19.51.3.41 use\_backend()** [2/2]

```
def pygenn.genn_model.GeNNModel.use_backend (
    self,
    backend )
```

**19.51.4 Member Data Documentation****19.51.4.1 backend\_log\_level**

```
pygenn.genn_model.GeNNModel.backend_log_level
```

**19.51.4.2 current\_sources**

```
pygenn.genn_model.GeNNModel.current_sources
```

**19.51.4.3 default\_var\_location**

```
pygenn.genn_model.GeNNModel.default_var_location
```

#### 19.51.4.4 dT

```
pygenn.genn_model.GeNNModel.dT
```

#### 19.51.4.5 model\_name

```
pygenn.genn_model.GeNNModel.model_name
```

#### 19.51.4.6 neuron\_populations

```
pygenn.genn_model.GeNNModel.neuron_populations
```

#### 19.51.4.7 synapse\_populations

```
pygenn.genn_model.GeNNModel.synapse_populations
```

#### 19.51.4.8 use\_backend

```
pygenn.genn_model.GeNNModel.use_backend
```


The documentation for this class was generated from the following file:

- [genn\\_model.py](#)

## 19.52 pygenn.genn\_groups.Group Class Reference

Parent class of [NeuronGroup](#), [SynapseGroup](#) and [CurrentSource](#).

Inheritance diagram for pygenn.genn\_groups.Group:



### Public Member Functions

- def `__init__`(self, [name](#))  
*Init Group.*
- def `set_var`(self, var\_name, values)  
*Set values for a Variable.*

### Public Attributes

- [name](#)
- [vars](#)
- [extra\\_global\\_params](#)

### 19.52.1 Detailed Description

Parent class of [NeuronGroup](#), [SynapseGroup](#) and [CurrentSource](#).

### 19.52.2 Constructor & Destructor Documentation

#### 19.52.2.1 `__init__()`

```
def pygenn.genn_groups.Group.__init__ (
    self,
    name )
```

Init [Group](#).

#### Parameters

<i>name</i>	string name of the <a href="#">Group</a>
-------------	--

### 19.52.3 Member Function Documentation

#### 19.52.3.1 `set_var()`

```
def pygenn.genn_groups.Group.set_var (
    self,
    var_name,
    values )
```

Set values for a Variable.

#### Parameters

<i>var_name</i>	string with the name of the variable
<i>values</i>	iterable or a single value

### 19.52.4 Member Data Documentation

#### 19.52.4.1 `extra_global_params`

`pygenn.genn_groups.Group.extra_global_params`

#### 19.52.4.2 `name`

`pygenn.genn_groups.Group.name`

#### 19.52.4.3 `vars`

`pygenn.genn_groups.Group.vars`


The documentation for this class was generated from the following file:

- [genn\\_groups.py](#)

### 19.53 InitSparseConnectivitySnippet::Init Class Reference

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::Init:



#### Public Member Functions

- [Init](#) (const [Base](#) \*snippet, const std::vector< double > &params)

#### 19.53.1 Constructor & Destructor Documentation

##### 19.53.1.1 Init()

```
InitSparseConnectivitySnippet::Init::Init (
    const Base * snippet,
    const std::vector< double > & params ) [inline]
```

The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)

### 19.54 Snippet::Init< SnippetBase > Class Template Reference

```
#include <snippet.h>
```

#### Public Member Functions

- [Init](#) (const [SnippetBase](#) \*snippet, const std::vector< double > &params)
- const [SnippetBase](#) \* [getSnippet](#) () const
- const std::vector< double > & [getParams](#) () const
- const std::vector< double > & [getDerivedParams](#) () const
- void [initDerivedParams](#) (double dt)

#### 19.54.1 Detailed Description

```
template<typename SnippetBase>
class Snippet::Init< SnippetBase >
```

Class used to bind together everything required to utilize a snippet

1. A pointer to a variable initialisation snippet
2. The parameters required to control the variable initialisation snippet

## 19.54.2 Constructor & Destructor Documentation

### 19.54.2.1 Init()

```
template<typename SnippetBase>
Snippet::Init< SnippetBase >::Init (
    const SnippetBase * snippet,
    const std::vector< double > & params ) [inline]
```

## 19.54.3 Member Function Documentation

### 19.54.3.1 getDerivedParams()

```
template<typename SnippetBase>
const std::vector<double>& Snippet::Init< SnippetBase >::getDerivedParams ( ) const [inline]
```

### 19.54.3.2 getParams()

```
template<typename SnippetBase>
const std::vector<double>& Snippet::Init< SnippetBase >::getParams ( ) const [inline]
```

### 19.54.3.3 getSnippet()

```
template<typename SnippetBase>
const SnippetBase* Snippet::Init< SnippetBase >::getSnippet ( ) const [inline]
```

### 19.54.3.4 initDerivedParams()

```
template<typename SnippetBase>
void Snippet::Init< SnippetBase >::initDerivedParams (
    double dt ) [inline]
```


The documentation for this class was generated from the following file:

- [snippet.h](#)

## 19.55 SpineMLSimulator::Input::InterSpikeIntervalBase Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::InterSpikeIntervalBase:



## Public Member Functions

- virtual void [apply](#) (double dt, unsigned long long timestep) override

## Protected Member Functions

- [InterSpikeIntervalBase](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value, unsigned int popSize, unsigned int \*spikeQueuePtr, unsigned int \*hostSpikeCount, unsigned int \*hostSpikes, [PushCurrentSpikesFunc](#) pushCurrentSpikes)
- virtual double [getTimeToSpike](#) (double isiMs)=0

## Additional Inherited Members

### 19.55.1 Constructor & Destructor Documentation

#### 19.55.1.1 InterSpikeIntervalBase()

```

SpineMLSimulator::Input::InterSpikeIntervalBase::InterSpikeIntervalBase (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value,
    unsigned int popSize,
    unsigned int * spikeQueuePtr,
    unsigned int * hostSpikeCount,
    unsigned int * hostSpikes,
    PushCurrentSpikesFunc pushCurrentSpikes ) [protected]
  
```

### 19.55.2 Member Function Documentation

#### 19.55.2.1 apply()

```

void SpineMLSimulator::Input::InterSpikeIntervalBase::apply (
    double dt,
    unsigned long long timestep ) [override], [virtual]
  
```

Implements [SpineMLSimulator::Input::Base](#).

## 19.55.2.2 getTimeToSpike()

```
virtual double SpineMLSimulator::Input::InterSpikeIntervalBase::getTimeToSpike (
    double isiMs ) [protected], [pure virtual]
```

Implemented in [SpineMLSimulator::Input::PoissonSpikeRate](#), and [SpineMLSimulator::Input::RegularSpikeRate](#).

The documentation for this class was generated from the following files:


- [input.h](#)
- [input.cc](#)

## 19.56 NeuronModels::Izhikevich Class Reference

[Izhikevich](#) neuron with fixed parameters [1].

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::Izhikevich:



## Public Types

- typedef [Snippet::ValueBase](#)< 4 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 2 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [VarVec](#) [getVars](#) () const override  
*Gets names and types (as strings) of model variables.*

## Static Public Member Functions

- static const [NeuronModels::Izhikevich](#) \* [getInstance](#) ()

## Additional Inherited Members

### 19.56.1 Detailed Description

[Izhikevich](#) neuron with fixed parameters [1].

It is usually described as

$$\begin{aligned}\frac{dV}{dt} &= 0.04V^2 + 5V + 140 - U + I, \\ \frac{dU}{dt} &= a(bV - U),\end{aligned}$$

I is an external input current and the voltage V is reset to parameter c and U incremented by parameter d, whenever  $V \geq 30$  mV. This is paired with a particular integration procedure of two 0.5 ms Euler time steps for the V equation followed by one 1 ms time step of the U equation. Because of its popularity we provide this model in this form here event though due to the details of the usual implementation it is strictly speaking inconsistent with the displayed equations.

Variables are:

- V - Membrane potential
- U - Membrane recovery variable

Parameters are:

- a - time scale of U
- b - sensitivity of U
- c - after-spike reset value of V
- d - after-spike reset value of U

### 19.56.2 Member Typedef Documentation

#### 19.56.2.1 ParamValues

```
typedef Snippet::ValueBase< 4 > NeuronModels::Izhikevich::ParamValues
```

#### 19.56.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::Izhikevich::PostVarValues
```

#### 19.56.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::Izhikevich::PreVarValues
```

#### 19.56.2.4 VarValues

```
typedef Models::VarInitContainerBase< 2 > NeuronModels::Izhikevich::VarValues
```

### 19.56.3 Member Function Documentation



### 19.56.3.1 getInstance()

```
static const NeuronModels::Izhikevich* NeuronModels::Izhikevich::getInstance ( ) [inline],
[static]
```

### 19.56.3.2 getParamNames()

```
virtual StringVec NeuronModels::Izhikevich::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

Reimplemented in [NeuronModels::IzhikevichVariable](#).

### 19.56.3.3 getSimCode()

```
virtual std::string NeuronModels::Izhikevich::getSimCode ( ) const [inline], [override],
[virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

### 19.56.3.4 getThresholdConditionCode()

```
virtual std::string NeuronModels::Izhikevich::getThresholdConditionCode ( ) const [inline],
[override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

### 19.56.3.5 getVars()

```
virtual VarVec NeuronModels::Izhikevich::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

Reimplemented in [NeuronModels::IzhikevichVariable](#).

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.57 NeuronModels::IzhikevichVariable Class Reference

[Izhikevich](#) neuron with variable parameters [1].

```
#include <neuronModels.h>
```

Inheritance diagram for [NeuronModels::IzhikevichVariable](#):



### Public Types

- typedef [Snippet::ValueBase](#)< 0 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 6 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

### Public Member Functions

- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of (independent) model parameters.*
- virtual [VarVec](#) [getVars](#) () const override  
*Gets names and types (as strings) of model variables.*

### Static Public Member Functions

- static const [NeuronModels::IzhikevichVariable](#) \* [getInstance](#) ()

### Additional Inherited Members

#### 19.57.1 Detailed Description

[Izhikevich](#) neuron with variable parameters [1].

This is the same model as [Izhikevich](#) but parameters are defined as "variables" in order to allow users to provide individual values for each individual neuron instead of fixed values for all neurons across the population.

Accordingly, the model has the Variables:

- $V$  - Membrane potential
- $U$  - Membrane recovery variable
- $a$  - time scale of  $U$
- $b$  - sensitivity of  $U$
- $c$  - after-spike reset value of  $V$
- $d$  - after-spike reset value of  $U$

and no parameters.

## 19.57.2 Member Typedef Documentation

### 19.57.2.1 ParamValues

```
typedef Snippet::ValueBase< 0 > NeuronModels::IzhikevichVariable::ParamValues
```

### 19.57.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::IzhikevichVariable::PostVarValues
```

### 19.57.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::IzhikevichVariable::PreVarValues
```

### 19.57.2.4 VarValues

```
typedef Models::VarInitContainerBase< 6 > NeuronModels::IzhikevichVariable::VarValues
```

## 19.57.3 Member Function Documentation

### 19.57.3.1 getInstance()

```
static const NeuronModels::IzhikevichVariable* NeuronModels::IzhikevichVariable::getInstance (
) [inline], [static]
```

### 19.57.3.2 getParamNames()

```
virtual StringVec NeuronModels::IzhikevichVariable::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [NeuronModels::Izhikevich](#).

### 19.57.3.3 getVars()

```
virtual VarVec NeuronModels::IzhikevichVariable::getVars ( ) const [inline], [override],
[virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [NeuronModels::Izhikevich](#).


The documentation for this class was generated from the following file:

- [neuronModels.h](#)

## 19.58 NeuronModels::LIF Class Reference

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::LIF:



### Public Types

- typedef [Snippet::ValueBase< 7 >](#) [ParamValues](#)
- typedef [Models::VarInitContainerBase< 2 >](#) [VarValues](#)
- typedef [Models::VarInitContainerBase< 0 >](#) [PreVarValues](#)
- typedef [Models::VarInitContainerBase< 0 >](#) [PostVarValues](#)

### Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual std::string [getResetCode](#) () const override  
*Gets code that defines the reset action taken after a spike occurred. This can be empty.*
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [DerivedParamVec](#) [getDerivedParams](#) () const override
- virtual [VarVec](#) [getVars](#) () const override  
*Gets names and types (as strings) of model variables.*
- [SET\\_NEEDS\\_AUTO\\_REFRACTORY](#) (false)

### Static Public Member Functions

- static const [LIF](#) \* [getInstance](#) ()

### Additional Inherited Members

#### 19.58.1 Member Typedef Documentation

##### 19.58.1.1 ParamValues

```
typedef Snippet::ValueBase< 7 > NeuronModels::LIF::ParamValues
```

##### 19.58.1.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::LIF::PostVarValues
```

## 19.58.1.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::LIF::PreVarValues
```

## 19.58.1.4 VarValues

```
typedef Models::VarInitContainerBase< 2 > NeuronModels::LIF::VarValues
```

## 19.58.2 Member Function Documentation

## 19.58.2.1 getDerivedParams()

```
virtual DerivedParamVec NeuronModels::LIF::getDerivedParams ( ) const [inline], [override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented from [Snippet::Base](#).

## 19.58.2.2 getInstance()

```
static const LIF* NeuronModels::LIF::getInstance ( ) [inline], [static]
```

## 19.58.2.3 getParamNames()

```
virtual StringVec NeuronModels::LIF::getParamNames ( ) const [inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

## 19.58.2.4 getResetCode()

```
virtual std::string NeuronModels::LIF::getResetCode ( ) const [inline], [override], [virtual]
```

Gets code that defines the reset action taken after a spike occurred. This can be empty.

Reimplemented from [NeuronModels::Base](#).

## 19.58.2.5 getSimCode()

```
virtual std::string NeuronModels::LIF::getSimCode ( ) const [inline], [override], [virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

#### 19.58.2.6 `getThresholdConditionCode()`

```
virtual std::string NeuronModels::LIF::getThresholdConditionCode ( ) const [inline], [override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

#### 19.58.2.7 `getVars()`

```
virtual VarVec NeuronModels::LIF::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

#### 19.58.2.8 `SET_NEEDS_AUTO_REFRACTORY()`

```
NeuronModels::LIF::SET_NEEDS_AUTO_REFRACTORY (
    false )
```

The documentation for this class was generated from the following file:

- [neuronModels.h](#)

### 19.59 `CodeGenerator::MemAlloc` Class Reference

```
#include <backendBase.h>
```

#### Public Member Functions

- `size_t` [getHostBytes](#) () const
- `size_t` [getDeviceBytes](#) () const
- `size_t` [getZeroCopyBytes](#) () const
- `size_t` [getHostMBytes](#) () const
- `size_t` [getDeviceMBytes](#) () const
- `size_t` [getZeroCopyMBytes](#) () const
- [MemAlloc](#) & `operator+=` (const [MemAlloc](#) &rhs)

#### Static Public Member Functions

- static [MemAlloc](#) `zero` ()
- static [MemAlloc](#) `host` (size\_t hostBytes)
- static [MemAlloc](#) `device` (size\_t deviceBytes)
- static [MemAlloc](#) `zeroCopy` (size\_t zeroCopyBytes)

#### 19.59.1 Member Function Documentation

#### 19.59.1.1 device()

```
static MemAlloc CodeGenerator::MemAlloc::device (  
    size_t deviceBytes ) [inline], [static]
```

#### 19.59.1.2 getDeviceBytes()

```
size_t CodeGenerator::MemAlloc::getDeviceBytes ( ) const [inline]
```

#### 19.59.1.3 getDeviceMBytes()

```
size_t CodeGenerator::MemAlloc::getDeviceMBytes ( ) const [inline]
```

#### 19.59.1.4 getHostBytes()

```
size_t CodeGenerator::MemAlloc::getHostBytes ( ) const [inline]
```

#### 19.59.1.5 getHostMBytes()

```
size_t CodeGenerator::MemAlloc::getHostMBytes ( ) const [inline]
```

#### 19.59.1.6 getZeroCopyBytes()

```
size_t CodeGenerator::MemAlloc::getZeroCopyBytes ( ) const [inline]
```

#### 19.59.1.7 getZeroCopyMBytes()

```
size_t CodeGenerator::MemAlloc::getZeroCopyMBytes ( ) const [inline]
```

#### 19.59.1.8 host()

```
static MemAlloc CodeGenerator::MemAlloc::host (  
    size_t hostBytes ) [inline], [static]
```

#### 19.59.1.9 operator+=( )

```
MemAlloc& CodeGenerator::MemAlloc::operator+= (  
    const MemAlloc & rhs ) [inline]
```

#### 19.59.1.10 zero()

```
static MemAlloc CodeGenerator::MemAlloc::zero ( ) [inline], [static]
```

#### 19.59.1.11 zeroCopy()

```
static MemAlloc CodeGenerator::MemAlloc::zeroCopy (
```

```
size_t zeroCopyBytes ) [inline], [static]
```

The documentation for this class was generated from the following file:


- [backendBase.h](#)

## 19.60 ModelSpec Class Reference

Object used for specifying a neuronal network model.

```
#include <modelSpec.h>
```

Inheritance diagram for ModelSpec:



### Public Types

- typedef std::map< std::string, [NeuronGroupInternal](#) >::value\_type [NeuronGroupValueType](#)
- typedef std::map< std::string, [SynapseGroupInternal](#) >::value\_type [SynapseGroupValueType](#)

### Public Member Functions

- [ModelSpec](#) ()
- [ModelSpec](#) (const [ModelSpec](#) &)=delete
- [ModelSpec](#) & operator= (const [ModelSpec](#) &)=delete
- ~[ModelSpec](#) ()
- void [setName](#) (const std::string &name)  
*Method to set the neuronal network model name.*
- void [setPrecision](#) ([FloatType](#))  
*Set numerical precision for floating point.*
- void [setTimePrecision](#) ([TimePrecision](#) timePrecision)  
*Set numerical precision for time.*
- void [setDT](#) (double dt)  
*Set the integration step size of the model.*
- void [setTiming](#) (bool timingEnabled)  
*Set whether timers and timing commands are to be included.*
- void [setSeed](#) (unsigned int rngSeed)  
*Set the random seed (disables automatic seeding if argument not 0).*
- void [setDefaultVarLocation](#) ([VarLocation](#) loc)  
*What is the default location for model state variables?*
- void [setDefaultExtraGlobalParamLocation](#) ([VarLocation](#) loc)  
*What is the default location for model extra global parameters?*
- void [setDefaultSparseConnectivityLocation](#) ([VarLocation](#) loc)  
*What is the default location for sparse synaptic connectivity?*
- void [setDefaultNarrowSparseIndEnabled](#) (bool enabled)  
*Sets default for whether narrow i.e. less than 32-bit types are used for sparse matrix indices.*
- void [setMergePostsynapticModels](#) (bool merge)  
*Should compatible postsynaptic models and dendritic delay buffers be merged?*



- `const std::string & getName () const`  
*Gets the name of the neuronal network model.*
- `const std::string & getPrecision () const`  
*Gets the floating point numerical precision.*
- `std::string getTimePrecision () const`  
*Gets the floating point numerical precision used to represent time.*
- `double getDT () const`  
*Gets the model integration step size.*
- `unsigned int getSeed () const`  
*Get the random seed.*
- `bool isTimingEnabled () const`  
*Are timers and timing commands enabled.*
- `unsigned int getNumLocalNeurons () const`  
*How many neurons are simulated locally in this model.*
- `unsigned int getNumRemoteNeurons () const`  
*How many neurons are simulated remotely in this model.*
- `unsigned int getNumNeurons () const`  
*How many neurons make up the entire model.*
- `NeuronGroup * findNeuronGroup (const std::string &name)`  
*Find a neuron group by name.*
- `template<typename NeuronModel >`  
`NeuronGroup * addNeuronPopulation (const std::string &name, unsigned int size, const NeuronModel`  
`*model, const typename NeuronModel::ParamValues &paramValues, const typename NeuronModel::Var↵`  
`Values &varInitialisers, int hostID=0)`  
*Adds a new neuron group to the model using a neuron model managed by the user.*
- `template<typename NeuronModel >`  
`NeuronGroup * addNeuronPopulation (const std::string &name, unsigned int size, const typename Neuron↵`  
`Model::ParamValues &paramValues, const typename NeuronModel::VarValues &varInitialisers, int hostID=0)`  
*Adds a new neuron group to the model using a singleton neuron model created using standard DECLARE\_MODEL and IMPLEMENT\_MODEL macros.*
- `SynapseGroup * findSynapseGroup (const std::string &name)`  
*Find a synapse group by name.*
- `template<typename WeightUpdateModel, typename PostsynapticModel >`  
`SynapseGroup * addSynapsePopulation (const std::string &name, SynapseMatrixType mtype, unsigned`  
`int delaySteps, const std::string &src, const std::string &trg, const WeightUpdateModel *wum, const`  
`typename WeightUpdateModel::ParamValues &weightParamValues, const typename WeightUpdate↵`  
`Model::VarValues &weightVarInitialisers, const typename WeightUpdateModel::PreVarValues &weight↵`  
`PreVarInitialisers, const typename WeightUpdateModel::PostVarValues &weightPostVarInitialisers, const`  
`PostsynapticModel *psm, const typename PostsynapticModel::ParamValues &postsynapticParamValues,`  
`const typename PostsynapticModel::VarValues &postsynapticVarInitialisers, const InitSparseConnectivity↵`  
`Snippet::Init &connectivityInitialiser=uninitialisedConnectivity())`  
*Adds a synapse population to the model using weight update and postsynaptic models managed by the user.*
- `template<typename WeightUpdateModel, typename PostsynapticModel >`  
`SynapseGroup * addSynapsePopulation (const std::string &name, SynapseMatrixType mtype, unsigned`  
`int delaySteps, const std::string &src, const std::string &trg, const typename WeightUpdateModel::Param↵`  
`Values &weightParamValues, const typename WeightUpdateModel::VarValues &weightVarInitialisers, const`  
`typename PostsynapticModel::ParamValues &postsynapticParamValues, const typename Postsynaptic↵`  
`Model::VarValues &postsynapticVarInitialisers, const InitSparseConnectivitySnippet::Init &connectivity↵`  
`Initialiser=uninitialisedConnectivity())`  
*Adds a synapse population to the model using singleton weight update and postsynaptic models created using standard DECLARE\_MODEL and IMPLEMENT\_MODEL macros.*

- `template<typename WeightUpdateModel, typename PostsynapticModel >`  
`SynapseGroup * addSynapsePopulation` (const std::string &name, `SynapseMatrixType` mtype, unsigned int delaySteps, const std::string &src, const std::string &trg, const typename `WeightUpdateModel::ParamValues` &weightParamValues, const typename `WeightUpdateModel::VarValues` &weightVarInitialisers, const typename `WeightUpdateModel::PreVarValues` &weightPreVarInitialisers, const typename `WeightUpdateModel::PostVarValues` &weightPostVarInitialisers, const typename `PostsynapticModel::ParamValues` &postsynapticParamValues, const typename `PostsynapticModel::VarValues` &postsynapticVarInitialisers, const `InitSparseConnectivitySnippet::Init` &connectivityInitialiser=`uninitialisedConnectivity()`)  
*Adds a synapse population to the model using singleton weight update and postsynaptic models created using standard `DECLARE_MODEL` and `IMPLEMENT_MODEL` macros.*
- `CurrentSource * findCurrentSource` (const std::string &name)  
*Find a current source by name.*
- `template<typename CurrentSourceModel >`  
`CurrentSource * addCurrentSource` (const std::string &currentSourceName, const `CurrentSourceModel *model`, const std::string &targetNeuronGroupName, const typename `CurrentSourceModel::ParamValues` &paramValues, const typename `CurrentSourceModel::VarValues` &varInitialisers)  
*Adds a new current source to the model using a current source model managed by the user.*
- `template<typename CurrentSourceModel >`  
`CurrentSource * addCurrentSource` (const std::string &currentSourceName, const std::string &targetNeuronGroupName, const typename `CurrentSourceModel::ParamValues` &paramValues, const typename `CurrentSourceModel::VarValues` &varInitialisers)  
*Adds a new current source to the model using a singleton current source model created using standard `DECLARE_MODEL` and `IMPLEMENT_MODEL` macros.*

## Protected Member Functions

- void `finalize` ()  
*Finalise model.*
- std::string `scalarExpr` (double) const  
*Get the string literal that should be used to represent a value in the model's floating-point type.*
- bool `zeroCopyInUse` () const  
*Are any variables in any populations in this model using zero-copy memory?*
- const std::map< std::string, `NeuronGroupInternal` > & `getLocalNeuronGroups` () const  
*Get std::map containing local named `NeuronGroup` objects in model.*
- const std::map< std::string, `NeuronGroupInternal` > & `getRemoteNeuronGroups` () const  
*Get std::map containing remote named `NeuronGroup` objects in model.*
- const std::map< std::string, `SynapseGroupInternal` > & `getLocalSynapseGroups` () const  
*Get std::map containing local named `SynapseGroup` objects in model.*
- const std::map< std::string, `SynapseGroupInternal` > & `getRemoteSynapseGroups` () const  
*Get std::map containing remote named `SynapseGroup` objects in model.*
- const std::map< std::string, `CurrentSourceInternal` > & `getLocalCurrentSources` () const  
*Get std::map containing local named `CurrentSource` objects in model.*
- const std::map< std::string, `CurrentSourceInternal` > & `getRemoteCurrentSources` () const  
*Get std::map containing remote named `CurrentSource` objects in model.*

### 19.60.1 Detailed Description

Object used for specifying a neuronal network model.

### 19.60.2 Member Typedef Documentation

## 19.60.2.1 NeuronGroupValueType

```
typedef std::map<std::string, NeuronGroupInternal>::value_type ModelSpec::NeuronGroupValueType
```

## 19.60.2.2 SynapseGroupValueType

```
typedef std::map<std::string, SynapseGroupInternal>::value_type ModelSpec::SynapseGroupValueType
```

## 19.60.3 Constructor &amp; Destructor Documentation

## 19.60.3.1 ModelSpec() [1/2]

```
ModelSpec::ModelSpec ( )
```

## 19.60.3.2 ModelSpec() [2/2]

```
ModelSpec::ModelSpec (
    const ModelSpec & ) [delete]
```

## 19.60.3.3 ~ModelSpec()

```
ModelSpec::~ModelSpec ( )
```

## 19.60.4 Member Function Documentation

## 19.60.4.1 addCurrentSource() [1/2]

```
template<typename CurrentSourceModel >
CurrentSource* ModelSpec::addCurrentSource (
    const std::string & currentSourceName,
    const CurrentSourceModel * model,
    const std::string & targetNeuronGroupName,
    const typename CurrentSourceModel::ParamValues & paramValues,
    const typename CurrentSourceModel::VarValues & varInitialisers ) [inline]
```

Adds a new current source to the model using a current source model managed by the user.

## Template Parameters

<i>CurrentSourceModel</i>	type of current source model (derived from <a href="#">CurrentSourceModels::Base</a> ).
---------------------------	---

## Parameters

<i>currentSourceName</i>	string containing unique name of current source.
<i>model</i>	current source model to use for current source.
<i>targetNeuronGroupName</i>	string name of the target neuron group
<i>paramValues</i>	parameters for model wrapped in <code>CurrentSourceModel::ParamValues</code> object.

## Parameters

<i>varInitialisers</i>	state variable initialiser snippets and parameters wrapped in <code>CurrentSource::VarValues</code> object.
------------------------	---

## Returns

pointer to newly created [CurrentSource](#)

19.60.4.2 `addCurrentSource()` [2/2]

```
template<typename CurrentSourceModel >
CurrentSource* ModelSpec::addCurrentSource (
    const std::string & currentSourceName,
    const std::string & targetNeuronGroupName,
    const typename CurrentSourceModel::ParamValues & paramValues,
    const typename CurrentSourceModel::VarValues & varInitialisers ) [inline]
```

Adds a new current source to the model using a singleton current source model created using standard `DECLARE_MODEL` and `IMPLEMENT_MODEL` macros.

## Template Parameters

<i>CurrentSourceModel</i>	type of neuron model (derived from <code>CurrentSourceModel::Base</code> ).
---------------------------	---

## Parameters

<i>currentSourceName</i>	string containing unique name of current source.
<i>targetNeuronGroupName</i>	string name of the target neuron group
<i>paramValues</i>	parameters for model wrapped in <code>CurrentSourceModel::ParamValues</code> object.
<i>varInitialisers</i>	state variable initialiser snippets and parameters wrapped in <code>CurrentSourceModel::VarValues</code> object.

## Returns

pointer to newly created [CurrentSource](#)

19.60.4.3 `addNeuronPopulation()` [1/2]

```
template<typename NeuronModel >
NeuronGroup* ModelSpec::addNeuronPopulation (
    const std::string & name,
    unsigned int size,
    const NeuronModel * model,
    const typename NeuronModel::ParamValues & paramValues,
    const typename NeuronModel::VarValues & varInitialisers,
    int hostID = 0 ) [inline]
```

Adds a new neuron group to the model using a neuron model managed by the user.

## Template Parameters

<i>NeuronModel</i>	type of neuron model (derived from <a href="#">NeuronModels::Base</a> ).
--------------------	--

## Parameters

<i>name</i>	string containing unique name of neuron population.
<i>size</i>	integer specifying how many neurons are in the population.
<i>model</i>	neuron model to use for neuron group.
<i>paramValues</i>	parameters for model wrapped in NeuronModel::ParamValues object.
<i>varInitialisers</i>	state variable initialiser snippets and parameters wrapped in NeuronModel::VarValues object.
<i>hostID</i>	if using MPI, the ID of the node to simulate this population on.

## Returns

pointer to newly created [NeuronGroup](#)

## 19.60.4.4 addNeuronPopulation() [2/2]

```
template<typename NeuronModel >
NeuronGroup* ModelSpec::addNeuronPopulation (
    const std::string & name,
    unsigned int size,
    const typename NeuronModel::ParamValues & paramValues,
    const typename NeuronModel::VarValues & varInitialisers,
    int hostID = 0 ) [inline]
```

Adds a new neuron group to the model using a singleton neuron model created using standard DECLARE\_MODEL and IMPLEMENT\_MODEL macros.

## Template Parameters

<i>NeuronModel</i>	type of neuron model (derived from <a href="#">NeuronModels::Base</a> ).
--------------------	--

## Parameters

<i>name</i>	string containing unique name of neuron population.
<i>size</i>	integer specifying how many neurons are in the population.
<i>paramValues</i>	parameters for model wrapped in NeuronModel::ParamValues object.
<i>varInitialisers</i>	state variable initialiser snippets and parameters wrapped in NeuronModel::VarValues object.
<i>hostID</i>	if using MPI, the ID of the node to simulate this population on.

## Returns

pointer to newly created [NeuronGroup](#)

## 19.60.4.5 addSynapsePopulation() [1/3]

```
template<typename WeightUpdateModel , typename PostsynapticModel >
SynapseGroup* ModelSpec::addSynapsePopulation (
    const std::string & name,
    SynapseMatrixType mtype,
    unsigned int delaySteps,
    const std::string & src,
```

```

const std::string & trg,
const WeightUpdateModel * wum,
const typename WeightUpdateModel::ParamValues & weightParamValues,
const typename WeightUpdateModel::VarValues & weightVarInitialisers,
const typename WeightUpdateModel::PreVarValues & weightPreVarInitialisers,
const typename WeightUpdateModel::PostVarValues & weightPostVarInitialisers,
const PostsynapticModel * psm,
const typename PostsynapticModel::ParamValues & postsynapticParamValues,
const typename PostsynapticModel::VarValues & postsynapticVarInitialisers,
const InitSparseConnectivitySnippet::Init & connectivityInitialiser = uninitialised←
Connectivity() ) [inline]

```

Adds a synapse population to the model using weight update and postsynaptic models managed by the user.

#### Template Parameters

<i>WeightUpdateModel</i>	type of weight update model (derived from <a href="#">WeightUpdateModels::Base</a> ).
<i>PostsynapticModel</i>	type of postsynaptic model (derived from <a href="#">PostsynapticModels::Base</a> ).

#### Parameters

<i>name</i>	string containing unique name of neuron population.
<i>mtype</i>	how the synaptic matrix associated with this synapse population should be represented.
<i>delaySteps</i>	integer specifying number of timesteps delay this synaptic connection should incur (or NO_DELAY for none)
<i>src</i>	string specifying name of presynaptic (source) population
<i>trg</i>	string specifying name of postsynaptic (target) population
<i>wum</i>	weight update model to use for synapse group.
<i>weightParamValues</i>	parameters for weight update model wrapped in WeightUpdateModel::ParamValues object.
<i>weightVarInitialisers</i>	weight update model state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>weightPreVarInitialisers</i>	weight update model presynaptic state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>weightPostVarInitialisers</i>	weight update model postsynaptic state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>psm</i>	postsynaptic model to use for synapse group.
<i>postsynapticParamValues</i>	parameters for postsynaptic model wrapped in PostsynapticModel::ParamValues object.
<i>postsynapticVarInitialisers</i>	postsynaptic model state variable initialiser snippets and parameters wrapped in NeuronModel::VarValues object.
<i>connectivityInitialiser</i>	sparse connectivity initialisation snippet used to initialise connectivity for <a href="#">SynapseMatrixConnectivity::SPARSE</a> or <a href="#">SynapseMatrixConnectivity::BITMASK</a> . Typically wrapped with it's parameters using <code>initConnectivity</code> function

#### Returns

pointer to newly created [SynapseGroup](#)

#### 19.60.4.6 addSynapsePopulation() [2/3]

```
template<typename WeightUpdateModel , typename PostsynapticModel >
```

```

SynapseGroup* ModelSpec::addSynapsePopulation (
    const std::string & name,
    SynapseMatrixType mtype,
    unsigned int delaySteps,
    const std::string & src,
    const std::string & trg,
    const typename WeightUpdateModel::ParamValues & weightParamValues,
    const typename WeightUpdateModel::VarValues & weightVarInitialisers,
    const typename PostsynapticModel::ParamValues & postsynapticParamValues,
    const typename PostsynapticModel::VarValues & postsynapticVarInitialisers,
    const InitSparseConnectivitySnippet::Init & connectivityInitialiser = uninitialised←
Connectivity() ) [inline]

```

Adds a synapse population to the model using singleton weight update and postsynaptic models created using standard DECLARE\_MODEL and IMPLEMENT\_MODEL macros.

#### Template Parameters

<i>WeightUpdateModel</i>	type of weight update model (derived from <a href="#">WeightUpdateModels::Base</a> ).
<i>PostsynapticModel</i>	type of postsynaptic model (derived from <a href="#">PostsynapticModels::Base</a> ).

#### Parameters

<i>name</i>	string containing unique name of neuron population.
<i>mtype</i>	how the synaptic matrix associated with this synapse population should be represented.
<i>delaySteps</i>	integer specifying number of timesteps delay this synaptic connection should incur (or NO_DELAY for none)
<i>src</i>	string specifying name of presynaptic (source) population
<i>trg</i>	string specifying name of postsynaptic (target) population
<i>weightParamValues</i>	parameters for weight update model wrapped in WeightUpdateModel::ParamValues object.
<i>weightVarInitialisers</i>	weight update model state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>postsynapticParamValues</i>	parameters for postsynaptic model wrapped in PostsynapticModel::ParamValues object.
<i>postsynapticVarInitialisers</i>	postsynaptic model state variable initialiser snippets and parameters wrapped in NeuronModel::VarValues object.
<i>connectivityInitialiser</i>	sparse connectivity initialisation snippet used to initialise connectivity for <a href="#">SynapseMatrixConnectivity::SPARSE</a> or <a href="#">SynapseMatrixConnectivity::BITMASK</a> . Typically wrapped with it's parameters using <code>initConnectivity</code> function

#### Returns

pointer to newly created [SynapseGroup](#)

#### 19.60.4.7 addSynapsePopulation() [3/3]

```

template<typename WeightUpdateModel , typename PostsynapticModel >
SynapseGroup* ModelSpec::addSynapsePopulation (
    const std::string & name,
    SynapseMatrixType mtype,
    unsigned int delaySteps,

```

```

const std::string & src,
const std::string & trg,
const typename WeightUpdateModel::ParamValues & weightParamValues,
const typename WeightUpdateModel::VarValues & weightVarInitialisers,
const typename WeightUpdateModel::PreVarValues & weightPreVarInitialisers,
const typename WeightUpdateModel::PostVarValues & weightPostVarInitialisers,
const typename PostsynapticModel::ParamValues & postsynapticParamValues,
const typename PostsynapticModel::VarValues & postsynapticVarInitialisers,
const InitSparseConnectivitySnippet::Init & connectivityInitialiser = uninitialised←
Connectivity() ) [inline]

```

Adds a synapse population to the model using singleton weight update and postsynaptic models created using standard DECLARE\_MODEL and IMPLEMENT\_MODEL macros.

#### Template Parameters

<i>WeightUpdateModel</i>	type of weight update model (derived from <a href="#">WeightUpdateModels::Base</a> ).
<i>PostsynapticModel</i>	type of postsynaptic model (derived from <a href="#">PostsynapticModels::Base</a> ).

#### Parameters

<i>name</i>	string containing unique name of neuron population.
<i>mtype</i>	how the synaptic matrix associated with this synapse population should be represented.
<i>delaySteps</i>	integer specifying number of timesteps delay this synaptic connection should incur (or NO_DELAY for none)
<i>src</i>	string specifying name of presynaptic (source) population
<i>trg</i>	string specifying name of postsynaptic (target) population
<i>weightParamValues</i>	parameters for weight update model wrapped in WeightUpdateModel::ParamValues object.
<i>weightVarInitialisers</i>	weight update model per-synapse state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>weightPreVarInitialisers</i>	weight update model presynaptic state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>weightPostVarInitialisers</i>	weight update model postsynaptic state variable initialiser snippets and parameters wrapped in WeightUpdateModel::VarValues object.
<i>postsynapticParamValues</i>	parameters for postsynaptic model wrapped in PostsynapticModel::ParamValues object.
<i>postsynapticVarInitialisers</i>	postsynaptic model state variable initialiser snippets and parameters wrapped in NeuronModel::VarValues object.
<i>connectivityInitialiser</i>	sparse connectivity initialisation snippet used to initialise connectivity for <a href="#">SynapseMatrixConnectivity::SPARSE</a> or <a href="#">SynapseMatrixConnectivity::BITMASK</a> . Typically wrapped with it's parameters using <code>initConnectivity</code> function

#### Returns

pointer to newly created [SynapseGroup](#)

#### 19.60.4.8 finalize()

```
void ModelSpec::finalize ( ) [protected]
```

Finalise model.



**19.60.4.9 findCurrentSource()**

```
CurrentSource * ModelSpec::findCurrentSource (
    const std::string & name )
```

Find a current source by name.

This function attempts to find an existing current source.

**19.60.4.10 findNeuronGroup()**

```
NeuronGroup* ModelSpec::findNeuronGroup (
    const std::string & name ) [inline]
```

Find a neuron group by name.

**19.60.4.11 findSynapseGroup()**

```
SynapseGroup * ModelSpec::findSynapseGroup (
    const std::string & name )
```

Find a synapse group by name.

**19.60.4.12 getDT()**

```
double ModelSpec::getDT ( ) const [inline]
```

Gets the model integration step size.

**19.60.4.13 getLocalCurrentSources()**

```
const std::map<std::string, CurrentSourceInternal>& ModelSpec::getLocalCurrentSources ( )
const [inline], [protected]
```

Get std::map containing local named [CurrentSource](#) objects in model.

**19.60.4.14 getLocalNeuronGroups()**

```
const std::map<std::string, NeuronGroupInternal>& ModelSpec::getLocalNeuronGroups ( ) const
[inline], [protected]
```

Get std::map containing local named [NeuronGroup](#) objects in model.

**19.60.4.15 getLocalSynapseGroups()**

```
const std::map<std::string, SynapseGroupInternal>& ModelSpec::getLocalSynapseGroups ( ) const
[inline], [protected]
```

Get std::map containing local named [SynapseGroup](#) objects in model.

**19.60.4.16 getName()**

```
const std::string& ModelSpec::getName ( ) const [inline]
```

Gets the name of the neuronal network model.

#### 19.60.4.17 `getNumLocalNeurons()`

```
unsigned int ModelSpec::getNumLocalNeurons ( ) const
```

How many neurons are simulated locally in this model.

#### 19.60.4.18 `getNumNeurons()`

```
unsigned int ModelSpec::getNumNeurons ( ) const [inline]
```

How many neurons make up the entire model.

#### 19.60.4.19 `getNumRemoteNeurons()`

```
unsigned int ModelSpec::getNumRemoteNeurons ( ) const
```

How many neurons are simulated remotely in this model.

#### 19.60.4.20 `getPrecision()`

```
const std::string& ModelSpec::getPrecision ( ) const [inline]
```

Gets the floating point numerical precision.

#### 19.60.4.21 `getRemoteCurrentSources()`

```
const std::map<std::string, CurrentSourceInternal>& ModelSpec::getRemoteCurrentSources ( )  
const [inline], [protected]
```

Get std::map containing remote named [CurrentSource](#) objects in model.

#### 19.60.4.22 `getRemoteNeuronGroups()`

```
const std::map<std::string, NeuronGroupInternal>& ModelSpec::getRemoteNeuronGroups ( ) const  
[inline], [protected]
```

Get std::map containing remote named [NeuronGroup](#) objects in model.

#### 19.60.4.23 `getRemoteSynapseGroups()`

```
const std::map<std::string, SynapseGroupInternal>& ModelSpec::getRemoteSynapseGroups ( ) const  
[inline], [protected]
```

Get std::map containing remote named [SynapseGroup](#) objects in model.

#### 19.60.4.24 `getSeed()`

```
unsigned int ModelSpec::getSeed ( ) const [inline]
```

Get the random seed.

#### 19.60.4.25 getTimePrecision()

```
std::string ModelSpec::getTimePrecision ( ) const
```

Gets the floating point numerical precision used to represent time.

#### 19.60.4.26 isTimingEnabled()

```
bool ModelSpec::isTimingEnabled ( ) const [inline]
```

Are timers and timing commands enabled.

#### 19.60.4.27 operator=()

```
ModelSpec& ModelSpec::operator= (
    const ModelSpec & ) [delete]
```

#### 19.60.4.28 scalarExpr()

```
std::string ModelSpec::scalarExpr (
    double val ) const [protected]
```

Get the string literal that should be used to represent a value in the model's floating-point type.

#### 19.60.4.29 setDefaultExtraGlobalParamLocation()

```
void ModelSpec::setDefaultExtraGlobalParamLocation (
    VarLocation loc ) [inline]
```

What is the default location for model extra global parameters?

Historically, this was just left up to the user to handle

#### 19.60.4.30 setDefaultNarrowSparseIndEnabled()

```
void ModelSpec::setDefaultNarrowSparseIndEnabled (
    bool enabled ) [inline]
```

Sets default for whether narrow i.e. less than 32-bit types are used for sparse matrix indices.

#### 19.60.4.31 setDefaultSparseConnectivityLocation()

```
void ModelSpec::setDefaultSparseConnectivityLocation (
    VarLocation loc ) [inline]
```

What is the default location for sparse synaptic connectivity?

Historically, everything was allocated on both the host AND device

#### 19.60.4.32 setDefaultVarLocation()

```
void ModelSpec::setDefaultVarLocation (
    VarLocation loc ) [inline]
```

What is the default location for model state variables?

Historically, everything was allocated on both the host AND device

#### 19.60.4.33 `setDT()`

```
void ModelSpec::setDT (
    double dt ) [inline]
```

Set the integration step size of the model.

#### 19.60.4.34 `setMergePostsynapticModels()`

```
void ModelSpec::setMergePostsynapticModels (
    bool merge ) [inline]
```

Should compatible postsynaptic models and dendritic delay buffers be merged?

This can significantly reduce the cost of updating neuron population but means that per-synapse group inSyn arrays can not be retrieved

#### 19.60.4.35 `setName()`

```
void ModelSpec::setName (
    const std::string & name ) [inline]
```

Method to set the neuronal network model name.

#### 19.60.4.36 `setPrecision()`

```
void ModelSpec::setPrecision (
    FloatType floattype )
```

Set numerical precision for floating point.

This function sets the numerical precision of floating type variables. By default, it is GENN\_GENN\_FLOAT.

#### 19.60.4.37 `setSeed()`

```
void ModelSpec::setSeed (
    unsigned int rngSeed ) [inline]
```

Set the random seed (disables automatic seeding if argument not 0).

#### 19.60.4.38 `setTimePrecision()`

```
void ModelSpec::setTimePrecision (
    TimePrecision timePrecision ) [inline]
```

Set numerical precision for time.

#### 19.60.4.39 `setTiming()`

```
void ModelSpec::setTiming (
    bool timingEnabled ) [inline]
```

Set whether timers and timing commands are to be included.

## 19.60.4.40 zeroCopyInUse()

```
bool ModelSpec::zeroCopyInUse ( ) const [protected]
```

Are any variables in any populations in this model using zero-copy memory?


The documentation for this class was generated from the following files:

- [modelSpec.h](#)
- [modelSpec.cc](#)

## 19.61 ModelSpecInternal Class Reference

```
#include <modelSpecInternal.h>
```

Inheritance diagram for ModelSpecInternal:



## Additional Inherited Members

The documentation for this class was generated from the following file:

- [modelSpecInternal.h](#)

## 19.62 SpineMLSimulator::NetworkClient Class Reference

```
#include <networkClient.h>
```

## Public Types

- enum [Mode](#) : char { [Mode::Source](#) = 45, [Mode::Target](#) = 46 }
- enum [DataType](#) : char { [DataType::Analogue](#) = 31, [DataType::Events](#) = 32, [DataType::Impulses](#) = 33 }

## Public Member Functions

- [NetworkClient](#) ()
- [NetworkClient](#) (const std::string &hostname, unsigned int port, unsigned int size, [DataType](#) dataType, [Mode](#) mode, const std::string &connectionName)
- [~NetworkClient](#) ()
- bool [connect](#) (const std::string &hostname, unsigned int port, unsigned int size, [DataType](#) dataType, [Mode](#) mode, const std::string &connectionName)
- bool [receive](#) (std::vector< double > &buffer)
- bool [send](#) (const std::vector< double > &buffer)

## 19.62.1 Member Enumeration Documentation

#### 19.62.1.1 DataType

```
enum SpineMLSimulator::NetworkClient::DataType : char [strong]
```

## Enumerator

Analogue	
Events	
Impulses	

## 19.62.1.2 Mode

```
enum SpineMLSimulator::NetworkClient::Mode : char [strong]
```

## Enumerator

Source	
Target	

## 19.62.2 Constructor &amp; Destructor Documentation

## 19.62.2.1 NetworkClient() [1/2]

```
SpineMLSimulator::NetworkClient::NetworkClient ( )
```

## 19.62.2.2 NetworkClient() [2/2]

```
SpineMLSimulator::NetworkClient::NetworkClient (
    const std::string & hostname,
    unsigned int port,
    unsigned int size,
    DataType dataType,
    Mode mode,
    const std::string & connectionName )
```

## 19.62.2.3 ~NetworkClient()

```
SpineMLSimulator::NetworkClient::~~NetworkClient ( )
```

## 19.62.3 Member Function Documentation

## 19.62.3.1 connect()

```
bool SpineMLSimulator::NetworkClient::connect (
    const std::string & hostname,
    unsigned int port,
    unsigned int size,
    DataType dataType,
    Mode mode,
    const std::string & connectionName )
```

### 19.62.3.2 receive()

```
bool SpineMLSimulator::NetworkClient::receive (
    std::vector< double > & buffer )
```

### 19.62.3.3 send()

```
bool SpineMLSimulator::NetworkClient::send (
    const std::vector< double > & buffer )
```


The documentation for this class was generated from the following files:

- [networkClient.h](#)
- [networkClient.cc](#)

## 19.63 pygenn.genn\_groups.NeuronGroup Class Reference

Class representing a group of neurons.

Inheritance diagram for pygenn.genn\_groups.NeuronGroup:



### Public Member Functions

- def [\\_\\_init\\_\\_](#) (self, [name](#))  
*Init NeuronGroup.*
- def [current\\_spikes](#) (self)  
*Current spikes from GeNN.*
- def [delay\\_slots](#) (self)  
*Maximum delay steps needed for this group.*
- def [size](#) (self)
- def [set\\_neuron](#) (self, model, param\_space, var\_space)  
*Set neuron, its parameters and initial variables.*
- def [add\\_to](#) (self, model\_spec, num\_neurons)  
*Add this NeuronGroup to a model.*
- def [add\\_extra\\_global\\_param](#) (self, param\_name, param\_values)  
*Set extra global parameter.*
- def [set\\_extra\\_global\\_param](#) (self, param\_name, param\_values)  
*Set extra global parameter.*
- def [load](#) (self, slm, scalar)  
*Loads neuron group.*
- def [reinitialise](#) (self, slm, scalar)  
*Reinitialise neuron group.*



## Public Attributes

- [neuron](#)
- [spikes](#)
- [spike\\_count](#)
- [spike\\_que\\_ptr](#)
- [is\\_spike\\_source\\_array](#)
- [type](#)
- [pop](#)

## 19.63.1 Detailed Description

Class representing a group of neurons.

## 19.63.2 Constructor &amp; Destructor Documentation

## 19.63.2.1 \_\_init\_\_()

```
def pygenn.genn_groups.NeuronGroup.__init__ (
    self,
    name )
```

Init [NeuronGroup](#).

## Parameters

<i>name</i>	string name of the group
-------------	--------------------------

## 19.63.3 Member Function Documentation

## 19.63.3.1 add\_extra\_global\_param()

```
def pygenn.genn_groups.NeuronGroup.add_extra_global_param (
    self,
    param_name,
    param_values )
```

Set extra global parameter.

## Parameters

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

## 19.63.3.2 add\_to()

```
def pygenn.genn_groups.NeuronGroup.add_to (
    self,
    model_spec,
```

```
num_neurons )
```

Add this [NeuronGroup](#) to a model.

#### Parameters

<i>model_spec</i>	<a href="#">pygenn.genn_model.GeNNModel</a> to add to
<i>num_neurons</i>	int number of neurons

#### 19.63.3.3 `current_spikes()`

```
def pygenn.genn_groups.NeuronGroup.current_spikes (
    self )
```

Current spikes from GeNN.

#### 19.63.3.4 `delay_slots()`

```
def pygenn.genn_groups.NeuronGroup.delay_slots (
    self )
```

Maximum delay steps needed for this group.

#### 19.63.3.5 `load()`

```
def pygenn.genn_groups.NeuronGroup.load (
    self,
    slm,
    scalar )
```

Loads neuron group.

#### Parameters

<i>slm</i>	<a href="#">SharedLibraryModel</a> instance for accessing variables
<i>scalar</i>	String specifying "scalar" type

#### 19.63.3.6 `reinitialise()`

```
def pygenn.genn_groups.NeuronGroup.reinitialise (
    self,
    slm,
    scalar )
```

Reinitialise neuron group.

#### Parameters

<i>slm</i>	<a href="#">SharedLibraryModel</a> instance for accessing variables
<i>scalar</i>	String specifying "scalar" type

**19.63.3.7 set\_extra\_global\_param()**

```
def pygenn.genn_groups.NeuronGroup.set_extra_global_param (
    self,
    param_name,
    param_values )
```

Set extra global parameter.

**Parameters**

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

**19.63.3.8 set\_neuron()**

```
def pygenn.genn_groups.NeuronGroup.set_neuron (
    self,
    model,
    param_space,
    var_space )
```

Set neuron, its parameters and initial variables.

**Parameters**

<i>model</i>	type as string of intance of the model
<i>param_space</i>	dict with model parameters
<i>var_space</i>	dict with model variables

**19.63.3.9 size()**

```
def pygenn.genn_groups.NeuronGroup.size (
    self )
```

**19.63.4 Member Data Documentation****19.63.4.1 is\_spike\_source\_array**

```
pygenn.genn_groups.NeuronGroup.is_spike_source_array
```

**19.63.4.2 neuron**

```
pygenn.genn_groups.NeuronGroup.neuron
```

**19.63.4.3 pop**

```
pygenn.genn_groups.NeuronGroup.pop
```

#### 19.63.4.4 spike\_count

```
pygenn.genn_groups.NeuronGroup.spike_count
```

#### 19.63.4.5 spike\_que\_ptr

```
pygenn.genn_groups.NeuronGroup.spike_que_ptr
```

#### 19.63.4.6 spikes

```
pygenn.genn_groups.NeuronGroup.spikes
```

#### 19.63.4.7 type

```
pygenn.genn_groups.NeuronGroup.type
```


The documentation for this class was generated from the following file:

- [genn\\_groups.py](#)

### 19.64 NeuronGroup Class Reference

```
#include <neuronGroup.h>
```

Inheritance diagram for NeuronGroup:



#### Public Member Functions

- `NeuronGroup (const NeuronGroup &)=delete`
- `NeuronGroup ()=delete`
- `void setSpikeLocation (VarLocation loc)`  
*Set location of this neuron group's output spikes.*
- `void setSpikeEventLocation (VarLocation loc)`  
*Set location of this neuron group's output spike events.*
- `void setSpikeTimeLocation (VarLocation loc)`  
*Set location of this neuron group's output spike times.*
- `void setVarLocation (const std::string &varName, VarLocation loc)`  
*Set variable location of neuron model state variable.*
- `void setExtraGlobalParamLocation (const std::string &paramName, VarLocation loc)`  
*Set location of neuron model extra global parameter.*
- `const std::string &getName () const`
- `unsigned int getNumNeurons () const`  
*Gets number of neurons in group.*
- `const NeuronModels::Base * getNeuronModel () const`  
*Gets the neuron model used by this group.*

- `const std::vector< double > & getParams () const`
- `const std::vector< Models::VarInit > & getVarInitialisers () const`
- `int getClusterHostID () const`
- `bool isSpikeTimeRequired () const`
- `bool isTrueSpikeRequired () const`
- `bool isSpikeEventRequired () const`
- `unsigned int getNumDelaySlots () const`
- `bool isDelayRequired () const`
- `bool isZeroCopyEnabled () const`
- `VarLocation getSpikeLocation () const`  
*Get location of this neuron group's output spikes.*
- `VarLocation getSpikeEventLocation () const`  
*Get location of this neuron group's output spike events.*
- `VarLocation getSpikeTimeLocation () const`  
*Get location of this neuron group's output spike times.*
- `VarLocation getVarLocation (const std::string &varName) const`  
*Get location of neuron model state variable by name.*
- `VarLocation getVarLocation (size_t index) const`  
*Get location of neuron model state variable by index.*
- `VarLocation getExtraGlobalParamLocation (const std::string &paramName) const`  
*Get location of neuron model extra global parameter by name.*
- `VarLocation getExtraGlobalParamLocation (size_t index) const`  
*Get location of neuron model extra global parameter by index.*
- `bool isSimRNGRequired () const`  
*Does this neuron group require an RNG to simulate?*
- `bool isInitRNGRequired () const`  
*Does this neuron group require an RNG for its init code?*
- `bool hasOutputToHost (int targetHostID) const`  
*Does this neuron group have outgoing connections specified host id?*

### Protected Member Functions

- `NeuronGroup (const std::string &name, int numNeurons, const NeuronModels::Base *neuronModel, const std::vector< double > &params, const std::vector< Models::VarInit > &varInitialisers, VarLocation defaultVarLocation, VarLocation defaultExtraGlobalParamLocation, int hostID)`
- `void checkNumDelaySlots (unsigned int requiredDelay)`  
*Checks delay slots currently provided by the neuron group against a required delay and extends if required.*
- `void updatePreVarQueues (const std::string &code)`  
*Update which presynaptic variables require queues based on piece of code.*
- `void updatePostVarQueues (const std::string &code)`  
*Update which postsynaptic variables require queues based on piece of code.*
- `void addSpkEventCondition (const std::string &code, const std::string &supportCodeNamespace)`
- `void addInSyn (SynapseGroupInternal *synapseGroup)`
- `void addOutSyn (SynapseGroupInternal *synapseGroup)`
- `void initDerivedParams (double dt)`
- `void mergeIncomingPSM (bool merge)`  
*Merge incoming postsynaptic models.*
- `void injectCurrent (CurrentSourceInternal *source)`  
*add input current source*
- `const std::vector< SynapseGroupInternal * > & getInSyn () const`  
*Gets pointers to all synapse groups which provide input to this neuron group.*

- `const std::vector< std::pair< SynapseGroupInternal *, std::vector< SynapseGroupInternal * > > > & getMergedInSyn () const`
- `const std::vector< SynapseGroupInternal * > & getOutSyn () const`  
*Gets pointers to all synapse groups emanating from this neuron group.*
- `const std::vector< CurrentSourceInternal * > & getCurrentSources () const`  
*Gets pointers to all current sources which provide input to this neuron group.*
- `const std::vector< double > & getDerivedParams () const`
- `const std::set< std::pair< std::string, std::string > > & getSpikeEventCondition () const`
- `bool isParamRequiredBySpikeEventCondition (const std::string &pnamefull) const`  
*Do any of the spike event conditions tested by this neuron require specified parameter?*
- `std::string getCurrentQueueOffset (const std::string &devPrefix) const`  
*Get the expression to calculate the queue offset for accessing state of variables this timestep.*
- `std::string getPrevQueueOffset (const std::string &devPrefix) const`  
*Get the expression to calculate the queue offset for accessing state of variables in previous timestep.*
- `bool isVarQueueRequired (const std::string &var) const`
- `bool isVarQueueRequired (size_t index) const`

### 19.64.1 Constructor & Destructor Documentation

#### 19.64.1.1 [NeuronGroup\(\)](#) [1/3]

```
NeuronGroup::NeuronGroup (
    const NeuronGroup & ) [delete]
```

#### 19.64.1.2 [NeuronGroup\(\)](#) [2/3]

```
NeuronGroup::NeuronGroup ( ) [delete]
```

#### 19.64.1.3 [NeuronGroup\(\)](#) [3/3]

```
NeuronGroup::NeuronGroup (
    const std::string & name,
    int numNeurons,
    const NeuronModels::Base * neuronModel,
    const std::vector< double > & params,
    const std::vector< Models::VarInit > & varInitialisers,
    VarLocation defaultVarLocation,
    VarLocation defaultExtraGlobalParamLocation,
    int hostID ) [inline], [protected]
```

### 19.64.2 Member Function Documentation

#### 19.64.2.1 [addInSyn\(\)](#)

```
void NeuronGroup::addInSyn (
    SynapseGroupInternal * synapseGroup ) [inline], [protected]
```

**19.64.2.2 addOutSyn()**

```
void NeuronGroup::addOutSyn (
    SynapseGroupInternal * synapseGroup ) [inline], [protected]
```

**19.64.2.3 addSpkEventCondition()**

```
void NeuronGroup::addSpkEventCondition (
    const std::string & code,
    const std::string & supportCodeNamespace ) [protected]
```

**19.64.2.4 checkNumDelaySlots()**

```
void NeuronGroup::checkNumDelaySlots (
    unsigned int requiredDelay ) [protected]
```

Checks delay slots currently provided by the neuron group against a required delay and extends if required.

**19.64.2.5 getClusterHostID()**

```
int NeuronGroup::getClusterHostID ( ) const [inline]
```

**19.64.2.6 getCurrentQueueOffset()**

```
std::string NeuronGroup::getCurrentQueueOffset (
    const std::string & devPrefix ) const [protected]
```

Get the expression to calculate the queue offset for accessing state of variables this timestep.

**19.64.2.7 getCurrentSources()**

```
const std::vector<CurrentSourceInternal*>& NeuronGroup::getCurrentSources ( ) const [inline],
[protected]
```

Gets pointers to all current sources which provide input to this neuron group.

**19.64.2.8 getDerivedParams()**

```
const std::vector<double>& NeuronGroup::getDerivedParams ( ) const [inline], [protected]
```

**19.64.2.9 getExtraGlobalParamLocation()** [1/2]

```
VarLocation NeuronGroup::getExtraGlobalParamLocation (
    const std::string & paramName ) const
```

Get location of neuron model extra global parameter by name.

This is only used by extra global parameters which are pointers

**19.64.2.10 getExtraGlobalParamLocation()** [2/2]

```
VarLocation NeuronGroup::getExtraGlobalParamLocation (
    size_t index ) const [inline]
```

Get location of neuron model extra global parameter by omdex.

This is only used by extra global parameters which are pointers

#### 19.64.2.11 `getInSyn()`

```
const std::vector<SynapseGroupInternal*>& NeuronGroup::getInSyn ( ) const [inline], [protected]
```

Gets pointers to all synapse groups which provide input to this neuron group.

#### 19.64.2.12 `getMergedInSyn()`

```
const std::vector<std::pair<SynapseGroupInternal*, std::vector<SynapseGroupInternal*> > >&
NeuronGroup::getMergedInSyn ( ) const [inline], [protected]
```

#### 19.64.2.13 `getName()`

```
const std::string& NeuronGroup::getName ( ) const [inline]
```

#### 19.64.2.14 `getNeuronModel()`

```
const NeuronModels::Base* NeuronGroup::getNeuronModel ( ) const [inline]
```

Gets the neuron model used by this group.

#### 19.64.2.15 `getNumDelaySlots()`

```
unsigned int NeuronGroup::getNumDelaySlots ( ) const [inline]
```

#### 19.64.2.16 `getNumNeurons()`

```
unsigned int NeuronGroup::getNumNeurons ( ) const [inline]
```

Gets number of neurons in group.

#### 19.64.2.17 `getOutSyn()`

```
const std::vector<SynapseGroupInternal*>& NeuronGroup::getOutSyn ( ) const [inline], [protected]
```

Gets pointers to all synapse groups emanating from this neuron group.

#### 19.64.2.18 `getParams()`

```
const std::vector<double>& NeuronGroup::getParams ( ) const [inline]
```

#### 19.64.2.19 `getPrevQueueOffset()`

```
std::string NeuronGroup::getPrevQueueOffset (
    const std::string & devPrefix ) const [protected]
```

Get the expression to calculate the queue offset for accessing state of variables in previous timestep.



**19.64.2.20 getSpikeEventCondition()**

```
const std::set<std::pair<std::string, std::string> >& NeuronGroup::getSpikeEventCondition ( )  
const [inline], [protected]
```

**19.64.2.21 getSpikeEventLocation()**

```
VarLocation NeuronGroup::getSpikeEventLocation ( ) const [inline]
```

Get location of this neuron group's output spike events.

**19.64.2.22 getSpikeLocation()**

```
VarLocation NeuronGroup::getSpikeLocation ( ) const [inline]
```

Get location of this neuron group's output spikes.

**19.64.2.23 getSpikeTimeLocation()**

```
VarLocation NeuronGroup::getSpikeTimeLocation ( ) const [inline]
```

Get location of this neuron group's output spike times.

**19.64.2.24 getVarInitialisers()**

```
const std::vector<Models::VarInit>& NeuronGroup::getVarInitialisers ( ) const [inline]
```

**19.64.2.25 getVarLocation() [1/2]**

```
VarLocation NeuronGroup::getVarLocation (   
    const std::string & varName ) const
```

Get location of neuron model state variable by name.

**19.64.2.26 getVarLocation() [2/2]**

```
VarLocation NeuronGroup::getVarLocation (   
    size_t index ) const [inline]
```

Get location of neuron model state variable by index.

**19.64.2.27 hasOutputToHost()**

```
bool NeuronGroup::hasOutputToHost (   
    int targetHostID ) const
```

Does this neuron group have outgoing connections specified host id?

**19.64.2.28 initDerivedParams()**

```
void NeuronGroup::initDerivedParams (   
    double dt ) [protected]
```

**19.64.2.29 injectCurrent()**

```
void NeuronGroup::injectCurrent (
    CurrentSourceInternal * source ) [protected]
```

add input current source

**19.64.2.30 isDelayRequired()**

```
bool NeuronGroup::isDelayRequired ( ) const [inline]
```

**19.64.2.31 isInitRNGRequired()**

```
bool NeuronGroup::isInitRNGRequired ( ) const
```

Does this neuron group require an RNG for it's init code?

**19.64.2.32 isParamRequiredBySpikeEventCondition()**

```
bool NeuronGroup::isParamRequiredBySpikeEventCondition (
    const std::string & pnamefull ) const [protected]
```

Do any of the spike event conditions tested by this neuron require specified parameter?

**19.64.2.33 isSimRNGRequired()**

```
bool NeuronGroup::isSimRNGRequired ( ) const
```

Does this neuron group require an RNG to simulate?

**19.64.2.34 isSpikeEventRequired()**

```
bool NeuronGroup::isSpikeEventRequired ( ) const
```

**19.64.2.35 isSpikeTimeRequired()**

```
bool NeuronGroup::isSpikeTimeRequired ( ) const
```

**19.64.2.36 isTrueSpikeRequired()**

```
bool NeuronGroup::isTrueSpikeRequired ( ) const
```

**19.64.2.37 isVarQueueRequired()** [1/2]

```
bool NeuronGroup::isVarQueueRequired (
    const std::string & var ) const [protected]
```

**19.64.2.38 isVarQueueRequired()** [2/2]

```
bool NeuronGroup::isVarQueueRequired (
    size_t index ) const [inline], [protected]
```

**19.64.2.39 isZeroCopyEnabled()**

```
bool NeuronGroup::isZeroCopyEnabled ( ) const
```

**19.64.2.40 mergeIncomingPSM()**

```
void NeuronGroup::mergeIncomingPSM (
    bool merge ) [protected]
```

Merge incoming postsynaptic models.

**19.64.2.41 setExtraGlobalParamLocation()**

```
void NeuronGroup::setExtraGlobalParamLocation (
    const std::string & paramName,
    VarLocation loc )
```

Set location of neuron model extra global parameter.

This is ignored for simulations on hardware with a single memory space and only applies to extra global parameters which are pointers.

**19.64.2.42 setSpikeEventLocation()**

```
void NeuronGroup::setSpikeEventLocation (
    VarLocation loc ) [inline]
```

Set location of this neuron group's output spike events.

This is ignored for simulations on hardware with a single memory space

**19.64.2.43 setSpikeLocation()**

```
void NeuronGroup::setSpikeLocation (
    VarLocation loc ) [inline]
```

Set location of this neuron group's output spikes.

This is ignored for simulations on hardware with a single memory space

**19.64.2.44 setSpikeTimeLocation()**

```
void NeuronGroup::setSpikeTimeLocation (
    VarLocation loc ) [inline]
```

Set location of this neuron group's output spike times.

This is ignored for simulations on hardware with a single memory space

**19.64.2.45 setVarLocation()**

```
void NeuronGroup::setVarLocation (
    const std::string & varName,
    VarLocation loc )
```

Set variable location of neuron model state variable.

This is ignored for simulations on hardware with a single memory space

#### 19.64.2.46 updatePostVarQueues()

```
void NeuronGroup::updatePostVarQueues (
    const std::string & code ) [protected]
```

Update which postsynaptic variables require queues based on piece of code.

#### 19.64.2.47 updatePreVarQueues()

```
void NeuronGroup::updatePreVarQueues (
    const std::string & code ) [protected]
```

Update which presynaptic variables require queues based on piece of code.


The documentation for this class was generated from the following files:

- [neuronGroup.h](#)
- [neuronGroup.cc](#)

### 19.65 NeuronGroupInternal Class Reference

```
#include <neuronGroupInternal.h>
```

Inheritance diagram for NeuronGroupInternal:



#### Public Member Functions

- [NeuronGroupInternal](#) (const std::string &name, int numNeurons, const [NeuronModels::Base](#) \*neuronModel, const std::vector< double > &params, const std::vector< [Models::VarInit](#) > &varInitialisers, [VarLocation](#) defaultVarLocation, [VarLocation](#) defaultExtraGlobalParamLocation, int hostID)

#### Additional Inherited Members

#### 19.65.1 Constructor & Destructor Documentation

##### 19.65.1.1 NeuronGroupInternal()

```
NeuronGroupInternal::NeuronGroupInternal (
    const std::string & name,
    int numNeurons,
    const NeuronModels::Base * neuronModel,
    const std::vector< double > & params,
    const std::vector< Models::VarInit > & varInitialisers,
    VarLocation defaultVarLocation,
    VarLocation defaultExtraGlobalParamLocation,
    int hostID ) [inline]
```

The documentation for this class was generated from the following file:


- [neuronGroupInternal.h](#)

## 19.66 InitVarSnippet::Normal Class Reference

Initialises variable by sampling from the normal distribution.

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Normal:



### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitVarSnippet::Normal](#), 2)
- [SET\\_CODE](#) ("\$(value) = \$(mean) + (\$(gennrand\_normal) \* \$(sd));")
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*

### Additional Inherited Members

#### 19.66.1 Detailed Description

Initialises variable by sampling from the normal distribution.

This snippet takes 2 parameters:

- `mean` - The mean
- `sd` - The standard distribution

#### 19.66.2 Member Function Documentation

##### 19.66.2.1 DECLARE\_SNIPPET()

```
InitVarSnippet::Normal::DECLARE_SNIPPET (
    InitVarSnippet::Normal ,
    2 )
```

##### 19.66.2.2 getParamNames()

```
virtual StringVec InitVarSnippet::Normal::getParamNames ( ) const [inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

### 19.66.2.3 SET\_CODE()

```
InitVarSnippet::Normal::SET_CODE ( )
```


The documentation for this class was generated from the following file:

- [initVarSnippet.h](#)

## 19.67 SpineMLSimulator::ModelProperty::NormalDistribution Class Reference

```
#include <modelProperty.h>
```

Inheritance diagram for SpineMLSimulator::ModelProperty::NormalDistribution:



### Public Member Functions

- [NormalDistribution](#) (const `pugi::xml_node &node`, const [StateVar](#)< `scalar` > &stateVar, unsigned int size)
- void [setValue](#) (`scalar` mean, `scalar` variance)

### 19.67.1 Constructor & Destructor Documentation

#### 19.67.1.1 NormalDistribution()

```
SpineMLSimulator::ModelProperty::NormalDistribution::NormalDistribution (
    const pugi::xml_node & node,
    const StateVar< scalar > & stateVar,
    unsigned int size )
```

### 19.67.2 Member Function Documentation

#### 19.67.2.1 setValue()

```
void SpineMLSimulator::ModelProperty::NormalDistribution::setValue (
    scalar mean,
    scalar variance )
```

The documentation for this class was generated from the following files:

- [modelProperty.h](#)
- [modelProperty.cc](#)

## 19.68 CodeGenerator::CodeStream::OB Struct Reference

An open bracket marker.

```
#include <codeStream.h>
```

### Public Member Functions

- [OB](#) (unsigned int level)

### Public Attributes

- const unsigned int [Level](#)

#### 19.68.1 Detailed Description

An open bracket marker.

Write to code stream `os` using:

```
os << OB(16);
```

#### 19.68.2 Constructor & Destructor Documentation

##### 19.68.2.1 OB()

```
CodeGenerator::CodeStream::OB::OB (  
    unsigned int level ) [inline]
```

#### 19.68.3 Member Data Documentation

##### 19.68.3.1 Level

```
const unsigned int CodeGenerator::CodeStream::OB::Level
```

The documentation for this struct was generated from the following file:


- [codeStream.h](#)

## 19.69 InitSparseConnectivitySnippet::OneToOne Class Reference

Initialises connectivity to a 'one-to-one' diagonal matrix.

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::OneToOne:



## Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitSparseConnectivitySnippet::OneToOne](#), 0)
- [SET\\_ROW\\_BUILD\\_CODE](#) ("\$(addSynapse, \$(id\_pre));\n\$(endRow);\n")
- [SET\\_MAX\\_ROW\\_LENGTH](#) (1)
- [SET\\_MAX\\_COL\\_LENGTH](#) (1)

## Additional Inherited Members

### 19.69.1 Detailed Description

Initialises connectivity to a 'one-to-one' diagonal matrix.

### 19.69.2 Member Function Documentation

#### 19.69.2.1 DECLARE\_SNIPPET()

```
InitSparseConnectivitySnippet::OneToOne::DECLARE_SNIPPET (
    InitSparseConnectivitySnippet::OneToOne ,
    0 )
```

#### 19.69.2.2 SET\_MAX\_COL\_LENGTH()

```
InitSparseConnectivitySnippet::OneToOne::SET_MAX_COL_LENGTH (
    1 )
```

#### 19.69.2.3 SET\_MAX\_ROW\_LENGTH()

```
InitSparseConnectivitySnippet::OneToOne::SET_MAX_ROW_LENGTH (
    1 )
```

#### 19.69.2.4 SET\_ROW\_BUILD\_CODE()

```
InitSparseConnectivitySnippet::OneToOne::SET_ROW_BUILD_CODE (
    "$(addSynapse, $(id_pre));\n$(endRow);\n" )
```

The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)



## 19.70 Snippet::Base::ParamVal Struct Reference

Additional input variables, row state variables and other things have a name, a type and an initial value.

```
#include <snippet.h>
```

### Public Attributes

- std::string [name](#)
- std::string [type](#)
- double [value](#)

### 19.70.1 Detailed Description

Additional input variables, row state variables and other things have a name, a type and an initial value.

### 19.70.2 Member Data Documentation

#### 19.70.2.1 name

```
std::string Snippet::Base::ParamVal::name
```

#### 19.70.2.2 type

```
std::string Snippet::Base::ParamVal::type
```

#### 19.70.2.3 value

```
double Snippet::Base::ParamVal::value
```

The documentation for this struct was generated from the following file:


- [snippet.h](#)

## 19.71 WeightUpdateModels::PiecewiseSTDP Class Reference

This is a simple STDP rule including a time delay for the finite transmission speed of the synapse.

```
#include <weightUpdateModels.h>
```

Inheritance diagram for WeightUpdateModels::PiecewiseSTDP:



## Public Member Functions


- `DECLARE_WEIGHT_UPDATE_MODEL` (`PiecewiseSTDP`, 10, 2, 0, 0)
- virtual `StringVec getParamNames ()` const override  
*Gets names of of (independent) model parameters.*
- virtual `VarVec getVars ()` const override  
*Gets names and types (as strings) of model variables.*
- virtual `std::string getSimCode ()` const override  
*Gets simulation code run when 'true' spikes are received.*
- virtual `std::string getLearnPostCode ()` const override  
*Gets code to include in the learnSynapsesPost kernel/function.*
- virtual `DerivedParamVec getDerivedParams ()` const override
- virtual `bool isPreSpikeTimeRequired ()` const override  
*Whether presynaptic spike times are needed or not.*
- virtual `bool isPostSpikeTimeRequired ()` const override  
*Whether postsynaptic spike times are needed or not.*

## Additional Inherited Members

## 19.71.1 Detailed Description

This is a simple STDP rule including a time delay for the finite transmission speed of the synapse.

The STDP window is defined as a piecewise function:



The STDP curve is applied to the raw synaptic conductance  $g_{Raw}$ , which is then filtered through the sigmoidal filter displayed above to obtain the value of  $g$ .

**Note**

The STDP curve implies that unpaired pre- and post-synaptic spikes incur a negative increment in  $g_{Raw}$  (and hence in  $g$ ).

The time of the last spike in each neuron, "sTXX", where XX is the name of a neuron population is (somewhat arbitrarily) initialised to -10.0 ms. If neurons never spike, these spike times are used.

It is the raw synaptic conductance  $g_{Raw}$  that is subject to the STDP rule. The resulting synaptic conductance is a sigmoid filter of  $g_{Raw}$ . This implies that  $g$  is initialised but not  $g_{Raw}$ , the synapse will revert to the value that corresponds to  $g_{Raw}$ .

An example how to use this synapse correctly is given in `map_classol.cc` (MBody1 userproject):

```
for (int i= 0; i < model.neuronN[1]*model.neuronN[3]; i++) {
    if (gKCDN[i] < 2.0*SCALAR_MIN){
        cnt++;
        fprintf(stdout, "Too low conductance value %e detected and set to 2*SCALAR_MIN= %e, at index %d\n", gKCDN[i], 2*SCALAR_MIN, i);
        gKCDN[i] = 2.0*SCALAR_MIN; //to avoid log(0)/0 below
    }
    scalar tmp = gKCDN[i] / myKCDN_p[5]*2.0 ;
    gRawKCDN[i]= 0.5 * log( tmp / (2.0 - tmp)) /myKCDN_p[7] + myKCDN_p[6];
}
cerr << "Total number of low value corrections: " << cnt << endl;
```

**Note**

One cannot set values of  $g$  fully to 0, as this leads to  $g_{Raw} = -\infty$  and this is not support. I.e., 'g' needs to be some nominal value  $> 0$  (but can be extremely small so that it acts like it's 0).

The model has 2 variables:

- $g$ : conductance of scalar type
- $g_{Raw}$ : raw conductance of scalar type

Parameters are (compare to the figure above):

- $t_{Lrn}$ : Time scale of learning changes
- $t_{Chng}$ : Width of learning window
- $t_{Decay}$ : Time scale of synaptic strength decay
- $t_{Punish10}$ : Time window of suppression in response to 1/0
- $t_{Punish01}$ : Time window of suppression in response to 0/1
- $g_{Max}$ : Maximal conductance achievable
- $g_{Mid}$ : Midpoint of sigmoid  $g$  filter curve
- $g_{Slope}$ : Slope of sigmoid  $g$  filter curve
- $\tau_{Shift}$ : Shift of learning curve
- $g_{Syn0}$ : Value of syn conductance  $g$  decays to

**19.71.2 Member Function Documentation**

#### 19.71.2.1 DECLARE\_WEIGHT\_UPDATE\_MODEL()

```
WeightUpdateModels::PiecewiseSTDP::DECLARE_WEIGHT_UPDATE_MODEL (
    PiecewiseSTDP ,
    10 ,
    2 ,
    0 ,
    0 )
```

#### 19.71.2.2 getDerivedParams()

```
virtual DerivedParamVec WeightUpdateModels::PiecewiseSTDP::getDerivedParams ( ) const [inline],
[override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented from [Snippet::Base](#).

#### 19.71.2.3 getLearnPostCode()

```
virtual std::string WeightUpdateModels::PiecewiseSTDP::getLearnPostCode ( ) const [inline],
[override], [virtual]
```

Gets code to include in the learnSynapsesPost kernel/function.

For examples when modelling STDP, this is where the effect of postsynaptic spikes which occur *after* presynaptic spikes are applied.

Reimplemented from [WeightUpdateModels::Base](#).

#### 19.71.2.4 getParamNames()

```
virtual StringVec WeightUpdateModels::PiecewiseSTDP::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

#### 19.71.2.5 getSimCode()

```
virtual std::string WeightUpdateModels::PiecewiseSTDP::getSimCode ( ) const [inline], [override],
[virtual]
```

Gets simulation code run when 'true' spikes are received.

Reimplemented from [WeightUpdateModels::Base](#).

#### 19.71.2.6 getVars()

```
virtual VarVec WeightUpdateModels::PiecewiseSTDP::getVars ( ) const [inline], [override],
[virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

## 19.71.2.7 isPostSpikeTimeRequired()

```
virtual bool WeightUpdateModels::PiecewiseSTDP::isPostSpikeTimeRequired ( ) const [inline],
[override], [virtual]
```

Whether postsynaptic spike times are needed or not.

Reimplemented from [WeightUpdateModels::Base](#).

## 19.71.2.8 isPreSpikeTimeRequired()

```
virtual bool WeightUpdateModels::PiecewiseSTDP::isPreSpikeTimeRequired ( ) const [inline],
[override], [virtual]
```

Whether presynaptic spike times are needed or not.

Reimplemented from [WeightUpdateModels::Base](#).

The documentation for this class was generated from the following file:


- [weightUpdateModels.h](#)

## 19.72 NeuronModels::Poisson Class Reference

[Poisson](#) neurons.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::Poisson:



## Public Types

- typedef [Snippet::ValueBase](#)< 4 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 2 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [VarVec](#) [getVars](#) () const override

*Gets names and types (as strings) of model variables.*

- virtual `EGPVec getExtraGlobalParams ()` const override

#### Static Public Member Functions

- static const `NeuronModels::Poisson * getInstance ()`

#### Additional Inherited Members

##### 19.72.1 Detailed Description

`Poisson` neurons.

`Poisson` neurons have constant membrane potential (`Vrest`) unless they are activated randomly to the `Vspike` value if  $(t - \text{SpikeTime}) > \text{trefract}$ .

It has 2 variables:

- `V` - Membrane potential (mV)
- `SpikeTime` - Time at which the neuron spiked for the last time (ms)

and 4 parameters:

- `trefract` - Refractory period (ms)
- `tspike` - duration of spike (ms)
- `Vspike` - Membrane potential at spike (mV)
- `Vrest` - Membrane potential at rest (mV)

#### Note

The initial values array for the `Poisson` type needs two entries for `V`, and `SpikeTime` and the parameter array needs four entries for `therate`, `trefract`, `Vspike` and `Vrest`, *in that order*.

This model uses a linear approximation for the probability of firing a spike in a given time step of size `DT`, i.e. the probability of firing is  $\lambda$  times `DT`:  $p = \lambda \Delta t$ . This approximation is usually very good, especially for typical, quite small time steps and moderate firing rates. However, it is worth noting that the approximation becomes poor for very high firing rates and large time steps.

##### 19.72.2 Member Typedef Documentation

###### 19.72.2.1 ParamValues

```
typedef Snippet::ValueBase< 4 > NeuronModels::Poisson::ParamValues
```

###### 19.72.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::Poisson::PostVarValues
```

## 19.72.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::Poisson::PreVarValues
```

## 19.72.2.4 VarValues

```
typedef Models::VarInitContainerBase< 2 > NeuronModels::Poisson::VarValues
```

## 19.72.3 Member Function Documentation

## 19.72.3.1 getExtraGlobalParams()

```
virtual EGPVec NeuronModels::Poisson::getExtraGlobalParams ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of additional per-population parameters for the weight update model.

Reimplemented from [Models::Base](#).

## 19.72.3.2 getInstance()

```
static const NeuronModels::Poisson\* NeuronModels::Poisson::getInstance ( ) [inline], [static]
```

## 19.72.3.3 getParamNames()

```
virtual StringVec NeuronModels::Poisson::getParamNames ( ) const [inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

## 19.72.3.4 getSimCode()

```
virtual std::string NeuronModels::Poisson::getSimCode ( ) const [inline], [override], [virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

## 19.72.3.5 getThresholdConditionCode()

```
virtual std::string NeuronModels::Poisson::getThresholdConditionCode ( ) const [inline], [override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

### 19.72.3.6 getVars()

```
virtual VarVec NeuronModels::Poisson::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.73 NeuronModels::PoissonNew Class Reference

[Poisson](#) neurons.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::PoissonNew:



### Public Types

- typedef [Snippet::ValueBase](#)< 1 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 1 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

### Public Member Functions

- virtual std::string [getSimCode](#) ( ) const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) ( ) const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual [StringVec](#) [getParamNames](#) ( ) const override  
*Gets names of of (independent) model parameters.*
- virtual [VarVec](#) [getVars](#) ( ) const override  
*Gets names and types (as strings) of model variables.*
- virtual [DerivedParamVec](#) [getDerivedParams](#) ( ) const override
- [SET\\_NEEDS\\_AUTO\\_REFRACTORY](#) (false)

### Static Public Member Functions

- static const [NeuronModels::PoissonNew](#) \* [getInstance](#) ( )



## Additional Inherited Members

### 19.73.1 Detailed Description

Poisson neurons.

It has 1 state variable:

- `timeStepToSpike` - Number of timesteps to next spike

and 1 parameter:

- `rate` - Mean firing rate (Hz)

## Note

Internally this samples from the exponential distribution using the C++ 11 `<random>` library on the CPU and by transforming the uniform distribution, generated using `cuRAND`, with a natural log on the GPU.

### 19.73.2 Member Typedef Documentation

#### 19.73.2.1 ParamValues

```
typedef Snippet::ValueBase< 1 > NeuronModels::PoissonNew::ParamValues
```

#### 19.73.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::PoissonNew::PostVarValues
```

#### 19.73.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::PoissonNew::PreVarValues
```

#### 19.73.2.4 VarValues

```
typedef Models::VarInitContainerBase< 1 > NeuronModels::PoissonNew::VarValues
```

### 19.73.3 Member Function Documentation

#### 19.73.3.1 getDerivedParams()

```
virtual DerivedParamVec NeuronModels::PoissonNew::getDerivedParams ( ) const [inline], [override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented from [Snippet::Base](#).

#### 19.73.3.2 getInstance()

```
static const NeuronModels::PoissonNew* NeuronModels::PoissonNew::getInstance ( ) [inline],  
[static]
```

#### 19.73.3.3 getParamNames()

```
virtual StringVec NeuronModels::PoissonNew::getParamNames ( ) const [inline], [override],  
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

#### 19.73.3.4 getSimCode()

```
virtual std::string NeuronModels::PoissonNew::getSimCode ( ) const [inline], [override],  
[virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

#### 19.73.3.5 getThresholdConditionCode()

```
virtual std::string NeuronModels::PoissonNew::getThresholdConditionCode ( ) const [inline],  
[override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

#### 19.73.3.6 getVars()

```
virtual VarVec NeuronModels::PoissonNew::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

#### 19.73.3.7 SET\_NEEDS\_AUTO\_REFRACTORY()

```
NeuronModels::PoissonNew::SET_NEEDS_AUTO_REFRACTORY (   
    false )
```


The documentation for this class was generated from the following file:

- [neuronModels.h](#)

### 19.74 SpineMLSimulator::Input::PoissonSpikeRate Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::PoissonSpikeRate:



#### Public Member Functions

- [PoissonSpikeRate](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value, unsigned int popSize, unsigned int \*spikeQueuePtr, unsigned int \*hostSpikeCount, unsigned int \*hostSpikes, [PushCurrentSpikesFunc](#) pushCurrentSpikes)

#### Protected Member Functions

- virtual double [getTimeToSpike](#) (double isiMs)

#### Additional Inherited Members

#### 19.74.1 Constructor & Destructor Documentation

##### 19.74.1.1 PoissonSpikeRate()

```

SpineMLSimulator::Input::PoissonSpikeRate::PoissonSpikeRate (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value,
    unsigned int popSize,
    unsigned int * spikeQueuePtr,
    unsigned int * hostSpikeCount,
    unsigned int * hostSpikes,
    PushCurrentSpikesFunc pushCurrentSpikes )

```

#### 19.74.2 Member Function Documentation

##### 19.74.2.1 getTimeToSpike()

```

double SpineMLSimulator::Input::PoissonSpikeRate::getTimeToSpike (
    double isiMs ) [protected], [virtual]

```

Implements [SpineMLSimulator::Input::InterSpikeIntervalBase](#).

The documentation for this class was generated from the following files:


- [input.h](#)
- [input.cc](#)

## 19.75 CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan Class Reference

Postsynaptic parallelism.

```
#include <presynapticUpdateStrategy.h>
```

Inheritance diagram for CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan:



### Public Member Functions

- virtual `size_t` `getNumThreads` (const `SynapseGroupInternal` &sg) const override  
*Get the number of threads that presynaptic updates should be parallelised across.*
- virtual `size_t` `getSynapticMatrixRowStride` (const `SynapseGroupInternal` &sg) const override  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual `bool` `isCompatible` (const `SynapseGroupInternal` &sg, const `cudaDeviceProp` &deviceProps, const `Preferences` &preferences) const override  
*Is this presynaptic update strategy compatible with a given synapse group?*
- virtual `size_t` `getSharedMemoryPerThread` (const `SynapseGroupInternal` &sg, const `Backend` &backend) const override  
*How many neurons does each thread accumulate the outputs of into shared memory.*
- virtual `void` `genPreamble` (`CodeStream` &os, const `ModelSpecInternal` &model, const `SynapseGroupInternal` &sg, const `Substitutions` &popSubs, const `Backend` &backend, `size_t` idStart) const override
- virtual `void` `genUpdate` (`CodeStream` &os, const `ModelSpecInternal` &model, const `SynapseGroupInternal` &sg, const `Substitutions` &popSubs, const `Backend` &backend, `bool` trueSpike, `size_t` idStart, `BackendBase::SynapseGroupHandler` wumThreshHandler, `BackendBase::SynapseGroupHandler` wumSimHandler, `BackendBase::SynapseGroupHandler` wumProceduralConnectHandler) const override  
*Generate presynaptic update code.*
- virtual `void` `genPostamble` (`CodeStream` &os, const `ModelSpecInternal` &model, const `SynapseGroupInternal` &sg, const `Substitutions` &popSubs, const `Backend` &backend, `size_t` idStart) const override

### 19.75.1 Detailed Description

Postsynaptic parallelism.

### 19.75.2 Member Function Documentation

#### 19.75.2.1 genPostamble()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::genPostamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements `CodeGenerator::CUDA::PresynapticUpdateStrategy::Base`.

## 19.75.2.2 genPreamble()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::genPreamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.75.2.3 genUpdate()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::genUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    bool trueSpike,
    size_t idStart,
    BackendBase::SynapseGroupHandler wumThreshHandler,
    BackendBase::SynapseGroupHandler wumSimHandler,
    BackendBase::SynapseGroupHandler wumProceduralConnectHandler ) const [override],
[virtual]
```

Generate presynaptic update code.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.75.2.4 getNumThreads()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::getNumThreads (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Get the number of threads that presynaptic updates should be parallelised across.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.75.2.5 getSharedMemoryPerThread()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::getSharedMemoryPerThread (
    const SynapseGroupInternal & sg,
    const Backend & backend ) const [override], [virtual]
```

How many neurons does each thread accumulate the outputs of into shared memory.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.75.2.6 getSynapticMatrixRowStride()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.75.2.7 isCompatible()

```
bool CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan::isCompatible (
    const SynapseGroupInternal & sg,
    const cudaDeviceProp & deviceProps,
    const Preferences & preferences ) const [override], [virtual]
```

Is this presynaptic update strategy compatible with a given synapse group?

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

The documentation for this class was generated from the following files:


- [presynapticUpdateStrategy.h](#)
- [presynapticUpdateStrategy.cc](#)

## 19.76 CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask Class Reference

Postsynaptic parallelism.

```
#include <presynapticUpdateStrategy.h>
```

Inheritance diagram for CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask:



### Public Member Functions

- virtual size\_t [getNumThreads](#) (const [SynapseGroupInternal](#) &sg) const override  
*Get the number of threads that presynaptic updates should be parallelised across.*
- virtual size\_t [getSynapticMatrixRowStride](#) (const [SynapseGroupInternal](#) &sg) const override  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual bool [isCompatible](#) (const [SynapseGroupInternal](#) &sg, const cudaDeviceProp &deviceProps, const [Preferences](#) &preferences) const override  
*Is this presynaptic update strategy compatible with a given synapse group?*
- virtual size\_t [getSharedMemoryPerThread](#) (const [SynapseGroupInternal](#) &sg, const [Backend](#) &backend) const override  
*How many neurons does each thread accumulate the outputs of into shared memory.*
- virtual void [genPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const override
- virtual void [genUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, bool trueSpike, size\_t idStart, [BackendBase::SynapseGroupHandler](#) wumThreshHandler, [BackendBase::SynapseGroupHandler](#) wumSimHandler, [BackendBase::SynapseGroupHandler](#) wumProceduralConnectHandler) const override  
*Generate presynaptic update code.*
- virtual void [genPostamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const override

### 19.76.1 Detailed Description

Postsynaptic parallelism.

## 19.76.2 Member Function Documentation

## 19.76.2.1 genPostamble()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::genPostamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.76.2.2 genPreamble()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::genPreamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.76.2.3 genUpdate()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::genUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    bool trueSpike,
    size_t idStart,
    BackendBase::SynapseGroupHandler wumThreshHandler,
    BackendBase::SynapseGroupHandler wumSimHandler,
    BackendBase::SynapseGroupHandler wumProceduralConnectHandler ) const [override],
[virtual]
```

Generate presynaptic update code.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

## 19.76.2.4 getNumThreads()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::getNumThreads (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Get the number of threads that presynaptic updates should be parallelised across.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.76.2.5 getSharedMemoryPerThread()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::getSharedMemoryPerThread (
    const SynapseGroupInternal & sg,
    const Backend & backend ) const [override], [virtual]
```

How many neurons does each thread accumulate the outputs of into shared memory.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.76.2.6 getSynapticMatrixRowStride()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.76.2.7 isCompatible()

```
bool CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask::isCompatible (
    const SynapseGroupInternal & sg,
    const cudaDeviceProp & deviceProps,
    const Preferences & preferences ) const [override], [virtual]
```

Is this presynaptic update strategy compatible with a given synapse group?

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

The documentation for this class was generated from the following files:


- [presynapticUpdateStrategy.h](#)
- [presynapticUpdateStrategy.cc](#)

## 19.77 CodeGenerator::CUDA::Preferences Struct Reference

[Preferences](#) for [CUDA](#) backend.

```
#include <backend.h>
```

Inheritance diagram for CodeGenerator::CUDA::Preferences:



### Public Member Functions

- [Preferences](#) ()

### Public Attributes

- bool [showPtxInfo](#) = false



*Should PTX assembler information be displayed for each [CUDA](#) kernel during compilation?*

- bool [generateLineInfo](#) = false

*Should line info be included in resultant executable for debugging/profiling purposes?*

- [DeviceSelect](#) [deviceSelectMethod](#) = [DeviceSelect::OPTIMAL](#)

*How to select GPU device.*

- unsigned int [manualDeviceID](#) = 0

*If device select method is set to [DeviceSelect::MANUAL](#), id of device to use.*

- [BlockSizeSelect](#) [blockSizeSelectMethod](#) = [BlockSizeSelect::OCCUPANCY](#)

*How to select [CUDA](#) blocksize.*

- [KernelBlockSize](#) [manualBlockSizes](#)

*If block size select method is set to [BlockSizeSelect::MANUAL](#), block size to use for each kernel.*

- std::string [userNvccFlags](#) = ""

*NVCC compiler options for all GPU code.*

### 19.77.1 Detailed Description

[Preferences](#) for [CUDA](#) backend.

### 19.77.2 Constructor & Destructor Documentation

#### 19.77.2.1 Preferences()

```
CodeGenerator::CUDA::Preferences::Preferences ( ) [inline]
```

### 19.77.3 Member Data Documentation

#### 19.77.3.1 blockSizeSelectMethod

[BlockSizeSelect](#) CodeGenerator::CUDA::Preferences::blockSizeSelectMethod = [BlockSizeSelect::OCCUPANCY](#)

How to select [CUDA](#) blocksize.

#### 19.77.3.2 deviceSelectMethod

[DeviceSelect](#) CodeGenerator::CUDA::Preferences::deviceSelectMethod = [DeviceSelect::OPTIMAL](#)

How to select GPU device.

#### 19.77.3.3 generateLineInfo

```
bool CodeGenerator::CUDA::Preferences::generateLineInfo = false
```

Should line info be included in resultant executable for debugging/profiling purposes?

### 19.77.3.4 manualBlockSizes

`KernelBlockSize` `CodeGenerator::CUDA::Preferences::manualBlockSizes`

If block size select method is set to `BlockSizeSelect::MANUAL`, block size to use for each kernel.

### 19.77.3.5 manualDeviceID

`unsigned int` `CodeGenerator::CUDA::Preferences::manualDeviceID` = 0

If device select method is set to `DeviceSelect::MANUAL`, id of device to use.

### 19.77.3.6 showPtxInfo

`bool` `CodeGenerator::CUDA::Preferences::showPtxInfo` = false

Should PTX assembler information be displayed for each `CUDA` kernel during compilation?

### 19.77.3.7 userNvccFlags

`std::string` `CodeGenerator::CUDA::Preferences::userNvccFlags` = ""

NVCC compiler options for all GPU code.


The documentation for this struct was generated from the following file:

- [cuda/backend.h](#)

## 19.78 CodeGenerator::SingleThreadedCPU::Preferences Struct Reference

```
#include <backend.h>
```

Inheritance diagram for `CodeGenerator::SingleThreadedCPU::Preferences`:



### Additional Inherited Members

The documentation for this struct was generated from the following file:


- [single\\_threaded\\_cpu/backend.h](#)

## 19.79 CodeGenerator::PreferencesBase Struct Reference

Base class for backend preferences - can be accessed via a global in 'classic' C++ code generator.

```
#include <backendBase.h>
```

Inheritance diagram for `CodeGenerator::PreferencesBase`:



### Public Attributes

- bool `optimizeCode` = false  
*Generate speed-optimized code, potentially at the expense of floating-point accuracy.*
- bool `debugCode` = false  
*Generate code with debug symbols.*
- bool `enableBitmaskOptimisations` = false
- bool `automaticCopy` = false  
*If backend/device supports it, copy data automatically when required rather than requiring push and pull.*
- std::string `userCxxFlagsGNU` = ""  
*C++ compiler options to be used for building all host side code (used for unix based platforms)*
- std::string `userNvccFlagsGNU` = ""  
*NVCC compiler options they may want to use for all GPU code (used for unix based platforms)*
- plog::Severity `logLevel` = plog::info  
*Logging level to use for code generation.*

#### 19.79.1 Detailed Description

Base class for backend preferences - can be accessed via a global in 'classic' C++ code generator.

#### 19.79.2 Member Data Documentation

##### 19.79.2.1 automaticCopy

```
bool CodeGenerator::PreferencesBase::automaticCopy = false
```

If backend/device supports it, copy data automatically when required rather than requiring push and pull.

##### 19.79.2.2 debugCode

```
bool CodeGenerator::PreferencesBase::debugCode = false
```

Generate code with debug symbols.

##### 19.79.2.3 enableBitmaskOptimisations

```
bool CodeGenerator::PreferencesBase::enableBitmaskOptimisations = false
```

New optimizations made to kernels for simulating synapse groups with BITMASK connectivity Improve performance but break backward compatibility due to word-padding each row

##### 19.79.2.4 logLevel

```
plog::Severity CodeGenerator::PreferencesBase::logLevel = plog::info
```

Logging level to use for code generation.

### 19.79.2.5 optimizeCode

```
bool CodeGenerator::PreferencesBase::optimizeCode = false
```

Generate speed-optimized code, potentially at the expense of floating-point accuracy.

### 19.79.2.6 userCxxFlagsGNU

```
std::string CodeGenerator::PreferencesBase::userCxxFlagsGNU = ""
```

C++ compiler options to be used for building all host side code (used for unix based platforms)

### 19.79.2.7 userNvccFlagsGNU

```
std::string CodeGenerator::PreferencesBase::userNvccFlagsGNU = ""
```

NVCC compiler options they may want to use for all GPU code (used for unix based platforms)

The documentation for this struct was generated from the following file:


- [backendBase.h](#)

## 19.80 CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan Class Reference

Presynaptic parallelism.

```
#include <presynapticUpdateStrategy.h>
```

Inheritance diagram for CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan:



### Public Member Functions

- virtual `size_t` [getNumThreads](#) (const [SynapseGroupInternal](#) &sg) const override  
*Get the number of threads that presynaptic updates should be parallelised across.*
- virtual `size_t` [getSynapticMatrixRowStride](#) (const [SynapseGroupInternal](#) &sg) const override  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual `bool` [isCompatible](#) (const [SynapseGroupInternal](#) &sg, const `cudaDeviceProp` &deviceProps, const [Preferences](#) &preferences) const override  
*Is this presynaptic update strategy compatible with a given synapse group?*
- virtual `size_t` [getSharedMemoryPerThread](#) (const [SynapseGroupInternal](#) &sg, const [Backend](#) &backend) const override  
*How many neurons does each thread accumulate the outputs of into shared memory.*
- virtual `void` [genPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, `size_t` idStart) const override
- virtual `void` [genUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, `bool` trueSpike, `size_t` idStart, [BackendBase::SynapseGroupHandler](#) wumThreshHandler, [BackendBase::SynapseGroupHandler](#) wumSimHandler, [BackendBase::SynapseGroupHandler](#) wumProceduralConnectHandler) const override  
*Generate presynaptic update code.*

- virtual void [genPostamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const override

### 19.80.1 Detailed Description

Presynaptic parallelism.

### 19.80.2 Member Function Documentation

#### 19.80.2.1 genPostamble()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::genPostamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

#### 19.80.2.2 genPreamble()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::genPreamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

#### 19.80.2.3 genUpdate()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::genUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    bool trueSpike,
    size_t idStart,
    BackendBase::SynapseGroupHandler wumThreshHandler,
    BackendBase::SynapseGroupHandler wumSimHandler,
    BackendBase::SynapseGroupHandler wumProceduralConnectHandler ) const [override],
[virtual]
```

Generate presynaptic update code.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

#### 19.80.2.4 `getNumThreads()`

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::getNumThreads (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Get the number of threads that presynaptic updates should be parallelised across.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

#### 19.80.2.5 `getSharedMemoryPerThread()`

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::getSharedMemoryPerThread (
    const SynapseGroupInternal & sg,
    const Backend & backend ) const [override], [virtual]
```

How many neurons does each thread accumulate the outputs of into shared memory.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

#### 19.80.2.6 `getSynapticMatrixRowStride()`

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

#### 19.80.2.7 `isCompatible()`

```
bool CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan::isCompatible (
    const SynapseGroupInternal & sg,
    const cudaDeviceProp & deviceProps,
    const Preferences & preferences ) const [override], [virtual]
```

Is this presynaptic update strategy compatible with a given synapse group?

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

The documentation for this class was generated from the following files:


- [presynapticUpdateStrategy.h](#)
- [presynapticUpdateStrategy.cc](#)

### 19.81 `CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural` Class Reference

Presynaptic parallelism with procedural connectivity.

```
#include <presynapticUpdateStrategy.h>
```

Inheritance diagram for `CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural`:



## Public Member Functions

- virtual size\_t [getNumThreads](#) (const [SynapseGroupInternal](#) &sg) const override  
*Get the number of threads that presynaptic updates should be parallelised across.*
- virtual size\_t [getSynapticMatrixRowStride](#) (const [SynapseGroupInternal](#) &sg) const override  
*Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.*
- virtual bool [isCompatible](#) (const [SynapseGroupInternal](#) &sg, const cudaDeviceProp &deviceProps, const [Preferences](#) &preferences) const override  
*Is this presynaptic update strategy compatible with a given synapse group?*
- virtual size\_t [getSharedMemoryPerThread](#) (const [SynapseGroupInternal](#) &sg, const [Backend](#) &backend) const override  
*How many neurons does each thread accumulate the outputs of into shared memory.*
- virtual void [genPreamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const override
- virtual void [genUpdate](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, bool trueSpike, size\_t idStart, [BackendBase::SynapseGroupHandler](#) wumThreshHandler, [BackendBase::SynapseGroupHandler](#) wumSimHandler, [BackendBase::SynapseGroupHandler](#) wumProceduralConnectHandler) const override  
*Generate presynaptic update code.*
- virtual void [genPostamble](#) ([CodeStream](#) &os, const [ModelSpecInternal](#) &model, const [SynapseGroupInternal](#) &sg, const [Substitutions](#) &popSubs, const [Backend](#) &backend, size\_t idStart) const override

## 19.81.1 Detailed Description

Presynaptic parallelism with procedural connectivity.

## 19.81.2 Member Function Documentation

19.81.2.1 [genPostamble\(\)](#)

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::genPostamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

19.81.2.2 [genPreamble\(\)](#)

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::genPreamble (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    size_t idStart ) const [override], [virtual]
```

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.81.2.3 genUpdate()

```
void CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::genUpdate (
    CodeStream & os,
    const ModelSpecInternal & model,
    const SynapseGroupInternal & sg,
    const Substitutions & popSubs,
    const Backend & backend,
    bool trueSpike,
    size_t idStart,
    BackendBase::SynapseGroupHandler wumThreshHandler,
    BackendBase::SynapseGroupHandler wumSimHandler,
    BackendBase::SynapseGroupHandler wumProceduralConnectHandler ) const [override],
[virtual]
```

Generate presynaptic update code.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.81.2.4 getNumThreads()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::getNumThreads (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Get the number of threads that presynaptic updates should be parallelised across.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.81.2.5 getSharedMemoryPerThread()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::getSharedMemoryPerThread (
    const SynapseGroupInternal & sg,
    const Backend & backend ) const [override], [virtual]
```

How many neurons does each thread accumulate the outputs of into shared memory.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.81.2.6 getSynapticMatrixRowStride()

```
size_t CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::getSynapticMatrixRowStride (
    const SynapseGroupInternal & sg ) const [override], [virtual]
```

Gets the stride used to access synaptic matrix rows, taking into account sparse data structure, padding etc.

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).

### 19.81.2.7 isCompatible()

```
bool CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural::isCompatible (
    const SynapseGroupInternal & sg,
    const cudaDeviceProp & deviceProps,
    const Preferences & preferences ) const [override], [virtual]
```

Is this presynaptic update strategy compatible with a given synapse group?

Implements [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#).




The documentation for this class was generated from the following files:

- [presynapticUpdateStrategy.h](#)
- [presynapticUpdateStrategy.cc](#)

## 19.82 SpineMLSimulator::Input::RegularSpikeRate Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::RegularSpikeRate:



### Public Member Functions

- [RegularSpikeRate](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value, unsigned int popSize, unsigned int \*spikeQueuePtr, unsigned int \*hostSpikeCount, unsigned int \*hostSpikes, [PushCurrentSpikesFunc](#) pushCurrentSpikes)

### Protected Member Functions

- virtual double [getTimeToSpike](#) (double isiMs) override

### Additional Inherited Members

#### 19.82.1 Constructor & Destructor Documentation

##### 19.82.1.1 RegularSpikeRate()

```

SpineMLSimulator::Input::RegularSpikeRate::RegularSpikeRate (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value,
    unsigned int popSize,
    unsigned int * spikeQueuePtr,
    unsigned int * hostSpikeCount,
    unsigned int * hostSpikes,
    PushCurrentSpikesFunc pushCurrentSpikes )

```

#### 19.82.2 Member Function Documentation

### 19.82.2.1 getTimeToSpike()

```
double SpineMLSimulator::Input::RegularSpikeRate::getTimeToSpike (
    double isiMs ) [override], [protected], [virtual]
```

Implements [SpineMLSimulator::Input::InterSpikeIntervalBase](#).

The documentation for this class was generated from the following files:


- [input.h](#)
- [input.cc](#)

## 19.83 NeuronModels::RulkovMap Class Reference

Rulkov Map neuron.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::RulkovMap:



### Public Types

- typedef [Snippet::ValueBase](#)< 4 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 2 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

### Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [VarVec](#) [getVars](#) () const override  
*Gets names and types (as strings) of model variables.*
- virtual [DerivedParamVec](#) [getDerivedParams](#) () const override

### Static Public Member Functions

- static const [NeuronModels::RulkovMap](#) \* [getInstance](#) ()

## Additional Inherited Members

## 19.83.1 Detailed Description

Rulkov Map neuron.

The [RulkovMap](#) type is a map based neuron model based on [5] but in the 1-dimensional map form used in [4] :

$$V(t + \Delta t) = \begin{cases} V_{\text{spike}} \left( \frac{\alpha V_{\text{spike}}}{V_{\text{spike}} - V(t) \beta I_{\text{syn}}} + y \right) & V(t) \leq 0 \\ V_{\text{spike}} (\alpha + y) & V(t) \leq V_{\text{spike}} (\alpha + y) \ \& \ V(t - \Delta t) \leq 0 \\ -V_{\text{spike}} & \text{otherwise} \end{cases}$$

## Note

The [RulkovMap](#) type only works as intended for the single time step size of  $\Delta T = 0.5$ .

The [RulkovMap](#) type has 2 variables:

- `V` - the membrane potential
- `preV` - the membrane potential at the previous time step

and it has 4 parameters:

- `Vspike` - determines the amplitude of spikes, typically -60mV
- `alpha` - determines the shape of the iteration function, typically  $\alpha = 3$
- `y` - "shift / excitation" parameter, also determines the iteration function, originally,  $y = -2.468$
- `beta` - roughly speaking equivalent to the input resistance, i.e. it regulates the scale of the input into the neuron, typically  $\beta = 2.64 \text{ M}\Omega$ .

## Note

The initial values array for the [RulkovMap](#) type needs two entries for `V` and `Vpre` and the parameter array needs four entries for `Vspike`, `alpha`, `y` and `beta`, *in that order*.

## 19.83.2 Member Typedef Documentation

## 19.83.2.1 ParamValues

```
typedef Snippet::ValueBase< 4 > NeuronModels::RulkovMap::ParamValues
```

## 19.83.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::RulkovMap::PostVarValues
```

## 19.83.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::RulkovMap::PreVarValues
```

#### 19.83.2.4 VarValues

```
typedef Models::VarInitContainerBase< 2 > NeuronModels::RulkovMap::VarValues
```

### 19.83.3 Member Function Documentation

#### 19.83.3.1 getDerivedParams()

```
virtual DerivedParamVec NeuronModels::RulkovMap::getDerivedParams ( ) const [inline], [override], [virtual]
```

Gets names of derived model parameters and the function objects to call to Calculate their value from a vector of model parameter values

Reimplemented from [Snippet::Base](#).

#### 19.83.3.2 getInstance()

```
static const NeuronModels::RulkovMap\* NeuronModels::RulkovMap::getInstance ( ) [inline], [static]
```

#### 19.83.3.3 getParamNames()

```
virtual StringVec NeuronModels::RulkovMap::getParamNames ( ) const [inline], [override], [virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

#### 19.83.3.4 getSimCode()

```
virtual std::string NeuronModels::RulkovMap::getSimCode ( ) const [inline], [override], [virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

#### 19.83.3.5 getThresholdConditionCode()

```
virtual std::string NeuronModels::RulkovMap::getThresholdConditionCode ( ) const [inline], [override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

#### 19.83.3.6 getVars()

```
virtual VarVec NeuronModels::RulkovMap::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).


The documentation for this class was generated from the following file:

- [neuronModels.h](#)

## 19.84 SpineMLSimulator::InputValue::ScalarBase Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::ScalarBase:



### Protected Member Functions

- [ScalarBase](#) (unsigned int numNeurons, const pugi::xml\_node &node)
- void [applyScalar](#) (double value, std::function< void(unsigned int, double)> applyValueFunc) const

### Additional Inherited Members

#### 19.84.1 Constructor & Destructor Documentation

##### 19.84.1.1 ScalarBase()

```
SpineMLSimulator::InputValue::ScalarBase::ScalarBase (
    unsigned int numNeurons,
    const pugi::xml_node & node ) [inline], [protected]
```

#### 19.84.2 Member Function Documentation

##### 19.84.2.1 applyScalar()

```
void SpineMLSimulator::InputValue::ScalarBase::applyScalar (
    double value,
    std::function< void(unsigned int, double)> applyValueFunc ) const [protected]
```

The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

## 19.85 CodeGenerator::CodeStream::Scope Class Reference

```
#include <codeStream.h>
```

## Public Member Functions

- [Scope](#) ([CodeStream](#) &codeStream)
- [~Scope](#) ()

### 19.85.1 Constructor & Destructor Documentation

#### 19.85.1.1 Scope()

```
CodeGenerator::CodeStream::Scope::Scope (
    CodeStream & codeStream ) [inline]
```

#### 19.85.1.2 ~Scope()

```
CodeGenerator::CodeStream::Scope::~~Scope ( ) [inline]
```

The documentation for this class was generated from the following files:

- [codeStream.h](#)
- [codeStream.cc](#)

### 19.86 SharedLibraryModel< scalar > Class Template Reference

```
#include <sharedLibraryModel.h>
```

## Public Member Functions

- [SharedLibraryModel](#) ()
- [SharedLibraryModel](#) (const std::string &pathToModel, const std::string &modelName)
- virtual [~SharedLibraryModel](#) ()
- bool [open](#) (const std::string &pathToModel, const std::string &modelName)
- void [allocateExtraGlobalParam](#) (const std::string &popName, const std::string &varName, unsigned int count)
- void [freeExtraGlobalParam](#) (const std::string &popName, const std::string &varName)
- void [pullStateFromDevice](#) (const std::string &popName)
- void [pullSpikesFromDevice](#) (const std::string &popName)
- void [pullCurrentSpikesFromDevice](#) (const std::string &popName)
- void [pullConnectivityFromDevice](#) (const std::string &popName)
- void [pullVarFromDevice](#) (const std::string &popName, const std::string &varName)
- void [pullExtraGlobalParam](#) (const std::string &popName, const std::string &varName, unsigned int count)
- void [pushStateToDevice](#) (const std::string &popName, bool uninitialisedOnly=false)
- void [pushSpikesToDevice](#) (const std::string &popName, bool uninitialisedOnly=false)
- void [pushCurrentSpikesToDevice](#) (const std::string &popName, bool uninitialisedOnly=false)
- void [pushConnectivityToDevice](#) (const std::string &popName, bool uninitialisedOnly=false)
- void [pushVarToDevice](#) (const std::string &popName, const std::string &varName, bool uninitialisedOnly=false)
- void [pushExtraGlobalParam](#) (const std::string &popName, const std::string &varName, unsigned int count)
- template<typename T >  
T \* [getArray](#) (const std::string &varName)
- template<typename T >  
T \* [getScalar](#) (const std::string &varName)
- void [allocateMem](#) ()
- void [freeMem](#) ()
- size\_t [getFreeDeviceMemBytes](#) ()

- void `initialize()`
- void `initializeSparse()`
- void `stepTime()`
- scalar `getTime()` const
- unsigned long long `getTimestep()` const
- void `setTime`(scalar t)
- void `setTimestep`(unsigned long long iT)
- double `getNeuronUpdateTime()` const
- double `getInitTime()` const
- double `getPresynapticUpdateTime()` const
- double `getPostsynapticUpdateTime()` const
- double `getSynapseDynamicsTime()` const
- double `getInitSparseTime()` const
- void \* `getSymbol`(const std::string &symbolName, bool allowMissing=false, void \*defaultSymbol=nullptr) const

### 19.86.1 Constructor & Destructor Documentation

#### 19.86.1.1 SharedLibraryModel() [1/2]

```
template<typename scalar = float>
SharedLibraryModel< scalar >::SharedLibraryModel ( ) [inline]
```

#### 19.86.1.2 SharedLibraryModel() [2/2]

```
template<typename scalar = float>
SharedLibraryModel< scalar >::SharedLibraryModel (
    const std::string & pathToModel,
    const std::string & modelName ) [inline]
```

#### 19.86.1.3 ~SharedLibraryModel()

```
template<typename scalar = float>
virtual SharedLibraryModel< scalar >::~~SharedLibraryModel ( ) [inline], [virtual]
```

### 19.86.2 Member Function Documentation

#### 19.86.2.1 allocateExtraGlobalParam()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::allocateExtraGlobalParam (
    const std::string & popName,
    const std::string & varName,
    unsigned int count ) [inline]
```

#### 19.86.2.2 allocateMem()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::allocateMem ( ) [inline]
```

### 19.86.2.3 freeExtraGlobalParam()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::freeExtraGlobalParam (
    const std::string & popName,
    const std::string & varName ) [inline]
```

### 19.86.2.4 freeMem()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::freeMem ( ) [inline]
```

### 19.86.2.5 getArray()

```
template<typename scalar = float>
template<typename T >
T* SharedLibraryModel< scalar >::getArray (
    const std::string & varName ) [inline]
```

### 19.86.2.6 getFreeDeviceMemBytes()

```
template<typename scalar = float>
size_t SharedLibraryModel< scalar >::getFreeDeviceMemBytes ( ) [inline]
```

### 19.86.2.7 getInitSparseTime()

```
template<typename scalar = float>
double SharedLibraryModel< scalar >::getInitSparseTime ( ) const [inline]
```

### 19.86.2.8 getInitTime()

```
template<typename scalar = float>
double SharedLibraryModel< scalar >::getInitTime ( ) const [inline]
```

### 19.86.2.9 getNeuronUpdateTime()

```
template<typename scalar = float>
double SharedLibraryModel< scalar >::getNeuronUpdateTime ( ) const [inline]
```

### 19.86.2.10 getPostsynapticUpdateTime()

```
template<typename scalar = float>
double SharedLibraryModel< scalar >::getPostsynapticUpdateTime ( ) const [inline]
```

### 19.86.2.11 getPresynapticUpdateTime()

```
template<typename scalar = float>
```



```
double SharedLibraryModel< scalar >::getPresynapticUpdateTime ( ) const [inline]
```

#### 19.86.2.12 getScalar()

```
template<typename scalar = float>
template<typename T >
T* SharedLibraryModel< scalar >::getScalar (
    const std::string & varName ) [inline]
```

#### 19.86.2.13 getSymbol()

```
template<typename scalar = float>
void* SharedLibraryModel< scalar >::getSymbol (
    const std::string & symbolName,
    bool allowMissing = false,
    void * defaultSymbol = nullptr ) const [inline]
```

#### 19.86.2.14 getSynapseDynamicsTime()

```
template<typename scalar = float>
double SharedLibraryModel< scalar >::getSynapseDynamicsTime ( ) const [inline]
```

#### 19.86.2.15 getTime()

```
template<typename scalar = float>
scalar SharedLibraryModel< scalar >::getTime ( ) const [inline]
```

#### 19.86.2.16 getTimestep()

```
template<typename scalar = float>
unsigned long long SharedLibraryModel< scalar >::getTimestep ( ) const [inline]
```

#### 19.86.2.17 initialize()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::initialize ( ) [inline]
```

#### 19.86.2.18 initializeSparse()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::initializeSparse ( ) [inline]
```

#### 19.86.2.19 open()

```
template<typename scalar = float>
bool SharedLibraryModel< scalar >::open (
    const std::string & pathToModel,
    const std::string & modelName ) [inline]
```

**19.86.2.20 pullConnectivityFromDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pullConnectivityFromDevice (
    const std::string & popName ) [inline]
```

**19.86.2.21 pullCurrentSpikesFromDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pullCurrentSpikesFromDevice (
    const std::string & popName ) [inline]
```

**19.86.2.22 pullExtraGlobalParam()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pullExtraGlobalParam (
    const std::string & popName,
    const std::string & varName,
    unsigned int count ) [inline]
```

**19.86.2.23 pullSpikesFromDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pullSpikesFromDevice (
    const std::string & popName ) [inline]
```

**19.86.2.24 pullStateFromDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pullStateFromDevice (
    const std::string & popName ) [inline]
```

**19.86.2.25 pullVarFromDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pullVarFromDevice (
    const std::string & popName,
    const std::string & varName ) [inline]
```

**19.86.2.26 pushConnectivityToDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pushConnectivityToDevice (
    const std::string & popName,
    bool uninitialisedOnly = false ) [inline]
```

**19.86.2.27 pushCurrentSpikesToDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pushCurrentSpikesToDevice (
    const std::string & popName,
    bool uninitialisedOnly = false ) [inline]
```

**19.86.2.28 pushExtraGlobalParam()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pushExtraGlobalParam (
    const std::string & popName,
    const std::string & varName,
    unsigned int count ) [inline]
```

**19.86.2.29 pushSpikesToDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pushSpikesToDevice (
    const std::string & popName,
    bool uninitialisedOnly = false ) [inline]
```

**19.86.2.30 pushStateToDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pushStateToDevice (
    const std::string & popName,
    bool uninitialisedOnly = false ) [inline]
```

**19.86.2.31 pushVarToDevice()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::pushVarToDevice (
    const std::string & popName,
    const std::string & varName,
    bool uninitialisedOnly = false ) [inline]
```

**19.86.2.32 setTime()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::setTime (
    scalar t ) [inline]
```

**19.86.2.33 setTimeStep()**

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::setTimeStep (
    unsigned long long iT ) [inline]
```

### 19.86.2.34 stepTime()

```
template<typename scalar = float>
void SharedLibraryModel< scalar >::stepTime ( ) [inline]
```

The documentation for this class was generated from the following file:

- [sharedLibraryModel.h](#)

## 19.87 SpineMLSimulator::Simulator Class Reference

```
#include <simulator.h>
```

### Public Member Functions

- [Simulator](#) (plog::Severity logLevel=plog::warning)
- [Simulator](#) (const std::string &experimentXML, const std::string &overrideOutputPath="", plog::Severity logLevel=plog::warning)
- [~Simulator](#) ()
- void [load](#) (const std::string &experimentXML, const std::string &overrideOutputPath="")  
*Load model from XML file.*
- void [stepTime](#) ()  
*Advance simulation by one timestep.*
- const [LogOutput::AnalogueExternal](#) \* [getExternalLogger](#) (const std::string &name) const  
*Get an external logger by name.*
- [InputValue::External](#) \* [getExternalInput](#) (const std::string &name) const  
*Get an external input by name.*
- double [getDT](#) () const  
*Get the simulation timestep (in ms)*
- double [getDurationMs](#) () const  
*Get duration of simulation read from experiment in ms.*
- double [getInputMs](#) () const  
*Get the total times accumulated in each stage of the simulation.*
- double [getSimulateMs](#) () const
- double [getLogMs](#) () const
- double [getNeuronUpdateTime](#) () const  
*Timings of individual kernels provided by GeNN.*
- double [getInitTime](#) () const
- double [getPresynapticUpdateTime](#) () const
- double [getPostsynapticUpdateTime](#) () const
- double [getSynapseDynamicsTime](#) () const
- double [getInitSparseTime](#) () const
- unsigned long long [calcNumTimesteps](#) () const  
*Calculate duration of simulation read from experiment in timesteps.*

### 19.87.1 Constructor & Destructor Documentation

#### 19.87.1.1 Simulator() [1/2]

```
SpineMLSimulator::Simulator::Simulator (
    plog::Severity logLevel = plog::warning )
```

### 19.87.1.2 Simulator() [2/2]

```
SpineMLSimulator::Simulator::Simulator (
    const std::string & experimentXML,
    const std::string & overrideOutputPath = "",
    plog::Severity logLevel = plog::warning )
```

### 19.87.1.3 ~Simulator()

```
SpineMLSimulator::Simulator::~~Simulator ( )
```

## 19.87.2 Member Function Documentation

### 19.87.2.1 calcNumTimesteps()

```
unsigned long long SpineMLSimulator::Simulator::calcNumTimesteps ( ) const [inline]
```

Calculate duration of simulation read from experiment in timesteps.

### 19.87.2.2 getDT()

```
double SpineMLSimulator::Simulator::getDT ( ) const [inline]
```

Get the simulation timestep (in ms)

### 19.87.2.3 getDurationMs()

```
double SpineMLSimulator::Simulator::getDurationMs ( ) const [inline]
```

Get duration of simulation read from experiment in ms.

### 19.87.2.4 getExternalInput()

```
InputValue::External * SpineMLSimulator::Simulator::getExternalInput (
    const std::string & name ) const
```

Get an external input by name.

### 19.87.2.5 getExternalLogger()

```
const LogOutput::AnalogueExternal * SpineMLSimulator::Simulator::getExternalLogger (
    const std::string & name ) const
```

Get an external logger by name.

### 19.87.2.6 getInitSparseTime()

```
double SpineMLSimulator::Simulator::getInitSparseTime ( ) const
```

**19.87.2.7 getInitTime()**

```
double SpineMLSimulator::Simulator::getInitTime ( ) const
```

**19.87.2.8 getInputMs()**

```
double SpineMLSimulator::Simulator::getInputMs ( ) const [inline]
```

Get the total times accumulated in each stage of the simulation.

**19.87.2.9 getLogMs()**

```
double SpineMLSimulator::Simulator::getLogMs ( ) const [inline]
```

**19.87.2.10 getNeuronUpdateTime()**

```
double SpineMLSimulator::Simulator::getNeuronUpdateTime ( ) const
```

Timings of individual kernels provided by GeNN.

**19.87.2.11 getPostsynapticUpdateTime()**

```
double SpineMLSimulator::Simulator::getPostsynapticUpdateTime ( ) const
```

**19.87.2.12 getPresynapticUpdateTime()**

```
double SpineMLSimulator::Simulator::getPresynapticUpdateTime ( ) const
```

**19.87.2.13 getSimulateMs()**

```
double SpineMLSimulator::Simulator::getSimulateMs ( ) const [inline]
```

**19.87.2.14 getSynapseDynamicsTime()**

```
double SpineMLSimulator::Simulator::getSynapseDynamicsTime ( ) const
```

**19.87.2.15 load()**

```
void SpineMLSimulator::Simulator::load (
    const std::string & experimentXML,
    const std::string & overrideOutputPath = "" )
```

Load model from XML file.

**19.87.2.16 stepTime()**

```
void SpineMLSimulator::Simulator::stepTime ( )
```

Advance simulation by one timestep.


The documentation for this class was generated from the following files:

- [simulator.h](#)
- [simulator.cc](#)

## 19.88 SpineMLSimulator::Input::SpikeBase Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::SpikeBase:



### Protected Types

- typedef void(\* [PushCurrentSpikesFunc](#)) ()

### Protected Member Functions

- [SpikeBase](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value, unsigned int popSize, unsigned int \*spikeQueuePtr, unsigned int \*hostSpikeCount, unsigned int \*hostSpikes, [PushCurrentSpikesFunc](#) pushCurrentSpikes)
- void [injectSpike](#) (unsigned int neuronID)
- void [uploadSpikes](#) ()

### Additional Inherited Members

#### 19.88.1 Member Typedef Documentation

##### 19.88.1.1 PushCurrentSpikesFunc

```
typedef void(* SpineMLSimulator::Input::SpikeBase::PushCurrentSpikesFunc) () [protected]
```

#### 19.88.2 Constructor & Destructor Documentation

##### 19.88.2.1 SpikeBase()

```
SpineMLSimulator::Input::SpikeBase::SpikeBase (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value,
    unsigned int popSize,
    unsigned int * spikeQueuePtr,
    unsigned int * hostSpikeCount,
    unsigned int * hostSpikes,
    PushCurrentSpikesFunc pushCurrentSpikes ) [protected]
```

### 19.88.3 Member Function Documentation

#### 19.88.3.1 injectSpike()

```
void SpineMLSimulator::Input::SpikeBase::injectSpike (
    unsigned int neuronID ) [protected]
```

#### 19.88.3.2 uploadSpikes()

```
void SpineMLSimulator::Input::SpikeBase::uploadSpikes ( ) [protected]
```

The documentation for this class was generated from the following files:


- [input.h](#)
- [input.cc](#)

### 19.89 SpikeRecorder< Writer > Class Template Reference

Class to read spikes from neuron groups.

```
#include <spikeRecorder.h>
```

Inheritance diagram for SpikeRecorder< Writer >:



#### Public Types

- typedef unsigned int &(\* [GetCurrentSpikeCountFunc](#)) ()
- typedef unsigned int \*(\* [GetCurrentSpikesFunc](#)) ()

#### Public Member Functions

- template<typename... WriterArgs>  
[SpikeRecorder](#) ([GetCurrentSpikesFunc](#) getCurrentSpikes, [GetCurrentSpikeCountFunc](#) getCurrentSpikeCount, WriterArgs &&... writerArgs)
- void [record](#) (double t)
- unsigned int [getSum](#) () const

#### 19.89.1 Detailed Description

```
template<typename Writer = SpikeWriterText>
class SpikeRecorder< Writer >
```

Class to read spikes from neuron groups.

#### 19.89.2 Member Typedef Documentation



### 19.89.2.1 GetCurrentSpikeCountFunc

```
template<typename Writer = SpikeWriterText>
typedef unsigned int&(* SpikeRecorder< Writer >::GetCurrentSpikeCountFunc) ()
```

### 19.89.2.2 GetCurrentSpikesFunc

```
template<typename Writer = SpikeWriterText>
typedef unsigned int&(* SpikeRecorder< Writer >::GetCurrentSpikesFunc) ()
```

## 19.89.3 Constructor & Destructor Documentation

### 19.89.3.1 SpikeRecorder()

```
template<typename Writer = SpikeWriterText>
template<typename... WriterArgs>
SpikeRecorder< Writer >::SpikeRecorder (
    GetCurrentSpikesFunc getCurrentSpikes,
    GetCurrentSpikeCountFunc getCurrentSpikeCount,
    WriterArgs &&... writerArgs ) [inline]
```

## 19.89.4 Member Function Documentation

### 19.89.4.1 getSum()

```
template<typename Writer = SpikeWriterText>
unsigned int SpikeRecorder< Writer >::getSum ( ) const [inline]
```

### 19.89.4.2 record()

```
template<typename Writer = SpikeWriterText>
void SpikeRecorder< Writer >::record (
    double t ) [inline]
```

The documentation for this class was generated from the following file:


- [spikeRecorder.h](#)

## 19.90 NeuronModels::SpikeSource Class Reference

Empty neuron which allows setting spikes from external sources.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::SpikeSource:



## Public Types

- typedef [Snippet::ValueBase](#)< 0 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- virtual std::string [getThresholdConditionCode](#) () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- [SET\\_NEEDS\\_AUTO\\_REFRACTORY](#) (false)

## Static Public Member Functions

- static const [NeuronModels::SpikeSource](#) \* [getInstance](#) ()

## Additional Inherited Members

### 19.90.1 Detailed Description

Empty neuron which allows setting spikes from external sources.

This model does not contain any update code and can be used to implement the equivalent of a [SpikeGenerator](#)↔ Group in Brian or a [SpikeSourceArray](#) in PyNN.

### 19.90.2 Member Typedef Documentation

#### 19.90.2.1 ParamValues

```
typedef Snippet::ValueBase< 0 > NeuronModels::SpikeSource::ParamValues
```

#### 19.90.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::SpikeSource::PostVarValues
```

## 19.90.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::SpikeSource::PreVarValues
```

## 19.90.2.4 VarValues

```
typedef Models::VarInitContainerBase< 0 > NeuronModels::SpikeSource::VarValues
```

## 19.90.3 Member Function Documentation

## 19.90.3.1 getInstance()

```
static const NeuronModels::SpikeSource* NeuronModels::SpikeSource::getInstance ( ) [inline],
[static]
```

## 19.90.3.2 getThresholdConditionCode()

```
virtual std::string NeuronModels::SpikeSource::getThresholdConditionCode ( ) const [inline],
[override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

## 19.90.3.3 SET\_NEEDS\_AUTO\_REFRACTORY()

```
NeuronModels::SpikeSource::SET_NEEDS_AUTO_REFRACTORY (
    false )
```

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.91 NeuronModels::SpikeSourceArray Class Reference

Spike source array.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::SpikeSourceArray:



## Public Types

- typedef [Snippet::ValueBase](#)< 0 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 2 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual std::string [getThresholdConditionCode](#) () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual std::string [getResetCode](#) () const override  
*Gets code that defines the reset action taken after a spike occurred. This can be empty.*
- virtual [VarVec](#) [getVars](#) () const override  
*Gets names and types (as strings) of model variables.*
- virtual [EGPVec](#) [getExtraGlobalParams](#) () const override
- [SET\\_NEEDS\\_AUTO\\_REFRACTORY](#) (false)

## Static Public Member Functions

- static const [NeuronModels::SpikeSourceArray](#) \* [getInstance](#) ()

## Additional Inherited Members

### 19.91.1 Detailed Description

Spike source array.

A neuron which reads spike times from a global spikes array It has 2 variables:

- `startSpike` - Index of the next spike in the global array
- `endSpike` - Index of the spike next to the last in the global array

and 1 global parameter:

- `spikeTimes` - Array with all spike times

### 19.91.2 Member Typedef Documentation

#### 19.91.2.1 ParamValues

```
typedef Snippet::ValueBase< 0 > NeuronModels::SpikeSourceArray::ParamValues
```

#### 19.91.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::SpikeSourceArray::PostVarValues
```

## 19.91.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::SpikeSourceArray::PreVarValues
```

## 19.91.2.4 VarValues

```
typedef Models::VarInitContainerBase< 2 > NeuronModels::SpikeSourceArray::VarValues
```

## 19.91.3 Member Function Documentation

## 19.91.3.1 getExtraGlobalParams()

```
virtual EGPVec NeuronModels::SpikeSourceArray::getExtraGlobalParams ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of additional per-population parameters for the weight update model.

Reimplemented from [Models::Base](#).

## 19.91.3.2 getInstance()

```
static const NeuronModels::SpikeSourceArray* NeuronModels::SpikeSourceArray::getInstance ( ) [inline], [static]
```

## 19.91.3.3 getResetCode()

```
virtual std::string NeuronModels::SpikeSourceArray::getResetCode ( ) const [inline], [override], [virtual]
```

Gets code that defines the reset action taken after a spike occurred. This can be empty.

Reimplemented from [NeuronModels::Base](#).

## 19.91.3.4 getSimCode()

```
virtual std::string NeuronModels::SpikeSourceArray::getSimCode ( ) const [inline], [override], [virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

## 19.91.3.5 getThresholdConditionCode()

```
virtual std::string NeuronModels::SpikeSourceArray::getThresholdConditionCode ( ) const [inline], [override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

### 19.91.3.6 getVars()

```
virtual VarVec NeuronModels::SpikeSourceArray::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

### 19.91.3.7 SET\_NEEDS\_AUTO\_REFRACTORY()

```
NeuronModels::SpikeSourceArray::SET_NEEDS_AUTO_REFRACTORY (
    false )
```


The documentation for this class was generated from the following file:

- [neuronModels.h](#)

## 19.92 SpineMLSimulator::Input::SpikeTime Class Reference

```
#include <input.h>
```

Inheritance diagram for SpineMLSimulator::Input::SpikeTime:



### Public Member Functions

- [SpikeTime](#) (double dt, const pugi::xml\_node &node, std::unique\_ptr< [InputValue::Base](#) > value, unsigned int popSize, unsigned int \*spikeQueuePtr, unsigned int \*hostSpikeCount, unsigned int \*hostSpikes, [Push↔CurrentSpikesFunc](#) pushCurrentSpikes)
- virtual void [apply](#) (double dt, unsigned long long timestep) override

### Additional Inherited Members

#### 19.92.1 Constructor & Destructor Documentation

##### 19.92.1.1 SpikeTime()

```
SpineMLSimulator::Input::SpikeTime::SpikeTime (
    double dt,
    const pugi::xml_node & node,
    std::unique_ptr< InputValue::Base > value,
    unsigned int popSize,
    unsigned int * spikeQueuePtr,
    unsigned int * hostSpikeCount,
    unsigned int * hostSpikes,
    PushCurrentSpikesFunc pushCurrentSpikes )
```

## 19.92.2 Member Function Documentation

### 19.92.2.1 apply()

```
void SpineMLSimulator::Input::SpikeTime::apply (
    double dt,
    unsigned long long timestep ) [override], [virtual]
```

Implements [SpineMLSimulator::Input::Base](#).

The documentation for this class was generated from the following files:

- [input.h](#)
- [input.cc](#)

## 19.93 SpikeWriterText Class Reference

Class to write spikes to text file.

```
#include <spikeRecorder.h>
```

### Public Member Functions

- [SpikeWriterText](#) (const std::string &filename, const std::string &delimiter=" ", bool header=false)

### Protected Member Functions

- void [recordSpikes](#) (double t, unsigned int spikeCount, const unsigned int \*currentSpikes)

### 19.93.1 Detailed Description

Class to write spikes to text file.

## 19.93.2 Constructor & Destructor Documentation

### 19.93.2.1 SpikeWriterText()

```
SpikeWriterText::SpikeWriterText (
    const std::string & filename,
    const std::string & delimiter = " ",
    bool header = false ) [inline]
```

## 19.93.3 Member Function Documentation

### 19.93.3.1 recordSpikes()

```
void SpikeWriterText::recordSpikes (
    double t,
    unsigned int spikeCount,
    const unsigned int * currentSpikes ) [inline], [protected]
```

The documentation for this class was generated from the following file:

- [spikeRecorder.h](#)

## 19.94 SpikeWriterTextCached Class Reference

Class to write spikes to text file, caching in memory before writing.

```
#include <spikeRecorder.h>
```

### Public Member Functions

- [SpikeWriterTextCached](#) (const std::string &filename, const std::string &delimiter=" ", bool header=false)
- [~SpikeWriterTextCached](#) ()
- void [writeCache](#) ()

### Protected Member Functions

- void [recordSpikes](#) (double t, unsigned int spikeCount, const unsigned int \*currentSpikes)

#### 19.94.1 Detailed Description

Class to write spikes to text file, caching in memory before writing.

#### 19.94.2 Constructor & Destructor Documentation

##### 19.94.2.1 SpikeWriterTextCached()

```
SpikeWriterTextCached::SpikeWriterTextCached (  
    const std::string & filename,  
    const std::string & delimiter = " ",  
    bool header = false ) [inline]
```

##### 19.94.2.2 ~SpikeWriterTextCached()

```
SpikeWriterTextCached::~SpikeWriterTextCached ( ) [inline]
```

#### 19.94.3 Member Function Documentation

##### 19.94.3.1 recordSpikes()

```
void SpikeWriterTextCached::recordSpikes (  
    double t,  
    unsigned int spikeCount,  
    const unsigned int * currentSpikes ) [inline], [protected]
```



## 19.94.3.2 writeCache()

```
void SpikeWriterTextCached::writeCache ( ) [inline]
```

The documentation for this class was generated from the following file:

- [spikeRecorder.h](#)

## 19.95 SpineMLSimulator::StateVar&lt; T &gt; Class Template Reference

```
#include <stateVar.h>
```

## Public Member Functions

- [StateVar](#) (const std::string &stateVarName, std::function< void \*(const char \*, bool)> getLibrarySymbolFunc)
- bool [isAccessible](#) () const
- void [push](#) () const
- void [pull](#) () const
- T \* [get](#) ()
- const T \* [get](#) () const

## 19.95.1 Constructor &amp; Destructor Documentation

## 19.95.1.1 StateVar()

```
template<typename T>
SpineMLSimulator::StateVar< T >::StateVar (
    const std::string & stateVarName,
    std::function< void *(const char *, bool)> getLibrarySymbolFunc ) [inline]
```

## 19.95.2 Member Function Documentation

## 19.95.2.1 get() [1/2]

```
template<typename T>
T* SpineMLSimulator::StateVar< T >::get ( ) [inline]
```

## 19.95.2.2 get() [2/2]

```
template<typename T>
const T* SpineMLSimulator::StateVar< T >::get ( ) const [inline]
```

## 19.95.2.3 isAccessible()

```
template<typename T>
bool SpineMLSimulator::StateVar< T >::isAccessible ( ) const [inline]
```

#### 19.95.2.4 pull()

```
template<typename T>
void SpineMLSimulator::StateVar< T >::pull ( ) const [inline]
```

#### 19.95.2.5 push()

```
template<typename T>
void SpineMLSimulator::StateVar< T >::push ( ) const [inline]
```

### 19.95.3 Member Data Documentation

#### 19.95.3.1 m\_Direct

```
template<typename T>
Direct SpineMLSimulator::StateVar< T >::m_Direct
```

#### 19.95.3.2 m\_Indirect

```
template<typename T>
Indirect SpineMLSimulator::StateVar< T >::m_Indirect
```

The documentation for this class was generated from the following file:


- [stateVar.h](#)

## 19.96 WeightUpdateModels::StaticGraded Class Reference

Graded-potential, static synapse.

```
#include <weightUpdateModels.h>
```

Inheritance diagram for WeightUpdateModels::StaticGraded:



#### Public Member Functions

- [DECLARE\\_WEIGHT\\_UPDATE\\_MODEL](#) ([StaticGraded](#), 2, 1, 0, 0)
- virtual [StringVec getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*
- virtual [VarVec getVars](#) () const override  
*Gets names and types (as strings) of model variables.*

- virtual std::string [getEventCode](#) () const override  
*Gets code run when events (all the instances where event threshold condition is met) are received.*
- virtual std::string [getEventThresholdConditionCode](#) () const override  
*Gets codes to test for events.*

### Additional Inherited Members

#### 19.96.1 Detailed Description

Graded-potential, static synapse.

In a graded synapse, the conductance is updated gradually with the rule:

$$gSyn = g * \tanh((V - E_{pre})/V_{slope})$$

whenever the membrane potential  $V$  is larger than the threshold  $E_{pre}$ . The model has 1 variable:

- `g`: conductance of `scalar` type

The parameters are:

- `Epre`: Presynaptic threshold potential
- `Vslope`: Activation slope of graded release

event code is:

```
$(addToInSyn, $(g) * tanh(($(V_pre)-$(Epre))*DT*2/$(Vslope)));
```

event threshold condition code is:

```
$(V_pre) > $(Epre)
```

### Note

The pre-synaptic variables are referenced with the suffix `_pre` in synapse related code such as an the event threshold test. Users can also access post-synaptic neuron variables using the suffix `_post`.

#### 19.96.2 Member Function Documentation

##### 19.96.2.1 DECLARE\_WEIGHT\_UPDATE\_MODEL()

```
WeightUpdateModels::StaticGraded::DECLARE_WEIGHT_UPDATE_MODEL (
    StaticGraded ,
    2 ,
    1 ,
    0 ,
    0 )
```

##### 19.96.2.2 getEventCode()

```
virtual std::string WeightUpdateModels::StaticGraded::getEventCode ( ) const [inline], [override],
[virtual]
```

Gets code run when events (all the instances where event threshold condition is met) are received.

Reimplemented from [WeightUpdateModels::Base](#).

### 19.96.2.3 `getEventThresholdConditionCode()`

```
virtual std::string WeightUpdateModels::StaticGraded::getEventThresholdConditionCode ( ) const
[inline], [override], [virtual]
```

Gets codes to test for events.

Reimplemented from [WeightUpdateModels::Base](#).

### 19.96.2.4 `getParamNames()`

```
virtual StringVec WeightUpdateModels::StaticGraded::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

### 19.96.2.5 `getVars()`

```
virtual VarVec WeightUpdateModels::StaticGraded::getVars ( ) const [inline], [override],
[virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

The documentation for this class was generated from the following file:


- [weightUpdateModels.h](#)

## 19.97 WeightUpdateModels::StaticPulse Class Reference

Pulse-coupled, static synapse.

```
#include <weightUpdateModels.h>
```

Inheritance diagram for `WeightUpdateModels::StaticPulse`:



### Public Member Functions

- [DECLARE\\_WEIGHT\\_UPDATE\\_MODEL](#) ([StaticPulse](#), 0, 1, 0, 0)
- virtual [VarVec](#) [getVars](#) ( ) const override  
*Gets names and types (as strings) of model variables.*
- virtual `std::string` [getSimCode](#) ( ) const override  
*Gets simulation code run when 'true' spikes are received.*

## Additional Inherited Members

## 19.97.1 Detailed Description

Pulse-coupled, static synapse.

No learning rule is applied to the synapse and for each pre-synaptic spikes, the synaptic conductances are simply added to the postsynaptic input variable. The model has 1 variable:

- `g` - conductance of scalar type and no other parameters.

sim code is:

```
"$(addToInSyn, $(g));\n"
```

## 19.97.2 Member Function Documentation

## 19.97.2.1 DECLARE\_WEIGHT\_UPDATE\_MODEL()

```
WeightUpdateModels::StaticPulse::DECLARE_WEIGHT_UPDATE_MODEL (
    StaticPulse ,
    0 ,
    1 ,
    0 ,
    0 )
```

## 19.97.2.2 getSimCode()

```
virtual std::string WeightUpdateModels::StaticPulse::getSimCode ( ) const [inline], [override], [virtual]
```

Gets simulation code run when 'true' spikes are received.

Reimplemented from [WeightUpdateModels::Base](#).

## 19.97.2.3 getVars()

```
virtual VarVec WeightUpdateModels::StaticPulse::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

The documentation for this class was generated from the following file:


- [weightUpdateModels.h](#)

## 19.98 WeightUpdateModels::StaticPulseDendriticDelay Class Reference

Pulse-coupled, static synapse with heterogenous dendritic delays.

```
#include <weightUpdateModels.h>
```

Inheritance diagram for `WeightUpdateModels::StaticPulseDendriticDelay`:



### Public Member Functions

- `DECLARE_WEIGHT_UPDATE_MODEL` (`StaticPulseDendriticDelay`, 0, 2, 0, 0)
- virtual `VarVec getVars ()` const override  
*Gets names and types (as strings) of model variables.*
- virtual `std::string getSimCode ()` const override  
*Gets simulation code run when 'true' spikes are received.*

### Additional Inherited Members

#### 19.98.1 Detailed Description

Pulse-coupled, static synapse with heterogenous dendritic delays.

No learning rule is applied to the synapse and for each pre-synaptic spikes, the synaptic conductances are simply added to the postsynaptic input variable. The model has 2 variables:

- g - conductance of scalar type
- d - dendritic delay in timesteps and no other parameters.

sim code is:

```
" $(addToInSynDelay, $(g), $(d));\n\
```

#### 19.98.2 Member Function Documentation

##### 19.98.2.1 DECLARE\_WEIGHT\_UPDATE\_MODEL()

```
WeightUpdateModels::StaticPulseDendriticDelay::DECLARE_WEIGHT_UPDATE_MODEL (
    StaticPulseDendriticDelay ,
    0 ,
    2 ,
    0 ,
    0 )
```

##### 19.98.2.2 getSimCode()

```
virtual std::string WeightUpdateModels::StaticPulseDendriticDelay::getSimCode ( ) const [inline],
[override], [virtual]
```

Gets simulation code run when 'true' spikes are received.

Reimplemented from [WeightUpdateModels::Base](#).

### 19.98.2.3 getVars()

```
virtual VarVec WeightUpdateModels::StaticPulseDendriticDelay::getVars ( ) const [inline],
[override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

The documentation for this class was generated from the following file:

- [weightUpdateModels.h](#)

## 19.99 CodeGenerator::Substitutions Class Reference

```
#include <substitutions.h>
```

### Public Member Functions

- [Substitutions](#) (const [Substitutions](#) \*parent=nullptr)
- [Substitutions](#) (const std::vector< [FunctionTemplate](#) > &functions, const std::string &ftype)
- template<typename T >  
void [addVarNameSubstitution](#) (const std::vector< T > &variables, const std::string &sourceSuffix="", const std::string &destPrefix="", const std::string &destSuffix="")
- void [addParamNameSubstitution](#) (const std::vector< std::string > &paramNames, const std::string &source←  
Suffix="", const std::string &destPrefix="", const std::string &destSuffix="")
- template<typename T >  
void [addVarValueSubstitution](#) (const std::vector< T > &variables, const std::vector< double > &values, const std::string &sourceSuffix="")
- void [addParamValueSubstitution](#) (const std::vector< std::string > &paramNames, const std::vector< double > &values, const std::string &sourceSuffix="")
- void [addVarSubstitution](#) (const std::string &source, const std::string &destination, bool allowOverride=false)
- void [addFuncSubstitution](#) (const std::string &source, unsigned int numArguments, const std::string &func←  
Template, bool allowOverride=false)
- bool [hasVarSubstitution](#) (const std::string &source) const
- const std::string & [getVarSubstitution](#) (const std::string &source) const
- void [apply](#) (std::string &code) const
- void [applyCheckUnreplaced](#) (std::string &code, const std::string &context) const
- const std::string [operator\[\]](#) (const std::string &source) const

### 19.99.1 Constructor & Destructor Documentation

#### 19.99.1.1 Substitutions() [1/2]

```
CodeGenerator::Substitutions::Substitutions (
    const Substitutions * parent = nullptr ) [inline]
```

#### 19.99.1.2 Substitutions() [2/2]

```
CodeGenerator::Substitutions::Substitutions (
    const std::vector< FunctionTemplate > & functions,
    const std::string & ftype ) [inline]
```

## 19.99.2 Member Function Documentation

### 19.99.2.1 addFuncSubstitution()

```
void CodeGenerator::Substitutions::addFuncSubstitution (
    const std::string & source,
    unsigned int numArguments,
    const std::string & funcTemplate,
    bool allowOverride = false ) [inline]
```

### 19.99.2.2 addParamNameSubstitution()

```
void CodeGenerator::Substitutions::addParamNameSubstitution (
    const std::vector< std::string > & paramNames,
    const std::string & sourceSuffix = "",
    const std::string & destPrefix = "",
    const std::string & destSuffix = "" ) [inline]
```

### 19.99.2.3 addParamValueSubstitution()

```
void CodeGenerator::Substitutions::addParamValueSubstitution (
    const std::vector< std::string > & paramNames,
    const std::vector< double > & values,
    const std::string & sourceSuffix = "" ) [inline]
```

### 19.99.2.4 addVarNameSubstitution()

```
template<typename T >
void CodeGenerator::Substitutions::addVarNameSubstitution (
    const std::vector< T > & variables,
    const std::string & sourceSuffix = "",
    const std::string & destPrefix = "",
    const std::string & destSuffix = "" ) [inline]
```

### 19.99.2.5 addVarSubstitution()

```
void CodeGenerator::Substitutions::addVarSubstitution (
    const std::string & source,
    const std::string & destination,
    bool allowOverride = false ) [inline]
```

### 19.99.2.6 addVarValueSubstitution()

```
template<typename T >
void CodeGenerator::Substitutions::addVarValueSubstitution (
    const std::vector< T > & variables,
    const std::vector< double > & values,
    const std::string & sourceSuffix = "" ) [inline]
```



## 19.99.2.7 apply()

```
void CodeGenerator::Substitutions::apply (
    std::string & code ) const [inline]
```

## 19.99.2.8 applyCheckUnreplaced()

```
void CodeGenerator::Substitutions::applyCheckUnreplaced (
    std::string & code,
    const std::string & context ) const [inline]
```

## 19.99.2.9 getVarSubstitution()

```
const std::string& CodeGenerator::Substitutions::getVarSubstitution (
    const std::string & source ) const [inline]
```

## 19.99.2.10 hasVarSubstitution()

```
bool CodeGenerator::Substitutions::hasVarSubstitution (
    const std::string & source ) const [inline]
```

## 19.99.2.11 operator[]()

```
const std::string CodeGenerator::Substitutions::operator[] (
    const std::string & source ) const [inline]
```


The documentation for this class was generated from the following file:

- [substitutions.h](#)

## 19.100 pygenn.genn\_groups.SynapseGroup Class Reference

Class representing synaptic connection between two groups of neurons.

Inheritance diagram for pygenn.genn\_groups.SynapseGroup:



## Public Member Functions

- def [\\_\\_init\\_\\_](#) (self, [name](#))  
*Init SynapseGroup.*
- def [num\\_synapses](#) (self)  
*Number of synapses in group.*
- def [weight\\_update\\_var\\_size](#) (self)

- Size of each weight update variable.*
- def `max_row_length` (self)
- def `set_psm_var` (self, var\_name, values)
  - Set values for a postsynaptic model variable.*
- def `set_pre_var` (self, var\_name, values)
  - Set values for a presynaptic variable.*
- def `set_post_var` (self, var\_name, values)
  - Set values for a postsynaptic variable.*
- def `set_weight_update` (self, model, param\_space, var\_space, pre\_var\_space, post\_var\_space)
  - Set weight update model, its parameters and initial variables.*
- def `set_post_syn` (self, model, param\_space, var\_space)
  - Set postsynaptic model, its parameters and initial variables.*
- def `get_var_values` (self, var\_name)
- def `is_connectivity_init_required` (self)
- def `matrix_type` (self)
  - Type of the projection matrix.*
- def `matrix_type` (self, matrix\_type)
- def `is_ragged` (self)
  - Tests whether synaptic connectivity uses Ragged format.*
- def `is_bitmask` (self)
  - Tests whether synaptic connectivity uses Bitmask format.*
- def `is_dense` (self)
  - Tests whether synaptic connectivity uses dense format.*
- def `has_individual_synapse_vars` (self)
  - Tests whether synaptic connectivity has individual weights.*
- def `has_individual_postsynaptic_vars` (self)
  - Tests whether synaptic connectivity has individual postsynaptic model variables.*
- def `set_sparse_connections` (self, pre\_indices, post\_indices)
  - Set ragged format connections between two groups of neurons.*
- def `get_sparse_pre_inds` (self)
  - Get presynaptic indices of synapse group connections.*
- def `get_sparse_post_inds` (self)
  - Get postsynaptic indices of synapse group connections.*
- def `set_connected_populations` (self, source, target)
  - Set two groups of neurons connected by this [SynapseGroup](#).*
- def `add_to` (self, model\_spec, delay\_steps)
  - Add this [SynapseGroup](#) to the a model.*
- def `add_extra_global_param` (self, param\_name, param\_values)
  - Set extra global parameter.*
- def `set_extra_global_param` (self, param\_name, param\_values)
  - Set extra global parameter to weight update model.*
- def `set_psm_extra_global_param` (self, param\_name, param\_values)
  - Set extra global parameter to postsynaptic model.*
- def `set_connectivity_extra_global_param` (self, param\_name, param\_values)
  - Set extra global parameter to connectivity initialisation snippet.*
- def `load` (self, slm, scalar)
- def `load_connectivity_init_egps` (self, slm, scalar)
- def `reinitialise` (self, slm, scalar)
  - Reinitialise synapse group.*

## Public Attributes

- [connections\\_set](#)
- [w\\_update](#)
- [postsyn](#)
- [src](#)
- [trg](#)
- [psm\\_vars](#)
- [pre\\_vars](#)
- [post\\_vars](#)
- [psm\\_extra\\_global\\_params](#)
- [connectivity\\_extra\\_global\\_params](#)
- [connectivity\\_initialiser](#)
- [synapse\\_order](#)
- [ind](#)
- [row\\_lengths](#)
- [pop](#)

## 19.100.1 Detailed Description

Class representing synaptic connection between two groups of neurons.

## 19.100.2 Constructor &amp; Destructor Documentation

19.100.2.1 `__init__()`

```
def pygenn.genn_groups.SynapseGroup.__init__ (
    self,
    name )
```

Init [SynapseGroup](#).

## Parameters

<i>name</i>	string name of the group
-------------	--------------------------

## 19.100.3 Member Function Documentation

19.100.3.1 `add_extra_global_param()`

```
def pygenn.genn_groups.SynapseGroup.add_extra_global_param (
    self,
    param_name,
    param_values )
```

Set extra global parameter.

## Parameters

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

### 19.100.3.2 `add_to()`

```
def pygenn.genn_groups.SynapseGroup.add_to (
    self,
    model_spec,
    delay_steps )
```

Add this [SynapseGroup](#) to the a model.

#### Parameters

<i>model_spec</i>	<a href="#">pygenn.genn_model.GeNNModel</a> to add to
<i>delay_steps</i>	number of axonal delay timesteps to simulate for this synapse group

### 19.100.3.3 `get_sparse_post_inds()`

```
def pygenn.genn_groups.SynapseGroup.get_sparse_post_inds (
    self )
```

Get postsynaptic indices of synapse group connections.

#### Returns

ndarrays of postsynaptic indices

### 19.100.3.4 `get_sparse_pre_inds()`

```
def pygenn.genn_groups.SynapseGroup.get_sparse_pre_inds (
    self )
```

Get presynaptic indices of synapse group connections.

#### Returns

ndarray of presynaptic indices

### 19.100.3.5 `get_var_values()`

```
def pygenn.genn_groups.SynapseGroup.get_var_values (
    self,
    var_name )
```

### 19.100.3.6 `has_individual_postsynaptic_vars()`

```
def pygenn.genn_groups.SynapseGroup.has_individual_postsynaptic_vars (
    self )
```

Tests whether synaptic connectivity has individual postsynaptic model variables.

**19.100.3.7 has\_individual\_synapse\_vars()**

```
def pygenn.genn_groups.SynapseGroup.has_individual_synapse_vars (
    self )
```

Tests whether synaptic connectivity has individual weights.

**19.100.3.8 is\_bitmask()**

```
def pygenn.genn_groups.SynapseGroup.is_bitmask (
    self )
```

Tests whether synaptic connectivity uses Bitmask format.

**19.100.3.9 is\_connectivity\_init\_required()**

```
def pygenn.genn_groups.SynapseGroup.is_connectivity_init_required (
    self )
```

**19.100.3.10 is\_dense()**

```
def pygenn.genn_groups.SynapseGroup.is_dense (
    self )
```

Tests whether synaptic connectivity uses dense format.

**19.100.3.11 is\_ragged()**

```
def pygenn.genn_groups.SynapseGroup.is_ragged (
    self )
```

Tests whether synaptic connectivity uses Ragged format.

**19.100.3.12 load()**

```
def pygenn.genn_groups.SynapseGroup.load (
    self,
    slm,
    scalar )
```

**19.100.3.13 load\_connectivity\_init\_egps()**

```
def pygenn.genn_groups.SynapseGroup.load_connectivity_init_egps (
    self,
    slm,
    scalar )
```

**19.100.3.14 matrix\_type()** [1/2]

```
def pygenn.genn_groups.SynapseGroup.matrix_type (
    self )
```

Type of the projection matrix.

**19.100.3.15 matrix\_type()** [2/2]

```
def pygenn.genn_groups.SynapseGroup.matrix_type (
    self,
    matrix_type )
```

**19.100.3.16 max\_row\_length()**

```
def pygenn.genn_groups.SynapseGroup.max_row_length (
    self )
```

**19.100.3.17 num\_synapses()**

```
def pygenn.genn_groups.SynapseGroup.num_synapses (
    self )
```

Number of synapses in group.

**19.100.3.18 reinitialise()**

```
def pygenn.genn_groups.SynapseGroup.reinitialise (
    self,
    slm,
    scalar )
```

Reinitialise synapse group.

**Parameters**

<i>slm</i>	<a href="#">SharedLibraryModel</a> instance for accessing variables
<i>scalar</i>	String specifying "scalar" type

**19.100.3.19 set\_connected\_populations()**

```
def pygenn.genn_groups.SynapseGroup.set_connected_populations (
    self,
    source,
    target )
```

Set two groups of neurons connected by this [SynapseGroup](#).

**Parameters**

<i>source</i>	string name of the presynaptic neuron group
<i>target</i>	string name of the postsynaptic neuron group

**19.100.3.20 set\_connectivity\_extra\_global\_param()**

```
def pygenn.genn_groups.SynapseGroup.set_connectivity_extra_global_param (
```

```

        self,
        param_name,
        param_values )

```

Set extra global parameter to connectivity initialisation snippet.

#### Parameters

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

#### 19.100.3.21 set\_extra\_global\_param()

```

def pygenn.genn_groups.SynapseGroup.set_extra_global_param (
    self,
    param_name,
    param_values )

```

Set extra global parameter to weight update model.

#### Parameters

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

#### 19.100.3.22 set\_post\_syn()

```

def pygenn.genn_groups.SynapseGroup.set_post_syn (
    self,
    model,
    param_space,
    var_space )

```

Set postsynaptic model, its parameters and initial variables.

#### Parameters

<i>model</i>	type as string of intance of the model
<i>param_space</i>	dict with model parameters
<i>var_space</i>	dict with model variables

#### 19.100.3.23 set\_post\_var()

```

def pygenn.genn_groups.SynapseGroup.set_post_var (
    self,
    var_name,
    values )

```

Set values for a postsynaptic variable.

#### Parameters

<i>var_name</i>	string with the name of the presynaptic variable
-----------------	--

**Parameters**

<i>values</i>	iterable or a single value
---------------	----------------------------

**19.100.3.24 set\_pre\_var()**

```
def pygenn.genn_groups.SynapseGroup.set_pre_var (
    self,
    var_name,
    values )
```

Set values for a presynaptic variable.

**Parameters**

<i>var_name</i>	string with the name of the presynaptic variable
<i>values</i>	iterable or a single value

**19.100.3.25 set\_psm\_extra\_global\_param()**

```
def pygenn.genn_groups.SynapseGroup.set_psm_extra_global_param (
    self,
    param_name,
    param_values )
```

Set extra global parameter to postsynaptic model.

**Parameters**

<i>param_name</i>	string with the name of the extra global parameter
<i>param_values</i>	iterable or a single value

**19.100.3.26 set\_psm\_var()**

```
def pygenn.genn_groups.SynapseGroup.set_psm_var (
    self,
    var_name,
    values )
```

Set values for a postsynaptic model variable.

**Parameters**

<i>var_name</i>	string with the name of the postsynaptic model variable
<i>values</i>	iterable or a single value

**19.100.3.27 set\_sparse\_connections()**

```
def pygenn.genn_groups.SynapseGroup.set_sparse_connections (
```



```

        self,
        pre_indices,
        post_indices )

```

Set ragged format connections between two groups of neurons.

#### Parameters

<i>pre_indices</i>	ndarray of presynaptic indices
<i>post_indices</i>	ndarray of postsynaptic indices

#### 19.100.3.28 set\_weight\_update()

```

def pygenn.genn_groups.SynapseGroup.set_weight_update (
    self,
    model,
    param_space,
    var_space,
    pre_var_space,
    post_var_space )

```

Set weight update model, its parameters and initial variables.

#### Parameters

<i>model</i>	type as string of intance of the model
<i>param_space</i>	dict with model parameters
<i>var_space</i>	dict with model variables
<i>pre_var_space</i>	dict with model presynaptic variables
<i>post_var_space</i>	dict with model postsynaptic variables

#### 19.100.3.29 weight\_update\_var\_size()

```

def pygenn.genn_groups.SynapseGroup.weight_update_var_size (
    self )

```

Size of each weight update variable.

### 19.100.4 Member Data Documentation

#### 19.100.4.1 connections\_set

```
pygenn.genn_groups.SynapseGroup.connections_set
```

#### 19.100.4.2 connectivity\_extra\_global\_params

```
pygenn.genn_groups.SynapseGroup.connectivity_extra_global_params
```

**19.100.4.3 connectivity\_initialiser**

```
pygenn.genn_groups.SynapseGroup.connectivity_initialiser
```

**19.100.4.4 ind**

```
pygenn.genn_groups.SynapseGroup.ind
```

**19.100.4.5 pop**

```
pygenn.genn_groups.SynapseGroup.pop
```

**19.100.4.6 post\_vars**

```
pygenn.genn_groups.SynapseGroup.post_vars
```

**19.100.4.7 postsyn**

```
pygenn.genn_groups.SynapseGroup.postsyn
```

**19.100.4.8 pre\_vars**

```
pygenn.genn_groups.SynapseGroup.pre_vars
```

**19.100.4.9 psm\_extra\_global\_params**

```
pygenn.genn_groups.SynapseGroup.psm_extra_global_params
```

**19.100.4.10 psm\_vars**

```
pygenn.genn_groups.SynapseGroup.psm_vars
```

**19.100.4.11 row\_lengths**

```
pygenn.genn_groups.SynapseGroup.row_lengths
```

**19.100.4.12 src**

```
pygenn.genn_groups.SynapseGroup.src
```

**19.100.4.13 synapse\_order**

```
pygenn.genn_groups.SynapseGroup.synapse_order
```

## 19.100.4.14 trg

```
pygenn.genn_groups.SynapseGroup.trg
```

## 19.100.4.15 w\_update

```
pygenn.genn_groups.SynapseGroup.w_update
```


The documentation for this class was generated from the following file:

- [genn\\_groups.py](#)

## 19.101 SynapseGroup Class Reference

```
#include <synapseGroup.h>
```

Inheritance diagram for SynapseGroup:



## Public Types

- enum [SpanType](#) { [SpanType::POSTSYNAPTIC](#), [SpanType::PRESYNAPTIC](#) }

## Public Member Functions

- [SynapseGroup](#) (const [SynapseGroup](#) &)=delete
- [SynapseGroup](#) ()=delete
- void [setWUVarLocation](#) (const std::string &varName, [VarLocation](#) loc)  
*Set location of weight update model state variable.*
- void [setWUPreVarLocation](#) (const std::string &varName, [VarLocation](#) loc)  
*Set location of weight update model presynaptic state variable.*
- void [setWUPostVarLocation](#) (const std::string &varName, [VarLocation](#) loc)  
*Set location of weight update model postsynaptic state variable.*
- void [setWUExtraGlobalParamLocation](#) (const std::string &paramName, [VarLocation](#) loc)  
*Set location of weight update model extra global parameter.*
- void [setPSVarLocation](#) (const std::string &varName, [VarLocation](#) loc)  
*Set location of postsynaptic model state variable.*
- void [setPSExtraGlobalParamLocation](#) (const std::string &paramName, [VarLocation](#) loc)  
*Set location of postsynaptic model extra global parameter.*
- void [setSparseConnectivityExtraGlobalParamLocation](#) (const std::string &paramName, [VarLocation](#) loc)  
*Set location of sparse connectivity initialiser extra global parameter.*
- void [setInSynVarLocation](#) ([VarLocation](#) loc)  
*Set location of variables used to combine input from this synapse group.*
- void [setSparseConnectivityLocation](#) ([VarLocation](#) loc)  
*Set variable mode used for sparse connectivity.*
- void [setDendriticDelayLocation](#) ([VarLocation](#) loc)  
*Set variable mode used for this synapse group's dendritic delay buffers.*

- void `setMaxConnections` (unsigned int maxConnections)  
*Sets the maximum number of target neurons any source neurons can connect to.*
- void `setMaxSourceConnections` (unsigned int maxPostConnections)  
*Sets the maximum number of source neurons any target neuron can connect to.*
- void `setMaxDendriticDelayTimesteps` (unsigned int maxDendriticDelay)  
*Sets the maximum dendritic delay for synapses in this synapse group.*
- void `setSpanType` (SpanType spanType)  
*Set how CUDA implementation is parallelised.*
- void `setNumThreadsPerSpike` (unsigned int numThreadsPerSpike)  
*Set how many threads CUDA implementation uses to process each spike when span type is PRESYNAPTIC.*
- void `setBackPropDelaySteps` (unsigned int timesteps)  
*Sets the number of delay steps used to delay postsynaptic spikes travelling back along dendrites to synapses.*
- void `setNarrowSparseIndEnabled` (bool enabled)  
*Enables or disables using narrow i.e. less than 32-bit types for sparse matrix indices.*
- const std::string & `getName` () const
- SpanType `getSpanType` () const
- unsigned int `getNumThreadsPerSpike` () const
- unsigned int `getDelaySteps` () const
- unsigned int `getBackPropDelaySteps` () const
- unsigned int `getMaxConnections` () const
- unsigned int `getMaxSourceConnections` () const
- unsigned int `getMaxDendriticDelayTimesteps` () const
- SynapseMatrixType `getMatrixType` () const
- VarLocation `getInSynLocation` () const  
*Get variable mode used for variables used to combine input from this synapse group.*
- VarLocation `getSparseConnectivityLocation` () const  
*Get variable mode used for sparse connectivity.*
- VarLocation `getDendriticDelayLocation` () const  
*Get variable mode used for this synapse group's dendritic delay buffers.*
- int `getClusterHostID` () const
- bool `isTrueSpikeRequired` () const  
*Does synapse group need to handle 'true' spikes.*
- bool `isSpikeEventRequired` () const  
*Does synapse group need to handle spike-like events.*
- const WeightUpdateModels::Base \* `getWUModel` () const
- const std::vector< double > & `getWUParams` () const
- const std::vector< Models::VarInit > & `getWUVarInitialisers` () const
- const std::vector< Models::VarInit > & `getWUPreVarInitialisers` () const
- const std::vector< Models::VarInit > & `getWUPostVarInitialisers` () const
- const std::vector< double > `getWUConstInitVals` () const
- const PostsynapticModels::Base \* `getPSModel` () const
- const std::vector< double > & `getPSParams` () const
- const std::vector< Models::VarInit > & `getPSVarInitialisers` () const
- const std::vector< double > `getPSConstInitVals` () const
- const InitSparseConnectivitySnippet::Init & `getConnectivityInitialiser` () const
- bool `isZeroCopyEnabled` () const
- VarLocation `getWUVarLocation` (const std::string &var) const  
*Get location of weight update model per-synapse state variable by name.*
- VarLocation `getWUVarLocation` (size\_t index) const  
*Get location of weight update model per-synapse state variable by index.*
- VarLocation `getWUPreVarLocation` (const std::string &var) const  
*Get location of weight update model presynaptic state variable by name.*

- [VarLocation getWUPreVarLocation](#) (size\_t index) const  
*Get location of weight update model presynaptic state variable by index.*
- [VarLocation getWUPostVarLocation](#) (const std::string &var) const  
*Get location of weight update model postsynaptic state variable by name.*
- [VarLocation getWUPostVarLocation](#) (size\_t index) const  
*Get location of weight update model postsynaptic state variable by index.*
- [VarLocation getWUExtraGlobalParamLocation](#) (const std::string &paramName) const  
*Get location of weight update model extra global parameter by name.*
- [VarLocation getWUExtraGlobalParamLocation](#) (size\_t index) const  
*Get location of weight update model extra global parameter by index.*
- [VarLocation getPSVarLocation](#) (const std::string &var) const  
*Get location of postsynaptic model state variable.*
- [VarLocation getPSVarLocation](#) (size\_t index) const  
*Get location of postsynaptic model state variable.*
- [VarLocation getPSExtraGlobalParamLocation](#) (const std::string &paramName) const  
*Get location of postsynaptic model extra global parameter by name.*
- [VarLocation getPSExtraGlobalParamLocation](#) (size\_t index) const  
*Get location of postsynaptic model extra global parameter by index.*
- [VarLocation getSparseConnectivityExtraGlobalParamLocation](#) (const std::string &paramName) const  
*Get location of sparse connectivity initialiser extra global parameter by name.*
- [VarLocation getSparseConnectivityExtraGlobalParamLocation](#) (size\_t index) const  
*Get location of sparse connectivity initialiser extra global parameter by index.*
- bool [isDendriticDelayRequired](#) () const  
*Does this synapse group require dendritic delay?*
- bool [isProceduralConnectivityRNGRequired](#) () const  
*Does this synapse group require an RNG to generate procedural connectivity?*
- bool [isPSInitRNGRequired](#) () const  
*Does this synapse group require an RNG for it's postsynaptic init code?*
- bool [isWUInitRNGRequired](#) () const  
*Does this synapse group require an RNG for it's weight update init code?*
- bool [isWUVarInitRequired](#) () const  
*Is var init code required for any variables in this synapse group's weight update model?*
- bool [isSparseConnectivityInitRequired](#) () const  
*Is sparse connectivity initialisation code required for this synapse group?*

### Protected Member Functions

- [SynapseGroup](#) (const std::string name, [SynapseMatrixType](#) matrixType, unsigned int delaySteps, const [WeightUpdateModels::Base](#) \*wu, const std::vector< double > &wuParams, const std::vector< [Models::VarInit](#) > &wuVarInitialisers, const std::vector< [Models::VarInit](#) > &wuPreVarInitialisers, const std::vector< [Models::VarInit](#) > &wuPostVarInitialisers, const [PostsynapticModels::Base](#) \*ps, const std::vector< double > &psParams, const std::vector< [Models::VarInit](#) > &psVarInitialisers, [NeuronGroupInternal](#) \*srcNeuronGroup, [NeuronGroupInternal](#) \*trgNeuronGroup, const [InitSparseConnectivitySnippet::Init](#) &connectivityInitialiser, [VarLocation](#) defaultVarLocation, [VarLocation](#) defaultExtraGlobalParamLocation, [VarLocation](#) defaultSparseConnectivityLocation, bool defaultNarrowSparseIndEnabled)
- [NeuronGroupInternal](#) \* [getSrcNeuronGroup](#) ()
- [NeuronGroupInternal](#) \* [getTrgNeuronGroup](#) ()
- void [setEventThresholdReTestRequired](#) (bool req)
- void [setPSModelMergeTarget](#) (const std::string &targetName)
- void [initDerivedParams](#) (double dt)
- const [NeuronGroupInternal](#) \* [getSrcNeuronGroup](#) () const
- const [NeuronGroupInternal](#) \* [getTrgNeuronGroup](#) () const

- `const std::vector< double > & getWUDerivedParams () const`
- `const std::vector< double > & getPSDerivedParams () const`
- *Does the event threshold needs to be retested in the synapse kernel?*
- `bool isEventThresholdReTestRequired () const`
- `const std::string & getPSModelTargetName () const`
- `bool isPSModelMerged () const`
- `std::string getPresynapticAxonalDelaySlot (const std::string &devPrefix) const`
- `std::string getPostsynapticBackPropDelaySlot (const std::string &devPrefix) const`
- `std::string getDendriticDelayOffset (const std::string &devPrefix, const std::string &offset="") const`
- `std::string getSparseIndType () const`
- *Get the type to use for sparse connectivity indices for synapse group.*

### 19.101.1 Member Enumeration Documentation

#### 19.101.1.1 SpanType

```
enum SynapseGroup::SpanType [strong]
```

##### Enumerator

POSTSYNAPTIC	
PRESYNAPTIC	

### 19.101.2 Constructor & Destructor Documentation

#### 19.101.2.1 SynapseGroup() [1/3]

```
SynapseGroup::SynapseGroup (
    const SynapseGroup & ) [delete]
```

#### 19.101.2.2 SynapseGroup() [2/3]

```
SynapseGroup::SynapseGroup ( ) [delete]
```

#### 19.101.2.3 SynapseGroup() [3/3]

```
SynapseGroup::SynapseGroup (
    const std::string name,
    SynapseMatrixType matrixType,
    unsigned int delaySteps,
    const WeightUpdateModels::Base * wu,
    const std::vector< double > & wuParams,
    const std::vector< Models::VarInit > & wuVarInitialisers,
    const std::vector< Models::VarInit > & wuPreVarInitialisers,
    const std::vector< Models::VarInit > & wuPostVarInitialisers,
    const PostsynapticModels::Base * ps,
    const std::vector< double > & psParams,
    const std::vector< Models::VarInit > & psVarInitialisers,
    NeuronGroupInternal * srcNeuronGroup,
```

```

    NeuronGroupInternal * trgNeuronGroup,
    const InitSparseConnectivitySnippet::Init & connectivityInitialiser,
    VarLocation defaultVarLocation,
    VarLocation defaultExtraGlobalParamLocation,
    VarLocation defaultSparseConnectivityLocation,
    bool defaultNarrowSparseIndEnabled ) [protected]

```

### 19.101.3 Member Function Documentation

#### 19.101.3.1 getBackPropDelaySteps()

```
unsigned int SynapseGroup::getBackPropDelaySteps ( ) const [inline]
```

#### 19.101.3.2 getClusterHostID()

```
int SynapseGroup::getClusterHostID ( ) const
```

#### 19.101.3.3 getConnectivityInitialiser()

```
const InitSparseConnectivitySnippet::Init& SynapseGroup::getConnectivityInitialiser ( ) const
[inline]
```

#### 19.101.3.4 getDelaySteps()

```
unsigned int SynapseGroup::getDelaySteps ( ) const [inline]
```

#### 19.101.3.5 getDendriticDelayLocation()

```
VarLocation SynapseGroup::getDendriticDelayLocation ( ) const [inline]
```

Get variable mode used for this synapse group's dendritic delay buffers.

#### 19.101.3.6 getDendriticDelayOffset()

```
std::string SynapseGroup::getDendriticDelayOffset (
    const std::string & devPrefix,
    const std::string & offset = "" ) const [protected]
```

#### 19.101.3.7 getInSynLocation()

```
VarLocation SynapseGroup::getInSynLocation ( ) const [inline]
```

Get variable mode used for variables used to combine input from this synapse group.

#### 19.101.3.8 getMatrixType()

```
SynapseMatrixType SynapseGroup::getMatrixType ( ) const [inline]
```

**19.101.3.9 getMaxConnections()**

```
unsigned int SynapseGroup::getMaxConnections ( ) const [inline]
```

**19.101.3.10 getMaxDendriticDelayTimesteps()**

```
unsigned int SynapseGroup::getMaxDendriticDelayTimesteps ( ) const [inline]
```

**19.101.3.11 getMaxSourceConnections()**

```
unsigned int SynapseGroup::getMaxSourceConnections ( ) const [inline]
```

**19.101.3.12 getName()**

```
const std::string& SynapseGroup::getName ( ) const [inline]
```

**19.101.3.13 getNumThreadsPerSpike()**

```
unsigned int SynapseGroup::getNumThreadsPerSpike ( ) const [inline]
```

**19.101.3.14 getPostsynapticBackPropDelaySlot()**

```
std::string SynapseGroup::getPostsynapticBackPropDelaySlot (
    const std::string & devPrefix ) const [protected]
```

Get the expression to calculate the delay slot for accessing Postsynaptic neuron state variables, taking into account back propagation delay

**19.101.3.15 getPresynapticAxonalDelaySlot()**

```
std::string SynapseGroup::getPresynapticAxonalDelaySlot (
    const std::string & devPrefix ) const [protected]
```

Get the expression to calculate the delay slot for accessing Presynaptic neuron state variables, taking into account axonal delay

**19.101.3.16 getPSConstInitVals()**

```
const std::vector< double > SynapseGroup::getPSConstInitVals ( ) const
```

**19.101.3.17 getPSDerivedParams()**

```
const std::vector<double>& SynapseGroup::getPSDerivedParams ( ) const [inline], [protected]
```

Does the event threshold needs to be retested in the synapse kernel?

**19.101.3.18 getPSExtraGlobalParamLocation()** [1/2]

```
VarLocation SynapseGroup::getPSExtraGlobalParamLocation (
    const std::string & paramName ) const
```

Get location of postsynaptic model extra global parameter by name.



This is only used by extra global parameters which are pointers

#### 19.101.3.19 getPSExtraGlobalParamLocation() [2/2]

```
VarLocation SynapseGroup::getPSExtraGlobalParamLocation (
    size_t index ) const [inline]
```

Get location of postsynaptic model extra global parameter by index.

This is only used by extra global parameters which are pointers

#### 19.101.3.20 getPSModel()

```
const PostsynapticModels::Base* SynapseGroup::getPSModel ( ) const [inline]
```

#### 19.101.3.21 getPSModelTargetName()

```
const std::string& SynapseGroup::getPSModelTargetName ( ) const [inline], [protected]
```

#### 19.101.3.22 getPSParams()

```
const std::vector<double>& SynapseGroup::getPSParams ( ) const [inline]
```

#### 19.101.3.23 getPSVarInitialisers()

```
const std::vector<Models::VarInit>& SynapseGroup::getPSVarInitialisers ( ) const [inline]
```

#### 19.101.3.24 getPSVarLocation() [1/2]

```
VarLocation SynapseGroup::getPSVarLocation (
    const std::string & var ) const
```

Get location of postsynaptic model state variable.

#### 19.101.3.25 getPSVarLocation() [2/2]

```
VarLocation SynapseGroup::getPSVarLocation (
    size_t index ) const [inline]
```

Get location of postsynaptic model state variable.

#### 19.101.3.26 getSpanType()

```
SpanType SynapseGroup::getSpanType ( ) const [inline]
```

#### 19.101.3.27 getSparseConnectivityExtraGlobalParamLocation() [1/2]

```
VarLocation SynapseGroup::getSparseConnectivityExtraGlobalParamLocation (
    const std::string & paramName ) const
```

Get location of sparse connectivity initialiser extra global parameter by name.

This is only used by extra global parameters which are pointers

**19.101.3.28** `getSparseConnectivityExtraGlobalParamLocation()` [2/2]

```
VarLocation SynapseGroup::getSparseConnectivityExtraGlobalParamLocation (
    size_t index ) const [inline]
```

Get location of sparse connectivity initialiser extra global parameter by index.

This is only used by extra global parameters which are pointers

**19.101.3.29** `getSparseConnectivityLocation()`

```
VarLocation SynapseGroup::getSparseConnectivityLocation ( ) const [inline]
```

Get variable mode used for sparse connectivity.

**19.101.3.30** `getSparseIndType()`

```
std::string SynapseGroup::getSparseIndType ( ) const [protected]
```

Get the type to use for sparse connectivity indices for synapse group.

**19.101.3.31** `getSrcNeuronGroup()` [1/2]

```
NeuronGroupInternal* SynapseGroup::getSrcNeuronGroup ( ) [inline], [protected]
```

**19.101.3.32** `getSrcNeuronGroup()` [2/2]

```
const NeuronGroupInternal* SynapseGroup::getSrcNeuronGroup ( ) const [inline], [protected]
```

**19.101.3.33** `getTrgNeuronGroup()` [1/2]

```
NeuronGroupInternal* SynapseGroup::getTrgNeuronGroup ( ) [inline], [protected]
```

**19.101.3.34** `getTrgNeuronGroup()` [2/2]

```
const NeuronGroupInternal* SynapseGroup::getTrgNeuronGroup ( ) const [inline], [protected]
```

**19.101.3.35** `getWUConstInitVals()`

```
const std::vector< double > SynapseGroup::getWUConstInitVals ( ) const
```

**19.101.3.36** `getWUDerivedParams()`

```
const std::vector<double>& SynapseGroup::getWUDerivedParams ( ) const [inline], [protected]
```

**19.101.3.37** `getWUExtraGlobalParamLocation()` [1/2]

```
VarLocation SynapseGroup::getWUExtraGlobalParamLocation (
    const std::string & paramName ) const
```

Get location of weight update model extra global parameter by name.

This is only used by extra global parameters which are pointers

#### 19.101.3.38 getWUExtraGlobalParamLocation() [2/2]

```
VarLocation SynapseGroup::getWUExtraGlobalParamLocation (
    size_t index ) const [inline]
```

Get location of weight update model extra global parameter by index.

This is only used by extra global parameters which are pointers

#### 19.101.3.39 getWUModel()

```
const WeightUpdateModels::Base* SynapseGroup::getWUModel ( ) const [inline]
```

#### 19.101.3.40 getWUParams()

```
const std::vector<double>& SynapseGroup::getWUParams ( ) const [inline]
```

#### 19.101.3.41 getWUPostVarInitialisers()

```
const std::vector<Models::VarInit>& SynapseGroup::getWUPostVarInitialisers ( ) const [inline]
```

#### 19.101.3.42 getWUPostVarLocation() [1/2]

```
VarLocation SynapseGroup::getWUPostVarLocation (
    const std::string & var ) const
```

Get location of weight update model postsynaptic state variable by name.

#### 19.101.3.43 getWUPostVarLocation() [2/2]

```
VarLocation SynapseGroup::getWUPostVarLocation (
    size_t index ) const [inline]
```

Get location of weight update model postsynaptic state variable by index.

#### 19.101.3.44 getWUPreVarInitialisers()

```
const std::vector<Models::VarInit>& SynapseGroup::getWUPreVarInitialisers ( ) const [inline]
```

#### 19.101.3.45 getWUPreVarLocation() [1/2]

```
VarLocation SynapseGroup::getWUPreVarLocation (
    const std::string & var ) const
```

Get location of weight update model presynaptic state variable by name.

#### 19.101.3.46 getWUPreVarLocation() [2/2]

```
VarLocation SynapseGroup::getWUPreVarLocation (
    size_t index ) const [inline]
```

Get location of weight update model presynaptic state variable by index.

#### 19.101.3.47 `getWUVarInitialisers()`

```
const std::vector<Models::VarInit>& SynapseGroup::getWUVarInitialisers ( ) const [inline]
```

#### 19.101.3.48 `getWUVarLocation()` [1/2]

```
VarLocation SynapseGroup::getWUVarLocation (
    const std::string & var ) const
```

Get location of weight update model per-synapse state variable by name.

#### 19.101.3.49 `getWUVarLocation()` [2/2]

```
VarLocation SynapseGroup::getWUVarLocation (
    size_t index ) const [inline]
```

Get location of weight update model per-synapse state variable by index.

#### 19.101.3.50 `initDerivedParams()`

```
void SynapseGroup::initDerivedParams (
    double dt ) [protected]
```

#### 19.101.3.51 `isDendriticDelayRequired()`

```
bool SynapseGroup::isDendriticDelayRequired ( ) const
```

Does this synapse group require dendritic delay?

#### 19.101.3.52 `isEventThresholdReTestRequired()`

```
bool SynapseGroup::isEventThresholdReTestRequired ( ) const [inline], [protected]
```

This is required when the pre-synaptic neuron population's outgoing synapse groups require different event threshold

#### 19.101.3.53 `isProceduralConnectivityRNGRequired()`

```
bool SynapseGroup::isProceduralConnectivityRNGRequired ( ) const
```

Does this synapse group require an RNG to generate procedural connectivity?

#### 19.101.3.54 `isPSInitRNGRequired()`

```
bool SynapseGroup::isPSInitRNGRequired ( ) const
```

Does this synapse group require an RNG for it's postsynaptic init code?

**19.101.3.55 isPSModelMerged()**

```
bool SynapseGroup::isPSModelMerged ( ) const [inline], [protected]
```

**19.101.3.56 isSparseConnectivityInitRequired()**

```
bool SynapseGroup::isSparseConnectivityInitRequired ( ) const
```

Is sparse connectivity initialisation code required for this synapse group?

**19.101.3.57 isSpikeEventRequired()**

```
bool SynapseGroup::isSpikeEventRequired ( ) const
```

Does synapse group need to handle spike-like events.

**19.101.3.58 isTrueSpikeRequired()**

```
bool SynapseGroup::isTrueSpikeRequired ( ) const
```

Does synapse group need to handle 'true' spikes.

**19.101.3.59 isWUInitRNGRequired()**

```
bool SynapseGroup::isWUInitRNGRequired ( ) const
```

Does this synapse group require an RNG for it's weight update init code?

**19.101.3.60 isWUVarInitRequired()**

```
bool SynapseGroup::isWUVarInitRequired ( ) const
```

Is var init code required for any variables in this synapse group's weight update model?

**19.101.3.61 isZeroCopyEnabled()**

```
bool SynapseGroup::isZeroCopyEnabled ( ) const
```

**19.101.3.62 setBackPropDelaySteps()**

```
void SynapseGroup::setBackPropDelaySteps (
    unsigned int timesteps )
```

Sets the number of delay steps used to delay postsynaptic spikes travelling back along dendrites to synapses.

**19.101.3.63 setDendriticDelayLocation()**

```
void SynapseGroup::setDendriticDelayLocation (
    VarLocation loc ) [inline]
```

Set variable mode used for this synapse group's dendritic delay buffers.

**19.101.3.64 setEventThresholdReTestRequired()**

```
void SynapseGroup::setEventThresholdReTestRequired (
    bool req ) [inline], [protected]
```

**19.101.3.65 setInSynVarLocation()**

```
void SynapseGroup::setInSynVarLocation (
    VarLocation loc ) [inline]
```

Set location of variables used to combine input from this synapse group.

This is ignored for simulations on hardware with a single memory space

**19.101.3.66 setMaxConnections()**

```
void SynapseGroup::setMaxConnections (
    unsigned int maxConnections )
```

Sets the maximum number of target neurons any source neurons can connect to.

Use with synaptic matrix types with [SynapseMatrixConnectivity::SPARSE](#) to optimise CUDA implementation

**19.101.3.67 setMaxDendriticDelayTimesteps()**

```
void SynapseGroup::setMaxDendriticDelayTimesteps (
    unsigned int maxDendriticDelay )
```

Sets the maximum dendritic delay for synapses in this synapse group.

**19.101.3.68 setMaxSourceConnections()**

```
void SynapseGroup::setMaxSourceConnections (
    unsigned int maxPostConnections )
```

Sets the maximum number of source neurons any target neuron can connect to.

Use with synaptic matrix types with [SynapseMatrixConnectivity::SPARSE](#) and postsynaptic learning to optimise CUDA implementation

**19.101.3.69 setNarrowSparseIndEnabled()**

```
void SynapseGroup::setNarrowSparseIndEnabled (
    bool enabled )
```

Enables or disables using narrow i.e. less than 32-bit types for sparse matrix indices.

**19.101.3.70 setNumThreadsPerSpike()**

```
void SynapseGroup::setNumThreadsPerSpike (
    unsigned int numThreadsPerSpike )
```

Set how many threads CUDA implementation uses to process each spike when span type is PRESYNAPTIC.

**19.101.3.71 setPSExtraGlobalParamLocation()**

```
void SynapseGroup::setPSExtraGlobalParamLocation (
    const std::string & paramName,
    VarLocation loc )
```

Set location of postsynaptic model extra global parameter.

This is ignored for simulations on hardware with a single memory space and only applies to extra global parameters which are pointers.

#### 19.101.3.72 setPSModelMergeTarget()

```
void SynapseGroup::setPSModelMergeTarget (
    const std::string & targetName ) [inline], [protected]
```

#### 19.101.3.73 setPSVarLocation()

```
void SynapseGroup::setPSVarLocation (
    const std::string & varName,
    VarLocation loc )
```

Set location of postsynaptic model state variable.

This is ignored for simulations on hardware with a single memory space

#### 19.101.3.74 setSpanType()

```
void SynapseGroup::setSpanType (
    SpanType spanType )
```

Set how CUDA implementation is parallelised.

with a thread per target neuron (default) or a thread per source spike

#### 19.101.3.75 setSparseConnectivityExtraGlobalParamLocation()

```
void SynapseGroup::setSparseConnectivityExtraGlobalParamLocation (
    const std::string & paramName,
    VarLocation loc )
```

Set location of sparse connectivity initialiser extra global parameter.

This is ignored for simulations on hardware with a single memory space and only applies to extra global parameters which are pointers.

#### 19.101.3.76 setSparseConnectivityLocation()

```
void SynapseGroup::setSparseConnectivityLocation (
    VarLocation loc ) [inline]
```

Set variable mode used for sparse connectivity.

This is ignored for simulations on hardware with a single memory space

#### 19.101.3.77 setWUExtraGlobalParamLocation()

```
void SynapseGroup::setWUExtraGlobalParamLocation (
    const std::string & paramName,
    VarLocation loc )
```

Set location of weight update model extra global parameter.

This is ignored for simulations on hardware with a single memory space and only applies to extra global parameters which are pointers.

#### 19.101.3.78 setWUPostVarLocation()

```
void SynapseGroup::setWUPostVarLocation (
    const std::string & varName,
```

```
VarLocation loc )
```

Set location of weight update model postsynaptic state variable.

This is ignored for simulations on hardware with a single memory space

#### 19.101.3.79 setWUPreVarLocation()

```
void SynapseGroup::setWUPreVarLocation (
    const std::string & varName,
    VarLocation loc )
```

Set location of weight update model presynaptic state variable.

This is ignored for simulations on hardware with a single memory space

#### 19.101.3.80 setWUVarLocation()

```
void SynapseGroup::setWUVarLocation (
    const std::string & varName,
    VarLocation loc )
```

Set location of weight update model state variable.

This is ignored for simulations on hardware with a single memory space


The documentation for this class was generated from the following files:

- [synapseGroup.h](#)
- [synapseGroup.cc](#)

## 19.102 SynapseGroupInternal Class Reference

```
#include <synapseGroupInternal.h>
```

Inheritance diagram for SynapseGroupInternal:



### Public Member Functions

- [SynapseGroupInternal](#) (const std::string name, [SynapseMatrixType](#) matrixType, unsigned int delaySteps, const [WeightUpdateModels::Base](#) \*wu, const std::vector< double > &wuParams, const std::vector< [Models::VarInit](#) > &wuVarInitialisers, const std::vector< [Models::VarInit](#) > &wuPostVarInitialisers, const [PostsynapticModels::Base](#) \*ps, const std::vector< double > &psParams, const std::vector< [Models::VarInit](#) > &psVarInitialisers, [NeuronGroupInternal](#) \*srcNeuronGroup, [NeuronGroupInternal](#) \*trgNeuronGroup, const [InitSparseConnectivitySnippet::Init](#) &connectivityInitialiser, [VarLocation](#) defaultVarLocation, [VarLocation](#) defaultExtraGlobalParamLocation, [VarLocation](#) defaultSparseConnectivityLocation, bool defaultNarrowSparseIndEnabled)

### Additional Inherited Members

#### 19.102.1 Constructor & Destructor Documentation



## 19.102.1.1 SynapseGroupInternal()

```

SynapseGroupInternal::SynapseGroupInternal (
    const std::string name,
    SynapseMatrixType matrixType,
    unsigned int delaySteps,
    const WeightUpdateModels::Base * wu,
    const std::vector< double > & wuParams,
    const std::vector< Models::VarInit > & wuVarInitialisers,
    const std::vector< Models::VarInit > & wuPreVarInitialisers,
    const std::vector< Models::VarInit > & wuPostVarInitialisers,
    const PostsynapticModels::Base * ps,
    const std::vector< double > & psParams,
    const std::vector< Models::VarInit > & psVarInitialisers,
    NeuronGroupInternal * srcNeuronGroup,
    NeuronGroupInternal * trgNeuronGroup,
    const InitSparseConnectivitySnippet::Init & connectivityInitialiser,
    VarLocation defaultVarLocation,
    VarLocation defaultExtraGlobalParamLocation,
    VarLocation defaultSparseConnectivityLocation,
    bool defaultNarrowSparseIndEnabled ) [inline]

```


The documentation for this class was generated from the following file:

- [synapseGroupInternal.h](#)

## 19.103 CodeGenerator::TeeBuf Class Reference

```
#include <teeStream.h>
```

Inheritance diagram for CodeGenerator::TeeBuf:



## Public Member Functions

- `template<typename... T>`  
[TeeBuf](#) (T &&... streamBufs)

## 19.103.1 Constructor &amp; Destructor Documentation

## 19.103.1.1 TeeBuf()

```

template<typename... T>
CodeGenerator::TeeBuf::TeeBuf (
    T &&... streamBufs ) [inline]

```


The documentation for this class was generated from the following file:

- [teeStream.h](#)

## 19.104 CodeGenerator::TeeStream Class Reference

```
#include <teeStream.h>
```

Inheritance diagram for CodeGenerator::TeeStream:



### Public Member Functions

- `template<typename... T>`  
[TeeStream](#) (T &&... streamBufs)

### 19.104.1 Constructor & Destructor Documentation

#### 19.104.1.1 TeeStream()

```
template<typename... T>
CodeGenerator::TeeStream::TeeStream (
    T &&... streamBufs ) [inline]
```

The documentation for this class was generated from the following file:

- [teeStream.h](#)

## 19.105 Timer Class Reference

A generic timer which can give the current elapsed time.

```
#include <timer.h>
```

### Public Member Functions

- [Timer](#) (const std::string &message, const std::string &filename="")  
*Create a new [Timer](#) with the specified name and optionally a filename to append time to.*
- [~Timer](#) ()  
*Stop the timer and print current elapsed time to terminal.*
- double [get](#) () const  
*Get the elapsed time since this object was created.*

### 19.105.1 Detailed Description

A generic timer which can give the current elapsed time.

### 19.105.2 Constructor & Destructor Documentation

#### 19.105.2.1 Timer()

```
Timer::Timer (
    const std::string & message,
    const std::string & filename = "" ) [inline]
```

Create a new [Timer](#) with the specified name and optionally a filename to append time to.

#### 19.105.2.2 ~Timer()

```
Timer::~Timer ( ) [inline]
```

Stop the timer and print current elapsed time to terminal.

### 19.105.3 Member Function Documentation

#### 19.105.3.1 get()

```
double Timer::get ( ) const [inline]
```

Get the elapsed time since this object was created.

The documentation for this class was generated from the following file:

- [userproject/include/timer.h](#)

## 19.106 SpineMLSimulator::Timer Class Reference

```
#include <timer.h>
```

### Public Member Functions

- [Timer](#) (const std::string &title)
- [~Timer](#) ()
- double [get](#) () const

### 19.106.1 Constructor & Destructor Documentation

#### 19.106.1.1 Timer()

```
SpineMLSimulator::Timer::Timer (
    const std::string & title ) [inline]
```

#### 19.106.1.2 ~Timer()

```
SpineMLSimulator::Timer::~Timer ( ) [inline]
```

## 19.106.2 Member Function Documentation

### 19.106.2.1 get()

```
double SpineMLSimulator::Timer::get ( ) const [inline]
```

The documentation for this class was generated from the following file:

- [include/spinml/simulator/timer.h](#)

## 19.107 TimerAccumulate Class Reference

A timer which adds its elapsed time to an accumulator variable on destruction.

```
#include <timer.h>
```

### Public Member Functions

- [TimerAccumulate](#) (double &accumulator)
- [~TimerAccumulate](#) ()
- double [get](#) () const  
*Get the elapsed time since this object was created.*

### 19.107.1 Detailed Description

A timer which adds its elapsed time to an accumulator variable on destruction.

## 19.107.2 Constructor & Destructor Documentation

### 19.107.2.1 TimerAccumulate()

```
TimerAccumulate::TimerAccumulate (
    double & accumulator ) [inline]
```

### 19.107.2.2 ~TimerAccumulate()

```
TimerAccumulate::~~TimerAccumulate ( ) [inline]
```

## 19.107.3 Member Function Documentation

### 19.107.3.1 get()

```
double TimerAccumulate::get ( ) const [inline]
```

Get the elapsed time since this object was created.

The documentation for this class was generated from the following file:

- [userproject/include/timer.h](#)

## 19.108 SpineMLSimulator::TimerAccumulate Class Reference

```
#include <timer.h>
```

### Public Member Functions

- [TimerAccumulate](#) (double &accumulator)
- [~TimerAccumulate](#) ()
- double [get](#) () const

### 19.108.1 Constructor & Destructor Documentation

#### 19.108.1.1 TimerAccumulate()

```
SpineMLSimulator::TimerAccumulate::TimerAccumulate (
    double & accumulator ) [inline]
```

#### 19.108.1.2 ~TimerAccumulate()

```
SpineMLSimulator::TimerAccumulate::~~TimerAccumulate ( ) [inline]
```

### 19.108.2 Member Function Documentation

#### 19.108.2.1 get()

```
double SpineMLSimulator::TimerAccumulate::get ( ) const [inline]
```


The documentation for this class was generated from the following file:

- [include/spineml/simulator/timer.h](#)

## 19.109 SpineMLSimulator::InputValue::TimeVarying Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::TimeVarying:



### Public Member Functions

- [TimeVarying](#) (double dt, unsigned int numNeurons, const pugi::xml\_node &node)
- virtual void [update](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc) override

## Additional Inherited Members

### 19.109.1 Constructor & Destructor Documentation

#### 19.109.1.1 TimeVarying()

```
SpineMLSimulator::InputValue::TimeVarying::TimeVarying (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node )
```

### 19.109.2 Member Function Documentation

#### 19.109.2.1 update()

```
void SpineMLSimulator::InputValue::TimeVarying::update (
    double dt,
    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) [override], [virtual]
```

Implements [SpineMLSimulator::InputValue::Base](#).


The documentation for this class was generated from the following files:

- [inputValue.h](#)
- [inputValue.cc](#)

### 19.110 SpineMLSimulator::InputValue::TimeVaryingArray Class Reference

```
#include <inputValue.h>
```

Inheritance diagram for SpineMLSimulator::InputValue::TimeVaryingArray:



## Public Member Functions

- [TimeVaryingArray](#) (double dt, unsigned int numNeurons, const pugi::xml\_node &node)
- virtual void [update](#) (double dt, unsigned long long timestep, std::function< void(unsigned int, double)> applyValueFunc) override

## Additional Inherited Members

### 19.110.1 Constructor & Destructor Documentation

## 19.110.1.1 TimeVaryingArray()

```
SpineMLSimulator::InputValue::TimeVaryingArray::TimeVaryingArray (
    double dt,
    unsigned int numNeurons,
    const pugi::xml_node & node )
```

## 19.110.2 Member Function Documentation

## 19.110.2.1 update()

```
void SpineMLSimulator::InputValue::TimeVaryingArray::update (
    double dt,
    unsigned long long timestep,
    std::function< void(unsigned int, double)> applyValueFunc ) [override], [virtual]
```

Implements [SpineMLSimulator::InputValue::Base](#).

The documentation for this class was generated from the following files:


- [inputValue.h](#)
- [inputValue.cc](#)

## 19.111 NeuronModels::TraubMiles Class Reference

Hodgkin-Huxley neurons with Traub & Miles algorithm.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::TraubMiles:



## Public Types

- typedef [Snippet::ValueBase](#)< 7 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 4 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*

- virtual std::string `getThresholdConditionCode` () const override  
*Gets code which defines the condition for a true spike in the described neuron model.*
- virtual `StringVec` `getParamNames` () const override  
*Gets names of (independent) model parameters.*
- virtual `VarVec` `getVars` () const override  
*Gets names and types (as strings) of model variables.*

#### Static Public Member Functions

- static const `NeuronModels::TraubMiles` \* `getInstance` ()

#### Additional Inherited Members

##### 19.111.1 Detailed Description

Hodgkin-Huxley neurons with Traub & Miles algorithm.

This conductance based model has been taken from [7] and can be described by the equations:

$$\begin{aligned}
 C \frac{dV}{dt} &= -I_{\text{Na}} - I_K - I_{\text{leak}} - I_M - I_{i,DC} - I_{i,\text{syn}} - I_i, \\
 I_{\text{Na}}(t) &= g_{\text{Na}} m_i(t)^3 h_i(t) (V_i(t) - E_{\text{Na}}) \\
 I_K(t) &= g_K n_i(t)^4 (V_i(t) - E_K) \\
 \frac{dy(t)}{dt} &= \alpha_y(V(t))(1 - y(t)) - \beta_y(V(t))y(t),
 \end{aligned}$$

where  $y_i = m, h, n$ , and

$$\begin{aligned}
 \alpha_n &= 0.032(-50 - V) / (\exp((-50 - V)/5) - 1) \\
 \beta_n &= 0.5 \exp((-55 - V)/40) \\
 \alpha_m &= 0.32(-52 - V) / (\exp((-52 - V)/4) - 1) \\
 \beta_m &= 0.28(25 + V) / (\exp((25 + V)/5) - 1) \\
 \alpha_h &= 0.128 \exp((-48 - V)/18) \\
 \beta_h &= 4 / (\exp((-25 - V)/5) + 1).
 \end{aligned}$$

and typical parameters are  $C = 0.143$  nF,  $g_{\text{leak}} = 0.02672$   $\mu\text{S}$ ,  $E_{\text{leak}} = -63.563$  mV,  $g_{\text{Na}} = 7.15$   $\mu\text{S}$ ,  $E_{\text{Na}} = 50$  mV,  $g_K = 1.43$   $\mu\text{S}$ ,  $E_K = -95$  mV.

It has 4 variables:

- $V$  - membrane potential E
- $m$  - probability for Na channel activation m
- $h$  - probability for not Na channel blocking h
- $n$  - probability for K channel activation n

and 7 parameters:

- $g_{\text{Na}}$  - Na conductance in  $1/(\text{mOhms} * \text{cm}^2)$
- $E_{\text{Na}}$  - Na equi potential in mV
- $g_K$  - K conductance in  $1/(\text{mOhms} * \text{cm}^2)$
- $E_K$  - K equi potential in mV



- $g_l$  - Leak conductance in  $1/(\text{mOhms} * \text{cm}^2)$
- $E_l$  - Leak equi potential in mV
- $C_{\text{mem}}$  - Membrane capacity density in  $\mu\text{F}/\text{cm}^2$

#### Note

Internally, the ordinary differential equations defining the model are integrated with a linear Euler algorithm and GeNN integrates 25 internal time steps for each neuron for each network time step. I.e., if the network is simulated at  $\text{DT} = 0.1 \text{ ms}$ , then the neurons are integrated with a linear Euler algorithm with  $\text{ldt} = 0.004 \text{ ms}$ . This variant uses IF statements to check for a value at which a singularity would be hit. If so, value calculated by L'Hospital rule is used.

### 19.111.2 Member Typedef Documentation

#### 19.111.2.1 ParamValues

```
typedef Snippet::ValueBase< 7 > NeuronModels::TraubMiles::ParamValues
```

#### 19.111.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMiles::PostVarValues
```

#### 19.111.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMiles::PreVarValues
```

#### 19.111.2.4 VarValues

```
typedef Models::VarInitContainerBase< 4 > NeuronModels::TraubMiles::VarValues
```

### 19.111.3 Member Function Documentation

#### 19.111.3.1 getInstance()

```
static const NeuronModels::TraubMiles* NeuronModels::TraubMiles::getInstance ( ) [inline],  
[static]
```

#### 19.111.3.2 getParamNames()

```
virtual StringVec NeuronModels::TraubMiles::getParamNames ( ) const [inline], [override],  
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

Reimplemented in [NeuronModels::TraubMilesNStep](#).

### 19.111.3.3 getSimCode()

```
virtual std::string NeuronModels::TraubMiles::getSimCode ( ) const [inline], [override], [virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::Base](#).

Reimplemented in [NeuronModels::TraubMilesNStep](#), [NeuronModels::TraubMilesAlt](#), and [NeuronModels::TraubMilesFast](#).

### 19.111.3.4 getThresholdConditionCode()

```
virtual std::string NeuronModels::TraubMiles::getThresholdConditionCode ( ) const [inline], [override], [virtual]
```

Gets code which defines the condition for a true spike in the described neuron model.

This evaluates to a bool (e.g. "V > 20").

Reimplemented from [NeuronModels::Base](#).

### 19.111.3.5 getVars()

```
virtual VarVec NeuronModels::TraubMiles::getVars ( ) const [inline], [override], [virtual]
```

Gets names and types (as strings) of model variables.

Reimplemented from [Models::Base](#).

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.112 NeuronModels::TraubMilesAlt Class Reference

Hodgkin-Huxley neurons with Traub & Miles algorithm.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::TraubMilesAlt:



## Public Types

- typedef [Snippet::ValueBase](#)< 7 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 4 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

## Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*

## Static Public Member Functions

- static const [NeuronModels::TraubMilesAlt](#) \* [getInstance](#) ()

## Additional Inherited Members

### 19.112.1 Detailed Description

Hodgkin-Huxley neurons with Traub & Miles algorithm.

Using a workaround to avoid singularity: adding the minimum numerical value of the floating point precision used.

### 19.112.2 Member Typedef Documentation

#### 19.112.2.1 ParamValues

```
typedef Snippet::ValueBase< 7 > NeuronModels::TraubMilesAlt::ParamValues
```

#### 19.112.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMilesAlt::PostVarValues
```

#### 19.112.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMilesAlt::PreVarValues
```

#### 19.112.2.4 VarValues

```
typedef Models::VarInitContainerBase< 4 > NeuronModels::TraubMilesAlt::VarValues
```

### 19.112.3 Member Function Documentation

### 19.112.3.1 getInstance()

```
static const NeuronModels::TraubMilesAlt* NeuronModels::TraubMilesAlt::getInstance ( ) [inline],
[static]
```

### 19.112.3.2 getSimCode()

```
virtual std::string NeuronModels::TraubMilesAlt::getSimCode ( ) const [inline], [override],
[virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::TraubMiles](#).

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.113 NeuronModels::TraubMilesFast Class Reference

Hodgkin-Huxley neurons with Traub & Miles algorithm: Original fast implementation, using 25 inner iterations.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::TraubMilesFast:



### Public Types

- typedef [Snippet::ValueBase](#)< 7 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 4 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

### Public Member Functions

- virtual std::string [getSimCode](#) ( ) const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*

### Static Public Member Functions

- static const [NeuronModels::TraubMilesFast](#) \* [getInstance](#) ( )

## Additional Inherited Members

### 19.113.1 Detailed Description

Hodgkin-Huxley neurons with Traub & Miles algorithm: Original fast implementation, using 25 inner iterations.

There are singularities in this model, which can be easily hit in float precision

### 19.113.2 Member Typedef Documentation

#### 19.113.2.1 ParamValues

```
typedef Snippet::ValueBase< 7 > NeuronModels::TraubMilesFast::ParamValues
```

#### 19.113.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMilesFast::PostVarValues
```

#### 19.113.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMilesFast::PreVarValues
```

#### 19.113.2.4 VarValues

```
typedef Models::VarInitContainerBase< 4 > NeuronModels::TraubMilesFast::VarValues
```

### 19.113.3 Member Function Documentation

#### 19.113.3.1 getInstance()

```
static const NeuronModels::TraubMilesFast* NeuronModels::TraubMilesFast::getInstance ( ) [inline],  
[static]
```

#### 19.113.3.2 getSimCode()

```
virtual std::string NeuronModels::TraubMilesFast::getSimCode ( ) const [inline], [override],  
[virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::TraubMiles](#).

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.114 NeuronModels::TraubMilesNStep Class Reference

Hodgkin-Huxley neurons with Traub & Miles algorithm.

```
#include <neuronModels.h>
```

Inheritance diagram for NeuronModels::TraubMilesNStep:



### Public Types

- typedef [Snippet::ValueBase](#)< 8 > [ParamValues](#)
- typedef [Models::VarInitContainerBase](#)< 4 > [VarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PreVarValues](#)
- typedef [Models::VarInitContainerBase](#)< 0 > [PostVarValues](#)

### Public Member Functions

- virtual std::string [getSimCode](#) () const override  
*Gets the code that defines the execution of one timestep of integration of the neuron model.*
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*

### Static Public Member Functions

- static const [NeuronModels::TraubMilesNStep](#) \* [getInstance](#) ()

### Additional Inherited Members

#### 19.114.1 Detailed Description

Hodgkin-Huxley neurons with Traub & Miles algorithm.

Same as standard [TraubMiles](#) model but number of inner loops can be set using a parameter

#### 19.114.2 Member Typedef Documentation

##### 19.114.2.1 ParamValues

```
typedef Snippet::ValueBase< 8 > NeuronModels::TraubMilesNStep::ParamValues
```

## 19.114.2.2 PostVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMilesNStep::PostVarValues
```

## 19.114.2.3 PreVarValues

```
typedef Models::VarInitContainerBase<0> NeuronModels::TraubMilesNStep::PreVarValues
```

## 19.114.2.4 VarValues

```
typedef Models::VarInitContainerBase< 4 > NeuronModels::TraubMilesNStep::VarValues
```

## 19.114.3 Member Function Documentation

## 19.114.3.1 getInstance()

```
static const NeuronModels::TraubMilesNStep* NeuronModels::TraubMilesNStep::getInstance ( )
[inline], [static]
```

## 19.114.3.2 getParamNames()

```
virtual StringVec NeuronModels::TraubMilesNStep::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [NeuronModels::TraubMiles](#).

## 19.114.3.3 getSimCode()

```
virtual std::string NeuronModels::TraubMilesNStep::getSimCode ( ) const [inline], [override],
[virtual]
```

Gets the code that defines the execution of one timestep of integration of the neuron model.

The code will refer to for the value of the variable with name "NN". It needs to refer to the predefined variable "ISYN", i.e. contain , if it is to receive input.

Reimplemented from [NeuronModels::TraubMiles](#).

The documentation for this class was generated from the following file:


- [neuronModels.h](#)

## 19.115 InitVarSnippet::Uniform Class Reference

Initialises variable by sampling from the uniform distribution.

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Uniform:



### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitVarSnippet::Uniform](#), 2)
- [SET\\_CODE](#) ("const scalar scale = \$(max) - \$(min);\n "\$ (value)=\$(min)+\$(gennrand\_uniform) \*scale);")
- virtual [StringVec](#) [getParamNames](#) () const override  
*Gets names of of (independent) model parameters.*

### Additional Inherited Members

#### 19.115.1 Detailed Description

Initialises variable by sampling from the uniform distribution.

This snippet takes 2 parameters:

- `min` - The minimum value
- `max` - The maximum value

#### 19.115.2 Member Function Documentation

##### 19.115.2.1 DECLARE\_SNIPPET()

```
InitVarSnippet::Uniform::DECLARE_SNIPPET (
    InitVarSnippet::Uniform ,
    2 )
```

##### 19.115.2.2 getParamNames()

```
virtual StringVec InitVarSnippet::Uniform::getParamNames ( ) const [inline], [override],
[virtual]
```

Gets names of of (independent) model parameters.

Reimplemented from [Snippet::Base](#).

##### 19.115.2.3 SET\_CODE()

```
InitVarSnippet::Uniform::SET_CODE (
    "const scalar scale = $(max) - $(min);\n "$ (value)=$(min)+$(gennrand_uniform) *scale);"
```

The documentation for this class was generated from the following file:


- [initVarSnippet.h](#)



## 19.116 SpineMLSimulator::ModelProperty::UniformDistribution Class Reference

```
#include <modelProperty.h>
```

Inheritance diagram for SpineMLSimulator::ModelProperty::UniformDistribution:



## Public Member Functions

- [UniformDistribution](#) (const pugi::xml\_node &node, const [StateVar](#)< [scalar](#) > &stateVar, unsigned int size)
- void [setValue](#) ([scalar](#) min, [scalar](#) max)

## 19.116.1 Constructor &amp; Destructor Documentation

## 19.116.1.1 UniformDistribution()

```
SpineMLSimulator::ModelProperty::UniformDistribution::UniformDistribution (
    const pugi::xml_node & node,
    const StateVar< scalar > & stateVar,
    unsigned int size )
```

## 19.116.2 Member Function Documentation

## 19.116.2.1 setValue()

```
void SpineMLSimulator::ModelProperty::UniformDistribution::setValue (
    scalar min,
    scalar max )
```

The documentation for this class was generated from the following files:


- [modelProperty.h](#)
- [modelProperty.cc](#)

## 19.117 InitVarSnippet::Uninitialised Class Reference

Used to mark variables as uninitialised - no initialisation code will be run.

```
#include <initVarSnippet.h>
```

Inheritance diagram for InitVarSnippet::Uninitialised:



#### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitVarSnippet::Uninitialised](#), 0)

#### Additional Inherited Members

##### 19.117.1 Detailed Description

Used to mark variables as uninitialised - no initialisation code will be run.

##### 19.117.2 Member Function Documentation

###### 19.117.2.1 DECLARE\_SNIPPET()

```
InitVarSnippet::Uninitialised::DECLARE_SNIPPET (
    InitVarSnippet::Uninitialised ,
    0 )
```

The documentation for this class was generated from the following file:


- [initVarSnippet.h](#)

## 19.118 InitSparseConnectivitySnippet::Uninitialised Class Reference

Used to mark connectivity as uninitialised - no initialisation code will be run.

```
#include <initSparseConnectivitySnippet.h>
```

Inheritance diagram for InitSparseConnectivitySnippet::Uninitialised:



#### Public Member Functions

- [DECLARE\\_SNIPPET](#) ([InitSparseConnectivitySnippet::Uninitialised](#), 0)

## Additional Inherited Members

### 19.118.1 Detailed Description

Used to mark connectivity as uninitialised - no initialisation code will be run.

### 19.118.2 Member Function Documentation

#### 19.118.2.1 DECLARE\_SNIPPET()

```
InitSparseConnectivitySnippet::Uninitialised::DECLARE_SNIPPET (
    InitSparseConnectivitySnippet::Uninitialised ,
    0 )
```

The documentation for this class was generated from the following file:

- [initSparseConnectivitySnippet.h](#)

## 19.119 Snippet::ValueBase< NumVars > Class Template Reference

```
#include <snippet.h>
```

### Public Member Functions

- `template<typename... T>`  
[ValueBase](#) (T &&... vals)
- `const std::vector< double > & getValues () const`  
*Gets values as a vector of doubles.*
- `double operator\[\] (size_t pos) const`

### 19.119.1 Constructor & Destructor Documentation

#### 19.119.1.1 ValueBase()

```
template<size_t NumVars>
template<typename... T>
Snippet::ValueBase< NumVars >::ValueBase (
    T &&... vals ) [inline]
```

### 19.119.2 Member Function Documentation

#### 19.119.2.1 getValues()

```
template<size_t NumVars>
const std::vector<double>& Snippet::ValueBase< NumVars >::getValues ( ) const [inline]
```

Gets values as a vector of doubles.

### 19.119.2.2 operator[]()

```
template<size_t NumVars>
double Snippet::ValueBase< NumVars >::operator[] (
    size_t pos ) const [inline]
```

The documentation for this class was generated from the following file:

- [snippet.h](#)

## 19.120 Snippet::ValueBase< 0 > Class Template Reference

```
#include <snippet.h>
```

### Public Member Functions

- template<typename... T>  
ValueBase (T &&... vals)
- std::vector< double > [getValues](#) () const  
*Gets values as a vector of doubles.*

### 19.120.1 Detailed Description

```
template<>
class Snippet::ValueBase< 0 >
```

Template specialisation of [ValueBase](#) to avoid compiler warnings in the case when a model requires no parameters or state variables

### 19.120.2 Constructor & Destructor Documentation

#### 19.120.2.1 ValueBase()

```
template<typename... T>
Snippet::ValueBase< 0 >::ValueBase (
    T &&... vals ) [inline]
```

### 19.120.3 Member Function Documentation

#### 19.120.3.1 getValues()

```
std::vector<double> Snippet::ValueBase< 0 >::getValues ( ) const [inline]
```

Gets values as a vector of doubles.


The documentation for this class was generated from the following file:

- [snippet.h](#)

## 19.121 SpineMLSimulator::ModelProperty::ValueList Class Reference

```
#include <modelProperty.h>
```

Inheritance diagram for SpineMLSimulator::ModelProperty::ValueList:



### Public Member Functions

- [ValueList](#) (const pugi::xml\_node &node, const filesystem::path &basePath, const std::vector< unsigned int > \*remapIndices, const [StateVar](#)< [scalar](#) > &stateVar, unsigned int size)
- void [setValue](#) (const std::vector< [scalar](#) > &values, const std::vector< unsigned int > \*remapIndices)

### 19.121.1 Constructor & Destructor Documentation

#### 19.121.1.1 ValueList()

```
SpineMLSimulator::ModelProperty::ValueList::ValueList (
    const pugi::xml_node & node,
    const filesystem::path & basePath,
    const std::vector< unsigned int > * remapIndices,
    const StateVar< scalar > & stateVar,
    unsigned int size )
```

### 19.121.2 Member Function Documentation

#### 19.121.2.1 setValue()

```
void SpineMLSimulator::ModelProperty::ValueList::setValue (
    const std::vector< scalar > & values,
    const std::vector< unsigned int > * remapIndices )
```

The documentation for this class was generated from the following files:

- [modelProperty.h](#)
- [modelProperty.cc](#)

## 19.122 Models::Base::Var Struct Reference

A variable has a name, a type and an access type.

```
#include <models.h>
```

### Public Member Functions

- [Var](#) (const std::string &n, const std::string &t, [VarAccess](#) a)

- [Var](#) (const std::string &n, const std::string &t)
- [Var](#) ()

#### Public Attributes

- std::string [name](#)
- std::string [type](#)
- [VarAccess](#) [access](#)

#### 19.122.1 Detailed Description

A variable has a name, a type and an access type.

Explicit constructors required as although, through the wonders of C++ aggregate initialization, access would default to [VarAccess::READ\\_WRITE](#) if not specified, this results in a -Wmissing-field-initializers warning on GCC and Clang

#### 19.122.2 Constructor & Destructor Documentation

##### 19.122.2.1 [Var\(\)](#) [1/3]

```
Models::Base::Var::Var (  
    const std::string & n,  
    const std::string & t,  
    VarAccess a ) [inline]
```

##### 19.122.2.2 [Var\(\)](#) [2/3]

```
Models::Base::Var::Var (  
    const std::string & n,  
    const std::string & t ) [inline]
```

##### 19.122.2.3 [Var\(\)](#) [3/3]

```
Models::Base::Var::Var ( ) [inline]
```

#### 19.122.3 Member Data Documentation

##### 19.122.3.1 [access](#)

[VarAccess](#) Models::Base::Var::access

##### 19.122.3.2 [name](#)

std::string Models::Base::Var::name

## 19.122.3.3 type

```
std::string Models::Base::Var::type
```


The documentation for this struct was generated from the following file:

- [models.h](#)

## 19.123 pygenn.model\_preprocessor.Variable Class Reference

Class holding information about GeNN variables.

Inheritance diagram for pygenn.model\_preprocessor.Variable:



## Public Member Functions

- `def __init__(self, variable_name, variable_type, values=None)`  
Init *Variable*.
- `def set_values(self, values)`  
Set *Variable*'s values.

## Public Attributes

- [name](#)
- [type](#)
- [view](#)
- [needs\\_allocation](#)
- [init\\_required](#)
- [init\\_val](#)
- [values](#)

## 19.123.1 Detailed Description

Class holding information about GeNN variables.

## 19.123.2 Constructor &amp; Destructor Documentation

## 19.123.2.1 \_\_init\_\_()

```
def pygenn.model_preprocessor.Variable.__init__(
    self,
    variable_name,
    variable_type,
    values = None )
```

Init *Variable*.

**Parameters**

<i>variable_name</i>	string name of the variable
<i>variable_type</i>	string type of the variable
<i>values</i>	iterable, single value or VarInit instance

**19.123.3 Member Function Documentation****19.123.3.1 set\_values()**

```
def pygenn.model_preprocessor.Variable.set_values (
    self,
    values )
```

Set [Variable](#)'s values.

**Parameters**

<i>values</i>	iterable, single value or VarInit instance
---------------	--

**19.123.4 Member Data Documentation****19.123.4.1 init\_required**

```
pygenn.model_preprocessor.Variable.init_required
```

**19.123.4.2 init\_val**

```
pygenn.model_preprocessor.Variable.init_val
```

**19.123.4.3 name**

```
pygenn.model_preprocessor.Variable.name
```

**19.123.4.4 needs\_allocation**

```
pygenn.model_preprocessor.Variable.needs_allocation
```

**19.123.4.5 type**

```
pygenn.model_preprocessor.Variable.type
```

**19.123.4.6 values**

```
pygenn.model_preprocessor.Variable.values
```



## 19.123.4.7 view

pygenn.model\_preprocessor.Variable.view


The documentation for this class was generated from the following file:

- [model\\_preprocessor.py](#)

## 19.124 Models::VarInit Class Reference

```
#include <models.h>
```

Inheritance diagram for Models::VarInit:



## Public Member Functions

- [VarInit](#) (const [InitVarSnippet::Base](#) \*snippet, const std::vector< double > &params)
- [VarInit](#) (double constant)

## 19.124.1 Constructor &amp; Destructor Documentation

## 19.124.1.1 VarInit() [1/2]

```
Models::VarInit::VarInit (
    const InitVarSnippet::Base * snippet,
    const std::vector< double > & params ) [inline]
```

## 19.124.1.2 VarInit() [2/2]

```
Models::VarInit::VarInit (
    double constant ) [inline]
```

The documentation for this class was generated from the following file:

- [models.h](#)

## 19.125 Models::VarInitContainerBase&lt; NumVars &gt; Class Template Reference

```
#include <models.h>
```

## Public Member Functions

- template<typename... T>  
[VarInitContainerBase](#) (T &&... initialisers)

- `const std::vector< VarInit > & getInitialisers () const`  
*Gets initialisers as a vector of Values.*
- `const VarInit & operator[] (size_t pos) const`

### 19.125.1 Detailed Description

```
template<size_t NumVars>
class Models::VarInitContainerBase< NumVars >
```

Wrapper to ensure at compile time that correct number of value initialisers are used when specifying the values of a model's initial state.

### 19.125.2 Constructor & Destructor Documentation

#### 19.125.2.1 VarInitContainerBase()

```
template<size_t NumVars>
template<typename... T>
Models::VarInitContainerBase< NumVars >::VarInitContainerBase (
    T &&... initialisers ) [inline]
```

### 19.125.3 Member Function Documentation

#### 19.125.3.1 getInitialisers()

```
template<size_t NumVars>
const std::vector<VarInit>& Models::VarInitContainerBase< NumVars >::getInitialisers ( )
const [inline]
```

Gets initialisers as a vector of Values.

#### 19.125.3.2 operator[]()

```
template<size_t NumVars>
const VarInit& Models::VarInitContainerBase< NumVars >::operator[] (
    size_t pos ) const [inline]
```

The documentation for this class was generated from the following file:

- [models.h](#)

## 19.126 Models::VarInitContainerBase< 0 > Class Template Reference

```
#include <models.h>
```

### Public Member Functions

- `template<typename... T>`  
`VarInitContainerBase (T &&... initialisers)`
- `VarInitContainerBase (const Snippet::ValueBase< 0 > &)`

- `std::vector< VarInit > getInitialisers ()` const

*Gets initialisers as a vector of Values.*

### 19.126.1 Detailed Description

```
template<>
class Models::VarInitContainerBase< 0 >
```

Template specialisation of ValueInitBase to avoid compiler warnings in the case when a model requires no variable initialisers

### 19.126.2 Constructor & Destructor Documentation

#### 19.126.2.1 VarInitContainerBase() [1/2]

```
template<typename... T>
Models::VarInitContainerBase< 0 >::VarInitContainerBase (
    T &&... initialisers ) [inline]
```

#### 19.126.2.2 VarInitContainerBase() [2/2]

```
Models::VarInitContainerBase< 0 >::VarInitContainerBase (
    const Snippet::ValueBase< 0 > & ) [inline]
```

### 19.126.3 Member Function Documentation

#### 19.126.3.1 getInitialisers()

```
std::vector<VarInit> Models::VarInitContainerBase< 0 >::getInitialisers ( ) const [inline]
```

*Gets initialisers as a vector of Values.*

The documentation for this class was generated from the following file:

- [models.h](#)

## 20 File Documentation

### 20.1 00\_MainPage.dox File Reference

### 20.2 01\_Installation.dox File Reference

### 20.3 02\_Quickstart.dox File Reference

### 20.4 03\_Examples.dox File Reference

### 20.5 05\_SpineML.dox File Reference

## 20.6 06\_Brian2GeNN.dox File Reference

## 20.7 07\_PyGeNN.dox File Reference

## 20.8 09\_ReleaseNotes.dox File Reference

## 20.9 10\_UserManual.dox File Reference

## 20.10 11\_Tutorial.dox File Reference

## 20.11 12\_Tutorial.dox File Reference

## 20.12 13\_UserGuide.dox File Reference

## 20.13 14\_Credits.dox File Reference

## 20.14 \_\_init\_\_.py File Reference

### Namespaces

- [pygenn](#)

## 20.15 analogueRecorder.h File Reference

```
#include <fstream>
#include <initializer_list>
#include <string>
#include <vector>
```

### Classes

- class [AnalogueRecorder](#)< T >

## 20.16 backend.cc File Reference

```
#include "backend.h"
#include <algorithm>
#include <numeric>
#include "gennUtils.h"
#include "logging.h"
#include "modelSpecInternal.h"
#include "code_generator/codeStream.h"
#include "code_generator/substitutions.h"
#include "code_generator/codeGenUtils.h"
#include "utils.h"
```

### Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::CUDA](#)

## 20.17 backend.cc File Reference

```
#include "backend.h"
#include <random>
#include "gennUtils.h"
#include "modelSpecInternal.h"
#include "code_generator/codeStream.h"
#include "code_generator/substitutions.h"
#include "code_generator/codeGenUtils.h"
```

### Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::SingleThreadedCPU](#)

## 20.18 backend.h File Reference

```
#include <algorithm>
#include <array>
#include <functional>
#include <map>
#include <string>
#include <unordered_set>
#include <cuda.h>
#include <cuda_runtime.h>
#include "backendExport.h"
#include "code_generator/backendBase.h"
#include "code_generator/codeStream.h"
#include "code_generator/substitutions.h"
#include "presynapticUpdateStrategy.h"
```

### Classes

- struct [CodeGenerator::CUDA::Preferences](#)  
*Preferences for CUDA backend.*
- class [CodeGenerator::CUDA::Backend](#)

### Namespaces

- [filesystem](#)
- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::CUDA](#)

### Typedefs

- using [CodeGenerator::CUDA::KernelBlockSize](#) = std::array< size\_t, KernelMax >  
*Array of block sizes for each kernel.*

## Enumerations

- enum `CodeGenerator::CUDA::DeviceSelect` { `CodeGenerator::CUDA::DeviceSelect::OPTIMAL`, `CodeGenerator::CUDA::DeviceSelect::MOST_MEMORY`, `CodeGenerator::CUDA::DeviceSelect::MANUAL` }  
*Methods for selecting CUDA device.*
- enum `CodeGenerator::CUDA::BlockSizeSelect` { `CodeGenerator::CUDA::BlockSizeSelect::OCCUPANCY`, `CodeGenerator::CUDA::BlockSizeSelect::MANUAL` }  
*Methods for selecting CUDA kernel block size.*
- enum `CodeGenerator::CUDA::Kernel` { `CodeGenerator::CUDA::KernelNeuronUpdate`, `CodeGenerator::CUDA::KernelPresynapticUpdate`, `CodeGenerator::CUDA::KernelPostsynapticUpdate`, `CodeGenerator::CUDA::KernelSynapseDynamicsUpdate`, `CodeGenerator::CUDA::KernelInitialize`, `CodeGenerator::CUDA::KernelInitializeSparse`, `CodeGenerator::CUDA::KernelPreNeuronReset`, `CodeGenerator::CUDA::KernelPreSynapseReset`, `CodeGenerator::CUDA::KernelMax` }  
*Kernels generated by CUDA backend.*

## 20.19 backend.h File Reference

```
#include <functional>
#include <map>
#include <string>
#include "backendExport.h"
#include "code_generator/backendBase.h"
```

## Classes

- struct `CodeGenerator::SingleThreadedCPU::Preferences`
- class `CodeGenerator::SingleThreadedCPU::Backend`

## Namespaces

- `filesystem`
- `CodeGenerator`  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- `CodeGenerator::SingleThreadedCPU`

## 20.20 backendBase.cc File Reference

```
#include "code_generator/backendBase.h"
#include "gennUtils.h"
#include "logging.h"
```

## Macros

- `#define TYPE(T) {#T, sizeof(T)}`

### 20.20.1 Macro Definition Documentation

## 20.20.1.1 TYPE

```
#define TYPE(  
    T ) {#T, sizeof(T)}
```

## 20.21 backendBase.h File Reference

```
#include <functional>  
#include <map>  
#include <string>  
#include <unordered_map>  
#include <vector>  
#include <plog/Severity.h>  
#include "codeStream.h"  
#include "gennExport.h"  
#include "variableMode.h"
```

## Classes

- struct [CodeGenerator::PreferencesBase](#)  
*Base class for backend preferences - can be accessed via a global in 'classic' C++ code generator.*
- class [CodeGenerator::MemAlloc](#)
- class [CodeGenerator::BackendBase](#)

## Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*

## 20.22 backendExport.h File Reference

## Macros

- #define [BACKEND\\_EXPORT](#)

## 20.22.1 Macro Definition Documentation

## 20.22.1.1 BACKEND\_EXPORT

```
#define BACKEND_EXPORT
```

## 20.23 binomial.cc File Reference

```
#include "binomial.h"  
#include <stdexcept>  
#include <cassert>  
#include <cmath>  
#include <cstdint>
```

## Functions

- unsigned int [binomialInverseCDF](#) (double cdf, unsigned int n, double p)

### 20.23.1 Function Documentation

#### 20.23.1.1 binomialInverseCDF()

```
unsigned int binomialInverseCDF (  
    double cdf,  
    unsigned int n,  
    double p )
```

### 20.24 binomial.h File Reference

```
#include "gennExport.h"
```

## Functions

- [GENN\\_EXPORT](#) unsigned int [binomialInverseCDF](#) (double cdf, unsigned int n, double p)

### 20.24.1 Function Documentation

#### 20.24.1.1 binomialInverseCDF()

```
GENN\_EXPORT unsigned int binomialInverseCDF (  
    double cdf,  
    unsigned int n,  
    double p )
```

### 20.25 codeGenUtils.cc File Reference

```
#include "code_generator/codeGenUtils.h"  
#include <regex>  
#include <cstring>  
#include "modelSpec.h"  
#include "code_generator/substitutions.h"
```

## Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*

## Enumerations

- enum [MathsFunc](#)



## Functions

- void `CodeGenerator::substitute` (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting strings in the neuron code strings or other templates.*
- bool `CodeGenerator::regexVarSubstitute` (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting variable names in the neuron code strings or other templates using regular expressions.*
- bool `CodeGenerator::regexFuncSubstitute` (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting function names in the neuron code strings or other templates using regular expressions.*
- void `CodeGenerator::functionSubstitute` (std::string &code, const std::string &funcName, unsigned int num←Params, const std::string &replaceFuncTemplate)  
*This function substitutes function calls in the form:*
- std::string `CodeGenerator::ensureFtype` (const std::string &oldcode, const std::string &type)  
*This function implements a parser that converts any floating point constant in a code snippet to a floating point constant with an explicit precision (by appending "f" or removing it).*
- void `CodeGenerator::checkUnreplacedVariables` (const std::string &code, const std::string &codeName)  
*This function checks for unknown variable definitions and returns a `gennError` if any are found.*
- void `CodeGenerator::preNeuronSubstitutionsInSynapticCode` (Substitutions &substitutions, const `Synapse←GroupInternal` &sg, const std::string &offset, const std::string &axonalDelayOffset, const std::string &postIdx, const std::string &devPrefix, const std::string &preVarPrefix="", const std::string &preVarSuffix="")  
*suffix to be used for presynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`*
- void `CodeGenerator::postNeuronSubstitutionsInSynapticCode` (Substitutions &substitutions, const `SynapseGroupInternal` &sg, const std::string &offset, const std::string &backPropDelayOffset, const std::string &preIdx, const std::string &devPrefix, const std::string &postVarPrefix="", const std::string &postVar←Suffix="")  
*suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`*
- void `CodeGenerator::neuronSubstitutionsInSynapticCode` (Substitutions &substitutions, const `Synapse←GroupInternal` &sg, const std::string &preIdx, const std::string &postIdx, const std::string &devPrefix, double dt, const std::string &preVarPrefix="", const std::string &preVarSuffix="", const std::string &postVarPrefix="", const std::string &postVarSuffix="")  
*Function for performing the code and value substitutions necessary to insert neuron related variables, parameters, and extraGlobal parameters into synaptic code.*

## 20.25.1 Enumeration Type Documentation

## 20.25.1.1 MathsFunc

```
enum MathsFunc
```

## 20.26 codeGenUtils.h File Reference

```
#include <iomanip>
#include <limits>
#include <string>
#include <sstream>
#include <vector>
#include "models.h"
#include "snippet.h"
#include "variableMode.h"
```

## Classes

- struct [CodeGenerator::FunctionTemplate](#)

## Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

## Functions

- void [CodeGenerator::substitute](#) (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting strings in the neuron code strings or other templates.*
- bool [CodeGenerator::regexVarSubstitute](#) (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting variable names in the neuron code strings or other templates using regular expressions.*
- bool [CodeGenerator::regexFuncSubstitute](#) (std::string &s, const std::string &trg, const std::string &rep)  
*Tool for substituting function names in the neuron code strings or other templates using regular expressions.*
- void [CodeGenerator::functionSubstitute](#) (std::string &code, const std::string &funcName, unsigned int num↵ Params, const std::string &replaceFuncTemplate)  
*This function substitutes function calls in the form:*
- template<class T, typename std::enable\_if< std::is\_floating\_point< T >::value >::type \* = nullptr>  
void [CodeGenerator::writePreciseString](#) (std::ostream &os, T value)  
*This function writes a floating point value to a stream -setting the precision so no digits are lost.*
- template<class T, typename std::enable\_if< std::is\_floating\_point< T >::value >::type \* = nullptr>  
std::string [CodeGenerator::writePreciseString](#) (T value)  
*This function writes a floating point value to a string - setting the precision so no digits are lost.*
- size\_t [CodeGenerator::ceilDivide](#) (size\_t numerator, size\_t denominator)  
*Divide two integers, rounding up i.e. effectively taking ceil.*
- size\_t [CodeGenerator::padSize](#) (size\_t size, size\_t blockSize)  
*Pad an integer to a multiple of another.*
- std::string [CodeGenerator::ensureFType](#) (const std::string &oldcode, const std::string &type)  
*This function implements a parser that converts any floating point constant in a code snippet to a floating point constant with an explicit precision (by appending "f" or removing it).*
- void [CodeGenerator::checkUnreplacedVariables](#) (const std::string &code, const std::string &codeName)  
*This function checks for unknown variable definitions and returns a `gennError` if any are found.*
- void [CodeGenerator::preNeuronSubstitutionsInSynapticCode](#) (Substitutions &substitutions, const [Synapse↵ GroupInternal](#) &sg, const std::string &offset, const std::string &axonalDelayOffset, const std::string &postIdx, const std::string &devPrefix, const std::string &preVarPrefix="", const std::string &preVarSuffix="")  
*suffix to be used for presynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`*
- void [CodeGenerator::postNeuronSubstitutionsInSynapticCode](#) (Substitutions &substitutions, const [SynapseGroupInternal](#) &sg, const std::string &offset, const std::string &backPropDelayOffset, const std::string &preIdx, const std::string &devPrefix, const std::string &postVarPrefix="", const std::string &postVar↵ Suffix="")  
*suffix to be used for postsynaptic variable accesses - typically combined with prefix to wrap in function call such as `__ldg(&XXX)`*
- void [CodeGenerator::neuronSubstitutionsInSynapticCode](#) (Substitutions &substitutions, const [Synapse↵ GroupInternal](#) &sg, const std::string &preIdx, const std::string &postIdx, const std::string &devPrefix, double dt, const std::string &preVarPrefix="", const std::string &preVarSuffix="", const std::string &postVarPrefix="", const std::string &postVarSuffix="")  
*Function for performing the code and value substitutions necessary to insert neuron related variables, parameters, and extraGlobal parameters into synaptic code.*

## 20.27 codeStream.cc File Reference

```
#include "code_generator/codeStream.h"  
#include <algorithm>
```

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- [GENN\\_EXPORT](#) std::ostream & [CodeGenerator::operator<<](#) (std::ostream &s, const CodeStream::OB &ob)
- [GENN\\_EXPORT](#) std::ostream & [CodeGenerator::operator<<](#) (std::ostream &s, const CodeStream::CB &cb)

## 20.28 codeStream.h File Reference

```
#include <ostream>  
#include <stdexcept>  
#include <streambuf>  
#include <string>  
#include <vector>  
#include "logging.h"  
#include "gennExport.h"
```

### Classes

- class [CodeGenerator::CodeStream](#)
- struct [CodeGenerator::CodeStream::OB](#)  
*An open bracket marker.*
- struct [CodeGenerator::CodeStream::CB](#)  
*A close bracket marker.*
- class [CodeGenerator::CodeStream::Scope](#)

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- [GENN\\_EXPORT](#) std::ostream & [CodeGenerator::operator<<](#) (std::ostream &s, const CodeStream::OB &ob)
- [GENN\\_EXPORT](#) std::ostream & [CodeGenerator::operator<<](#) (std::ostream &s, const CodeStream::CB &cb)

## 20.29 connectors.cc File Reference

```
#include "connectors.h"  
#include <algorithm>  
#include <fstream>  
#include <iostream>
```

```
#include <numeric>
#include <random>
#include <tuple>
#include <vector>
#include <cassert>
#include <cstdint>
#include "path.h"
#include "pugixml/pugixml.hpp"
#include "spineMLLogging.h"
```

### 20.30 connectors.h File Reference

```
#include <vector>
#include <cstdint>
```

#### Namespaces

- [pugi](#)
- [filesystem](#)
- [SpineMLSimulator](#)
- [SpineMLSimulator::Connectors](#)

#### Functions

- unsigned int [SpineMLSimulator::Connectors::create](#) (const pugi::xml\_node &node, double dt, unsigned int numPre, unsigned int numPost, unsigned int \*\*rowLength, unsigned int \*\*ind, uint8\_t \*\*delay, const unsigned int \*maxRowLength, const filesystem::path &basePath, std::vector< unsigned int > &remapIndices)

### 20.31 currentSource.cc File Reference

```
#include "currentSource.h"
#include <algorithm>
#include <cmath>
#include "gennUtils.h"
```

### 20.32 currentSource.h File Reference

```
#include <map>
#include <set>
#include <string>
#include <vector>
#include "currentSourceModels.h"
#include "gennExport.h"
#include "variableMode.h"
```

#### Classes

- class [CurrentSource](#)

## 20.33 `currentSourceInternal.h` File Reference

```
#include "currentSource.h"
```

### Classes

- class [CurrentSourceInternal](#)

## 20.34 `currentSourceModels.cc` File Reference

```
#include "currentSourceModels.h"
```

### Functions

- [IMPLEMENT\\_MODEL](#) ([CurrentSourceModels::DC](#))
- [IMPLEMENT\\_MODEL](#) ([CurrentSourceModels::GaussianNoise](#))

### 20.34.1 Function Documentation

#### 20.34.1.1 [IMPLEMENT\\_MODEL\(\)](#) [1/2]

```
IMPLEMENT_MODEL (
    CurrentSourceModels::DC )
```

#### 20.34.1.2 [IMPLEMENT\\_MODEL\(\)](#) [2/2]

```
IMPLEMENT_MODEL (
    CurrentSourceModels::GaussianNoise )
```

## 20.35 `currentSourceModels.h` File Reference

```
#include <array>
#include <functional>
#include <string>
#include <tuple>
#include <vector>
#include <cmath>
#include "gennExport.h"
#include "models.h"
```

### Classes

- class [CurrentSourceModels::Base](#)  
*Base class for all current source models.*
- class [CurrentSourceModels::DC](#)  
*DC source.*
- class [CurrentSourceModels::GaussianNoise](#)  
*Noisy current source with noise drawn from normal distribution.*

## Namespaces

- [CurrentSourceModels](#)

## Macros

- `#define` [SET\\_INJECTION\\_CODE](#)(INJECTION\_CODE) virtual std::string getInjectionCode() const override{ return INJECTION\_CODE; }

### 20.35.1 Macro Definition Documentation

#### 20.35.1.1 SET\_INJECTION\_CODE

```
#define SET_INJECTION_CODE(  
    INJECTION_CODE ) virtual std::string getInjectionCode() const override{ return  
INJECTION_CODE; }
```

### 20.36 generateAll.cc File Reference

```
#include "code_generator/generateAll.h"  
#include <fstream>  
#include <string>  
#include <vector>  
#include <plog/Log.h>  
#include "path.h"  
#include "code_generator/codeStream.h"  
#include "code_generator/generateInit.h"  
#include "code_generator/generateMPI.h"  
#include "code_generator/generateNeuronUpdate.h"  
#include "code_generator/generateSupportCode.h"  
#include "code_generator/generateSynapseUpdate.h"  
#include "code_generator/generateRunner.h"
```

### 20.37 generateAll.h File Reference

```
#include <string>  
#include <vector>  
#include "gennExport.h"
```

## Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [filesystem](#)

## Functions

- [GENN\\_EXPORT](#) std::vector< std::string > [CodeGenerator::generateAll](#) (const [ModelSpecInternal](#) &model, const [BackendBase](#) &backend, const [filesystem::path](#) &outputPath, bool standaloneModules=false)

## 20.38 generateInit.cc File Reference

```
#include "code_generator/generateInit.h"
#include <string>
#include "models.h"
#include "modelSpecInternal.h"
#include "code_generator/codeGenUtils.h"
#include "code_generator/codeStream.h"
#include "code_generator/substitutions.h"
#include "code_generator/backendBase.h"
```

## 20.39 generateInit.h File Reference

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- void [CodeGenerator::generateInit](#) (CodeStream &os, const [ModelSpecInternal](#) &model, const BackendBase &backend, bool standaloneModules)

## 20.40 generateMakefile.cc File Reference

```
#include "code_generator/generateMakefile.h"
#include <string>
#include "modelSpec.h"
#include "code_generator/backendBase.h"
```

## 20.41 generateMakefile.h File Reference

```
#include <string>
#include <vector>
#include "gennExport.h"
```

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- void [GENN\\_EXPORT CodeGenerator::generateMakefile](#) (std::ostream &os, const BackendBase &backend, const std::vector< std::string > &moduleNameNames)

## 20.42 generateMPI.cc File Reference

Contains functions to generate code for running the simulation with MPI. Part of the code generation section.

```
#include "code_generator/generateMPI.h"
#include <fstream>
#include <cstring>
#include "modelSpecInternal.h"
#include "code_generator/backendBase.h"
#include "code_generator/codeStream.h"
```

### 20.42.1 Detailed Description

Contains functions to generate code for running the simulation with MPI. Part of the code generation section.

## 20.43 generateMPI.h File Reference

Contains functions to generate code for running the simulation with MPI. Part of the code generation section.

```
#include <string>
#include "gennExport.h"
```

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- void [GENN\\_EXPORT CodeGenerator::generateMPI](#) (CodeStream &os, const [ModelSpecInternal](#) &model, const BackendBase &backend, bool standaloneModules)

*A function that generates predominantly MPI infrastructure code.*

### 20.43.1 Detailed Description

Contains functions to generate code for running the simulation with MPI. Part of the code generation section.

## 20.44 generateMSBuild.cc File Reference

```
#include "code_generator/generateMSBuild.h"
#include <string>
#include "code_generator/backendBase.h"
```

## 20.45 generateMSBuild.h File Reference

```
#include <string>
#include <vector>
#include "gennExport.h"
```



## Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

## Functions

- void [GENN\\_EXPORT CodeGenerator::generateMSBuild](#) (std::ostream &os, const BackendBase &backend, const std::string &projectGUID, const std::vector< std::string > &moduleNames)

## 20.46 generateNeuronUpdate.cc File Reference

```
#include "code_generator/generateNeuronUpdate.h"
#include <iostream>
#include <string>
#include <plog/Log.h>
#include "models.h"
#include "modelSpecInternal.h"
#include "code_generator/codeGenUtils.h"
#include "code_generator/codeStream.h"
#include "code_generator/substitutions.h"
#include "code_generator/backendBase.h"
```

## 20.47 generateNeuronUpdate.h File Reference

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- void [CodeGenerator::generateNeuronUpdate](#) (CodeStream &os, const [ModelSpecInternal](#) &model, const BackendBase &backend, bool standaloneModules)

## 20.48 generateRun.h File Reference

```
#include <algorithm>
#include <fstream>
#include <iostream>
#include <string>
#include <cstdlib>
#include "../include/genn/third_party/CLI11.hpp"
```

### Classes

- class [GenerateRunBase](#)

## 20.49 generateRunner.cc File Reference

```
#include "code_generator/generateRunner.h"
#include <sstream>
#include <string>
#include "gennUtils.h"
#include "modelSpecInternal.h"
#include "code_generator/codeGenUtils.h"
#include "code_generator/codeStream.h"
#include "code_generator/teeStream.h"
#include "code_generator/backendBase.h"
```

## 20.50 generateRunner.h File Reference

```
#include "code_generator/backendBase.h"
```

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- MemAlloc [CodeGenerator::generateRunner](#) (CodeStream &definitions, CodeStream &definitionsInternal, CodeStream &runner, const [ModelSpecInternal](#) &model, const BackendBase &backend, int localhostID)

## 20.51 generateSupportCode.cc File Reference

```
#include "code_generator/generateSupportCode.h"
#include <string>
#include "modelSpecInternal.h"
#include "code_generator/codeGenUtils.h"
#include "code_generator/codeStream.h"
```

## 20.52 generateSupportCode.h File Reference

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- void [CodeGenerator::generateSupportCode](#) (CodeStream &os, const [ModelSpecInternal](#) &model)

## 20.53 generateSynapseUpdate.cc File Reference

```
#include "code_generator/generateSynapseUpdate.h"
#include <string>
```

```
#include "modelSpecInternal.h"
#include "code_generator/codeStream.h"
#include "code_generator/substitutions.h"
#include "code_generator/backendBase.h"
```

## 20.54 generateSynapseUpdate.h File Reference

### Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

### Functions

- void [CodeGenerator::generateSynapseUpdate](#) (CodeStream &os, const [ModelSpecInternal](#) &model, const BackendBase &backend, bool standaloneModules)

## 20.55 genn\_groups.py File Reference

### Classes

- class [pygenn.genn\\_groups.Group](#)  
*Parent class of [NeuronGroup](#), [SynapseGroup](#) and [CurrentSource](#).*
- class [pygenn.genn\\_groups.NeuronGroup](#)  
*Class representing a group of neurons.*
- class [pygenn.genn\\_groups.SynapseGroup](#)  
*Class representing synaptic connection between two groups of neurons.*
- class [pygenn.genn\\_groups.CurrentSource](#)  
*Class representing a current injection into a group of neurons.*

### Namespaces

- [pygenn.genn\\_groups](#)

### Variables

- [pygenn.genn\\_groups.xrange](#) = range  
*GeNNGroups This module provides classes which automatize model checks and parameter convesions for GeNN Groups.*

## 20.56 genn\_model.py File Reference

### Classes

- class [pygenn.genn\\_model.GeNNModel](#)  
*[GeNNModel](#) class This class helps to define, build and run a GeNN model from python.*

### Namespaces

- [pygenn.genn\\_model](#)

## Functions

- def `pygenn.genn_model.init_var` (init\_var\_snippet, param\_space)  
*This helper function creates a VarInit object to easily initialise a variable using a snippet.*
- def `pygenn.genn_model.init_connectivity` (init\_sparse\_connect\_snippet, param\_space)  
*This helper function creates a InitSparseConnectivitySnippet::Init object to easily initialise connectivity using a snippet.*
- def `pygenn.genn_model.create_custom_neuron_class` (class\_name, param\_names=None, var\_name\_↵  
types=None, derived\_params=None, sim\_code=None, threshold\_condition\_code=None, reset\_code=None,  
support\_code=None, extra\_global\_params=None, additional\_input\_vars=None, is\_auto\_refractory\_↵  
required=None, custom\_body=None)  
*This helper function creates a custom NeuronModel class.*
- def `pygenn.genn_model.create_custom_postsynaptic_class` (class\_name, param\_names=None, var\_↵  
\_name\_types=None, derived\_params=None, decay\_code=None, apply\_input\_code=None, support\_↵  
code=None, custom\_body=None)  
*This helper function creates a custom PostsynapticModel class.*
- def `pygenn.genn_model.create_custom_weight_update_class` (class\_name, param\_names=None, var\_↵  
\_name\_types=None, pre\_var\_name\_types=None, post\_var\_name\_types=None, derived\_params=None,  
sim\_code=None, event\_code=None, learn\_post\_code=None, synapse\_dynamics\_code=None, event\_↵  
threshold\_condition\_code=None, pre\_spike\_code=None, post\_spike\_code=None, sim\_support\_code=None,  
learn\_post\_support\_code=None, synapse\_dynamics\_support\_code=None, extra\_global\_params=None,  
is\_pre\_spike\_time\_required=None, is\_post\_spike\_time\_required=None, custom\_body=None)  
*This helper function creates a custom WeightUpdateModel class.*
- def `pygenn.genn_model.create_custom_current_source_class` (class\_name, param\_names=None, var\_↵  
name\_types=None, derived\_params=None, injection\_code=None, extra\_global\_params=None, custom\_↵  
body=None)  
*This helper function creates a custom NeuronModel class.*
- def `pygenn.genn_model.create_custom_model_class` (class\_name, base, param\_names, var\_name\_types,  
derived\_params, custom\_body)  
*This helper function completes a custom model class creation.*
- def `pygenn.genn_model.create_dpfc_class` (dp\_func)  
*Helper function to create derived parameter function class.*
- def `pygenn.genn_model.create_cmif_class` (cmif\_func)  
*Helper function to create function class for calculating sizes of matrices initialised with sparse connectivity initialisation snippet.*
- def `pygenn.genn_model.create_custom_init_var_snippet_class` (class\_name, param\_names=None,  
derived\_params=None, var\_init\_code=None, custom\_body=None)  
*This helper function creates a custom InitVarSnippet class.*
- def `pygenn.genn_model.create_custom_sparse_connect_init_snippet_class` (class\_name, param\_↵  
names=None, derived\_params=None, row\_build\_code=None, row\_build\_state\_vars=None, calc\_max\_↵  
row\_len\_func=None, calc\_max\_col\_len\_func=None, extra\_global\_params=None, custom\_body=None)  
*This helper function creates a custom InitSparseConnectivitySnippet class.*

## Variables

- `pygenn.genn_model.backend_modules` = OrderedDict()
- `pygenn.genn_model.m` = import\_module(".genn\_wrapper." + b + "Backend", "pygenn")

## 20.57 gennExport.h File Reference

### Macros

- #define `GENN_EXPORT`

## 20.57.1 Macro Definition Documentation

## 20.57.1.1 GENN\_EXPORT

```
#define GENN_EXPORT
```

## 20.58 gennUtils.cc File Reference

```
#include "gennUtils.h"
#include <algorithm>
```

## Namespaces

- [Utils](#)

## Functions

- [GENN\\_EXPORT](#) bool [Utils::isRNGRequired](#) (const std::string &code)  
*Does the code string contain any functions requiring random number generator.*
- [GENN\\_EXPORT](#) bool [Utils::isRNGRequired](#) (const std::vector< [Models::VarInit](#) > &varInitialisers)  
*Does the model with the vectors of variable initialisers and modes require an RNG for the specified init location i.e. host or device.*
- [GENN\\_EXPORT](#) bool [Utils::isTypePointer](#) (const std::string &type)  
*Function to determine whether a string containing a type is a pointer.*
- [GENN\\_EXPORT](#) std::string [Utils::getUnderlyingType](#) (const std::string &type)  
*Assuming type is a string containing a pointer type, function to return the underlying type.*

## 20.59 gennUtils.h File Reference

```
#include <string>
#include <vector>
#include "gennExport.h"
#include "models.h"
```

## Namespaces

- [Utils](#)

## Functions

- [GENN\\_EXPORT](#) bool [Utils::isRNGRequired](#) (const std::string &code)  
*Does the code string contain any functions requiring random number generator.*
- [GENN\\_EXPORT](#) bool [Utils::isRNGRequired](#) (const std::vector< [Models::VarInit](#) > &varInitialisers)  
*Does the model with the vectors of variable initialisers and modes require an RNG for the specified init location i.e. host or device.*
- [GENN\\_EXPORT](#) bool [Utils::isTypePointer](#) (const std::string &type)  
*Function to determine whether a string containing a type is a pointer.*
- [GENN\\_EXPORT](#) std::string [Utils::getUnderlyingType](#) (const std::string &type)  
*Assuming type is a string containing a pointer type, function to return the underlying type.*

## 20.60 `initSparseConnectivitySnippet.cc` File Reference

```
#include "initSparseConnectivitySnippet.h"
```

### Functions

- [IMPLEMENT\\_SNIPPET \(InitSparseConnectivitySnippet::Uninitialised\)](#)
- [IMPLEMENT\\_SNIPPET \(InitSparseConnectivitySnippet::OneToOne\)](#)
- [IMPLEMENT\\_SNIPPET \(InitSparseConnectivitySnippet::FixedProbability\)](#)
- [IMPLEMENT\\_SNIPPET \(InitSparseConnectivitySnippet::FixedProbabilityNoAutapse\)](#)

### 20.60.1 Function Documentation

#### 20.60.1.1 `IMPLEMENT_SNIPPET()` [1/4]

```
IMPLEMENT_SNIPPET (
    InitSparseConnectivitySnippet::Uninitialised )
```

#### 20.60.1.2 `IMPLEMENT_SNIPPET()` [2/4]

```
IMPLEMENT_SNIPPET (
    InitSparseConnectivitySnippet::OneToOne )
```

#### 20.60.1.3 `IMPLEMENT_SNIPPET()` [3/4]

```
IMPLEMENT_SNIPPET (
    InitSparseConnectivitySnippet::FixedProbability )
```

#### 20.60.1.4 `IMPLEMENT_SNIPPET()` [4/4]

```
IMPLEMENT_SNIPPET (
    InitSparseConnectivitySnippet::FixedProbabilityNoAutapse )
```

## 20.61 `initSparseConnectivitySnippet.h` File Reference

```
#include <functional>
#include <vector>
#include <cassert>
#include <cmath>
#include "binomial.h"
#include "snippet.h"
```

### Classes

- class [InitSparseConnectivitySnippet::Base](#)
- class [InitSparseConnectivitySnippet::Init](#)
- class [InitSparseConnectivitySnippet::Uninitialised](#)

*Used to mark connectivity as uninitialised - no initialisation code will be run.*

- class [InitSparseConnectivitySnippet::OneToOne](#)  
*Initialises connectivity to a 'one-to-one' diagonal matrix.*
- class [InitSparseConnectivitySnippet::FixedProbabilityBase](#)
- class [InitSparseConnectivitySnippet::FixedProbability](#)
- class [InitSparseConnectivitySnippet::FixedProbabilityNoAutapse](#)

## Namespaces

- [InitSparseConnectivitySnippet](#)  
*Base class for all sparse connectivity initialisation snippets.*

## Macros

- `#define SET_ROW_BUILD_CODE(CODE) virtual std::string getRowBuildCode() const override{ return CODE; }`
- `#define SET_ROW_BUILD_STATE_VARS(...) virtual ParamValVec getRowBuildStateVars() const override{ return __VA_ARGS__; }`
- `#define SET_CALC_MAX_ROW_LENGTH_FUNC(FUNC) virtual CalcMaxLengthFunc getCalcMaxRowLengthFunc() const override{ return FUNC; }`
- `#define SET_CALC_MAX_COL_LENGTH_FUNC(FUNC) virtual CalcMaxLengthFunc getCalcMaxColLengthFunc() const override{ return FUNC; }`
- `#define SET_MAX_ROW_LENGTH(MAX_ROW_LENGTH) virtual CalcMaxLengthFunc getCalcMaxRowLengthFunc() const override{ return [](unsigned int, unsigned int, const std::vector<double> &){ return MAX_ROW_LENGTH; };`
- `#define SET_MAX_COL_LENGTH(MAX_COL_LENGTH) virtual CalcMaxLengthFunc getCalcMaxColLengthFunc() const override{ return [](unsigned int, unsigned int, const std::vector<double> &){ return MAX_COL_LENGTH; };`
- `#define SET_EXTRA_GLOBAL_PARAMS(...) virtual EGPVec getExtraGlobalParams() const override{ return __VA_ARGS__; }`

## 20.61.1 Macro Definition Documentation

### 20.61.1.1 SET\_CALC\_MAX\_COL\_LENGTH\_FUNC

```
#define SET_CALC_MAX_COL_LENGTH_FUNC(  
    FUNC ) virtual CalcMaxLengthFunc getCalcMaxColLengthFunc() const override{ return  
FUNC; }
```

### 20.61.1.2 SET\_CALC\_MAX\_ROW\_LENGTH\_FUNC

```
#define SET_CALC_MAX_ROW_LENGTH_FUNC(  
    FUNC ) virtual CalcMaxLengthFunc getCalcMaxRowLengthFunc() const override{ return  
FUNC; }
```

### 20.61.1.3 SET\_EXTRA\_GLOBAL\_PARAMS

```
#define SET_EXTRA_GLOBAL_PARAMS(  
    ... ) virtual EGPVec getExtraGlobalParams() const override{ return __VA_ARGS__;  
}
```

#### 20.61.1.4 SET\_MAX\_COL\_LENGTH

```
#define SET_MAX_COL_LENGTH(  
    MAX_COL_LENGTH ) virtual CalcMaxLengthFunc getCalcMaxColLengthFunc() const override{  
    return [](unsigned int, unsigned int, const std::vector<double> &){ return MAX_COL_LENGTH; };  
}
```

#### 20.61.1.5 SET\_MAX\_ROW\_LENGTH

```
#define SET_MAX_ROW_LENGTH(  
    MAX_ROW_LENGTH ) virtual CalcMaxLengthFunc getCalcMaxRowLengthFunc() const override{  
    return [](unsigned int, unsigned int, const std::vector<double> &){ return MAX_ROW_LENGTH; };  
}
```

#### 20.61.1.6 SET\_ROW\_BUILD\_CODE

```
#define SET_ROW_BUILD_CODE(  
    CODE ) virtual std::string getRowBuildCode() const override{ return CODE; }
```

#### 20.61.1.7 SET\_ROW\_BUILD\_STATE\_VARS

```
#define SET_ROW_BUILD_STATE_VARS(  
    ... ) virtual ParamValVec getRowBuildStateVars() const override{ return __VA_ARGS__  
RGS__; }
```

### 20.62 initVarSnippet.cc File Reference

```
#include "initVarSnippet.h"
```

#### Functions

- [IMPLEMENT\\_SNIPPET \(InitVarSnippet::Uninitialised\)](#)
- [IMPLEMENT\\_SNIPPET \(InitVarSnippet::Constant\)](#)
- [IMPLEMENT\\_SNIPPET \(InitVarSnippet::Uniform\)](#)
- [IMPLEMENT\\_SNIPPET \(InitVarSnippet::Normal\)](#)
- [IMPLEMENT\\_SNIPPET \(InitVarSnippet::Exponential\)](#)
- [IMPLEMENT\\_SNIPPET \(InitVarSnippet::Gamma\)](#)

#### 20.62.1 Function Documentation

##### 20.62.1.1 IMPLEMENT\_SNIPPET() [1/6]

```
IMPLEMENT_SNIPPET (  
    InitVarSnippet::Uninitialised )
```

##### 20.62.1.2 IMPLEMENT\_SNIPPET() [2/6]

```
IMPLEMENT_SNIPPET (  
    InitVarSnippet::Constant )
```



20.62.1.3 `IMPLEMENT_SNIPPET()` [3/6]

```
IMPLEMENT_SNIPPET (
    InitVarSnippet::Uniform )
```

20.62.1.4 `IMPLEMENT_SNIPPET()` [4/6]

```
IMPLEMENT_SNIPPET (
    InitVarSnippet::Normal )
```

20.62.1.5 `IMPLEMENT_SNIPPET()` [5/6]

```
IMPLEMENT_SNIPPET (
    InitVarSnippet::Exponential )
```

20.62.1.6 `IMPLEMENT_SNIPPET()` [6/6]

```
IMPLEMENT_SNIPPET (
    InitVarSnippet::Gamma )
```

20.63 `initVarSnippet.h` File Reference

```
#include "snippet.h"
```

## Classes

- class `InitVarSnippet::Base`
- class `InitVarSnippet::Uninitialised`  
Used to mark variables as uninitialised - no initialisation code will be run.
- class `InitVarSnippet::Constant`  
Initialises variable to a constant value.
- class `InitVarSnippet::Uniform`  
Initialises variable by sampling from the uniform distribution.
- class `InitVarSnippet::Normal`  
Initialises variable by sampling from the normal distribution.
- class `InitVarSnippet::Exponential`  
Initialises variable by sampling from the exponential distribution.
- class `InitVarSnippet::Gamma`  
Initialises variable by sampling from the exponential distribution.

## Namespaces

- `InitVarSnippet`  
Base class for all value initialisation snippets.

## Macros

- `#define SET_CODE(CODE) virtual std::string getCode() const override{ return CODE; }`

## 20.63.1 Macro Definition Documentation

### 20.63.1.1 SET\_CODE

```
#define SET_CODE(  
    CODE ) virtual std::string getCode() const override{ return CODE; }
```

## 20.64 input.cc File Reference

```
#include "input.h"  
#include <limits>  
#include <iostream>  
#include <cmath>  
#include "pugixml/pugixml.hpp"  
#include "spineMLLogging.h"  
#include "inputValue.h"  
#include "modelProperty.h"
```

## 20.65 input.h File Reference

```
#include <functional>  
#include <map>  
#include <memory>  
#include <random>
```

### Classes

- class [SpineMLSimulator::Input::Base](#)
- class [SpineMLSimulator::Input::SpikeBase](#)
- class [SpineMLSimulator::Input::InterSpikeIntervalBase](#)
- class [SpineMLSimulator::Input::RegularSpikeRate](#)
- class [SpineMLSimulator::Input::PoissonSpikeRate](#)
- class [SpineMLSimulator::Input::SpikeTime](#)
- class [SpineMLSimulator::Input::Analogue](#)

### Namespaces

- [pugi](#)
- [SpineMLSimulator](#)
- [SpineMLSimulator::InputValue](#)
- [SpineMLSimulator::ModelProperty](#)
- [SpineMLSimulator::Input](#)

## 20.66 inputValue.cc File Reference

```
#include "inputValue.h"  
#include <iostream>  
#include <sstream>  
#include <cassert>  
#include <cmath>
```

```
#include <cstring>
#include "pugixml/pugixml.hpp"
#include "spineMLLogging.h"
#include "spineMLUtils.h"
```

## 20.67 inputValue.h File Reference

```
#include <functional>
#include <map>
#include <memory>
#include <string>
#include <vector>
#include "networkClient.h"
```

### Classes

- class [SpineMLSimulator::InputValue::Base](#)
- class [SpineMLSimulator::InputValue::ScalarBase](#)
- class [SpineMLSimulator::InputValue::Constant](#)
- class [SpineMLSimulator::InputValue::ConstantArray](#)
- class [SpineMLSimulator::InputValue::TimeVarying](#)
- class [SpineMLSimulator::InputValue::TimeVaryingArray](#)
- class [SpineMLSimulator::InputValue::External](#)
- class [SpineMLSimulator::InputValue::ExternalNetwork](#)

### Namespaces

- [pugi](#)
- [SpineMLSimulator](#)
- [SpineMLSimulator::InputValue](#)

### Functions

- `std::unique_ptr< Base > SpineMLSimulator::InputValue::create (double dt, unsigned int numNeurons, const pugi::xml_node &node, std::map< std::string, InputValue::External *> &externalInputs)`

## 20.68 logging.cc File Reference

```
#include "logging.h"
```

## 20.69 logging.h File Reference

```
#include <plog/Log.h>
#include <plog/Severity.h>
#include "gennExport.h"
```

## Namespaces

- [plog](#)
- [Logging](#)

## Macros

- `#define LOGV_GENN LOGV_(Logging::CHANNEL_GENN)`
- `#define LOGD_GENN LOGD_(Logging::CHANNEL_GENN)`
- `#define LOGI_GENN LOGI_(Logging::CHANNEL_GENN)`
- `#define LOGW_GENN LOGW_(Logging::CHANNEL_GENN)`
- `#define LOGE_GENN LOGE_(Logging::CHANNEL_GENN)`
- `#define LOGF_GENN LOGF_(Logging::CHANNEL_GENN)`
- `#define LOGV_CODE_GEN LOGV_(Logging::CHANNEL_CODE_GEN)`
- `#define LOGD_CODE_GEN LOGD_(Logging::CHANNEL_CODE_GEN)`
- `#define LOGI_CODE_GEN LOGI_(Logging::CHANNEL_CODE_GEN)`
- `#define LOGW_CODE_GEN LOGW_(Logging::CHANNEL_CODE_GEN)`
- `#define LOGE_CODE_GEN LOGE_(Logging::CHANNEL_CODE_GEN)`
- `#define LOGF_CODE_GEN LOGF_(Logging::CHANNEL_CODE_GEN)`
- `#define LOGV_BACKEND LOGV_(Logging::CHANNEL_BACKEND)`
- `#define LOGD_BACKEND LOGD_(Logging::CHANNEL_BACKEND)`
- `#define LOGI_BACKEND LOGI_(Logging::CHANNEL_BACKEND)`
- `#define LOGW_BACKEND LOGW_(Logging::CHANNEL_BACKEND)`
- `#define LOGE_BACKEND LOGE_(Logging::CHANNEL_BACKEND)`
- `#define LOGF_BACKEND LOGF_(Logging::CHANNEL_BACKEND)`

## Enumerations

- `enum Logging::Channel { Logging::CHANNEL_GENN = 0, Logging::CHANNEL_CODE_GEN = 1, Logging::CHANNEL_BACKEND = 2, Logging::CHANNEL_MAX }`

## Functions

- `GENN_EXPORT void Logging::init (plog::Severity gennLevel, plog::Severity codeGeneratorLevel, plog::IAppender *gennAppender, plog::IAppender *codeGeneratorAppender)`

### 20.69.1 Macro Definition Documentation

#### 20.69.1.1 LOGD\_BACKEND

```
#define LOGD_BACKEND LOGD_(Logging::CHANNEL_BACKEND)
```

#### 20.69.1.2 LOGD\_CODE\_GEN

```
#define LOGD_CODE_GEN LOGD_(Logging::CHANNEL_CODE_GEN)
```

#### 20.69.1.3 LOGD\_GENN

```
#define LOGD_GENN LOGD_(Logging::CHANNEL_GENN)
```

#### 20.69.1.4 LOGE\_BACKEND

```
#define LOGE_BACKEND LOGE_(Logging::CHANNEL_BACKEND)
```

#### 20.69.1.5 LOGE\_CODE\_GEN

```
#define LOGE_CODE_GEN LOGE_(Logging::CHANNEL_CODE_GEN)
```

#### 20.69.1.6 LOGE\_GENN

```
#define LOGE_GENN LOGE_(Logging::CHANNEL_GENN)
```

#### 20.69.1.7 LOGF\_BACKEND

```
#define LOGF_BACKEND LOGF_(Logging::CHANNEL_BACKEND)
```

#### 20.69.1.8 LOGF\_CODE\_GEN

```
#define LOGF_CODE_GEN LOGF_(Logging::CHANNEL_CODE_GEN)
```

#### 20.69.1.9 LOGF\_GENN

```
#define LOGF_GENN LOGF_(Logging::CHANNEL_GENN)
```

#### 20.69.1.10 LOGI\_BACKEND

```
#define LOGI_BACKEND LOGI_(Logging::CHANNEL_BACKEND)
```

#### 20.69.1.11 LOGI\_CODE\_GEN

```
#define LOGI_CODE_GEN LOGI_(Logging::CHANNEL_CODE_GEN)
```

#### 20.69.1.12 LOGI\_GENN

```
#define LOGI_GENN LOGI_(Logging::CHANNEL_GENN)
```

#### 20.69.1.13 LOGV\_BACKEND

```
#define LOGV_BACKEND LOGV_(Logging::CHANNEL_BACKEND)
```

#### 20.69.1.14 LOGV\_CODE\_GEN

```
#define LOGV_CODE_GEN LOGV_(Logging::CHANNEL_CODE_GEN)
```

#### 20.69.1.15 LOGV\_GENN

```
#define LOGV_GENN LOGV_(Logging::CHANNEL_GENN)
```

#### 20.69.1.16 LOGW\_BACKEND

```
#define LOGW_BACKEND LOGW_(Logging::CHANNEL_BACKEND)
```

#### 20.69.1.17 LOGW\_CODE\_GEN

```
#define LOGW_CODE_GEN LOGW_(Logging::CHANNEL_CODE_GEN)
```

#### 20.69.1.18 LOGW\_GENN

```
#define LOGW_GENN LOGW_(Logging::CHANNEL_GENN)
```

### 20.70 logOutput.cc File Reference

```
#include "logOutput.h"  
#include <algorithm>  
#include <limits>  
#include <iostream>  
#include <cassert>  
#include <cmath>  
#include "path.h"  
#include "pugixml/pugixml.hpp"  
#include "spineMLLogging.h"  
#include "spineMLUtils.h"
```

### 20.71 logOutput.h File Reference

```
#include <fstream>  
#include <set>  
#include <string>  
#include <vector>  
#include "modelProperty.h"  
#include "networkClient.h"
```

#### Classes

- class [SpineMLSimulator::LogOutput::Base](#)
- class [SpineMLSimulator::LogOutput::AnalogueBase](#)
- class [SpineMLSimulator::LogOutput::AnalogueFile](#)
- class [SpineMLSimulator::LogOutput::AnalogueExternal](#)
- class [SpineMLSimulator::LogOutput::AnalogueNetwork](#)
- class [SpineMLSimulator::LogOutput::Event](#)

#### Namespaces

- [pugi](#)

- [filesystem](#)
- [SpineMLSimulator](#)
- [SpineMLSimulator::LogOutput](#)

## 20.72 logWriter.h File Reference

## 20.73 model\_preprocessor.py File Reference

### Classes

- class [pygenn.model\\_preprocessor.Variable](#)  
*Class holding information about GeNN variables.*
- class [pygenn.model\\_preprocessor.ExtraGlobalVariable](#)  
*Class holding information about GeNN extra global pointer variable.*

### Namespaces

- [pygenn.model\\_preprocessor](#)

### Functions

- def [pygenn.model\\_preprocessor.prepare\\_model](#) (model, param\_space, var\_space, pre\_var\_space=None, post\_var\_space=None, model\_family=None)  
*Prepare a model by checking its validity and extracting information about variables and parameters.*
- def [pygenn.model\\_preprocessor.prepare\\_snippet](#) (snippet, param\_space, snippet\_family)  
*Prepare a snippet by checking its validity and extracting information about parameters.*
- def [pygenn.model\\_preprocessor.is\\_model\\_valid](#) (model, model\_family)  
*Check whether the model is valid, i.e is native or derived from model\_family.Custom.*
- def [pygenn.model\\_preprocessor.param\\_space\\_to\\_vals](#) (model, param\_space)  
*Convert a param\_space dict to ParamValues.*
- def [pygenn.model\\_preprocessor.param\\_space\\_to\\_val\\_vec](#) (model, param\_space)  
*Convert a param\_space dict to a std::vector<double>*
- def [pygenn.model\\_preprocessor.var\\_space\\_to\\_vals](#) (model, var\_space)  
*Convert a var\_space dict to VarValues.*
- def [pygenn.model\\_preprocessor.pre\\_var\\_space\\_to\\_vals](#) (model, var\_space)  
*Convert a var\_space dict to PreVarValues.*
- def [pygenn.model\\_preprocessor.post\\_var\\_space\\_to\\_vals](#) (model, var\_space)  
*Convert a var\_space dict to PostVarValues.*

### Variables

- [pygenn.model\\_preprocessor.GeNNType](#) = namedtuple("GeNNType", ["np\_dtype", "assign\_ext\_ptr\_array", "assign\_ext\_ptr\_single"])
- dictionary [pygenn.model\\_preprocessor.genn\\_types](#)

## 20.74 modelProperty.cc File Reference

```
#include "modelProperty.h"
#include <algorithm>
#include <fstream>
#include <iostream>
#include <cassert>
#include <cstring>
#include "path.h"
#include "pugixml/pugixml.hpp"
#include "spineMLLogging.h"
```

## 20.75 modelProperty.h File Reference

```
#include <memory>
#include <random>
#include <vector>
#include "stateVar.h"
```

### Classes

- class [SpineMLSimulator::ModelProperty::Base](#)
- class [SpineMLSimulator::ModelProperty::Fixed](#)
- class [SpineMLSimulator::ModelProperty::ValueList](#)
- class [SpineMLSimulator::ModelProperty::UniformDistribution](#)
- class [SpineMLSimulator::ModelProperty::NormalDistribution](#)
- class [SpineMLSimulator::ModelProperty::ExponentialDistribution](#)

### Namespaces

- [pugi](#)
- [filesystem](#)
- [SpineMLSimulator](#)
- [SpineMLSimulator::ModelProperty](#)

### Typedefs

- typedef float [SpineMLSimulator::scalar](#)

### Functions

- `std::unique_ptr< Base > SpineMLSimulator::ModelProperty::create (const pugi::xml_node &node, const StateVar< scalar > &stateVar, unsigned int size, bool skipGeNNInitialised, const filesystem::path &basePath, const std::string &valueNamespace, const std::vector< unsigned int > *remapIndices)`

## 20.76 models.h File Reference

```
#include <string>
#include <vector>
#include "snippet.h"
#include "initVarSnippet.h"
```



## Classes

- class [Models::VarInit](#)
- class [Models::VarInitContainerBase< NumVars >](#)
- class [Models::VarInitContainerBase< 0 >](#)
- class [Models::Base](#)  
*Base class for all models - in addition to the parameters snippets have, models can have state variables.*
- struct [Models::Base::Var](#)  
*A variable has a name, a type and an access type.*

## Namespaces

- [Models](#)

## Macros

- `#define DECLARE_MODEL(TYPE, NUM_PARAMS, NUM_VARS)`
- `#define IMPLEMENT_MODEL(TYPE) IMPLEMENT_SNIPPET(TYPE)`
- `#define SET_VARS(...) virtual VarVec getVars() const override{ return __VA_ARGS__; }`
- `#define SET_EXTRA_GLOBAL_PARAMS(...) virtual EGPVec getExtraGlobalParams() const override{ return __VA_ARGS__; }`

## Enumerations

- enum [VarAccess](#) { [VarAccess::READ\\_WRITE](#) = 0, [VarAccess::READ\\_ONLY](#) }
- How is this variable accessed by model?*

## 20.76.1 Macro Definition Documentation

## 20.76.1.1 DECLARE\_MODEL

```
#define DECLARE_MODEL(
    TYPE,
    NUM_PARAMS,
    NUM_VARS )
```

## Value:

```
DECLARE_SNIPPET(TYPE, NUM_PARAMS);
    typedef Models::VarInitContainerBase<NUM_VARS> VarValues;
    \
    typedef Models::VarInitContainerBase<0> PreVarValues;
    \
    typedef Models::VarInitContainerBase<0> PostVarValues
```

## 20.76.1.2 IMPLEMENT\_MODEL

```
#define IMPLEMENT_MODEL(
    TYPE ) IMPLEMENT_SNIPPET(TYPE)
```

### 20.76.1.3 SET\_EXTRA\_GLOBAL\_PARAMS

```
#define SET_EXTRA_GLOBAL_PARAMS(  
    ... ) virtual EGPVec getExtraGlobalParams() const override{ return __VA_ARGS__;  
}
```

### 20.76.1.4 SET\_VARS

```
#define SET_VARS(  
    ... ) virtual VarVec getVars() const override{ return __VA_ARGS__; }
```

## 20.76.2 Enumeration Type Documentation

### 20.76.2.1 VarAccess

```
enum VarAccess [strong]
```

How is this variable accessed by model?

#### Enumerator

READ_WRITE	
READ_ONLY	This variable is both read and written by the model.

## 20.77 modelSpec.cc File Reference

```
#include <algorithm>  
#include <numeric>  
#include <typeinfo>  
#include <cstdio>  
#include <cmath>  
#include <cassert>  
#include "modelSpec.h"  
#include "code_generator/codeGenUtils.h"  
#include "code_generator/substitutions.h"
```

## 20.78 modelSpec.h File Reference

Header file that contains the class (struct) definition of `neuronModel` for defining a neuron model and the class definition of [ModelSpec](#) for defining a neuronal network model. Part of the code generation and generated code sections.

```
#include <map>  
#include <set>  
#include <string>  
#include <vector>  
#include "gennExport.h"  
#include "neuronGroupInternal.h"  
#include "synapseGroupInternal.h"  
#include "currentSourceInternal.h"
```

## Classes

- class [ModelSpec](#)  
*Object used for specifying a neuronal network model.*

## Macros

- `#define NO_DELAY 0`  
*Macro used to indicate no synapse delay for the group (only one queue slot will be generated)*

## Typedefs

- typedef [ModelSpec](#) NNmodel

## Enumerations

- enum [FloatType](#) { , [GENN\\_LONG\\_DOUBLE](#) }  
*Floating point precision to use for models.*
- enum [TimePrecision](#) { [TimePrecision::DEFAULT](#), [TimePrecision::FLOAT](#), [TimePrecision::DOUBLE](#) }  
*Precision to use for variables which store time.*

## Functions

- template<typename S >  
[Models::VarInit](#) [initVar](#) (const typename S::ParamValues &params)  
*Initialise a variable using an initialisation snippet.*
- template<typename S >  
std::enable\_if< std::is\_same< typename S::ParamValues, [Snippet::ValueBase](#)< 0 > >::value, [Models::VarInit](#) >::type [initVar](#) ()  
*Initialise a variable using an initialisation snippet with no parameters.*
- [Models::VarInit](#) [uninitialisedVar](#) ()  
*Mark a variable as uninitialised.*
- template<typename S >  
[InitSparseConnectivitySnippet::Init](#) [initConnectivity](#) (const typename S::ParamValues &params)  
*Initialise connectivity using a sparse connectivity snippet.*
- template<typename S >  
std::enable\_if< std::is\_same< typename S::ParamValues, [Snippet::ValueBase](#)< 0 > >::value, [InitSparseConnectivitySnippet::Init](#) >::type [initConnectivity](#) ()  
*Initialise connectivity using a sparse connectivity snippet with no parameters.*
- [InitSparseConnectivitySnippet::Init](#) [uninitialisedConnectivity](#) ()  
*Mark a synapse group's sparse connectivity as uninitialised.*

## 20.78.1 Detailed Description

Header file that contains the class (struct) definition of [neuronModel](#) for defining a neuron model and the class definition of [ModelSpec](#) for defining a neuronal network model. Part of the code generation and generated code sections.

## 20.78.2 Macro Definition Documentation

### 20.78.2.1 NO\_DELAY

```
#define NO_DELAY 0
```

Macro used to indicate no synapse delay for the group (only one queue slot will be generated)

## 20.78.3 Typedef Documentation

### 20.78.3.1 NNmodel

```
typedef ModelSpec NNmodel
```

## 20.78.4 Enumeration Type Documentation

### 20.78.4.1 FloatType

```
enum FloatType
```

Floating point precision to use for models.

Enumerator

GENN_LONG_DOUBLE	
------------------	--

### 20.78.4.2 TimePrecision

```
enum TimePrecision [strong]
```

Precision to use for variables which store time.

Enumerator

DEFAULT	Time uses default model precision.
FLOAT	Time uses single precision - not suitable for long simulations.
DOUBLE	Time uses double precision - may reduce performance.

## 20.78.5 Function Documentation

### 20.78.5.1 initConnectivity() [1/2]

```
template<typename S >
InitSparseConnectivitySnippet::Init initConnectivity (
    const typename S::ParamValues & params ) [inline]
```

Initialise connectivity using a sparse connectivity snippet.

Template Parameters

S	type of sparse connectivity initialisation snippet (derived from <a href="#">InitSparseConnectivitySnippet::Base</a> ).
---	---

## Parameters

<i>params</i>	parameters for snippet wrapped in S::ParamValues object.
---------------	--

## Returns

[InitSparseConnectivitySnippet::Init](#) object for passing to [ModelSpec::addSynapsePopulation](#)

## 20.78.5.2 initConnectivity() [2/2]

```
template<typename S >
std::enable_if<std::is_same<typename S::ParamValues, Snippet::ValueBase<0> >::value, InitSparseConnectivitySnippet::Init>::type initConnectivity ( ) [inline]
```

Initialise connectivity using a sparse connectivity snippet with no parameters.

## Template Parameters

S	type of sparse connectivity initialisation snippet (derived from <a href="#">InitSparseConnectivitySnippet::Base</a> ).
---	---

## Returns

[InitSparseConnectivitySnippet::Init](#) object for passing to [ModelSpec::addSynapsePopulation](#)

## 20.78.5.3 initVar() [1/2]

```
template<typename S >
Models::VarInit initVar (
    const typename S::ParamValues & params ) [inline]
```

Initialise a variable using an initialisation snippet.

## Template Parameters

S	type of variable initialisation snippet (derived from <a href="#">InitVarSnippet::Base</a> ).
---	---

## Parameters

<i>params</i>	parameters for snippet wrapped in S::ParamValues object.
---------------	--

## Returns

[Models::VarInit](#) object for use within model's VarValues

## 20.78.5.4 initVar() [2/2]

```
template<typename S >
std::enable_if<std::is_same<typename S::ParamValues, Snippet::ValueBase<0> >::value, Models::VarInit>::type initVar ( ) [inline]
```

Initialise a variable using an initialisation snippet with no parameters.

## Template Parameters

S	type of variable initialisation snippet (derived from <a href="#">InitVarSnippet::Base</a> ).
---	---

## Returns

[Models::VarInit](#) object for use within model's VarValues

### 20.78.5.5 uninitialisedConnectivity()

```
InitSparseConnectivitySnippet::Init uninitialisedConnectivity ( ) [inline]
```

Mark a synapse group's sparse connectivity as uninitialised.

This means that the backend will not generate any automatic initialization code, but will instead copy the connectivity from host to device during `initializeSparse` function (and, if necessary generate any additional data structures it requires)

### 20.78.5.6 uninitialisedVar()

```
Models::VarInit uninitialisedVar ( ) [inline]
```

Mark a variable as uninitialised.

This means that the backend will not generate any automatic initialization code, but will instead copy the variable from host to device during `initializeSparse` function

## 20.79 modelSpecInternal.h File Reference

```
#include "modelSpec.h"
```

## Classes

- class [ModelSpecInternal](#)

## 20.80 networkClient.cc File Reference

```
#include "networkClient.h"
#include <stdexcept>
#include <cstring>
#include "spineMLLogging.h"
```

## 20.81 networkClient.h File Reference

```
#include <iostream>
#include <string>
#include <vector>
#include <arpa/inet.h>
#include <netinet/in.h>
#include <netinet/tcp.h>
#include <sys/socket.h>
#include <sys/types.h>
```

```
#include <unistd.h>
#include "spineMLLogging.h"
```

#### Classes

- class [SpineMLSimulator::NetworkClient](#)

#### Namespaces

- [SpineMLSimulator](#)

## 20.82 neuronGroup.cc File Reference

```
#include "neuronGroup.h"
#include <algorithm>
#include <cmath>
#include "currentSourceInternal.h"
#include "logging.h"
#include "neuronGroupInternal.h"
#include "synapseGroupInternal.h"
#include "gennUtils.h"
```

## 20.83 neuronGroup.h File Reference

```
#include <map>
#include <set>
#include <string>
#include <vector>
#include "gennExport.h"
#include "neuronModels.h"
#include "variableMode.h"
```

#### Classes

- class [NeuronGroup](#)

## 20.84 neuronGroupInternal.h File Reference

```
#include "neuronGroup.h"
```

#### Classes

- class [NeuronGroupInternal](#)

## 20.85 neuronModels.cc File Reference

```
#include "neuronModels.h"
```

## Functions

- [IMPLEMENT\\_MODEL \(NeuronModels::RulkovMap\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::Izhikevich\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::IzhikevichVariable\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::LIF\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::SpikeSource\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::SpikeSourceArray\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::Poisson\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::PoissonNew\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::TraubMiles\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::TraubMilesFast\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::TraubMilesAlt\)](#)
- [IMPLEMENT\\_MODEL \(NeuronModels::TraubMilesNStep\)](#)

### 20.85.1 Function Documentation

#### 20.85.1.1 [IMPLEMENT\\_MODEL\(\)](#) [1/12]

```
IMPLEMENT_MODEL (
    NeuronModels::RulkovMap )
```

#### 20.85.1.2 [IMPLEMENT\\_MODEL\(\)](#) [2/12]

```
IMPLEMENT_MODEL (
    NeuronModels::Izhikevich )
```

#### 20.85.1.3 [IMPLEMENT\\_MODEL\(\)](#) [3/12]

```
IMPLEMENT_MODEL (
    NeuronModels::IzhikevichVariable )
```

#### 20.85.1.4 [IMPLEMENT\\_MODEL\(\)](#) [4/12]

```
IMPLEMENT_MODEL (
    NeuronModels::LIF )
```

#### 20.85.1.5 [IMPLEMENT\\_MODEL\(\)](#) [5/12]

```
IMPLEMENT_MODEL (
    NeuronModels::SpikeSource )
```

#### 20.85.1.6 [IMPLEMENT\\_MODEL\(\)](#) [6/12]

```
IMPLEMENT_MODEL (
    NeuronModels::SpikeSourceArray )
```



**20.85.1.7 IMPLEMENT\_MODEL()** [7/12]

```
IMPLEMENT_MODEL (
    NeuronModels::Poisson )
```

**20.85.1.8 IMPLEMENT\_MODEL()** [8/12]

```
IMPLEMENT_MODEL (
    NeuronModels::PoissonNew )
```

**20.85.1.9 IMPLEMENT\_MODEL()** [9/12]

```
IMPLEMENT_MODEL (
    NeuronModels::TraubMiles )
```

**20.85.1.10 IMPLEMENT\_MODEL()** [10/12]

```
IMPLEMENT_MODEL (
    NeuronModels::TraubMilesFast )
```

**20.85.1.11 IMPLEMENT\_MODEL()** [11/12]

```
IMPLEMENT_MODEL (
    NeuronModels::TraubMilesAlt )
```

**20.85.1.12 IMPLEMENT\_MODEL()** [12/12]

```
IMPLEMENT_MODEL (
    NeuronModels::TraubMilesNStep )
```

**20.86 neuronModels.h File Reference**

```
#include <array>
#include <functional>
#include <string>
#include <tuple>
#include <vector>
#include <cmath>
#include "models.h"
```

**Classes**

- class [NeuronModels::Base](#)  
*Base class for all neuron models.*
- class [NeuronModels::RulkovMap](#)  
*Rulkov Map neuron.*
- class [NeuronModels::Izhikevich](#)  
*Izhikevich neuron with fixed parameters [1].*
- class [NeuronModels::IzhikevichVariable](#)

- Izhikevich* neuron with variable parameters [1].
- class `NeuronModels::LIF`
- class `NeuronModels::SpikeSource`  
Empty neuron which allows setting spikes from external sources.
- class `NeuronModels::SpikeSourceArray`  
Spike source array.
- class `NeuronModels::Poisson`  
*Poisson* neurons.
- class `NeuronModels::PoissonNew`  
*Poisson* neurons.
- class `NeuronModels::TraubMiles`  
Hodgkin-Huxley neurons with Traub & Miles algorithm.
- class `NeuronModels::TraubMilesFast`  
Hodgkin-Huxley neurons with Traub & Miles algorithm: Original fast implementation, using 25 inner iterations.
- class `NeuronModels::TraubMilesAlt`  
Hodgkin-Huxley neurons with Traub & Miles algorithm.
- class `NeuronModels::TraubMilesNStep`  
Hodgkin-Huxley neurons with Traub & Miles algorithm.

## Namespaces

- `NeuronModels`

## Macros

- `#define SET_SIM_CODE(SIM_CODE) virtual std::string getSimCode() const override{ return SIM_CODE; }`
- `#define SET_THRESHOLD_CONDITION_CODE(THRESHOLD_CONDITION_CODE) virtual std::string getThresholdConditionCode() const override{ return THRESHOLD_CONDITION_CODE; }`
- `#define SET_RESET_CODE(RESET_CODE) virtual std::string getResetCode() const override{ return RESET_CODE; }`
- `#define SET_SUPPORT_CODE(SUPPORT_CODE) virtual std::string getSupportCode() const override{ return SUPPORT_CODE; }`
- `#define SET_ADDITIONAL_INPUT_VARS(...) virtual ParamValVec getAdditionalInputVars() const override{ return __VA_ARGS__; }`
- `#define SET_NEEDS_AUTO_REFRACTORY(AUTO_REFRACTORY_REQUIRED) virtual bool isAutoRefractoryRequired() const override{ return AUTO_REFRACTORY_REQUIRED; }`

## 20.86.1 Macro Definition Documentation

### 20.86.1.1 SET\_ADDITIONAL\_INPUT\_VARS

```
#define SET_ADDITIONAL_INPUT_VARS(
    ... ) virtual ParamValVec getAdditionalInputVars() const override{ return __VA_ARGS__; }
```

### 20.86.1.2 SET\_NEEDS\_AUTO\_REFRACTORY

```
#define SET_NEEDS_AUTO_REFRACTORY(
    AUTO_REFRACTORY_REQUIRED ) virtual bool isAutoRefractoryRequired() const override{
return AUTO_REFRACTORY_REQUIRED; }
```

### 20.86.1.3 SET\_RESET\_CODE

```
#define SET_RESET_CODE(
    RESET_CODE ) virtual std::string getResetCode() const override{ return RESET_CODE; }
```

### 20.86.1.4 SET\_SIM\_CODE

```
#define SET_SIM_CODE(
    SIM_CODE ) virtual std::string getSimCode() const override{ return SIM_CODE; }
```

### 20.86.1.5 SET\_SUPPORT\_CODE

```
#define SET_SUPPORT_CODE(
    SUPPORT_CODE ) virtual std::string getSupportCode() const override{ return SUPPORT_CODE; }
```

### 20.86.1.6 SET\_THRESHOLD\_CONDITION\_CODE

```
#define SET_THRESHOLD_CONDITION_CODE(
    THRESHOLD_CONDITION_CODE ) virtual std::string getThresholdConditionCode() const override{ return THRESHOLD_CONDITION_CODE; }
```

## 20.87 optimiser.cc File Reference

```
#include "optimiser.h"
#include <algorithm>
#include <iostream>
#include <map>
#include <numeric>
#include <cstdlib>
#include <cuda.h>
#include <cuda_runtime.h>
#include <plog/Log.h>
#include "path.h"
#include "logging.h"
#include "modelSpecInternal.h"
#include "code_generator/generateAll.h"
#include "utils.h"
```

### Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::CUDA](#)
- [CodeGenerator::CUDA::Optimiser](#)

### Functions

- [BACKEND\\_EXPORT](#) Backend [CodeGenerator::CUDA::Optimiser::createBackend](#) (const [ModelSpecInternal](#) &model, const filesystem::path &outputPath, plog::Severity backendLevel, plog::IAppender \*backendAppender, int localhostID, const Preferences &preferences)

## 20.88 optimiser.cc File Reference

```
#include "optimiser.h"
#include "modelSpecInternal.h"
```

### Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::SingleThreadedCPU](#)
- [CodeGenerator::SingleThreadedCPU::Optimiser](#)

### Functions

- [BACKEND\\_EXPORT](#) Backend [CodeGenerator::SingleThreadedCPU::Optimiser::createBackend](#) (const [ModelSpecInternal](#) &model, const filesystem::path &outputPath, plog::Severity backendLevel, plog::IAppender \*backendAppender, int localHostID, const Preferences &preferences)

## 20.89 optimiser.h File Reference

```
#include "backendExport.h"
#include "backend.h"
```

### Namespaces

- [plog](#)
- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::CUDA](#)
- [CodeGenerator::CUDA::Optimiser](#)

### Functions

- [BACKEND\\_EXPORT](#) Backend [CodeGenerator::CUDA::Optimiser::createBackend](#) (const [ModelSpecInternal](#) &model, const filesystem::path &outputPath, plog::Severity backendLevel, plog::IAppender \*backendAppender, int localHostID, const Preferences &preferences)

## 20.90 optimiser.h File Reference

```
#include <plog/Severity.h>
#include "backendExport.h"
#include "backend.h"
```

### Namespaces

- [plog](#)
- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::SingleThreadedCPU](#)
- [CodeGenerator::SingleThreadedCPU::Optimiser](#)

## Functions

- [BACKEND\\_EXPORT](#) Backend [CodeGenerator::SingleThreadedCPU::Optimiser::createBackend](#) (const [ModelSpecInternal](#) &model, const filesystem::path &outputPath, plog::Severity backendLevel, plog::l↵ Appender \*backendAppender, int localhostID, const Preferences &preferences)

## 20.91 postsynapticModels.cc File Reference

```
#include "postsynapticModels.h"
```

## Functions

- [IMPLEMENT\\_MODEL](#) ([PostsynapticModels::ExpCurr](#))
- [IMPLEMENT\\_MODEL](#) ([PostsynapticModels::ExpCond](#))
- [IMPLEMENT\\_MODEL](#) ([PostsynapticModels::DeltaCurr](#))

## 20.91.1 Function Documentation

## 20.91.1.1 IMPLEMENT\_MODEL() [1/3]

```
IMPLEMENT_MODEL (
    PostsynapticModels::ExpCurr )
```

## 20.91.1.2 IMPLEMENT\_MODEL() [2/3]

```
IMPLEMENT_MODEL (
    PostsynapticModels::ExpCond )
```

## 20.91.1.3 IMPLEMENT\_MODEL() [3/3]

```
IMPLEMENT_MODEL (
    PostsynapticModels::DeltaCurr )
```

## 20.92 postsynapticModels.h File Reference

```
#include <cmath>
#include "models.h"
```

## Classes

- class [PostsynapticModels::Base](#)  
*Base class for all postsynaptic models.*
- class [PostsynapticModels::ExpCurr](#)  
*Exponential decay with synaptic input treated as a current value.*
- class [PostsynapticModels::ExpCond](#)  
*Exponential decay with synaptic input treated as a conductance value.*
- class [PostsynapticModels::DeltaCurr](#)  
*Simple delta current synapse.*

## Namespaces

- [PostsynapticModels](#)

## Macros

- `#define SET_DECAY_CODE(DECAY_CODE) virtual std::string getDecayCode() const override{ return DECAY_CODE; }`
- `#define SET_CURRENT_CONVERTER_CODE(CURRENT_CONVERTER_CODE) virtual std::string getApplyInputCode() const override{ return "$(Isyn) += " CURRENT_CONVERTER_CODE ";"; }`
- `#define SET_APPLY_INPUT_CODE(APPLY_INPUT_CODE) virtual std::string getApplyInputCode() const override{ return APPLY_INPUT_CODE; }`
- `#define SET_SUPPORT_CODE(SUPPORT_CODE) virtual std::string getSupportCode() const override{ return SUPPORT_CODE; }`

### 20.92.1 Macro Definition Documentation

#### 20.92.1.1 SET\_APPLY\_INPUT\_CODE

```
#define SET_APPLY_INPUT_CODE(
    APPLY_INPUT_CODE ) virtual std::string getApplyInputCode() const override{ return
APPLY_INPUT_CODE; }
```

#### 20.92.1.2 SET\_CURRENT\_CONVERTER\_CODE

```
#define SET_CURRENT_CONVERTER_CODE(
    CURRENT_CONVERTER_CODE ) virtual std::string getApplyInputCode() const override{
return "$(Isyn) += " CURRENT_CONVERTER_CODE ";"; }
```

#### 20.92.1.3 SET\_DECAY\_CODE

```
#define SET_DECAY_CODE(
    DECAY_CODE ) virtual std::string getDecayCode() const override{ return DECAY_CODE; }
```

#### 20.92.1.4 SET\_SUPPORT\_CODE

```
#define SET_SUPPORT_CODE(
    SUPPORT_CODE ) virtual std::string getSupportCode() const override{ return SUPPORT_CODE; }
```

### 20.93 presynapticUpdateStrategy.cc File Reference

```
#include "presynapticUpdateStrategy.h"
#include <numeric>
#include <cuda_runtime.h>
#include "gennUtils.h"
#include "modelSpecInternal.h"
#include "code_generator/codeGenUtils.h"
#include "code_generator/codeStream.h"
```

```
#include "code_generator/substitutions.h"
#include "backend.h"
#include "utils.h"
```

#### Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::CUDA](#)
- [CodeGenerator::CUDA::PresynapticUpdateStrategy](#)

## 20.94 presynapticUpdateStrategy.h File Reference

```
#include "code_generator/backendBase.h"
```

#### Classes

- class [CodeGenerator::CUDA::PresynapticUpdateStrategy::Base](#)
- class [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpan](#)  
*Presynaptic parallelism.*
- class [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpan](#)  
*Postsynaptic parallelism.*
- class [CodeGenerator::CUDA::PresynapticUpdateStrategy::PostSpanBitmask](#)  
*Postsynaptic parallelism.*
- class [CodeGenerator::CUDA::PresynapticUpdateStrategy::PreSpanProcedural](#)  
*Presynaptic parallelism with procedural connectivity.*

#### Namespaces

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*
- [CodeGenerator::CUDA](#)
- [CodeGenerator::CUDA::PresynapticUpdateStrategy](#)

## 20.95 sharedLibraryModel.h File Reference

```
#include <algorithm>
#include <array>
#include <iostream>
#include <string>
#include <vector>
#include <utility>
#include <unordered_map>
#include <bitset>
#include <dlfcn.h>
```

#### Classes

- class [SharedLibraryModel< scalar >](#)

## 20.96 simulator.cc File Reference

```
#include "simulator.h"
#include <functional>
#include <iostream>
#include <map>
#include <memory>
#include <random>
#include <set>
#include <string>
#include <cassert>
#include <cmath>
#include <cstdlib>
#include <dlfcn.h>
#include "path.h"
#include "pugixml/pugixml.hpp"
#include <plog/Log.h>
#include <plog/Appenders/ConsoleAppender.h>
#include "spineMLLogging.h"
#include "spineMLUtils.h"
#include "connectors.h"
#include "input.h"
#include "inputValue.h"
#include "logOutput.h"
#include "modelProperty.h"
#include "stateVar.h"
#include "timer.h"
```

### Namespaces

- [SpineMLSimulator](#)

## 20.97 simulator.h File Reference

```
#include <map>
#include <set>
#include <string>
#include <tuple>
#include <plog/Severity.h>
#include <plog/Appenders/ConsoleAppender.h>
#include "input.h"
#include "inputValue.h"
#include "logOutput.h"
#include "modelProperty.h"
```

### Classes

- class [SpineMLSimulator::Simulator](#)

### Namespaces

- [SpineMLSimulator](#)



## 20.98 snippet.h File Reference

```
#include <algorithm>
#include <functional>
#include <string>
#include <vector>
#include <cassert>
#include "gennExport.h"
```

### Classes

- class [Snippet::ValueBase< NumVars >](#)
- class [Snippet::ValueBase< 0 >](#)
- class [Snippet::Base](#)  
*Base class for all code snippets.*
- struct [Snippet::Base::EGP](#)  
*An extra global parameter has a name and a type.*
- struct [Snippet::Base::ParamVal](#)  
*Additional input variables, row state variables and other things have a name, a type and an initial value.*
- struct [Snippet::Base::DerivedParam](#)  
*A derived parameter has a name and a function for obtaining its value.*
- class [Snippet::Init< SnippetBase >](#)

### Namespaces

- [Snippet](#)

### Macros

- `#define DECLARE\_SNIPPET(TYPE, NUM_PARAMS)`
- `#define IMPLEMENT\_SNIPPET(TYPE) TYPE *TYPE::s_Instance = NULL`
- `#define SET\_PARAM\_NAMES(...) virtual StringVec getParamNames() const override{ return __VA_ARGS__↵  
__;} }`
- `#define SET\_DERIVED\_PARAMS(...) virtual DerivedParamVec getDerivedParams() const override{ return  
__VA_ARGS__;} }`

#### 20.98.1 Macro Definition Documentation

##### 20.98.1.1 DECLARE\_SNIPPET

```
#define DECLARE_SNIPPET(  
    TYPE,  
    NUM_PARAMS )
```

#### Value:

```
private:  
    GENN_EXPORT static TYPE *s_Instance;  
public:  
    static const TYPE *getInstance()  
    {  
        if(s_Instance == NULL)  
        {  
            s_Instance = new TYPE;
```

```
    /  
    /  
    /  
    /  
    /
```

```
        }
        return s_Instance;
    }
    typedef Snippet::ValueBase<NUM_PARAMS> ParamValues
```

#### 20.98.1.2 IMPLEMENT\_SNIPPET

```
#define IMPLEMENT_SNIPPET(
    TYPE ) TYPE *TYPE::s_Instance = NULL
```

#### 20.98.1.3 SET\_DERIVED\_PARAMS

```
#define SET_DERIVED_PARAMS(
    ... ) virtual DerivedParamVec getDerivedParams() const override{ return __VA_ARGS__
RGS__;
```

#### 20.98.1.4 SET\_PARAM\_NAMES

```
#define SET_PARAM_NAMES(
    ... ) virtual StringVec getParamNames() const override{ return __VA_ARGS__; }
```

### 20.99 spikeRecorder.h File Reference

```
#include <algorithm>
#include <fstream>
#include <iterator>
#include <list>
#include <tuple>
#include <vector>
```

#### Classes

- class [SpikeWriterText](#)  
*Class to write spikes to text file.*
- class [SpikeWriterTextCached](#)  
*Class to write spikes to text file, caching in memory before writing.*
- class [SpikeRecorder< Writer >](#)  
*Class to read spikes from neuron groups.*

### 20.100 stateVar.h File Reference

```
#include <functional>
#include "spineMLLogging.h"
```

#### Classes

- class [SpineMLSimulator::StateVar< T >](#)

## Namespaces

- [SpineMLSimulator](#)

## 20.101 substitutions.h File Reference

```
#include <map>
#include <stdexcept>
#include <string>
#include <cassert>
#include "logging.h"
#include "codeGenUtils.h"
```

## Classes

- class [CodeGenerator::Substitutions](#)

## Namespaces

- [CodeGenerator](#)

*Helper class for generating code - automatically inserts brackets, indents etc.*

## 20.102 synapseGroup.cc File Reference

```
#include "synapseGroup.h"
#include <algorithm>
#include <cmath>
#include <iostream>
#include "neuronGroupInternal.h"
#include "gennUtils.h"
```

## 20.103 synapseGroup.h File Reference

```
#include <map>
#include <set>
#include <string>
#include <vector>
#include "gennExport.h"
#include "initSparseConnectivitySnippet.h"
#include "postsynapticModels.h"
#include "weightUpdateModels.h"
#include "synapseMatrixType.h"
#include "variableMode.h"
```

## Classes

- class [SynapseGroup](#)

## 20.104 synapseGroupInternal.h File Reference

```
#include "synapseGroup.h"
```

### Classes

- class [SynapseGroupInternal](#)

## 20.105 synapseMatrixType.h File Reference

### Enumerations

- enum [SynapseMatrixConnectivity](#) : unsigned int { [SynapseMatrixConnectivity::DENSE](#) = (1 << 0), [SynapseMatrixConnectivity::BITMASK](#) = (1 << 1), [SynapseMatrixConnectivity::SPARSE](#) = (1 << 2), [SynapseMatrixConnectivity::PROCEDURAL](#) = (1 << 3) }  
*< Flags defining different types of synaptic matrix connectivity*
- enum [SynapseMatrixWeight](#) : unsigned int { [SynapseMatrixWeight::GLOBAL](#) = (1 << 5), [SynapseMatrixWeight::INDIVIDUAL](#) = (1 << 6), [SynapseMatrixWeight::PROCEDURAL](#) = (1 << 7), [SynapseMatrixWeight::INDIVIDUAL\\_PSM](#) = (1 << 8) }
- enum [SynapseMatrixType](#) : unsigned int {  
[SynapseMatrixType::DENSE\\_GLOBALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::DENSE) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL), [SynapseMatrixType::DENSE\\_GLOBALG\\_INDIVIDUAL\\_PSM](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::DENSE) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM), [SynapseMatrixType::DENSE\\_INDIVIDUALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::DENSE) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM), [SynapseMatrixType::BITMASK\\_GLOBALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::BITMASK) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL), [SynapseMatrixType::BITMASK\\_GLOBALG\\_INDIVIDUAL\\_PSM](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::BITMASK) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM), [SynapseMatrixType::SPARSE\\_GLOBALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::SPARSE) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL), [SynapseMatrixType::SPARSE\\_GLOBALG\\_INDIVIDUAL\\_PSM](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::SPARSE) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM), [SynapseMatrixType::SPARSE\\_INDIVIDUALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::SPARSE) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM), [SynapseMatrixType::PROCEDURAL\\_GLOBALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::PROCEDURAL) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL), [SynapseMatrixType::PROCEDURAL\\_GLOBALG\\_INDIVIDUAL\\_PSM](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::PROCEDURAL) | static\_cast<unsigned int>(SynapseMatrixWeight::GLOBAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM), [SynapseMatrixType::PROCEDURAL\\_PROCEDURALG](#) = static\_cast<unsigned int>(SynapseMatrixConnectivity::PROCEDURAL) | static\_cast<unsigned int>(SynapseMatrixWeight::PROCEDURAL) | static\_cast<unsigned int>(SynapseMatrixWeight::INDIVIDUAL\_PSM) }

### Functions

- bool [operator&](#) ([SynapseMatrixType](#) type, [SynapseMatrixConnectivity](#) connType)
- bool [operator&](#) ([SynapseMatrixType](#) type, [SynapseMatrixWeight](#) weightType)
- [SynapseMatrixType operator|](#) ([SynapseMatrixWeight](#) weightType, [SynapseMatrixConnectivity](#) connType)

## 20.105.1 Enumeration Type Documentation

## 20.105.1.1 SynapseMatrixConnectivity

```
enum SynapseMatrixConnectivity : unsigned int [strong]
```

< Flags defining different types of synaptic matrix connectivity

## Enumerator

DENSE	
BITMASK	
SPARSE	
PROCEDURAL	

## 20.105.1.2 SynapseMatrixType

```
enum SynapseMatrixType : unsigned int [strong]
```

## Enumerator

DENSE_GLOBALG	
DENSE_GLOBALG_INDIVIDUAL_PSM	
DENSE_INDIVIDUALG	
BITMASK_GLOBALG	
BITMASK_GLOBALG_INDIVIDUAL_PSM	
SPARSE_GLOBALG	
SPARSE_GLOBALG_INDIVIDUAL_PSM	
SPARSE_INDIVIDUALG	
PROCEDURAL_GLOBALG	
PROCEDURAL_GLOBALG_INDIVIDUAL_PSM	
PROCEDURAL_PROCEDURALG	

## 20.105.1.3 SynapseMatrixWeight

```
enum SynapseMatrixWeight : unsigned int [strong]
```

## Enumerator

GLOBAL	
INDIVIDUAL	
PROCEDURAL	
INDIVIDUAL_PSM	

## 20.105.2 Function Documentation

**20.105.2.1 operator&() [1/2]**

```
bool operator & (
    SynapseMatrixType type,
    SynapseMatrixConnectivity connType ) [inline]
```

**20.105.2.2 operator&() [2/2]**

```
bool operator & (
    SynapseMatrixType type,
    SynapseMatrixWeight weightType ) [inline]
```

**20.105.2.3 operator" | ()**

```
SynapseMatrixType operator| (
    SynapseMatrixWeight weightType,
    SynapseMatrixConnectivity connType ) [inline]
```

**20.106 teeStream.h File Reference**

```
#include <ostream>
#include <streambuf>
#include <vector>
```

**Classes**

- class [CodeGenerator::TeeBuf](#)
- class [CodeGenerator::TeeStream](#)

**Namespaces**

- [CodeGenerator](#)  
*Helper class for generating code - automatically inserts brackets, indents etc.*

**20.107 timer.h File Reference**

```
#include <chrono>
#include <iostream>
#include <string>
#include "spineMLLogging.h"
```

**Classes**

- class [SpineMLSimulator::Timer](#)
- class [SpineMLSimulator::TimerAccumulate](#)

**Namespaces**

- [SpineMLSimulator](#)

## 20.108 timer.h File Reference

```
#include <chrono>
#include <fstream>
#include <iostream>
#include <string>
```

### Classes

- class [Timer](#)  
*A generic timer which can give the current elapsed time.*
- class [TimerAccumulate](#)  
*A timer which adds its elapsed time to an accumulator variable on destruction.*

## 20.109 utils.h File Reference

```
#include <iostream>
#include "logging.h"
```

### Macros

- #define [CHECK\\_CU\\_ERRORS](#)(call) call
- #define [CHECK\\_CUDA\\_ERRORS](#)(call)

### 20.109.1 Macro Definition Documentation

#### 20.109.1.1 CHECK\_CU\_ERRORS

```
#define CHECK_CU_ERRORS(  
    call ) call
```

#### 20.109.1.2 CHECK\_CUDA\_ERRORS

```
#define CHECK_CUDA_ERRORS(  
    call )
```

#### Value:

```
{  
    \  
    cudaError_t error = call;  
    \  
    if (error != cudaSuccess) {  
        \  
        LOGE_BACKEND << __FILE__ << ": " << __LINE__ << ": cuda runtime error " << error << ": " <<  
        cudaGetErrorString(error); \  
        exit(EXIT_FAILURE);  
        \  
    }  
    \  
}
```

## 20.110 variableMode.h File Reference

```
#include <stdint>
```

### Enumerations

- enum [VarLocation](#) : uint8\_t {  
[VarLocation::HOST](#) = (1 << 0), [VarLocation::DEVICE](#) = (1 << 1), [VarLocation::ZERO\\_COPY](#) = (1 << 2),  
[VarLocation::HOST\\_DEVICE](#) = HOST | DEVICE,  
[VarLocation::HOST\\_DEVICE\\_ZERO\\_COPY](#) = HOST | DEVICE | ZERO\_COPY }  
*< Flags defining which memory space variables should be allocated in*

### Functions

- bool [operator&](#) ([VarLocation](#) locA, [VarLocation](#) locB)

### 20.110.1 Enumeration Type Documentation

#### 20.110.1.1 VarLocation

```
enum VarLocation : uint8_t [strong]
```

< Flags defining which memory space variables should be allocated in

#### Enumerator

HOST	
DEVICE	
ZERO_COPY	
HOST_DEVICE	
HOST_DEVICE_ZERO_COPY	

### 20.110.2 Function Documentation

#### 20.110.2.1 operator&()

```
bool operator & (  

    VarLocation locA,  

    VarLocation locB ) [inline]
```

## 20.111 weightUpdateModels.cc File Reference

```
#include "weightUpdateModels.h"
```

### Functions

- [IMPLEMENT\\_MODEL](#) ([WeightUpdateModels::StaticPulse](#))



- [IMPLEMENT\\_MODEL](#) ([WeightUpdateModels::StaticPulseDendriticDelay](#))
- [IMPLEMENT\\_MODEL](#) ([WeightUpdateModels::StaticGraded](#))
- [IMPLEMENT\\_MODEL](#) ([WeightUpdateModels::PiecewiseSTDP](#))

### 20.111.1 Function Documentation

#### 20.111.1.1 IMPLEMENT\_MODEL() [1/4]

```
IMPLEMENT_MODEL (
    WeightUpdateModels::StaticPulse )
```

#### 20.111.1.2 IMPLEMENT\_MODEL() [2/4]

```
IMPLEMENT_MODEL (
    WeightUpdateModels::StaticPulseDendriticDelay )
```

#### 20.111.1.3 IMPLEMENT\_MODEL() [3/4]

```
IMPLEMENT_MODEL (
    WeightUpdateModels::StaticGraded )
```

#### 20.111.1.4 IMPLEMENT\_MODEL() [4/4]

```
IMPLEMENT_MODEL (
    WeightUpdateModels::PiecewiseSTDP )
```

## 20.112 weightUpdateModels.h File Reference

```
#include "models.h"
```

### Classes

- class [WeightUpdateModels::Base](#)  
*Base class for all weight update models.*
- class [WeightUpdateModels::StaticPulse](#)  
*Pulse-coupled, static synapse.*
- class [WeightUpdateModels::StaticPulseDendriticDelay](#)  
*Pulse-coupled, static synapse with heterogenous dendritic delays.*
- class [WeightUpdateModels::StaticGraded](#)  
*Graded-potential, static synapse.*
- class [WeightUpdateModels::PiecewiseSTDP](#)  
*This is a simple STDP rule including a time delay for the finite transmission speed of the synapse.*

### Namespaces

- [WeightUpdateModels](#)

## Macros

- `#define DECLARE_WEIGHT_UPDATE_MODEL(TYPE, NUM_PARAMS, NUM_VARS, NUM_PRE_VARS, NUM_POST_VARS)`
- `#define SET_SIM_CODE(SIM_CODE) virtual std::string getSimCode() const override{ return SIM_CODE; }`
- `#define SET_EVENT_CODE(EVENT_CODE) virtual std::string getEventCode() const override{ return EVENT_CODE; }`
- `#define SET_LEARN_POST_CODE(LEARN_POST_CODE) virtual std::string getLearnPostCode() const override{ return LEARN_POST_CODE; }`
- `#define SET_SYNAPSE_DYNAMICS_CODE(SYNAPSE_DYNAMICS_CODE) virtual std::string getSynapseDynamicsCode() const override{ return SYNAPSE_DYNAMICS_CODE; }`
- `#define SET_EVENT_THRESHOLD_CONDITION_CODE(EVENT_THRESHOLD_CONDITION_CODE) virtual std::string getEventThresholdConditionCode() const override{ return EVENT_THRESHOLD_CONDITION_CODE; }`
- `#define SET_SIM_SUPPORT_CODE(SIM_SUPPORT_CODE) virtual std::string getSimSupportCode() const override{ return SIM_SUPPORT_CODE; }`
- `#define SET_LEARN_POST_SUPPORT_CODE(LEARN_POST_SUPPORT_CODE) virtual std::string getLearnPostSupportCode() const override{ return LEARN_POST_SUPPORT_CODE; }`
- `#define SET_SYNAPSE_DYNAMICS_SUPPORT_CODE(SYNAPSE_DYNAMICS_SUPPORT_CODE) virtual std::string getSynapseDynamicsSupportCode() const override{ return SYNAPSE_DYNAMICS_SUPPORT_CODE; }`
- `#define SET_PRE_SPIKE_CODE(PRE_SPIKE_CODE) virtual std::string getPreSpikeCode() const override{ return PRE_SPIKE_CODE; }`
- `#define SET_POST_SPIKE_CODE(POST_SPIKE_CODE) virtual std::string getPostSpikeCode() const override{ return POST_SPIKE_CODE; }`
- `#define SET_PRE_VARS(...) virtual VarVec getPreVars() const override{ return __VA_ARGS__; }`
- `#define SET_POST_VARS(...) virtual VarVec getPostVars() const override{ return __VA_ARGS__; }`
- `#define SET_NEEDS_PRE_SPIKE_TIME(PRE_SPIKE_TIME_REQUIRED) virtual bool isPreSpikeTimeRequired() const override{ return PRE_SPIKE_TIME_REQUIRED; }`
- `#define SET_NEEDS_POST_SPIKE_TIME(POST_SPIKE_TIME_REQUIRED) virtual bool isPostSpikeTimeRequired() const override{ return POST_SPIKE_TIME_REQUIRED; }`

### 20.112.1 Macro Definition Documentation

#### 20.112.1.1 DECLARE\_WEIGHT\_UPDATE\_MODEL

```
#define DECLARE_WEIGHT_UPDATE_MODEL(
    TYPE,
    NUM_PARAMS,
    NUM_VARS,
    NUM_PRE_VARS,
    NUM_POST_VARS )
```

#### Value:

```
DECLARE_SNIPPET(TYPE, NUM_PARAMS);
    \
    typedef Models::VarInitContainerBase<NUM_VARS> VarValues;
    \
    typedef Models::VarInitContainerBase<NUM_PRE_VARS>
    PreVarValues;
    \
    typedef Models::VarInitContainerBase<NUM_POST_VARS>
    PostVarValues
```

### 20.112.1.2 SET\_EVENT\_CODE

```
#define SET_EVENT_CODE(  
    EVENT_CODE ) virtual std::string getEventCode() const override{ return EVENT_CODE;  
}; }
```

### 20.112.1.3 SET\_EVENT\_THRESHOLD\_CONDITION\_CODE

```
#define SET_EVENT_THRESHOLD_CONDITION_CODE(  
    EVENT_THRESHOLD_CONDITION_CODE ) virtual std::string getEventThresholdConditionCode() const override{ return EVENT_THRESHOLD_CONDITION_CODE; }
```

### 20.112.1.4 SET\_LEARN\_POST\_CODE

```
#define SET_LEARN_POST_CODE(  
    LEARN_POST_CODE ) virtual std::string getLearnPostCode() const override{ return LEARN_POST_CODE; }
```

### 20.112.1.5 SET\_LEARN\_POST\_SUPPORT\_CODE

```
#define SET_LEARN_POST_SUPPORT_CODE(  
    LEARN_POST_SUPPORT_CODE ) virtual std::string getLearnPostSupportCode() const override{ return LEARN_POST_SUPPORT_CODE; }
```

### 20.112.1.6 SET\_NEEDS\_POST\_SPIKE\_TIME

```
#define SET_NEEDS_POST_SPIKE_TIME(  
    POST_SPIKE_TIME_REQUIRED ) virtual bool isPostSpikeTimeRequired() const override{ return POST_SPIKE_TIME_REQUIRED; }
```

### 20.112.1.7 SET\_NEEDS\_PRE\_SPIKE\_TIME

```
#define SET_NEEDS_PRE_SPIKE_TIME(  
    PRE_SPIKE_TIME_REQUIRED ) virtual bool isPreSpikeTimeRequired() const override{ return PRE_SPIKE_TIME_REQUIRED; }
```

### 20.112.1.8 SET\_POST\_SPIKE\_CODE

```
#define SET_POST_SPIKE_CODE(  
    POST_SPIKE_CODE ) virtual std::string getPostSpikeCode() const override{ return POST_SPIKE_CODE; }
```

### 20.112.1.9 SET\_POST\_VARS

```
#define SET_POST_VARS(  
    ... ) virtual VarVec getPostVars() const override{ return __VA_ARGS__; }
```

**20.112.1.10 SET\_PRE\_SPIKE\_CODE**

```
#define SET_PRE_SPIKE_CODE(  
    PRE_SPIKE_CODE ) virtual std::string getPreSpikeCode() const override{ return P←  
RE_SPIKE_CODE; }
```

**20.112.1.11 SET\_PRE\_VARS**

```
#define SET_PRE_VARS(  
    ... ) virtual VarVec getPreVars() const override{ return __VA_ARGS__; }
```

**20.112.1.12 SET\_SIM\_CODE**

```
#define SET_SIM_CODE(  
    SIM_CODE ) virtual std::string getSimCode() const override{ return SIM_CODE; }
```

**20.112.1.13 SET\_SIM\_SUPPORT\_CODE**

```
#define SET_SIM_SUPPORT_CODE(  
    SIM_SUPPORT_CODE ) virtual std::string getSimSupportCode() const override{ return  
SIM_SUPPORT_CODE; }
```

**20.112.1.14 SET\_SYNAPSE\_DYNAMICS\_CODE**

```
#define SET_SYNAPSE_DYNAMICS_CODE(  
    SYNAPSE_DYNAMICS_CODE ) virtual std::string getSynapseDynamicsCode() const override{  
return SYNAPSE_DYNAMICS_CODE; }
```

**20.112.1.15 SET\_SYNAPSE\_DYNAMICS\_SUPPORT\_CODE**

```
#define SET_SYNAPSE_DYNAMICS_SUPPORT_CODE(  
    SYNAPSE_DYNAMICS_SUPPORT_CODE ) virtual std::string getSynapseDynamicsSuppport←  
Code() const override{ return SYNAPSE_DYNAMICS_SUPPORT_CODE; }
```

## References

- [1] Eugene M Izhikevich. Simple model of spiking neurons. *IEEE Transactions on neural networks*, 14(6):1569–1572, 2003. [7](#), [8](#), [9](#), [65](#), [83](#), [223](#), [224](#), [225](#), [226](#), [409](#), [410](#)
- [2] Abigail Morrison, Markus Diesmann, and Wulfram Gerstner. Phenomenological models of synaptic plasticity based on spike timing. *Biological Cybernetics*, 98:459–478, 2008. [34](#)
- [3] T. Nowotny. Parallel implementation of a spiking neuronal network model of unsupervised olfactory learning on NVidia CUDA. In P. Sobrevilla, editor, *IEEE World Congress on Computational Intelligence*, pages 3238–3245, Barcelona, 2010. IEEE. [34](#)
- [4] Thomas Nowotny, Ramón Huerta, Henry DI Abarbanel, and Mikhail I Rabinovich. Self-organization in the olfactory system: one shot odor recognition in insects. *Biological cybernetics*, 93(6):436–446, 2005. [11](#), [291](#)
- [5] Nikolai F Rulkov. Modeling of spiking-bursting neural behavior using two-dimensional map. *Physical Review E*, 65(4):041922, 2002. [291](#)
- [6] Marcel Stimberg, Dan F. M. Goodman, and Thomas Nowotny. Brian2genn: a system for accelerating a large variety of spiking neural networks with graphics hardware. *bioRxiv*, 2018. [14](#)
- [7] R. D. Traub and R. Miles. *Neural Networks of the Hippocampus*. Cambridge University Press, New York, 1991. [11](#), [12](#), [352](#)



## Index

- `__init__`
    - `pygenn::genn_groups::CurrentSource`, 176
    - `pygenn::genn_groups::Group`, 219
    - `pygenn::genn_groups::NeuronGroup`, 249
    - `pygenn::genn_groups::SynapseGroup`, 323
    - `pygenn::genn_model::GeNNModel`, 210
    - `pygenn::model_preprocessor::ExtraGlobalVariable`, 197
    - `pygenn::model_preprocessor::Variable`, 367
  - `__init__.py`, 372
  - `~BackendBase`
    - `CodeGenerator::BackendBase`, 138
  - `~Base`
    - `Snippet::Base`, 157
    - `SpineMLSimulator::Input::Base`, 165
    - `SpineMLSimulator::InputValue::Base`, 166
    - `SpineMLSimulator::LogOutput::Base`, 168
    - `SpineMLSimulator::ModelProperty::Base`, 169
  - `~ModelSpec`
    - `ModelSpec`, 235
  - `~NetworkClient`
    - `SpineMLSimulator::NetworkClient`, 247
  - `~Scope`
    - `CodeGenerator::CodeStream::Scope`, 294
  - `~SharedLibraryModel`
    - `SharedLibraryModel`, 295
  - `~Simulator`
    - `SpineMLSimulator::Simulator`, 301
  - `~SpikeWriterTextCached`
    - `SpikeWriterTextCached`, 312
  - `~Timer`
    - `SpineMLSimulator::Timer`, 347
    - `Timer`, 347
  - `~TimerAccumulate`
    - `SpineMLSimulator::TimerAccumulate`, 349
    - `TimerAccumulate`, 348
- 00\_MainPage.dox, 371
- 01\_Installation.dox, 371
- 02\_Quickstart.dox, 371
- 03\_Examples.dox, 371
- 05\_SpineML.dox, 371
- 06\_Brian2GeNN.dox, 372
- 07\_PyGeNN.dox, 372
- 09\_ReleaseNotes.dox, 372
- 10\_UserManual.dox, 372
- 11\_Tutorial.dox, 372
- 12\_Tutorial.dox, 372
- 13\_UserGuide.dox, 372
- 14\_Credits.dox, 372
- `access`
  - `Models::Base::Var`, 366
- `add_current_source`
  - `pygenn::genn_model::GeNNModel`, 210
- `add_extra_global_param`
  - `pygenn::genn_groups::CurrentSource`, 176
  - `pygenn::genn_groups::NeuronGroup`, 249
  - `pygenn::genn_groups::SynapseGroup`, 323
- `add_neuron_population`
  - `pygenn::genn_model::GeNNModel`, 211
- `add_synapse_population`
  - `pygenn::genn_model::GeNNModel`, 211
- `add_to`
  - `pygenn::genn_groups::CurrentSource`, 176
  - `pygenn::genn_groups::NeuronGroup`, 249
  - `pygenn::genn_groups::SynapseGroup`, 324
- `addCurrentSource`
  - `ModelSpec`, 235, 236
- `addFuncSubstitution`
  - `CodeGenerator::Substitutions`, 320
- `addInSyn`
  - `NeuronGroup`, 254
- `addNeuronPopulation`
  - `ModelSpec`, 236, 237
- `addOutSyn`
  - `NeuronGroup`, 254
- `addParamNameSubstitution`
  - `CodeGenerator::Substitutions`, 320
- `addParamValueSubstitution`
  - `CodeGenerator::Substitutions`, 320
- `addPresynapticUpdateStrategy`
  - `CodeGenerator::CUDA::Backend`, 110
- `addSpkEventCondition`
  - `NeuronGroup`, 255
- `addSynapsePopulation`
  - `ModelSpec`, 237–239
- `addType`
  - `CodeGenerator::BackendBase`, 138
- `addVarNameSubstitution`
  - `CodeGenerator::Substitutions`, 320
- `addVarSubstitution`
  - `CodeGenerator::Substitutions`, 320
- `addVarValueSubstitution`
  - `CodeGenerator::Substitutions`, 320
- `allocateExtraGlobalParam`
  - `SharedLibraryModel`, 295
- `allocateMem`
  - `SharedLibraryModel`, 295
- `Analogue`
  - `SpineMLSimulator::Input::Analogue`, 101
- `AnalogueBase`
  - `SpineMLSimulator::LogOutput::AnalogueBase`, 102
- `AnalogueExternal`
  - `SpineMLSimulator::LogOutput::AnalogueExternal`, 104
- `AnalogueFile`
  - `SpineMLSimulator::LogOutput::AnalogueFile`, 105
- `AnalogueNetwork`

- SpineMLSimulator::LogOutput::AnalogueNetwork, 106
- AnalogueRecorder
  - AnalogueRecorder, 107
  - record, 107
- AnalogueRecorder< T >, 107
- analogueRecorder.h, 372
- apply
  - CodeGenerator::Substitutions, 320
  - SpineMLSimulator::Input::Analogue, 102
  - SpineMLSimulator::Input::Base, 165
  - SpineMLSimulator::Input::InterSpikeIntervalBase, 222
  - SpineMLSimulator::Input::SpikeTime, 311
- applyCheckUnreplaced
  - CodeGenerator::Substitutions, 321
- applyScalar
  - SpineMLSimulator::InputValue::ScalarBase, 293
- automaticCopy
  - CodeGenerator::PreferencesBase, 283
- BACKEND\_EXPORT
  - backendExport.h, 375
- Backend
  - CodeGenerator::CUDA::Backend, 110
  - CodeGenerator::SingleThreadedCPU::Backend, 124
- backend.cc, 372, 373
- backend.h, 373, 374
- backend\_log\_level
  - pygenn::genn\_model::GeNNModel, 217
- backend\_modules
  - pygenn::genn\_model, 92
- BackendBase
  - CodeGenerator::BackendBase, 138
- backendBase.cc, 374
  - TYPE, 374
- backendBase.h, 375
- backendExport.h, 375
  - BACKEND\_EXPORT, 375
- Base
  - SpineMLSimulator::Input::Base, 165
  - SpineMLSimulator::InputValue::Base, 166
  - SpineMLSimulator::LogOutput::Base, 167
  - SpineMLSimulator::ModelProperty::Base, 169
- binomial.cc, 375
  - binomialInverseCDF, 376
- binomial.h, 376
  - binomialInverseCDF, 376
- binomialInverseCDF
  - binomial.cc, 376
  - binomial.h, 376
- BlockSizeSelect
  - CodeGenerator::CUDA, 79
- blockSizeSelectMethod
  - CodeGenerator::CUDA::Preferences, 281
- build
  - pygenn::genn\_model::GeNNModel, 212
- buildAndRun
  - GenerateRunBase, 207
- CHECK\_CU\_ERRORS
  - utils.h, 423
- CHECK\_CUDA\_ERRORS
  - utils.h, 423
- CalcMaxLengthFunc
  - InitSparseConnectivitySnippet::Base, 150
- calcNumTimesteps
  - SpineMLSimulator::Simulator, 301
- CB
  - CodeGenerator::CodeStream::CB, 170
- ceilDivide
  - CodeGenerator, 73
- Channel
  - Logging, 82
- checkNumDelaySlots
  - NeuronGroup, 255
- checkUnreplacedVariables
  - CodeGenerator, 73
- codeGenUtils.cc, 376
  - MathsFunc, 377
- codeGenUtils.h, 377
- CodeGenerator, 71
  - ceilDivide, 73
  - checkUnreplacedVariables, 73
  - ensureFtype, 73
  - functionSubstitute, 73
  - generateAll, 74
  - generateInit, 74
  - generateMPI, 74
  - generateMSBuild, 74
  - generateMakefile, 74
  - generateNeuronUpdate, 74
  - generateRunner, 75
  - generateSupportCode, 75
  - generateSynapseUpdate, 75
  - neuronSubstitutionsInSynapticCode, 75
  - operator<<, 76
  - padSize, 76
  - postNeuronSubstitutionsInSynapticCode, 76
  - preNeuronSubstitutionsInSynapticCode, 77
  - regexFuncSubstitute, 77
  - regexVarSubstitute, 77
  - substitute, 77
  - writePreciseString, 78
- CodeGenerator::BackendBase, 134
  - ~BackendBase, 138
  - addType, 138
  - BackendBase, 138
  - genAllocateMemPreamble, 138
  - genArray, 138
  - genCurrentSpikeLikeEventPull, 138
  - genCurrentSpikeLikeEventPush, 139
  - genCurrentTrueSpikePull, 139
  - genCurrentTrueSpikePush, 139
  - genCurrentVariablePull, 139
  - genCurrentVariablePush, 139
  - genCurrentVariablePushPull, 140



- genDefinitionsInternalPreamble, 140
- genDefinitionsPreamble, 140
- genExtraGlobalParamAllocation, 140
- genExtraGlobalParamDefinition, 140
- genExtraGlobalParamImplementation, 141
- genExtraGlobalParamPull, 141
- genExtraGlobalParamPush, 141
- genGlobalRNG, 141
- genInit, 141
- genMSBuildCompileModule, 142
- genMSBuildConfigProperties, 142
- genMSBuildImportProps, 143
- genMSBuildImportTarget, 143
- genMSBuildItemDefinitions, 143
- genMakefileCompileRule, 142
- genMakefileLinkRule, 142
- genMakefilePreamble, 142
- genNeuronUpdate, 143
- genPopVariableInit, 144
- genPopulationRNG, 143
- genReturnFreeDeviceMemoryBytes, 144
- genRunnerPreamble, 144
- genScalar, 144
- genStepTimeFinalisePreamble, 144
- genSynapseUpdate, 145
- genSynapseVariableRowInit, 145
- genTimer, 145
- genVariableAllocation, 146
- genVariableDefinition, 146
- genVariableFree, 146
- genVariableImplementation, 146
- genVariableInit, 146
- genVariablePull, 147
- genVariablePush, 147
- genVariablePushPull, 147
- getDeviceMemoryBytes, 147
- getLocalHostID, 148
- getSize, 148
- getSynapticMatrixRowStride, 148
- getVarPrefix, 148
- GroupHandler, 137
- Handler, 137
- isAutomaticCopyEnabled, 148
- isGlobalRNGRequired, 148
- isPostsynapticRemapRequired, 148
- isSynRemapRequired, 149
- NeuronGroupHandler, 137
- NeuronGroupSimHandler, 137
- SynapseGroupHandler, 137
- CodeGenerator::CUDA::Backend, 107
  - addPresynapticUpdateStrategy, 110
  - Backend, 110
  - genAllocateMemPreamble, 110
  - genCurrentSpikeLikeEventPull, 111
  - genCurrentSpikeLikeEventPush, 111
  - genCurrentTrueSpikePull, 111
  - genCurrentTrueSpikePush, 111
  - genCurrentVariablePull, 111
  - genCurrentVariablePush, 112
  - genDefinitionsInternalPreamble, 112
  - genDefinitionsPreamble, 112
  - genExtraGlobalParamAllocation, 112
  - genExtraGlobalParamDefinition, 112
  - genExtraGlobalParamImplementation, 113
  - genExtraGlobalParamPull, 113
  - genExtraGlobalParamPush, 113
  - genGlobalRNG, 113
  - genInit, 113
  - genMSBuildCompileModule, 114
  - genMSBuildConfigProperties, 114
  - genMSBuildImportProps, 115
  - genMSBuildImportTarget, 115
  - genMSBuildItemDefinitions, 115
  - genMakefileCompileRule, 114
  - genMakefileLinkRule, 114
  - genMakefilePreamble, 114
  - genNeuronUpdate, 115
  - genPopVariableInit, 116
  - genPopulationRNG, 115
  - genReturnFreeDeviceMemoryBytes, 116
  - genRunnerPreamble, 116
  - genStepTimeFinalisePreamble, 116
  - genSynapseUpdate, 116
  - genSynapseVariableRowInit, 117
  - genTimer, 117
  - genVariableAllocation, 118
  - genVariableDefinition, 118
  - genVariableFree, 118
  - genVariableImplementation, 118
  - genVariableInit, 118
  - genVariablePull, 119
  - genVariablePush, 119
  - getChosenCUDADevice, 119
  - getChosenDeviceID, 119
  - getDeviceMemoryBytes, 119
  - getFloatAtomicAdd, 119
  - getKernelBlockSize, 119
  - getNVCCFlags, 120
  - getNumInitialisationRNGStreams, 120
  - getNumPostsynapticUpdateThreads, 120
  - getNumPresynapticUpdateThreads, 120
  - getNumSynapseDynamicsThreads, 120
  - getRuntimeVersion, 120
  - getSynapticMatrixRowStride, 120
  - getVarPrefix, 120
  - isAutomaticCopyEnabled, 121
  - isGlobalRNGRequired, 121
  - isPostsynapticRemapRequired, 121
  - isSynRemapRequired, 121
  - KernelNames, 121
- CodeGenerator::CUDA::Optimiser, 80
  - createBackend, 80
- CodeGenerator::CUDA::Preferences, 280
  - blockSizeSelectMethod, 281
  - deviceSelectMethod, 281
  - generateLineInfo, 281

- manualBlockSizes, 281
- manualDeviceID, 282
- Preferences, 281
- showPtxInfo, 282
- userNvccFlags, 282
- CodeGenerator::CUDA::PresynapticUpdateStrategy, 80
- CodeGenerator::CUDA::PresynapticUpdateStrategy::↔
  - Base, 159
  - genPostamble, 159
  - genPreamble, 160
  - genUpdate, 160
  - getNumThreads, 160
  - getSharedMemoryPerThread, 160
  - getSynapticMatrixRowStride, 161
  - isCompatible, 161
- CodeGenerator::CUDA::PresynapticUpdateStrategy::↔
  - PostSpan, 276
  - genPostamble, 276
  - genPreamble, 276
  - genUpdate, 277
  - getNumThreads, 277
  - getSharedMemoryPerThread, 277
  - getSynapticMatrixRowStride, 277
  - isCompatible, 278
- CodeGenerator::CUDA::PresynapticUpdateStrategy::↔
  - PostSpanBitmask, 278
  - genPostamble, 279
  - genPreamble, 279
  - genUpdate, 279
  - getNumThreads, 279
  - getSharedMemoryPerThread, 279
  - getSynapticMatrixRowStride, 280
  - isCompatible, 280
- CodeGenerator::CUDA::PresynapticUpdateStrategy::↔
  - PreSpan, 284
  - genPostamble, 285
  - genPreamble, 285
  - genUpdate, 285
  - getNumThreads, 285
  - getSharedMemoryPerThread, 286
  - getSynapticMatrixRowStride, 286
  - isCompatible, 286
- CodeGenerator::CUDA::PresynapticUpdateStrategy::↔
  - PreSpanProcedural, 286
  - genPostamble, 287
  - genPreamble, 287
  - genUpdate, 287
  - getNumThreads, 288
  - getSharedMemoryPerThread, 288
  - getSynapticMatrixRowStride, 288
  - isCompatible, 288
- CodeGenerator::CUDA, 78
  - BlockSizeSelect, 79
  - DeviceSelect, 79
  - Kernel, 79
  - KernelBlockSize, 79
- CodeGenerator::CodeStream, 170
  - CodeStream, 171
  - operator<<, 171
  - setSink, 171
- CodeGenerator::CodeStream::CB, 169
  - CB, 170
  - Level, 170
- CodeGenerator::CodeStream::OB, 263
  - Level, 263
  - OB, 263
- CodeGenerator::CodeStream::Scope, 293
  - ~Scope, 294
  - Scope, 294
- CodeGenerator::FunctionTemplate, 202
  - doublePrecisionTemplate, 203
  - genericName, 203
  - numArguments, 203
  - operator=, 203
  - singlePrecisionTemplate, 203
- CodeGenerator::MemAlloc, 230
  - device, 230
  - getDeviceBytes, 231
  - getDeviceMBytes, 231
  - getHostBytes, 231
  - getHostMBytes, 231
  - getZeroCopyBytes, 231
  - getZeroCopyMBytes, 231
  - host, 231
  - operator+=, 231
  - zero, 231
  - zeroCopy, 231
- CodeGenerator::PreferencesBase, 282
  - automaticCopy, 283
  - debugCode, 283
  - enableBitmaskOptimisations, 283
  - logLevel, 283
  - optimizeCode, 283
  - userCxxFlagsGNU, 284
  - userNvccFlagsGNU, 284
- CodeGenerator::SingleThreadedCPU::Backend, 122
  - Backend, 124
  - genAllocateMemPreamble, 124
  - genCurrentSpikeLikeEventPull, 124
  - genCurrentSpikeLikeEventPush, 125
  - genCurrentTrueSpikePull, 125
  - genCurrentTrueSpikePush, 125
  - genCurrentVariablePull, 125
  - genCurrentVariablePush, 125
  - genDefinitionsInternalPreamble, 125
  - genDefinitionsPreamble, 126
  - genExtraGlobalParamAllocation, 126
  - genExtraGlobalParamDefinition, 126
  - genExtraGlobalParamImplementation, 126
  - genExtraGlobalParamPull, 126
  - genExtraGlobalParamPush, 127
  - genGlobalRNG, 127
  - genInit, 127
  - genMSBuildCompileModule, 128
  - genMSBuildConfigProperties, 128
  - genMSBuildImportProps, 128

- genMSBuildImportTarget, 128
- genMSBuildItemDefinitions, 128
- genMakefileCompileRule, 127
- genMakefileLinkRule, 128
- genMakefilePreamble, 128
- genNeuronUpdate, 129
- genPopVariableInit, 129
- genPopulationRNG, 129
- genReturnFreeDeviceMemoryBytes, 130
- genRunnerPreamble, 130
- genStepTimeFinalisePreamble, 130
- genSynapseUpdate, 130
- genSynapseVariableRowInit, 131
- genTimer, 131
- genVariableAllocation, 131
- genVariableDefinition, 131
- genVariableFree, 132
- genVariableImplementation, 132
- genVariableInit, 132
- genVariablePull, 132
- genVariablePush, 132
- getDeviceMemoryBytes, 133
- getSynapticMatrixRowStride, 133
- getVarPrefix, 133
- isAutomaticCopyEnabled, 133
- isGlobalRNGRequired, 133
- isPostsynapticRemapRequired, 134
- isSynRemapRequired, 134
- CodeGenerator::SingleThreadedCPU::Optimiser, 81
  - createBackend, 81
- CodeGenerator::SingleThreadedCPU::Preferences, 282
- CodeGenerator::SingleThreadedCPU, 80
- CodeGenerator::Substitutions, 319
  - addFuncSubstitution, 320
  - addParamNameSubstitution, 320
  - addParamValueSubstitution, 320
  - addVarNameSubstitution, 320
  - addVarSubstitution, 320
  - addVarValueSubstitution, 320
  - apply, 320
  - applyCheckUnreplaced, 321
  - getVarSubstitution, 321
  - hasVarSubstitution, 321
  - operator[], 321
  - Substitutions, 319
- CodeGenerator::TeeBuf, 345
  - TeeBuf, 345
- CodeGenerator::TeeStream, 346
  - TeeStream, 346
- CodeStream
  - CodeGenerator::CodeStream, 171
- codeStream.cc, 379
- codeStream.h, 379
- connect
  - SpineMLSimulator::NetworkClient, 247
- connections\_set
  - pygenn::genn\_groups::SynapseGroup, 329
- connectivity\_extra\_global\_params
  - pygenn::genn\_groups::SynapseGroup, 329
- connectivity\_initialiser
  - pygenn::genn\_groups::SynapseGroup, 329
- connectors.cc, 379
- connectors.h, 380
- Constant
  - SpineMLSimulator::InputValue::Constant, 173
- ConstantArray
  - SpineMLSimulator::InputValue::ConstantArray, 174
- create
  - SpineMLSimulator::Connectors, 98
  - SpineMLSimulator::InputValue, 99
  - SpineMLSimulator::ModelProperty, 100
- create\_cmlf\_class
  - pygenn::genn\_model, 86
- create\_custom\_current\_source\_class
  - pygenn::genn\_model, 86
- create\_custom\_init\_var\_snippet\_class
  - pygenn::genn\_model, 87
- create\_custom\_model\_class
  - pygenn::genn\_model, 87
- create\_custom\_neuron\_class
  - pygenn::genn\_model, 88
- create\_custom\_postsynaptic\_class
  - pygenn::genn\_model, 89
- create\_custom\_sparse\_connect\_init\_snippet\_class
  - pygenn::genn\_model, 89
- create\_custom\_weight\_update\_class
  - pygenn::genn\_model, 90
- create\_dpf\_class
  - pygenn::genn\_model, 91
- createBackend
  - CodeGenerator::CUDA::Optimiser, 80
  - CodeGenerator::SingleThreadedCPU::Optimiser, 81
- current\_source\_model
  - pygenn::genn\_groups::CurrentSource, 178
- current\_sources
  - pygenn::genn\_model::GeNNModel, 217
- current\_spikes
  - pygenn::genn\_groups::NeuronGroup, 250
- CurrentSource, 178
  - CurrentSource, 179
  - getCurrentSourceModel, 179
  - getDerivedParams, 180
  - getExtraGlobalParamLocation, 180
  - getName, 180
  - getParams, 180
  - getVarInitialisers, 180
  - getVarLocation, 180
  - initDerivedParams, 180
  - isInitRNGRequired, 181
  - isSimRNGRequired, 181
  - setExtraGlobalParamLocation, 181
  - setVarLocation, 181
- currentSource.cc, 380
- currentSource.h, 380
- CurrentSourceInternal, 181

- CurrentSourceInternal, 182
- currentSourceInternal.h, 381
- CurrentSourceModels, 81
- currentSourceModels.cc, 381
- IMPLEMENT\_MODEL, 381
- currentSourceModels.h, 381
- SET\_INJECTION\_CODE, 382
- CurrentSourceModels::Base, 149
  - getInjectionCode, 149
- CurrentSourceModels::DC, 182
  - getInstance, 183
  - getParamNames, 183
  - ParamValues, 183
  - PostVarValues, 183
  - PreVarValues, 183
  - SET\_INJECTION\_CODE, 183
  - VarValues, 183
- CurrentSourceModels::GaussianNoise, 205
  - getInstance, 206
  - getParamNames, 206
  - ParamValues, 206
  - PostVarValues, 206
  - PreVarValues, 206
  - SET\_INJECTION\_CODE, 206
  - VarValues, 206
- DECLARE\_MODEL
  - models.h, 401
- DECLARE\_SNIPPET
  - InitSparseConnectivitySnippet::FixedProbability, 199
  - InitSparseConnectivitySnippet::FixedProbability↔NoAutapse, 202
  - InitSparseConnectivitySnippet::OneToOne, 264
  - InitSparseConnectivitySnippet::Uninitialised, 363
  - InitVarSnippet::Constant, 172
  - InitVarSnippet::Exponential, 192
  - InitVarSnippet::Gamma, 204
  - InitVarSnippet::Normal, 261
  - InitVarSnippet::Uniform, 360
  - InitVarSnippet::Uninitialised, 362
  - snippet.h, 417
- DECLARE\_WEIGHT\_UPDATE\_MODEL
  - weightUpdateModels.h, 426
  - WeightUpdateModels::PiecewiseSTDP, 267
  - WeightUpdateModels::StaticGraded, 315
  - WeightUpdateModels::StaticPulse, 317
  - WeightUpdateModels::StaticPulseDendriticDelay, 318
- DataType
  - SpineMLSimulator::NetworkClient, 245
- debugCode
  - CodeGenerator::PreferencesBase, 283
- default\_sparse\_connectivity\_location
  - pygenn::genn\_model::GeNNModel, 212, 213
- default\_var\_location
  - pygenn::genn\_model::GeNNModel, 213, 217
- delay\_slots
  - pygenn::genn\_groups::NeuronGroup, 250
- DerivedParamVec
  - Snippet::Base, 156
- device
  - CodeGenerator::MemAlloc, 230
- DeviceSelect
  - CodeGenerator::CUDA, 79
- deviceSelectMethod
  - CodeGenerator::CUDA::Preferences, 281
- doublePrecisionTemplate
  - CodeGenerator::FunctionTemplate, 203
- dT
  - pygenn::genn\_model::GeNNModel, 213, 218
- EGPVec
  - Snippet::Base, 157
- enableBitmaskOptimisations
  - CodeGenerator::PreferencesBase, 283
- end
  - pygenn::genn\_model::GeNNModel, 213
- ensureFtype
  - CodeGenerator, 73
- Event
  - SpineMLSimulator::LogOutput::Event, 187
- ExponentialDistribution
  - SpineMLSimulator::ModelProperty::Exponential↔Distribution, 193
- External
  - SpineMLSimulator::InputValue::External, 194
- ExternalNetwork
  - SpineMLSimulator::InputValue::ExternalNetwork, 195
- extra\_global\_params
  - pygenn::genn\_groups::Group, 219
- filesystem, 81
- finalize
  - ModelSpec, 240
- findCurrentSource
  - ModelSpec, 241
- findNeuronGroup
  - ModelSpec, 241
- findSynapseGroup
  - ModelSpec, 241
- Fixed
  - SpineMLSimulator::ModelProperty::Fixed, 198
- FloatType
  - modelSpec.h, 404
- free\_device\_mem\_bytes
  - pygenn::genn\_model::GeNNModel, 213
- freeExtraGlobalParam
  - SharedLibraryModel, 296
- freeMem
  - SharedLibraryModel, 296
- func
  - Snippet::Base::DerivedParam, 186
- functionSubstitute
  - CodeGenerator, 73
- GENN\_EXPORT

- gennExport.h, 389
- GeNNType
  - pygenn::model\_preprocessor, 97
- genAllocateMemPreamble
  - CodeGenerator::BackendBase, 138
  - CodeGenerator::CUDA::Backend, 110
  - CodeGenerator::SingleThreadedCPU::Backend, 124
- genArray
  - CodeGenerator::BackendBase, 138
- genCurrentSpikeLikeEventPull
  - CodeGenerator::BackendBase, 138
  - CodeGenerator::CUDA::Backend, 111
  - CodeGenerator::SingleThreadedCPU::Backend, 124
- genCurrentSpikeLikeEventPush
  - CodeGenerator::BackendBase, 139
  - CodeGenerator::CUDA::Backend, 111
  - CodeGenerator::SingleThreadedCPU::Backend, 125
- genCurrentTrueSpikePull
  - CodeGenerator::BackendBase, 139
  - CodeGenerator::CUDA::Backend, 111
  - CodeGenerator::SingleThreadedCPU::Backend, 125
- genCurrentTrueSpikePush
  - CodeGenerator::BackendBase, 139
  - CodeGenerator::CUDA::Backend, 111
  - CodeGenerator::SingleThreadedCPU::Backend, 125
- genCurrentVariablePull
  - CodeGenerator::BackendBase, 139
  - CodeGenerator::CUDA::Backend, 111
  - CodeGenerator::SingleThreadedCPU::Backend, 125
- genCurrentVariablePush
  - CodeGenerator::BackendBase, 139
  - CodeGenerator::CUDA::Backend, 112
  - CodeGenerator::SingleThreadedCPU::Backend, 125
- genCurrentVariablePushPull
  - CodeGenerator::BackendBase, 140
- genDefinitionsInternalPreamble
  - CodeGenerator::BackendBase, 140
  - CodeGenerator::CUDA::Backend, 112
  - CodeGenerator::SingleThreadedCPU::Backend, 125
- genDefinitionsPreamble
  - CodeGenerator::BackendBase, 140
  - CodeGenerator::CUDA::Backend, 112
  - CodeGenerator::SingleThreadedCPU::Backend, 126
- genExtraGlobalParamAllocation
  - CodeGenerator::BackendBase, 140
  - CodeGenerator::CUDA::Backend, 112
  - CodeGenerator::SingleThreadedCPU::Backend, 126
- genExtraGlobalParamDefinition
  - CodeGenerator::BackendBase, 140
  - CodeGenerator::CUDA::Backend, 112
  - CodeGenerator::SingleThreadedCPU::Backend, 126
- genExtraGlobalParamImplementation
  - CodeGenerator::BackendBase, 141
  - CodeGenerator::CUDA::Backend, 113
  - CodeGenerator::SingleThreadedCPU::Backend, 126
- genExtraGlobalParamPull
  - CodeGenerator::BackendBase, 141
  - CodeGenerator::CUDA::Backend, 113
  - CodeGenerator::SingleThreadedCPU::Backend, 126
- genExtraGlobalParamPush
  - CodeGenerator::BackendBase, 141
  - CodeGenerator::CUDA::Backend, 113
  - CodeGenerator::SingleThreadedCPU::Backend, 127
- genGlobalRNG
  - CodeGenerator::BackendBase, 141
  - CodeGenerator::CUDA::Backend, 113
  - CodeGenerator::SingleThreadedCPU::Backend, 127
- genInit
  - CodeGenerator::BackendBase, 141
  - CodeGenerator::CUDA::Backend, 113
  - CodeGenerator::SingleThreadedCPU::Backend, 127
- genMSBuildCompileModule
  - CodeGenerator::BackendBase, 142
  - CodeGenerator::CUDA::Backend, 114
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genMSBuildConfigProperties
  - CodeGenerator::BackendBase, 142
  - CodeGenerator::CUDA::Backend, 114
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genMSBuildImportProps
  - CodeGenerator::BackendBase, 143
  - CodeGenerator::CUDA::Backend, 115
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genMSBuildImportTarget
  - CodeGenerator::BackendBase, 143
  - CodeGenerator::CUDA::Backend, 115
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genMSBuildItemDefinitions
  - CodeGenerator::BackendBase, 143
  - CodeGenerator::CUDA::Backend, 115
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genMakefileCompileRule
  - CodeGenerator::BackendBase, 142
  - CodeGenerator::CUDA::Backend, 114
  - CodeGenerator::SingleThreadedCPU::Backend, 128

- 127
- genMakefileLinkRule
  - CodeGenerator::BackendBase, 142
  - CodeGenerator::CUDA::Backend, 114
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genMakefilePreamble
  - CodeGenerator::BackendBase, 142
  - CodeGenerator::CUDA::Backend, 114
  - CodeGenerator::SingleThreadedCPU::Backend, 128
- genNeuronUpdate
  - CodeGenerator::BackendBase, 143
  - CodeGenerator::CUDA::Backend, 115
  - CodeGenerator::SingleThreadedCPU::Backend, 129
- genPopVariableInit
  - CodeGenerator::BackendBase, 144
  - CodeGenerator::CUDA::Backend, 116
  - CodeGenerator::SingleThreadedCPU::Backend, 129
- genPopulationRNG
  - CodeGenerator::BackendBase, 143
  - CodeGenerator::CUDA::Backend, 115
  - CodeGenerator::SingleThreadedCPU::Backend, 129
- genPostamble
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::Base, 159
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PostSpan, 276
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PostSpanBitmask, 279
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PreSpan, 285
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PreSpanProcedural, 287
- genPreamble
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::Base, 160
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PostSpan, 276
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PostSpanBitmask, 279
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PreSpan, 285
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PreSpanProcedural, 287
- genReturnFreeDeviceMemoryBytes
  - CodeGenerator::BackendBase, 144
  - CodeGenerator::CUDA::Backend, 116
  - CodeGenerator::SingleThreadedCPU::Backend, 130
- genRunnerPreamble
  - CodeGenerator::BackendBase, 144
  - CodeGenerator::CUDA::Backend, 116
  - CodeGenerator::SingleThreadedCPU::Backend, 130
- genScalar
  - CodeGenerator::BackendBase, 144
- genStepTimeFinalisePreamble
  - CodeGenerator::BackendBase, 144
  - CodeGenerator::CUDA::Backend, 116
  - CodeGenerator::SingleThreadedCPU::Backend, 130
- genSynapseUpdate
  - CodeGenerator::BackendBase, 145
  - CodeGenerator::CUDA::Backend, 116
  - CodeGenerator::SingleThreadedCPU::Backend, 130
- genSynapseVariableRowInit
  - CodeGenerator::BackendBase, 145
  - CodeGenerator::CUDA::Backend, 117
  - CodeGenerator::SingleThreadedCPU::Backend, 131
- genTimer
  - CodeGenerator::BackendBase, 145
  - CodeGenerator::CUDA::Backend, 117
  - CodeGenerator::SingleThreadedCPU::Backend, 131
- genUpdate
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::Base, 160
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PostSpan, 277
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PostSpanBitmask, 279
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PreSpan, 285
  - CodeGenerator::CUDA::PresynapticUpdate↔ Strategy::PreSpanProcedural, 287
- genVariableAllocation
  - CodeGenerator::BackendBase, 146
  - CodeGenerator::CUDA::Backend, 118
  - CodeGenerator::SingleThreadedCPU::Backend, 131
- genVariableDefinition
  - CodeGenerator::BackendBase, 146
  - CodeGenerator::CUDA::Backend, 118
  - CodeGenerator::SingleThreadedCPU::Backend, 131
- genVariableFree
  - CodeGenerator::BackendBase, 146
  - CodeGenerator::CUDA::Backend, 118
  - CodeGenerator::SingleThreadedCPU::Backend, 132
- genVariableImplementation
  - CodeGenerator::BackendBase, 146
  - CodeGenerator::CUDA::Backend, 118
  - CodeGenerator::SingleThreadedCPU::Backend, 132
- genVariableInit
  - CodeGenerator::BackendBase, 146
  - CodeGenerator::CUDA::Backend, 118
  - CodeGenerator::SingleThreadedCPU::Backend, 132



- genVariablePull
  - CodeGenerator::BackendBase, 147
  - CodeGenerator::CUDA::Backend, 119
  - CodeGenerator::SingleThreadedCPU::Backend, 132
- genVariablePush
  - CodeGenerator::BackendBase, 147
  - CodeGenerator::CUDA::Backend, 119
  - CodeGenerator::SingleThreadedCPU::Backend, 132
- genVariablePushPull
  - CodeGenerator::BackendBase, 147
- generateAll
  - CodeGenerator, 74
- generateAll.cc, 382
- generateAll.h, 382
- generateInit
  - CodeGenerator, 74
- generateInit.cc, 383
- generateInit.h, 383
- generateLineInfo
  - CodeGenerator::CUDA::Preferences, 281
- generateMPI.cc, 384
- generateMPI.h, 384
- generateMPI
  - CodeGenerator, 74
- generateMSBuild
  - CodeGenerator, 74
- generateMSBuild.cc, 384
- generateMSBuild.h, 384
- generateMakefile
  - CodeGenerator, 74
- generateMakefile.cc, 383
- generateMakefile.h, 383
- generateNeuronUpdate
  - CodeGenerator, 74
- generateNeuronUpdate.cc, 385
- generateNeuronUpdate.h, 385
- generateRun.h, 385
- GenerateRunBase, 207
  - buildAndRun, 207
  - GenerateRunBase, 207
  - getApp, 207
  - getExitCode, 207
  - getExperimentName, 207
  - getOutDir, 208
  - parseCommandLine, 208
  - runTools, 208
  - writeSizes, 208
- generateRunner
  - CodeGenerator, 75
- generateRunner.cc, 386
- generateRunner.h, 386
- generateSupportCode
  - CodeGenerator, 75
- generateSupportCode.cc, 386
- generateSupportCode.h, 386
- generateSynapseUpdate
  - CodeGenerator, 75
- generateSynapseUpdate.cc, 386
- generateSynapseUpdate.h, 387
- genericName
  - CodeGenerator::FunctionTemplate, 203
- genn\_groups.py, 387
- genn\_model.py, 387
- genn\_types
  - pygenn::model\_preprocessor, 96
- gennExport.h, 388
- GENN\_EXPORT, 389
- gennUtils.cc, 389
- gennUtils.h, 389
- get
  - SpineMLSimulator::StateVar, 313
  - SpineMLSimulator::Timer, 348
  - SpineMLSimulator::TimerAccumulate, 349
  - Timer, 347
  - TimerAccumulate, 348
- get\_sparse\_post\_inds
  - pygenn::genn\_groups::SynapseGroup, 324
- get\_sparse\_pre\_inds
  - pygenn::genn\_groups::SynapseGroup, 324
- get\_var\_values
  - pygenn::genn\_groups::SynapseGroup, 324
- getAdditionalInputVars
  - NeuronModels::Base, 154
- getApp
  - GenerateRunBase, 207
- getApplyInputCode
  - PostsynapticModels::Base, 158
  - PostsynapticModels::DeltaCurr, 185
  - PostsynapticModels::ExpCond, 189
  - PostsynapticModels::ExpCurr, 191
- getArray
  - SharedLibraryModel, 296
- getBackPropDelaySteps
  - SynapseGroup, 335
- getBuffer
  - SpineMLSimulator::InputValue::External, 194
- getBufferBegin
  - SpineMLSimulator::InputValue::External, 194
- getBufferEnd
  - SpineMLSimulator::InputValue::External, 194
- getCalcMaxColLengthFunc
  - InitSparseConnectivitySnippet::Base, 150
- getCalcMaxRowLengthFunc
  - InitSparseConnectivitySnippet::Base, 150
- getChosenCUDADevice
  - CodeGenerator::CUDA::Backend, 119
- getChosenDeviceID
  - CodeGenerator::CUDA::Backend, 119
- getClusterHostID
  - NeuronGroup, 255
  - SynapseGroup, 335
- getCode
  - InitVarSnippet::Base, 152
- getConnectivityInitialiser

- SynapseGroup, 335
- getCurrentQueueOffset
  - NeuronGroup, 255
- getCurrentSourceModel
  - CurrentSource, 179
- getCurrentSources
  - NeuronGroup, 255
- GetCurrentSpikeCountFunc
  - SpikeRecorder, 304
- GetCurrentSpikesFunc
  - SpikeRecorder, 305
- getDecayCode
  - PostsynapticModels::Base, 158
  - PostsynapticModels::ExpCond, 189
  - PostsynapticModels::ExpCurr, 191
- getDelaySteps
  - SynapseGroup, 335
- getDendriticDelayLocation
  - SynapseGroup, 335
- getDendriticDelayOffset
  - SynapseGroup, 335
- getDerivedParams
  - CurrentSource, 180
  - InitSparseConnectivitySnippet::FixedProbability↵  
Base, 200
  - NeuronGroup, 255
  - NeuronModels::LIF, 229
  - NeuronModels::PoissonNew, 273
  - NeuronModels::RulkovMap, 292
  - PostsynapticModels::ExpCond, 189
  - PostsynapticModels::ExpCurr, 191
  - Snippet::Base, 157
  - Snippet::Init, 221
  - WeightUpdateModels::PiecewiseSTDP, 268
- getDeviceBytes
  - CodeGenerator::MemAlloc, 231
- getDeviceMBytes
  - CodeGenerator::MemAlloc, 231
- getDeviceMemoryBytes
  - CodeGenerator::BackendBase, 147
  - CodeGenerator::CUDA::Backend, 119
  - CodeGenerator::SingleThreadedCPU::Backend,  
133
- getDT
  - ModelSpec, 241
  - SpineMLSimulator::Simulator, 301
- getDurationMs
  - SpineMLSimulator::Simulator, 301
- getEndTimestep
  - SpineMLSimulator::LogOutput::Base, 168
- getEventCode
  - WeightUpdateModels::Base, 162
  - WeightUpdateModels::StaticGraded, 315
- getEventThresholdConditionCode
  - WeightUpdateModels::Base, 162
  - WeightUpdateModels::StaticGraded, 315
- getExitCode
  - GenerateRunBase, 207
- getExperimentName
  - GenerateRunBase, 207
- getExternalInput
  - SpineMLSimulator::Simulator, 301
- getExternalLogger
  - SpineMLSimulator::Simulator, 301
- getExtraGlobalParamIndex
  - InitSparseConnectivitySnippet::Base, 151
  - Models::Base, 153
- getExtraGlobalParamLocation
  - CurrentSource, 180
  - NeuronGroup, 255
- getExtraGlobalParams
  - InitSparseConnectivitySnippet::Base, 151
  - Models::Base, 153
  - NeuronModels::Poisson, 271
  - NeuronModels::SpikeSourceArray, 309
- getFloatAtomicAdd
  - CodeGenerator::CUDA::Backend, 119
- getFreeDeviceMemBytes
  - SharedLibraryModel, 296
- getHostBytes
  - CodeGenerator::MemAlloc, 231
- getHostMBytes
  - CodeGenerator::MemAlloc, 231
- getHostStateVar
  - SpineMLSimulator::ModelProperty::Base, 169
- getInSyn
  - NeuronGroup, 256
- getInSynLocation
  - SynapseGroup, 335
- getIndices
  - SpineMLSimulator::LogOutput::AnalogueBase,  
103
- getInitSparseTime
  - SharedLibraryModel, 296
  - SpineMLSimulator::Simulator, 301
- getInitTime
  - SharedLibraryModel, 296
  - SpineMLSimulator::Simulator, 301
- getInitialisers
  - Models::VarInitContainerBase, 370
  - Models::VarInitContainerBase< 0 >, 371
- getInjectionCode
  - CurrentSourceModels::Base, 149
- getInputMs
  - SpineMLSimulator::Simulator, 302
- getInstance
  - CurrentSourceModels::DC, 183
  - CurrentSourceModels::GaussianNoise, 206
  - NeuronModels::Izhikevich, 224
  - NeuronModels::IzhikevichVariable, 227
  - NeuronModels::LIF, 229
  - NeuronModels::Poisson, 271
  - NeuronModels::PoissonNew, 273
  - NeuronModels::RulkovMap, 292
  - NeuronModels::SpikeSource, 307
  - NeuronModels::SpikeSourceArray, 309



- NeuronModels::TraubMiles, 353
- NeuronModels::TraubMilesAlt, 355
- NeuronModels::TraubMilesFast, 357
- NeuronModels::TraubMilesNStep, 359
- PostsynapticModels::DeltaCurr, 185
- PostsynapticModels::ExpCond, 189
- PostsynapticModels::ExpCurr, 191
- getKernelBlockSize
  - CodeGenerator::CUDA::Backend, 119
- getLearnPostCode
  - WeightUpdateModels::Base, 162
  - WeightUpdateModels::PiecewiseSTDP, 268
- getLearnPostSupportCode
  - WeightUpdateModels::Base, 162
- getLocalCurrentSources
  - ModelSpec, 241
- getLocalHostID
  - CodeGenerator::BackendBase, 148
- getLocalNeuronGroups
  - ModelSpec, 241
- getLocalSynapseGroups
  - ModelSpec, 241
- getLogMs
  - SpineMLSimulator::Simulator, 302
- getMatrixType
  - SynapseGroup, 335
- getMaxConnections
  - SynapseGroup, 335
- getMaxDendriticDelayTimesteps
  - SynapseGroup, 336
- getMaxSourceConnections
  - SynapseGroup, 336
- getMergedInSyn
  - NeuronGroup, 256
- getModelPropertySize
  - SpineMLSimulator::LogOutput::AnalogueBase, 103
- getNVCCFlags
  - CodeGenerator::CUDA::Backend, 120
- getName
  - CurrentSource, 180
  - ModelSpec, 241
  - NeuronGroup, 256
  - SynapseGroup, 336
- getNamedVecIndex
  - Snippet::Base, 157
- getNeuronModel
  - NeuronGroup, 256
- getNeuronUpdateTime
  - SharedLibraryModel, 296
  - SpineMLSimulator::Simulator, 302
- getNumDelaySlots
  - NeuronGroup, 256
- getNumInitialisationRNGStreams
  - CodeGenerator::CUDA::Backend, 120
- getNumLocalNeurons
  - ModelSpec, 242
- getNumNeurons
  - ModelSpec, 242
  - NeuronGroup, 256
  - SpineMLSimulator::InputValue::Base, 166
- getNumPostsynapticUpdateThreads
  - CodeGenerator::CUDA::Backend, 120
- getNumPresynapticUpdateThreads
  - CodeGenerator::CUDA::Backend, 120
- getNumRemoteNeurons
  - ModelSpec, 242
- getNumSynapseDynamicsThreads
  - CodeGenerator::CUDA::Backend, 120
- getNumThreads
  - CodeGenerator::CUDA::PresynapticUpdate↔Strategy::Base, 160
  - CodeGenerator::CUDA::PresynapticUpdate↔Strategy::PostSpan, 277
  - CodeGenerator::CUDA::PresynapticUpdate↔Strategy::PostSpanBitmask, 279
  - CodeGenerator::CUDA::PresynapticUpdate↔Strategy::PreSpan, 285
  - CodeGenerator::CUDA::PresynapticUpdate↔Strategy::PreSpanProcedural, 288
- getNumThreadsPerSpike
  - SynapseGroup, 336
- getOutDir
  - GenerateRunBase, 208
- getOutSyn
  - NeuronGroup, 256
- getPSConstInitVals
  - SynapseGroup, 336
- getPSDerivedParams
  - SynapseGroup, 336
- getPSExtraGlobalParamLocation
  - SynapseGroup, 336, 337
- getPSModel
  - SynapseGroup, 337
- getPSModelTargetName
  - SynapseGroup, 337
- getPSParams
  - SynapseGroup, 337
- getPSVarInitialisers
  - SynapseGroup, 337
- getPSVarLocation
  - SynapseGroup, 337
- getParamNames
  - CurrentSourceModels::DC, 183
  - CurrentSourceModels::GaussianNoise, 206
  - InitSparseConnectivitySnippet::FixedProbability↔Base, 201
  - InitVarSnippet::Constant, 173
  - InitVarSnippet::Exponential, 192
  - InitVarSnippet::Gamma, 204
  - InitVarSnippet::Normal, 261
  - InitVarSnippet::Uniform, 360
  - NeuronModels::Izhikevich, 225
  - NeuronModels::IzhikevichVariable, 227
  - NeuronModels::LIF, 229
  - NeuronModels::Poisson, 271

- NeuronModels::PoissonNew, 274
- NeuronModels::RulkovMap, 292
- NeuronModels::TraubMiles, 353
- NeuronModels::TraubMilesNStep, 359
- PostsynapticModels::ExpCond, 189
- PostsynapticModels::ExpCurr, 191
- Snippet::Base, 157
- WeightUpdateModels::PiecewiseSTDP, 268
- WeightUpdateModels::StaticGraded, 316
- getParams
  - CurrentSource, 180
  - NeuronGroup, 256
  - Snippet::Init, 221
- getPostSpikeCode
  - WeightUpdateModels::Base, 163
- getPostVarIndex
  - WeightUpdateModels::Base, 163
- getPostVars
  - WeightUpdateModels::Base, 163
- getPostsynapticBackPropDelaySlot
  - SynapseGroup, 336
- getPostsynapticUpdateTime
  - SharedLibraryModel, 296
  - SpineMLSimulator::Simulator, 302
- getPreSpikeCode
  - WeightUpdateModels::Base, 163
- getPreVarIndex
  - WeightUpdateModels::Base, 163
- getPreVars
  - WeightUpdateModels::Base, 163
- getPrecision
  - ModelSpec, 242
- getPresynapticAxonalDelaySlot
  - SynapseGroup, 336
- getPresynapticUpdateTime
  - SharedLibraryModel, 296
  - SpineMLSimulator::Simulator, 302
- getPrevQueueOffset
  - NeuronGroup, 256
- getRemoteCurrentSources
  - ModelSpec, 242
- getRemoteNeuronGroups
  - ModelSpec, 242
- getRemoteSynapseGroups
  - ModelSpec, 242
- getResetCode
  - NeuronModels::Base, 155
  - NeuronModels::LIF, 229
  - NeuronModels::SpikeSourceArray, 309
- getRowBuildCode
  - InitSparseConnectivitySnippet::Base, 151
  - InitSparseConnectivitySnippet::FixedProbability←  
Base, 201
- getRowBuildStateVars
  - InitSparseConnectivitySnippet::Base, 151
- getRuntimeVersion
  - CodeGenerator::CUDA::Backend, 120
- getScalar
  - SharedLibraryModel, 297
- getSeed
  - ModelSpec, 242
- getSharedMemoryPerThread
  - CodeGenerator::CUDA::PresynapticUpdate←  
Strategy::Base, 160
  - CodeGenerator::CUDA::PresynapticUpdate←  
Strategy::PostSpan, 277
  - CodeGenerator::CUDA::PresynapticUpdate←  
Strategy::PostSpanBitmask, 279
  - CodeGenerator::CUDA::PresynapticUpdate←  
Strategy::PreSpan, 286
  - CodeGenerator::CUDA::PresynapticUpdate←  
Strategy::PreSpanProcedural, 288
- getSimCode
  - NeuronModels::Base, 155
  - NeuronModels::Izhikevich, 225
  - NeuronModels::LIF, 229
  - NeuronModels::Poisson, 271
  - NeuronModels::PoissonNew, 274
  - NeuronModels::RulkovMap, 292
  - NeuronModels::SpikeSourceArray, 309
  - NeuronModels::TraubMiles, 353
  - NeuronModels::TraubMilesAlt, 356
  - NeuronModels::TraubMilesFast, 357
  - NeuronModels::TraubMilesNStep, 359
  - WeightUpdateModels::Base, 163
  - WeightUpdateModels::PiecewiseSTDP, 268
  - WeightUpdateModels::StaticPulse, 317
  - WeightUpdateModels::StaticPulseDendriticDelay,  
318
- getSimSupportCode
  - WeightUpdateModels::Base, 164
- getSimulateMs
  - SpineMLSimulator::Simulator, 302
- getSize
  - CodeGenerator::BackendBase, 148
  - SpineMLSimulator::InputValue::External, 194
  - SpineMLSimulator::ModelProperty::Base, 169
- getSnippet
  - Snippet::Init, 221
- getSpanType
  - SynapseGroup, 337
- getSparseConnectivityExtraGlobalParamLocation
  - SynapseGroup, 337
- getSparseConnectivityLocation
  - SynapseGroup, 338
- getSparseIndType
  - SynapseGroup, 338
- getSpikeEventCondition
  - NeuronGroup, 256
- getSpikeEventLocation
  - NeuronGroup, 257
- getSpikeLocation
  - NeuronGroup, 257
- getSpikeTimeLocation
  - NeuronGroup, 257
- getSrcNeuronGroup

- SynapseGroup, 338
- getStateVarBegin
  - SpineMLSimulator::LogOutput::AnalogueBase, 103
- getStateVarEnd
  - SpineMLSimulator::LogOutput::AnalogueBase, 103
- getSum
  - SpikeRecorder, 305
- getSupportCode
  - NeuronModels::Base, 155
  - PostsynapticModels::Base, 158
- getSymbol
  - SharedLibraryModel, 297
- getSynapseDynamicsCode
  - WeightUpdateModels::Base, 164
- getSynapseDynamicsSupportCode
  - WeightUpdateModels::Base, 164
- getSynapseDynamicsTime
  - SharedLibraryModel, 297
  - SpineMLSimulator::Simulator, 302
- getSynapticMatrixRowStride
  - CodeGenerator::BackendBase, 148
  - CodeGenerator::CUDA::Backend, 120
  - CodeGenerator::CUDA::PresynapticUpdate↔
    - Strategy::Base, 161
  - CodeGenerator::CUDA::PresynapticUpdate↔
    - Strategy::PostSpan, 277
  - CodeGenerator::CUDA::PresynapticUpdate↔
    - Strategy::PostSpanBitmask, 280
  - CodeGenerator::CUDA::PresynapticUpdate↔
    - Strategy::PreSpan, 286
  - CodeGenerator::CUDA::PresynapticUpdate↔
    - Strategy::PreSpanProcedural, 288
  - CodeGenerator::SingleThreadedCPU::Backend, 133
- getTargetIndices
  - SpineMLSimulator::InputValue::Base, 167
- getThresholdConditionCode
  - NeuronModels::Base, 155
  - NeuronModels::Izhikevich, 225
  - NeuronModels::LIF, 229
  - NeuronModels::Poisson, 271
  - NeuronModels::PoissonNew, 274
  - NeuronModels::RulkovMap, 292
  - NeuronModels::SpikeSource, 307
  - NeuronModels::SpikeSourceArray, 309
  - NeuronModels::TraubMiles, 354
- getTime
  - SharedLibraryModel, 297
- getTimePrecision
  - ModelSpec, 243
- getTimeToSpike
  - SpineMLSimulator::Input::InterSpikeIntervalBase, 222
  - SpineMLSimulator::Input::PoissonSpikeRate, 275
  - SpineMLSimulator::Input::RegularSpikeRate, 289
- getTimestep
- SharedLibraryModel, 297
- getTrgNeuronGroup
  - SynapseGroup, 338
- getUnderlyingType
  - Utils, 100
- getValues
  - Snippet::ValueBase, 363
  - Snippet::ValueBase< 0 >, 364
- getVarIndex
  - Models::Base, 153
- getVarInitialisers
  - CurrentSource, 180
  - NeuronGroup, 257
- getVarLocation
  - CurrentSource, 180
  - NeuronGroup, 257
- getVarPrefix
  - CodeGenerator::BackendBase, 148
  - CodeGenerator::CUDA::Backend, 120
  - CodeGenerator::SingleThreadedCPU::Backend, 133
- getVarSubstitution
  - CodeGenerator::Substitutions, 321
- getVars
  - Models::Base, 153
  - NeuronModels::Izhikevich, 225
  - NeuronModels::IzhikevichVariable, 227
  - NeuronModels::LIF, 230
  - NeuronModels::Poisson, 271
  - NeuronModels::PoissonNew, 274
  - NeuronModels::RulkovMap, 292
  - NeuronModels::SpikeSourceArray, 310
  - NeuronModels::TraubMiles, 354
  - WeightUpdateModels::PiecewiseSTDP, 268
  - WeightUpdateModels::StaticGraded, 316
  - WeightUpdateModels::StaticPulse, 317
  - WeightUpdateModels::StaticPulseDendriticDelay, 319
- getWUConstInitVals
  - SynapseGroup, 338
- getWUDerivedParams
  - SynapseGroup, 338
- getWUExtraGlobalParamLocation
  - SynapseGroup, 338, 339
- getWUModel
  - SynapseGroup, 339
- getWUParams
  - SynapseGroup, 339
- getWUPostVarInitialisers
  - SynapseGroup, 339
- getWUPostVarLocation
  - SynapseGroup, 339
- getWUPreVarInitialisers
  - SynapseGroup, 339
- getWUPreVarLocation
  - SynapseGroup, 339
- getWUVarInitialisers
  - SynapseGroup, 340

- getWUVarLocation
  - SynapseGroup, 340
- getZeroCopyBytes
  - CodeGenerator::MemAlloc, 231
- getZeroCopyMBytes
  - CodeGenerator::MemAlloc, 231
- GroupHandler
  - CodeGenerator::BackendBase, 137
- Handler
  - CodeGenerator::BackendBase, 137
- has\_individual\_postsynaptic\_vars
  - pygenn::genn\_groups::SynapseGroup, 324
- has\_individual\_synapse\_vars
  - pygenn::genn\_groups::SynapseGroup, 324
- hasOutputToHost
  - NeuronGroup, 257
- hasVarSubstitution
  - CodeGenerator::Substitutions, 321
- host
  - CodeGenerator::MemAlloc, 231
- IMPLEMENT\_MODEL
  - currentSourceModels.cc, 381
  - models.h, 401
  - neuronModels.cc, 408, 409
  - postsynapticModels.cc, 413
  - weightUpdateModels.cc, 425
- IMPLEMENT\_SNIPPET
  - initSparseConnectivitySnippet.cc, 390
  - initVarSnippet.cc, 392, 393
  - snippet.h, 418
- ind
  - pygenn::genn\_groups::SynapseGroup, 330
- Init
  - InitSparseConnectivitySnippet::Init, 220
  - Snippet::Init, 221
- init
  - Logging, 83
- init\_connectivity
  - pygenn::genn\_model, 92
- init\_required
  - pygenn::model\_preprocessor::Variable, 368
- init\_sparse\_time
  - pygenn::genn\_model::GeNNModel, 213
- init\_time
  - pygenn::genn\_model::GeNNModel, 214
- init\_val
  - pygenn::model\_preprocessor::Variable, 368
- init\_var
  - pygenn::genn\_model, 92
- initConnectivity
  - modelSpec.h, 404, 405
- initDerivedParams
  - CurrentSource, 180
  - NeuronGroup, 257
  - Snippet::Init, 221
  - SynapseGroup, 340
- InitSparseConnectivitySnippet, 81
  - initSparseConnectivitySnippet.cc, 390
  - IMPLEMENT\_SNIPPET, 390
  - initSparseConnectivitySnippet.h, 390
  - SET\_CALC\_MAX\_COL\_LENGTH\_FUNC, 391
  - SET\_CALC\_MAX\_ROW\_LENGTH\_FUNC, 391
  - SET\_EXTRA\_GLOBAL\_PARAMS, 391
  - SET\_MAX\_COL\_LENGTH, 391
  - SET\_MAX\_ROW\_LENGTH, 392
  - SET\_ROW\_BUILD\_CODE, 392
  - SET\_ROW\_BUILD\_STATE\_VARS, 392
  - InitSparseConnectivitySnippet::Base, 150
  - CalcMaxLengthFunc, 150
  - getCalcMaxColLengthFunc, 150
  - getCalcMaxRowLengthFunc, 150
  - getExtraGlobalParamIndex, 151
  - getExtraGlobalParams, 151
  - getRowBuildCode, 151
  - getRowBuildStateVars, 151
  - InitSparseConnectivitySnippet::FixedProbability, 199
  - DECLARE\_SNIPPET, 199
  - SET\_ROW\_BUILD\_CODE, 199
  - InitSparseConnectivitySnippet::FixedProbabilityBase, 200
  - getDerivedParams, 200
  - getParamNames, 201
  - getRowBuildCode, 201
  - SET\_CALC\_MAX\_COL\_LENGTH\_FUNC, 201
  - SET\_CALC\_MAX\_ROW\_LENGTH\_FUNC, 201
  - SET\_ROW\_BUILD\_STATE\_VARS, 201
  - InitSparseConnectivitySnippet::FixedProbabilityNoAutapse, 201
  - DECLARE\_SNIPPET, 202
  - SET\_ROW\_BUILD\_CODE, 202
  - InitSparseConnectivitySnippet::Init, 220
  - Init, 220
  - InitSparseConnectivitySnippet::OneToOne, 263
  - DECLARE\_SNIPPET, 264
  - SET\_MAX\_COL\_LENGTH, 264
  - SET\_MAX\_ROW\_LENGTH, 264
  - SET\_ROW\_BUILD\_CODE, 264
  - InitSparseConnectivitySnippet::Uninitialised, 362
  - DECLARE\_SNIPPET, 363
  - initVar
    - modelSpec.h, 405
  - InitVarSnippet, 82
  - initVarSnippet.cc, 392
  - IMPLEMENT\_SNIPPET, 392, 393
  - initVarSnippet.h, 393
  - SET\_CODE, 394
  - InitVarSnippet::Base, 151
  - getCode, 152
  - InitVarSnippet::Constant, 172
  - DECLARE\_SNIPPET, 172
  - getParamNames, 173
  - SET\_CODE, 173
  - InitVarSnippet::Exponential, 192
  - DECLARE\_SNIPPET, 192
  - getParamNames, 192

- SET\_CODE, [192](#)
- InitVarSnippet::Gamma, [204](#)
  - DECLARE\_SNIPPET, [204](#)
  - getParamNames, [204](#)
  - SET\_CODE, [205](#)
- InitVarSnippet::Normal, [261](#)
  - DECLARE\_SNIPPET, [261](#)
  - getParamNames, [261](#)
  - SET\_CODE, [262](#)
- InitVarSnippet::Uniform, [359](#)
  - DECLARE\_SNIPPET, [360](#)
  - getParamNames, [360](#)
  - SET\_CODE, [360](#)
- InitVarSnippet::Uninitialised, [361](#)
  - DECLARE\_SNIPPET, [362](#)
- initialize
  - SharedLibraryModel, [297](#)
- initializeSparse
  - SharedLibraryModel, [297](#)
- injectCurrent
  - NeuronGroup, [258](#)
- injectSpike
  - SpineMLSimulator::Input::SpikeBase, [304](#)
- input.cc, [394](#)
- input.h, [394](#)
- inputValue.cc, [394](#)
- inputValue.h, [395](#)
- InterSpikeIntervalBase
  - SpineMLSimulator::Input::InterSpikeIntervalBase, [222](#)
- is\_bitmask
  - pygenn::genn\_groups::SynapseGroup, [325](#)
- is\_connectivity\_init\_required
  - pygenn::genn\_groups::SynapseGroup, [325](#)
- is\_dense
  - pygenn::genn\_groups::SynapseGroup, [325](#)
- is\_model\_valid
  - pygenn::model\_preprocessor, [93](#)
- is\_ragged
  - pygenn::genn\_groups::SynapseGroup, [325](#)
- is\_scalar
  - pygenn::model\_preprocessor::ExtraGlobal↔  
Variable, [197](#)
- is\_spike\_source\_array
  - pygenn::genn\_groups::NeuronGroup, [251](#)
- isAccessible
  - SpineMLSimulator::StateVar, [313](#)
- isAutoRefractoryRequired
  - NeuronModels::Base, [155](#)
- isAutomaticCopyEnabled
  - CodeGenerator::BackendBase, [148](#)
  - CodeGenerator::CUDA::Backend, [121](#)
  - CodeGenerator::SingleThreadedCPU::Backend, [133](#)
- isCompatible
  - CodeGenerator::CUDA::PresynapticUpdate↔  
Strategy::Base, [161](#)
- CodeGenerator::CUDA::PresynapticUpdate↔  
Strategy::PostSpan, [278](#)
- CodeGenerator::CUDA::PresynapticUpdate↔  
Strategy::PostSpanBitmask, [280](#)
- CodeGenerator::CUDA::PresynapticUpdate↔  
Strategy::PreSpan, [286](#)
- CodeGenerator::CUDA::PresynapticUpdate↔  
Strategy::PreSpanProcedural, [288](#)
- isDelayRequired
  - NeuronGroup, [258](#)
- isDendriticDelayRequired
  - SynapseGroup, [340](#)
- isEventThresholdReTestRequired
  - SynapseGroup, [340](#)
- isGlobalRNGRequired
  - CodeGenerator::BackendBase, [148](#)
  - CodeGenerator::CUDA::Backend, [121](#)
  - CodeGenerator::SingleThreadedCPU::Backend, [133](#)
- isInitRNGRequired
  - CurrentSource, [181](#)
  - NeuronGroup, [258](#)
- isPSInitRNGRequired
  - SynapseGroup, [340](#)
- isPSModelMerged
  - SynapseGroup, [340](#)
- isParamRequiredBySpikeEventCondition
  - NeuronGroup, [258](#)
- isPostSpikeTimeRequired
  - WeightUpdateModels::Base, [164](#)
  - WeightUpdateModels::PiecewiseSTDP, [268](#)
- isPostsynapticRemapRequired
  - CodeGenerator::BackendBase, [148](#)
  - CodeGenerator::CUDA::Backend, [121](#)
  - CodeGenerator::SingleThreadedCPU::Backend, [134](#)
- isPreSpikeTimeRequired
  - WeightUpdateModels::Base, [164](#)
  - WeightUpdateModels::PiecewiseSTDP, [269](#)
- isProceduralConnectivityRNGRequired
  - SynapseGroup, [340](#)
- isRNGRequired
  - Utils, [100](#)
- isSimRNGRequired
  - CurrentSource, [181](#)
  - NeuronGroup, [258](#)
- isSparseConnectivityInitRequired
  - SynapseGroup, [341](#)
- isSpikeEventRequired
  - NeuronGroup, [258](#)
  - SynapseGroup, [341](#)
- isSpikeTimeRequired
  - NeuronGroup, [258](#)
- isSynRemapRequired
  - CodeGenerator::BackendBase, [149](#)
  - CodeGenerator::CUDA::Backend, [121](#)
  - CodeGenerator::SingleThreadedCPU::Backend, [134](#)

- isTimingEnabled
  - ModelSpec, [243](#)
- isTrueSpikeRequired
  - NeuronGroup, [258](#)
  - SynapseGroup, [341](#)
- isTypePointer
  - Utils, [101](#)
- isVarQueueRequired
  - NeuronGroup, [258](#)
- isWUInitRNGRequired
  - SynapseGroup, [341](#)
- isWUVarInitRequired
  - SynapseGroup, [341](#)
- isZeroCopyEnabled
  - NeuronGroup, [259](#)
  - SynapseGroup, [341](#)
- Kernel
  - CodeGenerator::CUDA, [79](#)
- KernelBlockSize
  - CodeGenerator::CUDA, [79](#)
- KernelNames
  - CodeGenerator::CUDA::Backend, [121](#)
- LOGD\_BACKEND
  - logging.h, [396](#)
- LOGD\_CODE\_GEN
  - logging.h, [396](#)
- LOGD\_GENN
  - logging.h, [396](#)
- LOGE\_BACKEND
  - logging.h, [396](#)
- LOGE\_CODE\_GEN
  - logging.h, [397](#)
- LOGE\_GENN
  - logging.h, [397](#)
- LOGF\_BACKEND
  - logging.h, [397](#)
- LOGF\_CODE\_GEN
  - logging.h, [397](#)
- LOGF\_GENN
  - logging.h, [397](#)
- LOGI\_BACKEND
  - logging.h, [397](#)
- LOGI\_CODE\_GEN
  - logging.h, [397](#)
- LOGI\_GENN
  - logging.h, [397](#)
- LOGV\_BACKEND
  - logging.h, [397](#)
- LOGV\_CODE\_GEN
  - logging.h, [397](#)
- LOGV\_GENN
  - logging.h, [397](#)
- LOGW\_BACKEND
  - logging.h, [398](#)
- LOGW\_CODE\_GEN
  - logging.h, [398](#)
- LOGW\_GENN
  - logging.h, [398](#)
- logging.h, [398](#)
- Level
  - CodeGenerator::CodeStream::CB, [170](#)
  - CodeGenerator::CodeStream::OB, [263](#)
- load
  - pygenn::genn\_groups::CurrentSource, [176](#)
  - pygenn::genn\_groups::NeuronGroup, [250](#)
  - pygenn::genn\_groups::SynapseGroup, [325](#)
  - pygenn::genn\_model::GeNNModel, [214](#)
  - SpineMLSimulator::Simulator, [302](#)
- load\_connectivity\_init\_egps
  - pygenn::genn\_groups::SynapseGroup, [325](#)
- logLevel
  - CodeGenerator::PreferencesBase, [283](#)
- logOutput.cc, [398](#)
- logOutput.h, [398](#)
- logWriter.h, [399](#)
- Logging, [82](#)
  - Channel, [82](#)
  - init, [83](#)
- logging.cc, [395](#)
- logging.h, [395](#)
  - LOGD\_BACKEND, [396](#)
  - LOGD\_CODE\_GEN, [396](#)
  - LOGD\_GENN, [396](#)
  - LOGE\_BACKEND, [396](#)
  - LOGE\_CODE\_GEN, [397](#)
  - LOGE\_GENN, [397](#)
  - LOGF\_BACKEND, [397](#)
  - LOGF\_CODE\_GEN, [397](#)
  - LOGF\_GENN, [397](#)
  - LOGI\_BACKEND, [397](#)
  - LOGI\_CODE\_GEN, [397](#)
  - LOGI\_GENN, [397](#)
  - LOGV\_BACKEND, [397](#)
  - LOGV\_CODE\_GEN, [397](#)
  - LOGV\_GENN, [397](#)
  - LOGW\_BACKEND, [398](#)
  - LOGW\_CODE\_GEN, [398](#)
  - LOGW\_GENN, [398](#)
- m
  - pygenn::genn\_model, [92](#)
- m\_Direct
  - SpineMLSimulator::StateVar, [314](#)
- m\_Indirect
  - SpineMLSimulator::StateVar, [314](#)
- manualBlockSizes
  - CodeGenerator::CUDA::Preferences, [281](#)
- manualDeviceID
  - CodeGenerator::CUDA::Preferences, [282](#)
- MathsFunc
  - codeGenUtils.cc, [377](#)
- matrix\_type
  - pygenn::genn\_groups::SynapseGroup, [325](#), [326](#)
- max\_row\_length
  - pygenn::genn\_groups::SynapseGroup, [326](#)
- mergeIncomingPSM
  - NeuronGroup, [259](#)



- Mode
  - SpineMLSimulator::NetworkClient, 247
- model\_name
  - pygenn::genn\_model::GeNNModel, 214, 218
- model\_preprocessor.py, 399
- modelProperty.cc, 400
- modelProperty.h, 400
- ModelSpec, 232
  - ~ModelSpec, 235
  - addCurrentSource, 235, 236
  - addNeuronPopulation, 236, 237
  - addSynapsePopulation, 237–239
  - finalize, 240
  - findCurrentSource, 241
  - findNeuronGroup, 241
  - findSynapseGroup, 241
  - getDT, 241
  - getLocalCurrentSources, 241
  - getLocalNeuronGroups, 241
  - getLocalSynapseGroups, 241
  - getName, 241
  - getNumLocalNeurons, 242
  - getNumNeurons, 242
  - getNumRemoteNeurons, 242
  - getPrecision, 242
  - getRemoteCurrentSources, 242
  - getRemoteNeuronGroups, 242
  - getRemoteSynapseGroups, 242
  - getSeed, 242
  - getTimePrecision, 243
  - isTimingEnabled, 243
  - ModelSpec, 235
  - NeuronGroupValueType, 234
  - operator=, 243
  - scalarExpr, 243
  - setDefaultExtraGlobalParamLocation, 243
  - setDefaultNarrowSparseIndEnabled, 243
  - setDefaultSparseConnectivityLocation, 243
  - setDefaultVarLocation, 243
  - setDT, 244
  - setMergePostsynapticModels, 244
  - setName, 244
  - setPrecision, 244
  - setSeed, 244
  - setTimePrecision, 244
  - setTiming, 244
  - SynapseGroupValueType, 235
  - zeroCopyInUse, 244
- modelSpec.cc, 402
- modelSpec.h, 402
  - FloatType, 404
  - initConnectivity, 404, 405
  - initVar, 405
  - NNmodel, 404
  - NO\_DELAY, 403
  - TimePrecision, 404
  - uninitialisedConnectivity, 406
  - uninitialisedVar, 406
- ModelSpecInternal, 245
- modelSpecInternal.h, 406
- Models, 83
- models.h, 400
  - DECLARE\_MODEL, 401
  - IMPLEMENT\_MODEL, 401
  - SET\_EXTRA\_GLOBAL\_PARAMS, 401
  - SET\_VARS, 402
  - VarAccess, 402
- Models::Base, 152
  - getExtraGlobalParamIndex, 153
  - getExtraGlobalParams, 153
  - getVarIndex, 153
  - getVars, 153
  - VarVec, 153
- Models::Base::Var, 365
  - access, 366
  - name, 366
  - type, 366
  - Var, 366
- Models::VarInit, 369
  - VarInit, 369
- Models::VarInitContainerBase
  - getInitialisers, 370
  - operator[], 370
  - VarInitContainerBase, 370
- Models::VarInitContainerBase< 0 >, 370
  - getInitialisers, 371
  - VarInitContainerBase, 371
- Models::VarInitContainerBase< NumVars >, 369
- NNmodel
  - modelSpec.h, 404
- NO\_DELAY
  - modelSpec.h, 403
- name
  - Models::Base::Var, 366
  - pygenn::genn\_groups::Group, 219
  - pygenn::model\_preprocessor::ExtraGlobalVariable, 197
  - pygenn::model\_preprocessor::Variable, 368
  - Snippet::Base::DerivedParam, 186
  - Snippet::Base::EGP, 186
  - Snippet::Base::ParamVal, 265
- needs\_allocation
  - pygenn::model\_preprocessor::Variable, 368
- NetworkClient
  - SpineMLSimulator::NetworkClient, 247
- networkClient.cc, 406
- networkClient.h, 406
- neuron
  - pygenn::genn\_groups::NeuronGroup, 251
- neuron\_populations
  - pygenn::genn\_model::GeNNModel, 218
- neuron\_update\_time
  - pygenn::genn\_model::GeNNModel, 214
- NeuronGroup, 252
  - addInSyn, 254
  - addOutSyn, 254

- addSpkEventCondition, 255
- checkNumDelaySlots, 255
- getClusterHostID, 255
- getCurrentQueueOffset, 255
- getCurrentSources, 255
- getDerivedParams, 255
- getExtraGlobalParamLocation, 255
- getInSyn, 256
- getMergedInSyn, 256
- getName, 256
- getNeuronModel, 256
- getNumDelaySlots, 256
- getNumNeurons, 256
- getOutSyn, 256
- getParams, 256
- getPrevQueueOffset, 256
- getSpikeEventCondition, 256
- getSpikeEventLocation, 257
- getSpikeLocation, 257
- getSpikeTimeLocation, 257
- getVarInitialisers, 257
- getVarLocation, 257
- hasOutputToHost, 257
- initDerivedParams, 257
- injectCurrent, 258
- isDelayRequired, 258
- isInitRNGRequired, 258
- isParamRequiredBySpikeEventCondition, 258
- isSimRNGRequired, 258
- isSpikeEventRequired, 258
- isSpikeTimeRequired, 258
- isTrueSpikeRequired, 258
- isVarQueueRequired, 258
- isZeroCopyEnabled, 259
- mergeIncomingPSM, 259
- NeuronGroup, 254
  - setExtraGlobalParamLocation, 259
  - setSpikeEventLocation, 259
  - setSpikeLocation, 259
  - setSpikeTimeLocation, 259
  - setVarLocation, 259
  - updatePostVarQueues, 260
  - updatePreVarQueues, 260
- neuronGroup.cc, 407
- neuronGroup.h, 407
- NeuronGroupHandler
  - CodeGenerator::BackendBase, 137
- NeuronGroupInternal, 260
  - NeuronGroupInternal, 260
- neuronGroupInternal.h, 407
- NeuronGroupSimHandler
  - CodeGenerator::BackendBase, 137
- NeuronGroupValueType
  - ModelSpec, 234
- NeuronModels, 83
- neuronModels.cc, 407
  - IMPLEMENT\_MODEL, 408, 409
- neuronModels.h, 409
  - SET\_ADDITIONAL\_INPUT\_VARS, 410
  - SET\_NEEDS\_AUTO\_REFRACTORY, 410
  - SET\_RESET\_CODE, 410
  - SET\_SIM\_CODE, 411
  - SET\_SUPPORT\_CODE, 411
  - SET\_THRESHOLD\_CONDITION\_CODE, 411
- NeuronModels::Base, 153
  - getAdditionalInputVars, 154
  - getResetCode, 155
  - getSimCode, 155
  - getSupportCode, 155
  - getThresholdConditionCode, 155
  - isAutoRefractoryRequired, 155
- NeuronModels::Izhikevich, 223
  - getInstance, 224
  - getParamNames, 225
  - getSimCode, 225
  - getThresholdConditionCode, 225
  - getVar, 225
  - ParamValues, 224
  - PostVarValues, 224
  - PreVarValues, 224
  - VarValues, 224
- NeuronModels::IzhikevichVariable, 225
  - getInstance, 227
  - getParamNames, 227
  - getVar, 227
  - ParamValues, 227
  - PostVarValues, 227
  - PreVarValues, 227
  - VarValues, 227
- NeuronModels::LIF, 227
  - getDerivedParams, 229
  - getInstance, 229
  - getParamNames, 229
  - getResetCode, 229
  - getSimCode, 229
  - getThresholdConditionCode, 229
  - getVar, 230
  - ParamValues, 228
  - PostVarValues, 228
  - PreVarValues, 228
  - SET\_NEEDS\_AUTO\_REFRACTORY, 230
  - VarValues, 229
- NeuronModels::Poisson, 269
  - getExtraGlobalParams, 271
  - getInstance, 271
  - getParamNames, 271
  - getSimCode, 271
  - getThresholdConditionCode, 271
  - getVar, 271
  - ParamValues, 270
  - PostVarValues, 270
  - PreVarValues, 270
  - VarValues, 271
- NeuronModels::PoissonNew, 272
  - getDerivedParams, 273
  - getInstance, 273



- getParamNames, [274](#)
- getSimCode, [274](#)
- getThresholdConditionCode, [274](#)
- getVars, [274](#)
- ParamValues, [273](#)
- PostVarValues, [273](#)
- PreVarValues, [273](#)
- SET\_NEEDS\_AUTO\_REFRACTORY, [274](#)
- VarValues, [273](#)
- NeuronModels::RulkovMap, [290](#)
  - getDerivedParams, [292](#)
  - getInstance, [292](#)
  - getParamNames, [292](#)
  - getSimCode, [292](#)
  - getThresholdConditionCode, [292](#)
  - getVars, [292](#)
  - ParamValues, [291](#)
  - PostVarValues, [291](#)
  - PreVarValues, [291](#)
  - VarValues, [291](#)
- NeuronModels::SpikeSource, [305](#)
  - getInstance, [307](#)
  - getThresholdConditionCode, [307](#)
  - ParamValues, [306](#)
  - PostVarValues, [306](#)
  - PreVarValues, [306](#)
  - SET\_NEEDS\_AUTO\_REFRACTORY, [307](#)
  - VarValues, [307](#)
- NeuronModels::SpikeSourceArray, [307](#)
  - getExtraGlobalParams, [309](#)
  - getInstance, [309](#)
  - getResetCode, [309](#)
  - getSimCode, [309](#)
  - getThresholdConditionCode, [309](#)
  - getVars, [310](#)
  - ParamValues, [308](#)
  - PostVarValues, [308](#)
  - PreVarValues, [308](#)
  - SET\_NEEDS\_AUTO\_REFRACTORY, [310](#)
  - VarValues, [309](#)
- NeuronModels::TraubMiles, [351](#)
  - getInstance, [353](#)
  - getParamNames, [353](#)
  - getSimCode, [353](#)
  - getThresholdConditionCode, [354](#)
  - getVars, [354](#)
  - ParamValues, [353](#)
  - PostVarValues, [353](#)
  - PreVarValues, [353](#)
  - VarValues, [353](#)
- NeuronModels::TraubMilesAlt, [354](#)
  - getInstance, [355](#)
  - getSimCode, [356](#)
  - ParamValues, [355](#)
  - PostVarValues, [355](#)
  - PreVarValues, [355](#)
  - VarValues, [355](#)
- NeuronModels::TraubMilesFast, [356](#)
  - getInstance, [357](#)
  - getSimCode, [357](#)
  - ParamValues, [357](#)
  - PostVarValues, [357](#)
  - PreVarValues, [357](#)
  - VarValues, [357](#)
- NeuronModels::TraubMilesNStep, [358](#)
  - getInstance, [359](#)
  - getParamNames, [359](#)
  - getSimCode, [359](#)
  - ParamValues, [358](#)
  - PostVarValues, [358](#)
  - PreVarValues, [359](#)
  - VarValues, [359](#)
- neuronSubstitutionsInSynapticCode
  - CodeGenerator, [75](#)
- NormalDistribution
  - SpineMLSimulator::ModelProperty::Normal↔  
Distribution, [262](#)
- num\_synapses
  - pygenn::genn\_groups::SynapseGroup, [326](#)
- numArguments
  - CodeGenerator::FunctionTemplate, [203](#)
- OB
  - CodeGenerator::CodeStream::OB, [263](#)
- open
  - SharedLibraryModel, [297](#)
- operator<<
  - CodeGenerator, [76](#)
  - CodeGenerator::CodeStream, [171](#)
- operator+=
  - CodeGenerator::MemAlloc, [231](#)
- operator=
  - CodeGenerator::FunctionTemplate, [203](#)
  - ModelSpec, [243](#)
- operator&
  - synapseMatrixType.h, [421](#), [422](#)
  - variableMode.h, [424](#)
- operator[]
  - CodeGenerator::Substitutions, [321](#)
  - Models::VarInitContainerBase, [370](#)
  - Snippet::ValueBase, [363](#)
- operator |
  - synapseMatrixType.h, [422](#)
- optimiser.cc, [411](#), [412](#)
- optimiser.h, [412](#)
- optimizeCode
  - CodeGenerator::PreferencesBase, [283](#)
- padSize
  - CodeGenerator, [76](#)
- param\_space\_to\_val\_vec
  - pygenn::model\_preprocessor, [94](#)
- param\_space\_to\_vals
  - pygenn::model\_preprocessor, [94](#)
- ParamValVec
  - Snippet::Base, [157](#)
- ParamValues

- CurrentSourceModels::DC, 183
- CurrentSourceModels::GaussianNoise, 206
- NeuronModels::Izhikevich, 224
- NeuronModels::IzhikevichVariable, 227
- NeuronModels::LIF, 228
- NeuronModels::Poisson, 270
- NeuronModels::PoissonNew, 273
- NeuronModels::RulkovMap, 291
- NeuronModels::SpikeSource, 306
- NeuronModels::SpikeSourceArray, 308
- NeuronModels::TraubMiles, 353
- NeuronModels::TraubMilesAlt, 355
- NeuronModels::TraubMilesFast, 357
- NeuronModels::TraubMilesNStep, 358
- PostsynapticModels::DeltaCurr, 184
- PostsynapticModels::ExpCond, 188
- PostsynapticModels::ExpCurr, 190
- parseCommandLine
  - GenerateRunBase, 208
- plog, 84
- PoissonSpikeRate
  - SpineMLSimulator::Input::PoissonSpikeRate, 275
- pop
  - pygenn::genn\_groups::CurrentSource, 178
  - pygenn::genn\_groups::NeuronGroup, 251
  - pygenn::genn\_groups::SynapseGroup, 330
- post\_var\_space\_to\_vals
  - pygenn::model\_preprocessor, 94
- post\_vars
  - pygenn::genn\_groups::SynapseGroup, 330
- postNeuronSubstitutionsInSynapticCode
  - CodeGenerator, 76
- PostVarValues
  - CurrentSourceModels::DC, 183
  - CurrentSourceModels::GaussianNoise, 206
  - NeuronModels::Izhikevich, 224
  - NeuronModels::IzhikevichVariable, 227
  - NeuronModels::LIF, 228
  - NeuronModels::Poisson, 270
  - NeuronModels::PoissonNew, 273
  - NeuronModels::RulkovMap, 291
  - NeuronModels::SpikeSource, 306
  - NeuronModels::SpikeSourceArray, 308
  - NeuronModels::TraubMiles, 353
  - NeuronModels::TraubMilesAlt, 355
  - NeuronModels::TraubMilesFast, 357
  - NeuronModels::TraubMilesNStep, 358
  - PostsynapticModels::DeltaCurr, 185
  - PostsynapticModels::ExpCond, 188
  - PostsynapticModels::ExpCurr, 190
- postsyn
  - pygenn::genn\_groups::SynapseGroup, 330
- postsynaptic\_update\_time
  - pygenn::genn\_model::GeNNModel, 214
- PostsynapticModels, 84
- postsynapticModels.cc, 413
  - IMPLEMENT\_MODEL, 413
- postsynapticModels.h, 413
  - SET\_APPLY\_INPUT\_CODE, 414
  - SET\_CURRENT\_CONVERTER\_CODE, 414
  - SET\_DECAY\_CODE, 414
  - SET\_SUPPORT\_CODE, 414
- PostsynapticModels::Base, 158
  - getApplyInputCode, 158
  - getDecayCode, 158
  - getSupportCode, 158
- PostsynapticModels::DeltaCurr, 184
  - getApplyInputCode, 185
  - getInstance, 185
  - ParamValues, 184
  - PostVarValues, 185
  - PreVarValues, 185
  - VarValues, 185
- PostsynapticModels::ExpCond, 187
  - getApplyInputCode, 189
  - getDecayCode, 189
  - getDerivedParams, 189
  - getInstance, 189
  - getParamNames, 189
  - ParamValues, 188
  - PostVarValues, 188
  - PreVarValues, 189
  - VarValues, 189
- PostsynapticModels::ExpCurr, 190
  - getApplyInputCode, 191
  - getDecayCode, 191
  - getDerivedParams, 191
  - getInstance, 191
  - getParamNames, 191
  - ParamValues, 190
  - PostVarValues, 190
  - PreVarValues, 191
  - VarValues, 191
- pre\_var\_space\_to\_vals
  - pygenn::model\_preprocessor, 95
- pre\_vars
  - pygenn::genn\_groups::SynapseGroup, 330
- preNeuronSubstitutionsInSynapticCode
  - CodeGenerator, 77
- PreVarValues
  - CurrentSourceModels::DC, 183
  - CurrentSourceModels::GaussianNoise, 206
  - NeuronModels::Izhikevich, 224
  - NeuronModels::IzhikevichVariable, 227
  - NeuronModels::LIF, 228
  - NeuronModels::Poisson, 270
  - NeuronModels::PoissonNew, 273
  - NeuronModels::RulkovMap, 291
  - NeuronModels::SpikeSource, 306
  - NeuronModels::SpikeSourceArray, 308
  - NeuronModels::TraubMiles, 353
  - NeuronModels::TraubMilesAlt, 355
  - NeuronModels::TraubMilesFast, 357
  - NeuronModels::TraubMilesNStep, 359
  - PostsynapticModels::DeltaCurr, 185
  - PostsynapticModels::ExpCond, 189

- PostsynapticModels::ExpCurr, [191](#)
- Preferences
  - CodeGenerator::CUDA::Preferences, [281](#)
- prepare\_model
  - pygenn::model\_preprocessor, [95](#)
- prepare\_snippet
  - pygenn::model\_preprocessor, [95](#)
- presynaptic\_update\_time
  - pygenn::genn\_model::GeNNModel, [214](#)
- presynapticUpdateStrategy.cc, [414](#)
- presynapticUpdateStrategy.h, [415](#)
- psm\_extra\_global\_params
  - pygenn::genn\_groups::SynapseGroup, [330](#)
- psm\_vars
  - pygenn::genn\_groups::SynapseGroup, [330](#)
- pugi, [84](#)
- pull
  - SpineMLSimulator::StateVar, [313](#)
- pull\_connectivity\_from\_device
  - pygenn::genn\_model::GeNNModel, [214](#)
- pull\_current\_spikes\_from\_device
  - pygenn::genn\_model::GeNNModel, [214](#)
- pull\_spikes\_from\_device
  - pygenn::genn\_model::GeNNModel, [215](#)
- pull\_state\_from\_device
  - pygenn::genn\_model::GeNNModel, [215](#)
- pull\_var\_from\_device
  - pygenn::genn\_model::GeNNModel, [215](#)
- pullConnectivityFromDevice
  - SharedLibraryModel, [298](#)
- pullCurrentSpikesFromDevice
  - SharedLibraryModel, [298](#)
- pullExtraGlobalParam
  - SharedLibraryModel, [298](#)
- pullFromDevice
  - SpineMLSimulator::ModelProperty::Base, [169](#)
- pullModelPropertyFromDevice
  - SpineMLSimulator::LogOutput::AnalogueBase, [103](#)
- pullSpikesFromDevice
  - SharedLibraryModel, [298](#)
- pullStateFromDevice
  - SharedLibraryModel, [298](#)
- pullVarFromDevice
  - SharedLibraryModel, [298](#)
- push
  - SpineMLSimulator::StateVar, [314](#)
- push\_connectivity\_to\_device
  - pygenn::genn\_model::GeNNModel, [215](#)
- push\_current\_spikes\_to\_device
  - pygenn::genn\_model::GeNNModel, [215](#)
- push\_spikes\_to\_device
  - pygenn::genn\_model::GeNNModel, [215](#)
- push\_state\_to\_device
  - pygenn::genn\_model::GeNNModel, [216](#)
- push\_var\_to\_device
  - pygenn::genn\_model::GeNNModel, [216](#)
- pushConnectivityToDevice
  - SharedLibraryModel, [298](#)
- PushCurrentSpikesFunc
  - SpineMLSimulator::Input::SpikeBase, [303](#)
- pushCurrentSpikesToDevice
  - SharedLibraryModel, [298](#)
- pushExtraGlobalParam
  - SharedLibraryModel, [299](#)
- pushSpikesToDevice
  - SharedLibraryModel, [299](#)
- pushStateToDevice
  - SharedLibraryModel, [299](#)
- pushToDevice
  - SpineMLSimulator::ModelProperty::Base, [169](#)
- pushVarToDevice
  - SharedLibraryModel, [299](#)
- pygenn, [84](#)
- pygenn.genn\_groups, [84](#)
- pygenn.genn\_groups.CurrentSource, [175](#)
- pygenn.genn\_groups.Group, [218](#)
- pygenn.genn\_groups.NeuronGroup, [248](#)
- pygenn.genn\_groups.SynapseGroup, [321](#)
- pygenn.genn\_model, [85](#)
- pygenn.genn\_model.GeNNModel, [208](#)
- pygenn.model\_preprocessor, [92](#)
- pygenn.model\_preprocessor.ExtraGlobalVariable, [196](#)
- pygenn.model\_preprocessor.Variable, [367](#)
- pygenn::genn\_groups
  - xrange, [85](#)
- pygenn::genn\_groups::CurrentSource
  - \_\_init\_\_, [176](#)
  - add\_extra\_global\_param, [176](#)
  - add\_to, [176](#)
  - current\_source\_model, [178](#)
  - load, [176](#)
  - pop, [178](#)
  - reinitialise, [177](#)
  - set\_current\_source\_model, [177](#)
  - set\_extra\_global\_param, [177](#)
  - size, [177](#), [178](#)
  - target\_pop, [178](#)
- pygenn::genn\_groups::Group
  - \_\_init\_\_, [219](#)
  - extra\_global\_params, [219](#)
  - name, [219](#)
  - set\_var, [219](#)
  - vars, [219](#)
- pygenn::genn\_groups::NeuronGroup
  - \_\_init\_\_, [249](#)
  - add\_extra\_global\_param, [249](#)
  - add\_to, [249](#)
  - current\_spikes, [250](#)
  - delay\_slots, [250](#)
  - is\_spike\_source\_array, [251](#)
  - load, [250](#)
  - neuron, [251](#)
  - pop, [251](#)
  - reinitialise, [250](#)
  - set\_extra\_global\_param, [250](#)

- set\_neuron, 251
- size, 251
- spike\_count, 251
- spike\_que\_ptr, 252
- spikes, 252
- type, 252
- pygenn::genn\_groups::SynapseGroup
  - \_\_init\_\_, 323
  - add\_extra\_global\_param, 323
  - add\_to, 324
  - connections\_set, 329
  - connectivity\_extra\_global\_params, 329
  - connectivity\_initialiser, 329
  - get\_sparse\_post\_inds, 324
  - get\_sparse\_pre\_inds, 324
  - get\_var\_values, 324
  - has\_individual\_postsynaptic\_vars, 324
  - has\_individual\_synapse\_vars, 324
  - ind, 330
  - is\_bitmask, 325
  - is\_connectivity\_init\_required, 325
  - is\_dense, 325
  - is\_ragged, 325
  - load, 325
  - load\_connectivity\_init\_egps, 325
  - matrix\_type, 325, 326
  - max\_row\_length, 326
  - num\_synapses, 326
  - pop, 330
  - post\_vars, 330
  - postsyn, 330
  - pre\_vars, 330
  - psm\_extra\_global\_params, 330
  - psm\_vars, 330
  - reinitialise, 326
  - row\_lengths, 330
  - set\_connected\_populations, 326
  - set\_connectivity\_extra\_global\_param, 326
  - set\_extra\_global\_param, 327
  - set\_post\_syn, 327
  - set\_post\_var, 327
  - set\_pre\_var, 328
  - set\_psm\_extra\_global\_param, 328
  - set\_psm\_var, 328
  - set\_sparse\_connections, 328
  - set\_weight\_update, 329
  - src, 330
  - synapse\_order, 330
  - trg, 330
  - w\_update, 331
  - weight\_update\_var\_size, 329
- pygenn::genn\_model
  - backend\_modules, 92
  - create\_cmlf\_class, 86
  - create\_custom\_current\_source\_class, 86
  - create\_custom\_init\_var\_snippet\_class, 87
  - create\_custom\_model\_class, 87
  - create\_custom\_neuron\_class, 88
  - create\_custom\_postsynaptic\_class, 89
  - create\_custom\_sparse\_connect\_init\_snippet\_class, 89
  - create\_custom\_weight\_update\_class, 90
  - create\_dpf\_class, 91
  - init\_connectivity, 92
  - init\_var, 92
  - m, 92
- pygenn::genn\_model::GeNNModel
  - \_\_init\_\_, 210
  - add\_current\_source, 210
  - add\_neuron\_population, 211
  - add\_synapse\_population, 211
  - backend\_log\_level, 217
  - build, 212
  - current\_sources, 217
  - default\_sparse\_connectivity\_location, 212, 213
  - default\_var\_location, 213, 217
  - dT, 213, 218
  - end, 213
  - free\_device\_mem\_bytes, 213
  - init\_sparse\_time, 213
  - init\_time, 214
  - load, 214
  - model\_name, 214, 218
  - neuron\_populations, 218
  - neuron\_update\_time, 214
  - postsynaptic\_update\_time, 214
  - presynaptic\_update\_time, 214
  - pull\_connectivity\_from\_device, 214
  - pull\_current\_spikes\_from\_device, 214
  - pull\_spikes\_from\_device, 215
  - pull\_state\_from\_device, 215
  - pull\_var\_from\_device, 215
  - push\_connectivity\_to\_device, 215
  - push\_current\_spikes\_to\_device, 215
  - push\_spikes\_to\_device, 215
  - push\_state\_to\_device, 216
  - push\_var\_to\_device, 216
  - reinitialise, 216
  - step\_time, 216
  - synapse\_dynamics\_time, 216
  - synapse\_populations, 218
  - t, 216
  - timestep, 216, 217
  - timing\_enabled, 217
  - use\_backend, 217, 218
- pygenn::model\_preprocessor
  - GeNNType, 97
  - genn\_types, 96
  - is\_model\_valid, 93
  - param\_space\_to\_val\_vec, 94
  - param\_space\_to\_vals, 94
  - post\_var\_space\_to\_vals, 94
  - pre\_var\_space\_to\_vals, 95
  - prepare\_model, 95
  - prepare\_snippet, 95
  - var\_space\_to\_vals, 96

- pygenn::model\_preprocessor::ExtraGlobalVariable
  - \_\_init\_\_, 197
  - is\_scalar, 197
  - name, 197
  - set\_values, 197
  - type, 197
  - values, 197
  - view, 198
- pygenn::model\_preprocessor::Variable
  - \_\_init\_\_, 367
  - init\_required, 368
  - init\_val, 368
  - name, 368
  - needs\_allocation, 368
  - set\_values, 368
  - type, 368
  - values, 368
  - view, 369
- receive
  - SpineMLSimulator::NetworkClient, 248
- record
  - AnalogueRecorder, 107
  - SpikeRecorder, 305
  - SpineMLSimulator::LogOutput::AnalogueExternal, 104
  - SpineMLSimulator::LogOutput::AnalogueFile, 105
  - SpineMLSimulator::LogOutput::Base, 168
  - SpineMLSimulator::LogOutput::Event, 187
- recordInternal
  - SpineMLSimulator::LogOutput::AnalogueExternal, 104
  - SpineMLSimulator::LogOutput::AnalogueNetwork, 106
- recordSpikes
  - SpikeWriterText, 311
  - SpikeWriterTextCached, 312
- regexFuncSubstitute
  - CodeGenerator, 77
- regexVarSubstitute
  - CodeGenerator, 77
- RegularSpikeRate
  - SpineMLSimulator::Input::RegularSpikeRate, 289
- reinitialise
  - pygenn::genn\_groups::CurrentSource, 177
  - pygenn::genn\_groups::NeuronGroup, 250
  - pygenn::genn\_groups::SynapseGroup, 326
  - pygenn::genn\_model::GeNNModel, 216
- row\_lengths
  - pygenn::genn\_groups::SynapseGroup, 330
- runTools
  - GenerateRunBase, 208
- SET\_ADDITIONAL\_INPUT\_VARS
  - neuronModels.h, 410
- SET\_APPLY\_INPUT\_CODE
  - postsynapticModels.h, 414
- SET\_CALC\_MAX\_COL\_LENGTH\_FUNC
  - initSparseConnectivitySnippet.h, 391
- InitSparseConnectivitySnippet::FixedProbability↔
  - Base, 201
- SET\_CALC\_MAX\_ROW\_LENGTH\_FUNC
  - initSparseConnectivitySnippet.h, 391
  - InitSparseConnectivitySnippet::FixedProbability↔
    - Base, 201
- SET\_CODE
  - initVarSnippet.h, 394
  - InitVarSnippet::Constant, 173
  - InitVarSnippet::Exponential, 192
  - InitVarSnippet::Gamma, 205
  - InitVarSnippet::Normal, 262
  - InitVarSnippet::Uniform, 360
- SET\_CURRENT\_CONVERTER\_CODE
  - postsynapticModels.h, 414
- SET\_DECAY\_CODE
  - postsynapticModels.h, 414
- SET\_DERIVED\_PARAMS
  - snippet.h, 418
- SET\_EVENT\_CODE
  - weightUpdateModels.h, 426
- SET\_EVENT\_THRESHOLD\_CONDITION\_CODE
  - weightUpdateModels.h, 427
- SET\_EXTRA\_GLOBAL\_PARAMS
  - initSparseConnectivitySnippet.h, 391
  - models.h, 401
- SET\_INJECTION\_CODE
  - currentSourceModels.h, 382
  - CurrentSourceModels::DC, 183
  - CurrentSourceModels::GaussianNoise, 206
- SET\_LEARN\_POST\_CODE
  - weightUpdateModels.h, 427
- SET\_LEARN\_POST\_SUPPORT\_CODE
  - weightUpdateModels.h, 427
- SET\_MAX\_COL\_LENGTH
  - initSparseConnectivitySnippet.h, 391
  - InitSparseConnectivitySnippet::OneToOne, 264
- SET\_MAX\_ROW\_LENGTH
  - initSparseConnectivitySnippet.h, 392
  - InitSparseConnectivitySnippet::OneToOne, 264
- SET\_NEEDS\_AUTO\_REFRACTORY
  - neuronModels.h, 410
  - NeuronModels::LIF, 230
  - NeuronModels::PoissonNew, 274
  - NeuronModels::SpikeSource, 307
  - NeuronModels::SpikeSourceArray, 310
- SET\_NEEDS\_POST\_SPIKE\_TIME
  - weightUpdateModels.h, 427
- SET\_NEEDS\_PRE\_SPIKE\_TIME
  - weightUpdateModels.h, 427
- SET\_PARAM\_NAMES
  - snippet.h, 418
- SET\_POST\_SPIKE\_CODE
  - weightUpdateModels.h, 427
- SET\_POST\_VARS
  - weightUpdateModels.h, 427
- SET\_PRE\_SPIKE\_CODE
  - weightUpdateModels.h, 427

SET\_PRE\_VARS  
     weightUpdateModels.h, 428  
 SET\_RESET\_CODE  
     neuronModels.h, 410  
 SET\_ROW\_BUILD\_CODE  
     initSparseConnectivitySnippet.h, 392  
     InitSparseConnectivitySnippet::FixedProbability,  
         199  
     InitSparseConnectivitySnippet::FixedProbability↔  
         NoAutapse, 202  
     InitSparseConnectivitySnippet::OneToOne, 264  
 SET\_ROW\_BUILD\_STATE\_VARS  
     initSparseConnectivitySnippet.h, 392  
     InitSparseConnectivitySnippet::FixedProbability↔  
         Base, 201  
 SET\_SIM\_CODE  
     neuronModels.h, 411  
     weightUpdateModels.h, 428  
 SET\_SIM\_SUPPORT\_CODE  
     weightUpdateModels.h, 428  
 SET\_SUPPORT\_CODE  
     neuronModels.h, 411  
     postsynapticModels.h, 414  
 SET\_SYNAPSE\_DYNAMICS\_CODE  
     weightUpdateModels.h, 428  
 SET\_SYNAPSE\_DYNAMICS\_SUPPORT\_CODE  
     weightUpdateModels.h, 428  
 SET\_THRESHOLD\_CONDITION\_CODE  
     neuronModels.h, 411  
 SET\_VARS  
     models.h, 402  
 scalar  
     SpineMLSimulator, 98  
 ScalarBase  
     SpineMLSimulator::InputValue::ScalarBase, 293  
 scalarExpr  
     ModelSpec, 243  
 Scope  
     CodeGenerator::CodeStream::Scope, 294  
 send  
     SpineMLSimulator::NetworkClient, 248  
 set\_connected\_populations  
     pygenn::genn\_groups::SynapseGroup, 326  
 set\_connectivity\_extra\_global\_param  
     pygenn::genn\_groups::SynapseGroup, 326  
 set\_current\_source\_model  
     pygenn::genn\_groups::CurrentSource, 177  
 set\_extra\_global\_param  
     pygenn::genn\_groups::CurrentSource, 177  
     pygenn::genn\_groups::NeuronGroup, 250  
     pygenn::genn\_groups::SynapseGroup, 327  
 set\_neuron  
     pygenn::genn\_groups::NeuronGroup, 251  
 set\_post\_syn  
     pygenn::genn\_groups::SynapseGroup, 327  
 set\_post\_var  
     pygenn::genn\_groups::SynapseGroup, 327  
 set\_pre\_var  
     pygenn::genn\_groups::SynapseGroup, 328  
 set\_psm\_extra\_global\_param  
     pygenn::genn\_groups::SynapseGroup, 328  
 set\_psm\_var  
     pygenn::genn\_groups::SynapseGroup, 328  
 set\_sparse\_connections  
     pygenn::genn\_groups::SynapseGroup, 328  
 set\_values  
     pygenn::model\_preprocessor::ExtraGlobal↔  
         Variable, 197  
     pygenn::model\_preprocessor::Variable, 368  
 set\_var  
     pygenn::genn\_groups::Group, 219  
 set\_weight\_update  
     pygenn::genn\_groups::SynapseGroup, 329  
 setBackPropDelaySteps  
     SynapseGroup, 341  
 setDefaultExtraGlobalParamLocation  
     ModelSpec, 243  
 setDefaultNarrowSparseIndEnabled  
     ModelSpec, 243  
 setDefaultSparseConnectivityLocation  
     ModelSpec, 243  
 setDefaultVarLocation  
     ModelSpec, 243  
 setDendriticDelayLocation  
     SynapseGroup, 341  
 setDT  
     ModelSpec, 244  
 setEventThresholdReTestRequired  
     SynapseGroup, 341  
 setExtraGlobalParamLocation  
     CurrentSource, 181  
     NeuronGroup, 259  
 setInSynVarLocation  
     SynapseGroup, 342  
 setMaxConnections  
     SynapseGroup, 342  
 setMaxDendriticDelayTimesteps  
     SynapseGroup, 342  
 setMaxSourceConnections  
     SynapseGroup, 342  
 setMergePostsynapticModels  
     ModelSpec, 244  
 setName  
     ModelSpec, 244  
 setNarrowSparseIndEnabled  
     SynapseGroup, 342  
 setNumThreadsPerSpike  
     SynapseGroup, 342  
 setPSExtraGlobalParamLocation  
     SynapseGroup, 342  
 setPSModelMergeTarget  
     SynapseGroup, 343  
 setPSVarLocation  
     SynapseGroup, 343  
 setPrecision  
     ModelSpec, 244



- setSeed
  - ModelSpec, 244
- setSink
  - CodeGenerator::CodeStream, 171
- setSpanType
  - SynapseGroup, 343
- setSparseConnectivityExtraGlobalParamLocation
  - SynapseGroup, 343
- setSparseConnectivityLocation
  - SynapseGroup, 343
- setSpikeEventLocation
  - NeuronGroup, 259
- setSpikeLocation
  - NeuronGroup, 259
- setSpikeTimeLocation
  - NeuronGroup, 259
- setTime
  - SharedLibraryModel, 299
- setTimePrecision
  - ModelSpec, 244
- setTimestep
  - SharedLibraryModel, 299
- setTiming
  - ModelSpec, 244
- setValue
  - SpineMLSimulator::ModelProperty::Exponential↔
    - Distribution, 193
  - SpineMLSimulator::ModelProperty::Fixed, 198
  - SpineMLSimulator::ModelProperty::Normal↔
    - Distribution, 262
  - SpineMLSimulator::ModelProperty::Uniform↔
    - Distribution, 361
  - SpineMLSimulator::ModelProperty::ValueList, 365
- setVarLocation
  - CurrentSource, 181
  - NeuronGroup, 259
- setWUExtraGlobalParamLocation
  - SynapseGroup, 343
- setWUPostVarLocation
  - SynapseGroup, 343
- setWUPreVarLocation
  - SynapseGroup, 344
- setWUVarLocation
  - SynapseGroup, 344
- SharedLibraryModel
  - ~SharedLibraryModel, 295
  - allocateExtraGlobalParam, 295
  - allocateMem, 295
  - freeExtraGlobalParam, 296
  - freeMem, 296
  - getArray, 296
  - getFreeDeviceMemBytes, 296
  - getInitSparseTime, 296
  - getInitTime, 296
  - getNeuronUpdateTime, 296
  - getPostsynapticUpdateTime, 296
  - getPresynapticUpdateTime, 296
  - getScalar, 297
  - getSymbol, 297
  - getSynapseDynamicsTime, 297
  - getTime, 297
  - getTimestep, 297
  - initialize, 297
  - initializeSparse, 297
  - open, 297
  - pullConnectivityFromDevice, 298
  - pullCurrentSpikesFromDevice, 298
  - pullExtraGlobalParam, 298
  - pullSpikesFromDevice, 298
  - pullStateFromDevice, 298
  - pullVarFromDevice, 298
  - pushConnectivityToDevice, 298
  - pushCurrentSpikesToDevice, 298
  - pushExtraGlobalParam, 299
  - pushSpikesToDevice, 299
  - pushStateToDevice, 299
  - pushVarToDevice, 299
  - setTime, 299
  - setTimestep, 299
  - SharedLibraryModel, 295
  - stepTime, 299
- SharedLibraryModel< scalar >, 294
- sharedLibraryModel.h, 415
- shouldApply
  - SpineMLSimulator::Input::Base, 165
- shouldRecord
  - SpineMLSimulator::LogOutput::Base, 168
- showPtxInfo
  - CodeGenerator::CUDA::Preferences, 282
- Simulator
  - SpineMLSimulator::Simulator, 300
- simulator.cc, 416
- simulator.h, 416
- singlePrecisionTemplate
  - CodeGenerator::FunctionTemplate, 203
- size
  - pygenn::genn\_groups::CurrentSource, 177, 178
  - pygenn::genn\_groups::NeuronGroup, 251
- Snippet, 97
- snippet.h, 417
  - DECLARE\_SNIPPET, 417
  - IMPLEMENT\_SNIPPET, 418
  - SET\_DERIVED\_PARAMS, 418
  - SET\_PARAM\_NAMES, 418
- Snippet::Base, 156
  - ~Base, 157
  - DerivedParamVec, 156
  - EGPVec, 157
  - getDerivedParams, 157
  - getNamedVecIndex, 157
  - getParamNames, 157
  - ParamValVec, 157
  - StringVec, 157
- Snippet::Base::DerivedParam, 185
  - func, 186
  - name, 186

Snippet::Base::EGP, 186  
     name, 186  
     type, 186  
 Snippet::Base::ParamVal, 265  
     name, 265  
     type, 265  
     value, 265  
 Snippet::Init  
     getDerivedParams, 221  
     getParams, 221  
     getSnippet, 221  
     Init, 221  
     initDerivedParams, 221  
 Snippet::Init< SnippetBase >, 220  
 Snippet::ValueBase  
     getValues, 363  
     operator[], 363  
     ValueBase, 363  
 Snippet::ValueBase< 0 >, 364  
     getValues, 364  
     ValueBase, 364  
 Snippet::ValueBase< NumVars >, 363  
 SpanType  
     SynapseGroup, 334  
 spike\_count  
     pygenn::genn\_groups::NeuronGroup, 251  
 spike\_que\_ptr  
     pygenn::genn\_groups::NeuronGroup, 252  
 SpikeBase  
     SpineMLSimulator::Input::SpikeBase, 303  
 SpikeRecorder  
     GetCurrentSpikeCountFunc, 304  
     GetCurrentSpikesFunc, 305  
     getSum, 305  
     record, 305  
     SpikeRecorder, 305  
 SpikeRecorder< Writer >, 304  
 spikeRecorder.h, 418  
 SpikeTime  
     SpineMLSimulator::Input::SpikeTime, 310  
 SpikeWriterText, 311  
     recordSpikes, 311  
     SpikeWriterText, 311  
 SpikeWriterTextCached, 312  
     ~SpikeWriterTextCached, 312  
     recordSpikes, 312  
     SpikeWriterTextCached, 312  
     writeCache, 312  
 spikes  
     pygenn::genn\_groups::NeuronGroup, 252  
 SpineMLSimulator, 97  
     scalar, 98  
 SpineMLSimulator::Connectors, 98  
     create, 98  
 SpineMLSimulator::Input, 98  
 SpineMLSimulator::Input::Analogue, 101  
     Analogue, 101  
     apply, 102  
 SpineMLSimulator::Input::Base, 164  
     ~Base, 165  
     apply, 165  
     Base, 165  
     shouldApply, 165  
     updateValues, 165  
 SpineMLSimulator::Input::InterSpikeIntervalBase, 221  
     apply, 222  
     getTimeToSpike, 222  
     InterSpikeIntervalBase, 222  
 SpineMLSimulator::Input::PoissonSpikeRate, 274  
     getTimeToSpike, 275  
     PoissonSpikeRate, 275  
 SpineMLSimulator::Input::RegularSpikeRate, 289  
     getTimeToSpike, 289  
     RegularSpikeRate, 289  
 SpineMLSimulator::Input::SpikeBase, 303  
     injectSpike, 304  
     PushCurrentSpikesFunc, 303  
     SpikeBase, 303  
     uploadSpikes, 304  
 SpineMLSimulator::Input::SpikeTime, 310  
     apply, 311  
     SpikeTime, 310  
 SpineMLSimulator::InputValue, 98  
     create, 99  
 SpineMLSimulator::InputValue::Base, 166  
     ~Base, 166  
     Base, 166  
     getNumNeurons, 166  
     getTargetIndices, 167  
     update, 167  
 SpineMLSimulator::InputValue::Constant, 173  
     Constant, 173  
     update, 174  
 SpineMLSimulator::InputValue::ConstantArray, 174  
     ConstantArray, 174  
     update, 174  
 SpineMLSimulator::InputValue::External, 193  
     External, 194  
     getBuffer, 194  
     getBufferBegin, 194  
     getBufferEnd, 194  
     getSize, 194  
     update, 195  
     updateInternal, 195  
 SpineMLSimulator::InputValue::ExternalNetwork, 195  
     ExternalNetwork, 195  
     updateInternal, 196  
 SpineMLSimulator::InputValue::ScalarBase, 293  
     applyScalar, 293  
     ScalarBase, 293  
 SpineMLSimulator::InputValue::TimeVarying, 349  
     TimeVarying, 350  
     update, 350  
 SpineMLSimulator::InputValue::TimeVaryingArray, 350  
     TimeVaryingArray, 350  
     update, 351



- SpineMLSimulator::LogOutput, 99
- SpineMLSimulator::LogOutput::AnalogueBase, 102
  - AnalogueBase, 102
  - getIndices, 103
  - getModelPropertySize, 103
  - getStateVarBegin, 103
  - getStateVarEnd, 103
  - pullModelPropertyFromDevice, 103
- SpineMLSimulator::LogOutput::AnalogueExternal, 103
  - AnalogueExternal, 104
  - record, 104
  - recordInternal, 104
- SpineMLSimulator::LogOutput::AnalogueFile, 105
  - AnalogueFile, 105
  - record, 105
- SpineMLSimulator::LogOutput::AnalogueNetwork, 106
  - AnalogueNetwork, 106
  - recordInternal, 106
- SpineMLSimulator::LogOutput::Base, 167
  - ~Base, 168
  - Base, 167
  - getEndTimestep, 168
  - record, 168
  - shouldRecord, 168
- SpineMLSimulator::LogOutput::Event, 186
  - Event, 187
  - record, 187
- SpineMLSimulator::ModelProperty, 99
  - create, 100
- SpineMLSimulator::ModelProperty::Base, 168
  - ~Base, 169
  - Base, 169
  - getHostStateVar, 169
  - getSize, 169
  - pullFromDevice, 169
  - pushToDevice, 169
- SpineMLSimulator::ModelProperty::Exponential↵
  - Distribution, 193
  - ExponentialDistribution, 193
  - setValue, 193
- SpineMLSimulator::ModelProperty::Fixed, 198
  - Fixed, 198
  - setValue, 198
- SpineMLSimulator::ModelProperty::NormalDistribution, 262
  - NormalDistribution, 262
  - setValue, 262
- SpineMLSimulator::ModelProperty::UniformDistribution, 361
  - setValue, 361
  - UniformDistribution, 361
- SpineMLSimulator::ModelProperty::ValueList, 365
  - setValue, 365
  - ValueList, 365
- SpineMLSimulator::NetworkClient, 245
  - ~NetworkClient, 247
  - connect, 247
  - DataType, 245
  - Mode, 247
  - NetworkClient, 247
  - receive, 248
  - send, 248
- SpineMLSimulator::Simulator, 300
  - ~Simulator, 301
  - calcNumTimesteps, 301
  - getDT, 301
  - getDurationMs, 301
  - getExternalInput, 301
  - getExternalLogger, 301
  - getInitSparseTime, 301
  - getInitTime, 301
  - getInputMs, 302
  - getLogMs, 302
  - getNeuronUpdateTime, 302
  - getPostsynapticUpdateTime, 302
  - getPresynapticUpdateTime, 302
  - getSimulateMs, 302
  - getSynapseDynamicsTime, 302
  - load, 302
  - Simulator, 300
  - stepTime, 302
- SpineMLSimulator::StateVar
  - get, 313
  - isAccessible, 313
  - m\_Direct, 314
  - m\_Indirect, 314
  - pull, 313
  - push, 314
  - StateVar, 313
- SpineMLSimulator::StateVar< T >, 313
- SpineMLSimulator::Timer, 347
  - ~Timer, 347
  - get, 348
  - Timer, 347
- SpineMLSimulator::TimerAccumulate, 349
  - ~TimerAccumulate, 349
  - get, 349
  - TimerAccumulate, 349
- src
  - pygenn::genn\_groups::SynapseGroup, 330
- StateVar
  - SpineMLSimulator::StateVar, 313
- stateVar.h, 418
- step\_time
  - pygenn::genn\_model::GeNNModel, 216
- stepTime
  - SharedLibraryModel, 299
  - SpineMLSimulator::Simulator, 302
- StringVec
  - Snippet::Base, 157
- substitute
  - CodeGenerator, 77
- Substitutions
  - CodeGenerator::Substitutions, 319
- substitutions.h, 419
- synapse\_dynamics\_time

- pygenn::genn\_model::GeNNModel, 216
- synapse\_order
  - pygenn::genn\_groups::SynapseGroup, 330
- synapse\_populations
  - pygenn::genn\_model::GeNNModel, 218
- SynapseGroup, 331
  - getBackPropDelaySteps, 335
  - getClusterHostID, 335
  - getConnectivityInitialiser, 335
  - getDelaySteps, 335
  - getDendriticDelayLocation, 335
  - getDendriticDelayOffset, 335
  - getInSynLocation, 335
  - getMatrixType, 335
  - getMaxConnections, 335
  - getMaxDendriticDelayTimesteps, 336
  - getMaxSourceConnections, 336
  - getName, 336
  - getNumThreadsPerSpike, 336
  - getPSConstInitVals, 336
  - getPSDerivedParams, 336
  - getPSExtraGlobalParamLocation, 336, 337
  - getPSModel, 337
  - getPSModelTargetName, 337
  - getPSPParams, 337
  - getPSVarInitialisers, 337
  - getPSVarLocation, 337
  - getPostsynapticBackPropDelaySlot, 336
  - getPresynapticAxonalDelaySlot, 336
  - getSpanType, 337
  - getSparseConnectivityExtraGlobalParamLocation, 337
  - getSparseConnectivityLocation, 338
  - getSparseIndType, 338
  - getSrcNeuronGroup, 338
  - getTrgNeuronGroup, 338
  - getWUConstInitVals, 338
  - getWUDerivedParams, 338
  - getWUExtraGlobalParamLocation, 338, 339
  - getWUModel, 339
  - getWUParams, 339
  - getWUPostVarInitialisers, 339
  - getWUPostVarLocation, 339
  - getWUPreVarInitialisers, 339
  - getWUPreVarLocation, 339
  - getWUVarInitialisers, 340
  - getWUVarLocation, 340
  - initDerivedParams, 340
  - isDendriticDelayRequired, 340
  - isEventThresholdReTestRequired, 340
  - isPSInitRNGRequired, 340
  - isPSModelMerged, 340
  - isProceduralConnectivityRNGRequired, 340
  - isSparseConnectivityInitRequired, 341
  - isSpikeEventRequired, 341
  - isTrueSpikeRequired, 341
  - isWUInitRNGRequired, 341
  - isWUVarInitRequired, 341
  - isZeroCopyEnabled, 341
  - setBackPropDelaySteps, 341
  - setDendriticDelayLocation, 341
  - setEventThresholdReTestRequired, 341
  - setInSynVarLocation, 342
  - setMaxConnections, 342
  - setMaxDendriticDelayTimesteps, 342
  - setMaxSourceConnections, 342
  - setNarrowSparseIndEnabled, 342
  - setNumThreadsPerSpike, 342
  - setPSExtraGlobalParamLocation, 342
  - setPSModelMergeTarget, 343
  - setPSVarLocation, 343
  - setSpanType, 343
  - setSparseConnectivityExtraGlobalParamLocation, 343
  - setSparseConnectivityLocation, 343
  - setWUExtraGlobalParamLocation, 343
  - setWUPostVarLocation, 343
  - setWUPreVarLocation, 344
  - setWUVarLocation, 344
  - SpanType, 334
  - SynapseGroup, 334
- synapseGroup.cc, 419
- synapseGroup.h, 419
- SynapseGroupHandler
  - CodeGenerator::BackendBase, 137
- SynapseGroupInternal, 344
  - SynapseGroupInternal, 344
- synapseGroupInternal.h, 420
- SynapseGroupValueType
  - ModelSpec, 235
- SynapseMatrixConnectivity
  - synapseMatrixType.h, 421
- SynapseMatrixType
  - synapseMatrixType.h, 421
- synapseMatrixType.h, 420
  - operator&, 421, 422
  - operator|, 422
  - SynapseMatrixConnectivity, 421
  - SynapseMatrixType, 421
  - SynapseMatrixWeight, 421
- SynapseMatrixWeight
  - synapseMatrixType.h, 421
- t
  - pygenn::genn\_model::GeNNModel, 216
- TYPE
  - backendBase.cc, 374
- target\_pop
  - pygenn::genn\_groups::CurrentSource, 178
- TeeBuf
  - CodeGenerator::TeeBuf, 345
- TeeStream
  - CodeGenerator::TeeStream, 346
- teeStream.h, 422
- TimePrecision
  - modelSpec.h, 404
- TimeVarying

- SpineMLSimulator::InputValue::TimeVarying, 350
- TimeVaryingArray
  - SpineMLSimulator::InputValue::TimeVaryingArray, 350
- Timer, 346
  - ~Timer, 347
  - get, 347
  - SpineMLSimulator::Timer, 347
  - Timer, 347
- timer.h, 422, 423
- TimerAccumulate, 348
  - ~TimerAccumulate, 348
  - get, 348
  - SpineMLSimulator::TimerAccumulate, 349
  - TimerAccumulate, 348
- timestep
  - pygenn::genn\_model::GeNNModel, 216, 217
- timing\_enabled
  - pygenn::genn\_model::GeNNModel, 217
- trg
  - pygenn::genn\_groups::SynapseGroup, 330
- type
  - Models::Base::Var, 366
  - pygenn::genn\_groups::NeuronGroup, 252
  - pygenn::model\_preprocessor::ExtraGlobal↔Variable, 197
  - pygenn::model\_preprocessor::Variable, 368
  - Snippet::Base::EGP, 186
  - Snippet::Base::ParamVal, 265
- UniformDistribution
  - SpineMLSimulator::ModelProperty::Uniform↔Distribution, 361
- uninitialisedConnectivity
  - modelSpec.h, 406
- uninitialisedVar
  - modelSpec.h, 406
- update
  - SpineMLSimulator::InputValue::Base, 167
  - SpineMLSimulator::InputValue::Constant, 174
  - SpineMLSimulator::InputValue::ConstantArray, 174
  - SpineMLSimulator::InputValue::External, 195
  - SpineMLSimulator::InputValue::TimeVarying, 350
  - SpineMLSimulator::InputValue::TimeVaryingArray, 351
- updateInternal
  - SpineMLSimulator::InputValue::External, 195
  - SpineMLSimulator::InputValue::ExternalNetwork, 196
- updatePostVarQueues
  - NeuronGroup, 260
- updatePreVarQueues
  - NeuronGroup, 260
- updateValues
  - SpineMLSimulator::Input::Base, 165
- uploadSpikes
  - SpineMLSimulator::Input::SpikeBase, 304
- use\_backend
  - pygenn::genn\_model::GeNNModel, 217, 218
- userCxxFlagsGNU
  - CodeGenerator::PreferencesBase, 284
- userNvccFlags
  - CodeGenerator::CUDA::Preferences, 282
- userNvccFlagsGNU
  - CodeGenerator::PreferencesBase, 284
- Utils, 100
  - getUnderlyingType, 100
  - isRNGRequired, 100
  - isTypePointer, 101
- utils.h, 423
  - CHECK\_CU\_ERRORS, 423
  - CHECK\_CUDA\_ERRORS, 423
- value
  - Snippet::Base::ParamVal, 265
- ValueBase
  - Snippet::ValueBase, 363
  - Snippet::ValueBase< 0 >, 364
- ValueList
  - SpineMLSimulator::ModelProperty::ValueList, 365
- values
  - pygenn::model\_preprocessor::ExtraGlobal↔Variable, 197
  - pygenn::model\_preprocessor::Variable, 368
- Var
  - Models::Base::Var, 366
- var\_space\_to\_vals
  - pygenn::model\_preprocessor, 96
- VarAccess
  - models.h, 402
- VarInit
  - Models::VarInit, 369
- VarInitContainerBase
  - Models::VarInitContainerBase, 370
  - Models::VarInitContainerBase< 0 >, 371
- VarLocation
  - variableMode.h, 424
- VarValues
  - CurrentSourceModels::DC, 183
  - CurrentSourceModels::GaussianNoise, 206
  - NeuronModels::Izhikevich, 224
  - NeuronModels::IzhikevichVariable, 227
  - NeuronModels::LIF, 229
  - NeuronModels::Poisson, 271
  - NeuronModels::PoissonNew, 273
  - NeuronModels::RulkovMap, 291
  - NeuronModels::SpikeSource, 307
  - NeuronModels::SpikeSourceArray, 309
  - NeuronModels::TraubMiles, 353
  - NeuronModels::TraubMilesAlt, 355
  - NeuronModels::TraubMilesFast, 357
  - NeuronModels::TraubMilesNStep, 359
  - PostsynapticModels::DeltaCurr, 185
  - PostsynapticModels::ExpCond, 189
  - PostsynapticModels::ExpCurr, 191
- VarVec
  - Models::Base, 153
- variableMode.h, 424

- operator&, 424
- VarLocation, 424
- vars
  - pygenn::genn\_groups::Group, 219
- view
  - pygenn::model\_preprocessor::ExtraGlobal↵  
Variable, 198
  - pygenn::model\_preprocessor::Variable, 369
- w\_update
  - pygenn::genn\_groups::SynapseGroup, 331
- weight\_update\_var\_size
  - pygenn::genn\_groups::SynapseGroup, 329
- WeightUpdateModels, 101
- weightUpdateModels.cc, 424
  - IMPLEMENT\_MODEL, 425
- weightUpdateModels.h, 425
  - DECLARE\_WEIGHT\_UPDATE\_MODEL, 426
  - SET\_EVENT\_CODE, 426
  - SET\_EVENT\_THRESHOLD\_CONDITION\_CODE, 427
  - SET\_LEARN\_POST\_CODE, 427
  - SET\_LEARN\_POST\_SUPPORT\_CODE, 427
  - SET\_NEEDS\_POST\_SPIKE\_TIME, 427
  - SET\_NEEDS\_PRE\_SPIKE\_TIME, 427
  - SET\_POST\_SPIKE\_CODE, 427
  - SET\_POST\_VARS, 427
  - SET\_PRE\_SPIKE\_CODE, 427
  - SET\_PRE\_VARS, 428
  - SET\_SIM\_CODE, 428
  - SET\_SIM\_SUPPORT\_CODE, 428
  - SET\_SYNAPSE\_DYNAMICS\_CODE, 428
  - SET\_SYNAPSE\_DYNAMICS\_SUPPORT\_CODE, 428
- WeightUpdateModels::Base, 161
  - getEventCode, 162
  - getEventThresholdConditionCode, 162
  - getLearnPostCode, 162
  - getLearnPostSupportCode, 162
  - getPostSpikeCode, 163
  - getPostVarIndex, 163
  - getPostVars, 163
  - getPreSpikeCode, 163
  - getPreVarIndex, 163
  - getPreVars, 163
  - getSimCode, 163
  - getSimSupportCode, 164
  - getSynapseDynamicsCode, 164
  - getSynapseDynamicsSupportCode, 164
  - isPostSpikeTimeRequired, 164
  - isPreSpikeTimeRequired, 164
- WeightUpdateModels::PiecewiseSTDP, 265
  - DECLARE\_WEIGHT\_UPDATE\_MODEL, 267
  - getDerivedParams, 268
  - getLearnPostCode, 268
  - getParamNames, 268
  - getSimCode, 268
  - getVars, 268
  - isPostSpikeTimeRequired, 268
  - isPreSpikeTimeRequired, 269
- WeightUpdateModels::StaticGraded, 314
  - DECLARE\_WEIGHT\_UPDATE\_MODEL, 315
  - getEventCode, 315
  - getEventThresholdConditionCode, 315
  - getParamNames, 316
  - getVars, 316
- WeightUpdateModels::StaticPulse, 316
  - DECLARE\_WEIGHT\_UPDATE\_MODEL, 317
  - getSimCode, 317
  - getVars, 317
- WeightUpdateModels::StaticPulseDendriticDelay, 317
  - DECLARE\_WEIGHT\_UPDATE\_MODEL, 318
  - getSimCode, 318
  - getVars, 319
- writeCache
  - SpikeWriterTextCached, 312
- writePreciseString
  - CodeGenerator, 78
- writeSizes
  - GenerateRunBase, 208
- xrange
  - pygenn::genn\_groups, 85
- zero
  - CodeGenerator::MemAlloc, 231
- zeroCopy
  - CodeGenerator::MemAlloc, 231
- zeroCopyInUse
  - ModelSpec, 244