Function Catalogue and Verification Records

A New Framework for Efficient Multivariate Functional Bootstrapping

1 Reading the catalogue

This catalogue helps readers select a function, find its precise definition and input domain, and locate the evidence available for it. It contains **74 entries**: 45 finite-domain structural instances, 21 configurations with encrypted measurements, and 8 direct-construction families. Repeated functions on different domains remain separate entries. These counts do not mean 74 distinct function types or 74 speedups.

IDs	Evidence and intended use
O01–O45	Stored finite-domain checks and logical LUT-record counts. Use these to study representations; they are not encrypted timings.
T01–T21	Stored encrypted measurements for the stated configurations. Use the associated summaries, inputs and raw logs to inspect each result.
F01–F08	Applications of the existing count construction. These are function families, not additional measured configurations.

The machine-readable `catalog.csv` contains each entry's definition, original function name, domain, numerical values, evidence type, source and limitations. It also records the function category, applicability label, expected benefit and practical limit. These added descriptions keep representation suitability separate from measured runtime. Search its `catalog_id` column using the IDs printed here. Source paths in the CSV are relative to this directory; a suffix after `#` identifies a task or row in the cited file.

1.1 What a record count means

Write $[t] = \{0, \ldots, t-1\}$. A single-layer representation has the form

$$f(x) = Q\left(\sum_i p_i(x_i)\right), \qquad E = \max_x \sum_i p_i(x_i) - \min_x \sum_i p_i(x_i).$$

Under the paper's generic accounting, a direct table has t^n records, while the inner tables and contiguous outer table have $nt + E + 1$ records. The comparison-network and histogram constructions in the structural study instead sum the contiguous unary-table intervals used at successive steps. They are not all single-layer representations.

Logical records, abstract LUT calls, actual PBS calls, physical memory and elapsed time are different quantities. Table reuse, omission of affine maps and physical packing can affect implementation costs. The CSV therefore keeps `abstract_lut_evaluations` separate from `actual_ours_pbs`, and stores measured means in dedicated columns.

1.2 Scope of the comparisons

The structural study's `Alt.` column denotes a specified algebraic, sorting or histogram route. It is neither BBR26 timing nor a lower bound on the best implementation. The original script assigns no additional LUT records to ciphertext multiplication in those alternative routes. Their counts and route descriptions remain in the CSV and evidence files.

Each measured configuration has five warm-ups, thirty timed evaluations and decrypted-output checks. Timing starts with separately encrypted inputs and ends when the result ciphertext is returned. It includes server-side packing, conversion, evaluation and recovery, but excludes key generation, input encryption and offline table construction. BBR26 uses the authors' evaluator with an explicit decomposition for the function; Refined-LHE and Meta-PBS use the authors' programs and the saved input adapters.

Measured comparisons concern the recorded implementations and configurations. Encodings, parameters and overall failure probabilities have not been fully aligned. Lower latency in a row does not establish a ranking at a common security and reliability target. An empty cell means unmeasured; it is not zero time or an advantage.

How to assess a new function

The following groups are practical guidance based on the existing constructions and recorded examples. They are not a complete classification theorem. A function's input domain, representation and implementation must be considered together.

A. A direct low-span candidate. Start here when the function depends on a count with a short range, such as a threshold, interval, exact-count test or public-template Hamming distance. The indicator maps immediately provide a candidate representation. The proved integer-quotient construction is another explicit starting point for its stated domain. This label means that a construction is available; it does not promise compression at every small parameter or lower runtime.

B. A domain-specific construction or search is needed. Order statistics, frequency statistics and elementary composite functions may have useful intermediate values, but the complete representation must still be constructed and checked. A small alphabet or a histogram is a useful clue, not a guarantee. In particular, several counts may need to be combined, and that step can be costly. The O-series includes multistep comparison and histogram constructions as well as additive representations; their costs must not be merged under a single-layer formula.

C. No useful compression has been demonstrated in the attempted representation. If the representation has nearly as many records as the direct table, there is little or no useful entry reduction. This is a reason to stop or try another representation, not a proof that the function is inherently difficult. The historical synthetic example in Supplementary Notes, Section S1, gives 4104 records versus 4096 direct records at twelve binary inputs. That example is not added to the 74 entries. No T-series row is assigned to this group merely because its encrypted implementation is slower.

For a new function, use the following four checks before investing in an encrypted implementation.

1. Fix the exact function, legal input domain and output convention, including ties, rounding and public parameters. Look for a count, a frequency summary or another intermediate value that determines the required output.

2. Construct candidate inner maps and check that any two legal inputs with the same sum have the same function value. Use a proof where available or a complete finite-domain check where feasible. A small output range alone is insufficient.

3. Count all required inner and outer records using the appropriate convention. Compare with the direct table; include every step in a composed representation. Reject a candidate that provides no useful reduction for the intended domain, unless another stated benefit justifies it.

4. Check the evaluator's supported message ranges, encodings, output format and noise requirements. Only then measure the complete online route, including conversions. Fewer logical records can coexist with more costly PBS parameters and longer runtime.

What the existing records show

The table below reorganizes the same 74 entries by function category. Counts describe the catalogue's coverage, not the probability that a new function will work. The entries were selected in earlier studies and are not a random sample of functions. No new search or encrypted benchmark was run for this summary.

Category	Structural	Measured	Families	Total
Count-based functions	0	3	8	11
Exact integer quotient	1	4	0	5
Elementary composite functions	18	0	0	18
Order and small-range statistics	15	10	0	25
Histogram and frequency statistics	11	4	0	15
Total	45	21	8	74

Representation size. Define the record-compression ratio as the direct-table count divided by the representation count, retaining each row's original accounting convention. A ratio above one means fewer logical records. For the 18 elementary-composite records O02–O19, this ratio ranges from 2.12 to 4.36. For O20–O34 and O35–O45, the stored multistep constructions retain, respectively, about 0.03–0.17% and 0.06–0.10% of the direct-table records. Those percentages measure structural counts, not memory or elapsed time, and do not compare all possible implementations. The per-entry ratios are saved in `applicability_records.csv`; missing or symbolic counts remain blank.

Runtime. The three measured count functions have lower times than every measured baseline in their respective rows. Among the seven other small-domain statistical configurations, five have a lower time than at least one measured baseline; mode and interquartile range do not. None of the seven six-ternary-input statistical configurations has a lower time than a measured baseline. These contrasting outcomes show why an applicability label must be separate from a timing result. The comparisons remain limited to the saved parameters and implementations.

An explicit boundary case. The quotient measurements preserve the same distinction. The $t = 8$ measurement reuses a 205-record $T = 16$ circuit although its legal input domain has only 56 pairs; it is not a compressed representation of that restricted domain. For $t = 16, 32, 64$, the saved record counts are lower than their direct-table counts, but the fastest measured route is still a different implementation. A direct construction therefore provides a candidate to assess, not an assurance of faster evaluation.

What cannot be inferred. These records do not give a success rate for arbitrary functions, a success guarantee for simulated annealing, or a common-security and common-reliability performance ranking. The existing search comparison in Supplementary Notes concerns only its two stated functions, search space and budget. It should not be extrapolated to the whole catalogue.

The added CSV columns record the category, applicability, evidence type, expected benefit and practical limit. All previous columns and O/T/F identifiers remain unchanged. Run `python summarize_catalogue.py -check` from this directory to verify that the saved summary files match the catalogue; this performs arithmetic on saved entries and does not run experiments.

2 Count-based construction families

Set $p_i(x_i) = \mathbf{1}[x_i \in A]$ for a public set $A \subseteq [t]$. Then $S = \sum_i p_i(x_i) = c_A$ counts the inputs belonging to A. Changing the public outer table $Q(S)$ gives the following functions without searching for new inner maps for each threshold or interval.

Function	Output table	Code entry
F01 Set-membership count	$Q(S) = S$	`symbol_count`
F02 Threshold and majority	$Q(S) = \mathbf{1}[S \geq \tau]$	`symbol_set_threshold`
F03 Count interval	$Q(S) = \mathbf{1}[a \leq S \leq b]$	`symbol_set_interval`
F04 Exact-count test	$Q(S) = \mathbf{1}[S = k]$	`exact_k`
F05 Count parity	$Q(S) = S \bmod 2$	General indicator maps; specify Q
F06 Count modulo k	$Q(S) = S \bmod k$, $k \geq 2$	General indicator maps; specify Q
F07 Multilevel, binned or clipped count	Public $Q(0), \ldots, Q(n)$	General indicator maps; specify Q
F08 Hamming ball around a public template	$\mathbf{1}[\sum_i \mathbf{1}[x_i \neq a_i] \leq r]$	`hamming_ball`; `hamming_distance_representation`

For F01–F07, $x_i \in [t]$ and A is public; count thresholds and bounds lie in $0, \ldots, n$. Majority requires a tie rule for an even number of inputs. In F08, both the template a and radius r are public. This construction does not treat the template as an encrypted input.

For example, when $S = 5$, the threshold $\tau = 4$ returns 1, the interval $[2, 4]$ returns 0, and the exact count $k = 5$ returns 1. Parity returns 1, reduction modulo 3 returns 2, and clipping by $Q(S) = \min(S, 3)$ returns 3. The input $(0, 0, 0)$ has Hamming distance 1 from the public template $(0, 1, 0)$, so the radius-1 test returns 1. These examples explain definitions; they are not additional experiments.

The generic inner and outer tables use at most $nt+n+1$ records. This yields compression under that convention only when $nt+n+1 < t^n$. A change of input count, alphabet or output range still requires checks of the message space and noise constraints. No timing is supplied for unmeasured settings.

2.1 Using the existing implementation

`evidence/current_summaries/original_functions.py` defines the count, threshold, interval, exact-count and Hamming-ball targets. In the same directory, `original_compress.py` contains `indicator_representation`, which constructs the indicator inner maps, and `verify`, which checks every input of a supplied target function to confirm that each reachable sum has a consistent output.

Parity, residue and multilevel outputs are choices of the public outer table in that general interface. They are not presented as dedicated ciphertext benchmarks. The output message space for reduction modulo k must contain $0, \ldots, k-1$; this operation differs from only testing whether the residue is zero.

3 Measured small-domain statistics and counts

Let $c_A = \#\{i : x_i \in A\}$. The Hamming interval is $\mathbf{1}[4 \le \sum_{i=1}^{10} x_i \le 6]$; the set interval is $\mathbf{1}[2 \le c_{\{1,3\}} \le 4]$; the set threshold is $\mathbf{1}[c_{\{0,2\}} \ge 3]$.

For sorted inputs $x_{(1)} \le \cdots \le x_{(n)}$, the lower median is $x_{(\lfloor (n+1)/2 \rfloor)}$. A mode tie is resolved by selecting the smallest value. The interquartile range is

$$x_{(\lfloor 3(n-1)/4 \rfloor + 1)} - x_{(\lfloor (n-1)/4 \rfloor + 1)},$$

without interpolation. MAD is the lower median of the absolute deviations from the lower median of the inputs.

Function	Illustrative input	Output
T01 Hamming interval	Ten bits, five of them 1	1; weight 5 lies in $[4, 6]$
T02 Set interval	$(0, 1, 2, 3, 1, 0)$	1; three values lie in $\{1, 3\}$
T03 Set threshold	$(0, 1, 2, 3, 1, 0)$	1; three values lie in $\{0, 2\}$
T04 Lower median	$(0, 1, 2)$	1
T05 Mode	$(0, 0, 1, 1)$	0; smallest tied value
T06 Maximum	$(0, 1, 2)$	2
T07 Range	$(0, 1, 2)$	$2 - 0 = 2$
T08 Interquartile range	$(0, 1, 2, 2)$	$x_{(3)} - x_{(1)} = 2$
T09 MAD	$(0, 0, 2)$	0; centre 0, deviations $(0, 0, 2)$
T10 Distinct-value count	$(0, 0, 2)$	2; values 0 and 2

Recorded means in milliseconds. Refined denotes Refined-LHE and Meta denotes Meta-PBS.

Function	Domain	Ours	BBR26	Refined	Meta
T01 Hamming interval	$[2]^{10}$	19.31	37.45	68.51	72.80
T02 Set count interval	$[4]^6$	53.56	150.87	200.31	–
T03 Set count threshold	$[4]^6$	64.09	149.86	205.53	–
T04 Lower median	$[3]^3$	44.52	75.40	136.11	71.74
T05 Mode (smallest tie)	$[3]^4$	163.09	151.07	134.81	72.15
T06 Maximum	$[3]^3$	59.02	75.97	137.51	72.64
T07 Range	$[3]^3$	49.98	37.70	133.05	72.80
T08 Interquartile range	$[3]^4$	157.99	113.77	134.66	72.48
T09 MAD	$[3]^3$	45.56	76.22	136.49	73.09
T10 Distinct-value count	$[3]^3$	44.10	76.61	136.95	73.56

Ours has lower latency than the measured BBR26, Refined-LHE and Meta-PBS routes in 7, 8 and 6 of these instances, respectively. The three-input range is faster only than Refined-LHE and Meta-PBS. The four-input mode and interquartile range show no latency advantage. Missing methods and other domains are not included in these counts.

4 Larger statistical inputs and integer quotient

4.1 Six ternary inputs

These functions use the definitions on the preceding page. For $(0, 0, 1, 1, 2, 2)$, the outputs in the order listed below are $1, 0, 2, 2, 1, 1, 3$. The interquartile range is $x_{(4)} - x_{(2)}$; both medians in MAD are lower medians.

Function	Domain	Ours	BBR26	Refined	Meta
T11 Lower median	$[3]^6$	377.33	302.82	201.04	150.30
T12 Mode (smallest tie)	$[3]^6$	398.25	295.42	199.31	150.25
T13 Maximum	$[3]^6$	344.95	190.26	209.96	149.41
T14 Range	$[3]^6$	336.86	302.56	208.62	150.27
T15 Interquartile range	$[3]^6$	306.65	301.02	208.38	149.09
T16 MAD	$[3]^6$	308.38	152.62	200.04	149.30
T17 Distinct-value count	$[3]^6$	324.87	310.12	199.68	149.32

These instances passed the stored plaintext representation checks and recorded ciphertext-output checks, but the tested implementation of our method is slower than all three measured baselines. Its PBS parameters are larger in these configurations. A compact logical representation does not by itself imply lower encrypted latency.

4.2 Exact integer quotient

The target is $\lfloor m/d \rfloor$, with $0 \le m < t$ and $1 \le d < t$; for example, $m = 7, d = 2$ returns 3. Timings exclude the multiplication and subtraction needed to obtain a remainder. For $t = 16, 32, 64$, the representation uses 205, 501 and 1193 records, including the zero-divisor padding slot; the scales are 22, 44 and 89. The $t = 8$ measurement reuses the $T = 16, M = 22$ circuit rather than a separately minimized three-bit implementation.

ID	t	Ours	Native	BBR26	Refined	Meta
T21	8	330.55	534.31	1272.67	158.90	85.01
T18	16	319.15	436.12	2729.54	137.92	175.81
T19	32	911.32	742.76	7122.82	270.40	148.81
T20	64	1996.49	750.45	–	280.53	–

The $t = 8, 16$ rows have lower measured latency than Native and BBR26, but higher latency than Refined-LHE and Meta-PBS. At $t = 32$, only BBR26 is slower; at $t = 64$, no advantage is observed. The $t = 64$ row is a retained supplementary measurement, not an additional row in the paper's main quotient table.

All three successful BBR quotient records use PBS decomposition base log 15 with two levels, with underlying dimensions and encryption noise unchanged. Their failure probabilities have not been recalibrated; the original parameter labels are not carried over. At $t = 32$, four independently encrypted input blocks produce two $\mathbb{Z}_{17}$ outputs.

At $t = 8$, Refined-LHE retains two full four-bit CBS operations and a 256-entry table, Meta-PBS uses the positive half of an eight-bit negacyclic domain with online packing $m + 8d$, and Native retains two radix blocks. Meta-PBS uses a full-domain eight-bit configuration at $t = 16$ and the positive half of an eleven-bit negacyclic domain at $t = 32$. No corresponding ready-to-use $t = 64$ configuration was measured. Consult the saved parameter files and documentation for each method; this catalogue does not estimate a common overall failure probability.

5 Elementary composite functions: structural records

The following entries correspond to the structural study and its stored `intermediate_routes.csv`. "Records" sums the logical table entries; "calls" counts abstract unary-LUT evaluations, not measured PBS calls. Apart from the quotient identity proved in the paper, these numerical findings concern the finite domains checked by the original scripts. The transcendental-ratio outputs were cross-checked at 80- and 110-digit decimal precision, not proved symbolically over arbitrary parameters or all real inputs. Here $a{:}b$ denotes an inclusive integer interval.

Function	Checked domain	Direct	Records	Calls
O01 $\lfloor m/d \rfloor$	$m = 0{:}63,\ d = 1{:}63$	4032	1192	3
O02 $\lfloor (x_1x_2x_3)^{1/3} \rfloor$	$x_i = 1{:}15$	3375	1252	4
O03 $\lfloor a^{1/b} \rfloor$	$a, b = 2 : 16$	225	106	3
O04 $\lfloor a^{1/b} \rfloor$	$a, b = 2 : 32$	961	234	3
O05 $\lfloor \log_a b \rfloor$	$a, b = 2 : 32$	961	347	3
O06 $\lfloor \log(1+x)/\log(1+y) \rfloor$	$x, y = 1 : 31$	961	343	3
O07 $\lfloor \log(1+x^2)/\log(1+y^2) \rfloor$	$x, y = 1 : 31$	961	435	3
O08 $\lfloor \sqrt{1+x^2}/\sqrt{1+y^2} \rfloor$	$x, y = 1 : 31$	961	437	3
O09 $\lfloor \operatorname{asinh}(x)/\operatorname{asinh}(y) \rfloor$	$x, y = 1 : 31$	961	411	3
O10 $\lfloor \sqrt{\log(1+x)/\log(1+y)} \rfloor$	$x, y = 1 : 31$	961	339	3
O11 $\lfloor \sqrt[3]{\log(1+x)/\log(1+y)} \rfloor$	$x, y = 1 : 31$	961	335	3
O12 $\lfloor \sqrt{\operatorname{asinh}(x)/\operatorname{asinh}(y)} \rfloor$	$x, y = 1 : 31$	961	409	3
O13 $\lfloor \log(1+x)/\log(1+y) \rfloor$	$x, y = 1 : 63$	3969	913	3
O14 $\lfloor \log(1+x^2)/\log(1+y^2) \rfloor$	$x, y = 1 : 63$	3969	1187	3
O15 $\lfloor \sqrt{1+x^2}/\sqrt{1+y^2} \rfloor$	$x, y = 1 : 63$	3969	1311	3
O16 $\lfloor \operatorname{asinh}(x)/\operatorname{asinh}(y) \rfloor$	$x, y = 1 : 63$	3969	1001	3
O17 $\lfloor \sqrt{\log(1+x)/\log(1+y)} \rfloor$	$x, y = 1 : 63$	3969	911	3
O18 $\lfloor \sqrt[3]{\log(1+x)/\log(1+y)} \rfloor$	$x, y = 1 : 63$	3969	913	3
O19 $\lfloor \sqrt{\operatorname{asinh}(x)/\operatorname{asinh}(y)} \rfloor$	$x, y = 1 : 63$	3969	981	3

The three-input geometric mean returns 4 on $(2, 4, 8)$; the variable-index root returns 4 on $(a, b) = (16, 2)$; the variable-base logarithm returns 4 on $(a, b) = (2, 16)$. Each of O06–O19 returns 1 at $x = y = 1$.

O01 counts only the legal inner domains, $64 + 63$, and therefore has 1192 records. The timed quotient representation T20 includes one zero-divisor padding slot and counts $64 + 64$, giving 1193. This is an accounting difference, not a different correctness claim or a new timing experiment. The other elementary functions have no encrypted timings for the domains listed here; use their saved tables and finite-domain checks before making implementation-performance claims.

6 Order statistics: structural records

All entries on this page have domain $[8]^6$, with 262144 records in a direct table. Following the original study, write the sorted inputs with zero-based indices, $z_0 \le \cdots \le z_5$. The comparison-network constructions have the recorded costs below. No encrypted benchmark on this original domain is supplied; the ternary-input timings cannot be transferred to it.

The example column uses $(0, 1, 2, 3, 4, 5)$. "Calls" again means abstract unary-LUT evaluations.

Function	Definition	Example	Records	Calls
O20 Maximum	z_5	5	75	5
O21 Minimum	z_0	0	75	5
O22 Lower median	z_2	2	180	12
O23 Upper median	z_3	3	180	12
O24 Second smallest value	z_1	1	180	12
O25 Second largest value	z_4	4	180	12
O26 Range	$z_5 - z_0$	5	105	7
O27 Interquartile range	$z_3 - z_1$	2	180	12
O28 Sum of two largest values	$z_5 + z_4$	9	180	12
O29 Sum of two smallest values	$z_0 + z_1$	1	180	12
O30 Sum of three largest values	$z_3 + z_4 + z_5$	12	180	12
O31 Sum of middle four values	$z_1 + z_2 + z_3 + z_4$	10	105	7
O32 Central gap	$z_3 - z_2$	1	180	12
O33 Median absolute deviation	$\mathrm{med}_{\mathrm{low}}(\lvert x_i - z_2\rvert)$	1	450	30
O34 Count near lower median	$\sum_i \mathbf{1}[\lvert x_i - z_2\rvert \le 1]$	3	270	18

The stored full-sorting construction uses a twelve-comparator network. Range and the sum of the middle four values use a seven-comparator maximum/minimum procedure. MAD includes two sorting operations and six absolute-difference tables. These are the existing program's constructions; no optimality of the comparator count is claimed.

These examples demonstrate different ways to combine small tables. They are not all represented by one application of $Q(\sum_i p_i(x_i))$, and their logical record counts use the multistep accounting described on page 1. The same table can be invoked more than once; the original accounting conservatively accumulates those evaluations.

The CSV preserves the comparison routes and alternative logical counts from the original study. Those alternatives are specific constructions, not a complete search over all possible encrypted implementations. No abstract-call count in this section should be read as a measured PBS count or converted directly into a running time.

7 Histogram statistics: structural records

All entries on this page have domain $[5]^8$, with 390625 records in a direct table. Let $c_v = \#\{i : x_i = v\}$, and let $c_{[1]} \geq c_{[2]}$ denote the two largest frequencies, including zero frequencies. Accounting includes 200 records for constructing all five counts, followed by count-table evaluations or comparisons.

The example input is $(0, 0, 0, 1, 1, 2, 3, 4)$, whose histogram is $(c_0, c_1, c_2, c_3, c_4) = (3, 2, 1, 1, 1)$.

Function	Definition	Example	Records	Calls
O35 Mode (smallest tie)	$\min \arg\max_v c_v$	0	268	44
O36 Distinct-value count	$\sum_v \mathbf{1}[c_v > 0]$	5	245	45
O37 Gap between two largest frequencies	$c_{[1]} - c_{[2]}$	1	353	49
O38 Modal frequency	$\max_v c_v$	3	268	44
O39 Singleton count	$\sum_v \mathbf{1}[c_v = 1]$	3	245	45
O40 Values occurring at least twice	$\sum_v \mathbf{1}[c_v \geq 2]$	2	245	45
O41 Values occurring exactly twice	$\sum_v \mathbf{1}[c_v = 2]$	1	245	45
O42 Values occurring at least three times	$\sum_v \mathbf{1}[c_v \geq 3]$	1	245	45
O43 Minimum positive frequency	$\min\{c_v : c_v > 0\}$	1	313	49
O44 Range of positive frequencies	$\max_v c_v - \min\{c_v : c_v > 0\}$	2	381	53
O45 Number of tied modes	$\sum_v \mathbf{1}[c_v = \max_u c_u]$	1	353	49

These entries broaden the set of constructions available for reuse. They do not imply compression for arbitrary input counts or alphabet sizes, nor that every listed construction can be replaced by a single-layer additive representation. Other candidates, rows not retained by the original comparison criterion and stored repeat checks remain in the evidence files. They are not counted here as additional supported claims.

7.1 Limits to retain when reusing the catalogue

- A finite-domain check supports the stated domain. High-precision numerical checks of transcendental expressions do not establish a theorem over all real inputs.
- Structural compression is a count of logical records under a specified convention. It does not establish smaller physical buffers, fewer encrypted operations or shorter elapsed time.
- The measured results describe the listed hardware, programs, encodings and parameters. They do not establish an absolute ordering at unified security and failure probability.
- Correct outputs in the stored runs are an observed result, not a formal failure-probability bound. In particular, the changed BBR quotient parameters have no renewed failure calibration.
- Slower measured configurations remain included. Absence of a latency advantage does not make a function unrepresentable.

8 Finding and reproducing the records

8.1 Files in this directory

`catalog.csv` The complete 74-row index. All numerical values retain their stored precision. The PDF rounds elapsed-time means to two decimals for readability.

`evidence/current_summaries/` Saved timing summaries, function definitions and plaintext verification outputs. The full inputs and per-evaluation logs are under `experiments/` at repository root.

`evidence/original_study/` Source scripts, all saved CSV/JSON outputs and repeat-check records for the structural catalogue. These support O01–O45; they are not encrypted timing records for the paper's final comparison tables.

`evidence/Application_function_original.pdf` The original English structural catalogue, preserved unchanged for provenance. Its old release-status statements and directory names are historical. The current README and reproduction guide describe the distributed code.

The root `TABLE_INDEX.csv` links reported measured cells to their code, parameter files, inputs, raw logs and summaries. It is the entry point for reconstructing the final reported tables. The repository's `archive/historical_results/` is separately labelled: historical records are not used for final reported results.

8.2 Program locations

Paths below are relative to repository root. The reproduction guide in `docs/` gives environment setup and the complete commands.

- Our small-domain and count programs: `experiments/ours_small/ours/src/bin/functions_checked.rs`; six-ternary-input program: `experiments/ours_large/ours/src/bin/functions_checked.rs`.
- BBR statistics: `experiments/bbr/source/HLUT-rs/src/bin/`, including `matched_functions.rs` and `matched_small_functions.rs`. The corrected quotient driver is `matched_division_pbs15x2.rs`.
- Refined-LHE statistics: `experiments/refined_statistics/` and `experiments/refined_small/`, each under `source/refined-tfhe-lhe/benches/bench_functions.rs`.
- Meta-PBS statistics: `experiments/meta_statistics/source/META-FBS/cmd/dccextended/main.go` and `experiments/meta_small/source/META-FBS/cmd/dccsmall/main.go`.
- Quotient drivers: `experiments/division_t8/source/` for four $t = 8$ methods; `experiments/bbr_division/source/` for BBR $t = 8, 32$. Their adjacent input, result and summary directories contain the saved records.

8.3 Checking saved records and rebuilding this document

From `functions/`, the following first command checks the structural study's stored records; it does not rerun its function enumeration. The two subsequent commands rebuild this PDF from its English source using a standard LaTeX installation.

```
python evidence/original_study/verify_records.py
pdflatex -interaction=nonstopmode -halt-on-error \
  Function_Catalogue_and_Verification_Records.tex
pdflatex -interaction=nonstopmode -halt-on-error \
  Function_Catalogue_and_Verification_Records.tex
```

To rerun the original finite-domain study, use `run_experiments.py` and `compare_intermediate_routes.py` inside `evidence/original_study/`. They enumerate functions and write results; run them in a separate working copy to preserve the supplied evidence. Encrypted benchmarks likewise require the documented dependencies and parameters. This catalogue was assembled from stored records; its preparation did not rerun those experiments.