

The `tocbibind` package*

Author: Peter Wilson, Herries Press

Maintainer: Will Robertson

`will dot robertson at latex-project dot org`

2010/10/13

Abstract

The `tocbibind` package can be used to add document elements like a bibliography or an index to the Table of Contents. The package is designed to work with the four standard `book`, `report`, `article` and `proc` classes, and to a limited extent with the `ltxdoc` class. Results with other classes may be problematical. The package has been tested with the `tocloft` package, but has not been tested with other packages that change the definitions of the `\chapter*` or `\section*` commands.

Contents

1	Introduction	1
2	The <code>tocbibind</code> package	2
2.1	Numbering the List of Figures, etc.	3
2.2	Page styles	4
2.3	Package Defined Listof...	5
2.4	Abstracts	6
3	The package code	6

1 Introduction

Questions about adding the bibliography to the Table of Contents seem to pop up fairly regularly on the `comp.text.tex` newsgroup.

The `tocbibind` package provides a solution for automatically inserting references to a bibliography or an index, or other headed document elements into the Table of Contents. (`tocbibind` is meant to be shorthand for ‘Table of Contents, Bibliography, Index, etc’). Portions of the package were developed as part of a class and package bundle for typesetting ISO standards [Wil96]. This manual is typeset according

*This file (`tocbibind.dtx`) has version number v1.5k, last revised 2010/10/13.

to the conventions of the \LaTeX DOCSTRIP utility which enables the automatic extraction of the \LaTeX macro source files [GMS94].

Section 2 describes the usage of the package. Commented source code for the package is in Section 3.

2 The `tocbibind` package

The `tocbibind` package enables the titles of the Table of Contents, the List of Figures, the List of Tables, the Bibliography and the Index all to be added to the Table of Contents. By default, all of these document elements, if they exist, will be incorporated into the Table of Contents (ToC for short). Package options are available to switch off any of these inclusions.

- `notbib` Disables the inclusion of the Bibliography.
- `notindex` Disables the inclusion of the Index (inclusion of the Index of an `ltxdoc` class document is permanently disabled).
- `nottoc` Disables the inclusion of the ToC.
- `notlot` Disables the inclusion of the List of Tables.
- `notlof` Disables the inclusion of the List of Figures.
- `chapter` Use chapter-level headings, if possible.
- `section` Use section-level headings, if possible.
- `numbib` Number the Bibliography heading (default is no number).
- `numindex` Number the Index heading (default is no number).
- `other` Use a non-traditional heading command. This option effectively requires the use of the `\tocotherhead` command.
- `none` Disables everything.

The package is designed to work with the standard \LaTeX document classes `book`, `report`, `article`, `proc` and `ltxdoc` class (which is based to a large extent on the `article` class). In the `article`, `proc` and `ltxdoc` classes \LaTeX uses the `\section*` heading style for the bibliography etc., while for the other two classes it uses the `\chapter*` heading style. `tocbibind` honours these conventions. However, if the package is used with another class (perhaps with a class for typesetting theses which has different conventions), then the `chapter` or `section` options can be used to select the appropriate style (but the class must define `\chapter*` and `\@makeschapterhead`, or `\section*` respectively).

The standard classes, except for `ltxdoc`, have a feature whereby the height of the title for an index is at a different height than any other in a document (latex bug 3126). The `tocbibind` package disables this feature. The disablement has

the side effect that the `\columnseprule` and `\columnsep` lengths can be set via `\setlength` to alter the column separation and the thickness of a rule between the two columns in the index. The effect of using the `none` option is to limit any changes to the single one of disabling this standard feature.

`\tocotherhead` In the standard L^AT_EX classes the bibliography and index headings are either both defined in terms of the `\chapter*` command or in terms of the `\section*` command. The package assumes that any class, other than the standard classes already mentioned, will either use code from the standard classes for implementing the bibliography and other headings, or will use very similar code. Some classes (and maybe packages) change the names of the heading commands. One example that I am aware of uses `\clause` instead of `\section`, `\sclause` instead of `\subsection` and so on. If your document's headings are defined like this and the same heading level is used for the bibliography, etc., then you can use the `other` option and the `\tocotherhead{<headingname>}` command to cater for this. If your document uses `\clause` then put `\tocotherhead{clause}` in the preamble after loading the package. The package then assumes that the bibliography heading is defined in terms of `\clause*`.

If you use the `\tocotherhead` command, then it overrides any `chapter` or `section` option.

`\tocbibname` The package attempts to pick up the name for the Bibliography from the class definition. (Note that the `article` class and its derivatives stores the name text in the `\refname` whilst the `book` and `report` classes store the name in `\bibname`). This package uses `\tocbibname` to store the name of the bibliography.

`\setindexname` These commands set the heading texts for the index, ToC, list of tables and list of figures. When used with the three standard classes, the heading text is picked up from the `\indexname`, `\contentsname`, `\listtablename` and `\listfigurename` commands respectively. The heading texts can be changed by changing the standard commands, or by using `\setindexname{<name>}`, and similarly for the other headings. Thus, the following two lines of code have the same effect:

```
\renewcommand{\listfigurename}{Figures}
\setlofname{Figures}
```

Note that these commands replace the `\toc...name` commands that were in version 1.1.

2.1 Numbering the List of Figures, etc.

Some authors like, or are required, to number the Listof headings. Some commands are provided to simplify doing this.

`\simplechapter` In chaptered documents, the Listof headings are effectively typeset as `\chapter*{<name>}`.
`\simplechapterdelim` The natural way to get numbered headings would be to typeset them as `\chapter{<name>}` but this has the potential disadvantage that the word ‘Chapter’,
`\restorechapter` or equivalent, would be written before the heading, which is probably not what is required. The `\simplechapter[<name>]` command modifies any subsequent `\chapter` commands so that the result looks like that of `\chapter*` except

that the chapter number is put on the same line as the title and the value of `\simplechapterdelim` is typeset immediately after the number. By default, `\simplechapterdelim` is empty. If the optional $\langle name \rangle$ argument is present, the $\langle name \rangle$ is typeset before the number. For example:

```
\renewcommand{\simplechapterdelim}{:}
\simplechapter[Chap]
```

will result in `\chapter{First chapter}` being typeset like:

Chap 1: First chapter.

The `\restorechapter` command resets any subsequent `\chapter` commands to their default behaviour.

`\tocchapter` Internally, the Listof commands in the `tocbibind` package use `\toc@chapter` for typesetting the Listof headings in chaptered documents and `\toc@section` for non-chaptered documents. The `\tocchapter` command modifies the `\toc@chapter` command to use a ‘simple chapter’ heading. The `\tocsection` command modifies `\toc@section` to typeset using `\section` instead of `\section*`.

For example, to get a numbered List of Figures heading in a chaptered document, put the following in the preamble:

```
\renewcommand{\listoffigures}{\begingroup
\tocchapter
\tocfile{\listfigurename}{lof}
\endgroup}
```

while to get a numbered List of Tables in a non-chaptered document:

```
\renewcommand{\listoftables}{\begingroup
\tocsection
\tocfile{\listtablename}{lot}
\endgroup}
```

More generally, to number the Table of Contents in a (non-)chaptered document you can do:

```
\renewcommand{\tableofcontents}{\begingroup
\tocsection
\tocchapter
\tocfile{\contentsname}{toc}
\endgroup}
```

The `\begingroup \endgroup` pairing keeps the changes local.

2.2 Page styles

The package, by default, supports the standard `empty`, `plain`, and `headings` page styles. Other page styles, for example ones you specify yourself via the `fancyhdr` package, are indirectly supported.

As an example, assume that you are using the `fancyhdr` package and you use a `fancy` pagestyle in a `book/report` class document like:

```
\pagestyle{fancy}
\renewcommand{\chaptermark}[1]{\markboth{\thechapter.\ #1}{}}
```

then you will find that the chapter titles in headers are in normalcase but the ToC, etc., headers are still in uppercase.

`\tocetcmak` In this package, the marks for the ToC, LoF... headers are specified via the command `\tocetcmak{<head>}`. To match the `fancy` pagestyle this must be redefined, like:

```
\pagestyle{fancy}
\renewcommand{\chaptermark}[1]{\markboth{\thechapter.\ #1}{}}
\renewcommand{\tocetcmak}[1]{\markboth{#1}{}}
```

which will give normalcase headers for the ToC, LoF... As these are not normally numbered, it would be a misjudgement to try and get a non-existent chapter number into the header.

Documents with sections, but not chapters, can be treated in a similar manner by redefining `\tocetcmak` appropriately.

2.3 Package Defined Listof...

There are packages, such as `listings` and `ccaption`, that provide new Listof lists. These can be handled by the `tocbibind` package in a similar manner to the usual Listofs. Two examples are given below.

The `listings` package version 0.2 provides a `\lstlistoflistings` command to print a list of listings. The header name for this list is in `\lstlistingname` and the listing file has the extension `lol`. This can be treated just like the `\listoffigure`, etc., commands. To add the List of Listings header to the ToC do:

```
\renewcommand{\lstlistoflistings}{\begingroup
\tofile{\lstlistingname}{lol}
\endgroup}
```

and to number the Listof heading do:

```
\renewcommand{\lstlistoflistings}{\begingroup
\tocsection
\tocchapter
\tofile{\lstlistingname}{lol}
\endgroup}
```

The `ccaption` package enables authors to define new kinds of floats (together with their captions) and Listof for each new kind of float. The command to define a

new float is essentially `\newfloatlist{⟨fenv⟩}{⟨ext⟩}{⟨listname⟩}{⟨capname⟩}`, where `⟨fenv⟩` is the name of the new float environment and `⟨ext⟩` is the file extension for the listof file. The typesetting of the Listof listing is called by the command `\listoffenv`, where `fenv` is the name `⟨fenv⟩`. For example, a new float environment for diagrams could be defined via

```
\newfloatlist{diagram}{dia}{List of Diagrams}{Diagram}, and the Listof
called for by
\listofdiagram
```

In this case, to add the ‘List of Diagrams’ to the ToC it is necessary to define a new listof command, and use this in place of the `\listoffenv`. For the diagram example this could be (unnumbered):

```
\newcommand{\listofdia}{\begingroup
  \tocfile{List of Diagrams}{dia}
\endgroup}
```

and correspondingly for a numbered version:

```
\newcommand{\listofdia}{\begingroup
  \tocsection
  \tocchapter
  \tocfile{List of Diagrams}{dia}
\endgroup}
```

and then use `\listofdia` instead of `\listofdiagram`.

2.4 Abstracts

On rare occasions a publisher may want an abstract listed in the ToC. This package does not provide for that, partly because it is easier to do than the other headings. Just proceed along the lines below, where `section` might have to be `chapter`, and if you are using the `hyperref` package you have to use the `\phantomsection` macro.

```
\begin{abstract}
% \phantomsection % required if using hyperref
\addcontentsline{toc}{section}{\abstractname}
... rest of the abstract
```

3 The package code

Announce the name and version of the package, which requires L^AT_EX 2_ε.

```
1 ⟨*usc⟩
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{tocbibind}[2010/10/13 v1.5k extra ToC listings]
```

`\PRWPackageNote` These two commands write a package Note to the terminal and log file. Use
`\PRWPackageNoteNoLine` as `\PRWPackageNote{<package name>}{<note text>}`. The NoLine version does
not show the line number. The commands are intermediate between the kernel
`\PackageWarning` and `\PackageInfo` commands. I have provided them as other
packages (of mine) may also incorporate them. The code is based on `lterror.dtx`.

```

4 \providecommand{\PRWPackageNote}[2]{%
5   \GenericWarning{%
6     (#1)\@spaces\@spaces\@spaces\@spaces
7   }{%
8     Package #1 Note: #2%
9   }%
10 }
11 \providecommand{\PRWPackageNoteNoLine}[2]{%
12   \PRWPackageNote{#1}{#2\@gobble}%
13 }
14
```

`\@bibquit` We need to know what sectional divisions are supported.
`\if@bibchapter`

```

15 \newcommand{\@bibquit}{}
16 \newif\if@bibchapter
17 \@ifundefined{chapter}{}%
18 \@bibchapterfalse
19 \@ifundefined{section}{}%
20   \PackageWarning{tocbibind}%
21     {I don't recognize any sectional divisions.\MessageBreak
22     I hope you have used the 'other' option\MessageBreak
23     otherwise I'll ignore the package}
24   \renewcommand{\@bibquit}{\endinput}
25   }\PackageInfo{tocbibind}{The document has section divisions}}
26 }\@bibchaptertrue
27   \PackageInfo{tocbibind}{The document has chapter divisions}}
28
```

`\if@inltxdoc` This is used as a flag for the ltxdoc class. This has a particular kind of index that
I am not going to mess with.

```

29 \newif\if@inltxdoc
30 \@ifclassloaded{ltxdoc}{\@inltxdoctrue}{\@inltxdocfalse}
31
```

`\if@dotocbib` A set of booleans for deciding what is to go into the ToC. By default add every-
`\if@dotocind` thing.

```

32 \newif\if@dotocbib\@dotocbibtrue
33 \newif\if@dotocind\@dotocindtrue
34 \newif\if@dotocloc\@dotoclocfalse
35 \newif\if@dotoclot\@dotoclottrue
36 \newif\if@dotoclof\@dotocloftrue
37
```

```

    \if@donumbib A set of booleans for deciding whether or not to produce numbered headings
    \if@donumindex (default is to do unnumbered headings).
38 \newif\if@donumbib\@donumbibfalse
39 \newif\if@donumindex\@donumindexfalse

\if@dot@cb@bsection If TRUE, use a section heading for the bibliography no matter what the main
document divisions are.
40 \newif\if@dot@cb@bsection\@dot@cb@bsectionfalse
41

```

Now we can do the options. Most of them are easy.

```

42 \DeclareOption{section}{\@bibchapterfalse}
43 \DeclareOption{notbib}{\@dotocbibfalse}
44 \DeclareOption{notindex}{\@dotocindfalse}
45 \DeclareOption{nottoc}{\@dotoctocfalse}
46 \DeclareOption{notlot}{\@dotoclotfalse}
47 \DeclareOption{notlof}{\@dotocloffalse}
48 \DeclareOption{numbib}{\@donumbibtrue}
49 \DeclareOption{numindex}{\@donumindextrue}
50

```

The `chapter` option needs to check whether or not the chapter heading commands are defined. If they are not, then go with the section level headings.

```

51 \DeclareOption{chapter}{%
52   \if@bibchapter\else
53     \PackageWarning{tocbibind}%
54       {Chapters are undefined, using section instead}
55   \fi}
56

```

The other option makes `\@bibquit` a no-op and cancels any chapter based processing.

```

57 \DeclareOption{other}{\renewcommand{\@bibquit}{}
58   \@bibchapterfalse}

```

The `none` option turns everything off.

```

59 \DeclareOption{none}{%
60   \@dotocbibfalse
61   \@dotocindfalse
62   \@dotoctocfalse
63   \@dotoclotfalse
64   \@dotocloffalse
65   \@donumbibfalse
66   \@donumindexfalse
67 }

```

Process the options now, and then quit if necessary.

```

68 \ProcessOptions\relax
69 \@bibquit
70

```


Issue a note about the heading style being used.

```
71 \if@bibchapter
72   \PRWPackageNoteNoLine{tocbibind}{Using chapter style headings, unless overridden}
73 \else
74   \PRWPackageNoteNoLine{tocbibind}{Using section or other style headings}
75 \fi
```

Ensure that the index is not processed if it is an ltxdoc class.

```
76 \if@inltxdoc \dotocindfalse \fi
77
```

`\@tocextra` `\@tocextra` is the internal command to store the heading command name.
`\tocotherhead` `\tocotherhead{<name>}` is the user command to set the heading command
`<name>` (without the backslash). The default is section.

```
78 \newcommand{\@tocextra}{section}
79 \newcommand{\tocotherhead}[1]{\renewcommand{\@tocextra}{#1}}
80
```

`\tocetcmak` Utility macros, as the code that they represent gets used several times over. They
`\prw@mkboth` deal with marking for page headers (code taken from `classes.dtx`), and adding
`\toc@section` starred sectional headings to the ToC.
`\toc@headstar` `\tocetcmak{<text>}` is the default mark code as called by sectional headings.

```
81 \newcommand{\tocetcmak}[1]{%
82   \@mkboth{\MakeUppercase{#1}}{\MakeUppercase{#1}}}
83 \prw@mkboth{<text>} is used later for the ToC headings.
84 \newcommand{\prw@mkboth}[1]{\tocetcmak{#1}}
```

`\toc@section{<sec>}{<text>}` is a generalised version of `\sec*{<text>}` which
also makes an entry of `<text>` into the ToC, where `<sec>` is the name of a sectional
division (with no backslash). `\toc@headstar{<sec>}{<text>}` is similar except that
it makes no entry into the ToC.

```
84 \newcommand{\toc@section}[2]{%
85   \@nameuse{#1}*{#2\prw@mkboth{#2}}
86   \addcontentsline{toc}{#1}{#2}}
87 \newcommand{\toc@headstar}[2]{%
88   \@nameuse{#1}*{#2}}
```

`\toc@chapter` `\toc@chapter{<text>}` is equivalent to `\chapter*{<text>}` except that it makes an
entry into the ToC.

Until version 1.5f the chapter part of the code was `\chapter*{#1\prw@mkboth{#1}}`.
On 2003/03/12 James Szinger¹ wrote that this failed for a bibliography in a two
column book; the page headings for the previous chapter continued through the
bibliography! James suggested that the mark part should be moved outside the
chapter part (as is now done). I have no idea why there should have been this
problem. As part of looking at it I even replaced the `\toc@chapter` as used in

¹szinger@lanl.gov

the `thebibliography` environment with the standard book class definition, which failed as well.

```
89 \newcommand{\toc@chapter}[1]{%
90   \chapter*{#1}\prw@mkboth{#1}
91   \addcontentsline{toc}{chapter}{#1}}
```

`\tocbibname` This holds the text for the Bibliography heading. We try and get the text from the class (either `\bibname` or `\refname`).

```
92 \ifx\bibname\undefined
93   \ifx\refname\undefined
94     \newcommand{\tocbibname}{References}
95   \else
96     \newcommand{\tocbibname}{\refname}
97   \fi
98 \else
99   \newcommand{\tocbibname}{\bibname}
100 \fi
```

`\setindexname` The remaining heading texts are simpler as we only need to check if their respective names are defined in the class. Note that these commands in version 1.2 have been changed from version 1.1 in order to integrate with the `tocloft` package (which operates with the `\contentsname` etc commands).

```
\settocbibname 101 \providecommand{\indexname}{Index}
102 \newcommand{\setindexname}[1]{\renewcommand{\indexname}{#1}}
103 \providecommand{\contentsname}{Contents}
104 \newcommand{\settocname}[1]{\renewcommand{\contentsname}{#1}}
105 \providecommand{\listtablename}{List of Tables}
106 \newcommand{\setlotname}[1]{\renewcommand{\listtablename}{#1}}
107 \providecommand{\listfigurename}{List of Figures}
108 \newcommand{\setlofname}[1]{\renewcommand{\listfigurename}{#1}}
109 \newcommand{\settocbibname}[1]{\renewcommand{\tocbibname}{#1}}
```

The rest is just hacking the various environments and commands from `classes.dtx`.

Following a suggestion by Donald Arseneau (CTT, ‘Re: memoir, natbib, and chapterbib’, 9 Jan 2003), use `\bibsection` as a hook into `thebibliography` for the style of the heading.

`\t@cb@bchapsection` Internal macros holding the heading for `thebibliography`.

```
\t@cb@bsection 110 \newcommand{\t@cb@bchapsec}{%
111   \if@bibchapter
112     \if@donumbib
113       \chapter{\tocbibname}%
114     \else
115       \toc@chapter{\tocbibname}%
116   \fi
117 \else
118   \if@donumbib
```

```

119     \@nameuse{\@tocextra}{\tocbibname}%
120     \else
121     \toc@section{\@tocextra}{\tocbibname}%
122     \fi
123 \fi}
124 \newcommand{\t@cb@bsection}{%
125     \if@donumbib
126     \@nameuse{\@tocextra}{\tocbibname}%
127     \else
128     \toc@section{\@tocextra}{\tocbibname}%
129     \fi}
130

```

Redefine `thebibliography`, but only if requested. Take care that the `natbib` package has not already modified the environment, noting that `natbib` defines and uses `\bibsection`.

```

131 \if@dotocbib
132     \@ifpackageloaded{natbib}{}{% natbib not loaded

```

The `natbib` package has not been used (yet), so go ahead and change the environment.

```

\bibsection Macro holding heading for thebibliography.
133     \newcommand{\bibsection}{\t@cb@bchapsec}

```

`thebibliography`

```

134     \renewenvironment{thebibliography}[1]{%
135         \bibsection
136         \begin{thebibitemlist}{#1}}{\end{thebibitemlist}}

```

`thebibitemlist` Just as a matter of style, I have extracted the list making code from the definition of the `thebibliography`. It might also make it easier for someone to change the list environment. The code is a straight copy from `classes.dtx`.

```

137 \newenvironment{thebibitemlist}[1]{
138     \list{\@biblabel{\@arabic{c@enumiv}}}%
139         {\settowidth\labelwidth{\@biblabel{#1}}%
140         \leftmargin\labelwidth
141         \advance\leftmargin\labelsep
142         \@openbib@code
143         \usecounter{enumiv}%
144         \let\p@enumiv\empty
145         \renewcommand\theenumiv{\@arabic{c@enumiv}}}%
146     \sloppy
147     \clubpenalty4000
148     \@clubpenalty \clubpenalty
149     \widowpenalty4000%
150     \sfcode'\.\@m}
151 {\def\@noitemerr
152     {\@latex@warning{Empty 'thebibliography' environment}}}%

```

```

153     \endlist}
154
\sectionbib The chapterbib package defines a macro \sectionbib which, if its sectionbib
option is used, it calls at the beginning of the document to fiddle with the
thebibliography environment (but it doesn't work when it is renewed as above).
We need to disable the macro because we do our own fiddling
155 \ifpackagewith{chapterbib}{sectionbib}%
156   {\renewcommand{\sectionbib}[2]{}}%
157   {}
158
This is the end of \if@dotocbib.
159 \fi
160
At the end of the preamble we have to check if the natbib and/or chapterbib
packages have been loaded after the tocibind package. If this is the case, we have
to make sure that we have control with respect to their sectionbib options.
161 \AtBeginDocument{%
162   \ifpackagewith{natbib}{sectionbib}{\dot@cb@bsectiontrue}{}
If the chapterbib package was loaded before tocibind we have already killed
\sectionbib. If chapterbib has been loaded afterwards we must kill \sectionbib
now before it gets used.
163   \ifpackagewith{chapterbib}{sectionbib}%
164     {\dot@cb@bsectiontrue
165      \ifundefined{sectionbib}{}{\def\sectionbib#1#2{}}}%
166     {}
167
Lastly, use our definition of \bibsection for the thebibliography environment.
168 \if@dotocbib
169   \if@dot@cb@bsection
170     \renewcommand{\bibsection}{\t@cb@bsection}%
171   \else
172     \renewcommand{\bibsection}{\t@cb@bchapsec}%
173   \fi
174 \fi
This is the end of \AtBeginDocument
175 }
176
theindex In an earlier version of this package, for reasons that I didn't understand, I had to
add/remove some vertical space around the Index heading to make its height match
other chapter/section headings. In an unrelated thread on the comp.text.tex
newsgroup, Donald Arseneau pointed out that that this effect was a known fea-
ture of the standard classes and recorded as latex bug 3126, and was caused by
misplaced topskips. The following removes this feature for all except the doc class.

```

The first bit of code is a copy from `classes.dtx`.

```

177 \if@inltxdoc\else
178   \renewenvironment{theindex}%
179     {\if@twocolumn
180       \@restonecolfalse
181     \else
182       \@restonecoltrue
183     \fi
184   \if@bibchapter
185     \if@donumindex
186       \refstepcounter{chapter}
187       \twocolumn[\vspace*{2\topskip}%
188         \@makechapterhead{\indexname}]]%
189       \addcontentsline{toc}{chapter}{\protect\numberline{\thechapter}\indexname}
190       \chaptermark{\indexname}
191     \else
192       \if@dotocind
193         \twocolumn[\vspace*{2\topskip}%
194           \@makeschapterhead{\indexname}]]%
195         \prw@mkboth{\indexname}
196         \addcontentsline{toc}{chapter}{\indexname}
197       \else
198         \twocolumn[\vspace*{2\topskip}%
199           \@makeschapterhead{\indexname}]]%
200         \prw@mkboth{\indexname}
201       \fi
202     \fi
203   \else
204     \if@donumindex
205       \twocolumn[\vspace*{-1.5\topskip}%
206         \@nameuse{\@tocextra}{\indexname}]]%
207       \csname \@tocextra mark\endcsname{\indexname}
208     \else
209       \if@dotocind
210         \twocolumn[\vspace*{-1.5\topskip}%
211           \toc@headstar{\@tocextra}{\indexname}]]%
212         \prw@mkboth{\indexname}
213         \addcontentsline{toc}{\@tocextra}{\indexname}
214       \else
215         \twocolumn[\vspace*{-1.5\topskip}%
216           \toc@headstar{\@tocextra}{\indexname}]]%
217         \prw@mkboth{\indexname}
218       \fi
219     \fi
220   \fi

```

Now we are back to the original code.

```

221 \thispagestyle{plain}\parindent\z@
222 \parskip\z@ \@plus .3\p@\relax
223 \let\item\@idxitem}
224 {\if@restonecol\onecolumn\else\clearpage\fi}
225 \fi
226

```

`\toc@start` These two macros deal with the start and finish of the `\tableofcontents` and `\toc@finish` friends by adjusting the column settings if need be.

```

227 \newcommand{\toc@start}{%
228 \if@bibchapter
229 \if@twocolumn
230 \@restonecoltrue\onecolumn
231 \else
232 \@restonecolfalse
233 \fi
234 \fi}
235
236 \newcommand{\toc@finish}{%
237 \if@bibchapter
238 \if@restonecol\twocolumn\fi
239 \fi}

```

`\tocfile` The code for `\tableofcontents`, `\listoftables` and `\listoffigures` is virtually identical in each case, except for the heading text. `\tocfile` embodies the common code. This is virtually a parameterized copy from `classes.dtx`, except that it handles the differences between the `article` class and the other two, and incorporates the code for additions to the ToC. It is a useful hook if any other package wants to extend `tocbibind` for other kinds of listings.

The command is `\tocfile{<head-text>}{<file-extension>}`, where `<head-text>` is the heading (e.g., List of Figures) and `<file-extension>` is the file extension (e.g., `lof`).

```

240 \newcommand{\tocfile}[2]{%
241 \toc@start
242 \if@bibchapter
243 \toc@chapter{#1}
244 \else
245 \toc@section{\@tocextra}{#1}
246 \fi

```

And finish up with a parameterized call to start the listing and tidy up.

```

247 \@starttoc{#2}
248 \toc@finish}
249

```

`\tableofcontents` If requested, we redefine this command, using `\tocfile` to do all the work for us.

```

250 \if@dotoc
251   \renewcommand{\tableofcontents}{%
252     \tocfile{\contentsname}{toc}
253   }
254 \fi
255
\listoftables This is almost identical to the code for \tableofcontents
256 \if@dotoc
257   \renewcommand{\listoftables}{%
258     \tocfile{\listtablename}{lot}
259   }
260 \fi
261
\listoffigures This is almost identical to the code for \tableofcontents
262 \if@dotoc
263   \renewcommand{\listoffigures}{%
264     \tocfile{\listfigurename}{lof}
265   }
266 \fi
267
\simplechapter The \simplechapter command modifies the \@makechapterhead command to
\restorechapter result in an appearance akin to \@makeschapterhead, and is based on the latter.
\simplechapterdelim The \restorechapter command restores everything back to its original state.
The value of \simplechapterdelim is appended to the chapter number before
the title text.
268 \newcommand{\simplechapter}[1][\@empty]{%
269   \let\@tbiold@makechapterhead\@makechapterhead
270   \renewcommand{\@makechapterhead}[1]{%
271     \vspace*{50\p@}%
272     {\parindent \z@ \raggedright
273       \normalfont
274       \interlinepenalty\@M
275       \Huge\bfseries #1\space\thechapter\simplechapterdelim\space
276       ##1\par\nobreak
277       \vskip 40\p@
278     }}
279 }
280 \newcommand{\restorechapter}{%
281   \@ifundefined{tbiold@makechapterhead}{}%
282   {\let\@makechapterhead\@tbiold@makechapterhead}
283 }
284 \newcommand{\simplechapterdelim}{}
285
\tocchapter These two commands modify the \toc@chapter and \toc@section commands to
\tocsection make numbered Listof headings.

```

```

286 \newcommand{\tocchapter}{%
287   \providecommand{\@makechapterhead}{}
288   \simplechapter
289   \renewcommand{\toc@chapter}[1]{\chapter{##1}}
290 }
291 \newcommand{\tocsection}{%
292   \renewcommand{\toc@section}[2]{\@nameuse{##1}{##2}}
293 }
294

```

The end of this package.

```
295 \</usc>
```

References

- [GMS94] Michel Goossens, Frank Mittelbach, and Alexander Samarin. *The LaTeX Companion*. Addison-Wesley Publishing Company, 1994.
- [Wil96] Peter R. Wilson. *LaTeX for standards: The LaTeX package files user manual*. NIST Report NISTIR, June 1996.

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
\@bibchapterfalse	18, 42, 58	\@dotocloffalse . 47, 64
\@bibchaptertrue	26	\@dotoclofftrue 36
\@biblabel	138, 139	\@dotoclotfalse . 46, 63
\@bibquit	<u>15</u> , 57, 69	\@dotoclottrue 35
\@clubpenalty	148	\@dotocloctofalse . 45, 62
\@donumbibfalse	38, 65	\@dotocloctottrue 34
\@donumbibtrue	48	\@idxitem 223
\@donumindexfalse	39, 66	\@ifclassloaded 30
\@donumindextrue	49	\@ifpackageloaded . 132
\@dot@cb@bsectionfalse	40	\@ifpackagewith 155, 162, 163
\@dot@cb@bsectiontrue	162, 164	\@ifundefined 17, 19, 165, 281
\@dotocbibfalse	43, 60	\@inltxdocfalse 30
\@dotocbibtrue	32	\@inltxdoctrue 30
\@dotocindfalse	44, 61, 76	\@latex@warning 152
\@dotocindtrue	33	\@makechapterhead 188, 269, 270, 282, 287
		\@makeschapterhead 194, 199
		\@nameuse 85, 88, 119, 126, 206, 292
		\@noitemerr 151
		\@openbib@code 142
		\@restonecolfalse 180, 232
		\@restonecoltrue 182, 230
		\@spaces 6
		\@starttoc 247
		\@tbiold@makechapterhead 269, 282
		\@tocextra <u>78</u> , 119, 121, 126, 128, 206, 207, 211, 213, 216, 245

A		S	
\addcontentsline ..	86, 91, 189, 196, 213	\indexname ...	101, 102, 188–190, 194–196, 199, 200, 206, 207, 211–213, 216, 217
\AtBeginDocument ..	161	\interlinepenalty ..	274
B		\item	223
\bibname	92, 99	L	
\bibsection	133, 135, 170, 172	\labelsep	141
C		\labelwidth ...	139, 140
\c@enumiv	138, 145	\leftmargin ...	140, 141
\chapter ..	90, 113, 289	\listfigurename ...	107, 108, 264
\chaptermark	190	\listoffigures	262
\clearpage	224	\listoftables	256
\clubpenalty ..	147, 148	\listtablename	105, 106, 258
\contentsname	103, 104, 252	M	
\csname	207	\MakeUppercase	82
E		\MessageBreak ...	21, 22
\endcsname	207	N	
\endinput	24	\newif	16, 29, 32–36, 38–40
environments:		\normalfont	273
thebibitemlist ..	137	O	
thebibliography ..	134	\onecolumn ...	224, 230
theindex	177	P	
G		\p@enumiv	144
\GenericWarning	5	\PackageInfo	25, 27
H		\PackageWarning ..	20, 53
\Huge	275	\parindent ...	221, 272
I		\parskip	222
\if@bibchapter	15, 52, 71, 111, 184, 228, 237, 242	\providecommand ...	4, 11, 101, 103, 105, 107, 287
\if@donumbib	38, 112, 118, 125	\ProvidesPackage ...	3
\if@donumindex	38, 185, 204	\prw@mkboth ..	81, 90, 195, 200, 212, 217
\if@dot@cb@bsection	40, 169	\PRWPackageNote	4
\if@dot@cbib ..	32, 131, 168	\PRWPackageNoteNoLine	4, 72, 74
\if@dot@cind ..	32, 192, 209	R	
\if@dot@clof ...	32, 262	\refname	93, 96
\if@dot@clot ...	32, 256	\renewenvironment ..	134, 178
\if@dot@ctoc ...	32, 250	\restorechapter ..	3, 268
\if@inltxdoc ..	29, 76, 177	W	
\if@restonecol ..	224, 238	\widowpenalty	149
\if@twocolumn ..	179, 229		
		\sectionbib ...	155, 165
		\setindexname ...	3, 101
		\setlofname	3, 101
		\setlotname	3, 101
		\settocbibname ..	3, 101
		\settocname	3, 101
		\simplechapter	3, 268, 288
		\simplechapterdelim	3, 268
		T	
		\t@cb@bchapsec	110, 133, 172
		\t@cb@bchapsection ..	110
		\t@cb@bsection ..	110, 170
		\tableofcontents ..	250
		thebibitemlist (environment) ...	137
		thebibliography (environment) ...	134
		\thechapter ...	189, 275
		\theenumiv	145
		theindex (environment)	177
		\thispagestyle	221
		\toc@chapter	89, 115, 243, 289
		\toc@finish ...	227, 248
		\toc@headstar	81, 211, 216
		\toc@section ...	81, 121, 128, 245, 292
		\toc@start ...	227, 241
		\tocbibname ..	3, 92, 109, 113, 115, 119, 121, 126, 128
		\tocchapter	4, 286
		\tocetcmark	5, 81
		\tocfile	240, 252, 258, 264
		\tocotherhead	3, 78
		\tocsection	4, 286
		\topskip ..	187, 193, 198, 205, 210, 215
		\twocolumn	187, 193, 198, 205, 210, 215, 238