

Lecture 19

Plan: Hierarchical routing, Broadcast routing, multicast routing

Review:

Flooding: extremely robust

Distance Vector Routing: local, adaptive (slow convergence)

Link State Routing: Global, adaptive (routers are loaded with many jobs)

Topic today: more routing algorithms

1. Hierarchical Routing

Problem: If the network (we mean a single protocol network) grows too big, it costs too much to use LS Routing

Q:/ Why?


A:/

- too many information to send among routers
- too big a graph to build
- too much time to use the D's algorithm

Q:/ How to solve this problem?

A:/ Decompose the network hierarchically so

- each router only needs to know every other router inside its region
- each router only needs to know how to get to other regions instead of every host in other regions



(a)

Full table for 1A

Dest.	Line	Hops
1A	—	—
1B	1B	1
1C	1C	1
2A	1B	2
2B	1B	3
2C	1B	3
2D	1B	4
3A	1C	3
3B	1C	2
4A	1C	3
4B	1C	4
4C	1C	4
5A	1C	4
5B	1C	5
5C	1B	5
5D	1C	6
5E	1C	5

(b)

Hierarchical table for 1A

Dest.	Line	Hops
1A	—	—
1B	1B	1
1C	1C	1
2	1B	2
3	1C	2
4	1C	3
5	1C	4

(c)

the table of router A decreased from 17 entries to 7 entries

Q:/ What is the catch?

A:/ may result in an increase in the mean routing distances. e.g. 1A to 5C now has a larger distance

2. Broadcast Routing

Scenario: a packet needs to be delivered to many or all other hosts in a network


Q:/ Do we need a special routing algorithm for this? Why not just send a packet to every host as a single message?

A:/ Wastes too much bandwidth

Q:/ What can we do?

A:/

1. Flooding → again too much bandwidth
2. Multidestination routing
 - a. packet knows a list of destination addresses
 - b. When the packet arrives at a router, **the router determines a set of output ports** to forward the packet
 - c. It basically partition the destination set at the output lines
e.g. part a of the graph



If a host connected to I wants to send a packet to ABCDE

- I looks up its forwarding table ABCDE will all go through F
- I forward the packet to F
- F looks at its table and found that E will go through A and BC will go through D
- F generates a new copy of the packet addressing AE and forward it to A
- F generates another copy of the packet addressing BCD and forward it to D

3. Spanning tree

- a. Each router knows a spanning tree for the network
- b. when a packet arrives, the router sends it only on links which are part of the tree
e.g. part b of the previous graph

If I wants to send a packet to all other hosts

I → FHNJ

F → AD, J → GO, N → M

A → E, D → C, M → K

C → B, K → L

four hops and 14 extra packets

- c. Pro: bandwidth efficient

Con: each router has to know the spanning tree (good for Link state, not for distance vector)

Q:/ Can routers do broadcast routing without knowing the spanning tree AND we don't have to put a list of destination addresses in our packets?

A:/ yes

4. Reverse path forwarding

- a. When a packet arrives from some source S, the router looks to see what its forwarding table indicates for packets **destined for S**

- b. If the packet arrives on that link, forward it to all other links

- c. Otherwise, discard it.

e.g. part c of the previous figure

Assume that the preferred path of a router follows the tree (for ease of illustration) for the tree as before

If I has a packet to send to all other hosts

I → FHNJ

Q:/ Does this packet from I come from the destined port to I on router F?

A:/ Yes. → So this packet will be forwarded to all other ports of F

Similarly for H, N and J

F → AD, H → EK, N → MO, J → GO

A → E, D → CG, M → K, O → N, G → D

E → H, C → B, K → HL,

B → L, L → B

So 5 hops with 24 extra packets

Pro: Easy to implement and no need to know the sink tree; also no need to use sequence numbers to stop looping

3. Multicast Routing

Q:/ What is the difference between multicast and broadcast?

A:/ broadcast means send a packet to all hosts. Multicast means send a packet to all members of a multicast group

Need a protocol for managing group membership

Can use a spanning tree or reverse path forwarding for each group

Can also use addresses (IP multicast) → later this chapter