

Axiom

An FFmpeg Interface for Windows



Axiom UI generates command scripts to be interpreted and processed by multimedia encoder, FFmpeg, and streams analyzer, FFprobe.

It is portable and can be run from any location on the computer.

Convert, Cut, Resize multimedia with Lossless, Constant, and Variable Quality Modes.



FFmpeg is separate command-line software, developed and maintained at www.ffmpeg.org.

Axiom first checks Window's Environment Variables to see if FFmpeg is installed and uses that location. If not found, it looks for `ffmpeg.exe` & `ffprobe.exe` in `ffmpeg\bin\`, within its current folder.



Enable FFmpeg Through Command Prompt (optional)

Move FFmpeg folder to a location of your choice, such as `C:\Program Files\`.


- Control Panel → System and Security → System → Advanced system settings
- Advanced Tab → Environment Variables → System variables → Path
- Add `C:\Program Files\FFmpeg\bin\`
- Separate multiple paths with semicolon ;

Typing **ffmpeg** in Command Prompt will now execute without needing to specify a direct path.

Interface



Windows




Crop

Set the Crop Position and Aspect.

X is the position from the left.

Y is the position from the top.


Width & Height is the size of the cropped area.



Advanced Optimize

In the Options section, under Opt, select Advanced from the dropdown.

These options are only available for x264 and x265 codecs.



Log Console

This window displays all actions performed by the program. These same actions can be saved to an output.log file through the Configure Window.

Interface Settings

FFmpeg

The interface looks for ffmpeg.exe & ffprobe.exe in {Current Folder}\ffmpeg\bin\.

If you already have FFmpeg installed on your system, the included ffmpeg and ffprobe are not needed.

Custom compiled versions of FFmpeg may not work if they are missing certain codecs.

Browse / Output

Select a file to convert and choose a directory to output to.

If you do not choose Output, the default output directory will be the same as the input directory.

Batch

First check the Batch checkbox, then Browse for a folder to batch process the files within.

Auto

Attempts to copy the original bit-rate with 2 Pass encoding or uses acodec copy if input and output are the same format.

Copy

If Auto mode selected and input/output formats are the same, Copy will automatically activate in the Codec dropdown.

Lossless

Sets the format's correct lossless codec options or uses -crf 0, depending on format.

Video

Custom CRF Quality:

0 <----- 18 <----- 23 -----> 28 -----> 51

lossless better default worse worst

VP8/VP9:

Ultra: Bit-rate 4M + CRF 8

High: Bit-rate 2M + CRF 10

Med: Bit-rate 1.3M + CRF 14

Low: Bit-rate 600K + CRF 18

Sub: Bit-rate 250K + CRF 23

x264:

Ultra: CRF 18

High: CRF 23

Med: CRF 30

Low: CRF 37

Sub: CRF 45

x265:

Ultra: CRF 23

High: CRF 28

Med: CRF 35

Low: CRF 42

Sub: CRF 50

Theora:

Ultra: qscale 10

High: qscale 8

Med: qscale 6

Low: qscale 4

Sub: qscale 2

Video Bit-rate is measured in bytes, K or M. (e.g 3000000 or 3000K or 3M)

Audio

Default is Constant Bit-rate (CBR).

VBR enables a Variable Bit-rate equivalent to the CBR value selected in the Audio drop down list.

e.g. MP3: 320k (CBR) = V0 (VBR)

Track

If your video has multiple audio tracks, such as English or Japanese, you can select which one to use or keep all.

View the video properties through a media player to find the number of the track.

The default (auto) uses the first track or copies all tracks if you are converting to the same format.

Resize

Specify a custom Width and Height.


Typing "auto" (without quotes) in a text field will select the correct width or height to match.

Cut


Format must be 00:00:00.000

Hours:Minutes:Seconds.milliseconds (note the period instead of colon).

FFmpeg Command-line



```
ffmpeg -i "C:\Videos\input.mpg" -y  
-vcodec libvpx -b:v 3.5M -crf 8 -pix_fmt yuv420p -quality good -cpu-used 1  
-vf scale=-1:1080 -r 24  
-acodec libvorbis -q:a 9 -ar 48000 -af "volume=1.2"  
-map 0:v:0? -map 0:a:0? -sn -movflags faststart -ss 00:00:23.000 -to 00:01:05.000  
-threads 8 "C:\Videos\input.webm"
```



FFmpeg Batch Command-line

Change to Directory

```
cd "C:\Users\Videos\" &
```

Batch Process Filetype

```
for %f in (*.mpg) do ffprobe -i "C:\Users\Videos\%~f" -select_streams v:0 -show_entries format=bit_rate -v quiet -of csv="p=0" &
```

FFprobe File's Size

```
for /f "tokens=*" %S in ("ffprobe -i "C:\Users\Videos\%~f" -select_streams v:0 -show_entries format=size -v quiet -of csv=p=0") do (echo ) &
```

Set the Size Variable %S using a temp text file

```
(%S > tmp_size) & SET /p size= < tmp_size & del tmp_size &
```

Expand the Variable

```
for /F %S in ('echo %size%') do (echo %S) &
```

FFprobe File's Duration

```
for /f "tokens=*" %D in ("ffprobe -i "C:\Users\Videos\%~f" -select_streams v:0 -show_entries format=duration -v quiet -of csv=p=0") do (echo ) &
```

Set the Duration Variable %D using a temp text file

```
(%D > tmp_duration) & SET /p duration= < tmp_duration & del tmp_duration &
```

Remove Duration Decimals for DOS

```
for /f "tokens=1 delims=." %R in ('echo %duration%') do set duration=%R &
```

Expand the Variable

```
for /F %D in ('echo %duration%') do (echo %D) &
```

FFprobe File's Video Bit-rate

```
for /f "tokens=*" %V in ("ffprobe -i "C:\Users\Videos\%~f" -select_streams v:0 -show_entries format=bit_rate -v quiet -of csv=p=0") do (echo ) &
```

Set the Video Bit-rate %V using a temp text file

```
(%V > tmp_vBitrate) & SET /p vBitrate= < tmp_vBitrate & del tmp_vBitrate &
```

Expand the Variable

```
for /F %V in ('echo %vBitrate%') do (echo %V) &
```

If Video Variable = N/A, Calculate Bit-rate (((Filesize*8)/1000)/Duration)*1000

```
(if %V EQU N/A (set /a vBitrate=%S*8/1000/%D*1000) else (echo Video Bitrate Detected)) &
```

Expand the Variable

```
for /F %V in ('echo %vBitrate%') do (echo %V) &
```

FFprobe File's Audio Bit-rate

```
ffprobe -i "C:\Users\Videos\%~f" -select_streams a:0 -show_entries stream=bit_rate -v quiet -of csv="p=0" & for /f "tokens=*" %A in ("ffprobe -i "C:\Users\Videos\%~f" -select_streams a:0 -show_entries stream=bit_rate -v quiet -of csv=p=0") do (echo ) &
```

Set the Audio Bitrate %A using a temp text file

```
(%A > tmp_aBitrate) & SET /p aBitrate= < tmp_aBitrate & del tmp_aBitrate &
```

If Audio Variable = N/A, Default to 320k

```
for /F %A in ('echo %aBitrate%') do echo %A & (if %A EQU N/A (set aBitrate=320000)) &
```

Limit Audio Variable bit-rate to Output Format's maximum allowed bit-rate

```
for /F %A in ('echo %aBitrate%') do echo %A & (if %A gtr 400000 (set aBitrate=400000) else (echo Bitrate within AAC Limit of 400k)) &
```

Expand the Variable

```
for /F %A in ('echo %aBitrate%') do (echo %A) &
```

Start FFmpeg

```
ffmpeg -i "C:\Users\Videos\%~f" -y -vcodec libx264 -profile:v main -b:v %V -acodec aac -b:a %A -map 0:v:0? -map 0:a:0? -map 0:s:0? -strict experimental -vf scale="trunc(iw/2)*2:trunc(ih/2)*2" -threads 8 -pass 1 "C:\Users\Desktop\%~nf.mp4" & ffmpeg -i "C:\Users\Videos\%~f" -y -vcodec libx264 -profile:v main -b:v %V -acodec aac -b:a %A -map 0:v:0? -map 0:a:0? -map 0:s:0? -strict experimental -vf scale="trunc(iw/2)*2:trunc(ih/2)*2" -threads 8 -pass 2 "C:\Users\Desktop\%~nf.mp4"
```