

SAFETY DATA SHEET

Version 8.6 Revision Date 03/02/2024 Print Date 06/15/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Benzene for analysis EMPARTA® ACS

 Product Number
 : 1.07033

 Catalogue No.
 : 107033

 Brand
 : Millipore

 Index-No.
 : 601-020-00-8

 CAS-No.
 : 71-43-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis, Solvent

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose

under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225 Skin irritation (Category 2), H315 Eye irritation (Category 2A), H319

Germ cell mutagenicity (Category 1B), H340

Millipore - 1.07033

Page 1 of 14



Carcinogenicity (Category 1A), H350

Specific target organ toxicity - repeated exposure (Category 1), Blood, H372 Aspiration hazard (Category 1), H304

Pictogram

Long-term (chronic) aquatic hazard (Category 3), H412

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

rictograffi	
Signal Word	Danger
Hazard Statements	
H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs (Blood) through prolonged or
, _	repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
Precautionary Statements	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and
	understood.
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No
	smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe mist or vapors.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated
1303 1 1301 1 1333	clothing. Rinse skin with water/ shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes.
1303 1 1331 1 1330	Remove contact lenses, if present and easy to do. Continue
	rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
·	Table 111 2011 and the distribution of the control

In case of fire: Use dry sand, dry chemical or alcohol-resistant

Millipore - 1.07033



Page 2 of 14

P370 + P378

foam to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal

plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula : C6H6

Molecular weight : 78.11 g/mol CAS-No. : 71-43-2 EC-No. : 200-753-7 Index-No. : 601-020-00-8

Component	Classification	Concentration					
benzene							
	Flam. Liq. 2; Skin Irrit. 2; Eye Irrit. 2A; Muta. 1B; Carc. 1A; STOT RE 1; Asp. Tox. 1; Aquatic Chronic 3; H225, H315, H319, H340, H350, H372, H304, H412	<= 100 %					

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

Millipore - 1.07033

Page 3 of 14



4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

Millipore - 1.07033

Page 4 of 14

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

ingredients with workplace control parameters							
Component	CAS-No.	Value	Control	Basis			
			parameters				
benzene	71-43-2	TWA	0.5 ppm	USA. ACGIH Threshold Limit			
				Values (TLV)			
	Remarks	Leukemia					
		Substances for which there is a Biological Exposure Index					
		or Indices (see BEI® section)					
		Confirmed human carcinogen					
		Danger of cutaneous absorption					
		STEL	2.5 ppm	USA. ACGIH Threshold Limit			
				Values (TLV)			
		Leukemia					
		Substances for which there is a Biological Exposure Index					
		or Indices ((see BEI® section	on)			
		Confirmed human carcinogen					
		Danger of cutaneous absorption					

Millipore - 1.07033 Page 5 of 14



TWA	10 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
Z37.40-1969				
CEIL	25 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
Z37.40-1969				
Peak	50 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z-2		
Z37.40-1969				
See 1910.1028. See Table Z-2 for the limits applicable in the operations or sectors excluded in 1910.1028 The final benzene standard in 1910.1028 applies to all occupational exposures to benzene except some subsegments of industry where exposures are consistently under the action level (i.e., distribution and sale of fuels, sealed containers and pipelines, coke production, oil and gas drilling and production, natural gas processing, and the percentage exclusion for liquid mixtures); for the excepted subsegments, the benzene limits in Table Z-2 apply.				
TWA	0.1 ppm	USA. NIOSH Recommended Exposure Limits		
Potential Occupational Carcinogen See Appendix A				
ST	1 ppm	USA. NIOSH Recommended Exposure Limits		
Potential Occupational Carcinogen See Appendix A				

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: Viton®

Minimum layer thickness: 0.7 mm Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other

Millipore - 1.07033 Page 6 of 14



substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm Break through time: 10 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A-(P3)

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odorc) Odor Thresholddata availableNo data available

d) pH No data available

e) Melting point: 5.5 °C (41.9 °F)

f) Initial boiling point 80.1 °C 176.2 °F and boiling range

point/freezing point

g) Flash point -11 °C (12 °F) - DIN 51755 Part 1

h) Evaporation rate No data availablei) Flammability (solid, No data available

gas)

j) Upper/lower Upper explosion limit: 8.0 %(V) flammability or Lower explosion limit: 1.2 %(V)

explosive limits

k) Vapor pressure 100 hPa at 20 °C (68 °F)

I) Vapor density No data available



m) Density 0.88 g/cm3 at 20 °C (68 °F)

Relative density No data available

n) Water solubility ca.1.88 g/l at 23.5 °C (74.3 °F) - soluble

o) Partition coefficient: log Pow: 2.13 at 25 °C (77 °F) - Bioaccumulation is not

n-octanol/water expected., (ECHA)

p) Autoignition 498 °C (928 °F) at 1,013.5 hPa

temperature

q) Decomposition No data available

temperature

r) Viscosity 0.604 mm2/s at 25 °C (77 °F) -

s) Explosive properties No data available

t) Oxidizing properties none

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.3 Possibility of hazardous reactions

Exothermic reaction with:

halogens

Halogenated hydrocarbon

in the presence of:

Light metals

Risk of explosion with:

halogen-halogen compounds

Nitric acid

Boranes

Ozone

peroxi compounds

perchlorates

permanganic acid

perchloryl fluoride

Strong oxidizing agents

Chlorine

fluorides

uranium hexafluoride

Oxygen

liquid

Risk of ignition or formation of inflammable gases or vapours with:

chromium(VI) oxide



Fluorine
nitryl compounds
Oxygen
oxyhalogenic compounds
Violent reactions possible with:
mineral acids
sulfur

10.4 Conditions to avoid

Warming.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - > 2,000 mg/kg

(OECD Test Guideline 401)

Symptoms: Nausea

LD50 Oral - Rat - male and female - 3,002 mg/kg

(OECD Test Guideline 401)

Symptoms: Risk of aspiration upon vomiting., Aspiration may cause pulmonary edema and

pneumonitis.

Inhalation: No data available Symptoms: mucosal irritations

LD50 Dermal - Rabbit - 13,630 mg/kg

Remarks: (IUCLID) No data available

Skin corrosion/irritation

Skin - Rabbit Result: irritating

(OECD Test Guideline 404)

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Irritating to eyes. (OECD Test Guideline 405)

Remarks: (IUCLID)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Respiratory or skin sensitization

Maximization Test - Guinea pig



Result: negative

(OECD Test Guideline 406)

Germ cell mutagenicity

May cause genetic defects. Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster lung cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: Mutagenicity (mammal cell test): micronucleus.

Species: Mouse

Cell type: Bone marrow

Application Route: inhalation (vapor) Method: OECD Test Guideline 474

Result: positive

Carcinogenicity

May cause cancer. Positive evidence from human epidemiological studies.

IARC: 1 - Group 1: Carcinogenic to humans (benzene)

NTP: Known - Known to be human carcinogen (benzene)
OSHA: OSHA specifically regulated carcinogen (benzene)

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

- Blood

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Aspiration hazard

Aspiration may cause pulmonary edema and pneumonitis.

11.2 Additional Information

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 600 mg/kg

Millipore - 1.07033

Page 10 of 14

Nausea, Dizziness, Headache, narcosis, Inhalation of high concentrations of benzene may have an initial stimulatory effect on the central nervous system characterized by exhilaration, nervous excitation and/or giddiness, depression, drowsiness, or fatigue. The victim may experience tightness in the chest, breathlessness, and loss of consciousness. Tremors, convulsions, and death due to respiratory paralysis or circulatory collapse can occur in a few minutes to several hours following severe exposures. Aspiration of small amounts of liquid immediately causes pulmonary edema and hemorrhage of pulmonary tissue. Direct skin contact may cause erythema. Repeated or prolonged skin contact may result in drying, scaling dermatitis, or development of secondary skin infections. The chief target organ is the hematopoietic system. Bleeding from the nose, gums, or mucous membranes and the development of purpuric spots, pancytopenia, leukopenia, thrombocytopenia, aplastic anemia, and leukemia may occur as the condition progresses. The bone marrow may appear normal, aplastic or hyperplastic, and may not correlate with peripheral blood-forming tissues. The onset of effects of prolonged benzene exposure may be delayed for many months or years after the actual exposure has ceased., Blood disorders

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

After absorption of large quantities:

narcosis respiratory arrest Convulsions

Possible damages:

Damage to:

Liver Kidney Central nervous system

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish semi-static test LC50 - Oryzias latipes (Orange-red killifish) - > 100

mq/l - 96 h

(OECD Test Guideline 203)

Toxicity to daphnia and other aquatic

semi-static test EC50 - Daphnia magna (Water flea) - > 1,000 mg/l

invertebrates

(OECD Test Guideline 202)

semi-static test NOEC - Daphnia magna (Water flea) - > 1,000 mg/l

- 48 h

(OECD Test Guideline 202)

Millipore - 1.07033

4illiPDRe

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata (green algae) - >

1,000 mg/l - 72 h

(OECD Test Guideline 201)

static test NOEC - Pseudokirchneriella subcapitata (green algae) - >=

1,000 mg/l - 72 h

(OECD Test Guideline 201)

Toxicity to bacteria static test EC50 - activated sludge - > 1,000 mg/l - 3 h

(OECD Test Guideline 209)

Toxicity to flow-through test NOEC - Pimephales promelas (fathead minnow) -

fish(Chronic toxicity) 0.8 mg/l - 32 d

Remarks: (ECHA)

Toxicity to daphnia

semi-static test LC50 - Daphnia magna (Water flea) - > 100 mg/l -

and other aquatic 21 d

invertebrates(Chronic (OECD Test Guideline 211)

toxicity)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 96 % - Readily biodegradable.

(OECD Test Guideline 301F)

12.3 Bioaccumulative potential

Bioaccumulation Leuciscus idus (Golden orfe) - 3 d

- 0.05 mg/l(benzene)

Bioconcentration factor (BCF): 10

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Endangers drinking-water supplies if allowed to enter soil or water.

Discharge into the environment must be avoided.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

SECTION 14: Transport information

DOT (US)

UN number: 1114 Class: 3 Packing group: II

Proper shipping name: Benzene Reportable Quantity (RQ): 10 lbs Reportable Quantity (RQ): 10 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1114 Class: 3 Packing group: II EMS-No: F-

E, S-D

Proper shipping name: BENZENE

IATA

UN number: 1114 Class: 3 Packing group: II

Proper shipping name: Benzene

SECTION 15: Regulatory information

SARA 302 Components

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

benzene CAS-No. Revision Date 71-43-2 2007-07-01

Reportable Quantity D018 lbs

Massachusetts Right To Know Components

benzene CAS-No. Revision Date 71-43-2 2007-07-01

Pennsylvania Right To Know Components

benzene CAS-No. Revision Date 71-43-2 2007-07-01

Millipore - 1.07033

Page 13 of 14

Millipore SigMa

California Prop. 65 Components

, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.benzene

CAS-No. 71-43-2

Revision Date 2009-02-01

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.6 Revision Date: 03/02/2024 Print Date: 06/15/2024

