```
%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up


Switch>en
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#int vlan 1
Switch(config-if)#ip address 192.168.0.2 255.255.255.0
Switch(config-if)#no sh

Switch(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

Switch(config-if)#line vty 0 5
Switch(config-line)#pass 123
Switch(config-line)#login
Switch(config-line)#enable pass 123
Switch(config)#
%SYS-5-CONFIG_I: Configured from console by console
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>telnet 192.168.0.2
Trying 192.168.0.2 ...Open


User Access Verification

Password:
Switch>en
Password:
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname sw1
sw1(config)#ip domain name test
sw1(config)#crypto key generate rsa
The name for the keys will be: sw1.test
Choose the size of the key modulus in the range of 360 to 4096 for your
  General Purpose Keys. Choosing a key modulus greater than 512 may take
  a few minutes.

How many bits in the modulus [512]: 768
% Generating 768 bit RSA keys, keys will be non-exportable...[OK]

sw1(config)#ip version 2
*Mar 1 0:3:54.370: %SSH-5-ENABLED: SSH 1.99 has been enabled
                ^
% Invalid input detected at '^' marker.

sw1(config)#line vty 0 15
sw1(config-line)#transport input ssh
sw1(config-line)#exit
sw1(config)#exit
sw1#exit

[Connection to 192.168.0.2 closed by foreign host]
C:\>ssh -1 admin 192.168.0.2
Invalid Command.

C:\>
```