

The Red Hat newlib C Math Library

libm 2.5.0
December 2016

Steve Chamberlain
Roland Pesch
Red Hat Support
Jeff Johnston

Red Hat Support
sac@cygnus.com
pesch@cygnus.com
jjohnstn@redhat.com

Copyright © 1992, 1993, 1994-2004 Red Hat, Inc.

libm includes software developed at SunPro, a Sun Microsystems, Inc. business. Permission to use, copy, modify, and distribute this software is freely granted, provided that this notice is preserved.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, subject to the terms of the GNU General Public License, which includes the provision that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions.

1 Mathematical Functions (`math.h`)

This chapter groups a wide variety of mathematical functions. The corresponding definitions and declarations are in `math.h`. Two definitions from `math.h` are of particular interest.

1. The representation of infinity as a `double` is defined as `HUGE_VAL`; this number is returned on overflow by many functions. The macro `HUGE_VALF` is a corresponding value for `float`.
2. The structure `exception` is used when you write customized error handlers for the mathematical functions. You can customize error handling for most of these functions by defining your own version of `matherr`; see the section on `matherr` for details.

Since the error handling code calls `fputs`, the mathematical subroutines require stubs or minimal implementations for the same list of OS subroutines as `fputs`: `close`, `fstat`, `isatty`, `lseek`, `read`, `sbrk`, `write`. See Section “System Calls” in *The Red Hat newlib C Library*, for a discussion and for sample minimal implementations of these support subroutines.

Alternative declarations of the mathematical functions, which exploit specific machine capabilities to operate faster—but generally have less error checking and may reflect additional limitations on some machines—are available when you include `fastmath.h` instead of `math.h`.

1.1 Error Handling

There are four different versions of the math library routines: IEEE, POSIX, X/Open, or SVID. The version may be selected at runtime by setting the global variable `_LIB_VERSION`, defined in `math.h`. It may be set to one of the following constants defined in `math.h`: `_IEEE_`, `_POSIX_`, `_XOPEN_`, or `_SVID_`. The `_LIB_VERSION` variable is not specific to any thread, and changing it will affect all threads.

The versions of the library differ only in how errors are handled.

In IEEE mode, the `matherr` function is never called, no warning messages are printed, and `errno` is never set.

In POSIX mode, `errno` is set correctly, but the `matherr` function is never called and no warning messages are printed.

In X/Open mode, `errno` is set correctly, and `matherr` is called, but warning message are not printed.

In SVID mode, functions which overflow return `3.40282346638528860e+38`, the maximum single-precision floating-point value, rather than infinity. Also, `errno` is set correctly, `matherr` is called, and, if `matherr` returns 0, warning messages are printed for some errors. For example, by default `'log(-1.0)'` writes this message on standard error output:

```
log: DOMAIN error
```

The library is set to X/Open mode by default.

The aforementioned error reporting is the supported Newlib libm error handling method. However, the majority of the functions are written so as to produce the floating-point exceptions (e.g. "invalid", "divide-by-zero") as required by the C and POSIX standards, for floating-point implementations that support them. Newlib does not provide the floating-point exception access routines defined in the standards for `fenv.h`, though, which is why they are considered unsupported. It is mentioned in case you have separately-provided access routines so that you are aware that they can be caused.

1.2 Standards Compliance And Portability

Most of the individual function descriptions describe the standards to which each function complies. However, these descriptions are mostly out of date, having been written before C99 was released. One of these days we'll get around to updating the rest of them. (If you'd like to help, please let us know.)

"C99" refers to ISO/IEC 9899:1999, "Programming languages-C". "POSIX" refers to IEEE Standard 1003.1. POSIX[®] is a registered trademark of The IEEE.

1.3 `acos`, `acosf`—arc cosine

Synopsis

```
#include <math.h>
double acos(double x);
float acosf(float x);
```

Description

`acos` computes the inverse cosine (arc cosine) of the input value. Arguments to `acos` must be in the range -1 to 1 .

`acosf` is identical to `acos`, except that it performs its calculations on `floats`.

Returns

`acos` and `acosf` return values in radians, in the range of 0 to π .

If x is not between -1 and 1 , the returned value is NaN (not a number) the global variable `errno` is set to `EDOM`, and a **DOMAIN error** message is sent as standard error output.

You can modify error handling for these functions using `matherr`.

1.4 acosh, acoshf—inverse hyperbolic cosine

Synopsis

```
#include <math.h>
double acosh(double x);
float acoshf(float x);
```

Description

acosh calculates the inverse hyperbolic cosine of *x*. **acosh** is defined as

$$\ln\left(x + \sqrt{x^2 - 1}\right)$$

x must be a number greater than or equal to 1.

acoshf is identical, other than taking and returning floats.

Returns

acosh and **acoshf** return the calculated value. If *x* less than 1, the return value is NaN and **errno** is set to **EDOM**.

You can change the error-handling behavior with the non-ANSI **matherr** function.

Portability

Neither **acosh** nor **acoshf** are ANSI C. They are not recommended for portable programs.

1.5 `asin`, `asinf`—arc sine

Synopsis

```
#include <math.h>
double asin(double x);
float asinf(float x);
```

Description

`asin` computes the inverse sine (arc sine) of the argument `x`. Arguments to `asin` must be in the range -1 to 1 .

`asinf` is identical to `asin`, other than taking and returning floats.

You can modify error handling for these routines using `matherr`.

Returns

`asin` returns values in radians, in the range of $-\pi/2$ to $\pi/2$.

If `x` is not in the range -1 to 1 , `asin` and `asinf` return NaN (not a number), set the global variable `errno` to `EDOM`, and issue a `DOMAIN error` message.

You can change this error treatment using `matherr`.

1.6 asinh, asinhf—inverse hyperbolic sine

Synopsis

```
#include <math.h>
double asinh(double x);
float asinhf(float x);
```

Description

asinh calculates the inverse hyperbolic sine of *x*. **asinh** is defined as

$$\text{sign}(x) \times \ln\left(|x| + \sqrt{1 + x^2}\right)$$

asinhf is identical, other than taking and returning floats.

Returns

asinh and **asinhf** return the calculated value.

Portability

Neither **asinh** nor **asinhf** are ANSI C.

1.7 `atan`, `atanf`—arc tangent

Synopsis

```
#include <math.h>
double atan(double x);
float atanf(float x);
```

Description

`atan` computes the inverse tangent (arc tangent) of the input value.

`atanf` is identical to `atan`, save that it operates on `floats`.

Returns

`atan` returns a value in radians, in the range of $-\pi/2$ to $\pi/2$.

Portability

`atan` is ANSI C. `atanf` is an extension.

1.8 atan2, atan2f—arc tangent of y/x

Synopsis

```
#include <math.h>
double atan2(double y, double x);
float atan2f(float y, float x);
```

Description

atan2 computes the inverse tangent (arc tangent) of y/x . **atan2** produces the correct result even for angles near $\pi/2$ or $-\pi/2$ (that is, when x is near 0).

atan2f is identical to **atan2**, save that it takes and returns **float**.

Returns

atan2 and **atan2f** return a value in radians, in the range of $-\pi$ to π .

You can modify error handling for these functions using **matherr**.

Portability

atan2 is ANSI C. **atan2f** is an extension.

1.9 `atanh`, `atanhf`—inverse hyperbolic tangent

Synopsis

```
#include <math.h>
double atanh(double x);
float atanhf(float x);
```

Description

`atanh` calculates the inverse hyperbolic tangent of `x`.

`atanhf` is identical, other than taking and returning `float` values.

Returns

`atanh` and `atanhf` return the calculated value.

If $|x|$ is greater than 1, the global `errno` is set to `EDOM` and the result is a NaN. A **DOMAIN error** is reported.

If $|x|$ is 1, the global `errno` is set to `EDOM`; and the result is infinity with the same sign as `x`. A **SING error** is reported.

You can modify the error handling for these routines using `matherr`.

Portability

Neither `atanh` nor `atanhf` are ANSI C.

1.10 jN, jNf, yN, yNf—Bessel functions

Synopsis

```
#include <math.h>
double j0(double x);
float j0f(float x);
double j1(double x);
float j1f(float x);
double jn(int n, double x);
float jnf(int n, float x);
double y0(double x);
float y0f(float x);
double y1(double x);
float y1f(float x);
double yn(int n, double x);
float ynf(int n, float x);
```

Description

The Bessel functions are a family of functions that solve the differential equation

$$x^2 \frac{d^2 y}{dx^2} + x \frac{dy}{dx} + (x^2 - p^2)y = 0$$

These functions have many applications in engineering and physics.

`jn` calculates the Bessel function of the first kind of order n . `j0` and `j1` are special cases for order 0 and order 1 respectively.

Similarly, `yn` calculates the Bessel function of the second kind of order n , and `y0` and `y1` are special cases for order 0 and 1.

`jnf`, `j0f`, `j1f`, `ynf`, `y0f`, and `y1f` perform the same calculations, but on `float` rather than `double` values.

Returns

The value of each Bessel function at x is returned.

Portability

None of the Bessel functions are in ANSI C.

1.11 `cbrt`, `cbrtf`—cube root

Synopsis

```
#include <math.h>
double cbrt(double x);
float  cbrtf(float x);
```

Description

`cbrt` computes the cube root of the argument.

Returns

The cube root is returned.

Portability

`cbrt` is in System V release 4. `cbrtf` is an extension.

1.12 copysign, copysignf—sign of *y*, magnitude of *x*

Synopsis

```
#include <math.h>
double copysign (double x, double y);
float copysignf (float x, float y);
```

Description

`copysign` constructs a number with the magnitude (absolute value) of its first argument, *x*, and the sign of its second argument, *y*.

`copysignf` does the same thing; the two functions differ only in the type of their arguments and result.

Returns

`copysign` returns a `double` with the magnitude of *x* and the sign of *y*. `copysignf` returns a `float` with the magnitude of *x* and the sign of *y*.

Portability

`copysign` is not required by either ANSI C or the System V Interface Definition (Issue 2).

1.13 `cosh`, `coshf`—hyperbolic cosine

Synopsis

```
#include <math.h>
double cosh(double x);
float coshf(float x);
```

Description

`cosh` computes the hyperbolic cosine of the argument `x`. `cosh(x)` is defined as

$$\frac{(e^x + e^{-x})}{2}$$

Angles are specified in radians. `coshf` is identical, save that it takes and returns `float`.

Returns

The computed value is returned. When the correct value would create an overflow, `cosh` returns the value `HUGE_VAL` with the appropriate sign, and the global value `errno` is set to `ERANGE`.

You can modify error handling for these functions using the function `matherr`.

Portability

`cosh` is ANSI. `coshf` is an extension.

1.14 erf, erff, erfc, erfcf—error function

Synopsis

```
#include <math.h>
double erf(double x);
float erff(float x);
double erfc(double x);
float erfcf(float x);
```

Description

erf calculates an approximation to the “error function”, which estimates the probability that an observation will fall within *x* standard deviations of the mean (assuming a normal distribution). The error function is defined as

$$\frac{2}{\sqrt{\pi}} \times \int_0^x e^{-t^2} dt$$

erfc calculates the complementary probability; that is, **erfc**(*x*) is 1 - **erf**(*x*). **erfc** is computed directly, so that you can use it to avoid the loss of precision that would result from subtracting large probabilities (on large *x*) from 1.

erff and **erfcf** differ from **erf** and **erfc** only in the argument and result types.

Returns

For positive arguments, **erf** and all its variants return a probability—a number between 0 and 1.

Portability

None of the variants of **erf** are ANSI C.

1.15 `exp`, `expf`—exponential

Synopsis

```
#include <math.h>
double exp(double x);
float expf(float x);
```

Description

`exp` and `expf` calculate the exponential of x , that is, e^x (where e is the base of the natural system of logarithms, approximately 2.71828).

You can use the (non-ANSI) function `matherr` to specify error handling for these functions.

Returns

On success, `exp` and `expf` return the calculated value. If the result underflows, the returned value is 0. If the result overflows, the returned value is `HUGE_VAL`. In either case, `errno` is set to `ERANGE`.

Portability

`exp` is ANSI C. `expf` is an extension.

1.16 exp10, exp10f—exponential, base 10

Synopsis

```
#include <math.h>
double exp10(double x);
float exp10f(float x);
```

Description

`exp10` and `exp10f` calculate 10^x , that is, 10^x

You can use the (non-ANSI) function `matherr` to specify error handling for these functions.

Returns

On success, `exp10` and `exp10f` return the calculated value. If the result underflows, the returned value is 0. If the result overflows, the returned value is `HUGE_VAL`. In either case, `errno` is set to `ERANGE`.

Portability

`exp10` and `exp10f` are GNU extensions.

1.17 `exp2`, `exp2f`—exponential, base 2

Synopsis

```
#include <math.h>
double exp2(double x);
float exp2f(float x);
```

Description

`exp2` and `exp2f` calculate 2^x , that is, 2^x

You can use the (non-ANSI) function `matherr` to specify error handling for these functions.

Returns

On success, `exp2` and `exp2f` return the calculated value. If the result underflows, the returned value is 0. If the result overflows, the returned value is `HUGE_VAL`. In either case, `errno` is set to `ERANGE`.

Portability

ANSI C, POSIX.

1.18 `expm1`, `expm1f`—exponential minus 1

Synopsis

```
#include <math.h>
double expm1(double x);
float expm1f(float x);
```

Description

`expm1` and `expm1f` calculate the exponential of x and subtract 1, that is, $e^x - 1$ (where e is the base of the natural system of logarithms, approximately 2.71828). The result is accurate even for small values of x , where using `exp(x)-1` would lose many significant digits.

Returns

e raised to the power x , minus 1.

Portability

Neither `expm1` nor `expm1f` is required by ANSI C or by the System V Interface Definition (Issue 2).

1.19 `fabs`, `fabsf`—absolute value (magnitude)

Synopsis

```
#include <math.h>
double fabs(double x);
float fabsf(float x);
```

Description

`fabs` and `fabsf` calculate $|x|$, the absolute value (magnitude) of the argument `x`, by direct manipulation of the bit representation of `x`.

Returns

The calculated value is returned. No errors are detected.

Portability

`fabs` is ANSI. `fabsf` is an extension.

1.20 fdim, fdimf—positive difference

Synopsis

```
#include <math.h>
double fdim(double x, double y);
float fdimf(float x, float y);
```

Description

The `fdim` functions determine the positive difference between their arguments, returning:

```
x - y if x > y, or
+0 if x ≤ y, or
NAN if either argument is NAN.
```

A range error may occur.

Returns

The `fdim` functions return the positive difference value.

Portability

ANSI C, POSIX.

1.21 `floor`, `floorf`, `ceil`, `ceilf`—floor and ceiling

Synopsis

```
#include <math.h>
double floor(double x);
float floorf(float x);
double ceil(double x);
float ceilf(float x);
```

Description

`floor` and `floorf` find $\lfloor x \rfloor$, the nearest integer less than or equal to x . `ceil` and `ceilf` find $\lceil x \rceil$, the nearest integer greater than or equal to x .

Returns

`floor` and `ceil` return the integer result as a double. `floorf` and `ceilf` return the integer result as a float.

Portability

`floor` and `ceil` are ANSI. `floorf` and `ceilf` are extensions.

1.22 fma, fmaf—floating multiply add

Synopsis

```
#include <math.h>
double fma(double x, double y, double z);
float fmaf(float x, float y, float z);
```

Description

The **fma** functions compute $(x * y) + z$, rounded as one ternary operation: they compute the value (as if) to infinite precision and round once to the result format, according to the rounding mode characterized by the value of `FLT_ROUNDS`. That is, they are supposed to do this: see below.

Returns

The **fma** functions return $(x * y) + z$, rounded as one ternary operation.

Bugs

This implementation does not provide the function that it should, purely returning " $(x * y) + z$;" with no attempt at all to provide the simulated infinite precision intermediates which are required. DO NOT USE THEM.

If double has enough more precision than float, then **fmaf** should provide the expected numeric results, as it does use double for the calculation. But since this is not the case for all platforms, this manual cannot determine if it is so for your case.

Portability

ANSI C, POSIX.

1.23 `fmax`, `fmaxf`—maximum

Synopsis

```
#include <math.h>
double fmax(double x, double y);
float fmaxf(float x, float y);
```

Description

The `fmax` functions determine the maximum numeric value of their arguments. NaN arguments are treated as missing data: if one argument is a NaN and the other numeric, then the `fmax` functions choose the numeric value.

Returns

The `fmax` functions return the maximum numeric value of their arguments.

Portability

ANSI C, POSIX.

1.24 `fmin`, `fminf`—minimum

Synopsis

```
#include <math.h>
double fmin(double x, double y);
float fminf(float x, float y);
```

Description

The `fmin` functions determine the minimum numeric value of their arguments. NaN arguments are treated as missing data: if one argument is a NaN and the other numeric, then the `fmin` functions choose the numeric value.

Returns

The `fmin` functions return the minimum numeric value of their arguments.

Portability

ANSI C, POSIX.

1.25 `fmod`, `fmodf`—floating-point remainder (modulo)

Synopsis

```
#include <math.h>
double fmod(double x, double y);
float fmodf(float x, float y);
```

Description

The `fmod` and `fmodf` functions compute the floating-point remainder of x/y (x modulo y).

Returns

The `fmod` function returns the value $x - i \times y$, for the largest integer i such that, if y is nonzero, the result has the same sign as x and magnitude less than the magnitude of y .

`fmod(x,0)` returns NaN, and sets `errno` to `EDOM`.

You can modify error treatment for these functions using `matherr`.

Portability

`fmod` is ANSI C. `fmodf` is an extension.

1.26 frexp, frexpf—split floating-point number

Synopsis

```
#include <math.h>
double frexp(double val, int *exp);
float frexpf(float val, int *exp);
```

Description

All nonzero, normal numbers can be described as $m * 2^p$. **frexp** represents the double *val* as a mantissa *m* and a power of two *p*. The resulting mantissa will always be greater than or equal to 0.5, and less than 1.0 (as long as *val* is nonzero). The power of two will be stored in **exp*.

m and *p* are calculated so that $val = m \times 2^p$.

frexpf is identical, other than taking and returning floats rather than doubles.

Returns

frexp returns the mantissa *m*. If *val* is 0, infinity, or Nan, **frexp** will set **exp* to 0 and return *val*.

Portability

frexp is ANSI. **frexpf** is an extension.

1.27 `gamma`, `gammaf`, `lgamma`, `lgammaf`, `gamma_r`, `gammaf_r`, `lgamma_r`, `lgammaf_r`, `tgamma`, and `tgammaf`—logarithmic and plain gamma functions

Synopsis

```
#include <math.h>
double gamma(double x);
float gammaf(float x);
double lgamma(double x);
float lgammaf(float x);
double gamma_r(double x, int *signgam);
float gammaf_r(float x, int *signgam);
double lgamma_r(double x, int *signgam);
float lgammaf_r(float x, int *signgam);
double tgamma(double x);
float tgammaf(float x);
```

Description

`gamma` calculates $\ln(\Gamma(x))$, the natural logarithm of the gamma function of x . The gamma function (`exp(gamma(x))`) is a generalization of factorial, and retains the property that $\Gamma(N) \equiv N \times \Gamma(N - 1)$. Accordingly, the results of the gamma function itself grow very quickly. `gamma` is defined as $\ln(\Gamma(x))$ rather than simply $\Gamma(x)$ to extend the useful range of results representable.

The sign of the result is returned in the global variable `signgam`, which is declared in `math.h`.

`gammaf` performs the same calculation as `gamma`, but uses and returns `float` values.

`lgamma` and `lgammaf` are alternate names for `gamma` and `gammaf`. The use of `lgamma` instead of `gamma` is a reminder that these functions compute the log of the gamma function, rather than the gamma function itself.

The functions `gamma_r`, `gammaf_r`, `lgamma_r`, and `lgammaf_r` are just like `gamma`, `gammaf`, `lgamma`, and `lgammaf`, respectively, but take an additional argument. This additional argument is a pointer to an integer. This additional argument is used to return the sign of the result, and the global variable `signgam` is not used. These functions may be used for reentrant calls (but they will still set the global variable `errno` if an error occurs).

`tgamma` and `tgammaf` are the "true gamma" functions, returning $\Gamma(x)$, the gamma function of x —without a logarithm. (They are apparently so named because of the prior existence of the old, poorly-named `gamma` functions which returned the log of gamma up through BSD 4.2.)

Returns

Normally, the computed result is returned.

When x is a nonpositive integer, `gamma` returns `HUGE_VAL` and `errno` is set to `EDOM`. If the result overflows, `gamma` returns `HUGE_VAL` and `errno` is set to `ERANGE`.

You can modify this error treatment using `matherr`.

Portability

Neither `gamma` nor `gammaf` is ANSI C. It is better not to use either of these; use `lgamma` or

`tgamma` instead.

`lgamma`, `lgammaf`, `tgamma`, and `tgammaf` are nominally C standard in terms of the base return values, although the `matherr` error-handling is not standard, nor is the *siggam* global for `lgamma`.

1.28 `hypot`, `hypotf`—distance from origin

Synopsis

```
#include <math.h>
double hypot(double x, double y);
float hypotf(float x, float y);
```

Description

`hypot` calculates the Euclidean distance $\sqrt{x^2 + y^2}$ between the origin (0,0) and a point represented by the Cartesian coordinates (x,y). `hypotf` differs only in the type of its arguments and result.

Returns

Normally, the distance value is returned. On overflow, `hypot` returns `HUGE_VAL` and sets `errno` to `ERANGE`.

You can change the error treatment with `matherr`.

Portability

`hypot` and `hypotf` are not ANSI C.

1.29 `ilogb`, `ilogbf`—get exponent of floating-point number

Synopsis

```
#include <math.h>
int ilogb(double val);
int ilogbf(float val);
```

Description

All nonzero, normal numbers can be described as $m * 2^{**}p$. `ilogb` and `ilogbf` examine the argument *val*, and return *p*. The functions `frexp` and `frexpf` are similar to `ilogb` and `ilogbf`, but also return *m*.

Returns

`ilogb` and `ilogbf` return the power of two used to form the floating-point argument. If *val* is 0, they return `FP_ILOGB0`. If *val* is infinite, they return `INT_MAX`. If *val* is NaN, they return `FP_ILOGBNAN`. (`FP_ILOGB0` and `FP_ILOGBNAN` are defined in `math.h`, but in turn are defined as `INT_MIN` or `INT_MAX` from `limits.h`. The value of `FP_ILOGB0` may be either `INT_MIN` or `-INT_MAX`. The value of `FP_ILOGBNAN` may be either `INT_MAX` or `INT_MIN`.)

Portability

C99, POSIX

1.30 `infinity`, `infinityf`—representation of infinity

Synopsis

```
#include <math.h>
double infinity(void);
float infinityf(void);
```

Description

`infinity` and `infinityf` return the special number IEEE infinity in double- and single-precision arithmetic respectively.

Portability

`infinity` and `infinityf` are neither standard C nor POSIX. C and POSIX require macros `HUGE_VAL` and `HUGE_VALF` to be defined in `math.h`, which Newlib defines to be infinities corresponding to these archaic `infinity()` and `infinityf()` functions in floating-point implementations which do have infinities.

1.31 `isgreater`, `isgreaterequal`, `isless`, `islessequal`, `islessgreater`, and `isunordered`—comparison macros

Synopsis

```
#include <math.h>
int isgreater(real-floating x, real-floating y);
int isgreaterequal(real-floating x, real-floating y);
int isless(real-floating x, real-floating y);
int islessequal(real-floating x, real-floating y);
int islessgreater(real-floating x, real-floating y);
int isunordered(real-floating x, real-floating y);
```

Description

`isgreater`, `isgreaterequal`, `isless`, `islessequal`, `islessgreater`, and `isunordered` are macros defined for use in comparing floating-point numbers without raising any floating-point exceptions.

The relational operators (i.e. `<`, `>`, `<=`, and `>=`) support the usual mathematical relationships between numeric values. For any ordered pair of numeric values exactly one of the relationships—less, greater, and equal—is true. Relational operators may raise the "invalid" floating-point exception when argument values are NaNs. For a NaN and a numeric value, or for two NaNs, just the unordered relationship is true (i.e., if one or both of the arguments a NaN, the relationship is called unordered). The specified macros are quiet (non floating-point exception raising) versions of the relational operators, and other comparison macros that facilitate writing efficient code that accounts for NaNs without suffering the "invalid" floating-point exception. In the synopses shown, "real-floating" indicates that the argument is an expression of real floating type.

Please note that saying that the macros do not raise floating-point exceptions, it is referring to the function that they are performing. It is certainly possible to give them an expression which causes an exception. For example:

`NaN < 1.0` causes an "invalid" exception,

```
isless(NaN, 1.0)
    does not, and
```

```
isless(NaN*0., 1.0)
    causes an exception due to the "NaN*0.", but not from the resultant reduced
    comparison of isless(NaN, 1.0).
```

Returns

No floating-point exceptions are raised for any of the macros.

The `isgreater` macro returns the value of `(x) > (y)`.

The `isgreaterequal` macro returns the value of `(x) >= (y)`.

The `isless` macro returns the value of `(x) < (y)`.

The `islessequal` macro returns the value of `(x) <= (y)`.

The `islessgreater` macro returns the value of `(x) < (y) || (x) > (y)`.

The `isunordered` macro returns 1 if either of its arguments is NaN and 0 otherwise.

Portability
C99, POSIX.

1.32 `fpclassify`, `isfinite`, `isinf`, `isnan`, and `isnormal`—floating-point classification macros; `finite`, `finitef`, `isinff`, `isinff`, `isnan`, `isnanf`—test for exceptional numbers

Synopsis

```
[C99 standard macros:]
#include <math.h>
int fpclassify(real-floating x);
int isfinite(real-floating x);
int isinf(real-floating x);
int isnan(real-floating x);
int isnormal(real-floating x);

[Archaic SUSv2 functions:]
#include <math.h>
int isnan(double arg);
int isinf(double arg);
int finite(double arg);
int isnanf(float arg);
int isinff(float arg);
int finitef(float arg);
```

Description

`fpclassify`, `isfinite`, `isinf`, `isnan`, and `isnormal` are macros defined for use in classifying floating-point numbers. This is a help because of special "values" like NaN and infinities. In the synopses shown, "real-floating" indicates that the argument is an expression of real floating type. These function-like macros are C99 and POSIX-compliant, and should be used instead of the now-archaic SUSv2 functions.

The `fpclassify` macro classifies its argument value as NaN, infinite, normal, subnormal, zero, or into another implementation-defined category. First, an argument represented in a format wider than its semantic type is converted to its semantic type. Then classification is based on the type of the argument. The `fpclassify` macro returns the value of the number classification macro appropriate to the value of its argument:

`FP_INFINITE`

`x` is either plus or minus infinity;

`FP_NAN` `x` is "Not A Number" (plus or minus);

`FP_NORMAL`

`x` is a "normal" number (i.e. is none of the other special forms);

`FP_SUBNORMAL`

`x` is too small to be stored as a regular normalized number (i.e. loss of precision is likely); or

`FP_ZERO` `x` is 0 (either plus or minus).

The "is" set of macros provide a useful set of shorthand ways for classifying floating-point numbers, providing the following equivalent relations:

isfinite(x) returns non-zero if *x* is finite. (It is equivalent to `(fpclassify(x) != FP_INFINITE && fpclassify(x) != FP_NAN)`.)

isinf(x) returns non-zero if *x* is infinite. (It is equivalent to `(fpclassify(x) == FP_INFINITE)`.)

isnan(x) returns non-zero if *x* is NaN. (It is equivalent to `(fpclassify(x) == FP_NAN)`.)

isnormal(x) returns non-zero if *x* is normal. (It is equivalent to `(fpclassify(x) == FP_NORMAL)`.)

The archaic SUSv2 functions provide information on the floating-point argument supplied. There are five major number formats ("exponent" referring to the biased exponent in the binary-encoded number):

zero A number which contains all zero bits, excluding the sign bit.

subnormal A number with a zero exponent but a nonzero fraction.

normal A number with an exponent and a fraction.

infinity A number with an all 1's exponent and a zero fraction.

NAN A number with an all 1's exponent and a nonzero fraction.

isnan returns 1 if the argument is a nan. **isinf** returns 1 if the argument is infinity. **finite** returns 1 if the argument is zero, subnormal or normal. The **isnanf**, **isinf** and **finitef** functions perform the same operations as their **isnan**, **isinf** and **finite** counterparts, but on single-precision floating-point numbers.

It should be noted that the C99 standard dictates that **isnan** and **isinf** are macros that operate on multiple types of floating-point. The SUSv2 standard declares **isnan** as a function taking double. Newlib has decided to declare them both as functions and as macros in `math.h` to maintain backward compatibility.

Returns

The **fpclassify** macro returns the value corresponding to the appropriate `FP_` macro.
 The **isfinite** macro returns nonzero if *x* is finite, else 0.
 The **isinf** macro returns nonzero if *x* is infinite, else 0.
 The **isnan** macro returns nonzero if *x* is an NaN, else 0.
 The **isnormal** macro returns nonzero if *x* has a normal value, else 0.

Portability

`math.h` macros are C99, POSIX.1-2001.

The functions originate from BSD; **isnan** was listed in the X/Open Portability Guide and Single Unix Specification, but was dropped when the macro was standardized in POSIX.1-2001.

1.33 ldexp, ldexpf—load exponent

Synopsis

```
#include <math.h>
double ldexp(double val, int exp);
float ldexpf(float val, int exp);
```

Description

`ldexp` calculates the value $val \times 2^{exp}$. `ldexpf` is identical, save that it takes and returns `float` rather than `double` values.

Returns

`ldexp` returns the calculated value.

Underflow and overflow both set `errno` to `ERANGE`. On underflow, `ldexp` and `ldexpf` return 0.0. On overflow, `ldexp` returns plus or minus `HUGE_VAL`.

Portability

`ldexp` is ANSI. `ldexpf` is an extension.

1.34 `log`, `logf`—natural logarithms

Synopsis

```
#include <math.h>
double log(double x);
float logf(float x);
```

Description

Return the natural logarithm of `x`, that is, its logarithm base `e` (where `e` is the base of the natural system of logarithms, 2.71828...). `log` and `logf` are identical save for the return and argument types.

You can use the (non-ANSI) function `matherr` to specify error handling for these functions.

Returns

Normally, returns the calculated value. When `x` is zero, the returned value is `-HUGE_VAL` and `errno` is set to `ERANGE`. When `x` is negative, the returned value is NaN (not a number) and `errno` is set to `EDOM`. You can control the error behavior via `matherr`.

Portability

`log` is ANSI. `logf` is an extension.

1.35 `log10`, `log10f`—base 10 logarithms

Synopsis

```
#include <math.h>
double log10(double x);
float log10f(float x);
```

Description

`log10` returns the base 10 logarithm of `x`. It is implemented as $\log(x) / \log(10)$.

`log10f` is identical, save that it takes and returns `float` values.

Returns

`log10` and `log10f` return the calculated value.

See the description of `log` for information on errors.

Portability

`log10` is ANSI C. `log10f` is an extension.

1.36 `log1p`, `log1pf`—log of $1 + x$

Synopsis

```
#include <math.h>
double log1p(double x);
float log1pf(float x);
```

Description

`log1p` calculates $\ln(1 + x)$, the natural logarithm of $1+x$. You can use `log1p` rather than ‘`log(1+x)`’ for greater precision when x is very small.

`log1pf` calculates the same thing, but accepts and returns `float` values rather than `double`.

Returns

`log1p` returns a `double`, the natural log of $1+x$. `log1pf` returns a `float`, the natural log of $1+x$.

Portability

Neither `log1p` nor `log1pf` is required by ANSI C or by the System V Interface Definition (Issue 2).

1.37 log2, log2f—base 2 logarithm

Synopsis

```
#include <math.h>
double log2(double x);
float log2f(float x);
```

Description

The `log2` functions compute the base-2 logarithm of x . A domain error occurs if the argument is less than zero. A range error occurs if the argument is zero.

The Newlib implementations are not full, intrinsic calculations, but rather are derivatives based on `log`. (Accuracy might be slightly off from a direct calculation.) In addition to functions, they are also implemented as macros defined in `math.h`:

```
#define log2(x) (log (x) / _M_LN2)
#define log2f(x) (logf (x) / (float) _M_LN2)
```

To use the functions instead, just undefine the macros first.

You can use the (non-ANSI) function `matherr` to specify error handling for these functions, indirectly through the respective `log` function.

Returns

The `log2` functions return $\log_2(x)$ on success. When x is zero, the returned value is `-HUGE_VAL` and `errno` is set to `ERANGE`. When x is negative, the returned value is NaN (not a number) and `errno` is set to `EDOM`. You can control the error behavior via `matherr`.

Portability

C99, POSIX, System V Interface Definition (Issue 6).

1.38 `logb`, `logbf`—get exponent of floating-point number

Synopsis

```
#include <math.h>
double logb(double x);
float logbf(float x);
```

Description

The `logb` functions extract the exponent of x , as a signed integer value in floating-point format. If x is subnormal it is treated as though it were normalized; thus, for positive finite x , $1 \leq (x \cdot FLT_RADIX^{-logb(x)}) < FLT_RADIX$. A domain error may occur if the argument is zero. In this floating-point implementation, `FLT_RADIX` is 2. Which also means that for finite x , $logb(x) = floor(log2(fabs(x)))$.

All nonzero, normal numbers can be described as $m \cdot 2^p$, where $1.0 \leq m < 2.0$. The `logb` functions examine the argument x , and return p . The `frexp` functions are similar to the `logb` functions, but returning m adjusted to the interval $[.5, 1)$ or 0, and $p+1$.

Returns

When x is:

`+inf` or `-inf`, `+inf` is returned;

`NaN`, `NaN` is returned;

0, `-inf` is returned, and the divide-by-zero exception is raised;

otherwise, the `logb` functions return the signed exponent of x .

Portability

ANSI C, POSIX

See Also

`frexp`, `ilogb`

1.39 `lrint`, `lrintf`, `llrint`, `llrintf`—round to integer

Synopsis

```
#include <math.h>
long int lrint(double x);
long int lrintf(float x);
long long int llrint(double x);
long long int llrintf(float x);
```

Description

The `lrint` and `llrint` functions round their argument to the nearest integer value, using the current rounding direction. If the rounded value is outside the range of the return type, the numeric result is unspecified. A range error may occur if the magnitude of `x` is too large. The "inexact" floating-point exception is raised in implementations that support it when the result differs in value from the argument (i.e., when a fraction actually has been truncated).

Returns

`x` rounded to an integral value, using the current rounding direction.

See Also

`lround`

Portability

ANSI C, POSIX

1.40 `lround`, `lroundf`, `llround`, `llroundf`—round to integer, to nearest

Synopsis

```
#include <math.h>
long int lround(double x);
long int lroundf(float x);
long long int llround(double x);
long long int llroundf(float x);
```

Description

The `lround` and `llround` functions round their argument to the nearest integer value, rounding halfway cases away from zero, regardless of the current rounding direction. If the rounded value is outside the range of the return type, the numeric result is unspecified (depending upon the floating-point implementation, not the library). A range error may occur if the magnitude of `x` is too large.

Returns

`x` rounded to an integral value as an integer.

See Also

See the `round` functions for the return being the same floating-point type as the argument. `lrint`, `llrint`.

Portability

ANSI C, POSIX

1.41 matherr—modifiable math error handler

Synopsis

```
#include <math.h>
int matherr(struct exception *e);
```

Description

matherr is called whenever a math library function generates an error. You can replace **matherr** by your own subroutine to customize error treatment. The customized **matherr** must return 0 if it fails to resolve the error, and non-zero if the error is resolved.

When **matherr** returns a nonzero value, no error message is printed and the value of **errno** is not modified. You can accomplish either or both of these things in your own **matherr** using the information passed in the structure *e*.

This is the **exception** structure (defined in ‘**math.h**’):

```
struct exception {
    int type;
    char *name;
    double arg1, arg2, retval;
    int err;
};
```

The members of the exception structure have the following meanings:

type The type of mathematical error that occurred; macros encoding error types are also defined in ‘**math.h**’.

name a pointer to a null-terminated string holding the name of the math library function where the error occurred.

arg1, arg2 The arguments which caused the error.

retval The error return value (what the calling function will return).

err If set to be non-zero, this is the new value assigned to **errno**.

The error types defined in ‘**math.h**’ represent possible mathematical errors as follows:

DOMAIN An argument was not in the domain of the function; e.g. **log**(-1.0).

SING The requested calculation would result in a singularity; e.g. **pow**(0.0,-2.0)

OVERFLOW A calculation would produce a result too large to represent; e.g. **exp**(1000.0).

UNDERFLOW A calculation would produce a result too small to represent; e.g. **exp**(-1000.0).

TLOSS Total loss of precision. The result would have no significant digits; e.g. **sin**(10e70).

PLOSS Partial loss of precision.

Returns

The library definition for **matherr** returns 0 in all cases.

You can change the calling function's result from a customized `matherr` by modifying `e->retval`, which propagates back to the caller.

If `matherr` returns 0 (indicating that it was not able to resolve the error) the caller sets `errno` to an appropriate value, and prints an error message.

Portability

`matherr` is not ANSI C.

1.42 `modf`, `modff`—split fractional and integer parts

Synopsis

```
#include <math.h>
double modf(double val, double *ipart);
float modff(float val, float *ipart);
```

Description

`modf` splits the double *val* apart into an integer part and a fractional part, returning the fractional part and storing the integer part in **ipart*. No rounding whatsoever is done; the sum of the integer and fractional parts is guaranteed to be exactly equal to *val*. That is, if *realpart* = `modf(val, &intpart)`; then ‘*realpart+intpart*’ is the same as *val*. `modff` is identical, save that it takes and returns `float` rather than `double` values.

Returns

The fractional part is returned. Each result has the same sign as the supplied argument *val*.

Portability

`modf` is ANSI C. `modff` is an extension.

1.43 `nan`, `nanf`—representation of “Not a Number”

Synopsis

```
#include <math.h>
double nan(const char *unused);
float nanf(const char *unused);
```

Description

`nan` and `nanf` return an IEEE NaN (Not a Number) in double- and single-precision arithmetic respectively. The argument is currently disregarded.

1.44 `nearbyint`, `nearbyintf`—round to integer

Synopsis

```
#include <math.h>
double nearbyint(double x);
float nearbyintf(float x);
```

Description

The `nearbyint` functions round their argument to an integer value in floating-point format, using the current rounding direction and (supposedly) without raising the "inexact" floating-point exception. See the `rint` functions for the same function with the "inexact" floating-point exception being raised when appropriate.

Bugs

Newlib does not support the floating-point exception model, so that the floating-point exception control is not present and thereby what may be seen will be compiler and hardware dependent in this regard. The Newlib `nearbyint` functions are identical to the `rint` functions with respect to the floating-point exception behavior, and will cause the "inexact" exception to be raised for most targets.

Returns

`x` rounded to an integral value, using the current rounding direction.

Portability

ANSI C, POSIX

See Also

`rint`, `round`

1.45 `nextafter`, `nextafterf`—get next number

Synopsis

```
#include <math.h>
double nextafter(double val, double dir);
float nextafterf(float val, float dir);
```

Description

`nextafter` returns the double-precision floating-point number closest to *val* in the direction toward *dir*. `nextafterf` performs the same operation in single precision. For example, `nextafter(0.0, 1.0)` returns the smallest positive number which is representable in double precision.

Returns

Returns the next closest number to *val* in the direction toward *dir*.

Portability

Neither `nextafter` nor `nextafterf` is required by ANSI C or by the System V Interface Definition (Issue 2).

1.46 pow, powf—x to the power y

Synopsis

```
#include <math.h>
double pow(double x, double y);
float powf(float x, float y);
```

Description

`pow` and `powf` calculate x raised to the exponent y . (That is, x^y .)

Returns

On success, `pow` and `powf` return the value calculated.

When the argument values would produce overflow, `pow` returns `HUGE_VAL` and set `errno` to `ERANGE`. If the argument x passed to `pow` or `powf` is a negative noninteger, and y is also not an integer, then `errno` is set to `EDOM`. If x and y are both 0, then `pow` and `powf` return 1.

You can modify error handling for these functions using `matherr`.

Portability

`pow` is ANSI C. `powf` is an extension.

1.47 `pow10`, `pow10f`—base 10 power functions

Synopsis

```
#include <math.h>
double pow10(double x);
float pow10f(float x);
```

Description

`pow10` and `pow10f` calculate 10^x , that is, 10^x

You can use the (non-ANSI) function `matherr` to specify error handling for these functions.

Returns

On success, `pow10` and `pow10f` return the calculated value. If the result underflows, the returned value is 0. If the result overflows, the returned value is `HUGE_VAL`. In either case, `errno` is set to `ERANGE`.

Portability

`pow10` and `pow10f` are GNU extensions.

1.48 remainder, remainderf—round and remainder

Synopsis

```
#include <math.h>
double remainder(double x, double y);
float remainderf(float x, float y);
```

Description

`remainder` and `remainderf` find the remainder of x/y ; this value is in the range $-y/2$.. $+y/2$.

Returns

`remainder` returns the integer result as a double.

Portability

`remainder` is a System V release 4. `remainderf` is an extension.

1.49 `remquo`, `remquof`—remainder and part of quotient

Synopsis

```
#include <math.h>
double remquo(double x, double y, int *quo);
float remquof(float x, float y, int *quo);
```

Description

The `remquo` functions compute the same remainder as the `remainder` functions; this value is in the range $-y/2 \dots +y/2$. In the object pointed to by `quo` they store a value whose sign is the sign of x/y and whose magnitude is congruent modulo 2^n to the magnitude of the integral quotient of x/y . (That is, `quo` is given the n lsbs of the quotient, not counting the sign.) This implementation uses $n=31$ if `int` is 32 bits or more, otherwise, n is 1 less than the width of `int`.

For example:

```
remquo(-29.0, 3.0, &quo)
```

returns -1.0 and sets `quo=10`, and

```
remquo(-98307.0, 3.0, &quo)
```

returns -0.0 and sets `quo=-32769`, although for 16-bit `int`, `quo=-1`. In the latter case, the actual quotient of $-(32769=0x8001)$ is reduced to -1 because of the 15-bit limitation for the quotient.

Returns

When either argument is NaN, NaN is returned. If y is 0 or x is infinite (and neither is NaN), a domain error occurs (i.e. the "invalid" floating point exception is raised or `errno` is set to `EDOM`), and NaN is returned. Otherwise, the `remquo` functions return $x \text{ REM } y$.

Bugs

IEEE754-2008 calls for `remquo(subnormal, inf)` to cause the "underflow" floating-point exception. This implementation does not.

Portability

C99, POSIX.

1.50 rint, rintf—round to integer

Synopsis

```
#include <math.h>
double rint(double x);
float rintf(float x);
```

Description

The **rint** functions round their argument to an integer value in floating-point format, using the current rounding direction. They raise the "inexact" floating-point exception if the result differs in value from the argument. See the **nearbyint** functions for the same function with the "inexact" floating-point exception never being raised. Newlib does not directly support floating-point exceptions. The **rint** functions are written so that the "inexact" exception is raised in hardware implementations that support it, even though Newlib does not provide access.

Returns

x rounded to an integral value, using the current rounding direction.

Portability

ANSI C, POSIX

See Also

nearbyint, **round**

1.51 `round`, `roundf`—round to integer, to nearest

Synopsis

```
#include <math.h>
double round(double x);
float roundf(float x);
```

Description

The `round` functions round their argument to the nearest integer value in floating-point format, rounding halfway cases away from zero, regardless of the current rounding direction. (While the "inexact" floating-point exception behavior is unspecified by the C standard, the `round` functions are written so that "inexact" is not raised if the result does not equal the argument, which behavior is as recommended by IEEE 754 for its related functions.)

Returns

`x` rounded to an integral value.

Portability

ANSI C, POSIX

See Also

`nearbyint`, `rint`

1.52 `scalbn`, `scalbnf`, `scalbln`, `scalblnf`—scale by power of `FLT_RADIX` (=2)

Synopsis

```
#include <math.h>
double scalbn(double x, int n);
float scalbnf(float x, int n);
double scalbln(double x, long int n);
float scalblnf(float x, long int n);
```

Description

The `scalbn` and `scalbln` functions compute $x \cdot FLT_RADIX^n$. efficiently. The result is computed by manipulating the exponent, rather than by actually performing an exponentiation or multiplication. In this floating-point implementation `FLT_RADIX`=2, which makes the `scalbn` functions equivalent to the `ldexp` functions.

Returns

x times 2 to the power n . A range error may occur.

Portability

ANSI C, POSIX

See Also

`ldexp`

1.53 `signbit`—Does floating-point number have negative sign?

Synopsis

```
#include <math.h>
int signbit(real-floating x);
```

Description

The `signbit` macro determines whether the sign of its argument value is negative. The macro reports the sign of all values, including infinities, zeros, and NaNs. If zero is unsigned, it is treated as positive. As shown in the synopsis, the argument is "real-floating," meaning that any of the real floating-point types (`float`, `double`, etc.) may be given to it.

Note that because of the possibilities of signed 0 and NaNs, the expression "`x < 0.0`" does not give the same result as `signbit` in all cases.

Returns

The `signbit` macro returns a nonzero value if and only if the sign of its argument value is negative.

Portability

C99, POSIX.

1.54 `sin`, `sinf`, `cos`, `cosf`—sine or cosine

Synopsis

```
#include <math.h>
double sin(double x);
float  sinf(float x);
double cos(double x);
float  cosf(float x);
```

Description

`sin` and `cos` compute (respectively) the sine and cosine of the argument `x`. Angles are specified in radians.

`sinf` and `cosf` are identical, save that they take and return `float` values.

Returns

The sine or cosine of `x` is returned.

Portability

`sin` and `cos` are ANSI C. `sinf` and `cosf` are extensions.

1.55 `sinh`, `sinhf`—hyperbolic sine

Synopsis

```
#include <math.h>
double sinh(double x);
float  sinhf(float x);
```

Description

`sinh` computes the hyperbolic sine of the argument `x`. Angles are specified in radians. `sinh(x)` is defined as

$$\frac{e^x - e^{-x}}{2}$$

`sinhf` is identical, save that it takes and returns `float` values.

Returns

The hyperbolic sine of `x` is returned.

When the correct result is too large to be representable (an overflow), `sinh` returns `HUGE_VAL` with the appropriate sign, and sets the global value `errno` to `ERANGE`.

You can modify error handling for these functions with `matherr`.

Portability

`sinh` is ANSI C. `sinhf` is an extension.

1.56 `sqrt`, `sqrtf`—positive square root

Synopsis

```
#include <math.h>
double sqrt(double x);
float sqrtf(float x);
```

Description

`sqrt` computes the positive square root of the argument. You can modify error handling for this function with `matherr`.

Returns

On success, the square root is returned. If `x` is real and positive, then the result is positive. If `x` is real and negative, the global value `errno` is set to `EDOM` (domain error).

Portability

`sqrt` is ANSI C. `sqrtf` is an extension.

1.57 `tan`, `tanf`—tangent

Synopsis

```
#include <math.h>
double tan(double x);
float tanf(float x);
```

Description

`tan` computes the tangent of the argument `x`. Angles are specified in radians.

`tanf` is identical, save that it takes and returns `float` values.

Returns

The tangent of `x` is returned.

Portability

`tan` is ANSI. `tanf` is an extension.

1.58 `tanh`, `tanhf`—hyperbolic tangent

Synopsis

```
#include <math.h>
double tanh(double x);
float tanhf(float x);
```

Description

`tanh` computes the hyperbolic tangent of the argument `x`. Angles are specified in radians.

`tanh(x)` is defined as

$$\sinh(x)/\cosh(x)$$

`tanhf` is identical, save that it takes and returns `float` values.

Returns

The hyperbolic tangent of `x` is returned.

Portability

`tanh` is ANSI C. `tanhf` is an extension.

1.59 `trunc`, `truncf`—round to integer, towards zero

Synopsis

```
#include <math.h>
double trunc(double x);
float truncf(float x);
```

Description

The `trunc` functions round their argument to the integer value, in floating format, nearest to but no larger in magnitude than the argument, regardless of the current rounding direction. (While the "inexact" floating-point exception behavior is unspecified by the C standard, the `trunc` functions are written so that "inexact" is not raised if the result does not equal the argument, which behavior is as recommended by IEEE 754 for its related functions.)

Returns

`x` truncated to an integral value.

Portability

ANSI C, POSIX

2 Mathematical Complex Functions (`complex.h`)

This chapter groups the complex mathematical functions. The corresponding definitions and declarations are in `complex.h`. Functions and documentations are taken from NetBSD.

2.1 `cabs`, `cabsf`, `cabsl`—complex absolute-value

Synopsis

```
#include <complex.h>
double cabs(double complex z);
float cabsf(float complex z);
long double cabsl(long double complex z);
```

Description

These functions compute the complex absolute value (also called norm, modulus, or magnitude) of `z`.

`cabsf` is identical to `cabs`, except that it performs its calculations on `float complex`.

`cabsl` is identical to `cabs`, except that it performs its calculations on `long double complex`.

Returns

The `cabs*` functions return the complex absolute value.

Portability

`cabs`, `cabsf` and `cabsl` are ISO C99

2.2 `cacos`, `cacosf`—complex arc cosine

Synopsis

```
#include <complex.h>
double complex cacos(double complex z);
float complex cacosf(float complex z);
```

Description

These functions compute the complex arc cosine of z , with branch cuts outside the interval $[-1, +1]$ along the real axis.

`cacosf` is identical to `cacos`, except that it performs its calculations on `floats` `complex`.

Returns

These functions return the complex arc cosine value, in the range of a strip mathematically unbounded along the imaginary axis and in the interval $[0, \pi]$ along the real axis.

Portability

`cacos` and `cacosf` are ISO C99

2.3 `cacosh`, `cacoshf`—complex arc hyperbolic cosine

Synopsis

```
#include <complex.h>
double complex cacosh(double complex z);
float complex cacoshf(float complex z);
```

Description

These functions compute the complex arc hyperbolic cosine of `z`, with a branch cut at values less than 1 along the real axis.

`cacoshf` is identical to `cacosh`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex arc hyperbolic cosine value, in the range of a half-strip of non-negative values along the real axis and in the interval $[-i\pi, +i\pi]$ along the imaginary axis.

Portability

`cacosh` and `cacoshf` are ISO C99

2.4 `carg`, `cargf`—argument (phase angle)

Synopsis

```
#include <complex.h>
double carg(double complex z);
float cargf(float complex z);
```

Description

These functions compute the argument (also called phase angle) of `z`, with a branch cut along the negative real axis.

`cargf` is identical to `carg`, except that it performs its calculations on `floats` `complex`.

Returns

The `carg` functions return the value of the argument in the interval $[-\pi, +\pi]$

Portability

`carg` and `cargf` are ISO C99

2.5 casin, casinf—complex arc sine

Synopsis

```
#include <complex.h>
double complex casin(double complex z);
float complex casinf(float complex z);
```

Description

These functions compute the complex arc sine of z , with branch cuts outside the interval $[-1, +1]$ along the real axis.

casinf is identical to **casin**, except that it performs its calculations on **floats complex**.

Returns

These functions return the complex arc sine value, in the range of a strip mathematically unbounded along the imaginary axis and in the interval $[-\pi/2, +\pi/2]$ along the real axis.

Portability

casin and **casinf** are ISO C99

2.6 `casinh`, `casinhf`—complex arc hyperbolic sine

Synopsis

```
#include <complex.h>
double complex casinh(double complex z);
float complex casinhf(float complex z);
```

Description

These functions compute the complex arc hyperbolic sine of z , with branch cuts outside the interval $[-i, +i]$ along the imaginary axis.

`casinhf` is identical to `casinh`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex arc hyperbolic sine value, in the range of a strip mathematically unbounded along the real axis and in the interval $[-i\pi/2, +i\pi/2]$ along the imaginary axis.

Portability

`casinh` and `casinhf` are ISO C99

2.7 catan, catanf—complex arc tangent

Synopsis

```
#include <complex.h>
double complex catan(double complex z);
float complex catanf(float complex z);
```

Description

These functions compute the complex arc tangent of z , with branch cuts outside the interval $[-i, +i]$ along the imaginary axis.

`catanf` is identical to `catan`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex arc tangent, in the range of a strip mathematically unbounded along the imaginary axis and in the interval $[-\pi/2, +\pi/2]$ along the real axis.

Portability

`catan` and `catanf` are ISO C99

2.8 `catanh`, `catanhf`—complex arc hyperbolic tangent

Synopsis

```
#include <complex.h>
double complex catanh(double complex z);
float complex catanhf(float complex z);
```

Description

These functions compute the complex arc hyperbolic tan of z , with branch cuts outside the interval $[-1, +1]$ along the real axis.

`catanhf` is identical to `catanh`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex arc hyperbolic tangent value, in the range of a strip mathematically unbounded along the real axis and in the interval $[-i\pi/2, +i\pi/2]$ along the imaginary axis.

Portability

`catanh` and `catanhf` are ISO C99

2.9 ccos, ccosf—complex cosine

Synopsis

```
#include <complex.h>
double complex ccos(double complex z);
float complex ccosf(float complex z);
```

Description

These functions compute the complex cosine of `z`.

`ccosf` is identical to `ccos`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex cosine value.

Portability

`ccos` and `ccosf` are ISO C99

2.10 `ccosh`, `ccoshf`—complex hyperbolic cosine

Synopsis

```
#include <complex.h>
double complex ccosh(double complex z);
float complex ccoshf(float complex z);
```

Description

These functions compute the complex hyperbolic cosine of `z`.

`ccoshf` is identical to `ccosh`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex hyperbolic cosine value.

Portability

`ccosh` and `ccoshf` are ISO C99

2.11 cexp, cexpf—complex base-e exponential

Synopsis

```
#include <complex.h>
double complex cexp(double complex z);
float complex cexpf(float complex z);
```

Description

These functions compute the complex base-e exponential of `z`.

`cexpf` is identical to `cexp`, except that it performs its calculations on `floats complex`.

Returns

The `cexp` functions return the complex base-e exponential value.

Portability

`cexp` and `cexpf` are ISO C99

2.12 `cimag`, `cimagf`, `cimagl`—imaginary part

Synopsis

```
#include <complex.h>
double cimag(double complex z);
float cimagf(float complex z);
long double cimagl(long double complex z);
```

Description

These functions compute the imaginary part of `z`.

`cimagf` is identical to `cimag`, except that it performs its calculations on `float complex`.

`cimagl` is identical to `cimag`, except that it performs its calculations on `long double complex`.

Returns

The `cimag*` functions return the imaginary part value (as a real).

Portability

`cimag`, `cimagf` and `cimagl` are ISO C99

2.13 clog, clogf—complex base-e logarithm

Synopsis

```
#include <complex.h>
double complex clog(double complex z);
float complex clogf(float complex z);
```

Description

These functions compute the complex natural (base- e) logarithm of z , with a branch cut along the negative real axis.

`clogf` is identical to `clog`, except that it performs its calculations on `floats complex`.

Returns

The `clog` functions return the complex natural logarithm value, in the range of a strip mathematically unbounded along the real axis and in the interval $[-i\pi, +i\pi]$ along the imaginary axis.

Portability

`clog` and `clogf` are ISO C99

2.14 `clog10`, `clog10f`—complex base-10 logarithm

Synopsis

```
#define _GNU_SOURCE
#include <complex.h>
double complex clog10(double complex z);
float complex clog10f(float complex z);
```

Description

These functions compute the complex base-10 logarithm of z . `clog10` is equivalent to `clog(z)/log(10)`.

`clog10f` is identical to `clog10`, except that it performs its calculations on floats `complex`.

Returns

The `clog10` functions return the complex base-10 logarithm value.

Portability

`clog10` and `clog10f` are GNU extensions.

2.15 conj, conjf—complex conjugate

Synopsis

```
#include <complex.h>
double complex conj(double complex z);
float complex conjf(float complex z);
```

Description

These functions compute the complex conjugate of *z*, by reversing the sign of its imaginary part.

`conjf` is identical to `conj`, except that it performs its calculations on **floats** **complex**.

Returns

The `conj` functions return the complex conjugate value.

Portability

`conj` and `conjf` are ISO C99

2.16 `cpow`, `cpowf`—complex power

Synopsis

```
#include <complex.h>
double complex cpow(double complex x, double complex y);
float complex cpowf(float complex x, float complex y);
```

Description

The `cpow` functions compute the complex power function x^y power, with a branch cut for the first parameter along the negative real axis.

`cpowf` is identical to `cpow`, except that it performs its calculations on `floats complex`.

Returns

The `cpow` functions return the complex power function value.

Portability

`cpow` and `cpowf` are ISO C99

2.17 cproj, cprojf— Riemann sphere projection

Synopsis

```
#include <complex.h>
double complex cproj(double complex z);
float complex cprojf(float complex z);
```

Description

These functions compute a projection of z onto the Riemann sphere: z projects to z except that all complex infinities (even those with one infinite part and one NaN part) project to positive infinity on the real axis. If z has an infinite part, then $\text{cproj}(z)$ is equivalent to $\text{INFINITY} + \text{I} * \text{copysign}(0.0, \text{cimag}(z))$

cprojf is identical to cproj , except that it performs its calculations on `floats complex`.

Returns

The cproj functions return the value of the projection onto the Riemann sphere.

Portability

cproj and cprojf are ISO C99

2.18 `creal`, `crealf`, `creall`—real part

Synopsis

```
#include <complex.h>
double creal(double complex z);
float crealf(float complex z);
double long creall(long double complex z);
```

Description

These functions compute the real part of `z`.

`crealf` is identical to `creal`, except that it performs its calculations on `float complex`.

`creall` is identical to `creal`, except that it performs its calculations on `long double complex`.

Returns

The `creal*` functions return the real part value.

Portability

`creal`, `crealf` and `creall` are ISO C99

2.19 `csin`, `csinf`—complex sine

Synopsis

```
#include <complex.h>
double complex csin(double complex z);
float complex csinf(float complex z);
```

Description

These functions compute the complex sine of `z`.

`csinf` is identical to `csin`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex sine value.

Portability

`csin` and `csinf` are ISO C99

2.20 `csinh`, `csinhf`—complex hyperbolic sine

Synopsis

```
#include <complex.h>
double complex csinh(double complex z);
float complex csinhf(float complex z);
```

Description

These functions compute the complex hyperbolic sine of `z`.

`ccoshf` is identical to `ccosh`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex hyperbolic sine value.

Portability

`csinh` and `csinhf` are ISO C99

2.21 csqrt, csqrtf—complex square root

Synopsis

```
#include <complex.h>
double complex csqrt(double complex z);
float complex csqrtf(float complex z);
```

Description

These functions compute the complex square root of z , with a branch cut along the negative real axis.

`csqrtf` is identical to `csqrt`, except that it performs its calculations on `floats complex`.

Returns

The `csqrt` functions return the complex square root value, in the range of the right halfplane (including the imaginary axis).

Portability

`csqrt` and `csqrtf` are ISO C99

2.22 `ctan`, `ctanf`—complex tangent

Synopsis

```
#include <complex.h>
double complex ctan(double complex z);
float complex ctanf(float complex z);
```

Description

These functions compute the complex tangent of `z`.

`ctanf` is identical to `ctan`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex tangent value.

Portability

`ctan` and `ctanf` are ISO C99

2.23 ctanh, ctanf—complex hyperbolic tangent

Synopsis

```
#include <complex.h>
double complex ctanh(double complex z);
float complex ctanhf(float complex z);
```

Description

These functions compute the complex hyperbolic tangent of z .

`ctanhf` is identical to `ctanh`, except that it performs its calculations on `floats complex`.

Returns

These functions return the complex hyperbolic tangent value.

Portability

`ctanh` and `ctanhf` are ISO C99

3 Reentrancy Properties of libm

When a libm function detects an exceptional case, `errno` may be set, the `matherr` function may be called, and a error message may be written to the standard error stream. This behavior may not be reentrant.

With reentrant C libraries like the Red Hat newlib C library, `errno` is a macro which expands to the per-thread error value. This makes it thread safe.

When the user provides his own `matherr` function it must be reentrant for the math library as a whole to be reentrant.

In normal debugged programs, there are usually no math subroutine errors—and therefore no assignments to `errno` and no `matherr` calls; in that situation, the math functions behave reentrantly.

4 The long double function support of libm

Currently, the full set of long double math functions is only provided on platforms where long double equals double. For such platforms, the long double math functions are implemented as calls to the double versions.

Document Index

M

`matherr` and reentrancy 89

O

OS stubs 1

R

reentrancy 89

S

stubs 1

support subroutines 1

system calls 1

The body of this manual is set in
cmr10 at 10.95pt,
with headings in **cmb10 at 10.95pt**
and examples in cmr10 at 10.95pt.
cmti10 at 10.95pt and
cmsl10 at 10.95pt
are used for emphasis.

Table of Contents

1	Mathematical Functions (math.h)	1
1.1	Error Handling	2
1.2	Standards Compliance And Portability	2
1.3	acos, acosf—arc cosine	3
1.4	acosh, acoshf—inverse hyperbolic cosine	4
1.5	asin, asinf—arc sine	5
1.6	asinh, asinhf—inverse hyperbolic sine	6
1.7	atan, atanf—arc tangent	7
1.8	atan2, atan2f—arc tangent of y/x	8
1.9	atanh, atanhf—inverse hyperbolic tangent	9
1.10	jN, jNf, yN, yNf—Bessel functions	10
1.11	cbirt, cbirtf—cube root	11
1.12	copysign, copysignf—sign of y, magnitude of x	12
1.13	cosh, coshf—hyperbolic cosine	13
1.14	erf, erff, erfc, erfcf—error function	14
1.15	exp, expf—exponential	15
1.16	exp10, exp10f—exponential, base 10	16
1.17	exp2, exp2f—exponential, base 2	17
1.18	expm1, expm1f—exponential minus 1	18
1.19	fabs, fabsf—absolute value (magnitude)	19
1.20	fdim, fdimf—positive difference	20
1.21	floor, floorf, ceil, ceilf—floor and ceiling	21
1.22	fma, fmaf—floating multiply add	22
1.23	fmax, fmaxf—maximum	23
1.24	fmin, fminf—minimum	24
1.25	fmod, fmodf—floating-point remainder (modulo)	25
1.26	frexp, frexpf—split floating-point number	26
1.27	gamma, gammaf, lgamma, lgammaf, gamma_r, gammaf_r, lgamma_r, lgammaf_r, tgamma, and tgammaf—logarithmic and plain gamma functions	27
1.28	hypot, hypotf—distance from origin	29
1.29	ilogb, ilogbf—get exponent of floating-point number	30
1.30	infinity, infinityf—representation of infinity	31
1.31	isgreater, isgreaterequal, isless, islessequal, islessgreater, and isunordered—comparison macros	32
1.32	fpclassify, isfinite, isinf, isnan, and isnormal—floating-point classification macros; finite, finitf, isinf, isinff, isnan, isnanf—test for exceptional numbers	34
1.33	ldexp, ldexpf—load exponent	36
1.34	log, logf—natural logarithms	37
1.35	log10, log10f—base 10 logarithms	38
1.36	log1p, log1pf—log of 1 + x	39
1.37	log2, log2f—base 2 logarithm	40
1.38	logb, logbf—get exponent of floating-point number	41

1.39	<code>lrint, lrintf, llrint, llrintf</code> —round to integer	42
1.40	<code>lround, lroundf, llround, llroundf</code> —round to integer, to nearest	43
1.41	<code>matherr</code> —modifiable math error handler	44
1.42	<code>modf, modff</code> —split fractional and integer parts	46
1.43	<code>nan, nanf</code> —representation of “Not a Number”	47
1.44	<code>nearbyint, nearbyintf</code> —round to integer	48
1.45	<code>nextafter, nextafterf</code> —get next number	49
1.46	<code>pow, powf</code> —x to the power y	50
1.47	<code>pow10, pow10f</code> —base 10 power functions	51
1.48	<code>remainder, remainderf</code> —round and remainder	52
1.49	<code>remquo, remquof</code> —remainder and part of quotient	53
1.50	<code>rint, rintf</code> —round to integer	54
1.51	<code>round, roundf</code> —round to integer, to nearest	55
1.52	<code>scalbn, scalbnf, scalbln, scalblnf</code> —scale by power of FLT_RADIX (=2)	56
1.53	<code>signbit</code> —Does floating-point number have negative sign?	57
1.54	<code>sin, sinf, cos, cosf</code> —sine or cosine	58
1.55	<code>sinh, sinh</code> f—hyperbolic sine	59
1.56	<code>sqrt, sqrtf</code> —positive square root	60
1.57	<code>tan, tanf</code> —tangent	61
1.58	<code>tanh, tanhf</code> —hyperbolic tangent	62
1.59	<code>trunc, truncf</code> —round to integer, towards zero	63

2 Mathematical Complex Functions (`complex.h`) .. 65

2.1	<code>cabs, cabsf, cabsl</code> —complex absolute-value	66
2.2	<code>cacos, cacosf</code> —complex arc cosine	67
2.3	<code>cacosh, cacoshf</code> —complex arc hyperbolic cosine	68
2.4	<code>carg, cargf</code> —argument (phase angle)	69
2.5	<code>casin, casinf</code> —complex arc sine	70
2.6	<code>casinh, casinhf</code> —complex arc hyperbolic sine	71
2.7	<code>catan, catanf</code> —complex arc tangent	72
2.8	<code>catanh, catanhf</code> —complex arc hyperbolic tangent	73
2.9	<code>ccos, ccosf</code> —complex cosine	74
2.10	<code>ccosh, ccoshf</code> —complex hyperbolic cosine	75
2.11	<code>cexp, cexpf</code> —complex base-e exponential	76
2.12	<code>cimag, cimagf, cimagl</code> —imaginary part	77
2.13	<code>clog, clogf</code> —complex base-e logarithm	78
2.14	<code>clog10, clog10f</code> —complex base-10 logarithm	79
2.15	<code>conj, conjf</code> —complex conjugate	80
2.16	<code>cpow, cpowf</code> —complex power	81
2.17	<code>cproj, cprojf</code> —Riemann sphere projection	82
2.18	<code>creal, crealf, creall</code> —real part	83
2.19	<code>csin, csinf</code> —complex sine	84
2.20	<code>csinh, csinhf</code> —complex hyperbolic sine	85
2.21	<code>csqrt, csqrtf</code> —complex square root	86
2.22	<code>ctan, ctanf</code> —complex tangent	87
2.23	<code>ctanh, ctanf</code> —complex hyperbolic tangent	88

3	Reentrancy Properties of libm	89
4	The long double function support of libm....	91
	Document Index	93

