ENGN6528 Computer Vision Semester 2, 2020

Thalaiyasingam Ajanthan

Majority of the slides from Miaomiao Liu

Week-1-part2

Image Formation, Representation

Outline

- What is a camera ?
- Geometric image formation
- Photometric image formation
- Image representation
  - Colour space

What is a camera ?



Slides from: F. Durand, S. Seitz, S. Lazebnik, S. Palmer

What is a camera ?



Slides from: F. Durand, S. Seitz, S. Lazebnik, S. Palmer

Let us design a camera

Let's design a camera



Idea 1: put a piece of film in front of an object

Will we get an image?

Slide by Steve Seitz

Turn any room into a camera

(Accidental pinhole, A. Torralba, MIT, published in IEEE CVPR 2012)

A new paper on ***Nature***

NEWS · 23 JANUARY 2019

How an ordinary camera can see around corners

Digital cameras have been used to reconstruct rough images of hidden objects just by analysing light that bounces off a wall.



Pinhole camera



Add a barrier to block off most of the rays

- This reduces blurring
- The opening is known as the ***aperture***

Slide by Steve Seitz

Shrinking the aperture



Why not make the aperture as small as possible?

- Less light gets through
- Diffraction effects…

Slide by Steve Seitz

Shrinking the aperture



Home-made pinhole camera

Slide by A. Efros

http://www.debevec.org/Pinhole/

Pinhole camera model



Pinhole model:

- Captures ***pencil of rays*** – all rays through a single point
- This point is called ***Center of Projection (focal point)***
- The image is formed on the **Image Plane**

Slide by Steve Seitz

Camera Obscura



Gemma Frisius, 1558

- Basic principle known to Mozi (470-390 BC, China), Aristotle (384-322 BC, Greek)
- Drawing aid for artists: described by Leonardo da Vinci (1452-1519)

Source: A. Efros

Adding a lens… to capture more light



A lens focuses light onto the film

- Rays passing through the center are not deviated

Slide by Steve Seitz

Adding a lens



Slide by Steve Seitz

Geometric Image Formation: Pinhole Camera Model

Pinhole camera

- Pinhole camera is a simple model to approximate imaging process: perspective **projection**.



- If we treat pinhole as a point, only one ray from any given point can enter the camera.

Fig from Forsyth and Ponce

Projection: world coordinates → image coordinates



General Camera Projection Matrix

Slide Credit: Saverese



$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{R} & \mathbf{t}\end{bmatrix}\mathbf{X}$$

x: Image Coordinates: (u,v,1)

K: Intrinsic Matrix (3x3)

R: Rotation (3x3)

t: Translation (3x1)

X: World Coordinates: (X,Y,Z,1)

Homogeneous coordinates Representation

Conversion

- Converting from Cartesian *to homogeneous* coordinates

$$(x, y) \Rightarrow \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

homogeneous image coordinates

$$(x, y, z) \Rightarrow \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

homogeneous scene coordinates

- Converting *from* homogeneous coordinates to cartesian

$$\begin{bmatrix} x \\ y \\ w \end{bmatrix} \Rightarrow (x/w, y/w)$$

$$\begin{bmatrix} x \\ y \\ z \\ w \end{bmatrix} \Rightarrow (x/w, y/w, z/w)$$

Homogeneous Coordinates

- Invariant to scaling

$$k\begin{bmatrix} x \\ y \\ w \end{bmatrix} = \begin{bmatrix} kx \\ ky \\ kw \end{bmatrix} \Rightarrow \begin{bmatrix} \frac{kx}{kw} \\ \frac{ky}{kw} \end{bmatrix} = \begin{bmatrix} \frac{x}{w} \\ \frac{y}{w} \end{bmatrix}$$

Homogeneous Coordinates **Cartesian Coordinates**

- Point in cartesian is a ray in homogeneous

Projection matrix



Intrinsic Assumptions

- Unit aspect ratio
- Optical center at (0,0)
- No skew

Extrinsic Assumptions

- No rotation
- Camera at (0,0,0)

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{I} & \mathbf{0}\end{bmatrix}\mathbf{X} \Rightarrow w\begin{bmatrix}u\\v\\1\end{bmatrix} = \overbrace{\begin{bmatrix}f & 0 & 0 & 0\\0 & f & 0 & 0\\0 & 0 & 1 & 0\end{bmatrix}}^{\mathbf{K}}\begin{bmatrix}x\\y\\z\\1\end{bmatrix}$$

Slide Credit: Saverese

Remove assumption of known optical center

Intrinsic Assumptions

- Unit aspect ratio
- No skew

Extrinsic Assumptions

- No rotation
- Camera at (0,0,0)

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{I} & \mathbf{0}\end{bmatrix}\mathbf{X} \Rightarrow w\begin{bmatrix}u\\v\\1\end{bmatrix} = \begin{bmatrix}f & 0 & u_0 & 0\\0 & f & v_0 & 0\\0 & 0 & 1 & 0\end{bmatrix}\begin{bmatrix}x\\y\\z\\1\end{bmatrix}$$

Remove assumption: square pixels

Intrinsic Assumptions

- No skew

Extrinsic Assumptions

- No rotation
- Camera at (0,0,0)

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{I} & \mathbf{0}\end{bmatrix}\mathbf{X} \Rightarrow w\begin{bmatrix}u\\ v\\ 1\end{bmatrix} = \begin{bmatrix}\alpha & 0 & u_0 & 0\\ 0 & \beta & v_0 & 0\\ 0 & 0 & 1 & 0\end{bmatrix}\begin{bmatrix}x\\ y\\ z\\ 1\end{bmatrix}$$

Remove assumption: non-skewed pixels

Intrinsic Assumptions

Extrinsic Assumptions

- No rotation
- Camera at (0,0,0)

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{I} & \mathbf{0}\end{bmatrix}\mathbf{X} \Rightarrow w\begin{bmatrix}u\\ v\\ 1\end{bmatrix} = \begin{bmatrix}\alpha & s & u_0 & 0\\ 0 & \beta & v_0 & 0\\ 0 & 0 & 1 & 0\end{bmatrix}\begin{bmatrix}x\\ y\\ z\\ 1\end{bmatrix}$$

Note: different books use different notation for parameters

Rotated and Translated Camera



Allow Camera Translation

Intrinsic Assumptions

Extrinsic Assumptions

- No rotation

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{I} & \mathbf{t}\end{bmatrix}\mathbf{X} \Rightarrow w\begin{bmatrix}u\\ v\\ 1\end{bmatrix} = \begin{bmatrix}\alpha & 0 & u_0\\ 0 & \beta & v_0\\ 0 & 0 & 1\end{bmatrix}\begin{bmatrix}1 & 0 & 0 & t_x\\ 0 & 1 & 0 & t_y\\ 0 & 0 & 1 & t_z\end{bmatrix}\begin{bmatrix}x\\ y\\ z\\ 1\end{bmatrix}$$

3D Rotation of Points

$$R_x(\theta) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(\theta) & -\sin(\theta) \\ 0 & \sin(\theta) & \cos(\theta) \end{bmatrix}$$



x coordinate is unchanged after rotation around x-axis



View looking down –x

3D Rotation of Points

$$R_y(\theta) = \begin{bmatrix} \cos(\theta) & 0 & \sin(\theta) \\ 0 & 1 & 0 \\ -\sin(\theta) & 0 & \cos(\theta) \end{bmatrix}$$



y coordinate is unchanged after rotation around y-axis



View looking down –y

3D Rotation of Points

$$R_z(\theta) = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



z coordinate is unchanged after rotation around z-axis



View looking down –z

General Camera Projection Matrix

Slide Credit: Saverese



$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{R} & \mathbf{t}\end{bmatrix}\mathbf{X}$$

x: Image Coordinates: (u,v,1)

K: Intrinsic Matrix (3x3)

R: Rotation (3x3)

t: Translation (3x1)

X: World Coordinates: (X,Y,Z,1)

General Camera Projection Matrix

Slide Credit: Saverese

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{R} & \mathbf{t}\end{bmatrix}\mathbf{X}$$

$$w\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \begin{bmatrix} \alpha & s & u_0 \\ 0 & \beta & v_0 \\ 0 & 0 & 1 \end{bmatrix}\begin{bmatrix} r_{11} & r_{12} & r_{13} & t_x \\ r_{21} & r_{22} & r_{23} & t_y \\ r_{31} & r_{32} & r_{33} & t_z \end{bmatrix}\begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

General Camera Projection Matrix

Slide Credit: Saverese

$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{R} & \mathbf{t}\end{bmatrix}\mathbf{X}$$

$$w\begin{bmatrix} u \\ v \\ 1 \end{bmatrix} = \underbrace{\begin{bmatrix} \alpha & s & u_0 \\ 0 & \beta & v_0 \\ 0 & 0 & 1 \end{bmatrix}}_{5} \underbrace{\begin{bmatrix} r_{11} & r_{12} & r_{13} & t_x \\ r_{21} & r_{22} & r_{23} & t_y \\ r_{31} & r_{32} & r_{33} & t_z \end{bmatrix}}_{6} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

A quick summary

- Pinhole camera model and camera projection matrix
- Homogeneous coordinates



$$\mathbf{x} = \mathbf{K}\begin{bmatrix}\mathbf{R} & \mathbf{t}\end{bmatrix}\mathbf{X}$$

$$(x, y) \Rightarrow \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

Perspective effects

3D computer vision aims to solve an inverse problem of computer graphics

Photometric (radiometric) image formation

What determines scene radiance?

- The amount of light that falls on the surface
- The fraction of light that is reflected (albedo)
- Geometry of light reflection
  - Shape of surface
  - Viewpoint



Surface Normal

Convenient notation for surface orientation

A smooth surface has a tangent plane at every point



We can model the surface using the normal at every point



Lambertian surface

- Ideal diffuse reflectors.

- The apparent brightness of such a surface to an observer is the same regardless of the observer's angle of view.



Ideal diffuse reflection (Lambertian surface)

Diffuse reflection with directional component



Lambertian Surface

- Appears equally bright from all viewing directions
- Reflects all light without absorbing
- Matte surface, no “shiny” spots
- Brightness of the surface as seen from camera is linearly correlated to the amount of light falling on the surface



Photometric Image Formation



Sensor Array



a b

FIGURE 2.17 (a) Continuos image projected onto a sensor array. (b) Result of image sampling and quantization.



CCD/CMOS sensor

Image Sensors : Array Sensor



CCD KAF-3200E from Kodak.

(2184 x 1472 pixels,

Pixel size 6.8 microns^2)

Charge-Coupled Device (CCD)

- Used for convert a continuous image into a digital image
- Contains an array of light sensors
- Converts photon into electric charges accumulated in each sensor unit

Human Color Perception



Figure 1





A website about human color perception:

- http://www.photo.net/photo/edscott/vis00010.htm

How many Colors can be Seen?

- Human eyes can distinguish about
  - 128 different hues
  - 130 different saturation levels

- We can distinguish about 380,000 colours!!



- Wavelength of the light





Colour Images

- are constructed from three intensity maps.
- Each intensity map is projected through a colour filter (*e.g.,* red, green, or blue, or cyan, magenta, or yellow) to create a monochrome image.
- The intensity maps are overlaid to create a color image.
- Each pixel in a color image is a three dimensional vector.



Digital image representation

The digital image (pixel matrix)



The digital image (pixel matrix)



Fundamentals of Digital Images

- An image = a function of spatial coordinates.
- Spatial coordinate: (x,y) for 2D case such as photograph,

  (x,y,z) for 3D case such as CT scan images

  (x,y,t) for video.
- The function f may represent intensity (for greyscale images) or color (for color images) or other associated values.

Conventional Coordinate for Image Representa



(Images from Rafael C. Gonzalez and Richard E. Wood, Digital Image Processing, 2nd Edition.

Grey-scale Image



Intensity image or grey-scale image

Each pixel corresponds to light intensity normally represented in gray scale (gray level).

Gray scale values

$$\begin{bmatrix} 10 & 10 & 16 & 28 \\ 9 & 6 & 26 & 37 \\ 15 & 25 & 13 & 22 \\ 32 & 15 & 87 & 39 \end{bmatrix}$$

Effect of Spatial Resolution



FIGURE 2.19 A 1024 × 1024, 8-bit image subsampled down to size 32 × 32 pixels. The number of allowable gray levels was kept at 256.

(Images from Rafael C. Gonzalez and Richard E. Wood, Digital Image Processing, 2nd Edition.

Effect of Spatial Resolution



a b c
d e f

FIGURE 2.20 (a) 1024 × 1024, 8-bit image. (b) 512 × 512 image resampled into 1024 × 1024 pixels by row and column duplication. (c) through (f) 256 × 256, 128 × 128, 64 × 64, and 32 × 32 images resampled into 1024 × 1024 pixels.

(Images from Rafael C. Gonzalez and Richard E Wood, Digital Image Processing, 2nd Edition.

Effect of Spatial Resolution

256x256 pixels



128x128 pixels



64x64 pixels



32x32 pixels

Effect of Quantization Levels



256 levels

128 levels



64 levels

32 levels

Effect of Quantization Levels (cont.)



16 levels



8 levels

In this image, it is easy to see false contour.

4 levels

2 levels

Two-level image: binary image

Binary image or black and white image

- Each pixel contains one bit :
  - 1 represent white
  - 0 represents black



Binary data

$$\begin{bmatrix} 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 1 & 1 & 1 \\ 1 & 1 & 1 & 1 \end{bmatrix}$$

Colour Images

A colourful image

Colour Image

- Colour images have 3 values per pixel;
- Greyscale images have 1 value per pixel.

a grid of squares, each of which contains a single colour

each square is called a pixel (for *picture element*)



Colour Image



Color (RGB) image:

- each pixel contains a vector representing red, green and blue components.

RGB components

$$\begin{bmatrix} 10 & 10 & 16 & 28 \\ 9 & \cdots & \cdots & \cdots \\ 15 & \cdots & \cdots & \cdots \\ 32 & \cdots & \cdots & \cdots \end{bmatrix} \quad \begin{bmatrix} 65 & 70 & 56 & 43 \\ 32 & \cdots & \cdots & \cdots \\ 21 & \cdots & \cdots & \cdots \\ 54 & \cdots & \cdots & \cdots \end{bmatrix} \quad \begin{bmatrix} 99 & 70 & 56 & 78 \\ 60 & 90 & 96 & 67 \\ 85 & 85 & 43 & 92 \\ 32 & 65 & 87 & 99 \end{bmatrix}$$

Colour Image



- Colour image = a multidimensional array of numbers (such as intensity image) or vectors (such as color image)

- Each component in the image called pixel associates with the pixel value (a single number in the case of intensity images or a vector in the case of color images)

Colour Image



Colour Images in Matlab

Images represented as a matrix

Suppose we have a NxM RGB image called “im”

- im(1,1,1) = top-left pixel value in R-channel
- im(y, x, b) = y pixels down, x pixels to right in the b^{th} channel

imread(filename) returns a uint8 image (values 0 to 255)

- **Convert to double format (values 0 to 1) with im2double(). (important !)**



Color spaces



http://en.wikipedia.org/wiki/File:RGB_illumination.jpg

RGB space

Default color space



R

(G=0,B=0)

G

(R=0,B=0)

B

(R=0,G=0)

Some drawbacks

- Strongly correlated channels
- Not perceptually meaningful.

Image from: http://en.wikipedia.org/wiki/File:RGB_color_solid_cube.

HSV space





H

(S=1,V=1)

S

(H=1,V=1)

V

(H=1,S=0)

Intuitive color space

YCbCr (YUV) space



Y

(Cb=0.5,Cr=0.5)

Cb

(Y=0.5,Cr=0.5)

Cr

(Y=0.5,Cb=05)

Fast to compute, good for compression, used by TV

CIE-L*a*b* space



“Perceptually uniform” color space

L

(a=0,b=0)

a

(L=65,b=0)

b

(L=65,a=0)

Conversions between different colour spaces

$$H = \arccos \frac{\frac{1}{2}((R-G)+(R-B))}{\sqrt{((R-G)^2+(R-B)(G-B))}}$$

$$S = 1-3\frac{\min(R,G,B)}{R+G+B}$$

$$V = \frac{1}{3}(R+G+B)$$

$$Y = 0.299R+0.587G+0.114B$$

$$C_r = R-Y$$

$$C_b = B-Y$$

Most semantic information is however contained in the intensity band



Original image

Most information is contained in intensity channel