X-Mem 2.4.1

Generated by Doxygen 1.8.6

Thu Apr 7 2016 08:15:17

Contents

1	REA	DME			1
2	Hier	archica			7
	2.1	Class	Hierarchy		7
3	Clas	s Index			9
	3.1	Class	List		9
4	File	Index			11
	4.1	File Lis	st		11
5	Clas	s Docu	mentation	1	13
	5.1	xmem:	::Parser::A	ction Struct Reference	13
		5.1.1	Member	Function Documentation	13
			5.1.1.1	finished	13
			5.1.1.2	perform	13
	5.2	xmem:	::Arg Struc	t Reference	14
		5.2.1	Detailed	Description	14
	5.3	xmem:	::Benchma	rk Class Reference	15
		5.3.1	Detailed	Description	17
		5.3.2	Construc	ctor & Destructor Documentation	17
			5.3.2.1	Benchmark	17
		5.3.3	Member	Function Documentation	18
			5.3.3.1	get25PercentileMetric	18
			5.3.3.2	get75PercentileMetric	18
			5.3.3.3	get95PercentileMetric	18
			5.3.3.4	get99PercentileMetric	18
			5.3.3.5	getChunkSize	18
			5.3.3.6	getCPUNode	18
			5.3.3.7	getIterations	19
			5.3.3.8	getLen	19
			5.3.3.9	getMaxMetric	19
			53310	getMeanDRAMPower	19

iv CONTENTS

	5.3.3.11	getMeanMetric	19
	5.3.3.12	getMedianMetric	19
	5.3.3.13	getMemNode	20
	5.3.3.14	getMetricOnIter	20
	5.3.3.15	getMetricUnits	20
	5.3.3.16	getMinMetric	20
	5.3.3.17	getModeMetric	20
	5.3.3.18	getName	20
	5.3.3.19	getNumThreads	21
	5.3.3.20	getPatternMode	21
	5.3.3.21	getPeakDRAMPower	21
	5.3.3.22	getRWMode	21
	5.3.3.23	getStrideSize	21
	5.3.3.24	hasRun	21
	5.3.3.25	isValid	21
	5.3.3.26	run	22
	5.3.3.27	runCore	22
	5.3.3.28	startPowerThreads	22
	5.3.3.29	stopPowerThreads	22
5.3.4	Member	Data Documentation	22
	5.3.4.1	chunk_size	22
	5.3.4.2	cpu_node	22
	5.3.4.3	dram_power_readers	22
	5.3.4.4	dram_power_threads	22
	5.3.4.5	has_run	23
	5.3.4.6	iterations	23
	5.3.4.7	len	23
	5.3.4.8	max_metric	23
	5.3.4.9	mean_dram_power_socket	23
	5.3.4.10	mean_metric	23
	5.3.4.11	median_metric	23
	5.3.4.12	mem_array	23
	5.3.4.13	mem_node	23
	5.3.4.14	metric_on_iter	23
	5.3.4.15	metric_units	23
	5.3.4.16	min_metric	24
	5.3.4.17	mode_metric	24
	5.3.4.18	name	24
	5.3.4.19	num_worker_threads	24
	5.3.4.20	obj_valid	24

CONTENTS

		5.3.4.21	pattern_mode	24
		5.3.4.22	peak_dram_power_socket	24
		5.3.4.23	percentile_25_metric	24
		5.3.4.24	percentile_75_metric	24
		5.3.4.25	percentile_95_metric	24
		5.3.4.26	percentile_99_metric	24
		5.3.4.27	rw_mode	25
		5.3.4.28	stride_size	25
		5.3.4.29	warning	25
5.4	xmem:	:Benchma	rkManager Class Reference	25
	5.4.1	Detailed	Description	25
	5.4.2	Construc	tor & Destructor Documentation	25
		5.4.2.1	BenchmarkManager	25
	5.4.3	Member	Function Documentation	26
		5.4.3.1	runAll	26
		5.4.3.2	runLatencyBenchmarks	26
		5.4.3.3	runThroughputBenchmarks	26
5.5	xmem:	:Configura	tor Class Reference	26
	5.5.1	Detailed	Description	28
	5.5.2	Member	Function Documentation	28
		5.5.2.1	configureFromInput	28
		5.5.2.2	extensionsEnabled	28
		5.5.2.3	getCpuNumaNodeAffinities	28
		5.5.2.4	getIterationsPerTest	28
		5.5.2.5	getMemoryNumaNodeAffinities	29
		5.5.2.6	getNumWorkerThreads	29
		5.5.2.7	getOutputFilename	29
		5.5.2.8	getStartingTestIndex	29
		5.5.2.9	getWorkingSetSizePerThread	29
		5.5.2.10	isNUMAEnabled	29
		5.5.2.11	latencyTestSelected	29
		5.5.2.12	runExtDelayInjectedLoadedLatencyBenchmark	30
		5.5.2.13	setUseOutputFile	30
		5.5.2.14	throughputTestSelected	30
		5.5.2.15	useChunk32b	30
		5.5.2.16	useLargePages	30
		5.5.2.17	useOutputFile	30
		5.5.2.18	useRandomAccessPattern	30
		5.5.2.19	useReads	31
		5.5.2.20	useSequentialAccessPattern	31

vi CONTENTS

		5.5.2.21	useStrideN1	31
		5.5.2.22	useStrideN16	31
		5.5.2.23	useStrideN2	31
		5.5.2.24	useStrideN4	31
		5.5.2.25	useStrideN8	31
		5.5.2.26	useStrideP1	32
		5.5.2.27	useStrideP16	32
		5.5.2.28	useStrideP2	32
		5.5.2.29	useStrideP4	32
		5.5.2.30	useStrideP8	32
		5.5.2.31	useWrites	32
		5.5.2.32	verboseMode	33
5.6	xmem:	:Stats::Cou	untOptionsAction Class Reference	33
	5.6.1	Construc	tor & Destructor Documentation	33
		5.6.1.1	CountOptionsAction	33
	5.6.2	Member I	Function Documentation	33
		5.6.2.1	perform	33
5.7	xmem:	•	r Struct Reference	33
	5.7.1	Detailed I	Description	34
	5.7.2	Member I	Data Documentation	34
		5.7.2.1	check_arg	34
		5.7.2.2	help	34
		5.7.2.3	index	35
		5.7.2.4	longopt	35
		5.7.2.5	shortopt	35
			type	36
5.8			arg Class Reference	36
5.9	xmem:	:PrintUsag	eImplementation::FunctionWriter< Function > Struct Template Reference	36
		_	eImplementation::IStringWriter Struct Reference	36
5.11		_	enchmark Class Reference	37
	5.11.1	Detailed I	Description	37
	5.11.2	Member I	Function Documentation	38
		5.11.2.1	getLoadMetricOnIter	38
		5.11.2.2	getMeanLoadMetric	38
		5.11.2.3	runCore	38
	5.11.3	Member I	Data Documentation	38
		5.11.3.1	load_metric_on_iter	38
			mean_load_metric	38
5.12			orker Class Reference	38
	5.12.1	Detailed I	Description	39

CONTENTS vii

5.12.2	Constructor & Destructor Documentation	39
	5.12.2.1 LatencyWorker	39
xmem::	:PrintUsageImplementation::LinePartIterator Class Reference	39
5.13.1	Member Function Documentation	40
	5.13.1.1 next	40
	5.13.1.2 nextRow	40
	5.13.1.3 nextTable	40
xmem::	:PrintUsageImplementation::LineWrapper Class Reference	40
5.14.1	Constructor & Destructor Documentation	41
	5.14.1.1 LineWrapper	41
5.14.2	Member Function Documentation	41
	5.14.2.1 process	41
xmem::	:LoadWorker Class Reference	41
5.15.1	Detailed Description	42
5.15.2	Constructor & Destructor Documentation	42
	5.15.2.1 LoadWorker	42
	5.15.2.2 LoadWorker	42
xmem::	:MemoryWorker Class Reference	42
5.16.1	Detailed Description	43
5.16.2	Constructor & Destructor Documentation	43
	5.16.2.1 MemoryWorker	43
5.16.3	Member Function Documentation	44
	5.16.3.1 getAdjustedTicks	44
	5.16.3.2 getBytesPerPass	44
	5.16.3.3 getElapsedDummyTicks	44
	5.16.3.4 getElapsedTicks	44
	5.16.3.5 getLen	44
	5.16.3.6 getPasses	45
	5.16.3.7 hadWarning	45
5.16.4	Member Data Documentation	45
	5.16.4.1 adjusted_ticks	45
	5.16.4.2 bytes_per_pass	45
	5.16.4.3 completed	45
	5.16.4.4 cpu_affinity	45
	5.16.4.5 elapsed_dummy_ticks	45
	5.16.4.6 elapsed_ticks	45
	5.16.4.7 len	45
	5.16.4.8 mem_array	46
	5.16.4.9 passes	46
	5.16.4.10 warning	46
	xmem: 5.13.1 xmem: 5.14.1 5.14.2 xmem: 5.15.1 5.15.2 xmem: 5.16.1 5.16.2	5.12.2.1 LatencyWorker xmem::PrintUsageImplementation::LinePartIterator Class Reference 5.13.1.1 next 5.13.1.2 nextRow 5.13.1.3 nextTable xmem::PrintUsageImplementation::LineWrapper Class Reference 5.14.1.1 LineWrapper 5.14.2.1 process xmem::LoadWorker Class Reference 5.15.1 Detailed Description 5.15.2.1 LoadWorker 5.15.2.2 LoadWorker 5.15.2.1 LoadWorker 5.15.2.2 LoadWorker 5.15.2.1 LoadWorker 5.15.2.2 LoadWorker 5.15.2.1 LoadWorker 5.16.2 LoadWorker 5.16.3.1 Detailed Description 5.16.2 Destructor & Destructor Documentation 5.16.3.1 getAgiustedTicks 5.16.3.2 getBytesPerPass 5.16.3.3 getElapsedDirks 5.16.3.5 getLapsedTicks 5.16.3.7 hadWarning 5.16.4.1 adjusted_ticks 5.16.4.2

viii CONTENTS

5.17	xmem::	MyArg Class Reference
5.18	xmem::	Option Class Reference
	5.18.1	Detailed Description
	5.18.2	Constructor & Destructor Documentation
		5.18.2.1 Option
		5.18.2.2 Option
	5.18.3	Member Function Documentation
		5.18.3.1 append
		5.18.3.2 count
		5.18.3.3 first
		5.18.3.4 isFirst
		5.18.3.5 isLast
		5.18.3.6 last
		5.18.3.7 next
		5.18.3.8 nextwrap
		5.18.3.9 operator const Option *
		5.18.3.10 operator Option *
		5.18.3.11 operator=
		5.18.3.12 prev
		5.18.3.13 prevwrap
		5.18.3.14 type
	5.18.4	Member Data Documentation
		5.18.4.1 arg
		5.18.4.2 desc
		5.18.4.3 name
		5.18.4.4 namelen
5.19	xmem::	PrintUsageImplementation::OStreamWriter< OStream > Struct Template Reference 52
5.20	xmem::	Parser Class Reference
	5.20.1	The second secon
	5.20.2	Constructor & Destructor Documentation
		5.20.2.1 Parser
	5.20.3	Member Function Documentation
		5.20.3.1 error
		5.20.3.2 nonOptions
		5.20.3.3 nonOptionsCount
		5.20.3.4 optionsCount
		5.20.3.5 parse
5.21		PowerReader Class Reference
		Detailed Description
	5.21.2	Constructor & Destructor Documentation

CONTENTS

		5.21.2.1 PowerReader	58
	5.21.3	Member Function Documentation	58
		5.21.3.1 calculateMetrics	58
		5.21.3.2 clear	58
		5.21.3.3 clearAndReset	58
		5.21.3.4 getLastSample	58
		5.21.3.5 getMeanPower	59
		5.21.3.6 getNumSamples	59
		5.21.3.7 getPeakPower	59
		5.21.3.8 getPowerTrace	59
		5.21.3.9 getPowerUnits	59
		5.21.3.10 getSamplingPeriod	60
		5.21.3.11 name	60
		5.21.3.12 stop	60
	5.21.4	Member Data Documentation	60
		5.21.4.1 cpu_affinity	60
		5.21.4.2 mean_power	60
		5.21.4.3 name	60
		5.21.4.4 num_samples	60
		5.21.4.5 peak_power	60
		5.21.4.6 power_trace	61
		5.21.4.7 power_units	61
		5.21.4.8 sampling_period	61
		5.21.4.9 stop_signal	61
5.22	xmem::	PrintUsageImplementation Struct Reference	61
	5.22.1	Member Function Documentation	61
		5.22.1.1 isWideChar	61
5.23	xmem::	Runnable Class Reference	62
	5.23.1	Detailed Description	62
	5.23.2	Member Function Documentation	62
		5.23.2.1 acquireLock	62
		5.23.2.2 releaseLock	63
5.24	xmem::	Stats Struct Reference	63
	5.24.1	Detailed Description	64
	5.24.2	Constructor & Destructor Documentation	64
		5.24.2.1 Stats	64
	5.24.3	Member Function Documentation	64
		5.24.3.1 add	64
	5.24.4	Member Data Documentation	65
		5.24.4.1 buffer_max	65

CONTENTS

		5.24.4.2 options_max
5.25	xmem:	Parser::StoreOptionAction Class Reference
	5.25.1	Constructor & Destructor Documentation
		5.25.1.1 StoreOptionAction
	5.25.2	Member Function Documentation
		5.25.2.1 finished
		5.25.2.2 perform
5.26	xmem:	PrintUsageImplementation::StreamWriter< Function, Stream > Struct Template Reference 66
5.27	xmem:	PrintUsageImplementation::SyscallWriter< Syscall > Struct Template Reference 6
5.28	xmem:	:PrintUsageImplementation::TemporaryWriter< Temporary > Struct Template Reference 6
5.29	xmem:	Thread Class Reference
	5.29.1	Detailed Description
	5.29.2	Constructor & Destructor Documentation
		5.29.2.1 Thread
		5.29.2.2 ~Thread
	5.29.3	Member Function Documentation
		5.29.3.1 cancel
		5.29.3.2 completed
		5.29.3.3 create_and_start
		5.29.3.4 created
		5.29.3.5 getExitCode
		5.29.3.6 getTarget
		5.29.3.7 isThreadRunning
		5.29.3.8 isThreadSuspended
		5.29.3.9 join
		5.29.3.10 started
		5.29.3.11 validTarget
5.30	xmem:	ThroughputBenchmark Class Reference
	5.30.1	Detailed Description
	5.30.2	Member Function Documentation
		5.30.2.1 runCore
5.31	xmem:	Timer Class Reference
	5.31.1	Detailed Description
	5.31.2	Member Function Documentation
		5.31.2.1 getNsPerTick
		5.31.2.2 getTicksPerMs
	5.31.3	Member Data Documentation
		5.31.3.1 ns_per_tick
		5.31.3.2 ticks_per_ms

CONTENTS xi

6	File I	Docume	ntation	73
	6.1	src/Ber	chmark.cpp File Reference	73
		6.1.1	Detailed Description	73
	6.2	src/ben	hmark_kernels.cpp File Reference	73
		6.2.1	Detailed Description	73
	6.3	src/Ber	hmarkManager.cpp File Reference	74
		6.3.1	Detailed Description	74
	6.4	src/con	mon.cpp File Reference	74
		6.4.1	Detailed Description	75
	6.5	src/Cor	igurator.cpp File Reference	75
		6.5.1	Detailed Description	75
	6.6		elayInjectedLoadedLatencyBenchmark/delay_injected_benchmark_kernels.cpp File Refer-	
				75
		6.6.1	•	75
	6.7		PelayInjectedLoadedLatencyBenchmark/DelayInjectedLoadedLatencyBenchmark.cpp File	75
		6.7.1	Detailed Description	76
	6.8	src/incl	de/Benchmark.h File Reference	76
		6.8.1	Detailed Description	76
	6.9	src/incl	de/benchmark_kernels.h File Reference	76
		6.9.1	Detailed Description	78
	6.10	src/incl	de/BenchmarkManager.h File Reference	78
		6.10.1	Detailed Description	79
	6.11	src/incl	de/common.h File Reference	79
		6.11.1	Detailed Description	81
		6.11.2	Macro Definition Documentation	81
			6.11.2.1 BENCHMARK_DURATION_MS	81
			6.11.2.2 DEFAULT_LARGE_PAGE_SIZE	81
			6.11.2.3 DEFAULT_NUM_L1_CACHES	81
			6.11.2.4 DEFAULT_NUM_L2_CACHES	81
			6.11.2.5 DEFAULT_NUM_L3_CACHES	81
			6.11.2.6 DEFAULT_NUM_L4_CACHES	81
			6.11.2.7 DEFAULT_NUM_LOGICAL_CPUS	82
			3.11.2.8 DEFAULT_NUM_NODES	82
			6.11.2.9 DEFAULT_NUM_PHYSICAL_CPUS	82
			6.11.2.10 DEFAULT_NUM_PHYSICAL_PACKAGES	82
			3.11.2.11 DEFAULT_NUM_WORKER_THREADS	82
			3.11.2.12 DEFAULT_PAGE_SIZE	82
			3.11.2.13 DEFAULT_WORKING_SET_SIZE_PER_THREAD	82
			5.11.2.14 EXT_DELAY_INJECTED_LOADED_LATENCY_BENCHMARK	82

xii CONTENTS

	6.11.2.15 LATENCY_BENCHMARK_UNROLL_LENGTH	82
	6.11.2.16 MIN_ELAPSED_TICKS	82
	6.11.2.17 POWER_SAMPLING_PERIOD_MS	82
	6.11.2.18 THROUGHPUT_BENCHMARK_BYTES_PER_PASS	83
	6.11.2.19 USE_OS_TIMER	83
6.12	src/include/Configurator.h File Reference	83
	6.12.1 Detailed Description	83
6.13	src/include/ExampleArg.h File Reference	84
	6.13.1 Detailed Description	84
6.14	src/include/ext/DelayInjectedLoadedLatencyBenchmark/delay_injected_benchmark_kernels.h File Reference	84
	6.14.1 Detailed Description	86
6.15	src/include/ext/DelayInjectedLoadedLatencyBenchmark/DelayInjectedLoadedLatencyBenchmark.h	86
	6.15.1 Detailed Description	86
6.16	src/include/LatencyBenchmark.h File Reference	86
	6.16.1 Detailed Description	86
6.17	src/include/LatencyWorker.h File Reference	86
	6.17.1 Detailed Description	87
6.18	src/include/LoadWorker.h File Reference	87
	6.18.1 Detailed Description	87
6.19	src/include/MemoryWorker.h File Reference	87
	6.19.1 Detailed Description	87
6.20	src/include/MyArg.h File Reference	87
	6.20.1 Detailed Description	88
6.21	src/include/optionparser.h File Reference	88
	6.21.1 Detailed Description	89
6.22	src/include/PowerReader.h File Reference	91
	6.22.1 Detailed Description	92
6.23	src/include/Runnable.h File Reference	92
	6.23.1 Detailed Description	92
6.24	src/include/Thread.h File Reference	92
	6.24.1 Detailed Description	92
6.25	src/include/ThroughputBenchmark.h File Reference	92
	6.25.1 Detailed Description	93
6.26	src/include/Timer.h File Reference	93
	6.26.1 Detailed Description	93
6.27	src/include/win/win_common_third_party.h File Reference	93
	6.27.1 Detailed Description	93
6.28	src/include/win/win_CPdhQuery.h File Reference	93

CONTENTS xiii

	6.28.1 Detailed Description	93
6.29	src/include/win/WindowsDRAMPowerReader.h File Reference	93
	6.29.1 Detailed Description	94
6.30	src/LatencyBenchmark.cpp File Reference	94
	6.30.1 Detailed Description	94
6.31	src/LatencyWorker.cpp File Reference	94
	6.31.1 Detailed Description	94
6.32	src/LoadWorker.cpp File Reference	94
	6.32.1 Detailed Description	94
6.33	src/main.cpp File Reference	95
	6.33.1 Detailed Description	95
6.34	src/MemoryWorker.cpp File Reference	95
	6.34.1 Detailed Description	95
6.35	src/PowerReader.cpp File Reference	95
	6.35.1 Detailed Description	95
6.36	src/Runnable.cpp File Reference	96
	6.36.1 Detailed Description	96
6.37	src/Thread.cpp File Reference	96
	6.37.1 Detailed Description	96
6.38	src/ThroughputBenchmark.cpp File Reference	96
	6.38.1 Detailed Description	96
6.39	src/Timer.cpp File Reference	97
	6.39.1 Detailed Description	97
6.40	src/win/win_common_third_party.cpp File Reference	97
	6.40.1 Detailed Description	97
6.41	src/win/WindowsDRAMPowerReader.cpp File Reference	97
	6.41.1 Detailed Description	97
Index		98

Chapter 1

README

X-Mem: A Cross-Platform and Extensible Memory Characterization Tool for the Cloud v2.4.1

X-Mem is a flexible open-source research tool for characterizing memory hierarchy throughput, latency, power, and more. The tool was developed jointly by Microsoft and the UCLA NanoCAD Lab. This project was started by Mark Gottscho (Email: mgottscho@ucla.edu) as a Summer 2014 PhD intern at Microsoft Research. X-Mem is released freely and open-source under the MIT License. The project is under active development.

PROJECT REVISION DATE: April 7, 2016

RESEARCH PAPER & ATTRIBUTION

We have a research tool paper describing the motivation, design, and implementation of X-Mem, as well as three experimental case studies using tools to deliver insights useful to both cloud providers and subscribers. If you use our tool and publish or otherwise publicly report results, we ask that you please cite the following paper as well as provide a link to our tool homepage (https://nanocad-lab.github.io/X-Mem).

Download the pre-print of our paper here: http://nanocad.ee.ucla.edu/pub/Main/Publications/-C91_paper.pdf.

Citation:

Mark Gottscho, Sriram Govindan, Bikash Sharma, Mohammed Shoaib, and Puneet Gupta. X-Mem: A Cross-Platform and Extensible Memory Characterization Tool for the Cloud. In Proceedings of the IEEE International Symposium on Performance Analysis of Systems and Software (ISPASS). Uppsala, Sweden, April 17-19, 2016.

BiBTeX:

{GottschoISPASS2016, author = {Gottscho, Mark and Govindan, Sriram and Sharma, Bikash and Shoaib, Mohammed and Gupta, Puneet}, booktitle = {Proceedings of the IEEE International Symposium on Performance Analysis of Systems and Software (ISPASS)}, title = {{X-Mem}: A Cross-Platform and Extensible Memory Characterization Tool for the Cloud}, month = {April}, year = {2016}}

VERSION CONTROL AND OBTAINING SOURCE CODE

This project is under version control using git. Its master repository is hosted at https://github.com/-Microsoft/X-Mem.git. There is also another mirrored fork at https://github.com/nanocad-lab/-X-Mem.git.

OBTAINING PRE-BUILT BINARIES

If you don't want to build X-Mem from source, you can get regular releases of pre-built binaries for Windows and GNU/Linux from the project homepage, located at https://nanocad-lab.github.io/X-Mem.

2 README

LICENSE

The MIT License (MIT)

Copyright (c) 2014 Microsoft

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

DESIGN PHILOSOPHY

Previous memory benchmarking tools such as STREAM/STREAM2, Imbench3, and mlc all had various shortcomings that made them inadequate for emerging needs in the cloud. In particular, cloud systems present four key challenges that we addressed with X-Mem. Please refer to our ISPASS'16 paper above for more information.

FEATURES

This tool is provided as open source with the hope of being useful to the broader research and development community. Here is a non-exhaustive list of X-Mem's features.

Flexibility: Easy reconfiguration for different combinations of tests.

- · Working sets in increments of 4KB, allowing cache up to main memory-level benchmarking.
- NUMA support.
- Multi-threading support.
- Large page support.

Extensibility: Modularity via C++11 object-oriented principles.

- · Supports rapid addition of new benchmark kernel routines.
- Example: stream triad algorithm, impact of false sharing, etc. are possible with minor changes.

Cross-platform: Currently implemented for two OSes and architecture families.

- GNU/Linux: Intel x86 (32-bit), x86-64, and x86-64 with AVX extensions, ARM (32-bit), ARM (32-bit) with NE-ON, ARMv8 (64-bit), Xeon Phi (Intel mic, Knights Corner). Tested specifically with Ubuntu 12.04, 14.04, and CentOS 7.
- Windows: Intel x86 (32-bit), x86-64, and x86-64 with AVX extensions. Tested specifically with Windows 8.1 and Server 2012 R2.
- ARM on Windows can compile using VC++, but cannot link due to a lack of library support for desktop/command-line ARM apps. This may be resolved in the future.
- Designed to allow straightforward porting to other operating systems and ISAs.

Memory throughput:

- · Accurate measurement of sustained memory throughput to all levels of cache and memory.
- Regular access patterns: forward & reverse sequential as well as strides of 2, 4, 8, and 16 words.
- · Random access patterns.
- · Read and write.
- 32, 64, 128, 256, 512-bit width memory instructions where applicable on each architecture.

Memory latency:

- · Accurate measurement of round-trip memory latency to all levels of cache and memory.
- · Loaded and unloaded latency via use of multithreaded load generation.

Memory power:

- · Support custom power instrumentation through a simple interface that end-users can implement.
- · Can collect DRAM power via custom driver exposed in Windows performance counter API.

Documentation:

· Extensive Doxygen source code comments, PDF manual, HTML.

INCLUDED EXTENSIONS (under src/include/ext and src/ext directories):

- Loaded latency benchmark variant with load delays inserted as nop instructions between memory instructions.
 - This is done for 32, 64, 128, 256, 512-bit load chunk sizes where applicable using the forward sequential read pattern.
- Other extensions may be released in the future. If you have a development request, or would like to mainstream your own extension, let us know!

Feel free to contact us for any other feature requests.

RUNTIME PREREQUISITES

There are a few runtime prerequisites in order for the software to run correctly.

HARDWARE:

- Intel x86, x86-64, x86-64+AVX, or MIC (Xeon Phi/Knights Corner) CPU. AMD CPUs that are compatible with Intel Architecture ISAs should also work fine.
- ARM Cortex-A series processors with VFP and NEON extensions. Specifically tested on ARM Cortex A9
 (32-bit) which is ARMv7. 64-bit builds for ARMv8-A should also work but have not been tested. GNU/Linux
 builds only. ARM on Windows can compile using VC++, but cannot link due to a lack of library support for
 desktop/command-line ARM apps. This may be resolved in the future. If you can get this working, let us
 know!

WINDOWS:

Microsoft Windows 8.1 64-bit or later, Server 2012 R2 or later.

4 README

- Microsoft Visual C++ 2013 Redistributables (32-bit) for x86 (32-bit) builds
- Microsoft Visual C++ 2013 Redistributables (64-bit) for x86-64 and x86-64 with AVX builds
- · You MAY need Administrator privileges, in order to:
 - Use large pages, if the -large pages option is selected (see USAGE, below)
 - The first time you use -large_pages on a given Windows machine, you may need to ensure that your Windows user account has the necessary rights to allow lockable memory pages. To do this on Windows 8, run gpedit.msc -> Local Computer Policy -> Computer Configuration -> Windows Settings -> Security Settings -> Local Policies -> User Rights Assignment -> Add your username to "Lock pages in memory". Then log out and then log back in.
 - Use the PowerReader interface, depending on end-user implementation
 - Elevate thread priority and pin threads to logical CPUs for improved performance and benchmarking consistency

GNU/LINUX:

- GNU utilities with support for C++11. Tested with gcc 4.8.2 on Ubuntu 14.04 LTS for x86 (32-bit), x86-64, x86-64+AVX, and MIC on Intel Sandy Bridge, Ivy Bridge, Haswell, and Knights Corner families.
- libhugetlbfs. You can obtain it at http://libhugetlbfs.sourceforge.net. On Ubuntu systems, you can install using "sudo apt-get install libhugetlbfs0". If you don't have this or cannot install it, this should be fine but you will not be able to use large pages.
- Potentially, administrator privileges, if you plan to use the -large_pages option.
 - During runtime, if the –large_pages option is selected, you may need to first manually ensure that large pages are available from the OS. This can be done by running "hugeadm --pool-list". It is recommended to set minimum pool to 1GB (in order to measure DRAM effectively). If needed, this can be done by running "hugeadm --pool-pages-min 2MB:512". Alternatively, run the linux_setup_runtime_hugetlbfs.sh script that is provided with X-Mem.

INSTALLATION

The only file that is needed to run on Windows is the respective executable xmem-win-<ARCH>.exe on Windows, and xmem-linux-<ARCH> on GNU/Linux. It has no other dependencies aside from the pre-installed system pre-requisites listed above.

USAGE

To get help using the tool, simply run it with the "-h" or "--help" option. It includes a list of all available options and provides usage examples.

BUILDING FROM SOURCE

After you have set the desired compile-time options, build the source. On Windows, running build-win.bat should suffice. On GNU/Linux, run build-linux.sh. Each takes a single argument specifying the target architecture.

If you customize your build, make sure you use the "Release" mode for your OS/compiler. Do not include debug capabilities as it can dramatically affect performance of the benchmarks, leading to pessimistic results.

BUILD PREREQUISITES

There are a few software build prerequisites, depending on your platform.

WINDOWS:

- Any version of Visual Studio 2013 64-bit (version 12.0) on Windows 8.1 or 2015 (version 14.0) on Windows
- Python 2.7. You can obtain it at http://www.python.org.
- SCons build system. You can obtain it at http://www.scons.org. Build tested with SCons 2.3.4.

GNU/LINUX:

- bash shell. Other shells will probably work but are untested.
- gcc with support for the C++11 standard. Tested with gcc version 4.8.2 on Ubuntu 14.04 LTS for x86 (32-bit), x86-64, x86-64 with AVX builds. To compile for Intel Xeon Phi/MIC/Knights Corner, we recommend the use of Intel's compiler (icc) instead of gcc.
- gcc cross-compiler for ARM targets (assumed build on x86-64 Ubuntu host).
- Python 2.7. You can obtain it at http://www.python.org. On Ubuntu systems, you can install using "sudo apt-get install python2.7". You may need some other Python 2.7 packages as well.
- SCons build system. You can obtain it at http://www.scons.org. On Ubuntu systems, you can install using "sudo apt-get install scons". Build tested with SCons 2.3.4.
- Kernel support for large (huge) pages. This support can be verified on your Linux installation by running "grep hugetlbfs /proc/filesystems". If you do not have huge page support in your kernel, you can build a kernel with the appropriate options switched on: "CONFIG HUGETLB PAGE" and "CONFIG HUGETLBFS".
- libhugetlbfs. This is used for allocating large (huge) pages if the —large_pages runtime option is selected. You can obtain it at http://libhugetlbfs.sourceforge.net. On Ubuntu systems, you can install using "sudo apt-get install libhugetlbfs-dev".

DOCUMENTATION BUILD PREREQUISITES

The following tools are only needed for automatically regenerating source code documentation with HTML and PDF. WINDOWS:

- doxygen tool. You can obtain it at http://www.stack.nl/~dimitri/doxygen.
- LaTeX distribution. You can get a Windows distribution at http://www.miktex.org.
- make for Windows. You can obtain it at http://gnuwin32.sourceforge.net/packages/make.-htm. You will have to manually add it to your Windows path.

GNU/LINUX:

- doxygen tool. You can obtain it at http://www.stack.nl/~dimitri/doxygen. On Ubuntu systems, you can install with "sudo apt-get install doxygen".
- LaTeX distribution. On Ubuntu systems, LaTeX distributed with doxygen should actually be sufficient. You can install with "sudo apt-get install doxygen-latex".
- make. This should be included on any GNU/Linux system.

SOURCE CODE DOCUMENTATION

The tool comes with built-in Doxygen comments in the source code, which can be used to generate both HTML and LaTeX —> PDF documentation. Documentation is maintained under the doc/ subdirectory. To build documentation after modifying the source, run build-docs-win.bat on Windows, or build-docs-linux.sh on GNU/Linux systems. Note that Doxygen and a LaTeX distribution must be installed on the system.

CONTACT, FEEDBACK, AND BUG REPORTS

For questions, comments, criticism, bug reports, and other feedback for this software, please contact Mark Gottscho via email at mgottscho@ucla.edu or via web at http://www.seas.ucla.edu/~gottscho.

6 README

ACKNOWLEDGMENT

Mark Gottscho would like to thank Dr. Mohammed Shoaib of Microsoft Research and Dr. Sriram Govindan of Microsoft for their mentorship in the creation of this software. Further thanks to Dr. Bikash Sharma, Mark Santaniello, Mike Andrewartha, and Laura Caulfield of Microsoft for their contributions, feedback, and assistance. Thank you as well to Dr. Jie Liu of Microsoft Research, Dr. Badriddine Khessib and Dr. Kushagra Vaid of Microsoft, and Prof. Puneet Gupta of UCLA for giving Mark the opportunity to create this work. Finally, Mark would like to thank Dr. Fedor Pikus of Mentor Graphics for teaching him some useful programming techniques.

Chapter 2

Hierarchical Index

2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

xmem::Parser::Action
xmem::Parser::StoreOptionAction
xmem::Stats::CountOptionsAction
xmem::Arg
xmem::ExampleArg
xmem::MyArg
xmem::Benchmark
xmem::LatencyBenchmark
xmem::ThroughputBenchmark
xmem::BenchmarkManager
xmem::Configurator
xmem::Descriptor
xmem::PrintUsageImplementation::IStringWriter
$xmem:: Print U sage Implementation:: Function Writer < Function > \dots $
xmem::PrintUsageImplementation::OStreamWriter< OStream >
xmem::PrintUsageImplementation::StreamWriter< Function, Stream >
xmem::PrintUsageImplementation::SyscallWriter< Syscall >
xmem::PrintUsageImplementation::TemporaryWriter< Temporary >
xmem::PrintUsageImplementation::LinePartIterator 33 xmem::PrintUsageImplementation::LineWrapper 44
xmem::PrintUsageImplementation::LineWrapper 40 xmem::Option 40
xmem::Parser
xmem::PrintUsageImplementation
xmem::Runnable
xmem::MemoryWorker
xmem::LatencyWorker
xmem::LoadWorker
xmem::PowerReader
xmem::Stats
xmem::Thread
xmem:Timer 7

8 **Hierarchical Index**

Chapter 3

Class Index

3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

xmem::Parser::Action	13
Functions for checking the validity of option arguments	14
xmem::Benchmark	
Flexible abstract class for any memory benchmark	15
xmem::BenchmarkManager	
Manages running all benchmarks at a high level	25
xmem::Configurator	
Handles all user input interpretation and generates the necessary flags for running benchmarks	26
xmem::Stats::CountOptionsAction	33
xmem::Descriptor	
Describes an option, its help text (usage) and how it should be parsed	33
xmem::ExampleArg	36
xmem::PrintUsageImplementation::FunctionWriter< Function >	36
xmem::PrintUsageImplementation::IStringWriter	36
xmem::LatencyBenchmark	
A type of benchmark that measures memory latency via random pointer chasing. Loading may	
be provided with separate threads which access memory as quickly as possible using given	
access patterns	37
xmem::LatencyWorker	
Multithreading-friendly class to do memory loading	38
xmem::PrintUsageImplementation::LinePartIterator	39
xmem::PrintUsageImplementation::LineWrapper	40
xmem::LoadWorker	
Multithreading-friendly class to do memory loading	41
xmem::MemoryWorker	
Multithreading-friendly class to run memory access kernels	42
xmem::MyArg	46
xmem::Option	
A parsed option from the command line together with its argument if it has one	46
xmem::PrintUsageImplementation::OStreamWriter< OStream >	52
xmem::Parser	
Checks argument vectors for validity and parses them into data structures that are easier to work	
with	52
xmem::PowerReader	

56

10 Class Index

xmem::Runnable	
A base class for any object that implements a thread-safe run() function for use by Thread objects	62
xmem::Stats	
Determines the minimum lengths of the buffer and options arrays used for Parser	63
xmem::Parser::StoreOptionAction	65
xmem::PrintUsageImplementation::StreamWriter< Function, Stream >	66
xmem::PrintUsageImplementation::SyscallWriter< Syscall >	67
xmem::PrintUsageImplementation::TemporaryWriter< Temporary >	67
xmem::Thread	
Nice wrapped thread interface independent of particular OS API	68
xmem::ThroughputBenchmark	
A type of benchmark that measures memory throughput	70
xmem::Timer	
This class abstracts some characteristics of simple high resolution stopwatch timer. However,	
due to the inability or complexity of abstracting shared hardware timers, this class does not	
actually provide start and stop functions	71

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

src/Benchmark.cpp	
Implementation file for the Benchmark class	73
src/benchmark_kernels.cpp	
Implementation file for benchmark kernel functions for doing the actual work we care about. :) .	73
src/BenchmarkManager.cpp	
Implementation file for the BenchmarkManager class	74
src/common.cpp	
Implementation file for common preprocessor definitions, macros, functions, and global con-	
stants	74
src/Configurator.cpp	
Implementation file for the Configurator class and some helper data structures	75
src/LatencyBenchmark.cpp	
Implementation file for the LatencyBenchmark class	94
src/LatencyWorker.cpp	
Implementation file for the LatencyWorker class	94
src/LoadWorker.cpp	
Implementation file for the LoadWorker class	94
src/main.cpp	
Main entry point to the tool	95
src/MemoryWorker.cpp	
Implementation file for the MemoryWorker class	95
src/PowerReader.cpp	
Implementation file for the PowerReader class	95
src/Runnable.cpp	
Implementation file for the Runnable class	96
src/Thread.cpp	
Implementation file for the Thread class	96
src/ThroughputBenchmark.cpp	
Implementation file for the ThroughputBenchmark class	96
src/Timer.cpp	
Implementation file for the Timer class	97
src/ext/DelayInjectedLoadedLatencyBenchmark/delay_injected_benchmark_kernels.cpp	
Implementation file for benchmark kernel functions for the delay-injected loaded latency bench-	
mark	75
src/ext/DelayInjectedLoadedLatencyBenchmark/DelayInjectedLoadedLatencyBenchmark.cpp	
Implementation file for the DelayInjectedLatencyBenchmark class	75
src/include/Benchmark.h	
Header file for the Benchmark class	76

12 File Index

src/include/benchmark_kernels.h	
Header file for benchmark kernel functions for doing the actual work we care about. :)	76
src/include/BenchmarkManager.h	
Header file for the BenchmarkManager class	78
src/include/build_datetime.h	??
src/include/common.h	
Header file for common preprocessor definitions, macros, functions, and global constants	79
src/include/Configurator.h	
Header file for the Configurator class and some helper data structures	83
src/include/ExampleArg.h	
Slightly-modified third-party code related to OptionParser	84
src/include/LatencyBenchmark.h	
Header file for the LatencyBenchmark class	86
src/include/LatencyWorker.h	
Header file for the LatencyWorker class	86
src/include/LoadWorker.h	
Header file for the LoadWorker class	87
src/include/MemoryWorker.h	
Header file for the MemoryWorker class	87
src/include/MyArg.h	
Extensions to third-party optionparser-related code	87
src/include/optionparser.h	
This is the only file required to use The Lean Mean C++ Option Parser. Just #include it and	
you're set	88
src/include/PowerReader.h	
Header file for the PowerReader class	91
src/include/Runnable.h	
Header file for the Runnable class	92
src/include/Thread.h	
Header file for the Thread class	92
src/include/ThroughputBenchmark.h	
Header file for the ThroughputBenchmark class	92
src/include/Timer.h	
Header file for the Timer class	93
src/include/ext/DelayInjectedLoadedLatencyBenchmark/delay_injected_benchmark_kernels.h	
Header file for benchmark kernel functions with integrated delays for doing the actual work we	
care about. :)	84
src/include/ext/DelayInjectedLoadedLatencyBenchmark/DelayInjectedLoadedLatencyBenchmark.h	
Header file for the DelayInjectedLoadedLatencyBenchmark class	86
src/include/win/win_common_third_party.h	
Header file for some third-party helper code for working with Windows APIs	93
src/include/win/win_CPdhQuery.h	
Header and implementation file for some third-party code for measuring Windows OS-exposed	
performance counters	93
src/include/win/WindowsDRAMPowerReader.h	
Header file for the WindowsDRAMPowerReader class	93
src/win/win_common_third_party.cpp	
Implementation file for some third-party helper code for working with Windows APIs	97
src/win/WindowsDRAMPowerReader.cpp	
Implementation file for the WindowsDRAMPowerReader class	97

Chapter 5

Class Documentation

5.1 xmem::Parser::Action Struct Reference

Inheritance diagram for xmem::Parser::Action:

Public Member Functions

• virtual bool perform (Option &)

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check_arg does not return ARG_ILLEGAL.

virtual bool finished (int numargs, const char **args)

Called by Parser::workhorse() after finishing the parse.

5.1.1 Member Function Documentation

5.1.1.1 virtual bool xmem::Parser::Action::finished (int numargs, const char ** args) [inline], [virtual]

Called by Parser::workhorse() after finishing the parse.

Parameters

numargs	the number of non-option arguments remaining
args	pointer to the first remaining non-option argument (if numargs $>$ 0).

Returns

false iff a fatal error has occurred.

Reimplemented in xmem::Parser::StoreOptionAction.

```
5.1.1.2 virtual bool xmem::Parser::Action::perform ( Option & ) [inline], [virtual]
```

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check_arg does not return ARG_ILLEGAL.

Returns false iff a fatal error has occured and the parse should be aborted.

Reimplemented in xmem::Parser::StoreOptionAction, and xmem::Stats::CountOptionsAction.

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

14 Class Documentation

5.2 xmem::Arg Struct Reference

Functions for checking the validity of option arguments.

```
#include <optionparser.h>
```

Inheritance diagram for xmem::Arg:

Static Public Member Functions

• static ArgStatus None (const Option &, bool)

For options that don't take an argument: Returns ARG_NONE.

• static ArgStatus Optional (const Option &option, bool)

Returns ARG_OK if the argument is attached and ARG_IGNORE otherwise.

5.2.1 Detailed Description

Functions for checking the validity of option arguments.

The following example code can serve as starting place for writing your own more complex CheckArg functions:

```
struct Arg: public option::Arg
  static void printError(const char* msg1, const option::Option& opt, const char* msg2)
    fprintf(stderr, "ERROR: %s", msg1);
    fwrite(opt.name, opt.namelen, 1, stderr);
fprintf(stderr, "%s", msg2);
  static option::ArgStatus Unknown(const option::Option& option, bool msg)
    if (msg) printError("Unknown option '", option, "'\n");
    return option::ARG_ILLEGAL;
  static option::ArgStatus Required(const option::Option& option, bool msg)
    if (option.arg != 0)
     return option::ARG_OK;
   if (msg) printError("Option '", option, "' requires an argument\n");
    return option::ARG_ILLEGAL;
  static option::ArgStatus NonEmpty(const option::Option& option, bool msg)
    if (option.arg != 0 && option.arg[0] != 0)
     return option::ARG_OK;
    if (msg) printError("Option '", option, "' requires a non-empty argument\n");
    return option::ARG_ILLEGAL;
  static option::ArgStatus Numeric(const option::Option& option, bool msg)
    char* endptr = 0;
    if (option.arg != 0 && strtol(option.arg, &endptr, 10)){};
    if (endptr != option.arg && *endptr == 0)
     return option::ARG_OK;
    if (msg) printError("Option '", option, "' requires a numeric argument\n");
    return option::ARG_ILLEGAL;
};
```

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

5.3 xmem::Benchmark Class Reference

Flexible abstract class for any memory benchmark.

#include <Benchmark.h>

Inheritance diagram for xmem::Benchmark:

Public Member Functions

Benchmark (void *mem_array, size_t len, uint32_t iterations, uint32_t num_worker_threads, uint32_t mem_node, uint32_t cpu_node, pattern_mode_t pattern_mode, rw_mode_t rw_mode, chunk_size_t chunk_size, int32_t stride_size, std::vector< PowerReader * > dram_power_readers, std::string metric_units, std::string name)

Constructor.

virtual ∼Benchmark ()

Destructor.

• bool run ()

Runs the benchmark.

void printBenchmarkHeader () const

Prints a header piece of information describing the benchmark to the console.

virtual void reportBenchmarkInfo () const

Reports benchmark configuration details to the console.

• virtual void reportResults () const

Reports results to the console.

• bool isValid () const

Checks to see that the object is in a valid state.

· bool hasRun () const

Checks to see if the benchmark has run.

• double getMetricOnIter (uint32_t iter) const

Extracts the metric of interest for a given iteration. Units are interpreted by the inheriting class.

• double getMeanMetric () const

Gets the arithmetic mean benchmark metric across all iterations.

double getMinMetric () const

Gets the minimum benchmark metric across all iterations.

· double get25PercentileMetric () const

Gets the 25th percentile benchmark metric across all iterations.

double getMedianMetric () const

Gets the median benchmark metric across all iterations.

• double get75PercentileMetric () const

Gets the 75th percentile benchmark metric across all iterations.

double get95PercentileMetric () const

Gets the 95th percentile benchmark metric across all iterations.

• double get99PercentileMetric () const

Gets the 99th percentile benchmark metric across all iterations.

• double getMaxMetric () const

Gets the maximum benchmark metric across all iterations.

• double getModeMetric () const

Gets the mode benchmark metric across all iterations.

• std::string getMetricUnits () const

Gets the units of the metric for this benchmark.

double getMeanDRAMPower (uint32_t socket_id) const

16 Class Documentation

Gets the arithmetic mean DRAM power over the benchmark.

double getPeakDRAMPower (uint32_t socket_id) const

Gets the peak DRAM power over the benchmark.

• size_t getLen () const

Gets the length of the memory region in bytes. This is not necessarily the "working set size" depending on multithreading configuration.

• uint32_t getIterations () const

Gets the number of iterations for this benchmark.

• chunk_size_t getChunkSize () const

Gets the width of memory access used in this benchmark.

• int32_t getStrideSize () const

Gets the stride size for this benchmark.

uint32 t getCPUNode () const

Gets the CPU NUMA node used in this benchmark.

• uint32_t getMemNode () const

Gets the memory NUMA node used in this benchmark.

uint32_t getNumThreads () const

Gets the number of worker threads used in this benchmark.

std::string getName () const

Gets the human-friendly name of this benchmark.

pattern_mode_t getPatternMode () const

Gets the pattern mode for this benchmark.

rw_mode_t getRWMode () const

Gets the read/write mode for this benchmark.

Protected Member Functions

virtual bool runCore ()=0

The core benchmark function.

• void computeMetrics ()

Computes the metrics across iterations.

• bool startPowerThreads ()

Starts the DRAM power measurement threads.

bool stopPowerThreads ()

Stops the DRAM power measurement threads. This is a blocking call.

Protected Attributes

- void * mem array
- size_t len_
- uint32_t iterations_
- uint32_t num_worker_threads_
- uint32_t mem_node_
- uint32_t cpu_node_
- pattern_mode_t pattern_mode_
- rw_mode_t rw_mode_
- chunk_size_t chunk_size_
- int32 t stride size
- std::vector< PowerReader * > dram_power_readers_
- std::vector< Thread * > dram power threads
- std::vector< double > metric_on_iter_

- double mean_metric_
- double min_metric_
- double percentile_25_metric_
- double median_metric_
- double percentile_75_metric_
- double percentile_95_metric_
- double percentile_99_metric_
- double max_metric_
- double mode_metric_
- std::string metric units
- std::vector< double > mean dram power socket
- std::vector< double > peak_dram_power_socket_
- · std::string name_
- · bool obj_valid_
- · bool has_run_
- bool warning

5.3.1 Detailed Description

Flexible abstract class for any memory benchmark.

This class provides a generic interface for interacting with a benchmark. All benchmarks should be derived from this class.

5.3.2 Constructor & Destructor Documentation

5.3.2.1 Benchmark::Benchmark (void * mem_array, size_t len, uint32_t iterations, uint32_t num_worker_threads, uint32_t mem_node, uint32_t cpu_node, pattern_mode_t pattern_mode, rw_mode_t rw_mode, chunk_size_t chunk_size, int32_t stride_size, std::vector< PowerReader * > dram_power_readers, std::string metric_units, std::string name
)

Constructor.

Parameters

mem_array	A pointer to a contiguous chunk of memory that has been allocated for benchmarking among		
	potentially several worker threads. This should be aligned to a 256-bit boundary.		
len	Length of mem_array in bytes. This must be a multiple of 4 KB and should be at least the		
	per-thread working set size times the number of worker threads.		
iterations	Number of iterations of the complete benchmark. Used to average results and provide a		
	measure of consistency and reproducibility.		
num_worker	The number of worker threads to use in the benchmark.		
threads			
mem_node	The logical memory NUMA node used in the benchmark.		
cpu_node	The logical CPU NUMA node to use for the benchmark.		
pattern_mode	This indicates the general type of access pattern used, e.g. sequential or random.		
rw_mode	This indicates the general type of read/write mix used, e.g. pure reads or pure writes.		
chunk_size	Size of an individual memory access for load-generating worker threads.		
stride_size	For sequential access patterns, this is the address distance between successive accesses,		
	counted in chunks. Negative values indicate a reversed access pattern. A stride of +/-1 is		
	purely sequential.		

18 Class Documentation

dram_power readers	A group of PowerReader objects for measuring DRAM power.
name	The name of the benchmark to use when reporting to console.

5.3.3 Member Function Documentation

5.3.3.1 double Benchmark::get25PercentileMetric () const

Gets the 25th percentile benchmark metric across all iterations.

Returns

The 25th percentile metric.

5.3.3.2 double Benchmark::get75PercentileMetric () const

Gets the 75th percentile benchmark metric across all iterations.

Returns

The 75th percentile metric.

5.3.3.3 double Benchmark::get95PercentileMetric () const

Gets the 95th percentile benchmark metric across all iterations.

Returns

The 95th percentile metric.

5.3.3.4 double Benchmark::get99PercentileMetric () const

Gets the 99th percentile benchmark metric across all iterations.

Returns

The 99th percentile metric.

 $5.3.3.5 \quad chunk_size_t \ Benchmark::getChunkSize \ (\quad) \ const$

Gets the width of memory access used in this benchmark.

Returns

The chunk size for this benchmark.

5.3.3.6 uint32_t Benchmark::getCPUNode () const

Gets the CPU NUMA node used in this benchmark.

Returns

The NUMA CPU node used in this benchmark.

5.3.3.7 uint32_t Benchmark::getIterations () const

Gets the number of iterations for this benchmark.

Returns

The number of iterations for this benchmark.

5.3.3.8 size_t Benchmark::getLen () const

Gets the length of the memory region in bytes. This is not necessarily the "working set size" depending on multi-threading configuration.

Returns

Length of the memory region in bytes.

5.3.3.9 double Benchmark::getMaxMetric () const

Gets the maximum benchmark metric across all iterations.

Returns

The maximum metric.

5.3.3.10 double Benchmark::getMeanDRAMPower (uint32_t socket_id) const

Gets the arithmetic mean DRAM power over the benchmark.

Returns

The mean DRAM power for a given socket in watts, or 0 if the data does not exist (power was unable to be collected or the benchmark has not run).

5.3.3.11 double Benchmark::getMeanMetric () const

Gets the arithmetic mean benchmark metric across all iterations.

Returns

The mean metric.

5.3.3.12 double Benchmark::getMedianMetric () const

Gets the median benchmark metric across all iterations.

Returns

The median metric.

20 Class Documentation

5.3.3.13 uint32_t Benchmark::getMemNode () const

Gets the memory NUMA node used in this benchmark.

Returns

The NUMA memory node used in this benchmark.

5.3.3.14 double Benchmark::getMetricOnlter (uint32_t iter) const

Extracts the metric of interest for a given iteration. Units are interpreted by the inheriting class.

Parameters

iter	Iteration to extract.

Returns

The metric on the iteration specified by the input.

5.3.3.15 std::string Benchmark::getMetricUnits () const

Gets the units of the metric for this benchmark.

Returns

A string representing the units for printing to console and file.

5.3.3.16 double Benchmark::getMinMetric () const

Gets the minimum benchmark metric across all iterations.

Returns

The minimum metric.

5.3.3.17 double Benchmark::getModeMetric () const

Gets the mode benchmark metric across all iterations.

Returns

The mode metric.

5.3.3.18 std::string Benchmark::getName () const

Gets the human-friendly name of this benchmark.

Returns

The benchmark test name.

5.3 xmem::Benchmark Class Reference 5.3.3.19 uint32_t Benchmark::getNumThreads () const Gets the number of worker threads used in this benchmark. Returns The number of worker threads used in this benchmark. 5.3.3.20 pattern_mode_t Benchmark::getPatternMode () const Gets the pattern mode for this benchmark. Returns The pattern mode enumerator. 5.3.3.21 double Benchmark::getPeakDRAMPower (uint32_t socket_id) const Gets the peak DRAM power over the benchmark. Returns The peak DRAM power for a given socket in watts, or 0 if the data does not exist (power was unable to be collected or the benchmark has not run). 5.3.3.22 rw_mode_t Benchmark::getRWMode () const Gets the read/write mode for this benchmark.

Returns

The read/write mix mode.

5.3.3.23 int32_t Benchmark::getStrideSize () const

Gets the stride size for this benchmark.

Returns

The stride size in chunks.

5.3.3.24 bool Benchmark::hasRun () const

Checks to see if the benchmark has run.

Returns

True if run() has already completed successfully.

5.3.3.25 bool Benchmark::isValid () const

Checks to see that the object is in a valid state.

Returns

True if the object was constructed correctly and can be used.

22 Class Documentation

```
5.3.3.26 bool Benchmark::run ( )
Runs the benchmark.
Returns
     True on benchmark success
Here is the call graph for this function:
5.3.3.27 virtual bool xmem::Benchmark::runCore() [protected], [pure virtual]
The core benchmark function.
Returns
     True on success.
Implemented in xmem::LatencyBenchmark, and xmem::ThroughputBenchmark.
5.3.3.28 bool Benchmark::startPowerThreads() [protected]
Starts the DRAM power measurement threads.
Returns
     True on success.
5.3.3.29 bool Benchmark::stopPowerThreads() [protected]
Stops the DRAM power measurement threads. This is a blocking call.
Returns
     True on success.
5.3.4 Member Data Documentation
5.3.4.1 chunk_size_t xmem::Benchmark::chunk_size_ [protected]
Chunk size of memory accesses in this benchmark.
5.3.4.2 uint32_t xmem::Benchmark::cpu_node_ [protected]
The CPU NUMA node used in this benchmark.
5.3.4.3 std::vector<PowerReader*> xmem::Benchmark::dram_power_readers_ [protected]
The power reading objects for measuring DRAM power on a per-socket basis during the benchmark.
5.3.4.4 std::vector<Thread*> xmem::Benchmark::dram_power_threads_ [protected]
The power reading threads for measuring DRAM power on a per-socket basis during the benchmark. These work
```

with the DRAM power readers. Although they are worker threads, they are not counted as the "official" benchmarking worker threads.

5.3.4.5 bool xmem::Benchmark::has_run_ [protected]

Indicates whether the benchmark has run.

5.3.4.6 uint32_t xmem::Benchmark::iterations_ [protected]

Number of iterations used in this benchmark.

5.3.4.7 size_t xmem::Benchmark::len_ [protected]

Length of the memory region in bytes. This is not the working set size per thread!

5.3.4.8 double xmem::Benchmark::max_metric_ [protected]

Maximum metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

5.3.4.9 std::vector<double> xmem::Benchmark::mean_dram_power_socket_ [protected]

The mean DRAM power in this benchmark, per socket.

5.3.4.10 double xmem::Benchmark::mean_metric_ [protected]

Average metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

5.3.4.11 double xmem::Benchmark::median_metric_ [protected]

Median metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

5.3.4.12 void* xmem::Benchmark::mem_array_ [protected]

Pointer to the memory region to use in this benchmark.

5.3.4.13 uint32_t xmem::Benchmark::mem_node_ [protected]

The memory NUMA node used in this benchmark.

5.3.4.14 std::vector<double> xmem::Benchmark::metric_on_iter_ [protected]

Metrics for each iteration of the benchmark. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

5.3.4.15 std::string xmem::Benchmark::metric_units_ [protected]

String representing the units of measurement for the metric.

```
5.3.4.16 double xmem::Benchmark::min_metric_ [protected]
```

Minimum metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.17 double xmem::Benchmark::mode_metric_ [protected]
```

Mode metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.18 std::string xmem::Benchmark::name_ [protected]
```

Name of this benchmark.

```
5.3.4.19 uint32_t xmem::Benchmark::num_worker_threads_ [protected]
```

The number of worker threads used in this benchmark.

```
5.3.4.20 bool xmem::Benchmark::obj_valid_ [protected]
```

Indicates whether this benchmark object is valid.

```
5.3.4.21 pattern_mode_t xmem::Benchmark::pattern_mode_ [protected]
```

Access pattern mode.

```
5.3.4.22 std::vector<double> xmem::Benchmark::peak_dram_power_socket_ [protected]
```

The peak DRAM power in this benchmark, per socket.

```
5.3.4.23 double xmem::Benchmark::percentile_25_metric_ [protected]
```

25th percentile metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.24 double xmem::Benchmark::percentile_75_metric_ [protected]
```

75th percentile metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.25 double xmem::Benchmark::percentile_95_metric_ [protected]
```

95th percentile metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.26 double xmem::Benchmark::percentile_99_metric_ [protected]
```

99th percentile metric over all iterations. Unit-less because any benchmark can set this metric as needed. It is up to the descendant class to interpret units.

```
5.3.4.27 rw_mode_t xmem::Benchmark::rw_mode_ [protected]
```

Read/write mode.

```
5.3.4.28 int32_t xmem::Benchmark::stride_size_ [protected]
```

Stride size in chunks for sequential pattern mode only.

```
5.3.4.29 bool xmem::Benchmark::warning_ [protected]
```

Indicates whether the benchmarks results might be clearly questionable/inaccurate/incorrect due to a variety of factors.

The documentation for this class was generated from the following files:

- src/include/Benchmark.h
- src/Benchmark.cpp

5.4 xmem::BenchmarkManager Class Reference

Manages running all benchmarks at a high level.

```
#include <BenchmarkManager.h>
```

Public Member Functions

• BenchmarkManager (Configurator &config)

Constructor.

∼BenchmarkManager ()

Destructor.

• bool runAll ()

Runs all benchmark configurations (does not include extensions).

bool runThroughputBenchmarks ()

Runs the throughput benchmarks.

• bool runLatencyBenchmarks ()

Runs the latency benchmark.

5.4.1 Detailed Description

Manages running all benchmarks at a high level.

5.4.2 Constructor & Destructor Documentation

5.4.2.1 BenchmarkManager::BenchmarkManager (Configurator & config)

Constructor.

Parameters

config The configuration object containing run-time options for this X-Mem execution instance.

Here is the call graph for this function:

5.4.3 Member Function Documentation

5.4.3.1 bool BenchmarkManager::runAll()

Runs all benchmark configurations (does not include extensions).

Returns

True on success.

Here is the call graph for this function:

5.4.3.2 bool BenchmarkManager::runLatencyBenchmarks ()

Runs the latency benchmark.

Returns

True on benchmarking success.

Here is the call graph for this function:

5.4.3.3 bool BenchmarkManager::runThroughputBenchmarks ()

Runs the throughput benchmarks.

Returns

True on benchmarking success.

Here is the call graph for this function:

The documentation for this class was generated from the following files:

- src/include/BenchmarkManager.h
- src/BenchmarkManager.cpp

5.5 xmem::Configurator Class Reference

Handles all user input interpretation and generates the necessary flags for running benchmarks.

```
#include <Configurator.h>
```

Public Member Functions

• Configurator ()

Default constructor. A default configuration is set. You will want to run configureFromInput() most likely.

int32 t configureFromInput (int argc, char *argv[])

Configures the tool based on user's command-line inputs.

bool extensionsEnabled () const

Determines whether user extensions are enabled.

bool runExtDelayInjectedLoadedLatencyBenchmark () const

If included at compile-time, determines whether the delay-injected loaded latency benchmark extension should be

bool latencyTestSelected () const

Indicates if the latency test has been selected.

bool throughputTestSelected () const

Indicates if the throughput test has been selected.

size t getWorkingSetSizePerThread () const

Gets the working set size in bytes for each worker thread, if applicable.

• bool useChunk32b () const

Determines if chunk size of 32 bits should be used in relevant benchmarks.

bool isNUMAEnabled () const

Determines if the benchmarks should test for all CPU/memory NUMA combinations.

std::list< uint32_t > getCpuNumaNodeAffinities () const

Gets a list of CPU NUMA nodes to affinitize for all benchmark experiments.

std::list< uint32_t > getMemoryNumaNodeAffinities () const

Gets a list of memory NUMA nodes to affinitize for all benchmark experiments.

• uint32 t getIterationsPerTest () const

Gets the number of iterations that should be run of each benchmark.

· bool useRandomAccessPattern () const

Determines if throughput benchmarks should use a random access pattern.

• bool useSequentialAccessPattern () const

Determines if throughput benchmarks should use a sequential access pattern.

uint32_t getNumWorkerThreads () const

Gets the number of worker threads to use.

uint32 t getStartingTestIndex () const

Gets the numerical index of the first benchmark for CSV output purposes.

std::string getOutputFilename () const

Gets the output filename to use, if applicable.

bool useOutputFile () const

Determines whether to generate an output CSV file.

void setUseOutputFile (bool use)

Changes whether an output file should be used.

bool verboseMode () const

Determines whether X-Mem is in verbose mode.

• bool useLargePages () const

Determines whether X-Mem should use large pages.

• bool useReads () const

 $\label{lem:def:Determines} \textit{ Whether reads should be used in throughput benchmarks}.$

• bool useWrites () const

Determines whether writes should be used in throughput benchmarks.

• bool useStrideP1 () const

Determines if a stride of +1 should be used in relevant benchmarks.

• bool useStrideN1 () const

Determines if a stride of -1 should be used in relevant benchmarks.

bool useStrideP2 () const

Determines if a stride of +2 should be used in relevant benchmarks.

· bool useStrideN2 () const

Determines if a stride of -2 should be used in relevant benchmarks.

• bool useStrideP4 () const

Determines if a stride of +4 should be used in relevant benchmarks.

• bool useStrideN4 () const

Determines if a stride of -4 should be used in relevant benchmarks.

• bool useStrideP8 () const

Determines if a stride of +8 should be used in relevant benchmarks.

bool useStrideN8 () const

Determines if a stride of -8 should be used in relevant benchmarks.

• bool useStrideP16 () const

Determines if a stride of +16 should be used in relevant benchmarks.

• bool useStrideN16 () const

Determines if a stride of -16 should be used in relevant benchmarks.

5.5.1 Detailed Description

Handles all user input interpretation and generates the necessary flags for running benchmarks.

5.5.2 Member Function Documentation

5.5.2.1 int32_t Configurator::configureFromInput (int argc, char * argv[])

Configures the tool based on user's command-line inputs.

Parameters

argc	The argc from main().
argv	The argv from main().

Returns

0 on success.

Here is the call graph for this function:

5.5.2.2 bool xmem::Configurator::extensionsEnabled () const [inline]

Determines whether user extensions are enabled.

Returns

True if extensions are enabled.

5.5.2.3 std::list<uint32_t> xmem::Configurator::getCpuNumaNodeAffinities () const [inline]

Gets a list of CPU NUMA nodes to affinitize for all benchmark experiments.

Returns

The list of NUMA node indices.

5.5.2.4 uint32_t xmem::Configurator::getIterationsPerTest() const [inline]

Gets the number of iterations that should be run of each benchmark.

Returns

The iterations for each test.

5.5.2.5 std::list<uint32_t> xmem::Configurator::getMemoryNumaNodeAffinities () const [inline]

Gets a list of memory NUMA nodes to affinitize for all benchmark experiments.

Returns

The list of NUMA node indices.

5.5.2.6 uint32_t xmem::Configurator::getNumWorkerThreads() const [inline]

Gets the number of worker threads to use.

Returns

The number of worker threads.

5.5.2.7 std::string xmem::Configurator::getOutputFilename()const [inline]

Gets the output filename to use, if applicable.

Returns

The output filename to use if useOutputFile() returns true. Otherwise return value is "".

5.5.2.8 uint32_t xmem::Configurator::getStartingTestIndex() const [inline]

Gets the numerical index of the first benchmark for CSV output purposes.

Returns

The starting benchmark index.

 $\textbf{5.5.2.9} \quad \textbf{size_t xmem::} \textbf{Configurator::getWorkingSetSizePerThread () const} \quad \texttt{[inline]}$

Gets the working set size in bytes for each worker thread, if applicable.

Returns

The working set size in bytes.

5.5.2.10 bool xmem::Configurator::isNUMAEnabled () const [inline]

Determines if the benchmarks should test for all CPU/memory NUMA combinations.

Returns

True if all NUMA nodes should be tested.

 $\textbf{5.5.2.11} \quad \textbf{bool xmem::} \textbf{Configurator::} \textbf{latencyTestSelected () const} \quad \texttt{[inline]}$

Indicates if the latency test has been selected.

Returns

True if the latency test has been selected to run.

5.5.2.12 bool xmem::Configurator::runExtDelayInjectedLoadedLatencyBenchmark() const [inline]

If included at compile-time, determines whether the delay-injected loaded latency benchmark extension should be run.

Returns

True if it should be run.

5.5.2.13 void xmem::Configurator::setUseOutputFile (bool use) [inline]

Changes whether an output file should be used.

Parameters

use If true, then use the output file.

5.5.2.14 bool xmem::Configurator::throughputTestSelected() const [inline]

Indicates if the throughput test has been selected.

Returns

True if the throughput test has been selected to run.

5.5.2.15 bool xmem::Configurator::useChunk32b() const [inline]

Determines if chunk size of 32 bits should be used in relevant benchmarks.

Returns

True if 32-bit chunks should be used.

5.5.2.16 bool xmem::Configurator::useLargePages () const [inline]

Determines whether X-Mem should use large pages.

Parameters

True if large pages should be used.

5.5.2.17 bool xmem::Configurator::useOutputFile() const [inline]

Determines whether to generate an output CSV file.

Returns

True if an output file should be used.

5.5.2.18 bool xmem::Configurator::useRandomAccessPattern() const [inline]

Determines if throughput benchmarks should use a random access pattern.

Returns

True if random access should be used.

```
5.5.2.19 bool xmem::Configurator::useReads() const [inline]
```

Determines whether reads should be used in throughput benchmarks.

Returns

True if reads should be used.

```
5.5.2.20 bool xmem::Configurator::useSequentialAccessPattern( ) const [inline]
```

Determines if throughput benchmarks should use a sequential access pattern.

Returns

True if sequential access should be used.

```
5.5.2.21 bool xmem::Configurator::useStrideN1 ( ) const [inline]
```

Determines if a stride of -1 should be used in relevant benchmarks.

Returns

True if a stride of -1 should be used.

```
5.5.2.22 bool xmem::Configurator::useStrideN16() const [inline]
```

Determines if a stride of -16 should be used in relevant benchmarks.

Returns

True if a stride of -16 should be used.

```
5.5.2.23 bool xmem::Configurator::useStrideN2( ) const [inline]
```

Determines if a stride of -2 should be used in relevant benchmarks.

Returns

True if a stride of -2 should be used.

```
5.5.2.24 bool xmem::Configurator::useStrideN4( ) const [inline]
```

Determines if a stride of -4 should be used in relevant benchmarks.

Returns

True if a stride of -4 should be used.

```
5.5.2.25 bool xmem::Configurator::useStrideN8() const [inline]
```

Determines if a stride of -8 should be used in relevant benchmarks.

Returns

True if a stride of -8 should be used.

```
5.5.2.26 bool xmem::Configurator::useStrideP1() const [inline]
Determines if a stride of +1 should be used in relevant benchmarks.
Returns
     True if a stride of +1 should be used.
5.5.2.27 bool xmem::Configurator::useStrideP16 ( ) const [inline]
Determines if a stride of +16 should be used in relevant benchmarks.
Returns
     True if a stride of +16 should be used.
5.5.2.28 bool xmem::Configurator::useStrideP2( ) const [inline]
Determines if a stride of +2 should be used in relevant benchmarks.
Returns
     True if a stride of +2 should be used.
5.5.2.29 bool xmem::Configurator::useStrideP4( ) const [inline]
Determines if a stride of +4 should be used in relevant benchmarks.
Returns
     True if a stride of +4 should be used.
5.5.2.30 bool xmem::Configurator::useStrideP8 ( ) const [inline]
Determines if a stride of +8 should be used in relevant benchmarks.
Returns
     True if a stride of +8 should be used.
5.5.2.31 bool xmem::Configurator::useWrites ( ) const [inline]
Determines whether writes should be used in throughput benchmarks.
```

Returns

True if writes should be used.

5.5.2.32 bool xmem::Configurator::verboseMode() const [inline]

Determines whether X-Mem is in verbose mode.

Returns

True if verbose mode is enabled.

The documentation for this class was generated from the following files:

- src/include/Configurator.h
- src/Configurator.cpp

5.6 xmem::Stats::CountOptionsAction Class Reference

Inheritance diagram for xmem::Stats::CountOptionsAction:

Collaboration diagram for xmem::Stats::CountOptionsAction:

Public Member Functions

- CountOptionsAction (unsigned *buffer_max_)
- bool perform (Option &)

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check_arg does not return ARG_ILLEGAL.

5.6.1 Constructor & Destructor Documentation

```
5.6.1.1 xmem::Stats::CountOptionsAction::CountOptionsAction ( unsigned * buffer_max_ ) [inline]
```

Creates a new CountOptionsAction that will increase *buffer_max_ for each parsed Option.

5.6.2 Member Function Documentation

```
5.6.2.1 bool xmem::Stats::CountOptionsAction::perform ( Option & ) [inline], [virtual]
```

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check_arg does not return ARG_ILLEGAL.

Returns false iff a fatal error has occured and the parse should be aborted.

Reimplemented from xmem::Parser::Action.

The documentation for this class was generated from the following file:

· src/include/optionparser.h

5.7 xmem::Descriptor Struct Reference

Describes an option, its help text (usage) and how it should be parsed.

```
#include <optionparser.h>
```

Public Attributes

· const unsigned index

Index of this option's linked list in the array filled in by the parser.

· const int type

Used to distinguish between options with the same index. See index for details.

const char *const shortopt

Each char in this string will be accepted as a short option character.

· const char *const longopt

The long option name (without the leading –).

· const CheckArg check arg

For each option that matches shortopt or longopt this function will be called to check a potential argument to the option.

const char * help

The usage text associated with the options in this Descriptor.

5.7.1 Detailed Description

Describes an option, its help text (usage) and how it should be parsed.

The main input when constructing an option::Parser is an array of Descriptors.

Example:

5.7.2 Member Data Documentation

5.7.2.1 const CheckArg xmem::Descriptor::check_arg

For each option that matches shortopt or longopt this function will be called to check a potential argument to the option.

This function will be called even if there is no potential argument. In that case it will be passed \mathtt{NULL} as \mathtt{arg} parameter. Do not confuse this with the empty string.

See CheckArg for more information.

5.7.2.2 const char* xmem::Descriptor::help

The usage text associated with the options in this Descriptor.

You can use option::printUsage() to format your usage message based on the help texts. You can use dummy Descriptors where shortopt and longopt are both the empty string to add text to the usage that is not related to a specific option.

See option::printUsage() for special formatting characters you can use in help to get a column layout.

Attention

Must be UTF-8-encoded. If your compiler supports C++11 you can use the "u8" prefix to make sure string literals are properly encoded.

5.7.2.3 const unsigned xmem::Descriptor::index

Index of this option's linked list in the array filled in by the parser.

Command line options whose Descriptors have the same index will end up in the same linked list in the order in which they appear on the command line. If you have multiple long option aliases that refer to the same option, give their descriptors the same index.

If you have options that mean exactly opposite things (e.g. <code>-enable-foo</code> and <code>-disable-foo</code>), you should also give them the same <code>index</code>, but distinguish them through different values for type. That way they end up in the same list and you can just take the last element of the list and use its type. This way you get the usual behaviour where switches later on the command line override earlier ones without having to code it manually.

Tip:

Use an enum rather than plain ints for better readability, as shown in the example at Descriptor.

5.7.2.4 const char* const xmem::Descriptor::longopt

The long option name (without the leading –).

If this Descriptor should not have a long option name, use the empty string "". NULL is not permitted here!

While shortopt allows multiple short option characters, each Descriptor can have only a single long option name. If you have multiple long option names referring to the same option use separate Descriptors that have the same index and type. You may repeat short option characters in such an alias Descriptor but there's no need to.

Dummy Descriptors:

You can use dummy Descriptors with an empty string for both shortopt and longopt to add text to the usage that is not related to a specific option. See help. The first dummy Descriptor will be used for unknown options (see below).

Unknown Option Descriptor:

The first dummy Descriptor in the list of Descriptors, whose shortopt and longopt are both the empty string, will be used as the Descriptor for unknown options. An unknown option is a string in the argument vector that is not a lone minus '-' but starts with a minus character and does not match any Descriptor's shortopt or longopt. Note that the dummy descriptor's check_arg function will be called and its return value will be evaluated as usual. I.e. if it returns ARG_ILLEGAL the parsing will be aborted with Parser::error() ==true. if check_arg does not return ARG_ILLEGAL the descriptor's index will be used to pick the linked list into which to put the unknown option.

If there is no dummy descriptor, unknown options will be dropped silently.

5.7.2.5 const char* const xmem::Descriptor::shortopt

Each char in this string will be accepted as a short option character.

The string must not include the minus character '-' or you'll get undefined behaviour.

If this Descriptor should not have short option characters, use the empty string "". NULL is not permitted here! See longopt for more information.

5.7.2.6 const int xmem::Descriptor::type

Used to distinguish between options with the same index. See index for details.

It is recommended that you use an enum rather than a plain int to make your code more readable.

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.8 xmem::ExampleArg Class Reference

Inheritance diagram for xmem::ExampleArg:

Collaboration diagram for xmem::ExampleArg:

Static Public Member Functions

- static void printError (const char *msg1, const Option &opt, const char *msg2)
- static ArgStatus Unknown (const Option &option, bool msg)
- static ArgStatus Required (const Option & option, bool msg)
- static ArgStatus NonEmpty (const Option & option, bool msg)

The documentation for this class was generated from the following file:

• src/include/ExampleArg.h

5.9 xmem::PrintUsageImplementation::FunctionWriter< Function > Struct Template Reference

 $Inheritance\ diagram\ for\ xmem:: Print Usage Implementation:: Function Writer < Function >:$

Collaboration diagram for xmem::PrintUsageImplementation::FunctionWriter< Function >:

Public Member Functions

- virtual void operator() (const char *str, int size)

 Writes the given number of chars beginning at the given pointer somewhere.
- FunctionWriter (Function *w)

Public Attributes

• Function * write

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.10 xmem::PrintUsageImplementation::IStringWriter Struct Reference

 $Inheritance\ diagram\ for\ xmem:: Print Usage Implementation:: IString Writer:$

Public Member Functions

virtual void operator() (const char *, int)

Writes the given number of chars beginning at the given pointer somewhere.

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.11 xmem::LatencyBenchmark Class Reference

A type of benchmark that measures memory latency via random pointer chasing. Loading may be provided with separate threads which access memory as quickly as possible using given access patterns.

```
#include <LatencyBenchmark.h>
```

Inheritance diagram for xmem::LatencyBenchmark:

Collaboration diagram for xmem::LatencyBenchmark:

Public Member Functions

LatencyBenchmark (void *mem_array, size_t len, uint32_t iterations, uint32_t num_worker_threads, uint32_t mem_node, uint32_t cpu_node, pattern_mode_t pattern_mode, rw_mode_t rw_mode, chunk_size_t chunk_size, int32_t stride_size, std::vector< PowerReader * > dram_power_readers, std::string name)

Constructor. Parameters are passed directly to the Benchmark constructor. See Benchmark class documentation for parameter semantics.

virtual ~LatencyBenchmark ()

Destructor.

• double getLoadMetricOnIter (uint32_t iter) const

Get the average load throughput in MB/sec that was imposed on the latency measurement during the given iteration.

• double getMeanLoadMetric () const

Get the overall arithmetic mean load throughput in MB/sec that was imposed on the latency measurement.

• virtual void reportBenchmarkInfo () const

Reports benchmark configuration details to the console.

· virtual void reportResults () const

Reports results to the console.

Protected Member Functions

• virtual bool runCore ()

The core benchmark function.

Protected Attributes

- std::vector< double > load_metric_on_iter_
- double mean_load_metric_

5.11.1 Detailed Description

A type of benchmark that measures memory latency via random pointer chasing. Loading may be provided with separate threads which access memory as quickly as possible using given access patterns.

5.11.2 Member Function Documentation

5.11.2.1 double LatencyBenchmark::getLoadMetricOnlter (uint32_t iter) const

Get the average load throughput in MB/sec that was imposed on the latency measurement during the given iteration. iter The iteration of interest.

Returns

The average throughput in MB/sec.

5.11.2.2 double LatencyBenchmark::getMeanLoadMetric () const

Get the overall arithmetic mean load throughput in MB/sec that was imposed on the latency measurement.

Returns

The mean throughput in MB/sec.

5.11.2.3 bool LatencyBenchmark::runCore() [protected], [virtual]

The core benchmark function.

Returns

True on success.

Implements xmem::Benchmark.

Here is the call graph for this function:

5.11.3 Member Data Documentation

5.11.3.1 std::vector<double> xmem::LatencyBenchmark::load_metric_on_iter_ [protected]

Load metrics for each iteration of the benchmark. This is in MB/s.

5.11.3.2 double xmem::LatencyBenchmark::mean_load_metric_ [protected]

The average load throughput in MB/sec that was imposed on the latency measurement.

The documentation for this class was generated from the following files:

- src/include/LatencyBenchmark.h
- src/LatencyBenchmark.cpp

5.12 xmem::LatencyWorker Class Reference

Multithreading-friendly class to do memory loading.

#include <LatencyWorker.h>

Inheritance diagram for xmem::LatencyWorker:

Collaboration diagram for xmem::LatencyWorker:

Public Member Functions

LatencyWorker (void *mem_array, size_t len, RandomFunction kernel_fptr, RandomFunction kernel_dummy_fptr, int32_t cpu_affinity)

Constructor for sequential-access patterns.

virtual ~LatencyWorker ()

Destructor.

virtual void run ()

Thread-safe worker method.

Additional Inherited Members

5.12.1 Detailed Description

Multithreading-friendly class to do memory loading.

5.12.2 Constructor & Destructor Documentation

5.12.2.1 LatencyWorker::LatencyWorker (void * mem_array, size_t len, RandomFunction kernel_fptr, RandomFunction kernel_dummy_fptr, int32_t cpu_affinity)

Constructor for sequential-access patterns.

Parameters

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
kernel_fptr	Pointer to the sequential core benchmark kernel to use.
kernel_dummy	Pointer to the sequential dummy version of the core benchmark kernel to use.
fptr	
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

The documentation for this class was generated from the following files:

- src/include/LatencyWorker.h
- src/LatencyWorker.cpp

5.13 xmem::PrintUsageImplementation::LinePartIterator Class Reference

Public Member Functions

• LinePartIterator (const Descriptor usage[])

Creates an iterator for usage.

· bool nextTable ()

Moves iteration to the next table (if any). Has to be called once on a new LinePartIterator to move to the 1st table.

• void restartTable ()

Reset iteration to the beginning of the current table.

• bool nextRow ()

Moves iteration to the next row (if any). Has to be called once after each call to nextTable() to move to the 1st row of the table.

· void restartRow ()

Reset iteration to the beginning of the current row.

• bool next ()

Moves iteration to the next part (if any). Has to be called once after each call to nextRow() to move to the 1st part of the row.

• int column ()

Returns the index (counting from 0) of the column in which the part pointed to by data() is located.

• int line ()

Returns the index (counting from 0) of the line within the current column this part belongs to.

• int length ()

Returns the length of the part pointed to by data() in raw chars (not UTF-8 characters).

int screenLength ()

Returns the width in screen columns of the part pointed to by data(). Takes multi-byte UTF-8 sequences and wide characters into account.

· const char * data ()

Returns the current part of the iteration.

5.13.1 Member Function Documentation

5.13.1.1 bool xmem::PrintUsageImplementation::LinePartIterator::next() [inline]

Moves iteration to the next part (if any). Has to be called once after each call to nextRow() to move to the 1st part of the row.

Return values

false	if moving to next part failed because no further part exists.

See LinePartIterator for details about the iteration.

5.13.1.2 bool xmem::PrintUsageImplementation::LinePartIterator::nextRow() [inline]

Moves iteration to the next row (if any). Has to be called once after each call to nextTable() to move to the 1st row of the table.

Return values

false	if moving to next row failed because no further row exists.

Here is the call graph for this function:

5.13.1.3 bool xmem::PrintUsageImplementation::LinePartIterator::nextTable() [inline]

Moves iteration to the next table (if any). Has to be called once on a new LinePartIterator to move to the 1st table. Return values

false if moving to next table failed because no further table exists.

Here is the call graph for this function:

The documentation for this class was generated from the following file:

• src/include/optionparser.h

5.14 xmem::PrintUsageImplementation::LineWrapper Class Reference

Public Member Functions

void flush (IStringWriter &write)

Writes out all remaining data from the LineWrapper using write. Unlike process() this method indents all lines including the first and will output a \n at the end (but only if something has been written).

void process (IStringWriter &write, const char *data, int len)

Process, wrap and output the next piece of data.

LineWrapper (int x1, int x2)

Constructs a LineWrapper that wraps its output to fit into screen columns x1 (incl.) to x2 (excl.).

5.14.1 Constructor & Destructor Documentation

5.14.1.1 xmem::PrintUsageImplementation::LineWrapper::LineWrapper (int x1, int x2) [inline]

Constructs a LineWrapper that wraps its output to fit into screen columns x1 (incl.) to x2 (excl.).

x1 gives the indentation LineWrapper uses if it needs to indent.

5.14.2 Member Function Documentation

5.14.2.1 void xmem::PrintUsageImplementation::LineWrapper::process (IStringWriter & write, const char * data, int len) [inline]

Process, wrap and output the next piece of data.

process() will output at least one line of output. This is not necessarily the data passed in. It may be data queued from a prior call to process(). If the internal buffer is full, more than 1 line will be output.

process() assumes that the a proper amount of indentation has already been output. It won't write any further indentation before the 1st line. If more than 1 line is written due to buffer constraints, the lines following the first will be indented by this method, though.

No \n is written by this method after the last line that is written.

Parameters

write	where to write the data.
data	the new chunk of data to write.
len	the length of the chunk of data to write.

Here is the call graph for this function:

The documentation for this class was generated from the following file:

• src/include/optionparser.h

5.15 xmem::LoadWorker Class Reference

Multithreading-friendly class to do memory loading.

#include <LoadWorker.h>

Inheritance diagram for xmem::LoadWorker:

Collaboration diagram for xmem::LoadWorker:

Public Member Functions

• LoadWorker (void *mem_array, size_t len, SequentialFunction kernel_fptr, SequentialFunction kernel_dummy_fptr, int32_t cpu_affinity)

Constructor for sequential-access patterns.

LoadWorker (void *mem_array, size_t len, RandomFunction kernel_fptr, RandomFunction kernel_dummy_fptr, int32_t cpu_affinity)

Constructor for random-access patterns.

virtual ~LoadWorker ()

Destructor.

· virtual void run ()

Thread-safe worker method.

Additional Inherited Members

5.15.1 Detailed Description

Multithreading-friendly class to do memory loading.

5.15.2 Constructor & Destructor Documentation

5.15.2.1 LoadWorker::LoadWorker (void * mem_array, size_t len, SequentialFunction kernel_fptr, SequentialFunction kernel_dummy_fptr, int32_t cpu_affinity)

Constructor for sequential-access patterns.

Parameters

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
kernel_fptr	Pointer to the sequential core benchmark kernel to use.
kernel_dummy	Pointer to the sequential dummy version of the core benchmark kernel to use.
fptr	
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

5.15.2.2 LoadWorker::LoadWorker (void * mem_array, size_t len, RandomFunction kernel_fptr, RandomFunction kernel_dummy_fptr, int32_t cpu_affinity)

Constructor for random-access patterns.

Parameters

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
kernel_fptr	Pointer to the random core benchmark kernel to use.
kernel_dummy	Pointer to the random dummy version of the core benchmark kernel to use.
fptr	
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

The documentation for this class was generated from the following files:

- src/include/LoadWorker.h
- src/LoadWorker.cpp

5.16 xmem::MemoryWorker Class Reference

Multithreading-friendly class to run memory access kernels.

#include <MemoryWorker.h>

Inheritance diagram for xmem::MemoryWorker:

Collaboration diagram for xmem::MemoryWorker:

Public Member Functions

• MemoryWorker (void *mem_array, size_t len, int32_t cpu_affinity)

Constructor.

virtual ∼MemoryWorker ()

Destructor.

• virtual void run ()=0

Thread-safe worker method.

• size_t getLen ()

Gets the length of the memory region used by this worker.

uint32_t getBytesPerPass ()

Gets the number of bytes used in each pass of the benchmark by this worker.

• uint32_t getPasses ()

Gets the number of passes for this worker.

• tick_t getElapsedTicks ()

Gets the elapsed ticks for this worker on the core benchmark kernel.

tick_t getElapsedDummyTicks ()

Gets the elapsed ticks for this worker on the dummy version of the core benchmark kernel.

tick_t getAdjustedTicks ()

Gets the adjusted ticks for this worker. This is elapsed ticks minus elapsed dummy ticks.

• bool hadWarning ()

Indicates whether worker's results may be questionable/inaccurate/invalid.

Protected Attributes

- void * mem array
- size_t len_
- int32_t cpu_affinity_
- uint32_t bytes_per_pass_
- uint32_t passes_
- tick_t elapsed_ticks_
- tick_t elapsed_dummy_ticks_
- tick_t adjusted_ticks_
- bool warning
- bool completed_

Additional Inherited Members

5.16.1 Detailed Description

Multithreading-friendly class to run memory access kernels.

5.16.2 Constructor & Destructor Documentation

5.16.2.1 MemoryWorker::MemoryWorker (void * mem_array, size_t len, int32_t cpu_affinity)

Constructor.

Parameters

mem_array	Pointer to the memory region to use by this worker.
len	Length of the memory region to use by this worker.
cpu_affinity	Logical CPU identifier to lock this worker's thread to.

5.16.3 Member Function Documentation

```
5.16.3.1 tick_t MemoryWorker::getAdjustedTicks ( )
```

Gets the adjusted ticks for this worker. This is elapsed ticks minus elapsed dummy ticks.

Returns

The adjusted ticks for this worker.

Here is the call graph for this function:

```
5.16.3.2 uint32_t MemoryWorker::getBytesPerPass ( )
```

Gets the number of bytes used in each pass of the benchmark by this worker.

Returns

Number of bytes in each pass.

Here is the call graph for this function:

```
5.16.3.3 tick_t MemoryWorker::getElapsedDummyTicks ( )
```

Gets the elapsed ticks for this worker on the dummy version of the core benchmark kernel.

Returns

The number of elapsed dummy ticks.

Here is the call graph for this function:

```
5.16.3.4 tick_t MemoryWorker::getElapsedTicks ( )
```

Gets the elapsed ticks for this worker on the core benchmark kernel.

Returns

The number of elapsed ticks.

Here is the call graph for this function:

```
5.16.3.5 size_t MemoryWorker::getLen ( )
```

Gets the length of the memory region used by this worker.

Returns

Length of memory region in bytes.

Here is the call graph for this function:

```
5.16.3.6 uint32_t MemoryWorker::getPasses ( )
Gets the number of passes for this worker.
Returns
     The number of passes.
Here is the call graph for this function:
5.16.3.7 bool MemoryWorker::hadWarning ( )
Indicates whether worker's results may be questionable/inaccurate/invalid.
Returns
     True if the worker's results had a warning.
Here is the call graph for this function:
5.16.4 Member Data Documentation
5.16.4.1 tick_t xmem::MemoryWorker::adjusted_ticks_ [protected]
Elapsed ticks minus dummy elapsed ticks.
5.16.4.2 uint32_t xmem::MemoryWorker::bytes_per_pass_ [protected]
Number of bytes accessed in each kernel pass.
5.16.4.3 bool xmem::MemoryWorker::completed_ [protected]
If true, worker completed.
5.16.4.4 int32_t xmem::MemoryWorker::cpu_affinity_ [protected]
The logical CPU affinity for this worker.
5.16.4.5 tick_t xmem::MemoryWorker::elapsed_dummy_ticks_ [protected]
Total elapsed ticks on the dummy kernel routine.
5.16.4.6 tick_t xmem::MemoryWorker::elapsed_ticks_ [protected]
Total elapsed ticks on the kernel routine.
5.16.4.7 size_t xmem::MemoryWorker::len_ [protected]
```

Generated on Thu Apr 7 2016 08:15:17 for X-Mem by Doxygen

The length of the memory region for this worker.

```
5.16.4.8 void* xmem::MemoryWorker::mem_array_ [protected]
```

The memory region for this worker.

```
5.16.4.9 uint32_t xmem::MemoryWorker::passes_ [protected]
```

Number of passes.

```
5.16.4.10 bool xmem::MemoryWorker::warning [protected]
```

If true, results may be suspect.

The documentation for this class was generated from the following files:

- src/include/MemoryWorker.h
- src/MemoryWorker.cpp

5.17 xmem::MyArg Class Reference

Inheritance diagram for xmem::MyArg:

Collaboration diagram for xmem::MyArg:

Static Public Member Functions

• static ArgStatus Integer (const Option &option, bool msg)

Checks an option that it is an integer.

static ArgStatus NonnegativeInteger (const Option & option, bool msg)

Checks an option that it is a nonnegative integer.

static ArgStatus PositiveInteger (const Option & option, bool msg)

Checks an option that it is a positive integer.

The documentation for this class was generated from the following file:

src/include/MyArg.h

5.18 xmem::Option Class Reference

A parsed option from the command line together with its argument if it has one.

```
#include <optionparser.h>
```

Collaboration diagram for xmem::Option:

Public Member Functions

• int type () const

Returns Descriptor::type of this Option's Descriptor, or 0 if this Option is invalid (unused).

• int index () const

Returns Descriptor::index of this Option's Descriptor, or -1 if this Option is invalid (unused).

• int count ()

Returns the number of times this Option (or others with the same Descriptor::index) occurs in the argument vector.

· bool isFirst () const

Returns true iff this is the first element of the linked list.

· bool isLast () const

Returns true iff this is the last element of the linked list.

• Option * first ()

Returns a pointer to the first element of the linked list.

Option * last ()

Returns a pointer to the last element of the linked list.

• Option * prev ()

Returns a pointer to the previous element of the linked list or NULL if called on first().

Option * prevwrap ()

Returns a pointer to the previous element of the linked list with wrap-around from first() to last().

• Option * next ()

Returns a pointer to the next element of the linked list or NULL if called on last().

Option * nextwrap ()

Returns a pointer to the next element of the linked list with wrap-around from last() to first().

void append (Option *new last)

Makes new_last the new last() by chaining it into the list after last().

operator const Option * () const

Casts from Option to const Option* but only if this Option is valid.

operator Option * ()

Casts from Option to Option* but only if this Option is valid.

• Option ()

Creates a new Option that is a one-element linked list and has NULL desc, name, arg and namelen.

Option (const Descriptor *desc_, const char *name_, const char *arg_)

Creates a new Option that is a one-element linked list and has the given values for desc, name and arg.

• void operator= (const Option &orig)

Makes *this a copy of orig except for the linked list pointers.

Option (const Option &orig)

Makes *this a copy of orig except for the linked list pointers.

Public Attributes

• const Descriptor * desc

Pointer to this Option's Descriptor.

• const char * name

The name of the option as used on the command line.

const char * arg

Pointer to this Option's argument (if any).

• int namelen

The length of the option name.

5.18.1 Detailed Description

A parsed option from the command line together with its argument if it has one.

The Parser chains all parsed options with the same Descriptor::index together to form a linked list. This allows you to easily implement all of the common ways of handling repeated options and enable/disable pairs.

Test for presence of a switch in the argument vector:

```
if ( options[QUIET] ) ...
```

• Evaluate -enable-foo/-disable-foo pair where the last one used wins:

```
if ( options[FOO].last()->type() == DISABLE ) ...
```

• Cumulative option (-v verbose, -vv more verbose, -vvv even more verbose):

```
int verbosity = options[VERBOSE].count();
```

Iterate over all –file=<fname> arguments:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

5.18.2 Constructor & Destructor Documentation

```
5.18.2.1 xmem::Option::Option (const Descriptor * desc_, const char * name_, const char * arg_ ) [inline]
```

Creates a new Option that is a one-element linked list and has the given values for desc, name and arg.

If name_points at a character other than '-' it will be assumed to refer to a short option and namelen will be set to 1. Otherwise the length will extend to the first '=' character or the string's 0-terminator.

```
5.18.2.2 xmem::Option:Option (const Option & orig) [inline]
```

Makes *this a copy of orig except for the linked list pointers.

After this operation *this will be a one-element linked list.

5.18.3 Member Function Documentation

```
5.18.3.1 void xmem::Option::append ( Option * new_last ) [inline]
```

Makes new_last the new last() by chaining it into the list after last().

It doesn't matter which element you call append() on. The new element will always be appended to last().

Attention

new_last must not yet be part of a list, or that list will become corrupted, because this method does not unchain new_last from an existing list.

Here is the call graph for this function:

```
5.18.3.2 int xmem::Option::count() [inline]
```

Returns the number of times this Option (or others with the same Descriptor::index) occurs in the argument vector.

This corresponds to the number of elements in the linked list this Option is part of. It doesn't matter on which element you call count(). The return value is always the same.

Use this to implement cumulative options, such as -v, -vv, -vvv for different verbosity levels.

Returns 0 when called for an unused/invalid option.

Here is the call graph for this function:

```
5.18.3.3 Option* xmem::Option::first() [inline]
```

Returns a pointer to the first element of the linked list.

Use this when you want the first occurrence of an option on the command line to take precedence. Note that this is not the way most programs handle options. You should probably be using last() instead.

Note

This method may be called on an unused/invalid option and will return a pointer to the option itself.

Here is the call graph for this function:

```
5.18.3.4 bool xmem::Option::isFirst() const [inline]
```

Returns true iff this is the first element of the linked list.

The first element in the linked list is the first option on the command line that has the respective Descriptor::index value.

Returns true for an unused/invalid option.

```
5.18.3.5 bool xmem::Option::isLast() const [inline]
```

Returns true iff this is the last element of the linked list.

The last element in the linked list is the last option on the command line that has the respective Descriptor::index value.

Returns true for an unused/invalid option.

```
5.18.3.6 Option*xmem::Option::last() [inline]
```

Returns a pointer to the last element of the linked list.

Use this when you want the last occurrence of an option on the command line to take precedence. This is the most common way of handling conflicting options.

Note

This method may be called on an unused/invalid option and will return a pointer to the option itself.

Tip:

If you have options with opposite meanings (e.g. -enable-foo and -disable-foo), you can assign them the same Descriptor::index to get them into the same list. Distinguish them by Descriptor::type and all you have to do is check last () ->type () to get the state listed last on the command line.

Here is the call graph for this function:

```
5.18.3.7 Option*xmem::Option::next() [inline]
```

Returns a pointer to the next element of the linked list or NULL if called on last().

If called on last() this method returns NULL. Otherwise it will return the option with the same Descriptor::index that follows this option on the command line.

Here is the call graph for this function:

```
5.18.3.8 Option* xmem::Option::nextwrap() [inline]
```

Returns a pointer to the next element of the linked list with wrap-around from last() to first().

If called on last() this method returns first(). Otherwise it will return the option with the same Descriptor::index that follows this option on the command line.

```
5.18.3.9 xmem::Option::operator const Option * ( ) const [inline]
```

Casts from Option to const Option* but only if this Option is valid.

If this Option is valid (i.e. desc!=NULL), returns this. Otherwise returns NULL. This allows testing an Option directly in an if-clause to see if it is used:

```
if (options[CREATE])
{
    ...
```

It also allows you to write loops like this:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

```
5.18.3.10 xmem::Option::operator Option * ( ) [inline]
```

Casts from Option to Option* but only if this Option is valid.

If this Option is valid (i.e. <code>desc!=NULL</code>), returns this. Otherwise returns NULL. This allows testing an Option directly in an if-clause to see if it is used:

```
if (options[CREATE])
{
    ...
}
```

It also allows you to write loops like this:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

5.18.3.11 void xmem::Option::operator=(const Option & orig) [inline]

Makes *this a copy of orig except for the linked list pointers.

After this operation *this will be a one-element linked list.

```
5.18.3.12 Option* xmem::Option::prev( ) [inline]
```

Returns a pointer to the previous element of the linked list or NULL if called on first().

If called on first() this method returns NULL. Otherwise it will return the option with the same Descriptor::index that precedes this option on the command line.

Here is the call graph for this function:

```
5.18.3.13 Option* xmem::Option::prevwrap() [inline]
```

Returns a pointer to the previous element of the linked list with wrap-around from first() to last().

If called on first() this method returns last(). Otherwise it will return the option with the same Descriptor::index that precedes this option on the command line.

```
5.18.3.14 int xmem::Option::type() const [inline]
```

Returns Descriptor::type of this Option's Descriptor, or 0 if this Option is invalid (unused).

Because this method (and last(), too) can be used even on unused Options with desc==0, you can (provided you arrange your types properly) switch on type() without testing validity first.

5.18.4 Member Data Documentation

5.18.4.1 const char* xmem::Option::arg

Pointer to this Option's argument (if any).

NULL if this option has no argument. Do not confuse this with the empty string which is a valid argument.

5.18.4.2 const Descriptor* xmem::Option::desc

Pointer to this Option's Descriptor.

Remember that the first dummy descriptor (see Descriptor::longopt) is used for unknown options.

Attention

desc==NULL signals that this Option is unused. This is the default state of elements in the result array. You don't need to test desc explicitly. You can simply write something like this:

```
if (options[CREATE])
{
    ...
}
```

This works because of operator const Option*() .

5.18.4.3 const char* xmem::Option::name

The name of the option as used on the command line.

The main purpose of this string is to be presented to the user in messages.

In the case of a long option, this is the actual argv pointer, i.e. the first character is a '-'. In the case of a short option this points to the option character within the argv string.

Note that in the case of a short option group or an attached option argument, this string will contain additional characters following the actual name. Use namelen to filter out the actual option name only.

5.18.4.4 int xmem::Option::namelen

The length of the option name.

Because name points into the actual <code>argv</code> string, the option name may be followed by more characters (e.g. other short options in the same short option group). This value is the number of bytes (not characters!) that are part of the actual name.

For a short option, this length is always 1. For a long option this length is always at least 2 if single minus long options are permitted and at least 3 if they are disabled.

Note

In the pathological case of a minus within a short option group (e.g. -xf-z), this length is incorrect, because this case will be misinterpreted as a long option and the name will therefore extend to the string's 0-terminator or a following '=" character if there is one. This is irrelevant for most uses of name and namelen. If you really need to distinguish the case of a long and a short option, compare name to the argv pointers. A long option's name is always identical to one of them, whereas a short option's is never.

The documentation for this class was generated from the following file:

• src/include/optionparser.h

5.19 xmem::PrintUsageImplementation::OStreamWriter< OStream > Struct Template Reference

 $Inheritance\ diagram\ for\ xmem:: Print Usage Implementation:: OS tream Writer < OS tream >:$

Collaboration diagram for xmem::PrintUsageImplementation::OStreamWriter< OStream >:

Public Member Functions

- virtual void operator() (const char *str, int size)
 Writes the given number of chars beginning at the given pointer somewhere.
- OStreamWriter (OStream &o)

Public Attributes

· OStream & ostream

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.20 xmem::Parser Class Reference

Checks argument vectors for validity and parses them into data structures that are easier to work with.

```
#include <optionparser.h>
```

Classes

- struct Action
- class StoreOptionAction

Public Member Functions

• Parser ()

Creates a new Parser.

 Parser (bool gnu, const Descriptor usage[], int argc, const char **argv, Option options[], Option buffer[], int min_abbr_len=0, bool single_minus_longopt=false, int bufmax=-1)

Creates a new Parser and immediately parses the given argument vector.

Parser (bool gnu, const Descriptor usage[], int argc, char **argv, Option options[], Option buffer[], int min_-abbr_len=0, bool single_minus_longopt=false, int bufmax=-1)

Parser(...) with non-const argv.

Parser (const Descriptor usage[], int argc, const char **argv, Option options[], Option buffer[], int min_abbr_len=0, bool single_minus_longopt=false, int bufmax=-1)

POSIX Parser(...) (gnu==false).

• Parser (const Descriptor usage[], int argc, char **argv, Option options[], Option buffer[], int min_abbr_len=0, bool single minus longopt=false, int bufmax=-1)

POSIX Parser(...) (gnu==false) with non-const argv.

void parse (bool gnu, const Descriptor usage[], int argc, const char **argv, Option options[], Option buffer[], int min_abbr_len=0, bool single_minus_longopt=false, int bufmax=-1)

Parses the given argument vector.

void parse (bool gnu, const Descriptor usage[], int argc, char **argv, Option options[], Option buffer[], int min_abbr_len=0, bool single_minus_longopt=false, int bufmax=-1)

parse() with non-const argv.

• void parse (const Descriptor usage[], int argc, const char **argv, Option options[], Option buffer[], int min_abbr_len=0, bool single_minus_longopt=false, int bufmax=-1)

POSIX parse() (gnu==false).

• void parse (const Descriptor usage[], int argc, char **argv, Option options[], Option buffer[], int min_abbr_-len=0, bool single_minus_longopt=false, int bufmax=-1)

POSIX parse() (gnu==false) with non-const argv.

• int optionsCount ()

Returns the number of valid Option objects in buffer[].

• int nonOptionsCount ()

Returns the number of non-option arguments that remained at the end of the most recent parse() that actually encountered non-option arguments.

const char ** nonOptions ()

Returns a pointer to an array of non-option arguments (only valid if nonOptionsCount() > 0).

const char * nonOption (int i)

Returns nonOptions () [i] (without checking if i is in range!).

bool error ()

Returns true if an unrecoverable error occurred while parsing options.

Friends

· struct Stats

5.20.1 Detailed Description

Checks argument vectors for validity and parses them into data structures that are easier to work with.

Example:

```
int main(int argc, char* argv[])
{
  argc-=(argc>0);  argv+=(argc>0);  // skip program name argv[0] if present
  option::Stats stats(usage, argc, argv);
  option::Option options[stats.options_max], buffer[stats.buffer_max];
  option::Parser parse(usage, argc, argv, options, buffer);

if (parse.error())
  return 1;

if (options[HELP])
...
```

5.20.2 Constructor & Destructor Documentation

5.20.2.1 xmem::Parser:(bool gnu, const Descriptor usage[], int argc, const char ** argv, Option options[],

Option buffer[], int min_abbr_len = 0, bool single_minus_longopt = false, int bufmax = -1) [inline]

Creates a new Parser and immediately parses the given argument vector.

Parameters

gnu	if true, parse() will not stop at the first non-option argument. Instead it will reorder arguments so that all non-options are at the end. This is the default behaviour of GNU getopt() but is not conforming to POSIX. Note, that once the argument vector has been reordered, the gnu flag will have no further effect on this argument vector. So it is enough to pass gnu==true when creating Stats.
usage	Array of Descriptor objects that describe the options to support. The last entry of this array must have 0 in all fields.
argc	The number of elements from <code>argv</code> that are to be parsed. If you pass -1, the number will be determined automatically. In that case the <code>argv</code> list must end with a NULL pointer.
argv	The arguments to be parsed. If you pass -1 as argc the last pointer in the argv list must be NULL to mark the end.
options	Each entry is the first element of a linked list of Options. Each new option that is parsed will be appended to the list specified by that Option's Descriptor::index. If an entry is not yet used (i.e. the Option is invalid), it will be replaced rather than appended to. The minimum length of this array is the greatest Descriptor::index value that occurs in usage PLUS ONE.
buffer	Each argument that is successfully parsed (including unknown arguments, if they have a Descriptor whose CheckArg does not return ARG_ILLEGAL) will be stored in this array. parse() scans the array for the first invalid entry and begins writing at that index. You can pass bufmax to limit the number of options stored.
min_abbr_len	Passing a value min_abbr_len > 0 enables abbreviated long options. The parser will match a prefix of a long option as if it was the full long option (e.gfoob=10 will be interpreted as if it was -foobar=10), as long as the prefix has at least min_abbr_len characters (not counting the -) and is unambiguous. Be careful if combining min_abbr_len=1 with single_minus_longopt=true because the ambiguity check does not consider short options and abbreviated single minus long options will take precedence over short options.
single_minus longopt	Passing true for this option allows long options to begin with a single minus. The double minus form will still be recognized. Note that single minus long options take precedence over short options and short option groups. E.g. $-file$ would be interpreted as $-file$ and not as $-file$ (assuming a long option named "file" exists).
bufmax	The greatest index in the <code>buffer[]</code> array that <code>parse()</code> will write to is <code>bufmax-1</code> . If there are more options, they will be processed (in particular their CheckArg will be called) but not stored. If you used <code>Stats::buffer_max</code> to dimension this array, you can pass -1 (or not pass <code>bufmax</code> at all) which tells <code>parse()</code> that the buffer is "large enough".

Attention

Remember that options and buffer store Option objects, not pointers. Therefore it is not possible for the same object to be in both arrays. For those options that are found in both buffer[] and options[] the respective objects are independent copies. And only the objects in options[] are properly linked via Option::next() and Option::prev(). You can iterate over buffer[] to process all options in the order they appear in the argument vector, but if you want access to the other Options with the same Descriptor::index, then you must access the linked list via options[]. You can get the linked list in options from a buffer object via something like options[buffer[i].index()].

Here is the call graph for this function:

5.20.3 Member Function Documentation

```
5.20.3.1 bool xmem::Parser::error( ) [inline]
```

Returns true if an unrecoverable error occurred while parsing options.

An illegal argument to an option (i.e. CheckArg returns ARG_ILLEGAL) is an unrecoverable error that aborts the parse. Unknown options are only an error if their CheckArg function returns ARG_ILLEGAL. Otherwise they are collected. In that case if you want to exit the program if either an illegal argument or an unknown option has been passed, use code like this

```
if (parser.error() || options[UNKNOWN])
  exit(1);
```

```
5.20.3.2 const char** xmem::Parser::nonOptions() [inline]
```

Returns a pointer to an array of non-option arguments (only valid if nonOptionsCount () >0).

Note

- parse() does not copy arguments, so this pointer points into the actual argument vector as passed to parse().
- As explained at nonOptionsCount() this pointer is only changed by parse() calls that actually encounter non-option arguments. A parse() call that encounters only options, will not change nonOptions().

```
5.20.3.3 int xmem::Parser::nonOptionsCount() [inline]
```

Returns the number of non-option arguments that remained at the end of the most recent parse() that actually encountered non-option arguments.

Note

A parse() that does not encounter non-option arguments will leave this value as well as nonOptions() undisturbed. This means you can feed the Parser a default argument vector that contains non-option arguments (e.g. a default filename). Then you feed it the actual arguments from the user. If the user has supplied at least one non-option argument, all of the non-option arguments from the default disappear and are replaced by the user's non-option arguments. However, if the user does not supply any non-option arguments the defaults will still be in effect.

```
5.20.3.4 int xmem::Parser::optionsCount() [inline]
```

Returns the number of valid Option objects in buffer[].

Note

- The returned value always reflects the number of Options in the buffer[] array used for the most recent call to parse().
- The count (and the buffer[]) includes unknown options if they are collected (see Descriptor::longopt).

```
5.20.3.5 void xmem::Parser::parse ( bool gnu, const Descriptor usage[], int argc, const char ** argv, Option options[], Option buffer[], int min_abbr_len = 0, bool single_minus_longopt = false, int bufmax = -1) [inline]
```

Parses the given argument vector.

Parameters

gnu	if true, parse() will not stop at the first non-option argument. Instead it will reorder arguments so that all non-options are at the end. This is the default behaviour of GNU getopt() but is not conforming to POSIX. Note, that once the argument vector has been reordered, the gnu flag will have no further effect on this argument vector. So it is enough to pass gnu==true when creating Stats.
usage	Array of Descriptor objects that describe the options to support. The last entry of this array must have 0 in all fields.
argc	The number of elements from <code>argv</code> that are to be parsed. If you pass -1, the number will be determined automatically. In that case the <code>argv</code> list must end with a NULL pointer.
argv	The arguments to be parsed. If you pass -1 as argc the last pointer in the argv list must be NULL to mark the end.
options	Each entry is the first element of a linked list of Options. Each new option that is parsed will be appended to the list specified by that Option's Descriptor::index. If an entry is not yet used (i.e. the Option is invalid), it will be replaced rather than appended to. The minimum length of this array is the greatest Descriptor::index value that occurs in usage PLUS ONE.
buffer	Each argument that is successfully parsed (including unknown arguments, if they have a Descriptor whose CheckArg does not return ARG_ILLEGAL) will be stored in this array. parse() scans the array for the first invalid entry and begins writing at that index. You can pass bufmax to limit the number of options stored.
min_abbr_len	Passing a value min_abbr_len > 0 enables abbreviated long options. The parser will match a prefix of a long option as if it was the full long option (e.gfoob=10 will be interpreted as if it was -foobar=10), as long as the prefix has at least min_abbr_len characters (not counting the -) and is unambiguous. Be careful if combining min_abbr_len=1 with single_minus_longopt=true because the ambiguity check does not consider short options and abbreviated single minus long options will take precedence over short options.
single_minus longopt	Passing true for this option allows long options to begin with a single minus. The double minus form will still be recognized. Note that single minus long options take precedence over short options and short option groups. E.g. $-file$ would be interpreted as $-file$ and not as $-file$ (assuming a long option named "file" exists).
bufmax	The greatest index in the <code>buffer[]</code> array that <code>parse()</code> will write to is <code>bufmax-1</code> . If there are more options, they will be processed (in particular their CheckArg will be called) but not stored. If you used <code>Stats::buffer_max</code> to dimension this array, you can pass -1 (or not pass <code>bufmax</code> at all) which tells <code>parse()</code> that the buffer is "large enough".

Attention

Remember that options and buffer store Option objects, not pointers. Therefore it is not possible for the same object to be in both arrays. For those options that are found in both buffer[] and options[] the respective objects are independent copies. And only the objects in options[] are properly linked via Option::next() and Option::prev(). You can iterate over buffer[] to process all options in the order they appear in the argument vector, but if you want access to the other Options with the same Descriptor::index, then you must access the linked list via options[]. You can get the linked list in options from a buffer object via something like options[buffer[i].index()].

The documentation for this class was generated from the following file:

• src/include/optionparser.h

5.21 xmem::PowerReader Class Reference

An abstract base class for measuring power from an arbitrary source. This class is runnable using a worker thread.

```
#include <PowerReader.h>
```

Inheritance diagram for xmem::PowerReader:

Collaboration diagram for xmem::PowerReader:

Public Member Functions

· PowerReader (uint32 t sampling period, double power units, std::string name, int32 t cpu affinity)

Constructor.

∼PowerReader ()

Destructor.

• virtual void run ()=0

Starts measuring power at the rate implied by the sampling_period passed in the constructor. Call stop() to indicate to stop measuring.

• bool stop ()

Signals to stop measuring power. This is a non-blocking call and return does not indicate the measurement has actually stopped.

• bool calculateMetrics ()

Calculates the relevant metrics.

• bool clear ()

Clears the stored power data.

bool clearAndReset ()

Clears the stored power data and resets state so that a new thread can be used with this object.

std::vector< double > getPowerTrace ()

Gets the power trace.

double getMeanPower ()

Gets the mean power.

double getPeakPower ()

Gets the peak power.

• double getLastSample ()

Gets the last sample.

• uint32_t getSamplingPeriod ()

Gets the sampling period.

• double getPowerUnits ()

Gets the units of samples in watts.

size_t getNumSamples ()

Gets the number of samples collected.

• std::string name ()

Gets the name of this object.

Protected Attributes

- · bool stop_signal_
- · double power_units_
- std::string name
- · int32_t cpu_affinity_
- std::vector< double > power_trace_
- double mean power
- · double peak_power_
- size_t num_samples_
- uint32_t sampling_period_

Additional Inherited Members

5.21.1 Detailed Description

An abstract base class for measuring power from an arbitrary source. This class is runnable using a worker thread.

5.21.2 Constructor & Destructor Documentation

5.21.2.1 PowerReader::PowerReader (uint32_t sampling_period, double power_units, std::string name, int32_t cpu_affinity)

Constructor.

Parameters

sampling_period	The time between power samples in milliseconds.
power_units	The power units for each sample in watts.
name	The human-friendly name of this object.
cpu_affinity	The logical CPU to be used by the thread calling this object's run() method. If negative, any
	CPU is OK (no affinity).

5.21.3 Member Function Documentation

5.21.3.1 bool PowerReader::calculateMetrics ()

Calculates the relevant metrics.

Returns

True on success.

Here is the call graph for this function:

5.21.3.2 bool PowerReader::clear ()

Clears the stored power data.

Returns

True on success.

Here is the call graph for this function:

5.21.3.3 bool PowerReader::clearAndReset ()

Clears the stored power data and resets state so that a new thread can be used with this object.

Returns

True on success.

Here is the call graph for this function:

5.21.3.4 double PowerReader::getLastSample ()

Gets the last sample.

Returns

The last power sample measured.

Here is the call graph for this function:

5.21.3.5 double PowerReader::getMeanPower ()

Gets the mean power.

Returns

The mean power from the measurements. If no data was collected, returns 0.

Here is the call graph for this function:

5.21.3.6 size_t PowerReader::getNumSamples ()

Gets the number of samples collected.

Returns

Number of samples collected.

Here is the call graph for this function:

5.21.3.7 double PowerReader::getPeakPower ()

Gets the peak power.

Returns

The peak power sample from the measurements. If no data was collected, returns 0.

Here is the call graph for this function:

5.21.3.8 std::vector< double > PowerReader::getPowerTrace ()

Gets the power trace.

Returns

The measured power trace in a vector. If no data was collected, the vector will be empty.

Here is the call graph for this function:

5.21.3.9 double PowerReader::getPowerUnits ()

Gets the units of samples in watts.

Returns

The power units for each measurement sample in watts. For example, if each measurement is in milliwatts, then this returns 1e-3.

Here is the call graph for this function:

60 Class Documentation

```
5.21.3.10 uint32_t PowerReader::getSamplingPeriod ( )
```

Gets the sampling period.

Returns

The sampling period of the measurements in milliseconds.

Here is the call graph for this function:

```
5.21.3.11 std::string PowerReader::name ( )
```

Gets the name of this object.

Returns

The human-friendly name of this PowerReader.

Here is the call graph for this function:

```
5.21.3.12 bool PowerReader::stop ( )
```

Signals to stop measuring power. This is a non-blocking call and return does not indicate the measurement has actually stopped.

Returns

True if it successfully signaled a stop.

Here is the call graph for this function:

```
5.21.4 Member Data Documentation
```

```
5.21.4.1 int32_t xmem::PowerReader::cpu_affinity_ [protected]
```

CPU affinity for any thread using this object's run() method. If negative, no affinity preference.

```
5.21.4.2 double xmem::PowerReader::mean_power_ [protected]
```

The mean power.

```
5.21.4.3 std::string xmem::PowerReader::name_ [protected]
```

Name of this object.

```
5.21.4.4 size_t xmem::PowerReader::num_samples_ [protected]
```

The number of samples collected.

```
5.21.4.5 double xmem::PowerReader::peak_power_ [protected]
```

The peak power observed.

```
5.21.4.6 std::vector<double> xmem::PowerReader::power_trace_ [protected]
```

The time-ordered list of power samples. The first index is the oldest measurement.

```
5.21.4.7 double xmem::PowerReader::power_units_ [protected]
```

Power units in watts.

```
5.21.4.8 uint32_t xmem::PowerReader::sampling_period_ [protected]
```

Power sampling period in milliseconds.

```
5.21.4.9 bool xmem::PowerReader::stop_signal_ [protected]
```

When true, the run() function should finish after the current sample iteration it is working on.

The documentation for this class was generated from the following files:

- src/include/PowerReader.h
- src/PowerReader.cpp

5.22 xmem::PrintUsageImplementation Struct Reference

Classes

- struct FunctionWriter
- struct IStringWriter
- class LinePartIterator
- · class LineWrapper
- struct OStreamWriter
- struct StreamWriter
- struct SyscallWriter
- struct TemporaryWriter

Static Public Member Functions

- static void upmax (int &i1, int i2)
- static void **indent** (IStringWriter &write, int &x, int want_x)
- static bool isWideChar (unsigned ch)

Returns true if ch is the unicode code point of a wide character.

• static void **printUsage** (IStringWriter &write, const Descriptor usage[], int width=80, int last_column_min_percent=50, int last_column_own_line_max_percent=75)

5.22.1 Member Function Documentation

```
5.22.1.1 static bool xmem::PrintUsageImplementation::isWideChar (unsigned ch ) [inline], [static]
```

Returns true if ch is the unicode code point of a wide character.

62 Class Documentation

Note

The following character ranges are treated as wide

```
1100..115F

2329..232A (just 2 characters!)

2E80..A4C6 except for 303F

A960..A97C

AC00..D7FB

F900..FAFF

FE10..FE6B

FF01..FF60

FFE0..FFE6

1B000.....
```

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.23 xmem::Runnable Class Reference

A base class for any object that implements a thread-safe run() function for use by Thread objects.

```
#include <Runnable.h>
```

Inheritance diagram for xmem::Runnable:

Public Member Functions

• Runnable ()

Constructor.

∼Runnable ()

Destructor.

• virtual void run ()=0

Does some "work". Pure virtual method that any derived class must implement in a thread-safe manner.

Protected Member Functions

• bool acquireLock (int32_t timeout)

Acquires the object lock to access all object state in thread-safe manner.

• bool releaseLock ()

Releases the object lock to access all object state in thread-safe manner.

5.23.1 Detailed Description

A base class for any object that implements a thread-safe run() function for use by Thread objects.

5.23.2 Member Function Documentation

```
5.23.2.1 bool Runnable::acquireLock(int32_t timeout) [protected]
```

Acquires the object lock to access all object state in thread-safe manner.

Parameters

timeout	timeout in milliseconds to acquire the lock. If 0, does not wait at all. If negative, waits indefi-
	nitely.

Returns

true on success. If not successful, the lock was not acquired, possibly due to a timeout, or the lock might already be held.

```
5.23.2.2 bool Runnable::releaseLock() [protected]
```

Releases the object lock to access all object state in thread-safe manner.

Returns

true on success. If not successful, the lock is either still held or the call was illegal (e.g., releasing a lock that was never acquired).

The documentation for this class was generated from the following files:

- src/include/Runnable.h
- src/Runnable.cpp

5.24 xmem::Stats Struct Reference

Determines the minimum lengths of the buffer and options arrays used for Parser.

```
#include <optionparser.h>
```

Classes

· class CountOptionsAction

Public Member Functions

· Stats ()

Creates a Stats object with counts set to 1 (for the sentinel element).

 Stats (bool gnu, const Descriptor usage[], int argc, const char **argv, int min_abbr_len=0, bool single_minus_ longopt=false)

Creates a new Stats object and immediately updates it for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options_max.

Stats (bool gnu, const Descriptor usage[], int argc, char **argv, int min_abbr_len=0, bool single_minus_longopt=false)

Stats(...) with non-const argv.

• Stats (const Descriptor usage[], int argc, const char **argv, int min_abbr_len=0, bool single_minus_longopt=false)

POSIX Stats(...) (gnu==false).

- Stats (const Descriptor usage[], int argc, char **argv, int min_abbr_len=0, bool single_minus_longopt=false)

 POSIX Stats(...) (gnu==false) with non-const argv.
- void add (bool gnu, const Descriptor usage[], int argc, const char **argv, int min_abbr_len=0, bool single_-minus_longopt=false)

64 Class Documentation

Updates this Stats object for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options max.

void add (bool gnu, const Descriptor usage[], int argc, char **argv, int min_abbr_len=0, bool single_minus_longopt=false)

add() with non-const argv.

void add (const Descriptor usage[], int argc, const char **argv, int min_abbr_len=0, bool single_minus_longopt=false)

POSIX add() (gnu==false).

• void add (const Descriptor usage[], int argc, char **argv, int min_abbr_len=0, bool single_minus_longopt=false)

POSIX add() (gnu==false) with non-const argv.

Public Attributes

unsigned buffer_max

Number of elements needed for a buffer[] array to be used for parsing the same argument vectors that were fed into this Stats object.

· unsigned options max

Number of elements needed for an options[] array to be used for parsing the same argument vectors that were fed into this Stats object.

5.24.1 Detailed Description

Determines the minimum lengths of the buffer and options arrays used for Parser.

Because Parser doesn't use dynamic memory its output arrays have to be pre-allocated. If you don't want to use fixed size arrays (which may turn out too small, causing command line arguments to be dropped), you can use Stats to determine the correct sizes. Stats work cumulative. You can first pass in your default options and then the real options and afterwards the counts will reflect the union.

5.24.2 Constructor & Destructor Documentation

5.24.2.1 xmem::Stats::Stats (bool gnu, const Descriptor usage[], int argc, const char ** argv, int min_abbr_len = 0, bool single_minus_longopt = false) [inline]

Creates a new Stats object and immediately updates it for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options_max.

Note

The calls to Stats methods must match the later calls to Parser methods. See Parser::parse() for the meaning of the arguments.

Here is the call graph for this function:

5.24.3 Member Function Documentation

5.24.3.1 void xmem::Stats::add (bool gnu, const Descriptor usage[], int argc, const char ** argv, int min_abbr_len = 0, bool single_minus_longopt = false) [inline]

Updates this Stats object for the given usage and argument vector. You may pass 0 for argc and/or argv, if you just want to update options_max.

Note

The calls to Stats methods must match the later calls to Parser methods. See Parser::parse() for the meaning of the arguments.

5.24.4 Member Data Documentation

5.24.4.1 unsigned xmem::Stats::buffer_max

Number of elements needed for a buffer[] array to be used for parsing the same argument vectors that were fed into this Stats object.

Note

This number is always 1 greater than the actual number needed, to give you a sentinel element.

5.24.4.2 unsigned xmem::Stats::options_max

Number of elements needed for an options[] array to be used for parsing the same argument vectors that were fed into this Stats object.

Note

- · This number is always 1 greater than the actual number needed, to give you a sentinel element.
- This number depends only on the usage, not the argument vectors, because the options array needs exactly one slot for each possible Descriptor::index.

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.25 xmem::Parser::StoreOptionAction Class Reference

Inheritance diagram for xmem::Parser::StoreOptionAction:

Collaboration diagram for xmem::Parser::StoreOptionAction:

Public Member Functions

StoreOptionAction (Parser &parser_, Option options_[], Option buffer_[], int bufmax_)

Number of slots in buffer. -1 means "large enough".

bool perform (Option & option)

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check_arg does not return ARG_ILLEGAL.

• bool finished (int numargs, const char **args)

Called by Parser::workhorse() after finishing the parse.

5.25.1 Constructor & Destructor Documentation

5.25.1.1 xmem::Parser::StoreOptionAction::StoreOptionAction (Parser & parser_, Option options_[], Option buffer_[], int bufmax_) [inline]

Number of slots in buffer. -1 means "large enough".

Creates a new StoreOption action.

66 Class Documentation

Parameters

parser_	the parser whose op_count should be updated.
options_	each Option o is chained into the linked list options_[o.desc->index]
buffer_	each Option is appended to this array as long as there's a free slot.
bufmax_	number of slots in buffer1 means "large enough".

5.25.2 Member Function Documentation

5.25.2.1 bool xmem::Parser::StoreOptionAction::finished (int numargs, const char ** args) [inline], [virtual]

Called by Parser::workhorse() after finishing the parse.

Parameters

numargs	the number of non-option arguments remaining
args	pointer to the first remaining non-option argument (if numargs $>$ 0).

Returns

false iff a fatal error has occurred.

Reimplemented from xmem::Parser::Action.

5.25.2.2 bool xmem::Parser::StoreOptionAction::perform(Option &) [inline], [virtual]

Called by Parser::workhorse() for each Option that has been successfully parsed (including unknown options if they have a Descriptor whose Descriptor::check_arg does not return ARG_ILLEGAL.

Returns false iff a fatal error has occured and the parse should be aborted.

Reimplemented from xmem::Parser::Action.

Here is the call graph for this function:

The documentation for this class was generated from the following file:

• src/include/optionparser.h

5.26 xmem::PrintUsageImplementation::StreamWriter< Function, Stream > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::StreamWriter< Function, Stream >:

Collaboration diagram for xmem::PrintUsageImplementation::StreamWriter< Function, Stream >:

Public Member Functions

- virtual void operator() (const char *str, int size)
 Writes the given number of chars beginning at the given pointer somewhere.
- StreamWriter (Function *w, Stream *s)

Public Attributes

- Function * fwrite
- Stream * stream

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.27 xmem::PrintUsageImplementation::SyscallWriter< Syscall > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::SyscallWriter< Syscall >: Collaboration diagram for xmem::PrintUsageImplementation::SyscallWriter< Syscall >:

Public Member Functions

- virtual void operator() (const char *str, int size)
 Writes the given number of chars beginning at the given pointer somewhere.
- SyscallWriter (Syscall *w, int f)

Public Attributes

- · Syscall * write
- · int fd

The documentation for this struct was generated from the following file:

• src/include/optionparser.h

5.28 xmem::PrintUsageImplementation::TemporaryWriter< Temporary > Struct Template Reference

Inheritance diagram for xmem::PrintUsageImplementation::TemporaryWriter< Temporary >: Collaboration diagram for xmem::PrintUsageImplementation::TemporaryWriter< Temporary >:

Public Member Functions

- virtual void operator() (const char *str, int size)
 Writes the given number of chars beginning at the given pointer somewhere.
- TemporaryWriter (const Temporary &u)

Public Attributes

• const Temporary & userstream

The documentation for this struct was generated from the following file:

· src/include/optionparser.h

68 Class Documentation

5.29 xmem::Thread Class Reference

a nice wrapped thread interface independent of particular OS API

```
#include <Thread.h>
```

Public Member Functions

- Thread (Runnable *target)
- ∼Thread ()
- bool create_and_start ()
- bool join ()
- bool cancel ()
- int32_t getExitCode ()
- bool started ()
- bool completed ()
- bool validTarget ()
- bool created ()
- bool isThreadSuspended ()
- bool isThreadRunning ()
- Runnable * getTarget ()

5.29.1 Detailed Description

a nice wrapped thread interface independent of particular OS API

5.29.2 Constructor & Destructor Documentation

```
5.29.2.1 Thread::Thread ( Runnable * target )
```

Constructor. Does not actually create the real thread or run it.

Parameters

target The target object to do some work with in a new thread.

```
5.29.2.2 Thread::\simThread ( )
```

Destructor. Immediately cancels the thread if it exists. This can be unsafe!

Here is the call graph for this function:

5.29.3 Member Function Documentation

```
5.29.3.1 bool Thread::cancel ( )
```

Cancels the worker thread immediately. This should only be done in emergencies, as it is effectively killed and undefined behavior might occur.

Returns

true if the worker thread was successfully killed.

```
5.29.3.2 bool Thread::completed ( )
```

Returns

true if the thread completed, regardless of the manner in which it terminated. Returns false if it has not been started.

```
5.29.3.3 bool Thread::create_and_start()
```

Creates and starts the thread immediately if the target Runnable is valid. This invokes the run() method in the Runnable target that was passed in the constructor.

Returns

true if the thread was successfully created and started.

```
5.29.3.4 bool Thread::created ( )
```

Returns

true if the thread has been created successfully.

```
5.29.3.5 int32_t Thread::getExitCode ( )
```

Returns

the exit code of the worker thread if it completed. If it did not complete or has not started, returns 0.

```
5.29.3.6 Runnable * Thread::getTarget ( )
```

Returns

a pointer to the target Runnable object

```
5.29.3.7 bool Thread::isThreadRunning ( )
```

Returns

true if the thread is running. Returns false if the thread has not been created.

```
5.29.3.8 bool Thread::isThreadSuspended ( )
```

Returns

true if the thread is suspended. Returns false if the thread has not been created.

```
5.29.3.9 bool Thread::join ( )
```

Blocks the calling thread until the worker thread managed by this object terminates. For simplicity, this does not support a timeout due to pthreads incompatibility with the Windows threading API. If the worker thread has already terminated, returns immediately. If the worker has not yet started, returns immediately.

Returns

true if the worker thread terminated successfully, false otherwise.

70 Class Documentation

```
5.29.3.10 bool Thread::started ( )
```

Returns

true if the thread has been started, regardless if has completed or not.

```
5.29.3.11 bool Thread::validTarget ( )
```

Returns

true if the Runnable target is valid.

The documentation for this class was generated from the following files:

- · src/include/Thread.h
- src/Thread.cpp

5.30 xmem::ThroughputBenchmark Class Reference

A type of benchmark that measures memory throughput.

```
#include <ThroughputBenchmark.h>
```

Inheritance diagram for xmem::ThroughputBenchmark:

Collaboration diagram for xmem::ThroughputBenchmark:

Public Member Functions

• ThroughputBenchmark (void *mem_array, size_t len, uint32_t iterations, uint32_t num_worker_threads, uint32_t mem_node, uint32_t cpu_node, pattern_mode_t pattern_mode, rw_mode_t rw_mode, chunk_size_t chunk_size, int32_t stride_size, std::vector< PowerReader * > dram_power_readers, std::string name)

Constructor. Parameters are passed directly to the Benchmark constructor. See Benchmark class documentation for parameter semantics.

• virtual \sim ThroughputBenchmark ()

Destructor.

Protected Member Functions

• virtual bool runCore ()

The core benchmark function.

Additional Inherited Members

5.30.1 Detailed Description

A type of benchmark that measures memory throughput.

5.30.2 Member Function Documentation

5.30.2.1 bool ThroughputBenchmark::runCore() [protected], [virtual]

The core benchmark function.

Returns

True on success.

Implements xmem::Benchmark.

Here is the call graph for this function:

The documentation for this class was generated from the following files:

- src/include/ThroughputBenchmark.h
- src/ThroughputBenchmark.cpp

5.31 xmem::Timer Class Reference

This class abstracts some characteristics of simple high resolution stopwatch timer. However, due to the inability or complexity of abstracting shared hardware timers, this class does not actually provide start and stop functions.

```
#include <Timer.h>
```

Public Member Functions

• Timer ()

Constructor. This may take a noticeable amount of time.

tick_t getTicksPerMs ()

Gets ticks per ms for this timer.

float getNsPerTick ()

Gets nanoseconds per tick for this timer.

Protected Attributes

- tick t ticks per ms
- float ns_per_tick_

5.31.1 Detailed Description

This class abstracts some characteristics of simple high resolution stopwatch timer. However, due to the inability or complexity of abstracting shared hardware timers, this class does not actually provide start and stop functions.

5.31.2 Member Function Documentation

```
5.31.2.1 float Timer::getNsPerTick ( )
```

Gets nanoseconds per tick for this timer.

Returns

the number of nanoseconds per tick

72 Class Documentation

```
5.31.2.2 tick_t Timer::getTicksPerMs ( )
```

Gets ticks per ms for this timer.

Returns

The reported number of ticks per ms.

5.31.3 Member Data Documentation

```
5.31.3.1 float xmem::Timer::ns_per_tick_ [protected]
```

Nanoseconds per tick for this timer.

```
5.31.3.2 tick_t xmem::Timer::ticks_per_ms_ [protected]
```

Ticks per ms for this timer.

The documentation for this class was generated from the following files:

- src/include/Timer.h
- src/Timer.cpp

Chapter 6

File Documentation

6.1 src/Benchmark.cpp File Reference

Implementation file for the Benchmark class.

```
#include <Benchmark.h>
#include <common.h>
#include <benchmark_kernels.h>
#include <PowerReader.h>
#include <cstdint>
#include <iostream>
#include <vector>
#include <map>
#include <algorithm>
#include <time.h>
Include dependency graph for Benchmark.cpp:
```

6.1.1 Detailed Description

Implementation file for the Benchmark class.

6.2 src/benchmark_kernels.cpp File Reference

Implementation file for benchmark kernel functions for doing the actual work we care about. :)

```
#include <benchmark_kernels.h>
#include <common.h>
#include <iostream>
#include <random>
#include <algorithm>
#include <time.h>
```

Include dependency graph for benchmark_kernels.cpp:

6.2.1 Detailed Description

Implementation file for benchmark kernel functions for doing the actual work we care about. :) Optimization tricks include:

• UNROLL macros to manual loop unrolling. This reduces the relative branch overhead of the loop. We don't want to benchmark loops, we want to benchmark memory! But unrolling too much can hurt code size and

instruction locality, potentially decreasing I-cache utilization and causing extra overheads. This is why we allow multiple unroll lengths at compile-time.

· volatile keyword to prevent compiler from optimizing the code and removing instructions that we need. The compiler is too smart for its own good!

6.3 src/BenchmarkManager.cpp File Reference

Implementation file for the BenchmarkManager class.

```
#include <BenchmarkManager.h>
#include <common.h>
#include <Configurator.h>
#include <cstdint>
#include <stdlib.h>
#include <iostream>
#include <sstream>
#include <assert.h>
```

Include dependency graph for BenchmarkManager.cpp:

6.3.1 **Detailed Description**

Implementation file for the BenchmarkManager class.

src/common.cpp File Reference

Implementation file for common preprocessor definitions, macros, functions, and global constants.

```
#include <common.h>
#include <Timer.h>
#include <iostream>
#include <vector>
```

Include dependency graph for common.cpp:

Variables

```
• bool xmem::g_verbose = false
    *typedef union {
size_t xmem::g_page_size
• size_t xmem::g_large_page_size
• uint32_t xmem::g_num_numa_nodes
· uint32 t xmem::g num logical cpus
uint32_t xmem::g_num_physical_cpus
uint32_t xmem::g_num_physical_packages
• uint32_t xmem::g_total_l1_caches
• uint32 t xmem::g total I2 caches
• uint32 t xmem::g total I3 caches
• uint32_t xmem::g_total_l4_caches
uint32_t xmem::g_starting_test_index
• uint32_t xmem::g_test_index
tick_t xmem::g_ticks_per_ms
```

float xmem::g ns per tick

6.4.1 Detailed Description

Implementation file for common preprocessor definitions, macros, functions, and global constants.

6.5 src/Configurator.cpp File Reference

Implementation file for the Configurator class and some helper data structures.

```
#include <Configurator.h>
#include <common.h>
#include <optionparser.h>
#include <MyArg.h>
#include <cstdint>
#include <iostream>
#include <string>
```

Include dependency graph for Configurator.cpp:

6.5.1 Detailed Description

Implementation file for the Configurator class and some helper data structures.

6.6 src/ext/DelayInjectedLoadedLatencyBenchmark/delay_injected_benchmark_kernels.cpp File Reference

Implementation file for benchmark kernel functions for the delay-injected loaded latency benchmark.

```
#include <delay_injected_benchmark_kernels.h>
#include <common.h>
#include <iostream>
```

Include dependency graph for delay_injected_benchmark_kernels.cpp:

6.6.1 Detailed Description

Implementation file for benchmark kernel functions for the delay-injected loaded latency benchmark. Optimization tricks include:

- UNROLL macros to manual loop unrolling. This reduces the relative branch overhead of the loop. We don't
 want to benchmark loops, we want to benchmark memory! But unrolling too much can hurt code size and
 instruction locality, potentially decreasing I-cache utilization and causing extra overheads. This is why we
 allow multiple unroll lengths at compile-time.
- volatile keyword to prevent compiler from optimizing the code and removing instructions that we need. The compiler is too smart for its own good!

6.7 src/ext/DelayInjectedLoadedLatencyBenchmark/DelayInjectedLoadedLatencyBenchmark.cpp File Reference

Implementation file for the DelayInjectedLatencyBenchmark class.

```
#include <common.h>
```

Include dependency graph for DelayInjectedLoadedLatencyBenchmark.cpp:

6.7.1 Detailed Description

Implementation file for the DelayInjectedLatencyBenchmark class.

6.8 src/include/Benchmark.h File Reference

Header file for the Benchmark class.

```
#include <common.h>
#include <PowerReader.h>
#include <Thread.h>
#include <Runnable.h>
#include <cstdint>
#include <string>
#include <vector>
```

Include dependency graph for Benchmark.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::Benchmark

Flexible abstract class for any memory benchmark.

6.8.1 Detailed Description

Header file for the Benchmark class.

6.9 src/include/benchmark kernels.h File Reference

Header file for benchmark kernel functions for doing the actual work we care about. :)

```
#include <common.h>
#include <cstdint>
#include <cstddef>
```

Include dependency graph for benchmark_kernels.h: This graph shows which files directly or indirectly include this file:

Typedefs

- typedef int32_t(* xmem::SequentialFunction)(void *, void *)
- typedef int32_t(* xmem::RandomFunction)(uintptr_t *, uintptr_t **, size_t)

Functions

 bool xmem::determine_sequential_kernel (rw_mode_t rw_mode, chunk_size_t chunk_size, int32_t stridesize, SequentialFunction *kernel_function, SequentialFunction *dummy_kernel_function)

Determines which sequential memory access kernel to use based on the read/write mode, chunk size, and stride size.

• bool **xmem::determine_random_kernel** (rw_mode_t rw_mode, chunk_size_t chunk_size, RandomFunction *kernel function, RandomFunction *dummy kernel function)

Determines which random memory access kernel to use based on the read/write mode, chunk size, and stride size.

bool xmem::build_random_pointer_permutation (void *start_address, void *end_address, chunk_size_t chunk_size)

Builds a random chain of pointers within the specified memory region.

• int32_t xmem::dummy_chasePointers (uintptr_t *, uintptr_t **, size_t len)

Mimics the chasePointers() method but doesn't do the memory accesses.

• int32 t xmem::chasePointers (uintptr t *first address, uintptr t **last touched address, size t len)

Walks over the allocated memory in random order by chasing pointers.

int32 t xmem::dummy_empty (void *, void *)

Does nothing. Used for measuring the time it takes just to call a benchmark routine via function pointer.

• int32_t xmem::dummy_forwSequentialLoop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in forward sequential Word 32 loops except for the memory access itself

• int32_t xmem::dummy_revSequentialLoop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in reverse sequential Word 32 loops except for the memory access itself.

• int32 t xmem::dummy forwStride2Loop Word32 (void *start address, void *end address)

Used for measuring the time spent doing everything in forward 2-strided Word 32 loops except for the memory access itself.

• int32_t xmem::dummy_revStride2Loop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in reverse 2-strided Word 32 loops except for the memory access itself.

int32_t xmem::dummy_forwStride4Loop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in forward 4-strided Word 32 loops except for the memory access itself

• int32_t xmem::dummy_revStride4Loop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in reverse 4-strided Word 32 loops except for the memory access itself

• int32 t xmem::dummy forwStride8Loop Word32 (void *start address, void *end address)

Used for measuring the time spent doing everything in forward 8-strided Word 32 loops except for the memory access itself.

int32_t xmem::dummy_revStride8Loop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in reverse 8-strided Word 32 loops except for the memory access itself.

• int32_t xmem::dummy_forwStride16Loop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in forward 16-strided Word 32 loops except for the memory

• int32_t xmem::dummy_revStride16Loop_Word32 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in reverse 16-strided Word 32 loops except for the memory access itself.

• int32_t xmem::dummy_randomLoop_Word32 (uintptr_t *, uintptr_t **, size_t len)

Mimics the randomRead Word32 and randomWrite Word32 functions except for the memory accesses.

• int32 t xmem::forwSequentialRead Word32 (void *start address, void *end address)

Walks over the allocated memory forward sequentially, reading in 32-bit chunks.

• int32_t xmem::revSequentialRead_Word32 (void *start_address, void *end_address)

Walks over the allocated memory reverse sequentially, reading in 32-bit chunks.

• int32 t xmem::forwSequentialWrite Word32 (void *start address, void *end address)

Walks over the allocated memory forward sequentially, writing in 32-bit chunks.

• int32_t xmem::revSequentialWrite_Word32 (void *start_address, void *end_address)

Walks over the allocated memory reverse sequentially, writing in 32-bit chunks.

• int32_t xmem::forwStride2Read_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in forward strides of size 2, reading in 32-bit chunks.

int32 t xmem::revStride2Read Word32 (void *start address, void *end address)

Walks over the allocated memory in reverse strides of size 2, reading in 32-bit chunks.

• int32 t xmem::forwStride2Write Word32 (void *start address, void *end address)

Walks over the allocated memory in forward strides of size 2, writing in 32-bit chunks.

• int32_t xmem::revStride2Write_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in reverse strides of size 2, writing in 32-bit chunks.

• int32_t xmem::forwStride4Read_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in forward strides of size 4, reading in 32-bit chunks.

• int32_t xmem::revStride4Read_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in reverse strides of size 4, reading in 32-bit chunks.

• int32_t xmem::forwStride4Write_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in forward strides of size 4, writing in 32-bit chunks.

• int32_t xmem::revStride4Write_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in reverse strides of size 4, writing in 32-bit chunks.

• int32_t xmem::forwStride8Read_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in forward strides of size 8, reading in 32-bit chunks.

• int32_t xmem::revStride8Read_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in reverse strides of size 8, reading in 32-bit chunks.

int32_t xmem::forwStride8Write_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in forward strides of size 8, writing in 32-bit chunks.

int32_t xmem::revStride8Write_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in reverse strides of size 8, writing in 32-bit chunks.

int32_t xmem::forwStride16Read_Word32 (void *start_address, void *end_address)

Walks over the allocated memory in forward strides of size 16, reading in 32-bit chunks.

• int32 t xmem::revStride16Read Word32 (void *start address, void *end address)

Walks over the allocated memory in reverse strides of size 16, reading in 32-bit chunks.

• int32_t xmem::forwStride16Write_Word32 (void *start_address, void *end_address)

mio__t xmomor void do Townio_morada (void wotart_dadaroos, void world_dadaroo

Walks over the allocated memory in forward strides of size 16, writing in 32-bit chunks.

• int32_t xmem::revStride16Write_Word32 (void *start_address, void *end_address)

z_t x...o.....ovotilao loviito_volao t (vola wotat t_aaarooo, vola wota _aaaroo

Walks over the allocated memory in reverse strides of size 16, writing in 32-bit chunks.

int32_t xmem::randomRead_Word32 (uintptr_t *first_address, uintptr_t **last_touched_address, size_t len)

Walks over the allocated memory in random order by chasing 64-bit pointers.

• int32_t xmem::randomWrite_Word32 (uintptr_t *first_address, uintptr_t **last_touched_address, size_-t len)

Walks over the allocated memory in random order by chasing 32-bit pointers. A pointer is read and written back with the same value before chasing to the next pointer. Thus, each memory address is a read followed by immediate write operation.

6.9.1 Detailed Description

Header file for benchmark kernel functions for doing the actual work we care about. :)

6.10 src/include/BenchmarkManager.h File Reference

Header file for the BenchmarkManager class.

```
#include <common.h>
#include <Timer.h>
#include <PowerReader.h>
#include <Benchmark.h>
#include <ThroughputBenchmark.h>
#include <LatencyBenchmark.h>
#include <Configurator.h>
#include <cstdint>
#include <vector>
#include <fstream>
```

Include dependency graph for BenchmarkManager.h: This graph shows which files directly or indirectly include this

file:

Classes

· class xmem::BenchmarkManager

Manages running all benchmarks at a high level.

6.10.1 Detailed Description

Header file for the BenchmarkManager class.

6.11 src/include/common.h File Reference

Header file for common preprocessor definitions, macros, functions, and global constants.

```
#include <cstdint>
#include <cstddef>
```

Include dependency graph for common.h: This graph shows which files directly or indirectly include this file:

Macros

- #define **VERSION** "2.4.0"
- #define KB 1024
- #define MB 1048576
- #define MB 4 4194304
- #define MB_16 16777216
- #define MB 64 67108864
- #define MB 256 268435456
- #define MB 512 536870912
- #define **GB** 1073741824
- #define DEFAULT_PAGE_SIZE 4*KB
- #define DEFAULT_LARGE_PAGE_SIZE 2*MB
- #define DEFAULT_WORKING_SET_SIZE_PER_THREAD DEFAULT_PAGE_SIZE
- #define DEFAULT_NUM_WORKER_THREADS 1
- #define DEFAULT NUM NODES 0
- #define DEFAULT_NUM_PHYSICAL_PACKAGES 0
- #define DEFAULT_NUM_PHYSICAL_CPUS 0
- #define DEFAULT NUM LOGICAL CPUS 0
- #define DEFAULT NUM L1 CACHES 0
- #define DEFAULT NUM L2 CACHES 0
- #define DEFAULT_NUM_L3_CACHES 0
- #define DEFAULT_NUM_L4_CACHES 0
- #define MIN_ELAPSED_TICKS 10000
- #define UNROLL2(x) x x
- #define **UNROLL4**(x) UNROLL2(x) UNROLL2(x)
- #define UNROLL8(x) UNROLL4(x) UNROLL4(x)
- #define **UNROLL16**(x) UNROLL8(x) UNROLL8(x)
- #define UNROLL32(x) UNROLL16(x) UNROLL16(x)
- #define UNROLL64(x) UNROLL32(x) UNROLL32(x)
- #define **UNROLL128**(x) UNROLL64(x) UNROLL64(x)
- #define UNROLL256(x) UNROLL128(x) UNROLL128(x)
- #define UNROLL512(x) UNROLL256(x) UNROLL256(x)

- #define UNROLL1024(x) UNROLL512(x) UNROLL512(x)
- #define UNROLL2048(x) UNROLL1024(x) UNROLL1024(x)
- #define UNROLL4096(x) UNROLL2048(x) UNROLL2048(x)
- #define **UNROLL8192**(x) UNROLL4096(x) UNROLL4096(x)
- #define UNROLL16384(x) UNROLL8192(x) UNROLL8192(x)
- #define UNROLL32768(x) UNROLL16384(x) UNROLL16384(x)
- #define UNROLL65536(x) UNROLL32768(x) UNROLL32768(x)
- #define LATENCY BENCHMARK UNROLL LENGTH 512
- #define USE OS TIMER
- #define BENCHMARK DURATION MS 5000
- #define THROUGHPUT BENCHMARK BYTES PER PASS 4096
- #define POWER SAMPLING PERIOD MS 1000
- #define EXT_DELAY_INJECTED_LOADED_LATENCY_BENCHMARK

Typedefs

- typedef uint64 t xmem::tick t
- · typedef uint32_t xmem::Word32_t

Enumerations

enum pattern_mode_t { SEQUENTIAL, RANDOM, NUM_PATTERN_MODES }

Memory access patterns are broadly categorized by sequential or random-access.

enum rw_mode_t { READ, WRITE, NUM_RW_MODES }

Memory access batterns are broadly categorized by reads and writes.

enum chunk_size_t { CHUNK_32b, NUM_CHUNK_SIZES }

Legal memory read/write chunk sizes in bits.

• enum ext_t { EXT_NUM_DELAY_INJECTED_LOADED_LATENCY_BENCHMARK, NUM_EXTENSIONS }

Functions

• void xmem::print_welcome_message ()

Prints a basic welcome message to the console with useful information.

void xmem::print_types_report ()

Prints the various C/C++ types to the console for this machine.

void xmem::print_compile_time_options ()

Prints compile-time option information to the console.

void xmem::setup_timer()

Initializes the timer and outputs results to the console for sanity checking.

void xmem::report_timer ()

Reports timer info to the console.

void xmem::test_thread_affinities ()

Checks to see if the calling thread can be locked to all logical CPUs in the system, and reports to the console the progress.

• bool xmem::lock thread to numa node (uint32 t numa node)

Sets the affinity of the calling thread to any of the CPUs in the NUMA node.

bool xmem::unlock_thread_to_numa_node ()

Clears the affinity of the calling thread to any given NUMA node.

bool xmem::lock_thread_to_cpu (uint32_t cpu_id)

Sets the affinity of the calling thread to a given logical CPU.

bool xmem::unlock_thread_to_cpu ()

Clears the affinity of the calling thread to any given logical CPU.

• int32_t xmem::cpu_id_in_numa_node (uint32_t numa_node, uint32_t cpu_in_node)

Gets the CPU ID for a logical CPU of interest in a particular NUMA node. For example, if numa_node is 1 and cpu_-in_node is 2, and there are 4 logical CPUs per node, then this will give the answer 6 (6th CPU), assuming CPU IDs start at 0.

size_t xmem::compute_number_of_passes (size_t working_set_size_KB)

Computes the number of passes to use for a given working set size in KB, when size-based benchmarking mode is enabled at compile-time. You may want to change this implementation to suit your needs. See the compile-time options in common.h.

bool xmem::config page size ()

Queries the page sizes from the system and sets relevant global variables.

• void xmem::init globals ()

Initializes useful global variables.

int32_t xmem::query_sys_info ()

Sets up global variables based on system information at runtime.

void xmem::report_sys_info ()

Reports the system configuration to the console as indicated by global variables.

tick t xmem::start_timer ()

Query the timer for the start of a timed section of code.

tick_t xmem::stop_timer ()

Query the timer for the end of a timed section of code.

6.11.1 Detailed Description

Header file for common preprocessor definitions, macros, functions, and global constants.

6.11.2 Macro Definition Documentation

6.11.2.1 #define BENCHMARK_DURATION_MS 5000

RECOMMENDED VALUE: At least 250. Number of milliseconds to run in each benchmark.

6.11.2.2 #define DEFAULT_LARGE_PAGE_SIZE 2*MB

Default platform large page size in bytes. This generally should not be relied on, but is a failsafe.

6.11.2.3 #define DEFAULT_NUM_L1_CACHES 0

Default number of L1 caches.

6.11.2.4 #define DEFAULT_NUM_L2_CACHES 0

Default number of L2 caches.

6.11.2.5 #define DEFAULT_NUM_L3_CACHES 0

Default number of L3 caches.

6.11.2.6 #define DEFAULT_NUM_L4_CACHES 0

Default number of L4 caches.

6.11.2.7 #define DEFAULT_NUM_LOGICAL_CPUS 0

Default number of logical CPU cores.

6.11.2.8 #define DEFAULT NUM NODES 0

Default number of NUMA nodes.

6.11.2.9 #define DEFAULT_NUM_PHYSICAL_CPUS 0

Default number of physical CPU cores.

6.11.2.10 #define DEFAULT_NUM_PHYSICAL_PACKAGES 0

Default number of physical packages.

6.11.2.11 #define DEFAULT_NUM_WORKER_THREADS 1

Default number of worker threads to use.

6.11.2.12 #define DEFAULT_PAGE_SIZE 4*KB

Default platform page size in bytes. This generally should not be relied on, but is a failsafe.

6.11.2.13 #define DEFAULT_WORKING_SET_SIZE_PER_THREAD DEFAULT_PAGE_SIZE

Default working set size in bytes.

6.11.2.14 #define EXT_DELAY_INJECTED_LOADED_LATENCY_BENCHMARK

RECOMMENDED ENABLED. This allows for a custom extension to X-Mem that performs latency benchmarking with forward sequential 64-bit and 256-bit read-based load threads with variable delays injected in between memory accesses.

6.11.2.15 #define LATENCY_BENCHMARK_UNROLL_LENGTH 512

Number of unrolls in the latency benchmark pointer chasing core function.

6.11.2.16 #define MIN_ELAPSED_TICKS 10000

If any routine measured fewer than this number of ticks its results should be viewed with suspicion. This is because the latency of the timer itself will matter.

6.11.2.17 #define POWER_SAMPLING_PERIOD_MS 1000

RECOMMENDED VALUE: 1000. Sampling period in milliseconds for all power measurement mechanisms.

6.11.2.18 #define THROUGHPUT_BENCHMARK_BYTES_PER_PASS 4096

RECOMMENDED VALUE: 4096. Number of bytes read or written per pass of any ThroughputBenchmark. This must be less than or equal to the minimum working set size, which is currently 4 KB.

```
6.11.2.19 #define USE_OS_TIMER
```

RECOMMENDED ENABLED. If enabled, uses the QPC timer on Windows and the POSIX clock_gettime() on GN-U/Linux for all timing purposes.

6.12 src/include/Configurator.h File Reference

Header file for the Configurator class and some helper data structures.

```
#include <common.h>
#include <optionparser.h>
#include <MyArg.h>
#include <cstdint>
#include <string>
#include <list>
```

Include dependency graph for Configurator.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::Configurator

Handles all user input interpretation and generates the necessary flags for running benchmarks.

Enumerations

enum optionIndex {
 UNKNOWN, ALL, CHUNK_SIZE, EXTENSION,
 OUTPUT_FILE, HELP, BASE_TEST_INDEX, NUM_WORKER_THREADS,
 MEAS_LATENCY, ITERATIONS, RANDOM_ACCESS_PATTERN, SEQUENTIAL_ACCESS_PATTERN,
 MEAS_THROUGHPUT, NUMA_DISABLE, VERBOSE, WORKING_SET_SIZE_PER_THREAD,
 CPU_NUMA_NODE_AFFINITY, USE_LARGE_PAGES, MEMORY_NUMA_NODE_AFFINITY, USE_READS,
 USE_WRITES, STRIDE_SIZE }

Enumerates all possible types of command-line options.

Variables

• const Descriptor xmem::usage []

Command-line option descriptors as needed by stuff in optionparser.h>. This is basically the help message content.

6.12.1 Detailed Description

Header file for the Configurator class and some helper data structures.

6.13 src/include/ExampleArg.h File Reference

Slightly-modified third-party code related to OptionParser.

```
#include <optionparser.h>
#include <cstdint>
#include <stdio.h>
```

Include dependency graph for ExampleArg.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::ExampleArg

6.13.1 Detailed Description

Slightly-modified third-party code related to OptionParser.

6.14 src/include/ext/DelayInjectedLoadedLatencyBenchmark/delay_injected_benchmark-_kernels.h File Reference

Header file for benchmark kernel functions with integrated delays for doing the actual work we care about. :)

```
#include <common.h>
#include <cstdint>
```

Include dependency graph for delay_injected_benchmark_kernels.h: This graph shows which files directly or indirectly include this file:

Macros

- #define my_nop2() my_nop(); my_nop()
- #define **my_nop4**() my_nop2(); my_nop2()
- #define my_nop8() my_nop4(); my_nop4()
- #define my_nop16() my_nop8(); my_nop8()
- #define my_nop32() my_nop16(); my_nop16()
- #define my_nop64() my_nop32(); my_nop32()
- #define **my_nop128**() my_nop64(); my_nop64()
- #define my nop256() my nop128(); my nop128()
- #define my_nop512() my_nop256(); my_nop256()
- #define my_nop1024() my_nop512(); my_nop512()

Functions

- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay1 (void *start_address, void *end_address)

 Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.
- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay2 (void *start_address, void *end_address)
 Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.
- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay4 (void *start_address, void *end_address)

 Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.
- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay8 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.

- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay16 (void *start_address, void *end_address)

 Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.
- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay32 (void *start_address, void *end_address)

 Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.
- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay64 (void *start_address, void *end_address)

 Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.
- int32_t xmem::dummy_forwSequentialLoop_Word32_Delay128 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.

int32_t xmem::dummy_forwSequentialLoop_Word32_Delay256 (void *start_address, void *end_address)

Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.

int32_t xmem::dummy_forwSequentialLoop_Word32_Delay512plus (void *start_address, void *end_address)

Used for measuring the time spent doing everything in delay-injected forward sequential Word 32 loops except for the memory access and delays themselves.

- int32_t xmem::forwSequentialRead_Word32_Delay1 (void *start_address, void *end_address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 1 delays (nops) are inserted between memory instructions.
- int32_t xmem::forwSequentialRead_Word32_Delay2 (void *start_address, void *end_address)

Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 2 delays (nops) are inserted between memory instructions.

- int32_t xmem::forwSequentialRead_Word32_Delay4 (void *start_address, void *end_address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 4 delays (nops) are inserted between memory instructions.
- int32_t xmem::forwSequentialRead_Word32_Delay8 (void *start_address, void *end_address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 8 delays (nops) are inserted between memory instructions.
- int32 t xmem::forwSequentialRead Word32 Delay16 (void *start address, void *end address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 16 delays (nops) are inserted between memory instructions.
- int32_t xmem::forwSequentialRead_Word32_Delay32 (void *start_address, void *end_address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 32 delays (nops) are inserted between memory instructions.
- int32 t xmem::forwSequentialRead Word32 Delay64 (void *start address, void *end address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 64 delays (nops) are inserted between memory instructions.
- int32_t xmem::forwSequentialRead_Word32_Delay128 (void *start_address, void *end_address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 128 delays (nops) are inserted between memory instructions.
- $\bullet \ \ int 32_t \ \textbf{xmem::} for w \textbf{SequentialRead_Word32_Delay256} \ (void *start_address, void *end_address)$
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 256 delays (nops) are inserted between memory instructions.
- int32_t xmem::forwSequentialRead_Word32_Delay512 (void *start_address, void *end_address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 512 delays (nops) are inserted between memory instructions.
- int32 t xmem::forwSequentialRead Word32 Delay1024 (void *start address, void *end address)
 - Walks over the allocated memory forward sequentially, reading in 32-bit chunks. 1024 delays (nops) are inserted between memory instructions.

6.14.1 Detailed Description

Header file for benchmark kernel functions with integrated delays for doing the actual work we care about. :)

6.15 src/include/ext/DelayInjectedLoadedLatencyBenchmark/DelayInjectedLoaded-LatencyBenchmark.h File Reference

Header file for the DelayInjectedLoadedLatencyBenchmark class.

6.15.1 Detailed Description

 $Header \ file \ for \ the \ DelayInjected Loaded Latency Benchmark \ class.$

6.16 src/include/LatencyBenchmark.h File Reference

Header file for the LatencyBenchmark class.

```
#include <Benchmark.h>
#include <common.h>
#include <cstdint>
#include <string>
```

Include dependency graph for LatencyBenchmark.h: This graph shows which files directly or indirectly include this file:

Classes

class xmem::LatencyBenchmark

A type of benchmark that measures memory latency via random pointer chasing. Loading may be provided with separate threads which access memory as quickly as possible using given access patterns.

6.16.1 Detailed Description

Header file for the LatencyBenchmark class.

6.17 src/include/LatencyWorker.h File Reference

Header file for the LatencyWorker class.

```
#include <MemoryWorker.h>
#include <benchmark_kernels.h>
#include <common.h>
```

Include dependency graph for LatencyWorker.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::LatencyWorker

Multithreading-friendly class to do memory loading.

6.17.1 Detailed Description

Header file for the LatencyWorker class.

6.18 src/include/LoadWorker.h File Reference

Header file for the LoadWorker class.

```
#include <MemoryWorker.h>
#include <benchmark kernels.h>
```

Include dependency graph for LoadWorker.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::LoadWorker

Multithreading-friendly class to do memory loading.

6.18.1 Detailed Description

Header file for the LoadWorker class.

6.19 src/include/MemoryWorker.h File Reference

Header file for the MemoryWorker class.

```
#include <common.h>
#include <Runnable.h>
#include <cstdint>
```

Include dependency graph for MemoryWorker.h: This graph shows which files directly or indirectly include this file:

Classes

class xmem::MemoryWorker

Multithreading-friendly class to run memory access kernels.

6.19.1 Detailed Description

Header file for the MemoryWorker class.

6.20 src/include/MyArg.h File Reference

Extensions to third-party optionparser-related code.

```
#include <ExampleArg.h>
#include <cstdint>
#include <stdio.h>
#include <cstdlib>
```

Include dependency graph for MyArg.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::MyArg

6.20.1 Detailed Description

Extensions to third-party optionparser-related code.

6.21 src/include/optionparser.h File Reference

This is the only file required to use The Lean Mean C++ Option Parser. Just #include it and you're set.

This graph shows which files directly or indirectly include this file:

Classes

• struct xmem::Descriptor

Describes an option, its help text (usage) and how it should be parsed.

· class xmem::Option

A parsed option from the command line together with its argument if it has one.

struct xmem::Arg

Functions for checking the validity of option arguments.

struct xmem::Stats

Determines the minimum lengths of the buffer and options arrays used for Parser.

class xmem::Parser

Checks argument vectors for validity and parses them into data structures that are easier to work with.

- struct xmem::Parser::Action
- · class xmem::Stats::CountOptionsAction
- class xmem::Parser::StoreOptionAction
- struct xmem::PrintUsageImplementation
- struct xmem::PrintUsageImplementation::IStringWriter
- struct xmem::PrintUsageImplementation::FunctionWriter< Function >
- struct xmem::PrintUsageImplementation::OStreamWriter< OStream >
- struct xmem::PrintUsageImplementation::TemporaryWriter< Temporary >
- struct xmem::PrintUsageImplementation::SyscallWriter< Syscall >
- struct xmem::PrintUsageImplementation::StreamWriter< Function, Stream >
- · class xmem::PrintUsageImplementation::LinePartIterator
- · class xmem::PrintUsageImplementation::LineWrapper

Typedefs

• typedef ArgStatus(* xmem::CheckArg)(const Option &option, bool msg)

Signature of functions that check if an argument is valid for a certain type of option.

Enumerations

enum ArgStatus { xmem::ARG_NONE, xmem::ARG_OK, xmem::ARG_IGNORE, xmem::ARG_ILLEGAL

Possible results when checking if an argument is valid for a certain option.

Functions

template<typename OStream >

void **xmem::printUsage** (OStream &prn, const Descriptor usage[], int width=80, int last_column_min_percent=50, int last_column_own_line_max_percent=75)

Outputs a nicely formatted usage string with support for multi-column formatting and line-wrapping.

template<typename Function >

void **xmem::printUsage** (Function *prn, const Descriptor usage[], int width=80, int last_column_min_percent=50, int last_column_own_line_max_percent=75)

• template<typename Temporary >

void **xmem::printUsage** (const Temporary &prn, const Descriptor usage[], int width=80, int last_column_-min_percent=50, int last_column_own_line_max_percent=75)

template<typename Syscall >

void **xmem::printUsage** (Syscall *prn, int fd, const Descriptor usage[], int width=80, int last_column_min_percent=50, int last_column_own_line_max_percent=75)

template<typename Function, typename Stream >
 void xmem::printUsage (Function *prn, Stream *stream, const Descriptor usage[], int width=80, int last_column min percent=50, int last column own line max percent=75)

6.21.1 Detailed Description

This is the only file required to use The Lean Mean C++ Option Parser. Just #include it and you're set. The Lean Mean C++ Option Parser handles the program's command line arguments (argc, argv). It supports the short and long option formats of getopt(), getopt_long() and getopt_long_only() but has a more convenient interface. The following features set it apart from other option parsers:

Highlights:

- It is a header-only library. Just #include "optionparser.h" and you're set.
- It is freestanding. There are no dependencies whatsoever, not even the C or C++ standard library.
- It has a usage message formatter that supports column alignment and line wrapping. This aids localization because it adapts to translated strings that are shorter or longer (even if they contain Asian wide characters).
- Unlike getopt() and derivatives it doesn't force you to loop through options sequentially. Instead you can access options directly like this:
 - Test for presence of a switch in the argument vector:

```
if ( options[QUIET] ) ...
```

- Evaluate -enable-foo/-disable-foo pair where the last one used wins:

```
if ( options[FOO].last()->type() == DISABLE ) ...
```

- Cumulative option (-v verbose, -vv more verbose, -vvv even more verbose):

```
int verbosity = options[VERBOSE].count();
```

– Iterate over all –file=<fname> arguments:

```
for (Option* opt = options[FILE]; opt; opt = opt->next())
fname = opt->arg; ...
```

– If you really want to, you can still process all arguments in order:

```
for (int i = 0; i < p.optionsCount(); ++i) {
  Option& opt = buffer[i];
  switch(opt.index()) {
    case HELP:
        case VERBOSE: ...
    case FILE:        fname = opt.arg; ...
    case UNKNOWN: ...</pre>
```

Despite these features the code size remains tiny. It is smaller than uClibc's GNU getopt() and just a couple 100 bytes larger than uClibc's SUSv3 getopt().

(This does not include the usage formatter, of course. But you don't have to use that.)

Download:

```
Tarball with examples and test programs: optionparser-1.3.tar.gz Just the header (this is all you really need): optionparser.h
```

Changelog:

Version 1.3: Compatible with Microsoft Visual C++.

Version 1.2: Added Option::namelen and removed the extraction of short option characters into a special buffer.

Changed Arg::Optional to accept arguments if they are attached rather than separate. This is what GNU getopt() does and how POSIX recommends utilities should interpret their arguments.

Version 1.1: Optional mode with argument reordering as done by GNU getopt(), so that options and non-options can be mixed. See Parser::parse().

Feedback:

Send questions, bug reports, feature requests etc. to: optionparser-feedback (a) lists.-sourceforge.net

Example program:

(Note: option::* identifiers are links that take you to their documentation.)

```
#include <iostream>
#include "optionparser.h"
enum optionIndex { UNKNOWN, HELP, PLUS };
const option::Descriptor usage[]
                           ,option::Arg::None, "USAGE: example [options]\n\n"
 {UNKNOWN, 0,"", ""
                                                  "Options:"
 {HELP, 0,"", "help",option::Arg::None, " --help \tPrint usage and exit."}, {PLUS, 0,"p", "plus",option::Arg::None, " --plus, -p \tIncrement count."}, {UNKNOWN, 0,"", "",option::Arg::None, "\nExamples:\n"
                        example --unknown -- --this_is_no_option\n"
                                                  " example -unk --plus -ppp file1 file2\n"},
 {0,0,0,0,0,0}
};
int main(int argc, char* argv[])
  argc-=(argc>0); argv+=(argc>0); // skip program name argv[0] if present
 option::Stats stats(usage, argc, argv);
option::Option options[stats.options_max], buffer[stats.buffer_max];
  option::Parser parse(usage, argc, argv, options, buffer);
  if (parse.error())
    return 1:
  if (options[HELP] || argc == 0) {
   option::printUsage(std::cout, usage);
  std::cout << "--plus count: " <<
    options[PLUS].count() << "\n";
  for (option::Option* opt = options[UNKNOWN]; opt; opt = opt->next())
    std::cout << "Unknown option: " << opt->name << "\n";
  for (int i = 0; i < parse.nonOptionsCount(); ++i) std::cout << "Non-option #" << i << ": " << parse.nonOption(i) << "\n";
```

Option syntax:

- The Lean Mean C++ Option Parser follows POSIX getopt() conventions and supports GNU-style getopt_long() long options as well as Perl-style single-minus long options (getopt_long_-only()).
- short options have the format -X where X is any character that fits in a char.
- short options can be grouped, i.e. -X -Y is equivalent to -XY.
- a short option may take an argument either separate (-X foo) or attached (-Xfoo). You can make the parser accept the additional format -X=foo by registering X as a long option (in addition to being a short option) and enabling single-minus long options.
- an argument-taking short option may be grouped if it is the last in the group, e.g. -ABCXfoo or -ABCX foo (foo is the argument to the -X option).

- a lone minus character '-' is not treated as an option. It is customarily used where a file name is expected to refer to stdin or stdout.
- long options have the format -option-name.
- the option-name of a long option can be anything and include any characters. Even = characters will work, but don't do that.
- [optional] long options may be abbreviated as long as the abbreviation is unambiguous. You can set a minimum length for abbreviations.
- [optional] long options may begin with a single minus. The double minus form is always accepted, too.
- a long option may take an argument either separate (-option arg) or attached (-option=arg). In the attached form the equals sign is mandatory.
- an empty string can be passed as an attached long option argument: -option-name= . Note the distinction between an empty string as argument and no argument at all.
- an empty string is permitted as separate argument to both long and short options.
- Arguments to both short and long options may start with a '-' character. E.g. -X-X, -X or -long-X=-X. If -X and -long-X take an argument, that argument will be "-X" in all 3 cases.
- If using the built-in Arg::Optional, optional arguments must be attached.
- the special option (i.e. without a name) terminates the list of options. Everything that follows is a non-option argument, even if it starts with a '-' character. The itself will not appear in the parse results.
- the first argument that doesn't start with '-' or '-' and does not belong to a preceding argument-taking option, will terminate the option list and is the first non-option argument. All following command line arguments are treated as non-option arguments, even if they start with '-'.

NOTE: This behaviour is mandated by POSIX, but GNU getopt() only honours this if it is explicitly requested (e.g. by setting POSIXLY_CORRECT).

You can enable the GNU behaviour by passing true as first argument to e.g. Parser::parse().

Arguments that look like options (i.e. '-' followed by at least 1 character) but aren't, are NOT treated
as non-option arguments. They are treated as unknown options and are collected into a list of unknown
options for error reporting.

This means that in order to pass a first non-option argument beginning with the minus character it is required to use the – special option, e.g.

```
\verb|program -x -- --strange-filename|
```

In this example, -strange-filename is a non-option argument. If the - were omitted, it would be treated as an unknown option.

See option::Descriptor::longopt for information on how to collect unknown options.

6.22 src/include/PowerReader.h File Reference

Header file for the PowerReader class.

```
#include <common.h>
#include <Runnable.h>
#include <cstdint>
#include <vector>
#include <string>
```

Include dependency graph for PowerReader.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::PowerReader

An abstract base class for measuring power from an arbitrary source. This class is runnable using a worker thread.

6.22.1 Detailed Description

Header file for the PowerReader class.

6.23 src/include/Runnable.h File Reference

Header file for the Runnable class.

```
#include <cstdint>
```

Include dependency graph for Runnable.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::Runnable

A base class for any object that implements a thread-safe run() function for use by Thread objects.

6.23.1 Detailed Description

Header file for the Runnable class.

6.24 src/include/Thread.h File Reference

Header file for the Thread class.

```
#include <Runnable.h>
#include <cstdint>
```

Include dependency graph for Thread.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::Thread

a nice wrapped thread interface independent of particular OS API

6.24.1 Detailed Description

Header file for the Thread class.

6.25 src/include/ThroughputBenchmark.h File Reference

Header file for the ThroughputBenchmark class.

```
#include <Benchmark.h>
#include <common.h>
#include <cstdint>
#include <string>
```

Include dependency graph for ThroughputBenchmark.h: This graph shows which files directly or indirectly include this file:

Classes

· class xmem::ThroughputBenchmark

A type of benchmark that measures memory throughput.

6.25.1 Detailed Description

Header file for the ThroughputBenchmark class.

6.26 src/include/Timer.h File Reference

Header file for the Timer class.

```
#include <common.h>
#include <cstdint>
```

Include dependency graph for Timer.h: This graph shows which files directly or indirectly include this file:

Classes

class xmem::Timer

This class abstracts some characteristics of simple high resolution stopwatch timer. However, due to the inability or complexity of abstracting shared hardware timers, this class does not actually provide start and stop functions.

6.26.1 Detailed Description

Header file for the Timer class.

6.27 src/include/win/win_common_third_party.h File Reference

Header file for some third-party helper code for working with Windows APIs.

6.27.1 Detailed Description

Header file for some third-party helper code for working with Windows APIs.

6.28 src/include/win/win_CPdhQuery.h File Reference

Header and implementation file for some third-party code for measuring Windows OS-exposed performance counters.

6.28.1 Detailed Description

Header and implementation file for some third-party code for measuring Windows OS-exposed performance counters.

6.29 src/include/win/WindowsDRAMPowerReader.h File Reference

Header file for the WindowsDRAMPowerReader class.

6.29.1 Detailed Description

Header file for the WindowsDRAMPowerReader class.

6.30 src/LatencyBenchmark.cpp File Reference

Implementation file for the LatencyBenchmark class.

```
#include <LatencyBenchmark.h>
#include <common.h>
#include <benchmark_kernels.h>
#include <MemoryWorker.h>
#include <LatencyWorker.h>
#include <LoadWorker.h>
#include <iostream>
#include <random>
#include <assert.h>
#include <time.h>
Include dependency graph for LatencyBenchmark.cpp:
```

6.30.1 Detailed Description

Implementation file for the LatencyBenchmark class.

6.31 src/LatencyWorker.cpp File Reference

Implementation file for the LatencyWorker class.

```
#include <LatencyWorker.h>
#include <benchmark_kernels.h>
#include <common.h>
#include <iostream>
Include dependency graph for LatencyWorker.cpp:
```

6.31.1 Detailed Description

Implementation file for the LatencyWorker class.

6.32 src/LoadWorker.cpp File Reference

Implementation file for the LoadWorker class.

```
#include <LoadWorker.h>
#include <benchmark_kernels.h>
#include <common.h>
#include <iostream>
Include dependency graph for LoadWorker.cpp:
```

6.32.1 Detailed Description

Implementation file for the LoadWorker class.

6.33 src/main.cpp File Reference

main entry point to the tool

```
#include <common.h>
#include <build_datetime.h>
#include <Configurator.h>
#include <BenchmarkManager.h>
#include <iostream>
#include <string>
Include dependency graph for main.cpp:
```

Functions

• int main (int argc, char *argv[])

The main entry point to the program.

6.33.1 Detailed Description

main entry point to the tool This tool is designed to measure bandwidth and latency of the memory system using several access patterns, strides, and working set sizes. The primary goal is to measure DRAM performance, although it can also measure cache performance depending on the configuration.

6.34 src/MemoryWorker.cpp File Reference

Implementation file for the MemoryWorker class.

```
#include <MemoryWorker.h>
#include <common.h>
Include dependency graph for MemoryWorker.cpp:
```

6.34.1 Detailed Description

Implementation file for the MemoryWorker class.

6.35 src/PowerReader.cpp File Reference

Implementation file for the PowerReader class.

```
#include <PowerReader.h>
#include <common.h>
#include <cstdint>
#include <vector>
#include <iostream>
Include dependency graph for PowerReader.cpp:
```

6.35.1 Detailed Description

Implementation file for the PowerReader class.

6.36 src/Runnable.cpp File Reference

Implementation file for the Runnable class.

```
#include <Runnable.h>
#include <iostream>
Include dependency graph for Runnable.cpp:
```

Variables

· return false

6.36.1 Detailed Description

Implementation file for the Runnable class.

6.37 src/Thread.cpp File Reference

Implementation file for the Thread class.

```
#include <Thread.h>
#include <stdlib.h>
#include <iostream>
Include dependency graph for Thread.cpp:
```

Variables

- · return false
- · return true

6.37.1 Detailed Description

Implementation file for the Thread class.

6.38 src/ThroughputBenchmark.cpp File Reference

Implementation file for the ThroughputBenchmark class.

```
#include <ThroughputBenchmark.h>
#include <common.h>
#include <LoadWorker.h>
#include <Thread.h>
#include <iostream>
#include <assert.h>
#include <time.h>
```

Include dependency graph for ThroughputBenchmark.cpp:

6.38.1 Detailed Description

Implementation file for the ThroughputBenchmark class.

6.39 src/Timer.cpp File Reference

Implementation file for the Timer class.

```
#include <Timer.h>
#include <common.h>
Include dependency graph for Timer.cpp:
```

6.39.1 Detailed Description

Implementation file for the Timer class.

6.40 src/win/win_common_third_party.cpp File Reference

Implementation file for some third-party helper code for working with Windows APIs.

6.40.1 Detailed Description

Implementation file for some third-party helper code for working with Windows APIs.

6.41 src/win/WindowsDRAMPowerReader.cpp File Reference

Implementation file for the WindowsDRAMPowerReader class.

6.41.1 Detailed Description

Implementation file for the WindowsDRAMPowerReader class.

Index

\sim Thread	cpu_affinity_
xmem::Thread, 68	xmem::MemoryWorker, 45
	xmem::PowerReader, 60
acquireLock	cpu_node_
xmem::Runnable, 62	xmem::Benchmark, 22
add	create_and_start
xmem::Stats, 64	xmem::Thread, 69
adjusted_ticks_	created
xmem::MemoryWorker, 45	xmem::Thread, 69
append	
xmem::Option, 48	DEFAULT_NUM_NODES
arg	common.h, 82
xmem::Option, 51	DEFAULT_PAGE_SIZE
	common.h, 82
Benchmark	desc
xmem::Benchmark, 17	xmem::Option, 51
BenchmarkManager	dram_power_readers_
xmem::BenchmarkManager, 25	xmem::Benchmark, 22
buffer_max	dram_power_threads_
xmem::Stats, 65	xmem::Benchmark, 22
bytes_per_pass_	
xmem::MemoryWorker, 45	elapsed_dummy_ticks_
	xmem::MemoryWorker, 45
calculateMetrics	elapsed_ticks_
xmem::PowerReader, 58	xmem::MemoryWorker, 45
cancel	error
xmem::Thread, 68	xmem::Parser, 55
check_arg	extensionsEnabled
xmem::Descriptor, 34	xmem::Configurator, 28
chunk_size_	
xmem::Benchmark, 22	finished
clear	xmem::Parser::Action, 13
xmem::PowerReader, 58	xmem::Parser::StoreOptionAction, 66
clearAndReset	first
xmem::PowerReader, 58	xmem::Option, 48
common.h	gatQE Daraantila Matria
DEFAULT_NUM_NODES, 82	get25PercentileMetric
DEFAULT_PAGE_SIZE, 82	xmem::Benchmark, 18
MIN_ELAPSED_TICKS, 82	get75PercentileMetric
USE_OS_TIMER, 83	xmem::Benchmark, 18
completed	get95PercentileMetric
xmem::Thread, 68	xmem::Benchmark, 18
completed_	get99PercentileMetric
xmem::MemoryWorker, 45	xmem::Benchmark, 18
configureFromInput	getAdjustedTicks
xmem::Configurator, 28	xmem::MemoryWorker, 44
count	getBytesPerPass
xmem::Option, 48	xmem::MemoryWorker, 44
CountOptionsAction	getCPUNode
xmem::Stats::CountOptionsAction, 33	xmem::Benchmark, 18

getChunkSize	xmem::MemoryWorker, 44
xmem::Benchmark, 18	getPatternMode
getCpuNumaNodeAffinities	xmem::Benchmark, 21
xmem::Configurator, 28	getPeakDRAMPower
getElapsedDummyTicks	xmem::Benchmark, 21
xmem::MemoryWorker, 44	getPeakPower
getElapsedTicks	xmem::PowerReader, 59
xmem::MemoryWorker, 44	getPowerTrace
getExitCode	xmem::PowerReader, 59
xmem::Thread, 69	getPowerUnits
getIterations	xmem::PowerReader, 59
xmem::Benchmark, 18	getRWMode
getIterationsPerTest	xmem::Benchmark, 21
xmem::Configurator, 28	getSamplingPeriod
getLastSample	xmem::PowerReader, 59
xmem::PowerReader, 58	getStartingTestIndex
getLen	xmem::Configurator, 29
	getStrideSize
xmem::Benchmark, 19 xmem::MemoryWorker, 44	xmem::Benchmark, 21
•	getTarget
getLoadMetricOnIter	xmem::Thread, 69
xmem::LatencyBenchmark, 38	getTicksPerMs
getMaxMetric	xmem::Timer, 71
xmem::Benchmark, 19	getWorkingSetSizePerThread
getMeanDRAMPower	xmem::Configurator, 29
xmem::Benchmark, 19	Amemoomigurator, 29
getMeanLoadMetric	hadWarning
xmem::LatencyBenchmark, 38	xmem::MemoryWorker, 45
getMeanMetric	has run
xmem::Benchmark, 19	xmem::Benchmark, 22
getMeanPower	hasRun
xmem::PowerReader, 59	xmem::Benchmark, 21
getMedianMetric	help
xmem::Benchmark, 19	xmem::Descriptor, 34
getMemNode	, , ,
xmem::Benchmark, 19	index
getMemoryNumaNodeAffinities	xmem::Descriptor, 35
xmem::Configurator, 28	isFirst
getMetricOnIter	xmem::Option, 49
xmem::Benchmark, 20	isLast
getMetricUnits	xmem::Option, 49
xmem::Benchmark, 20	isNUMAEnabled
getMinMetric	xmem::Configurator, 29
xmem::Benchmark, 20	isThreadRunning
getModeMetric	xmem::Thread, 69
xmem::Benchmark, 20	isThreadSuspended
getName	xmem::Thread, 69
xmem::Benchmark, 20	isValid
getNsPerTick	xmem::Benchmark, 21
xmem::Timer, 71	isWideChar
getNumSamples	xmem::PrintUsageImplementation, 61
xmem::PowerReader, 59	iterations_
getNumThreads	xmem::Benchmark, 23
xmem::Benchmark, 20	
getNumWorkerThreads	join
xmem::Configurator, 29	xmem::Thread, 69
getOutputFilename	
xmem::Configurator, 29	last
getPasses	xmem::Option, 49

latencyTestSelected	nextRow
xmem::Configurator, 29	xmem::PrintUsageImplementation::LinePart-
LatencyWorker	Iterator, 40
xmem::LatencyWorker, 39	nextTable
len_	xmem::PrintUsageImplementation::LinePart-
xmem::Benchmark, 23	Iterator, 40
xmem::MemoryWorker, 45	nextwrap
LineWrapper	xmem::Option, 49
xmem::PrintUsageImplementation::LineWrapper,	nonOptions
41	xmem::Parser, 55
load_metric_on_iter_	nonOptionsCount
xmem::LatencyBenchmark, 38	xmem::Parser, 55
LoadWorker	ns_per_tick_
xmem::LoadWorker, 42	xmem::Timer, 72
longopt	num_samples_
xmem::Descriptor, 35	xmem::PowerReader, 60
,	num_worker_threads_
MIN_ELAPSED_TICKS	xmem::Benchmark, 24
common.h, 82	,
max_metric_	obj_valid_
xmem::Benchmark, 23	xmem::Benchmark, 24
mean_dram_power_socket_	operator const Option *
xmem::Benchmark, 23	xmem::Option, 50
mean_load_metric_	operator Option *
xmem::LatencyBenchmark, 38	xmem::Option, 50
mean_metric_	operator=
xmem::Benchmark, 23	xmem::Option, 50
mean_power_	Option
xmem::PowerReader, 60	xmem::Option, 48
median_metric_	options_max
xmem::Benchmark, 23	xmem::Stats, 65
mem_array_	optionsCount
xmem::Benchmark, 23	xmem::Parser, 55
xmem::MemoryWorker, 45	Allomin disol, so
mem_node_	parse
xmem::Benchmark, 23	xmem::Parser, 55
MemoryWorker	Parser
xmem::MemoryWorker, 43	xmem::Parser, 54
metric_on_iter_	passes
xmem::Benchmark, 23	xmem::MemoryWorker, 46
metric_units_	pattern_mode_
xmem::Benchmark, 23	xmem::Benchmark, 24
	peak_dram_power_socket_
min_metric_	xmem::Benchmark, 24
xmem::Benchmark, 23	peak_power_
mode_metric_	xmem::PowerReader, 60
xmem::Benchmark, 24	percentile_25_metric_
nama	
name	xmem::Benchmark, 24
xmem::Option, 51	percentile_75_metric_
xmem::PowerReader, 60	xmem::Benchmark, 24
name_	percentile_95_metric_
xmem::Benchmark, 24	xmem::Benchmark, 24
xmem::PowerReader, 60	percentile_99_metric_
namelen	xmem::Benchmark, 24
xmem::Option, 51	perform
next	xmem::Parser::Action, 13
xmem::Option, 49	xmem::Parser::StoreOptionAction, 66
xmem::PrintUsageImplementation::LinePart-	xmem::Stats::CountOptionsAction, 33
Iterator, 40	power_trace_

ymamuDayarDaadar CO	ara/inaluda/EvamalaAra b. 04	
xmem::PowerReader, 60	src/include/ExampleArg.h, 84	
power_units_	src/include/LatencyBenchmark.h, 86	
xmem::PowerReader, 61	src/include/LatencyWorker.h, 86	
PowerReader	src/include/LoadWorker.h, 87	
xmem::PowerReader, 58	src/include/MemoryWorker.h, 87	
prev	src/include/MyArg.h, 87	
xmem::Option, 50	src/include/PowerReader.h, 91	
prevwrap	src/include/Runnable.h, 92	
xmem::Option, 50	src/include/Thread.h, 92	
process	src/include/ThroughputBenchmark.h, 92	
xmem::PrintUsageImplementation::LineWrapper,	src/include/Timer.h, 93	
41	src/include/benchmark_kernels.h, 76	
	src/include/common.h, 79	
releaseLock	src/include/ext/DelayInjectedLoadedLatencyBenchmark/-	
xmem::Runnable, 63	DelayInjectedLoadedLatencyBenchmark.h,	
run	86	
xmem::Benchmark, 21	src/include/ext/DelayInjectedLoadedLatencyBenchmark/delay-	
runAll	_injected_benchmark_kernels.h, 84	
xmem::BenchmarkManager, 26	src/include/optionparser.h, 88	
runCore	src/include/optionparser.in, 60 src/include/win/WindowsDRAMPowerReader.h, 93	
xmem::Benchmark, 22		
xmem::LatencyBenchmark, 38	src/include/win/win_CPdhQuery.h, 93	
	src/include/win/win_common_third_party.h, 93	
xmem::ThroughputBenchmark, 70	src/main.cpp, 95	
runExtDelayInjectedLoadedLatencyBenchmark	src/win/WindowsDRAMPowerReader.cpp, 97	
xmem::Configurator, 29	src/win/win_common_third_party.cpp, 97	
runLatencyBenchmarks	startPowerThreads	
xmem::BenchmarkManager, 26	xmem::Benchmark, 22	
runThroughputBenchmarks	started	
xmem::BenchmarkManager, 26	xmem::Thread, 69	
rw_mode_	Stats	
	Stats	
xmem::Benchmark, 24	xmem::Stats, 64	
xmem::Benchmark, 24		
xmem::Benchmark, 24 sampling_period_	xmem::Stats, 64 stop	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61	xmem::Stats, 64 stop xmem::PowerReader, 60	
xmem::Benchmark, 24 sampling_period_	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/LoadWorker.cpp, 95 src/PowerReader.cpp, 95	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/PowerReader.cpp, 96	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 95 src/PowerReader.cpp, 95 src/PowerReader.cpp, 96 src/Thread.cpp, 96	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/PowerReader.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/LoadWorker.cpp, 95 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50	
xmem::Benchmark, 24 sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/PowerReader.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74 src/ext/DelayInjectedLoadedLatencyBenchmark/Delay-	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50 USE_OS_TIMER	
sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/LoadWorker.cpp, 95 src/PowerReader.cpp, 95 src/PowerReader.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74 src/ext/DelayInjectedLoadedLatencyBenchmark/Delay- InjectedLoadedLatencyBenchmark.cpp, 75	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50 USE_OS_TIMER common.h, 83	
sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LatencyWorker.cpp, 95 src/NemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74 src/ext/DelayInjectedLoadedLatencyBenchmark/Delay-InjectedLoadedLatencyBenchmark/delay	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50 USE_OS_TIMER common.h, 83 useChunk32b	
sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74 src/ext/DelayInjectedLoadedLatencyBenchmark/Delay- Injected_benchmark_kernels.cpp, 75 src/ext/DelayInjectedLoadedLatencyBenchmark/delay- injected_benchmark_kernels.cpp, 75	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50 USE_OS_TIMER common.h, 83 useChunk32b xmem::Configurator, 30	
sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74 src/ext/DelayInjectedLoadedLatencyBenchmark/Delay- Injected_benchmark_kernels.cpp, 75 src/ext/DelayInjectedLoadedLatencyBenchmark/delay- injected_benchmark_kernels.cpp, 75 src/include/Benchmark.h, 76	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50 USE_OS_TIMER common.h, 83 useChunk32b xmem::Configurator, 30 useLargePages	
sampling_period_ xmem::PowerReader, 61 setUseOutputFile xmem::Configurator, 30 shortopt xmem::Descriptor, 35 src/Benchmark.cpp, 73 src/BenchmarkManager.cpp, 74 src/Configurator.cpp, 75 src/LatencyBenchmark.cpp, 94 src/LatencyWorker.cpp, 94 src/LoadWorker.cpp, 94 src/MemoryWorker.cpp, 95 src/PowerReader.cpp, 95 src/Runnable.cpp, 96 src/Thread.cpp, 96 src/ThroughputBenchmark.cpp, 96 src/Timer.cpp, 97 src/benchmark_kernels.cpp, 73 src/common.cpp, 74 src/ext/DelayInjectedLoadedLatencyBenchmark/Delay- Injected_benchmark_kernels.cpp, 75 src/ext/DelayInjectedLoadedLatencyBenchmark/delay- injected_benchmark_kernels.cpp, 75	xmem::Stats, 64 stop xmem::PowerReader, 60 stop_signal_ xmem::PowerReader, 61 stopPowerThreads xmem::Benchmark, 22 StoreOptionAction xmem::Parser::StoreOptionAction, 65 stride_size_ xmem::Benchmark, 25 Thread xmem::Thread, 68 throughputTestSelected xmem::Configurator, 30 ticks_per_ms_ xmem::Timer, 72 type xmem::Descriptor, 35 xmem::Option, 50 USE_OS_TIMER common.h, 83 useChunk32b xmem::Configurator, 30	

0 (1) 00	MA
xmem::Configurator, 30	getMetricOnIter, 20
useRandomAccessPattern	getMetricUnits, 20
xmem::Configurator, 30	getMinMetric, 20
useReads	getModeMetric, 20
xmem::Configurator, 30 useSequentialAccessPattern	getName, 20
xmem::Configurator, 31	getNumThreads, 20
useStrideN1	getPatternMode, 21
xmem::Configurator, 31	getPeakDRAMPower, 21 getRWMode, 21
useStrideN16	,
xmem::Configurator, 31	getStrideSize, 21 has_run_, 22
useStrideN2	hasRun, 21
xmem::Configurator, 31	isValid, 21
useStrideN4	iterations , 23
xmem::Configurator, 31	len , 23
useStrideN8	max metric , 23
xmem::Configurator, 31	mean dram power socket , 23
useStrideP1	mean_metric_, 23
xmem::Configurator, 31	median metric , 23
useStrideP16	mem_array_, 23
xmem::Configurator, 32	mem_node_, 23
useStrideP2	metric_on_iter_, 23
xmem::Configurator, 32	metric units , 23
useStrideP4	min_metric_, 23
xmem::Configurator, 32	mode_metric_, 24
useStrideP8	name_, 24
xmem::Configurator, 32	num_worker_threads_, 24
useWrites	obj_valid_, 24
xmem::Configurator, 32	pattern_mode_, 24
	peak_dram_power_socket_, 24
validTarget	percentile_25_metric_, 24
xmem::Thread, 70	percentile_75_metric_, 24
verboseMode	percentile 95 metric , 24
xmem::Configurator, 32	percentile_99_metric_, 24
	run, 21
warning_	runCore, 22
xmem::Benchmark, 25	rw_mode_, 24
xmem::MemoryWorker, 46	startPowerThreads, 22
vine a mary Avin. 114	stopPowerThreads, 22
xmem::Arg, 14	stride_size_, 25
xmem::Benchmark, 15	warning_, 25
Benchmark, 17	xmem::BenchmarkManager, 25
chunk_size_, 22	BenchmarkManager, 25
cpu_node_, 22	runAll, 26
dram_power_readers_, 22	runLatencyBenchmarks, 26
dram_power_threads_, 22 get25PercentileMetric, 18	runThroughputBenchmarks, 26
get75PercentileMetric, 18	xmem::Configurator, 26
get95PercentileMetric, 18	configureFromInput, 28
get99PercentileMetric, 18	extensionsEnabled, 28
getCPUNode, 18	getCpuNumaNodeAffinities, 28
getChunkSize, 18	getlerationsPerTest, 28
getIterations, 18	getMemoryNumaNodeAffinities, 28
getLen, 19	getNumWorkerThreads, 29
getMaxMetric, 19	getOutputFilename, 29
getMeanDRAMPower, 19	getStartingTestIndex, 29
getMeanMetric, 19	getWorkingSetSizePerThread, 29
getMedianMetric, 19	isNUMAEnabled, 29
getMemNode, 19	latencyTestSelected, 29

runExtDelayInjectedLoadedLatencyBenchmark, 29	xmem::MyArg, 46
setUseOutputFile, 30	xmem::Option, 46
throughputTestSelected, 30	append, 48
useChunk32b, 30	arg, <mark>51</mark>
useLargePages, 30	count, 48
useOutputFile, 30	desc, 51
useRandomAccessPattern, 30	first, 48
useReads, 30	isFirst, 49
useSequentialAccessPattern, 31	isLast, 49
useStrideN1, 31	last, 49
useStrideN16, 31	name, 51
useStrideN2, 31	namelen, 51
useStrideN4, 31	next, 49
useStrideN8, 31	nextwrap, 49
useStrideP1, 31	operator const Option *, 50
useStrideP16, 32	operator Option *, 50
useStrideP2, 32	operator=, 50
useStrideP4, 32	Option, 48
useStrideP8, 32	prev, 50
useWrites, 32	prevwrap, 50
verboseMode, 32	type, 50
xmem::Descriptor, 33	xmem::Parser, 52
check_arg, 34	error, 55
help, 34	nonOptions, 55
index, 35	nonOptionsCount, 55
longopt, 35	optionsCount, 55
shortopt, 35	parse, 55
•	•
type, 35	Parser, 54
xmem::ExampleArg, 36	xmem::Parser::Action, 13
xmem::LatencyBenchmark, 37	finished, 13
getLoadMetricOnIter, 38	perform, 13
getMeanLoadMetric, 38	xmem::Parser::StoreOptionAction, 65
load_metric_on_iter_, 38	finished, 66
mean_load_metric_, 38	perform, 66
runCore, 38	StoreOptionAction, 65
xmem::LatencyWorker, 38	xmem::PowerReader, 56
LatencyWorker, 39	calculateMetrics, 58
xmem::LoadWorker, 41	clear, 58
LoadWorker, 42	clearAndReset, 58
xmem::MemoryWorker, 42	cpu_affinity_, 60
adjusted ticks , 45	getLastSample, 58
bytes_per_pass_, 45	getMeanPower, 59
completed_, 45	getNumSamples, 59
cpu_affinity_, 45	getPeakPower, 59
elapsed dummy ticks , 45	getPowerTrace, 59
. – -	,
elapsed_ticks_, 45	getPowerUnits, 59
getAdjustedTicks, 44	getSamplingPeriod, 59
getBytesPerPass, 44	mean_power_, 60
getElapsedDummyTicks, 44	name, 60
getElapsedTicks, 44	name_, 60
getLen, 44	num_samples_, 60
getPasses, 44	peak_power_, 60
hadWarning, 45	power_trace_, 60
len_, 45	power_units_, 61
mem_array_, 45	PowerReader, 58
MemoryWorker, 43	sampling_period_, 61
passes_, 46	stop, 60
warning_, 46	stop_signal_, 61
₩αιτιιί <u>ς</u> , το	otop_oignal_, vi

```
xmem::PrintUsageImplementation, 61
    isWideChar, 61
xmem::PrintUsageImplementation::FunctionWriter<
         Function >, 36
xmem::PrintUsageImplementation::IStringWriter, 36
xmem::PrintUsageImplementation::LinePartIterator, 39
    next, 40
    nextRow, 40
    nextTable, 40
xmem::PrintUsageImplementation::LineWrapper, 40
    LineWrapper, 41
    process, 41
xmem::PrintUsageImplementation::OStreamWriter< O-
         Stream >, 52
xmem:: Print Usage Implementation:: Stream Writer <
         Function, Stream >, 66
xmem::PrintUsageImplementation::SyscallWriter<
         Syscall >, 67
xmem::PrintUsageImplementation::TemporaryWriter<
         Temporary >, 67
xmem::Runnable, 62
    acquireLock, 62
    releaseLock, 63
xmem::Stats, 63
    add, 64
    buffer_max, 65
    options_max, 65
    Stats, 64
xmem::Stats::CountOptionsAction, 33
    CountOptionsAction, 33
    perform, 33
xmem::Thread, 68
    \simThread, 68
    cancel, 68
    completed, 68
    create_and_start, 69
    created, 69
    getExitCode, 69
    getTarget, 69
    isThreadRunning, 69
    isThreadSuspended, 69
    join, 69
    started, 69
    Thread, 68
    validTarget, 70
xmem::ThroughputBenchmark, 70
    runCore, 70
xmem::Timer, 71
    getNsPerTick, 71
    getTicksPerMs, 71
    ns_per_tick_, 72
    ticks_per_ms_, 72
```